Québec • azette

Part No. 22

28 May 2003

Laws and Regulations

Volume 135

Summary

Table of Contents Regulations and other acts **Draft Regulations** Decisions Notices Index

Legal deposit-1st Quarter 1968 Bibliothèque nationale du Québec © Éditeur officiel du Québec, 2003

All rights reserved in all countries. No part of this publication may be translated, used or reproduced for commercial purposes by any means, whether electronic or mechanical, including micro-reproduction, without the written authorization of the Québec Official Publisher.

Table of Contents	Page
Regulations and other acts	
Devices which compensate for a physical deficiency (Amend.)	1699
Draft Regulations	
Automotive services — Drummond and Mauricie regions	1825
Decisions	
Chief electoral officer — Decision pursuant to the powers conferred upon him by section 490 of the Election Act, concerning the holding of a new election in the electoral division of Champlain	1829
Notices	
Annedda Nature Reserve — Recognition Marais-Kergus Nature Reserve — Recognition Pointe-de-la-Croix Nature Reserve — Recognition	1833 1833 1834

Regulations and other acts

Notice RAMQ 001-2003

Health Insurance Act (R.S.Q., c. A-29)

Devices which compensate for a physical deficiency — Amendments

Regulation dated 21 May 2003, made by the Régie de l'assurance maladie du Québec to amend the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act

THE RÉGIE DE L'ASSURANCE MALADIE DU QUÉBEC,

CONSIDERING the fifth paragraph of section 3 and section 72.1 of the Health Insurance Act (R.S.Q., c. A-29);

CONSIDERING that it is necessary to amend certain lists of locomotor and posture assists contained in the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act;

GIVES NOTICE

THAT the Régie, by resolution of its board of directors, CA-399-03-09 dated 21 May 2003, made the Regulation to amend the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act, the text of which appears below.

Québec, 21 May 2003

ANDRÉ-GAÉTAN CORNEAU, Secretary General of the Régie de l'assurance maladie du Québec

Regulation to amend the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act^{*}

Health Insurance Act (R.S.Q., c. A-29, s. 3, 5th and 10th pars. and s. 72.1)

I. The Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act is amended by replacing Divisions I, II and III of Part I of Chapter V of Title Two by the Divisions appearing in Schedule I to this Regulation.

2. This Regulation comes into force on 1 June 2003.

^{*} The Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act, made by Order in Council 612-94 dated 27 April 1994 (1994, *G.O.* 2, 1589), was last amended by the regulation made by Order in Council 999-2002 dated 28 August 2002 (2002, *G.O.* 2, 4729). For previous amendments, refer to the *Tableau des modifications et Index sommaire*, Éditeur officiel du Québec, 2003, updated to 1 March 2003.

SCHEDULE I

CHAPTER V LISTS

LOCOMOTOR AND POSTURE ASSISTS

PART I LOCOMOTOR ASSISTS

DIVISION I WHEEL CHAIRS

§1. Manual wheel chairs

DEVICE FROM: INVACARE CANADA INC.

MANUAL WHEEL CHAIR, "MVP" MODEL

Basic Component(s)

Body support system

- fixed back, height-adjustable from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- seat heights: $37.5 \text{ cm} (14^{3}/_{4} \text{ in.}), 54.0 \text{ cm} (21^{1}/_{4} \text{ in.})$
- seat width: from 38.1 cm (15 in.) to 45.7 cm (18 in.)
- seat depth: from 33.0 cm (13 in.) to 45.7 cm (18 in.)
- supple seat and back, nylon
- · push handles
- safety belt, velcro-type, auto-type

Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 25.4 cm (10 in.), short
- armrest pads, straight, contoured, long, short
- · tubular armrest pads
- clothing guards, flexible, rigid
- "U"-type armrests, detachable, flip-back, height-adjustable, short, long, from 25.4 cm (10 in.) to 35.6 cm (14 in.)
- "L"-type armrests, height-adjustable, short, long, from 12.7 cm (5 in.) to 25.4 cm (10 in.)

Footrests

- 60° footrests, detachable, swingaway, length-adjustable from 37.5 cm (14³/₄ in.) to 47.0 cm (18¹/₂ in.), or 70° footrests, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 47.0 cm (18¹/₂ in.)
- folding footplates, standard
- full-width footplate, tubular
- heel loops, non-adjustable
- heel loops, length-adjustable
- padded calfrests

PRICE \$1 150.00

Wheels and frame

- anodized aluminum handrims
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks, short
- threaded axles
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- heavy-duty rear wheels, solid tires, 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.), 7.6 cm (3 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 3.8 cm (1¹/₂ in.), 10.2 cm (4 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)

initial purchase replacement or replacement of component of wheel chair (unit price)
--

Basic or Optional Component(s)

Body support system

rigid seat, flat, lowered 140.00 176 modification of seat depth to 48.3 cm (19 in.), 50.8 cm (20 in.),	9.00 6.00 N/A N/A N/A
rigid seat, flat, lowered 140.00 176 modification of seat depth to 48.3 cm (19 in.), 50.8 cm (20 in.),	6.00 N/A N/A
modification of seat depth to 48.3 cm (19 in.), 50.8 cm (20 in.),	N/A N/A
	N/A
	N/A
53.3 cm (21 in.) or 55.9 cm (22 in.) 175.00 N	
modification of seat width to 48.3 cm (19 in.), 50.8 cm (20 in.)	
or 55.9 cm (22 in.) 175.00 N	N/A
modification of back height to 50.8 cm (20 in.) 32.00 N	
push handles N/C 38	8.00
supple back, nylon N/C 36	6.00
back, angle-adjustable 64.00 N	N/A
supple seat, nylon N/C 36	6.00
seat cushion, flat, foam, 5.1 cm (2 in.) 56.00 56	6.00
seat cushion, flat, foam, 7.6 cm (3 in.) 56.00 56	6.00
safety belt, velcro-type N/C 40	0.00
safety belt, auto-type N/C 50	0.00
Armrests :	
"L"-type armrests, detachable, swingaway, height-adjustable	
	5.00
"U"-type armrests, detachable, flip-back, height-adjustable	
	8.00
"T"-type armrests, detachable, height-adjustable	
from 15.2 cm (6 in.) to 25.4 cm (10 in.) or from 20.3 cm (8 in.)	
to 35.6 cm (14 in.), short or long	
pair 140.00	
each 125	5.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
"I"-type armrests, height-adjustable from 12.7 cm (5 in.)		
to 25.4 cm (10 in.), short or long	N/C	98.00
contoured armrest pads, short or long	N/C	26.00
tubular armrest pads	N/C	10.00
straight armrest pads, short	N/C	26.00
straight armrest pads, long	N/C	26.00
clothing guards, flexible	N/C	15.00
clothing guards, rigid	N/C	46.00
Footrests:		
60° footrests, detachable, swingaway, length-adjustable		
from 37.5 cm $(14^{3}/_{4} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$, or 70° footrests,		
detachable, swingaway, length-adjustable from $34.3 \text{ cm} (13^{1}/_2 \text{ in.})$		
to 47.0 cm ($18^{1}/_{2}$ in.)	N/C	81.00
70° footrests, tapered, detachable, swingaway, length-adjustable	100	01.00
from 40.0 cm $(15^{3}/_{4} \text{ in.})$ to 50.2 cm $(19^{3}/_{4} \text{ in.})$		
pair	107.00	
each	107.00	135.00
60° or 80° fixed footrests, length-adjustable from 37.5 cm (14 ³ / ₄ in.	.)	
to 47.0 cm $(18^{1}/_{2} \text{ in.})$	·)	
pair	167.00	
each		167.00
90° footrests, detachable, swingaway, length-adjustable		
from 12.7 cm (5 ¹ / ₄ in.) to 26.0 cm (10 ¹ / ₄ in.)		
pair	107.00	
each		135.00
60° footrests, MFX, detachable, swingaway, length-adjustable		
from 27.9 cm (11 in.) to 38.1 cm (15 in.), or 70° footrests, MFX,		
detachable, swingaway, length-adjustable from 34.3 cm $(13^{1}/_{2} \text{ in.})$		
to 47.0 cm $(18^{1}/_{2} \text{ in.})$		
pair	144.00	
each		153.00
elevating legrests, detachable, swingaway, length-adjustable		
from 38.7 cm $(15^{1}/_{4} \text{ in.})$ to 54.0 cm $(21^{1}/_{4} \text{ in.})$		
pair	230.00	
each		196.00
elevating legrests, compensating mechanism, from 40.6 cm (16 in.))	
to 53.3 cm (21 in.)		
pair	151.00	
each		157.00
modification of legrest length by -2.5 cm (1 in.)		
or by – 5.1 cm (2 in.)		
pair	190.00	
each		190.00
padded calfrests	N/C	20.00
single calf strap	22.00	35.00
double calf strap	34.00	52.00
-		

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
folding footplates, standard full-width footplate, tubular full-width footplate, tubular, plastic-coated full-width footplate, angle-adjustable, depth-adjustable footplates, angle-adjustable, depth-adjustable, standard or oversized, 18.4 cm $(7^{1}/_{4} \text{ in.})$	N/C N/C 30.00 72.00	40.00 120.00 150.00 192.00
pair each folding footplates, oversized pair	72.00 39.00	76.00
each heel loops, non-adjustable heel loops, length-adjustable	N/C N/C	60.00 5.00 12.00
Wheels and frame		
Types of drive systems : handrims with vertical or oblique projections pair	155.00	112.00
each anodized aluminum handrims plastic-coated handrims	N/C	112.00 34.00
pair each combined handrims	52.00	60.00
pair each anti-tip rollers	52.00	60.00
pair each cane holder	95.00 32.00	48.00 32.00
	52.00	32.00
Wheel locks: standard, push-to-lock standard, pull-to-lock wheel lock extensions	N/C N/C	44.00 44.00
pair each anti-rollback brakes	32.00	16.00
pair each scissor-type wheel locks	98.00	93.00
pair each	55.00	72.00
Types of forks : forks, standard or short fork-locking mechanisms	N/C	49.00
pair each	100.00	50.00

	Price upon	Price upon
	initial purchase or replacement of wheel chair	replacement of component (unit price)
Rear axles:		
threaded axles	N/C	15.00
extension plates for amputee	12.00	
pair each	42.00	21.00
		_1.00
Frame:	222.00	N/A
heavy-duty frame	232.00	IN/A
Types of wheels:		
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)	NIC	00.00
or 61.0 cm (24 in.) rear mag wheels, standard pressure, 50.8 cm (20 in.),	N/C	90.00
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	90.00
heavy-duty wheels, solid tires, 61.0 cm (24 in.) or 66.0 cm (26 in.)		126.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	126.00
spoked rear wheels, high pressure, 61.0 cm (24 in.) or 66.0 cm (26 i	n.) N/C	126.00
heavy-duty wheels, standard pressure, high pressure, solid tires,		
61.0 cm (24 in.) or 66.0 cm (26 in.)	79.00	
pair each	79.00	165.00
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.),		105.00
15.2 cm (6 in.), 12.7 cm (5 in.) or 7.6 cm (3 in.)	N/C	40.00
front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)		
pair	50.00	65.00
each front wheels some mean stin times 20.2 cm (8 in) \times 4.4 cm (13/ i	•)	65.00
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 4.4 cm $(1^3/_4)$ in pair	40.00	
each	+0.00	60.00
front wheels, solid tires, 20.3 cm (8 in.) x 3.8 cm $(1^{1}/_{2} \text{ in.})$,		00100
10.2 cm (4 in.), 12.7 cm (5 in.) or 15.2 cm (6 in.)	N/C	40.00
front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
pair	60.00	70.00
each front wheels, inner tube, 15.2 cm (6 in.)		70.00
or 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4} in.)$		
pair	25.00	
each		52.00
Component(s) under Special Consideration		
spoke guards*		
pair	82.00	
each	02.00	41.00
quick-release axles with lever mechanism*		
pair	76.00	
each		53.00

DEVICE FROM: ORTHOFAB INC.

MANUAL WHEEL CHAIR, "PRIMA" MODEL

Basic Component(s)

Body support system

- supple back, nylon
- back, height-adjustable from 38.1 cm (15 in.) to 45.7 cm (18 in.)
- seat-back angle: 90°, 96°
- telescopic backposts, 8° at 20.3 cm (8 in.), 0°
- seat width: from 35.6 cm (14 in.) to 55.9 cm (22 in.)
- seat depth: 40.6 cm (16 in.)
- supple seat, nylon
- front seat height: from 45.7 cm (18 in.) to 50.8 cm (20 in.)
- safety belt, auto-type
- push handles

Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable from 22.9 cm (9 in.) to 30.5 cm (12 in.), long
- straight armrest pads, short, long
- rigid clothing guards, detachable

Footrests

- 60° or 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests
- folding footplates, tubular
- heel loops, length-adjustable

Wheels and frame

- anodized aluminum handrims
- · standard brakes, push-to-lock
- standard forks, high forks
- threaded axles
- spoked rear wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.), 17.8 cm (7 in.)
- plates for amputee

Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
60.00	122.00
69.00	133.00
116.00	173.00
99.00	N/A
	initial purchase or replacement of wheel chair 69.00 116.00

1705

PRICE \$1 098.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
contoured headrest, nylon	100.00	100.00
articulated headrest mounting, uniball	115.00	115.00
back spreader bar with headrest support	99.00	99.00
modification of seat depth to 35.6 cm (14 in.), 38.1 cm (15 in.),		
43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in modification of seat height to less 45.7 cm (18 in.) down	n.) 101.00	N/A
to 34.3 cm $(13^{1}/_{2} \text{ in.})$	208.00	N/A
supple back, nylon	N/C	64.00
supple seat, nylon	N/C	57.00
push handles	N/C	N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, velcro-type	27.00	63.00
safety belt, auto-type	N/C	36.00
safety belt, airplane-type	38.00	74.00
telescopic backposts, 8° at 20.3 cm (8 in.) or 0°	N/C	N/A
"L"-type armrests, detachable, swingaway, height-adjustable from 22.9 cm (9 in.) to 30.5 cm (12 in.), long "U"-type armrests, detachable, flip-back, height-adjustable from 20.3 cm (8 in.) to 27.9 cm (11 in.) or from 22.9 cm (9 in.) to 30.3 cm (12 in.) with transfer assists and rigid clothing guards, she	N/C	48.00
pair each "U"-type armrests, detachable, flip-back, height-adjustable from 20.3 cm (8 in.) to 27.9 cm (11 in.) or from 22.9 cm (9 in.) to 30.5 cm (12 in.) with transfer assists and rigid clothing guards, lo	92.00	94.00
pair	144.00	
each		120.00
contoured armrest pads, long		
pair	48.00	
each		39.00
contoured armrest pads, short		
pair	44.00	
each		34.00
straight armrest pads, long	N/C	15.00
straight armrest pads, short	N/C	12.00
	N/C	65.00
rigid clothing guards, detachable	N/C	05.00
modification of "U"-type armrest height to under 20.3 cm (8 in.) of		05.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
60° footrests, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	29.00	N/A
70° footrests, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	29.00	N/A
60° footrests, tapered, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	102.00
70° footrests, tapered, detachable, swingaway, length-adjustable		102 00
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	102.00
elevating legrests, compensating mechanism, detachable, swingaw	ay,	
length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair	234.00	
each	234.00	219.00
elevating legrests, detachable, swingaway, length-adjustable		217.00
from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
pair	166.00	
each		185.00
contoured calfrests		
pair	60.00	
each		50.00
padded calfrests	N/C	20.00
modification of footrest or legrest length to under 35.6 cm (14 in.)	7 0.00	27/1
or to over 48.3 cm (19 in.)	79.00	N/A
folding footplates, oversized	40.00	
pair each	40.00	36.00
folding footplates, tubular	N/C	16.00
oversized footplates, angle-adjustable	100	10.00
pair	78.00	
each		55.00
standard footplates, angle-adjustable		
pair	72.00	
each		52.00
full-width footplate, angle-adjustable	168.00	200.00
double calf strap	55.00	55.00
heel loops, length-adjustable	N/C	11.00
toe loops	20.00	
pair each	30.00	15.00
front impact guard with rollers		15.00
pair	36.00	
each	20.00	18.00
Wheels and frame		
folding mechanism with double crossbars	257.00	N/A
angle-adjustable back	98.00	N/A N/A
back spreader bar	69.00	69.00
cuen spreader our	07.00	07.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of drive systems :		
non-slip handrims		
pair	84.00	
each		88.00
handrims, plastic-coated	56.00	
pair each	30.00	74.00
anodized aluminum handrims	N/C	46.00
combined handrims	N/C	+0.00
pair	66.00	
each	00100	79.00
anti-tip rollers		
pair	92.00	
each		46.00
cane holder	40.00	40.00
Wheel locks:		50.00
standard, push-to-lock	N/C	53.00
retractable wheel lock extensions	38.00	
pair each	58.00	19.00
fixed wheel lock extensions		19.00
pair	38.00	
each	50.00	19.00
anti-rollback brakes		
pair	86.00	
each		43.00
Types of forks:		20.00
standard forks	N/C	38.00
high forks	N/C	55.00
Rear axles:		
threaded axles	N/C	5.00
quick-release axles	n/c	5.00
pair	76.00	
each		43.00
plates for amputee	N/C	N/A
Types of wheels:		
spoked rear wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	74.00
rear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)	00.00	
pair	98.00	
each		123.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.0 cm (22 in.) or 61.0 cm (24 in.)		
55.9 cm (22 in.) or 61.0 cm (24 in.)	68.00	
pair each	68.00	108.00
		108.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
rear mag wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 (24 in.) pair	98.00	
each		123.00
heavy-duty rear wheels, solid tires, 55.9 cm (22 in.) or 61.0 (24 in.)		
pair	154.00	151.00
each heavy-duty rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)		151.00
pair	154.00	
each		151.00
heavy-duty rear wheels, high pressure, 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	154.00	
pair each	154.00	151.00
rear mag wheels, semi-pneumatic tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)		131.00
pair	128.00	
each		138.00
spoked rear wheels, semi-pneumatic tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)		
pair	68.00	
each		108.00
heavy-duty spoked rear wheels, semi-pneumatic tires,		
55.9 cm (22 in.) or 61.0 cm (24 in.)	4.5.4.00	
pair	154.00	151.00
each front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.),		151.00
12.7 cm (5 in.), 15.2 cm (6 in.) or 17.8 cm (7 in.)	N/C	30.00
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.)	100	50.00
or 15.2 cm (6 in.) x 3.2 cm $(1^{1}/_{4}$ in.)		
pair	32.00	
each		46.00
front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)	22.00	
pair each	32.00	46.00
front wheels, inner tube, 17.8 cm (7 in.) x 4.4 cm $(1^{3}/_{4} in.)$		40.00
pair	32.00	
each		46.00
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm $(1^{1}/_{2})$ in		
15.2 cm (6 in.) x 3,8 cm (1 ¹ / ₂ in.) or 12.7 cm (5 in.) x 3.8 cm (1 ¹ / ₂ in		
pair each	32.00	46.00
Cacii		+0.00

Component(s) under Special Consideration

spoke guards* pair	114.00	
each		57.00

MANUAL WHEEL CHAIR, "QUICKIE LXI" MODEL

Basic Component(s)

Body support system

- supple back, nylon
- back height: from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- front seat height: from 40.0 cm $(15^{3}/_{4} \text{ in.})$ to 54.6 cm $(21^{1}/_{2} \text{ in.})$
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.)
- supple seat, nylon
- safety belt, velcro-type, auto-type
- push handles
- backposts, at an 8° angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.)

Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- straight armrest pads, short, long
- tubular armrest pads
- flexible clothing guards

Footrests

- 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- · folding footplates, standard
- folding footplates, tubular
- heel loops, length-adjustable

Wheels and frame

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5¹/₄ in.), high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels, high forks, 17.8 cm (7 in.), for 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- fork stems, + 1.9 cm $(\frac{3}{4} \text{ in.})$, + 3.8 cm $(\frac{1}{2} \text{ in.})$
- · threaded axles
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 15.2 cm (6 in.) x 3.2 cm (1¹/₄ in.)
- rear mag wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)

PRICE

\$1 095.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
modification of seat depth to 35.6 cm (14 in.) or 38.1 cm (15 in.)	40.00	N/A
modification of seat width to 48.3 cm (19 in.) or 50.8 cm (20 in.)	95.00	N/A
modification of seat depth to 43.2 cm (17 in.) or 45.7 cm (18 in.)	67.00	N/A
supple back, nylon	N/C	62.00
supple back, tension-adjustable	74.00	136.00
supple seat, nylon seat cushion, flat, foam, 5.1 cm (2 in.)	N/C 56.00	53.00 56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
seat cushion, flat, foam, 10.2 cm (4 in.)	56.00	56.00
push handles	N/C	22.00
backposts, at an 8° angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	27.00
safety belt, velcro-type	N/C	28.00
safety belt, auto-type	N/C	41.00
Armrests :		
"L"-type armrests, detachable, swingaway, height-adjustable		
from 20.3 cm (8 in.) to 30.5 cm (12 in.), short	N/C	85.00
"U"-type armrests, detachable, flip-back, height-adjustable		
from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long	102 00	
pair	102.00	136.00
each "T"-type armrests, detachable, height-adjustable		150.00
from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long		
pair	139.00	
each		154.50
tubular armrest pads	N/C	2.00
straight armrest pads, short	N/C	15.00
straight armrest pads, long	N/C	17.00
clothing guards, rigid	00.00	
pair each	90.00	66.00
clothing guards, flexible	N/C	21.00
	ive	21.00
Footrests:		
60° or 70° footrests, detachable, swingaway, length-adjustable	NIC	52.00
from 35.6 cm (14 in.) to 48.3 cm (19 in.) 70° footrests, tapered, detachable, swingaway, length-adjustable	N/C	53.00
from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
pair	28.00	
each		67.00
90° footrests, detachable, swingaway, length-adjustable		
from 20.3 cm (8 in.) to 33.0 cm (13 in.)	N/C	53.00
elevating legrests		
pair	105.00	105 50
each		105.50

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
elevating legrests, compensating mechanism		
pair	194.00	
each		150.00
single calf strap	18.00	18.00
double calf strap	32.00	32.00
folding footplates, standard	N/C	48.00
folding footplates, angle-adjustable		
pair	51.00	
each		73.50
folding footplates, tubular	N/C	48.00
folding footplates, full-width, angle-adjustable	83.00	179.00
folding footplates, oversized		
pair	71.00	
each		83.50
heel loops, length-adjustable	N/C	10.00
modification of footrest length from 48.3 cm (19 in.)		
to 52.1 cm $(20^{1}/_{2} \text{ in.})$	30.00	29.00
modification of footrest mounting from 17.8 cm (7 in.)		
to 34.3 cm $(13^{1}/_{2} \text{ in.})$	54.00	33.00
modification of length of 90° footrest by + 5.1 cm (2 in.)		
or by $+ 10.2$ cm (4 in.)	30.00	15.00
Wheels and frame		
Types of drive systems :		
one-arm dual handrim drive	468.00	560.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	58.00
plastic-coated handrims		
pair	54.00	
each		85.00
handrims with vertical or oblique projections		
pair	88.00	
each		102.00
small plastic-coated handrim for one-arm drive	54.00	112.00
anti-tip rollers		
pair	43.00	
each		21.50
cane holder	44.00	44.00
Wheel leaker		
Wheel locks: standard wheel locks, push-to-lock or pull-to-lock	N/C	39.00
wheel lock extensions	N/C	39.00
	26.00	
pair each	26.00	13.00
anti-rollback brakes		13.00
	66.00	
pair each	00.00	33.00
Cacil		55.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of forks:		
standard forks, 15.2 cm (6 in.), short forks, 13.3 cm $(5^{1}/_{4} \text{ in.})$		
or high forks 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels	N/C	31.00
high forks, 17.8 cm (7 in.), for 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels		34.00
fork-locking mechanisms		54.00
pair	44.00	
each		22.00
fork stems, + 1.9 cm $({}^{3}/_{4}$ in.) or + 3.8 cm $(1{}^{1}/_{2}$ in.)	N/C	16.00
Rear axles:		
threaded axles	N/C	11.00
quick-release axles	4.0.00	
pair	43.00	22.50
each	64.00	32.50
extension plates for amputee	64.00	N/A
Types of wheels:		
rear mag wheels, solid tires, 50.8 cm (20 in.)	44.00	
pair each	44.00	132.00
rear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	132.00
rear mag wheels, standard pressure, 50.8 cm (20 in.)	1	102100
pair	44.00	
each		132.00
rear mag wheels, standard pressure, 55.9 cm (22 in.)	21/2	440.00
or 61.0 cm (24 in.)	N/C	110.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.) pair	44.00	
each	44.00	132.00
spoked rear wheels, high pressure, 61.0 cm (24 in.)		152.00
pair	44.00	
each		132.00
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	70.00	
pair each	78.00	149.00
front wheels, solid tires, 15.2 cm (6 in.)	N/C	60.00
front wheels, solid tires, 12.7 cm (5 in.)	N/C	46.00
front wheels, solid tires, $20.3 \text{ cm} (8 \text{ in.}) \times 2.5 \text{ cm} (1 \text{ in.})$	N/C	61.00
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.)	N/C	61.00
front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm $(1^{1}/_{4} \text{ in.})$	N/C	60.00
front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
pair	47.00	(2) \$ 0
each)	69.50
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm $(1^{1}/_{2}$ in or 15.2 cm (6 in.) x 3.8 cm $(1^{1}/_{2}$ in.)	.)	
pair	80.00	
each	00.00	86.00
		00.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
spoke guards* pair each quick-release axles with lever mechanism* pair	67.00 64.00	33.50
each	01.00	64.50
DEVICE FROM: SUNRISE MEDICAL CANADA INC.		PRICE
MANUAL WHEEL CHAIR, ADULT, "QUICKIE 2" MODEL		\$1 370.00
Basic Component(s)		
 Body support system supple back, nylon back height: from 21.6 cm (8¹/₂ in.) to 47.0 cm (18¹/₂ in.) supple seat, nylon seat width: from 35.6 cm (14 in.) to 50.8 cm (20 in.) seat depth: 40.6 cm (16 in.) front seat height: from 38.7 cm (15¹/₄ in.) to 54.6 cm (21¹/₂ in.) growth kit including : seat, back, footrests, front frame and crossbars (once only during first three years from date of purchase, for first user) safety belt, velcro-type, auto-type push handles 		
 Armrests "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short straight armrest pads, short, long tubular armrest pads clothing guards, flexible 		
 Footrests 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 70° or 80° footrests, detachable, swingaway, length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.) padded calfrests padded calfrests, for elevating legrests, compensating mechanism folding footplates, standard folding footplates, tubular heel loops, length-adjustable 	1	

Wheels and frame

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5¹/₄ in.); high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- high forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.)
- wheelsfork stems, + 1.9 cm $(^{3}/_{4} \text{ in.})$, + 3.8 cm $(1^{1}/_{2} \text{ in.})$
- · quick-release axles
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 15.2 cm (6 in.) x 3.2 cm (1¹/₄ in.)
- rear wheel camber, 3°, 6°, 9°
- adjustable axle plates
- adjustable axle plates, compensated

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
folding back, angle-adjustable	104.00	N/A
supple back, tension-adjustable	74.00	136.00
backposts, at an 8° angle, from 31.8 cm $(12^{1}/_{2} \text{ in.})$ to 47.0 cm (18^{1})		
pair	14.00	
each		26.00
supple back, nylon	N/C	62.00
back spreader bar	126.00	N/A
backposts, angle-adjustable from -3° to $+15^{\circ}$, 3 positions	118.00	N/A
supple seat, nylon	N/C	53.00
modification of seat depth to 35.6 cm (14 in.), 38.1 cm (15 in.),	20.00	
43.2 cm (17 in.) or 45.7 cm (18 in.)	39.00	N/A
modification of back height from 48.3 cm (19 in.) to 55.9 cm (22 growth kit including: seat, back, footrests, front frame and crossb		N/A
(once only during first three years from date of purchase, for first		N/A
push handles	N/C	19.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
seat cushion, flat, foam, 10.2 cm (4 in.)	56.00	56.00
safety belt, velcro-type	N/C	28.00
safety belt, auto-type	N/C	41.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests :		
"L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short "T"-type armrests, detachable, height-adjustable	N/C	93.00
from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair each "I" type armrests, detachable, flip back, height adjustable	77.00	131.50
"U"-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long pair each	69.00	127.50
"U"-type armrests, flip-back, height-adjustable from 22.9 cm (9 i to 33.0 cm. (13 in.) for angle-adjustable back, short	in.)	
pair each	160.00	173.00
"I"-type armrests, flip-back, height-adjustable from 22.2 cm $(8^{3}/_{4}$ to 34.9 cm $(13^{3}/_{4}$ in.), short pair	291.00	
each tubular armrest pads straight armrest pads, short	N/C N/C	238.50 2.00 15.00
clothing guards, flexible clothing guards, rigid pair	N/C 90.00	21.00
each	90.00	66.00
Footrests : 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 70° footrests, tapered, detachable, swingaway, length-adjustable	N/C	53.00
from 35.6 cm (14 in.) to 48.3 cm (19 in.) 70° or 80° fixed footrests, heavy-duty	N/C	53.00
pair each	63.00	84.50
70° or 80° footrests, detachable, swingaway, length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.) elevating legrests, compensating mechanism, detachable	N/C	55.00
pair each	194.00	150.00
elevating legrests, detachable pair each	105.00	105.50
padded calfrests contoured calfrests	N/C	18.00
pair	70.00	52.00
each padded calfrests, for elevating legrests, compensating mechanism single calf strap	18.00	53.00 39.00 18.00
double calf strap	32.00	32.00

folding footplates, standardN/C 48.00 folding footplates, angle-adjustable51.0073.50each71.0073.50folding footplates, ubular71.0083.00pair71.0083.50each83.00179.00modification of footrest length from 48.3 cm (19 in.)N/C10.00modification of footrest length from 48.3 cm (19 in.)30.0029.00to 34.3 cm (13½; in.) in length9air54.00each73.6033.00front impact guard with rollers9aireach36.0018.00Wheels and frame85.00Frame:36.0018.00wite-along frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in.)50.00N/AN/A55.9 cm (22 in.) wide, 350-1b. capacity360.00one-arm dual handrin midrive54.00688.00and and handrin midrive61.0 cm (24 in.)N/Cpair54.00688.00and handrin midrive51.0 cm (22 in.), s5.9 cm (22 in.),61.0 cm (24 in.) or 66.0 cm (26 in.)102.00plair54.00685.00non-slip handrims, 50.8 cm (20 in.), 55.9 cm (22 in.),61.0 cmgair54.00685.00non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.)85.00pair54.0064.00each140.00satir140.00satir140.00satir140.00satir140.00satir140.00		Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)	
pair 51.00 73.50 folding footplates, tubular 61.00 73.50 folding footplates, tubular 73.50 folding footplates, oversized 71.00 73.50 folding footplates, oversized 71.00 71.0		N/C	48.00	
each73.50folding footplates, tubularN/C48.00folding footplates, oversized71.0083.50pair71.0083.50full-width footplate, folding, angle-adjustable83.00179.00heel loops, length-adjustableN/C10.00modification of footrest length from 48.3 cm (19 in.)30.0029.00raised footplate mountings, from 17.8 cm (7 in.)30.0029.00vaised footplate mountings, from 17.8 cm (7 in.)36.0033.00front impact guard with rollers36.0086.00pair36.0018.00Wheels and frameFrame:optional heavy-duty frame, 45.7 cm (18 in.)to 55.9 cm (22 in.) wide, 350-lb. capacity360.00N/AAdvise systems:one-arm dual handrim driveadai aduinnum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.)646.00aduit vertical or oblique projections, 61.0 cm (24 in.)pairaduit colspan="2">aduit vertical or oblique projections, 61.0 cm (24 in.)pairaduit colspan="2">aduit vertical aduiting for one-arm driveaduit vertical or oblique for one-arm driveaduit vertical or oblique projections, 61.0 cm (24 in.)pairaduit vertical or oblique role on (24 in.)pairaduit vertical or oblique role on (24 in.)		51.00		
folding footplates, ubularN/C 48.00 folding footplates, oversized71.00each83.50each83.00full-width footplate, folding, angle-adjustable83.00heel loops, length-adjustableN/Cto 52.1 cm (20%) in.)30.00voit of footrest length from 48.3 cm (19 in.)000to 52.1 cm (20%) in.)30.00voit of 4.3 cm (13%) in.) in length33.00pair54.00each33.00front impact guard with rollers36.00pair36.00each18.00Wheels and frameFrame:optional heavy-duty frame, 45.7 cm (18 in.)to 55.9 cm (22 in.) wide, 350-lb. capacityone-arm dual handrim drive546.00N/CN/AN/ATypes of drive systems:one-arm dual handrim s, 50.8 cm (20 in.), 55.9 cm (22 in.),61.0 cm (24 in.) or 66.0 cm (26 in.)50.0 cm (24 in.)pair54.00688.00anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.),61.0 cm (24 in.) or 66.0 cm (26 in.)54.00pair54.00each102.00pair54.00each102.00pair54.00each102.00pair54.00each102.00pair54.00each102.00pair54.00each102.00		51.00	73 50	
folding footplates, oversized pair 71.00 each 71.00 each 71.00 modification of footplate, folding, angle-adjustable 83.00 full-width footplate, folding, angle-adjustable 83.00 modification of footrest length from 48.3 cm (19 in.) to 52.1 cm (20/i in.) a0.00 29.00 raised footplate mountings, from 17.8 cm (7 in.) to 34.3 cm (13/ ₂ in.) in length pair 54.00 each 33.00 front impact guard with rollers pair 36.00 each 80.00 Wheels and frame Frame: optional heavy-duty frame, 45.7 cm (18 in.) to 55.9 cm (22 in.) wide, 350-1b. capacity 360.00 x/ra Types of drive systems: one-arm dual handrim drive 48.3 cm (19 in.) and 50.8 cm (20 in.) 50.00 Types of drive systems: one-arm dual handrim drive 546.00 each 88.00 anodized aluminuum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair 55.9 cm (22 in.), of 61.0 cm (24 in.) pair 54.00 pair 64.00 pair 54.00 pair 64.00 pair 64.0		N/C		
pair71.00each83.50full-width footplate, folding, angle-adjustable83.00hord lication of footrest length from 48.3 cm (19 in.)N/Cto 52.1 cm (20/ ₂ in.)30.00visit of otplate mountings, from 17.8 cm (7 in.)30.00to 34.3 cm (13/ ₂ in.) in length36.00pair54.00each33.00ronn timpact guard with rollers36.00pair36.00each18.00Wheels and frame18.00Visit of the systems:optional heavy-duty frame, 45.7 cm (18 in.)to 55.9 cm (22 in.) wide, 350-lb. capacity360.00extra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in.)50.00N/AN/ATypes of drive systems:one-arm dual handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)N/Cpair54.00688.00acch102.00platic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)102.00platic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)85.00acch102.00pair54.0085.00each102.00pair54.0085.00ach140.00ach140.00ach140.00ach140.00ach140.00anti-tip rollers143.00pair64.00ach140.00 <td></td> <td>100</td> <td>10.00</td>		100	10.00	
full-width footplate, folding, angle-adjustable83.00179.00heel loops, length-adjustableN/C10.00modification of footrest length from 48.3 cm (19 in.)30.0029.00raised footplate mountings, from 17.8 cm (7 in.)30.0029.00raised footplate mountings, from 17.8 cm (7 in.)54.0033.00each54.0033.00each36.0080.00each36.0080.00each36.0080.00each18.0080.00Wheels and frameFrame:optional heavy-duty frame, 45.7 cm (18 in.)to 55.9 cm (22 in.) wide, 350-lb. capacity360.00N/ATypes of drive systems:one-arm dual handrim driveand (20 in.), 55.9 cm (22 in.),61.0 cm (24 in.) or 66.0 cm (26 in.)N/CS8.00ardardardoptional heavy-duty frame, 50.8 cm (20 in.), 55.9 cm (22 in.),61.0 cm (24 in.) or 66.0 cm (26 in.)N/CS8.00andand (20 in.), 55.9 cm (22 in.),61.0 cm (24 in.) or 66.0 cm (26 in.)pair64.00and colspan="2">and colspan=		71.00		
heel loops, length-adjustable N/C 10.00 modification of footrest length from 48.3 cm (19 in.) to 52.1 cm (20/y, in.) in length pair 54.00 each 53.1 cm (13/y, in.) in length pair 54.00 each 33.00 front impact guard with rollers 36.00 each 18.00 Wheels and frame Frame: 0 optional heavy-duty frame, 45.7 cm (18 in.) to 55.9 cm (22 in.) wide, 350-lb. capacity 360.00 N/A extra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in.) 50.00 N/A Types of drive systems: 546.00 anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) handrims with vertical or oblique projections, 61.0 cm (24 in.) pair 54.00 each 55.9 cm (22 in.) or 66.0 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair 54.00 each 102.00 plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair 54.00 each 102.00 plastic-coated handrims, 50.9 cm (22 in.), 61.0 cm (24 in.) pair 64.00 each 140.00 small plastic-coated handrim for one-arm drive 54.00 each 140.00 small plastic-coated handrim for one-arm drive 54.00 each 140.00 NA				
$\begin{array}{cccc} \operatorname{nodification of footrest length from 48.3 cm (19 in.) & 30.00 & 29.00 \\ \operatorname{to } 52.1 cm (20)'_{2} in.) & \operatorname{to } 17.8 cm (7 in.) & 54.00 & 20.00 \\ \operatorname{raised footplate mountings, from 17.8 cm (7 in.) & 54.00 & 30.00 & 20.00 \\ \operatorname{rot} to & 34.3 cm (13)'_{2} in.) & \operatorname{in length} & 54.00 & 30.00 & 20.00 \\ \operatorname{front} impact guard with rollers & 36.00 & 20.00 & 20.00 & 20.00 & 20.00 \\ \operatorname{rot} timpact guard with rollers & 36.00 & 20.00 &$				
to 52.1 cm (20½, in.) 30.00 29.00 raised footplate mountings, from 17.8 cm (7 in.) 54.00 33.00 pair 54.00 33.00 each 33.00 30.00 pair 54.00 33.00 each 30.00 30.00 each 30.00 30.00 each 30.00 30.00 wheels and frame 18.00 Frame: optional heavy-duty frame, $45.7 cm$ (18 in.) 50.00 N/A to $55.9 cm$ (22 in.) wide, $350-1b.$ capacity 360.00 N/A contrast for depths of $48.3 cm$ (19 in.) and $50.8 cm$ (20 in.) 50.00 N/A Types of drive systems: one-arm dual handrim drive 546.00 688.00 anodized aluminum handrims, $50.8 cm$ (20 in.), $55.9 cm$ (22 in.), $61.0 cm$ (24 in.) or $66.0 cm$ (26 in.) N/C 58.00 pair 88.00 $60.0 cm$ (26 in.) 102.00 pair 54.00 85.00 pair 54.00 85.00 <td co<="" td=""><td></td><td>N/C</td><td>10.00</td></td>	<td></td> <td>N/C</td> <td>10.00</td>		N/C	10.00
raised footplate mountings, from 17.8 cm (7 in.) to 34.3 cm (13½ in.) in length pair 54.00 each 33.00 front impact guard with rollers pair 36.00 each 18.00 Wheels and frame Frame: optional heavy-duty frame, 45.7 cm (18 in.) to 55.9 cm (22 in.) wide, 350-lb. capacity 360.00 extra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in.) 50.00 N/A Types of drive systems: one-arm dual handrim drive 546.00 anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair 88.00 each 102.00 plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair 54.00 each 102.00 plastic-coated handrims, 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair 54.00 each 102.00 plastic-coated handrims, 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair 48.00 each 102.00 plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair 48.00 each 102.00 plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 61.0 cm (24 in.) pair 48.00 each 102.00 plastic-coated handrim for one-arm drive 54.00 small plastic-coated handrim for one-arm drive		30.00	20.00	
to 34.3 cm (13 ¹ / ₂ in.) in length pair 54.00 33.00 front impact guard with rollers pair 36.00 and each 3100 Wheels and frame Frame: optional heavy-duty frame, 45.7 cm (18 in.) to 55.9 cm (22 in.) wide, 350-1b. capacity 360.00 N/A extra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in.) 50.00 N/A Types of drive systems: one-arm dual handrim drive 546.00 688.00 anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) N/C 58.00 handrims with vertical or oblique projections, 61.0 cm (24 in.) pair 64.00 each 54.00 each 85.00 non-slip handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) 55.9 cm (22 in.), 61.0 cm (24 in.) or 61.0 cm (24 in.) 55.9 cm (22 in.), 61.0 cm (24 in.) or 61.0 cm (24 in.) 700 each 54.00 N/A anti-tip rollers 74.00 N/A anti-tip rollers 74.00 N/A		50.00	29.00	
pair54.00each33.00front impact guard with rollers33.00pair36.00each18.00Wheels and frameFrame:optional heavy-duty frame, 45.7 cm (18 in.)to 55.9 cm (22 in.) wide, 350-lb. capacity360.00N/ATypes of drive systems:one-arm dual handrim driveof 0.0 cm (24 in.) or 66.0 cm (26 in.)N/Chandrims, 50.8 cm (20 in.), 55.9 cm (22 in.),61.0 cm (24 in.) or 66.0 cm (26 in.)N/Cpaireach102.00plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.),61.0 cm (24 in.) or 66.0 cm (26 in.)N/Cpaireachpair164.00each164.00armpaireach164.00armpaireach164.00armarmarmarmarmarmarmarmarmarmarm <td cols<="" td=""><td></td><td></td><td></td></td>	<td></td> <td></td> <td></td>			
$ \begin{array}{c} \mbox{front impact guard with rollers} \\ \mbox{pair} & 36.00 \\ \mbox{acch} & 36.00 \\ \mbox{sech} & 36.00 \\ \mbox{Wheels and frame} \\ \hline \mbox{Frame:} & & & & & & & & \\ \mbox{frame for depths of 48.3 cm (18 in.) to 55.9 cm (22 in.) wide, 350-lb. capacity & 360.00 & N/A \\ \mbox{extra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in.) 50.00 & N/A \\ \mbox{extra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in.) 50.00 & N/A \\ \mbox{Types of drive systems:} & & & & & & & \\ \mbox{on-arm dual handrim drive} & 546.00 & 688.00 \\ \mbox{anddirgs aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), \\ \mbox{61.0 cm (24 in.) or 66.0 cm (26 in.) & N/C & 58.00 \\ \mbox{handrims with vertical or oblique projections, 61.0 cm (24 in.) \\ \mbox{pair} & & & & & & & & \\ \mbox{each} & & & & & & & & \\ \mbox{plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), \\ \mbox{61.0 cm (24 in.) or 66.0 cm (26 in.) & } & & & & & \\ \mbox{plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), \\ \mbox{61.0 cm (24 in.) or 66.0 cm (26 in.) & } & & & & & \\ \mbox{plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), \\ \mbox{61.0 cm (24 in.) or 66.0 cm (26 in.) & } & & & & \\ \mbox{plastic-coated handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) & & & \\ \mbox{pair} & & & & & & & \\ \mbox{each} & & & & & & & \\ \mbox{each} & & & & & & & \\ \mbox{plastic-coated handrim for one-arm drive} & & & & & & & \\ \mbox{small plastic-coated handrim for one-arm drive} & & & & & & & \\ \mbox{small plastic-coated handrim for one-arm drive} & & & & & & & \\ \mbox{small plastic-coated handrim for one-arm drive} & & & & & & & & \\ \mbox{small plastic-coated handrim for one-arm drive} & & & & & & & \\ \mbox{small plastic-coated handrim for one-arm drive} & & & & & & & \\ \mbox{small plastic-coated handrim for one-arm drive} & & & & & & & \\ \mbox{small plastic-coated handrim for one-arm drive} & & & & & & & \\ \mbox{small plastic-coated handrim for one-arm drive} & & & & & & & & \\ \mbox{small plastic-coated handrim for one-arm drive} & &$		54.00		
pair 36.00 each18.00Wheels and frameFrame: optional heavy-duty frame, 45.7 cm (18 in.) to 55.9 cm (22 in.) wide, 350-lb. capacity 360.00 N/ATypes of drive systems: one-arm dual handrim drive 546.00 and und handrim drive 546.00 688.00 and uight in the expectation of the expe			33.00	
each18.00Wheels and frameFrame: optional heavy-duty frame, 45.7 cm (18 in.) to 55.9 cm (22 in.) wide, 350 -lb. capacity 360.00 N/AN/Aextra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in.) 50.00 N/ATypes of drive systems: one-arm dual handrim drive 546.00 688.00 anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)N/C 58.00 nadrims with vertical or oblique projections, 61.0 cm (24 in.) pair 80.00 each 102.00 plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair 85.00 acoh 85.00 acohnon-stip handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair 85.00 acoh 140.00 N/Aand-tims, 55.9 cm (22 in.) or 61.0 cm (24 in.) pair 85.00 acoh 140.00 and 21.50		26.00		
Wheels and frameFrame: optional heavy-duty frame, 45.7 cm (18 in.) to 55.9 cm (22 in.) wide, 350-lb. capacity 360.00 N/AN/Acontrol (22 in.) wide, 350-lb. capacity 360.00 N/Aextra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in.) 50.00 N/ATypes of drive systems: one-arm dual handrim drive 546.00 688.00 andrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)N/C 58.00 handrims with vertical or oblique projections, 61.0 cm (24 in.) pairN/C 58.00 each102.00pair64.00each102.00pair54.00each85.00non-silp handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)102.00pair54.00each85.00non-silp handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)pair64.00each164.00each164.00each164.00each140.00N/Apair64.00N/Aeach140.00 <td co<="" td=""><td></td><td>36.00</td><td>10.00</td></td>	<td></td> <td>36.00</td> <td>10.00</td>		36.00	10.00
Frame: optional heavy-duty frame, 45.7 cm (18 in.) to 55.9 cm (22 in.) wide, 350-lb. capacity 360.00 N/Ato 55.9 cm (22 in.) wide, 350-lb. capacity 360.00 N/ATypes of drive systems: one-arm dual handrim drive 546.00 688.00 one-arm dual handrim drive 546.00 688.00 anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)N/C 58.00 handrims with vertical or oblique projections, 61.0 cm (24 in.) 88.00 102.00 plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) 85.00 pair 54.00 85.00 102.00 plastic-coated handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) 85.00 140.00 main 54.00 85.00 one-arm drive 54.00 85.00 N/A	eacn		18.00	
optional heavy-duty frame, 45.7 cm (18 in.)to 55.9 cm (22 in.) wide, 350-lb. capacity360.00N/Aextra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in.)50.00N/ATypes of drive systems: one-arm dual handrim drive546.00688.00anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)N/C58.00handrims with vertical or oblique projections, 61.0 cm (24 in.) pairN/C58.00each102.00platic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair54.00685.00each88.00each102.00platic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair54.0085.00each102.00platic-coated handrims, 55.9 cm (22 in.), or 61.0 cm (24 in.) pair164.00each140.00small plastic-coated handrim for one-arm drive54.00N/Aanti-tip rollerspair43.00each21.50	Wheels and frame			
to 55.9 cm (22 in.) wide, 350-lb. capacity 360.00 N/A Types of drive systems : one-arm dual handrim drive 50.8 cm (20 in.) 50.00 N/A Types of drive systems : one-arm dual handrim, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) 546.00 688.00 handrims with vertical or oblique projections, 61.0 cm (24 in.) pairN/C 58.00 each plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair 88.00 each pair 54.00 685.00 non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) pair 85.00 non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) pair 85.00 non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) pair 164.00 each each small plastic-coated handrim for one-arm drive 54.00 N/A anti-tip rollers pair 43.00 21.50	Frame :			
extra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in.)50.00N/ATypes of drive systems: one-arm dual handrim drive546.00688.00anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)N/C58.00handrims with vertical or oblique projections, 61.0 cm (24 in.) pairN/C58.00pair (24 in.) or 66.0 cm (26 in.)N/C58.00pair (24 in.) or 66.0 cm (26 in.)88.00102.00plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)54.0085.00pair (24 in.) or 66.0 cm (26 in.)54.00140.00140.00pair (24 in.) or 61.0 cm (24 in.)164.00140.00140.00each (26 in.)140.00140.00140.00pair (26 in.)54.00140.00140.00small plastic-coated handrim for one-arm drive (24 in.)54.00140.00small plastic-coated handrim for one-arm drive (24 in.)54.00140.00small plastic-coated handrim for one-arm drive (26 in.)54.00140.00small plastic-coated handrim for one-arm drive (24 in.)54.00140.00small plastic-coated handrim for one-arm drive (26 in.)54.00150 <td>optional heavy-duty frame, 45.7 cm (18 in.)</td> <td></td> <td></td>	optional heavy-duty frame, 45.7 cm (18 in.)			
Types of drive systems: one-arm dual handrim drive546.00688.00anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)N/C58.00handrims with vertical or oblique projections, 61.0 cm (24 in.) pairN/C58.00cach102.00plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair102.00pair54.00each85.00non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) pair164.00each140.00small plastic-coated handrim for one-arm drive54.00anti-tip rollers43.00pair43.00				
one-arm dual handrim drive 546.00 688.00 anodized aluminum handrims, $50.8 \mathrm{cm} (20 \mathrm{in.})$, $55.9 \mathrm{cm} (22 \mathrm{in.})$, N/C 58.00 handrims with vertical or oblique projections, $61.0 \mathrm{cm} (24 \mathrm{in.})$ N/C 58.00 pair 88.00 88.00 each102.00plastic-coated handrims, $50.8 \mathrm{cm} (20 \mathrm{in.})$, $55.9 \mathrm{cm} (22 \mathrm{in.})$, $61.0 \mathrm{cm} (24 \mathrm{in.})$ or $66.0 \mathrm{cm} (26 \mathrm{in.})$ pair 54.00 85.00 each 85.00 non-slip handrims, $55.9 \mathrm{cm} (22 \mathrm{in.})$ or $61.0 \mathrm{cm} (24 \mathrm{in.})$ 85.00 pair 164.00 each 140.00 small plastic-coated handrim for one-arm drive 54.00 anti-tip rollers 43.00 pair 43.00	extra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in.)) 50.00	N/A	
one-arm dual handrim drive 546.00 688.00 anodized aluminum handrims, $50.8 \mathrm{cm} (20 \mathrm{in.})$, $55.9 \mathrm{cm} (22 \mathrm{in.})$, N/C 58.00 handrims with vertical or oblique projections, $61.0 \mathrm{cm} (24 \mathrm{in.})$ N/C 58.00 pair 88.00 88.00 each102.00plastic-coated handrims, $50.8 \mathrm{cm} (20 \mathrm{in.})$, $55.9 \mathrm{cm} (22 \mathrm{in.})$, $61.0 \mathrm{cm} (24 \mathrm{in.})$ or $66.0 \mathrm{cm} (26 \mathrm{in.})$ pair 54.00 85.00 each 85.00 non-slip handrims, $55.9 \mathrm{cm} (22 \mathrm{in.})$ or $61.0 \mathrm{cm} (24 \mathrm{in.})$ 85.00 pair 164.00 each 140.00 small plastic-coated handrim for one-arm drive 54.00 anti-tip rollers 43.00 pair 43.00	Types of drive systems :			
anodized aluminum handrims, $50.8 \text{ cm} (20 \text{ in.})$, $55.9 \text{ cm} (22 \text{ in.})$, 61.0 cm (24 in.) or 66.0 cm (26 in.) N/C $58.00handrims with vertical or oblique projections, 61.0 \text{ cm} (24 \text{ in.})pair 88.00each 102.00plastic-coated handrims, 50.8 \text{ cm} (20 \text{ in.}), 55.9 \text{ cm} (22 \text{ in.}),61.0 cm (24 in.) or 66.0 cm (26 in.)pair 54.00each 85.00non-slip handrims, 55.9 \text{ cm} (22 \text{ in.}) \text{ or} 61.0 \text{ cm} (24 \text{ in.})pair 164.00each 140.00small plastic-coated handrim for one-arm drive 54.00 N/Aanti-tip rollerspair 43.00each 21.50$		546.00	688.00	
handrims with vertical or oblique projections, $61.0 \text{ cm} (24 \text{ in.})$ 88.00pair88.00each102.00plastic-coated handrims, $50.8 \text{ cm} (20 \text{ in.})$, $55.9 \text{ cm} (22 \text{ in.})$,54.00each54.00each85.00non-slip handrims, $55.9 \text{ cm} (22 \text{ in.})$ or $61.0 \text{ cm} (24 \text{ in.})$ 164.00pair164.00each140.00small plastic-coated handrim for one-arm drive54.00anti-tip rollers21.50	anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.),			
pair 88.00 each 102.00 plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 54.00 61.0 cm (24 in.) or 66.0 cm (26 in.) 54.00 pair 54.00 each 85.00 non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) 164.00 pair 164.00 each 140.00 small plastic-coated handrim for one-arm drive 54.00 anti-tip rollers 143.00 pair 43.00		N/C	58.00	
each 102.00 plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 102.00 61.0 cm (24 in.) or 66.0 cm (26 in.) 54.00 pair 54.00 each 85.00 non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) 164.00 pair 164.00 each 140.00 small plastic-coated handrim for one-arm drive 54.00 anti-tip rollers 21.50		00.00		
$\begin{array}{cccc} \mbox{plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.),} & & & & & & & \\ \mbox{61.0 cm (24 in.) or 66.0 cm (26 in.)} & & & & & & & & \\ \mbox{pair} & 54.00 & & & & & & & \\ \mbox{non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.)} & & & & & & & & \\ \mbox{pair} & & 164.00 & & & & & & \\ \mbox{each} & & & & & & & 140.00 \\ \mbox{small plastic-coated handrim for one-arm drive} & 54.00 & & & & & & & \\ \mbox{small plastic-coated handrim for one-arm drive} & 54.00 & & & & & & & \\ \mbox{anti-tip rollers} & & & & & & & & \\ \mbox{pair} & & & & & & & & & \\ \mbox{pair} & & & & & & & & & & \\ \mbox{pair} & & & & & & & & & & \\ \mbox{pair} & & & & & & & & & & & & \\ \mbox{pair} & & & & & & & & & & & & \\ \mbox{pair} & & & & & & & & & & & & \\ \mbox{pair} & & & & & & & & & & & & & \\ \mbox{pair} & & & & & & & & & & & & & & \\ \mbox{pair} & & & & & & & & & & & & & & & \\ \mbox{pair} & & & & & & & & & & & & & & & \\ \mbox{pair} & & & & & & & & & & & & & & & & \\ \mbox{pair} & & & & & & & & & & & & & & & & & & \\ \mbox{pair} & & & & & & & & & & & & & & & & & & \\ \mbox{pair} & & & & & & & & & & & & & & & & & & &$		88.00	102.00	
			102.00	
pair 54.00 each 85.00 non-slip handrims, $55.9 \text{ cm} (22 \text{ in.}) \text{ or } 61.0 \text{ cm} (24 \text{ in.})$ 164.00 pair 164.00 each 140.00 small plastic-coated handrim for one-arm drive 54.00 anti-tip rollers 143.00 pair 43.00 each 21.50				
each85.00non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.)164.00pair164.00each140.00small plastic-coated handrim for one-arm drive54.00anti-tip rollers143.00pair43.00each21.50		54.00		
pair164.00each140.00small plastic-coated handrim for one-arm drive54.00anti-tip rollers743.00pair43.00each21.50	each		85.00	
each140.00small plastic-coated handrim for one-arm drive54.00N/Aanti-tip rollers43.0021.50				
small plastic-coated handrim for one-arm drive 54.00 N/A anti-tip rollers pair 43.00 21.50		164.00	1 40 00	
anti-tip rollers pair 43.00 each 21.50		54.00		
pair 43.00 21.50		54.00	IN/A	
each 21.50	1 A A A A A A A A A A A A A A A A A A A	43.00		
cane holder 44.00 44.00			21.50	
	cane holder	44.00	44.00	

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks:	240	20.00
standard wheel locks, push-to-lock or pull-to-lock wheel lock extensions	N/C	39.00
pair each	26.00	13.00
anti-rollback brakes	((0)	15.00
pair each	66.00	33.00
wheel locks, push-to-lock or pull-to-lock, unilateral control	124.00	N/A
Types of forks : standard forks, 15 cm (6 in.), short forks, 13.3 cm $(5^{1}/_{4}$ in.) or high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.),		
15.2 cm (6 in.) and 20.3 cm (8 in.) wheels high forks, 17.8 cm (7 in.), compatible	N/C	31.00
with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels	N/C	36.00
fork-locking mechanisms pair	44.00	
each fork stems, + 1.9 cm $({}^{3}/_{4}$ in.) or + 3.8 cm $({}^{1}/_{2}$ in.)	N/C	22.00 16.00
multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.)		
and 20.3 cm (8 in.) wheels	N/C	54.00
Rear axles : quick-release axles	N/C	32.50
extension plates for amputee	42.00	
pair each	42.00	71.00
curved multi-position plates pair	28.00	
each		64.00
rear wheel camber, 3°, 6°, 9°	N/C N/C	N/A 50.00
axle plates axle plates, compensated	N/C N/C	63.00
Types of wheels:		
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	149.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	132.00
spoked rear wheels, high pressure, 61.0 cm (24 in.) or 66.0 cm (26 in.) rear wheels, heavy-duty, standard pressure	N/C	132.00
or high pressure, 61.0 cm (24 in.) pair each	122.00	193.00
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	132.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
rear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C	132.00
rear mag wheels, standard pressure, 55.9 cm (22 in.) or 61.0 cm (110.00
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)	N/C	61.00
front wheels, solid tires, 15.2 cm (6 in.)	N/C	60.00
front wheels, solid tires, 12.7 cm (5 in.)	N/C	46.00
front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
pair	47.00	
each		69.50
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4} \text{ in.})$	N/C	61.00
front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm $(1^{1}/_{4}$ in.)	N/C	60.00
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm $(1^{1}/_{2})$		
or 15.2 cm (6 in.) x 3.8 cm $(1^{1}/_{2} in.)$		
pair	80.00	
each		86.00
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 in.	.)	
pair	65.00	
each		78.50
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm $(1^{1}/_{2})$	in.)	, 0.00
pair	100.00	
each	100000	96.00
Component(s) under Special Consideration		
spoke guards*		
pair	67.00	
each		33.50
quick-release axles with lever mechanism*		
pair	64.00	
each		64.50
DEVICE FROM: SUNRISE MEDICAL CANADA INC.		PRICE
MANUAL WHEEL CHAIR, ADULT, "QUICKIE 2 HP" MOI	DEI	\$1 475.00
	DEL	\$1 475.00
Basic Components		
 Body support system supple back, nylon back height: from 21.6 cm (8¹/₂ in.) to 47.0 cm (18¹/₂ in.) supple seat, nylon seat width: from 35.6 cm (14 in.) to 50.8 cm (20 in.) seat depth: 40.6 cm (16 in.) front seat height: from 43.8 cm (17¹/₄ in.) to 54.6 cm (21¹/₂ in.) safety belt, velcro-type, auto-type push handles 		

Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- straight armrest pads, short, long
- tubular armrest pads
- flexible clothing guards

Footrests

- 60° or 70° fixed footrests, parallel, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- folding footplates, standard
- folding footplates, tubular
- heel loops, length-adjustable

Wheels and frame

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5¹/₄ in.), high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- high forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- fork stems, + 1.9 cm $(^{3}/_{4} \text{ in.})$, + 3.8 cm $(1^{1}/_{2} \text{ in.})$
- quick-release axles
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 15.2 cm (6 in.) x 3.2 cm (1¹/₄ in.)
- rear wheel camber, 3°, 6°, 9°
- adjustable axle plates
- adjustable axle plates, compensated

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic or Optional Component(s)		
Body support system		
Seat and back:	5 4 9 9	126.00
supple back, tension-adjustable backposts, at an 8° angle, from 31.8 cm $(12^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$, with handles	74.00	136.00
pair	14.00	
each	11.00	26.00
back spreader bar	126.00	N/A
backposts, angle-adjustable from -3° à + 15°, 3 positions	118.00	N/A
supple back, nylon	N/C	62.00
supple seat, nylon modification of seat depth to 35.6 cm (14 in.), 38.1 cm (15 in.),	N/C	53.00
43.2 cm (17 in.) or 45.7 cm (18 in.)	47.00	N/A
modification of back height from 48.3 cm (19 in.) to 55.9 cm (2		N/A
push handles	N/C	19.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
seat cushion, flat, foam, 10.2 cm (4 in.)	56.00	56.00
safety belt, velcro-type safety belt, auto-type	N/C N/C	28.00 41.00
Armrests :		
"L"-type armrests, detachable, swingaway, height-adjustable		
from 20.3 cm (8 in.) to 30.5 cm (12 in.), short	N/C	93.00
"T"-type armrests, detachable, height-adjustable	1	25.00
from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long		
pair	77.00	
each		131.50
"U"-type armrests, detachable, flip-back, height-adjustable		
from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long		
pair	69.00	
each		127.50
"U"-type armrests, detachable, flip-back, height-adjustable		
for angle-adjustable back, from 22.9 cm (9 in.)		
to 33.0 cm (13 in.), short pair	160.00	
each	100.00	173.00
tubular armrest pads	N/C	2.00
straight armrest pads, long	N/C	17.00
straight armrest pads, short	N/C	15.00
clothing guards, flexible	N/C	21.00
clothing guards, rigid		
pair	90.00	
each		66.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests :		
60° or 70° fixed footrests, parallel, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	43.00
single calf strap	18.00	18.00
double calf strap	32.00	32.00
folding footplates, standard	N/C	48.00
folding footplates, angle-adjustable		
pair	51.00	
each		73.50
folding footplates, tubular	N/C	48.00
folding footplates, oversized	71.00	
pair	71.00	82.50
each	82.00	83.50
full-width footplate, folding, angle-adjustable	83.00 N/C	$\begin{array}{c} 179.00\\ 10.00 \end{array}$
heel loops, length-adjustable modification of footrest length from 48.3 cm (19 in.)	N/C	10.00
to 52.1 cm $(20^{1}/_{2} \text{ in.})$	30.00	29.00
raised footplate mounting, from 18.8 cm (7 in.)	30.00	29.00
to 34.3 cm $(13^{1}/_{2} \text{ in.})$ in length		
pair	54.00	
each	51.00	33.00
Wheels and frame		
Frame :		
optional heavy-duty frame, 45.7 cm (18 in.)		
to 55.9 cm (22 in.) wide, 350-lb. capacity	360.00	N/A
extra-long frame for depths of 48.3 cm (19 in.)		
and 50.8 cm (20 in.)	50.00	N/A
—		
Types of drive systems :	5 4 6 0 0	(00.00
one-arm dual handrim drive	546.00	688.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.),	NIC	58.00
61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	58.00
handrims with vertical or oblique projections, 61.0 cm (24 in.)	88.00	
pair each	88.00	102.00
plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.),		102.00
61.0 cm (24 in.) or 66.0 cm (26 in.)		
pair	54.00	
each	51.00	85.00
non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.)		00100
pair	164.00	
each		140.00
small plastic-coated handrim for one-arm drive	54.00	N/A
anti-tip rollers		
pair	43.00	
each		21.50
cane holder	44.00	44.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks:		
standard wheel locks, push-to-lock or pull-to-lock scissor-type wheel locks	N/C	39.00
pair	24.00	
each		51.00
wheel lock extensions	26.00	
pair each	20.00	13.00
wheel locks, push-to-lock or pull-to-lock, unilateral control anti-rollback brakes	124.00	N/A
pair	66.00	
each		33.00
Types of forks :		
standard forks, 15.2 cm (6 in.), short forks, 13.3 cm $(5^{1}/_{4}$ in.)		
or high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.),		
15.2 cm (6 in.) and 20.3 cm (8 in.) wheels high forks, 17.8 cm (7 in.), compatible	N/C	31.00
with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels	N/C	36.00
fork-locking mechanisms		
pair	44.00	
each fork stores $+ 1.0 \text{ cm} (3/\sin) \text{ cm} + 2.8 \text{ cm} (11/\sin)$	N/C	22.00
fork stems, + 1.9 cm $({}^{3}/_{4}$ in.) or + 3.8 cm $({}^{1}/_{2}$ in.) multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.)	N/C	16.00
and 20.3 cm (8 in.) wheels	N/C	54.00
Rear axles: quick-release axles	N/C	32.50
heavy-duty axles	N/C	52.50
pair	99.00	
each		82.00
extension plates for amputee	42.00	
pair each	42.00	71.00
curved multi-position plates		/ 1.00
pair	28.00	
each		64.00
rear wheel camber, 3°, 6°, 9°	N/C N/C	N/A 50.00
adjustable axle plates adjustable axle plates, compensated	N/C N/C	50.00 63.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels :		
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	149.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	132.00
spoked rear wheels, high pressure, 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	132.00
rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.)		
pair	122.00	102.00
each rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)		193.00
or 61.0 cm (24 in.)	N/C	132.00
rear mag wheels, standard pressure, 50.8 cm (20 in.) rear mag wheels, standard pressure, 55.9 cm (22 in.)	N/C	132.00
or 61.0 cm (24 in.)	N/C	110.00
front wheels, solid tires, $20.3 \text{ cm} (8 \text{ in.}) \times 2.5 \text{ cm} (1 \text{ in.})$	N/C	61.00
front wheels, solid tires, 15.2 cm (6 in.)	N/C	60.00
front wheels, solid tires, 12.7 cm (5 in.) front wheels, solid tires, 7.6 cm (3 in.)	N/C	46.00
pair	39.00	
each front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)		65.50
pair	47.00	
each	17.00	69.50
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4} in.)$	N/C	61.00
front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm ($1^{1/4}$ in.)	N/C	60.00
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm $(1^{1}/_{2}$ in or 15.2 cm (6 in.) x 3.8 cm $(1^{1}/_{2}$ in.)	ı.)	
pair	80.00	06.00
each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm $(1^{1}/_{2})$ in		86.00
pair	100.00	
each		96.00
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 in.)		
pair	65.00	78.50
each		78.50
Component(s) under Special Consideration		
spoke guards*		
pair	67.00	
each		33.50
quick-release axles with lever mechanism*		
pair	64.00	
each		64.50

DEVICE FROM : INVACARE CANADA INC.

MANUAL WHEEL CHAIR, "MVP JR" MODEL

Basic Component(s)

Body support system

- fixed back, height-adjustable from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- front seat height : from 37.5cm $(14^{3}/_{4} \text{ in.})$ to 54.0 cm $(21^{1}/_{4} \text{ in.})$
- seat widths : 30.5 cm (12 in.), 32.5 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.)
- seat depth : from 30.5 cm (12 in.) to 40.6 cm (16 in.)
- supple seat and back, nylon
- push handles
- safety belt, velcro-type, auto-type
- growth kit (once only during first three years from date of purchase, for first user)

Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 25.4 cm (10 in.), short
- "U"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long
- "L"-type armrests, height-adjustable from 12.7 cm (5 in.) to 25.4 cm (10 in.), short, long
- armrest pads, straight, contoured, short, long
- tubular armrest pads
- clothing guards, flexible, rigid, detachable

Footrests :

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 37.5 cm (14³/₄ in.) to 47.0 cm (18¹/₂ in.)
- 70° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 47.0 cm (18¹/₂ in.)
- 90° footrests, length-adjustable from 13.3 cm $(5^{1}/_{4} \text{ in.})$ to 26.0 cm $(10^{1}/_{4} \text{ in.})$
- 60° footrests, MFX, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 38.1 cm (15 in.)
- 70° footrests, MFX, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 47.0 cm (18¹/₂ in.)
- · padded calfrests
- · folding footplates, standard
- full-width footplate, tubular
- heel loops, non-adjustable
- heel loops, length-adjustable

PRICE

\$1 150.00

Wheels and frame

- · anodized aluminum handrims
- standard brakes, push-to-lock, pull-to-lock
- standard forks, short
- threaded axles
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), standard pressure, 40.6 cm (16 in.), 45.7 cm (18 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear wheel camber, 0°, 3°, 5°, 8°
- spoked rear wheels, high pressure, solid tires, 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 7.6 cm (3 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 3.8 cm (1¹/₂ in.), 10.2 cm (4 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic or Optional Component(s)		

Body support system

Seat and back :		
supple back, tension-adjustable	63.00	99.00
back, angle-adjustable	64.00	N/A
modification of seat height to 50.8 cm (20 in.)	32.00	N/A
supple back, nylon	N/C	36.00
rigid seat, flat, lowered 35.6 cm (14 in.) and more	140.00	176.00
supple seat, nylon	N/C	36.00
push handles	N/C	38.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, velcro-type	N/C	50.00
safety belt, auto-type	N/C	40.00
growth kit (once only during first three years from date		
of purchase, for first user)	N/C	N/A
Armrests :		
"L"-type armrests, detachable, swingaway, height-adjustable		
from 20.3 cm (8 in.) to 25.4 cm (10 in.), short	N/C	55.00
"U"-type armrests, detachable, height-adjustable	100	22.00
from 25.4 cm (10 in.) to 35.6 cm (14 in.), short or long	N/C	98.00
"T"-type armrests, detachable, height-adjustable	1	20100
from 15.2 cm (6 in.) to 25.4 cm (10 in.) or from 20.3 cm (8 in.)		
to 35.6 cm (14 in.), short or long		
pair	140.00	
each		125.00
		120100

	initial purchase or replacement of wheel chair	replacement of component (unit price)
T"-type armrests, height-adjustable from 12.7 cm (5 in.)		
o 25.4 cm (10 in.), short or long	N/C	98.00
clothing guards, flexible	N/C	15.00
clothing guards, rigid, detachable	N/C	46.00
urmrest pads, straight or contoured, short or long	N/C	26.00
ubular armrest pads	N/C	10.00
Footrests :		
50° or 80° fixed footrests, parallel, length-adjustable		
rom 37.5 cm $(14^{3}/_{4} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$		
air	167.00	
ach		167.00
50° footrests, parallel, detachable, swingaway, length-adjustable from 37.5 cm ($14^{3}/_{4}$ in.) to 47.0 cm ($18^{1}/_{2}$ in.), or 70° footrests,		
barallel, detachable, swingaway, length-adjustable		
from 34.3 cm $(13^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$	N/C	81.00
50° footrests, MFX, detachable, swingaway, length-adjustable	iv/c	01.00
From 27.9 cm (11 in.) to 38.1 cm (15 in.)	N/C	153.00
10° footrests, length-adjustable from 13.3 cm (5 ¹ / ₄ in.)	1000	155.00
$o 26.0 \text{ cm} (10^{1}/_4 \text{ in.})$	N/C	135.00
0° footrests, MFX, detachable, swingaway, length-adjustable	100	155.00
rom 34.3 cm $(13^{1}/_{2} \text{ in.})$ to 47 cm $(18^{1}/_{2} \text{ in.})$	N/C	153.00
0° footrests, tapered, detachable, length-adjustable	100	100100
rom 40.0 cm $(15^{3}/_{4} \text{ in.})$ to 50.2 cm $(19^{3}/_{4} \text{ in.})$		
air	107.00	
ach		135.00
levating legrests, from 38.7 cm $(15^{3}/_{4} \text{ in.})$ to 54.0 cm $(21^{1}/_{4} \text{ in.})$		
air	230.00	
ach		196.00
added calfrests	N/C	20.00
ingle calf strap	22.00	35.00
ouble calf strap	34.00	52.00
nodification of length of elevating legrests by – 2.5 cm (1 in.)		
r by – 5.1 cm (2 in.)	190.00	190.00
olding footplates, standard	N/C	40.00
versized footplates		
air	39.00	
ach		60.00
eel loops, length-adjustable	N/C	12.00
eel loops, non-adjustable	N/C	5.00
ull-width footplate, tubular, plastic-coated	30.00	150.00
ull-width footplate, angle-adjustable, depth-adjustable	72.00	192.00
ull-width footplate, tubular	N/C	120.00
potplates, angle-adjustable, depth-adjustable,		
andard or oversized		
air	72.00	
ach		76.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems : handrims with oblique or vertical projections pair each	155.00	112.00
plastic-coated handrims pair	52.00	
each anodized aluminum handrims combined handrims	N/C	60.00 34.00
pair each	52.00	60.00
anti-tip rollers pair	95.00	
each cane holder	32.00	48.00 32.00
Wheel locks : standard, push-to-lock or pull-to-lock scissor-type wheel locks	N/C	44.00
pair each	55.00	72.00
wheel lock extensions pair each anti-rollback brakes	32.00	16.00
pair each	98.00	93.00
Types of forks : forks, standard or short fork-locking mechanisms	N/C	49.00
pair each	100.00	50.00
Rear axles : threaded axles	N/C	15.00
quick-release axles pair each	76.00	53.00
extension plates for amputee pair each	42.00	21.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Frame :		
rear wheel camber, 0°, 3°, 5°, 8°	N/C	N/A
Types of wheels :		
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	90.00
rear mag wheels, standard pressure, 40.6 cm (16 in.),	140	20.00
45.7 cm (18 in.), 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)) N/C	90.00
spoked rear wheels, high pressure, 61.0 cm (24 in.)	N/C	126.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),	100	120.00
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	126.00
spoked rear wheels, solid tires, 61.0 cm (24 in.)	N/C	126.00
heavy-duty wheels, standard pressure, high pressure, solid tires,	1000	120.00
61.0 cm (24 in.)		
pair	79.00	
each	79.00	165.00
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.),		105:00
7.6 cm (3 in.), 12.7 cm (5 in.) or 15.2 cm (6 in.)	N/C	40.00
front wheels, solid tires, 20.3 cm (8 in.) x 3,8 cm $(1^{1}/_{2} in.)$,	ive	+0:00
10.2 cm (4 in.), 12.7 cm (5 in.) or 15.2 cm (6 in.)	N/C	40.00
front wheels, inner tube, $15.2 \text{ cm} (6 \text{ in.}) \times 3.2 \text{ cm} (1^{1}/_{4} \text{ in.})$	ive	40.00
or 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.)		
pair	25.00	
each	23.00	52.00
front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)		52.00
pair	48.00	
each	48.00	64.00
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4})$ in)	04.00
	.) 56.00	
pair each	30.00	68.00
each		08.00
Component(s) under Special Consideration		
spoke guards*		
pair	82.00	
each		41.00
quick-release axles with lever mechanism*		
pair	76.00	
each		53.00

DEVICE FROM : SUNRISE MEDICAL CANADA INC.

MANUAL WHEEL CHAIR, CHILD, "QUICKIE 2" MODEL

Basic Component(s)

Dusie Component(s)

- Body support system
- supple back, nylon
- back height : from 21.6 cm $(8^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$
- supple seat, nylon
- seat width : from 27.9 cm (11 in.) to 38.1 cm (15 in.)
- seat depth : 30.5 cm (12 in.), 35.6 cm (14 in.)
- front seat height : from 43.8 cm $(17^{1}/_{4} \text{ in.})$ to 54.6 cm $(21^{1}/_{2} \text{ in.})$
- growth kit including : seat, back, footrests, front frame and crossbars (once only during first three years from date of purchase, for first user)
- safety belt, velcro-type, auto-type
- push handles

Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- straight armrest pads, short, long
- tubular armrest pads
- clothing guards, flexible

Footrests

- 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- 70° or 80° footrests, detachable, swingaway, length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.)
- · padded calfrests
- padded calfrests for legrests, compensating mechanism
- · heel loops, length-adjustable
- folding footplates, standard
- folding footplates, tubular

Wheels and frame

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock or pull-to-lock
- standard forks, 15.2 cm (6 in.), short forks, 13.3 cm $(5^{1}/_{4} \text{ in.})$, high forks,
- 17.8 cm (7 in.), for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- standard forks, 17.8 cm (7 in.) for 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- fork stems, + 1.9 cm $(^{3}/_{4} \text{ in.})$, + 3.8 cm $(1^{1}/_{2} \text{ in.})$
- multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- quick-release axles

PRICE

\$1 370.00

- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 15.2 cm (6 in.) x 3.2 cm (1¹/₄ in.)
- rear wheel camber, 3°, 6°, 9°
- adjustable axle plates
- · adjustable axle plates, compensated

(***** F ****)		Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
-----------------------	--	--	---

Basic or Optional Component(s)

Body support system

Seat and back :		
folding back, angle-adjustable	104.00	N/A
back spreader bar	126.00	N/A
supple back, tension-adjustable	74.00	136.00
supple back, nylon	N/C	62.00
supple seat, nylon	N/C	53.00
modification of seat depth to 25.4 cm (10 in.), 27.9 cm (11 in.)		
or 33.0 cm (13 in.)	39.00	N/A
modification of seat width to 40.6 cm (16 in.)	105.00	N/A
growth kit including : seat, back, footrests, front frame and crossbars		
(once only during first three years from date of purchase, for first user)	N/C	N/A
modification of back height from 48.3 cm (19 in.) to 55.9 cm (22 in.)	100.00	N/A
backposts, angle-adjustable from -3° to $+15^{\circ}$, 3 positions	118.00	N/A
backposts, at an 8° angle, from 31.8 cm $(12^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$		
pair	14.00	
each		26.00
push handles	N/C	19.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
seat cushion, flat, foam, 10.2 cm (4 in.)	56.00	56.00
safety belt, velcro-type	N/C	28.00
safety belt, auto-type	N/C	41.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests : "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short "T"-type armrests, detachable, height-adjustable from 10 l cm (21/c in.) chock cm (12 in.) short cm (12 in.)	N/C	93.00
from 19.1 cm $(7^{1}/_{2}$ in.) to 30.5 cm (12 in.), short or long pair each "U"-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short	77.00	131.50
for angle-adjustable back pair each "I"-type armrests, flip-back, height-adjustable from 22.2 cm (8 ³ / ₄ in.) to 34.9 cm (13 ³ / ₄ in.), short	160.00	173.00
pair each tubular armrest pads straight armrest pads, long	291.00 N/C N/C	238.50 2.00 17.00
straight armrest pads, short clothing guards, flexible clothing guards, rigid pair each	N/C N/C 90.00	15.00 21.00 66.00
Footrests : 70° or 80° footrests, heavy-duty pair each	63.00	84.50
60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 90° footrests, detachable, swingaway, length-adjustable	N/C	53.00
from 20.3 cm (8 in.) to 33.0 cm (13 in.) 70° or 80° footrests, detachable, swingaway, length-adjustable	N/C	53.00
from 15.2 cm (6 in.) to 30.5 cm (12 in.) elevating legrests, compensating mechanism pair each	N/C 194.00	55.00 150.00
90° elevating legrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) pair each	69.00	87.50
elevating legrests, detachable, swingaway, length-adjustable pair each modification of footrest length from 17.8 cm (7 in.)	105.00	105.50
to 34.3 cm $(13^{1}/_{2} \text{ in.})$ modification of length of 90° footrests by + 5.1 cm (2 in.) or by + 10.2 cm (4 in.)	54.00	33.00
pair each	30.00	15.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
padded calfrests	N/C	18.00
contoured calfrests		
pair	70.00	
each		53.00
padded calfrests for legrests, compensating mechanism	N/C	39.00
single calf strap	18.00	18.00
double calf strap	32.00	32.00
folding footplates, standard	N/C	48.00
folding footplates, tubular	N/C	48.00
folding footplates, angle-adjustable		
pair	51.00	
each		73.50
folding footplates, oversized		
pair	71.00	
each		83.50
full-width footplate, angle-adjustable	83.00	179.00
full-width foot platform, 90°	89.00	185.00
heel loops, length-adjustable	N/C	10.00
front floor rollers	100	10.00
pair	55.00	
each	55.00	27.50
front impact guard with rollers		27.50
pair	36.00	
each	50.00	18.00
Wheels and frame		10100
Types of drive systems :		
one-arm dual handrim drive	546.00	688.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	58.00
handrims with oblique or vertical projections, 61.0 cm (24 in.)		
pair	88.00	
each		102.00
plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)		
pair	54.00	
each		85.00
non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.)		
pair	164.00	
each		140.00
small plastic-coated handrim for one-arm drive	54.00	N/A
anti-tip rollers		
pair	43.00	
each		21.50
cane holder	44.00	44.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks :		
standard wheel locks, push-to-lock or pull-to-lock wheel lock extensions	N/C	39.00
pair	26.00	12.00
each anti-rollback brakes		13.00
pair	66.00	
each	124.00	33.00 N/A
wheel locks, push-to-lock or pull-to-lock, unilateral control	124.00	N/A
Types of forks :		
standard forks, 15.2 cm (6 in.), short forks, 13.3 cm $(5^{1}/_{4}$ in.) or high forks, 17.8 cm (7 in.), for 12.7 cm (5 in.), 15.2 cm (6 in.)		
and 20.3 cm (8 in.) wheels	N/C	31.00
standard forks, 17.8 cm (7 in.),	N/C	26.00
for 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels fork-locking mechanisms	N/C	36.00
pair	44.00	
each fork stame $+ 1.0 \text{ cm} (3/\text{ in}) \text{ or } + 2.8 \text{ cm} (11/\text{ in})$	N/C	22.00 16.00
fork stems, + 1.9 cm $({}^{3}/_{4}$ in.) or + 3.8 cm $({}^{1}/_{2}$ in.) multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.)	N/C	10.00
and 20.3 cm (8 in.) wheels	N/C	54.00
Rear axles :		
quick-release axles	N/C	32.50
extension plates for amputee pair	42.00	
each	42.00	71.00
curved plates	29.00	
pair each	28.00	64.00
rear wheel camber, 3°, 6°, 9°	N/C	N/A
adjustable axle plates	N/C N/C	50.00 63.00
adjustable axle plates, compensated	N/C	03.00
Types of wheels :		
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	149.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),	ive.	149.00
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	132.00
spoked rear wheels, high pressure, 61.0 cm (24 in.) rear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C N/C	132.00 132.00
rear mag wheels, standard pressure, 55.9 cm (22 in.)		152.00
or $61.0 \text{ cm} (24 \text{ in.})$	N/C	110.00
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	132.00
		102.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)	N/C	61.00
front wheels, solid tires, 15.2 cm (6 in.)	N/C	60.00
front wheels, solid tires, 12.7 cm (5 in.)	N/C	46.00
front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
pair	47.00	
each	21/2	69.50
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1 ¹ / ₄ in.)	N/C	61.00
front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm $(1^{1}/_{4}$ in.) front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm $(1^{1}/_{2}$ in or 15.2 cm (6 in.) x 3.8 cm $(1^{1}/_{2}$ in.)	N/C .)	60.00
pair	80.00	
each	00.00	86.00
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 in.)		
pair	65.00	
each		78.50
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm $(1^{1}/_{2} \text{ in})$.)	
pair	100.00	
each		96.00
Component(s) under Special Consideration		
spoke guards*		
pair	67.00	
each	01.00	33.50
quick-release axles with lever mechanism*		
pair	64.00	
each		64.50
DEVICE FROM : SUNRISE MEDICAL CANADA INC.		PRIC
MANUAL WHEEL CHAIR, CHILD, "ZIPPIE GS" MODEL		\$1 430.0
		φ1 150.0
Basic Component(s)		
Body support system		
• supple back, nylon		
• folding back, angle-adjustable and height-adjustable		
• back height : from 35.6 cm (14 in.) to 45.7 cm (18 in.)		
• rigid seat, flat, adjustable		
• seat width : from 25.4 cm (10 in.) to 40.6 cm (16 in.)		
• seat depth : from 25.4 cm (10 in.) to 45.7 cm (18 in.) • front seat height : from 25.6 cm (14 in.) to 47.6 cm (18 ³ / in.)		
 front seat height : from 35.6 cm (14 in.) to 47.6 cm (18³/₄ in.) safety belt, velcro-type, auto-type 		

- safety belt, velcro-type, auto-type
- push handles
- backposts with push handles at 55.2 cm (21³/₄ in.), 62.9 cm (24³/₄ in.) or 70.5 cm (27³/₄ in.)

Armrests

- "T"-type armrests, detachable, height-adjustable from 19.1 cm ($7^{1}/_{2}$ in.) to 30.5 cm (12 in.), short, long
- "T"-type armrests, detachable, height-adjustable to 14.0 cm ($5^{1}/_{2}$ in.), 16.5 cm ($6^{1}/_{2}$ in.), 19.1 cm ($7^{1}/_{2}$ in.), short
- straight armrest pads, short, long
- tubular armrest pads

Footrests

- 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.), parallel
- 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.), parallel
- 70° or 80° footrests, detachable, swingaway, length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.), parallel
- 70°, 80° or 90° footrests, heavy-duty, detachable, non-flip-back
- heel loops, length-adjustable
- folding footplates, standard
- · padded calfrests for elevating legrests, compensating mechanism
- padded calfrests

- optional rigid frame
- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5¹/₄ in.), high forks 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- fork stems, + 1.9 cm $(\frac{3}{4} \text{ in.})$, + 3.8 cm $(1^{1}/_{2} \text{ in.})$
- · quick-release axles
- rear wheel camber, from 0° to 6°
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 15.2 cm (6 in.) x 3.2 cm (1¹/₄ in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic or Optional Component(s)		
Body support system		
Seat and back :		
headrest, small	90.00	93.00
headrest, medium	96.00	103.00
headrest, large	102.00	107.00
transversal bar for headrest mounting (folding)	226.00	242.00
articulated headrest mounting	154.00	168.00
transversal bar for headrest mounting (rigid)	194.00	206.00
folding back, angle-adjustable and height-adjustable	N/C	N/A
supple back, tension-adjustable	74.00	136.00
supple back, nylon	N/C	62.00
rigid seat, flat, adjustable	N/C	126.00
push handles	N/C	N/A
backposts, with push handles at 55.2 cm ($21^{3}/_{4}$ in.), 62.9 cm ($24^{3}/_{4}$ in		NI/A
or at 70.5 cm $(27^{3}/_{4} \text{ in.})$ back spreader bar	N/C 126.00	N/A N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, velcro-type	N/C	28.00
safety belt, auto-type	N/C	41.00
safety belt, airplane-type	49.00	77.00
safety belt, airplane-type, padded	74.00	102.00
Armrests :		
"T"-type armrests, detachable, height-adjustable		
from 19.1 cm $(7^{1}/_{2} \text{ in.})$ to 30.5 cm (12 in.), short or long "I"-type armrests, flip-back, height-adjustable from 16.5 cm $(6^{1}/_{2})$	N/C in.)	132.00
to 33.0 cm (13 in.), short, long pair	126.00	
each	120.00	195.00
"T"-type armrests, detachable, height-adjustable		175.00
from 14.0 cm $(5^{1}/_{2} \text{ in.})$ to 16.5 cm $(6^{1}/_{2} \text{ in.})$		
and to 19.1 cm $(7^{1}/_{2} \text{ in.})$, short	N/C	155.00
tubular armrest pads	N/C	2.00
straight armrest pads, long	N/C	17.00
straight armrest pads, short	N/C	15.00
clothing guards, rigid		
pair	90.00	
each		66.00
Footrests :		
60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	53.00
90° footrests, detachable, swingaway, length-adjustable	IN/C	55.00
from 20.3 cm (8 in.) to 33.0 cm (13 in.)	N/C	55.00
70° or 80° footrests, detachable, swingaway, length-adjustable	IN/C	55.00
from $15.2 \text{ cm} (6 \text{ in.})$ to $30.5 \text{ cm} (12 \text{ in.})$	N/C	55.00
70°, 80° or 90° footrests, heavy-duty, detachable, non-flip-back	N/C N/C	84.50
, o, or or yo roonests, heavy-duty, detachable, hon-mp-back	11/0	07.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
elevating legrests, compensating mechanism	10100	
pair	194.00	150.00
each 90° elevating legrests, detachable, swingaway, length-adjustable		150.00
from 20.3 cm (8 in.) to 33.0 cm (13 in.)		
pair	69.00	
each		87.50
elevating legrests, detachable, swingaway, length-adjustable	105.00	
pair each	105.00	105.50
padded calfrests	N/C	105.50
contoured calification	N/C	10.00
pair	70.00	
each		53.00
padded calfrests for elevating legrests, compensating mechanism	N/C	39.00
modification of footrest length from 48.3 cm (19 in.) to 52.1 cm $(20^{1}/_{2} \text{ in.})$	30.00	29.00
modification of length of 90° footrests by $+ 5.1 \text{ cm} (2 \text{ in.})$	50.00	29.00
or by $+ 10.2$ cm (4 in.)	30.00	15.00
single calf strap	18.00	18.00
folding footplates, standard	N/C	48.00
folding footplates, angle-adjustable	51.00	
pair each	51.00	73.50
full-width footplate, angle-adjustable	83.00	179.00
full-width footplate, rigid	89.00	185.00
footrest mounting, from 17.8 cm (7 in.) to 34.3 cm $(13^{1}/_{2} \text{ in.})$		
pair	54.00	22.00
each	N/C	33.00 10.00
heel loops, length-adjustable	N/C	10.00
Wheels and frame		
Types of drive systems :	546.00	(00.00
one-arm dual handrim drive anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.)	546.00	688.00
or 61.0 cm (24 in.)	N/C	58.00
handrims with oblique or vertical projections	00.00	
pair each	88.00	102.00
plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.)		102.00
or 61.0 cm (24 in.)		
pair	54.00	
each		85.00
non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) pair	164.00	
each	104.00	140.00
small plastic-coated handrim for one-arm drive	54.00	N/A
anti-tip rollers		
pair	43.00	
each	44.00	21.50
cane holder optional rigid frame	44.00 N/C	44.00 N/A
optional right frame	IN/C	1N/A

Wheel locks : Standard wheel locks, push-to-lock or pull-to-lock N/C 39.00 pair 26.00 13.00 each 13.00 13.00 anti-rollback brakes 13.00 33.00 Types of forks : standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5½ in.) 66.00 33.00 Types of forks : standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5½ in.) N/C 31.00 fork-iocking mechanism 22.00 60% 31.00 fork-locking mechanism 44.00 22.00 fork stems, + 1.9 cm (½ in.) or + 3.8 cm (1½ in.) N/C 16.00 Rear axles : N/C 32.50 quick-release axles N/C N/A Types of wheels : spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) N/C 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) N/C 132.00 rear wheel camber, 0° to 6.0 N/C 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) rear mag wheels, st		Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
wheel lock extensions, 15.2 cm (6 in.) 26.00 pair 26.00 each 13.00 anti-rollback brakes 33.00 Types of forks : standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5½, in.) or high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels pair 44.00 cach 22.00 fork-locking mechanism 22.00 fork stems, + 1.9 cm (½, in.) or + 3.8 cm (1½ in.) N/C 16.00 Rear axles : 22.00 quick-release axles N/C 32.50 rear wheel camber, 0° to 6° N/C 32.50 Spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) N/C 149.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.), N/C 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) or 61.0 cm (24 in.) N/C or 61.0 cm (24 in.) N/C 132.00 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.)			
pair 26.00 each 13.00 anti-rollback brakes 66.00 pair 66.00 each 33.00 Types of forks : standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5½, in.) or high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C fork-locking mechanism 22.00 pair 44.00 each 22.00 fork stems, + 1.9 cm (½ in.) or + 3.8 cm (1½ in.) N/C N/C act car wheel camber, 0° to 6° N/C N/C Types of wheels : spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) N/C 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) N/C 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) N/C 132.00 rear mag		N/C	39.00
pair 66.00 each 33.00 Types of forks : standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5 ¹ / ₄ in.) or high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork-locking mechanism N/C pair 44.00 each 22.00 fork stems, + 1.9 cm (¹ / ₄ in.) or + 3.8 cm (1 ¹ / ₂ in.) N/C 16.00 Rear axles : quick-release axles N/C 32.50 rear wheel camber, 0° to 6° N/C 32.50 N/C 32.00 spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or (1/2 in.) N/C 149.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.), Spoked rear wheels, standard pressure, 50.8 cm (20 in.), Spoked rear wheels, standard pressure, 50.8 cm (20 in.), rear ang wheels, standard pressure, 50.9 cm (22 in.) or (1.0 cm (24 in.) N/C not (24 in.) N/C 132.00 rear wheels, standard pressure, 50.9 cm (pair	26.00	13.00
each 33.00 Types of forks : standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5 ¹ /, in.) or high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.), add 20.3 cm (8 in.) wheels N/C 31.00 fork-locking mechanism pair 44.00 each 22.00 fork stems, + 1.9 cm (¹ / ₄ in.) or + 3.8 cm (1 ¹ / ₂ in.) N/C 16.00 Rear axles : quick-release axles N/C 32.50 rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) N/C 149.00 spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) N/C 149.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 car amag wheels, standard pressure, 50.9 cm (22 in.) N/C 132.00 or 61.0 cm (24 in.) N/C 132.00 10.00 <td< td=""><td></td><td></td><td></td></td<>			
standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5 $\frac{1}{4}$ in.) or high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork-locking mechanism pair 44.00 each 22.00 fork stems, + 1.9 cm ($\frac{1}{4}$ in.) or + 3.8 cm ($\frac{1}{2}$ in.) N/C 16.00 Rear axles : quick-release axles N/C 32.50 rear wheel camber, 0° to 6° N/C N/A Types of wheels : spoked rear wheels, stolid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) N/C 149.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) N/C 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) or 61.0 cm (24 in.) N/C 132.00 rear mag wheels, standard pressure, 30.5 cm (12 in.) N/C 132.00 rear mag wheels, standard pressure, 30.5 cm (12 in.) N/C 132.00 rear mag wheels, standard pressure, 40.6 cm (16 in.) pair 32.00 reach 142.00 front wheels, solid tires, 15.2 cm (6 in.) N/C 61.00 front wheels, solid tires, 15.2 cm (6 in.) N/C 46.00 front wheels, solid tires, 12.7 cm (5 in.) N/C 46.00 front wheels, solid tires, 12.7 cm (5 in.) N/C 46.00 front wheels, solid tires, 12.7 cm (5 in.) m/C 46.00 front wheels, solid tires, 12.7 cm (5 in.) m/C 46.00 front wheels, solid tires, 12.7 cm (5 in.) m/C 46.00 front wheels, solid tires, 12.7 cm (5 in.) m/C 46.00		66.00	33.00
standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5 $\frac{1}{4}$ in.) or high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork-locking mechanism pair 44.00 each 22.00 fork stems, + 1.9 cm ($\frac{1}{4}$ in.) or + 3.8 cm ($\frac{1}{2}$ in.) N/C 16.00 Rear axles : quick-release axles N/C 32.50 rear wheel camber, 0° to 6° N/C N/A Types of wheels : spoked rear wheels, stolid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) N/C 149.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) N/C 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) or 61.0 cm (24 in.) N/C 132.00 rear mag wheels, standard pressure, 30.5 cm (12 in.) N/C 132.00 rear mag wheels, standard pressure, 30.5 cm (12 in.) N/C 132.00 rear mag wheels, standard pressure, 40.6 cm (16 in.) pair 32.00 reach 142.00 front wheels, solid tires, 15.2 cm (6 in.) N/C 61.00 front wheels, solid tires, 15.2 cm (6 in.) N/C 46.00 front wheels, solid tires, 12.7 cm (5 in.) N/C 46.00 front wheels, solid tires, 12.7 cm (5 in.) N/C 46.00 front wheels, solid tires, 12.7 cm (5 in.) m/C 46.00 front wheels, solid tires, 12.7 cm (5 in.) m/C 46.00 front wheels, solid tires, 12.7 cm (5 in.) m/C 46.00 front wheels, solid tires, 12.7 cm (5 in.) m/C 46.00	Types of forks :		
15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork-locking mechanism pair 44.00 pair 44.00 22.00 fork stems, + 1.9 cm ($\frac{1}{4}$ in.) or + 3.8 cm ($\frac{1}{2}$ in.) N/C 16.00 Rear axles : quick-release axles N/C 32.50 rear wheel camber, 0° to 6° N/C N/A Types of wheels : spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) N/C 149.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) N/C 132.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 10.0 cm (24 in.) N/C 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 10.0 cm (24 in.) N/C 120.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) or 61.0 cm (24 in.) N/C 120.00 10.00 rear mag wheels, standard pressure, 30.5 cm (12 in.) N/C 132.00 126.00 120.00 126.00 120.00 <td< td=""><td>standard forks, 15.2 cm (6 in.), short forks, 13.3 cm $(5^{1}/_{4} \text{ in.})$</td><td></td><td></td></td<>	standard forks, 15.2 cm (6 in.), short forks, 13.3 cm $(5^{1}/_{4} \text{ in.})$		
pair 44.00 each 22.00 fork stems, $+ 1.9 \text{ cm} (^{3}/_{4} \text{ in.}) \text{ or } + 3.8 \text{ cm} (1^{1}/_{2} \text{ in.})$ N/C 16.00 Rear axles : quick-release axles N/C 32.50 rear wheel camber, 0° to 6° N/C N/A Types of wheels : spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) N/C 149.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) N/C 132.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) or 61.0 cm (24 in.) N/C 110.00 rear mag wheels, standard pressure, 50.9 cm (22 in.) or 61.0 cm (24 in.) N/C 132.00 rear mag wheels, standard pressure, 30.5 cm (12 in.) N/C 132.00 rear mag wheels, standard pressure, 30.5 cm (12 in.) N/C 126.00 <tr< td=""><td>15.2 cm (6 in.) and 20.3 cm (8 in.) wheels</td><td>N/C</td><td>31.00</td></tr<>	15.2 cm (6 in.) and 20.3 cm (8 in.) wheels	N/C	31.00
each 22.00 fork stems, + 1.9 cm ($^{3}/_{4}$ in.) or + 3.8 cm ($^{1}/_{2}$ in.) N/C 16.00 Rear axles : quick-release axles N/C 32.50 rear wheel camber, 0° to 6° N/C N/A Types of wheels : spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) N/C 149.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) N/C 132.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 10.00 rear mag wheels, standard pressure, 55.9 cm (22 in.) N/C 110.00 120.00 rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) N/C 120.00 rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) N/C 126.00 rear mag wheels, standard pressure, 30.5 cm (12 in.) N/C 126.00 rear mag wheels, standard pressure, 40.6 cm (16 in.) 32.00 22.00 rear mag wheels, solid tires, 12.3 cm (8 in.) x 2.5 cm (1 in.) N/C 61.00 front wheels, solid tires, 12.7 cm (5 in.	e	44.00	
Rear axles :N/C 32.50 rear wheel camber, 0° to 6°N/CN/ATypes of wheels :spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)N/C149.00spoked rear wheels, standard pressure, 50.8 cm (20 in.),55.9 cm (22 in.)N/C132.00spoked rear wheels, standard pressure, 50.8 cm (20 in.),S5.9 cm (22 in.) or 61.0 cm (24 in.)N/C132.00spoked rear wheels, standard pressure, 61.0 cm (24 in.)N/C132.00132.00spoked rear wheels, standard pressure, 50.8 cm (20 in.)N/C132.00132.00rear mag wheels, standard pressure, 55.9 cm (22 in.)N/C132.00132.00rear mag wheels, standard pressure, 55.9 cm (22 in.)N/C110.00126.00rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)N/C126.00142.00rear mag wheels, standard pressure, 30.5 cm (12 in.)N/C126.00142.00rear mag wheels, standard pressure, 40.6 cm (16 in.)32.0020.0020.00rear mag wheels, solid tires, 15.2 cm (6 in.)N/C61.0060.00front wheels, solid tires, 15.2 cm (6 in.)N/C60.0060.00front wheels, solid tires, 12.7 cm (5 in.)N/C46.0060.00pair47.0047.0047.0047.00	each		22.00
quick-release axlesN/C 32.50 N/Crear wheel camber, 0° to 6°N/CN/ATypes of wheels : spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)N/C149.00spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)N/C132.00spoked rear wheels, standard pressure, 50.8 cm (20 in.)N/C132.00spoked rear wheels, standard pressure, 61.0 cm (24 in.)N/C132.00spoked rear wheels, standard pressure, 50.8 cm (20 in.)N/C132.00rear mag wheels, standard pressure, 50.8 cm (20 in.)N/C110.00rear mag wheels, standard pressure, 50.9 cm (22 in.)or 61.0 cm (24 in.)N/C110.00rear mag wheels, standard pressure, 30.5 cm (12 in.)or 61.0 cm (24 in.)N/C132.00rear mag wheels, standard pressure, 30.5 cm (12 in.)N/C126.00rear mag wheels, standard pressure, 40.6 cm (16 in.)pair32.00each142.00front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)N/C61.00front wheels, solid tires, 12.7 cm (5 in.)N/C46.00front wheels, solid tires, 12.7 cm (5 in.)N/C46.00pair47.00	fork stems, + 1.9 cm $({}^{3}/_{4}$ in.) or + 3.8 cm $({}^{1}/_{2}$ in.)	N/C	16.00
rear wheel camber, 0° to 6°N/CN/ATypes of wheels : spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)N/C149.00spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)N/C132.00spoked rear wheels, standard pressure, 61.0 cm (24 in.)N/C132.00spoked rear wheels, standard pressure, 50.8 cm (20 in.)N/C132.00rear mag wheels, standard pressure, 50.8 cm (20 in.)N/C132.00rear mag wheels, standard pressure, 55.9 cm (22 in.)N/C132.00or 61.0 cm (24 in.)N/C110.00rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.)N/C132.00rear mag wheels, standard pressure, 30.5 cm (12 in.)N/C132.00rear mag wheels, standard pressure, 30.5 cm (12 in.)N/C132.00rear mag wheels, standard pressure, 40.6 cm (16 in.)142.00pair32.00142.00cach142.00front wheels, solid tires, 15.2 cm (6 in.)N/C60.00front wheels, solid tires, 12.7 cm (5 in.)N/C46.00front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)147.00pair47.00140.00	Rear axles :		
Types of wheels : spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) N/C 149.00 spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) N/C 132.00 spoked rear wheels, high pressure, 61.0 cm (24 in.) N/C 132.00 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 rear mag wheels, standard pressure, 50.8 cm (20 in.) N/C 132.00 rear mag wheels, standard pressure, 55.9 cm (22 in.) N/C 132.00 or 61.0 cm (24 in.) N/C 110.00 rear mag wheels, standard pressure, 30.5 cm (12 in.) N/C 132.00 rear mag wheels, standard pressure, 30.5 cm (12 in.) N/C 132.00 rear mag wheels, standard pressure, 40.6 cm (16 in.) N/C 126.00 pair 32.00 22.00 22.00 each 142.00 142.00 front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) N/C 61.00 front wheels, solid tires, 15.2 cm (6 in.) N/C 60.00 front wheels, solid tires, 12.7 cm (5 in.) N/C 46.00 front wheels, inner tube, 20.3 cm			
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)or 61.0 cm (24 in.)N/C149.00spoked rear wheels, standard pressure, 50.8 cm (20 in.),N/C132.00spoked rear wheels, high pressure, 61.0 cm (24 in.)N/C132.00rear mag wheels, standard pressure, 50.8 cm (20 in.)N/C132.00rear mag wheels, standard pressure, 50.8 cm (20 in.)N/C132.00rear mag wheels, standard pressure, 50.8 cm (20 in.)N/C110.00rear mag wheels, standard pressure, 55.9 cm (22 in.)N/C110.00rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)N/C132.00or 61.0 cm (24 in.)N/C132.00rear mag wheels, standard pressure, 30.5 cm (12 in.)N/C132.00rear mag wheels, standard pressure, 40.6 cm (16 in.)N/C126.00pair32.00142.00front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)N/C61.00front wheels, solid tires, 15.2 cm (6 in.)N/C60.00front wheels, solid tires, 12.7 cm (5 in.)N/C46.00front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)Y/C47.00	rear wheel camber, 0° to 6°	N/C	N/A
or $61.0 \text{ cm} (24 \text{ in.})$ N/C149.00spoked rear wheels, standard pressure, $50.8 \text{ cm} (20 \text{ in.})$,55.9 cm (22 in.) or $61.0 \text{ cm} (24 \text{ in.})$ N/C132.00spoked rear wheels, high pressure, $61.0 \text{ cm} (24 \text{ in.})$ N/C132.00132.00rear mag wheels, standard pressure, $50.8 \text{ cm} (20 \text{ in.})$ N/C132.00rear mag wheels, standard pressure, $55.9 \text{ cm} (22 \text{ in.})$ N/C110.00rear mag wheels, solid tires, $50.8 \text{ cm} (20 \text{ in.})$, $55.9 \text{ cm} (22 \text{ in.})$ N/C132.00rear mag wheels, solid tires, $50.8 \text{ cm} (20 \text{ in.})$, $55.9 \text{ cm} (22 \text{ in.})$ N/C132.00rear mag wheels, standard pressure, $30.5 \text{ cm} (12 \text{ in.})$ N/C132.00rear mag wheels, standard pressure, $40.6 \text{ cm} (16 \text{ in.})$ N/C142.00rear mag wheels, solid tires, $20.3 \text{ cm} (8 \text{ in.}) \times 2.5 \text{ cm} (1 \text{ in.})$ N/C61.00front wheels, solid tires, $15.2 \text{ cm} (6 \text{ in.})$ N/C46.00front wheels, inner tube, $20.3 \text{ cm} (8 \text{ in.}) \times 5.1 \text{ cm} (2 \text{ in.})$ N/C47.00			
spoked rear wheels, standard pressure, $50.8 \text{ cm} (20 \text{ in.})$,N/C132.0055.9 cm (22 in.) or $61.0 \text{ cm} (24 \text{ in.})$ N/C132.00spoked rear wheels, high pressure, $61.0 \text{ cm} (24 \text{ in.})$ N/C132.00rear mag wheels, standard pressure, $50.8 \text{ cm} (20 \text{ in.})$ N/C132.00rear mag wheels, standard pressure, $55.9 \text{ cm} (22 \text{ in.})$ N/C110.00or $61.0 \text{ cm} (24 \text{ in.})$ N/C110.00rear mag wheels, solid tires, $50.8 \text{ cm} (20 \text{ in.})$, $55.9 \text{ cm} (22 \text{ in.})$ N/C132.00or $61.0 \text{ cm} (24 \text{ in.})$ N/C132.00rear mag wheels, solid tires, $50.8 \text{ cm} (20 \text{ in.})$, $55.9 \text{ cm} (22 \text{ in.})$ N/C132.00rear mag wheels, solid tires, $50.8 \text{ cm} (20 \text{ in.})$, $55.9 \text{ cm} (22 \text{ in.})$ N/C132.00rear mag wheels, standard pressure, $30.5 \text{ cm} (12 \text{ in.})$ N/C132.00rear mag wheels, standard pressure, $40.6 \text{ cm} (16 \text{ in.})$ 126.00142.00rear mag wheels, solid tires, $20.3 \text{ cm} (8 \text{ in.}) \times 2.5 \text{ cm} (1 \text{ in.})$ N/C61.00front wheels, solid tires, $15.2 \text{ cm} (6 \text{ in.})$ N/C60.00front wheels, solid tires, $12.7 \text{ cm} (5 \text{ in.})$ N/C46.00front wheels, inner tube, $20.3 \text{ cm} (8 \text{ in.}) \times 5.1 \text{ cm} (2 \text{ in.})$ 147.00		N/C	140.00
$55.9 \text{ cm} (22 \text{ in.}) \text{ or } 61.0 \text{ cm} (24 \text{ in.})$ N/C132.00spoked rear wheels, high pressure, $61.0 \text{ cm} (24 \text{ in.})$ N/C132.00rear mag wheels, standard pressure, $50.8 \text{ cm} (20 \text{ in.})$ N/C132.00rear mag wheels, standard pressure, $55.9 \text{ cm} (22 \text{ in.})$ N/C110.00rear mag wheels, solid tires, $50.8 \text{ cm} (20 \text{ in.})$, $55.9 \text{ cm} (22 \text{ in.})$ N/C110.00rear mag wheels, solid tires, $50.8 \text{ cm} (20 \text{ in.})$, $55.9 \text{ cm} (22 \text{ in.})$ N/C132.00or $61.0 \text{ cm} (24 \text{ in.})$ N/C132.00rear mag wheels, standard pressure, $30.5 \text{ cm} (12 \text{ in.})$ N/C132.00rear mag wheels, standard pressure, $40.6 \text{ cm} (16 \text{ in.})$ N/C126.00rear mag wheels, standard pressure, $40.6 \text{ cm} (16 \text{ in.})$ 142.00ront wheels, solid tires, $20.3 \text{ cm} (8 \text{ in.}) \times 2.5 \text{ cm} (1 \text{ in.})$ N/C61.00front wheels, solid tires, $15.2 \text{ cm} (6 \text{ in.})$ N/C46.00front wheels, inner tube, $20.3 \text{ cm} (8 \text{ in.}) \times 5.1 \text{ cm} (2 \text{ in.})$ N/C47.00	spoked rear wheels, standard pressure, 50.8 cm (20 in.).	N/C	149.00
rear mag wheels, standard pressure, 50.8 cm (20 in.)N/C132.00rear mag wheels, standard pressure, 55.9 cm (22 in.)N/C110.00or 61.0 cm (24 in.)N/C110.00rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)N/C132.00or 61.0 cm (24 in.)N/C132.00rear mag wheels, standard pressure, 30.5 cm (12 in.)N/C126.00rear mag wheels, standard pressure, 40.6 cm (16 in.)N/C126.00pair32.0032.00each142.00front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)N/C61.00front wheels, solid tires, 15.2 cm (6 in.)N/C60.00front wheels, solid tires, 12.7 cm (5 in.)N/C46.00front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)Y/C47.00	55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	132.00
rear mag wheels, standard pressure, 55.9 cm (22 in.) N/C 110.00 or 61.0 cm (24 in.) N/C 132.00 rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) N/C 132.00 or 61.0 cm (24 in.) N/C 132.00 rear mag wheels, standard pressure, 30.5 cm (12 in.) N/C 126.00 rear mag wheels, standard pressure, 40.6 cm (16 in.) N/C 126.00 pair 32.00 22.00 each 142.00 142.00 front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) N/C 61.00 front wheels, solid tires, 15.2 cm (6 in.) N/C 46.00 front wheels, solid tires, 12.7 cm (5 in.) N/C 46.00 front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.) 90 47.00			
or $61.0 \text{ cm} (24 \text{ in.})$ N/C110.00rear mag wheels, solid tires, $50.8 \text{ cm} (20 \text{ in.})$, $55.9 \text{ cm} (22 \text{ in.})$ N/C132.00or $61.0 \text{ cm} (24 \text{ in.})$ N/C132.00rear mag wheels, standard pressure, $30.5 \text{ cm} (12 \text{ in.})$ N/C126.00rear mag wheels, standard pressure, $40.6 \text{ cm} (16 \text{ in.})$ 32.00pair32.00each142.00front wheels, solid tires, $20.3 \text{ cm} (8 \text{ in.}) \times 2.5 \text{ cm} (1 \text{ in.})$ N/C61.00front wheels, solid tires, $15.2 \text{ cm} (6 \text{ in.})$ N/C60.00front wheels, solid tires, $12.7 \text{ cm} (5 \text{ in.})$ N/C46.00front wheels, inner tube, $20.3 \text{ cm} (8 \text{ in.}) \times 5.1 \text{ cm} (2 \text{ in.})$ 47.00		N/C	132.00
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)or $61.0 \text{ cm } (24 \text{ in.})$ N/C132.00rear mag wheels, standard pressure, 30.5 cm (12 in.)N/C126.00rear mag wheels, standard pressure, 40.6 cm (16 in.)32.00142.00pair32.0061.00each142.00front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)N/C61.00front wheels, solid tires, 15.2 cm (6 in.)N/C60.00front wheels, solid tires, 12.7 cm (5 in.)N/C46.00front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)47.00		N/C	110.00
rear mag wheels, standard pressure, $30.5 \text{ cm} (12 \text{ in.})$ N/C 126.00 rear mag wheels, standard pressure, $40.6 \text{ cm} (16 \text{ in.})$ 32.00 pair 32.00 each 142.00 front wheels, solid tires, $20.3 \text{ cm} (8 \text{ in.}) \times 2.5 \text{ cm} (1 \text{ in.})$ N/C 61.00 front wheels, solid tires, $15.2 \text{ cm} (6 \text{ in.})$ N/C 60.00 front wheels, solid tires, $12.7 \text{ cm} (5 \text{ in.})$ N/C 46.00 front wheels, inner tube, $20.3 \text{ cm} (8 \text{ in.}) \times 5.1 \text{ cm} (2 \text{ in.})$ 47.00	rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)		
rear mag wheels, standard pressure, 40.6 cm (16 in.) 32.00 pair 32.00 each 142.00 front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) N/C 61.00 front wheels, solid tires, 15.2 cm (6 in.) N/C 60.00 front wheels, solid tires, 12.7 cm (5 in.) N/C 46.00 front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.) 47.00			
pair 32.00 each 142.00 front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) N/C 61.00 front wheels, solid tires, 15.2 cm (6 in.) N/C 60.00 front wheels, solid tires, 12.7 cm (5 in.) N/C 46.00 front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.) 47.00		N/C	126.00
each 142.00 front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) N/C 61.00 front wheels, solid tires, 15.2 cm (6 in.) N/C 60.00 front wheels, solid tires, 12.7 cm (5 in.) N/C 46.00 front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.) 47.00 47.00		32.00	
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) N/C 61.00 front wheels, solid tires, 15.2 cm (6 in.) N/C 60.00 front wheels, solid tires, 12.7 cm (5 in.) N/C 46.00 front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.) 47.00	1	32.00	142.00
front wheels, solid tires, 15.2 cm (6 in.)N/C60.00front wheels, solid tires, 12.7 cm (5 in.)N/C46.00front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)47.00		N/C	
front wheels, solid tires, 12.7 cm (5 in.) N/C 46.00 front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.) 47.00			
front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.) pair 47.00			
pair 47.00		100	10100
		47.00	
	1		69.50

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4}$ in.) front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm $(1^{1}/_{4}$ in.) front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm $(1^{1}/_{2})$ or 15.2 cm (6 in.) x 3.8 cm $(1^{1}/_{2}$ in.)	N/C N/C in.)	61.00 60.00
pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm $(1^{1}/_{2})$ pair	80.00 in.) 100.00	86.00
each Component(s) under Special Consideration		96.00
spoke guards*		
pair each	67.00	33.50
§2. Lightweight manual wheel chairs		
DEVICE FROM : INVACARE CANADA INC.		PRICE
LIGHTWEIGHT MANUAL WHEEL CHAIR, "A-4/F4" MOI	DEL	\$1 438.00
Basic Component(s)		
 Body support system folding back, height adjustable from 20.3 cm (8 in.) to 50.8 cm supple seat and back, nylon front seat height : from 43.2 cm (17 in.) to 53.3 cm (21 in.) seat width : from 30.5 cm (12 in.) to 50.8 cm (20 in.) seat depth : from 35.6 cm (14 in.) to 48.3 cm (19 in.) safety belt, velcro-type, auto-type push handles, bolt-on or integrated 	(20 in.)	
 Armrests "L"-type armrests, detachable, swingaway, height-adjustable from 22.9 cm (9 in.) to 27.9 cm (11 in.), short tubular armrest pads straight armrest pads, short, long clothing guards, flexible, rigid 		
 Footrests 60° footrests, parallel, detachable, swingaway, length-adjustabl from 37.5 cm (14³/₄ in.) to 47.0 cm (18¹/₂ in.), or 70° footrests, j detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in to 47.0 cm (18¹/₂ in.) 80° fixed footrests, pointing inwards, tapered, length-adjustable from 28.6 cm (11¹/₄ in.) to 51.4 cm (20¹/₄ in.) folding footplates, standard full-width footplate, tubular, one-piece full-width footplate, angle-adjustable, depth-adjustable single calf strap 	parallel, n.)	

Wheels and frame

- anodized aluminum handrims
- swing-away brakes, standard, push-to-lock, pull-to-lock
- standard forks, short
- quick-release axles
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear wheels, heavy-duty, standard pressure, high pressure, solid tires, 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear mag wheels, standard pressure, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, solid tires, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- front wheels, solid tires, 7.6 cm (3 in.), 10.2 cm (4 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 2.5 cm (1 in.), 10.2 cm (4 in.) x 2.5 cm (1 in.)
- double camber tubes for the following angles : 0°, 3°, 6°, 9° or 12°

Price upon	Price upon
initial purchase	replacement
or replacement	of component
of wheel chair	(unit price)

Basic or Optional Component(s)

Body support system

Seat and back :		
modification of seat width to 53.3 cm (21 in.) or 55.9 cm (22 in.)	51.00	N/A
modification of seat depth to 50.8 cm (20 in.) or 55.9 cm (22 in.)	51.00	N/A
folding back, height adjustable from 20.3 cm (8 in.) to 50.8 cm (20 in.)	N/C	N/A
supple back, tension-adjustable	63.00	99.00
push handles, bolt-on or integrated	N/C	38.00
push handles, quick-release	63.00	69.00
supple back, nylon	N/C	36.00
supple seat, nylon	N/C	36.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, velcro-type	N/C	40.00
safety belt, auto-type	N/C	50.00
Armrests : "L"-type armrests, detachable, swingaway, height-adjustable from 22.9 cm (9 in.) to 27.9 cm (11 in.), short "T"-type armrests, detachable, height-adjustable from 15.2 cm (6 in.) to 25.4 cm (10 in.) or from 20.3 cm (8 in.) to 35.6 cm (14 in.), short or long	N/C	55.00
pair	140.00	
each		125.00
clothing guards, flexible	N/C	15.00
clothing guards, rigid	N/C	46.00
clothing guards, fold-away, non-detachable	< 4 0 0	
pair	64.00	16.00
each	21/2	46.00
tubular armrest pads	N/C	10.00
armrest pads, straight, short or long	N/C	26.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests :		
80° fixed footrests, pointing inwards or tapered,		
from 28.6 cm $(11^{1}/_{4} \text{ in.})$ to 51.4 cm $(20^{1}/_{4} \text{ in.})$	N/C	N/A
60° footrests, parallel, detachable, swingaway, length-adjustable		
from 37.5 cm $(14^{3}/_{4} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$, or 70° footrests,		
parallel, detachable, swingaway, length-adjustable		
from 34.3 cm (13 ¹ / ₂ in.) to 47.0 cm (18 ¹ / ₂ in.)	N/C	81.00
70° footrests, tapered, detachable, swingaway, length-adjustable		
from 40.0 cm ($15^{3}/_{4}$ in.) to 50.2 cm ($19^{3}/_{4}$ in.)		
pair	107.00	
each		135.00
60° footrests, MFX, parallel, detachable, swingaway, length-adjust		
from 27.9 cm (11 in.) to 38.1 cm (15 in.), or 70° footrests, MFX,		
parallel, detachable, swingaway, length-adjustable		
from 34.3 cm $(13^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$		
pair	144.00	
each		153.00
single calf strap	N/C	35.00
double calf strap	34.00	52.00
folding footplates, standard	N/C	40.00
full-width footplate, tubular, one-piece	N/C	120.00
over-sized footplates	20.00	
pair	39.00	(0.00
each		60.00
footplates, standard, angle-adjustable, depth-adjustable	72.00	
pair each	72.00	76.00
	N/C	192.00
full-width footplate, angle-adjustable, depth-adjustable	N/C	192.00
Wheels and frame		
Types of drive systems :		
handrims with vertical or oblique projections		
pair	155.00	
each		112.00
anodized aluminum handrims	N/C	34.00
plastic-coated or combined handrims		
pair	52.00	
each		60.00
anti-tip rollers		
pair	95.00	
each		48.00
front floor roller	29.00	29.00
quick-release push handles	63.00	69.00
cane holder	32.00	32.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks :		
standard wheel locks, push-to-lock or pull-to-lock	N/C	44.00
scissor-type wheel locks	N/C	72.00
anti-rollback brakes		
pair	98.00	
each		93.00
modification of frame in order to install swingaway footrests	474.00	N/A
Types of forks :		
forks, standard or short	N/C	49.00
Rear axles :		
quick-release axles	N/C	53.00
double camber tubes for the following angles : 0°, 3°, 6°, 9° or 12°	N/C	101.00
rear wheel camber	49.00	101.00
Types of wheels :		
rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in		
or 61.0 cm (24 in.)	N/C	90.00
rear mag wheels, solid tires, 50.8 (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	90.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),	21/2	12(00
55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	126.00
spoked rear wheels, high pressure, $61.0 \text{ cm} (24 \text{ in.}) \text{ or } 66.0 \text{ cm} (26 \text{ in})$		126.00
spoked rear wheels, solid tires, 61.0 cm (24 in.) or 66.0 cm (26 in.) heavy-duty rear wheels, solid tires, standard or high pressure,	N/C	126.00
61.0 cm. (24 in.) or 66.0 cm (26 in.)		
pair	N/C	
each	N/C	165.00
front wheels, solid tires, 15.2 cm (6 in.), 12.7 cm (5 in.)		105.00
or 7.6 cm (3 in.)	N/C	40.00
front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm $(1^{1}/_{4} in.)$	100	10.00
pair	25.00	
each		52.00
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 2.5 cm (1 in.)		
or 10.2 cm (4 in.) x 2.5 cm (1 in.)	N/C	40.00
front wheels, solid tires, 7.6 cm (3 in.), 10.2 cm (4 in.), 12.7 cm (5 in	.)	
or 15.2 cm (6 in.)	N/C	40.00
Component(s) under Special Consideration		
spoke guards*		
pair	82.00	
each	-	41.00
quick-release axles with lever mechanism*		
pair	76.00	
each		53.00

DEVICE FROM : SUNRISE MEDIAL CANADA INC.

LIGHTWEIGHT MANUAL WHEEL CHAIR, "QUICKIE R2" MODEL \$1 350.00

Basic Component(s)

Body support system

- folding back, height adjustable from 20.3 cm (8 in.) to 50.8 cm (20 in.)
- supple seat and back, nylon
- front seat height : from 43.2 cm (17 in.) to 55.56 cm $(21^{7}/_{8} \text{ in.})$
- seat width : from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth : from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- safety belt, velcro-type, auto-type
- push handles, bolt-on or integrated

Armrests

- "L"-type armrests, for fixed frame, for adjustable frame, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- tubular armrest pads
- · clothing guards, flexible, rigid

Footrests

- 80° fixed footrests, pointing inwards, length-adjustable from 40.0 cm (15³/₄ in.) to 52.7 cm (20³/₄ in.)
- full-width footplate, angle-adjustable
- single calf strap

Wheels and frame

- anodized aluminum handrims, 61.0 cm (24 in.), 66.0 cm (26 in.)
- swing-away brakes, standard, push-to-lock or pull-to-lock
- standard forks, 10.8 cm (4¹/₄ in.) for 7.6 cm (3 in.), 10.2 cm (4 in.) and 12.7 cm (5 in.) wheels
- forks, $13.3 \text{ cm} (5^{1}/_{4} \text{ in.})$
- short forks, 8.3 cm $(3^{1}/_{4}$ in.) for 7.6 cm (3 in.) and 10.2 cm (4 in.) wheels
- high forks, 12.1 cm (4³/₄ in.) for 7.6 cm (3 in.), 10.2 cm (4 in.) and 12.7 cm (5 in.) wheels
- long stems, +1.9 cm $({}^{3}/_{4}$ in.), +3.8 cm $({}^{1}/_{2}$ in.)
- quick-release axles
- rear wheels, spoked, standard pressure, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear wheels, heavy-duty, standard pressure, high pressure, 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 61.0 cm (24 in.)
- front wheels, solid tires, 12.7 cm (5 in.), 10.2 cm (4 in.), 7.6 cm (3 in.)
- rear wheel camber, simple, 4°, 8°, 16°
- rear wheel camber, double, 0° and 12°, 3° and 12°

PRICE

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic or Optional Component(s)		
Body support system		
Seat and back : modification of seat width to 48.3 cm (19 in.) or 50.8 cm (20 in.) modification of seat width to 33.0 cm (13 in.) modification of seat depth to 25.4 cm (10 in.) folding back, height adjustable from 20.3 cm (8 in.) to 50.8 cm (20 i supple back, tension-adjustable push handles, bolt-on push handles, integrated supple back, nylon supple seat, nylon seat cushion, flat, foam, 5.1 cm (2 in.) seat cushion, flat, foam, 7.6 cm (3 in.) safety belt, velcro-type safety belt, auto-type	85.00 680.00 400.00 n.) N/C N/C N/C N/C N/C N/C 56.00 56.00 N/C N/C	N/A N/A N/A 139.00 27.00 24.00 65.00 53.00 56.00 56.00 28.00 41.00
Armrests : "L"-type armrests, for fixed frame, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short "L"-type armrests, for adjustable frame, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short clothing guards, flexible clothing guards, rigid tubular armrest pads	N/C N/C N/C N/C N/C N/C	54.00 58.00 15.00 51.00 2.00
Footrests : 80° fixed footrests, pointing inwards, length-adjustable from 40.0 cm ($15^{3}/_{4}$ in.) to 52.7 cm ($20^{3}/_{4}$ in.) single calf strap double calf strap full-width footplate, angle-adjustable footplate spacer, 5.1 cm (2 in.), 10.2 cm (4 in.) or 15.2 cm (6 in.) anti-tip rollers	N/C N/C 14.00 N/C 20.00 28.00	N/A 18.00 32.00 108.00 10.00 28.00
Wheels and frame		
Types of drive systems : handrims with vertical or oblique projections, 61.0 cm (24 in.) or 66.0 cm (26 in.) pair each anodized aluminum handrims, 61.0 cm (24 in.) or 66.0 cm (26 in.) plastic-coated handrims, 61.0 cm (24 in.) or 66.0 cm (26 in.) pair each	88.00 N/C 54.00	102.00 58.00 85.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
non-slip handrims, 61.0 cm (24 in.)		
pair	164.00	140.00
each anti-tip rollers		140.00
pair	43.00	
each		21.50
modification of angle of fixed frame	570.00 145.00	N/A N/A
adjustable frame option	145.00	IN/A
Wheel locks :		
standard wheel locks, push-to-lock	N/C	58.50
standard wheel locks, pull-to-lock scissor-type wheel locks	N/C N/C	58.50 72.00
wheel lock extensions	N/C	72.00
pair	26.00	
each		13.00
anti-rollback brakes pair	62.00	
each	02.00	31.00
There are a for franker a		
Types of forks : forks, $13.3 \text{ cm} (5^{1}/_4 \text{ in.})$	N/C	31.00
standard forks, 10.8 cm $(4^{1}/_{4} \text{ in.})$ for 7.6 cm (3 in.), 10.2 cm (4 in.)	ive	51.00
and 12.7 cm (5 in.) wheels	N/C	35.00
short forks, 8.3 cm $(3^{1}/_{4} \text{ in.})$ for 7.6 cm (3 in.)	N/C	40.00
and 10.2 cm (4 in.) wheels high forks, 12.1 cm ($4^{3}/_{4}$ in.), for 7.6 cm (3 in.), 10.2 cm (4 in.)	N/C	40.00
and 12.7 cm (5 in.) wheels	N/C	31.00
long stems, +1.9 cm ($^{3}/_{4}$ in.) or +3.8 cm ($^{1}/_{2}$ in.)	N/C	16.00
Deer seles :		
Rear axles : quick-release axles	N/C	32.50
rear wheel camber, simple, 4°, 8° or 16°	N/C	76.50
double camber tubes for the following angles : 0°, 3°, 6°, 9° or 12°		
rear wheel camber, double, 0° and 12° or 3° and 12°	N/C	112.50
other rear wheel cambers	46.00	N/A
Types of wheels :		
rear mag wheels, standard pressure, 61.0 cm (24 in.)	N/C	110.00
spoked rear wheels, standard pressure, 61.0 cm (24 in.)	N/C	132.00
or 66.0 cm (26 in.) spoked rear wheels, high pressure, 61.0 cm (24 in.) or 66.0 cm (26 in	n.) N/C	132.00
heavy-duty rear wheels, standard pressure or high pressure,		102.00
61.0 cm (24 in.)	N/C	193.00
heavy-duty rear wheels, standard pressure or high pressure,		
66.0 cm (26 in.) pair	55.00	
each	22.00	220.00
front wheels, solid tires, 12.7 cm (5 in.), 10.2 cm (4 in.)		14.05
or 7.6 cm (3 in.)	N/C	46.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 in.) pair each	65.00	78.50
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm $(1^{1}/_{2}$ in pair each	n.) 80.00	86.00
front wheels, semi-pneumatic tires, 10.2 cm (4 in.) pair each	24.00	70.00
Component(s) under Special Consideration		
spoke guards* pair each	67.00	33.50
quick-release axles with lever mechanism* pair each	64.00	64.50
heavy-duty axles* pair each	99.00	82.00
§3. Powered wheel chairs		
DEVICE FROM : INVACARE CANADA INC.		PRICE
POWERED WHEEL CHAIR, "STORM ARROW" MODEL		\$4 706.00
Basic Component(s)		
 Body support system supple back, leatherette, nylon rigid seat, flat seat width : from 35.6 cm (14 in.) to 45.7 cm (18 in.) seat depths : 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.) seat height : 44.5 cm (17¹/₂ in.) to 50.2 cm (19³/₄ in.) back height : from 30.5 cm (12 in.) to 48.3 cm (19 in.) push handles push bar safety belt, auto-type centre of gravity adjustment from seat 		
 Armrests "U"-type armrests, detachable, flip-back, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short, long "U"-type armrests, fixed height, short, long armrest pads, straight, contoured, short, long rigid clothing guards, built into armrests 		

Footrests

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 44.5 cm (17¹/₂ in.), or 70° footrests, parallel, detachable, swingaway, length-adjustable from 29.8 cm (11³/₄ in.) to 43.2 cm (17 in.)
- 70° footrests, tapered, detachable, swingaway, length-adjustable from 33.7 cm (13¹/₄ in.) to 43.8 cm (17¹/₄ in.)
- padded calfrests
- folding footplates, standard
- heel loops, non-adjustable
- heel loops, length-adjustable

Drive system

- · programmable joystick control
- battery charge display
- battery charger
- battery box, group 22, group 24
- toggle switch
- direction joystick
- controller
- 4-brush motors with gears
- G/B motors with gears
- side bracket for joystick control, swivel side bracket for joystick control, midline bracket for joystick control
- anti-tip rollers

- reflector strips
- standard forks
- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.),
- 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4} in.)$
- · tie-down points for adapted transport
- running lights
- · front wheel rims
- · rear wheel rims
- · rear suspension

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
padded headrest, flat	80.00	80.00
small headrest	106.00	106.00
large headrest	106.00	106.00
combined headrest/neckrest	106.00	106.00
headrest mounting, fixed	53.00	53.00
headrest mounting, articulated	122.00	122.00
seat/back structure with angle-adjustable back	566.00	566.00

	Price upon	Price upon
	initial purchase	replacement
	or replacement	of component
	of wheel chair	(unit price)
padded back, contoured, leatherette	399.00	399.00
padded back, contoured, fabric	299.00	299.00
padded back, contoured, fabric, non-standard sizes	379.00	379.00
padded back, contoured, leatherette, non-standard sizes	479.00	479.00
padded seat, contoured, fabric	241.00	241.00
padded seat, contoured, fabric, non-standard sizes	318.00	318.00
padded seat, contoured, leatherette	341.00	341.00
padded seat, contoured, leatherette, non-standard sizes	422.00	422.00
rigid seat, flat	N/C	75.00
modification of back height to 50.8 cm (20 in.), 53.3 cm (21 in.),	1.00	
55.9 cm (22 in.), 58.4 cm (23 in.) or 61.0 cm (24 in.)	89.00	85.00
modification of seat depth to $48.3 \text{ cm} (19 \text{ in.})$ or to $50.8 \text{ cm} (20 \text{ in.})$		N/A
modification of seat depth to 30.5 cm (12 in.), 33.0 cm (13 in.),	121.00	1,1,11
35.6 cm (14 in.) or 38.1 cm (15 in.)	62.00	N/A
modification of seat depth to 53.3 cm (21 in.) or to 55.9 cm (22 in.)		N/A
modification of seat width to 48.3 cm (19 in.), 50.8 cm (20 in.),	223.00	10/1
53.3 cm (21 in.) or 55.9 cm (22 in.)	225.00	N/A
modification of seat width to 58.4 cm (23 in.) or 61.0 cm (24 in.)	277.00	N/A
modification of seat height to 54.6 cm $(21^{1}/_{2} \text{ in.})$	134.00	N/A
centre of gravity adjustment from seat	N/C	N/A
supple back, nylon	N/C	58.00
supple back, leatherette	N/C	58.00
push handles	N/C	40.00
push bar	N/C	58.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, auto-type	N/C	50.00
Armrests : "U"-type armrests, detachable, flip-back, height-adjustable		
from 20.3 cm (8 in.) to 30.5 cm (12 in.), short or long	N/C	115.00
"U"-type armrests, fixed height, short, long	N/C	96.00
padded armrests, straight or contoured, short, long	N/C	26.00
rigid clothing guards built into armrests	N/C	20.00 N/A
modification of armrest height by $-2.5 \text{ cm} (1 \text{ in.})$	179.00	N/A N/A
modification of anniest neight by – 2.5 cm (1 m.)	179.00	IN/A
Footrests :		
60° footrests, parallel, detachable, swingaway, length-adjustable		
from 34.3 cm ($13^{1}/_{2}$ in.) to 44.5 cm ($17^{1}/_{2}$ in.), or 70° footrests,		
parallel, detachable, swingaway, length-adjustable		
from 29.8 cm $(11^{3}/_{4} \text{ in.})$ to 43.2 cm (17 in.)	N/C	81.00
70° footrests, tapered, detachable, swingaway, length-adjustable		
from 33.7 cm ($13^{1}/_{4}$ in.) to 43.8 cm ($17^{1}/_{4}$ in.)	N/C	135.00
60° footrests, MFX, parallel, detachable, swingaway,		
length-adjustable from 24.1 cm $(9^{1}/_{2} \text{ in.})$ to 36.8 cm $(14^{1}/_{2} \text{ in.})$,		
or 70° footrests, MFX, parallel, detachable, swingaway,		
length-adjustable from 11.4 cm $(4^{1}/_{2} \text{ in.})$ to 25.4 cm (10 in.)		
pair	107.00	
each		135.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
90° elevating legrests, detachable, swingaway, length-adjustable		
from 12.7 cm (5 in.) to 20.3 cm (8 in.)	107.00	
pair each	107.00	135.00
elevating legrests, detachable, swingaway, length-adjustable		155.00
from 40.6 cm (16 in.) to 50.8 cm (20 in.)		
pair	230.00	
each		196.00
elevating legrests with compensating mechanism, detachable,		
swingaway, length-adjustable from 43.8 cm $(17^{1}/_{4} \text{ in.})$		
to 54.6 cm $(21^{1}/_{2} \text{ in.})$	220.00	
pair	230.00	196.00
each modification of elevating legrest length by -2.5 cm (1 in.)		198.00
or by -5.1 cm (2 in.)	190.00	190.00
padded calfrests	N/C	20.00
single calf strap	22.00	34.00
double calf strap	35.00	52.00
folding footplates, standard	N/C	40.00
folding footplates, oversized		
pair	39.00	
each		60.00
folding footplates, standard, angle-adjustable	72.00	
pair each	72.00	76.00
folding footplates, oversized, angle-adjustable		70.00
pair	72.00	
each		76.00
heel loops, non-adjustable	N/C	5.00
heel loops, length-adjustable	N/C	12.00
Wheels and frame		
Types of drive systems :		
programmable joystick control	N/C	479.00
compact joystick control (requires display)	340.00	819.00
heavy-duty joystick control (requires display and interface)	96.00	575.00
modification of joystick control, each	60.00	60.00
battery charge display	N/C	N/A
battery charger	N/C	401.00
battery boxes, group 24	N/C	201.00
battery box, group 22	N/C	185.00
touch pad control control with separate switches (requires display and interface)	214.00 200.00	693.00 679.00
proportional chin control (requires display)	354.00	833.00
non-proportional chin control (requires display)	368.00	847.00
breath control	1 740.00	1 740.00
head control	1 426.00	1 905.00
laptray touch switch control (requires display)	1 159.00	1 636.00
foot control (requires display)	1 159.00	1 636.00
toggle switch	N/C	21.00
toggle switch extension	96.00	96.00

pracket for separate display module 115.00 115.00 220.00 220.00 220.00 230.00 1358.00 4-brush motors with gears N/C 1358.00 4-brush motors with gears N/C 1358.00 1-brush motors with gears N/C 1339.00 N/C 1339.00 N/C 1339.00 N/C 139.00 N/C 139.00 N/C 199.00 100 100 100 100 100 100 100 100 100		Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
idapted controls interface 692.00 692.00 separate display module 1 099.00 1 099.00 irrection joystick N/C 126.00 itck extension 5.00 5.00 side bracket for joystick control N/C 126.00 witck extension 19.00 19.00 witch bracket for joystick control N/C 120.00 ide bracket for joystick control N/C 120.00 witch bracket 357.00 357.00 scal control bracket 357.00 357.00 scal control bracket 357.00 150.00 scal control bracket 357.00 N/C scal control bracket 357.00 N/C scal control bracket	emergency stop ribbon switch	25.00	75.00
non-proportional controls interface 692.00 692.00 injection joystick 1099.00 1099.00 intection joystick N/C 126.00 all extension 19.00 19.00 all extension 19.00 19.00 T-type extension 19.00 19.00 wivel side bracket for joystick control N/C 12.00 indiline bracket for joystick control N/C 190.00 side bracket for joystick control N/C 190.00 bracket for joystick control N/C 190.00 side bracket for joystick control N/C 190.00 bracket for separate display module 115.00 150.00 thin control bracket 357.00 357.00 sate accontrol bracket 357.00 220.00 controller N/C 138.00 throught gears N/C 139.00 controller N/C 139.00 throught gears N/C 1139.00 standard forks N/C N/A veaty-duty base		692.00	692.00
separate display module 1099.00 1099.00 infection joystick N/C 126.00 sile stansion 5.00 5.00 T-type extension 19.00 19.00 side bracket for joystick control N/C 250.00 side bracket for joystick control N/C 120.00 side bracket for joystick control N/C 19.00 stand the bracket 357.00 357.00 side bracket for joystick control N/C 19.00 stand the bracket 357.00 357.00 stand the bracket 150.00 150.00 stanket for sparate display module 115.00 115.00 stanket for sparate display module 115.00 139.00 stanket for sparate display module 109.00 220.00 220.00 stanket for sparate display module 109.00 150.00 150.00 stanket for sparate display module 105.00 139.00 170.00 150.00 Standard forks N/C 139.00 170.00 190.00 190.00 <			
the circle joystick NC 126.00 trick extension 19.00 19.00 TT-type extension 19.00 19.00 NC 250.00 TT-type extension 19.00 19.00 NC 250.00 trick extext for joystick control N/C 12.00 midline bracket for joystick control N/C 190.00 seath control bracket 357.00 357.00 thin control bracket 357.00 357.00 thin control bracket 357.00 150.00 trick extension 150.00 150.00 trick extension 150.00 150.00 trick for separate display module 115.00 115.00 trin control bracket 357.00 220.00 trick for separate display module 115.00 115.00 trin control bracket 357.00 150.00 trick for separate display module 115.00 115.00 trin control bib 220.00 220.00 20.00 Trick for separate display module 115.00 115.00 trin control bib 200.00 220.00 Trick for separate display module 113.00 trick for separate display module 114.00 trick for separate display module 114.00 trick for separate display module trick for separate display module 119.00 tront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) tric show for separate display module display for module display			
tick extension 19.00 19.00 T'-type extension 19.00 19.00 T'-type extension 19.00 19.00 Side bracket for joystick control N/C 12.00 midline bracket for joystick control N/C 19.00 seath centrol bracket 357.00 357.00 preath centrol bracket 357.00 357.00 tead control bracket 150.00 115.00 tead control bracket 150.00 150.00 tead control bracket 135.00 135.00 tead control bracket 135.00 135.00 tead control bracket 135.00 139.00 trinke toring the gears N/C 138.00 through motors with gears N/C 1139.00 G/B motors with gears N/C 119.00 triandard forks N/C 19.00 tear suspension N/C 19.00 triandard forks N/C 19.00 tear suspension forks 19.00 N/A sach N/C 75.00 uxnilights N/C N/A			
hall extension 5.00 5.00 'T'-type extension 19.00 19.00 'T'-type extension 19.00 19.00 wivel side bracket for joystick control N/C 12.00 indline bracket for joystick control N/C 19.00 oreath control bracket 357.00 357.00 brin control bracket 357.00 357.00 read control bracket 150.00 150.00 transmitter 150.00 150.00 oracket for separate display module 115.00 115.00 brin control bracket 357.00 328.00 oracket for separate display module 115.00 1139.00 JZB motors with gears N/C 1139.00 JZB motors with gears N/C 1139.00 JZB motors with gears N/C 1139.00 unit-ip rollers N/C 1139.00 teav-duty base 557.00 N/A ear suspension N/C 119.00 transdard forks N/C N/A ear delector strips N/C N/A sair 72.00 20 <td></td> <td></td> <td></td>			
Tr-type extension19.0019.00wivel side bracket for joystick controlN/C250.00wide bracket for joystick controlN/C12.00midline bracket for joystick controlN/C12.00midline bracket for joystick controlN/C190.00brack control bracket357.00357.00acd control bracket150.00150.00bracket for separate display module115.00115.00bracket for separate display module115.00113.00chin control bib220.00220.00bracket for separate display moduleN/C138.00throw motors with gearsN/C1139.00unti-tip rollersN/C60.00acr suspensionN/C119.00Itypes of wheels :tatadard forksN/CAdapted transportN/CV/CN/Aic-down points for adapted transportN/CN/Awith earsN/CN/Atach72.00tach19.00Type addition (14 in.) x 5.1 cm (2 in.)N/C40.00tach19.00Type addition (14 in.) x 7.6 cm (3 in.)N/C40.00tach19.00addition (14 in.) x 7.6 cm (3 in.)N/C40.00colspan="2">tach19.00addition (14 in.) x 7.6 cm (3 in.)N/C40.00tach19			
wivel side bracket for joystick control N/C 250.00 midline bracket for joystick control N/C 12.00 midline bracket for joystick control N/C 190.00 oreath control bracket 357.00 357.00 in control bracket 357.00 150.00 read control bracket 150.00 150.00 pracket for separate display module 115.00 1139.00 chin control bib 220.00 220.00 control ler N/C 139.00 throught base N/C 139.00 G/B motors with gears N/C 139.00 G/B motors with gears N/C 119.00 Muti-tip rollers N/C 119.00 threavy-duty base 557.00 N/A era suspension N/C N/A tradard forks N/C N/A unning lights N/C N/A uxiliary manual brakes 20.00 20.00 sair 72.00 20.00 20.00 rach 130.00 119.00 119.00 ront wheels, inner tube tires, 15.2 cm (6 in.) x			
ide bracket for joystick control N/C 12.00 midline bracket for joystick control N/C 190.00 preath control bracket 357.00 357.00 brack for separate display module 115.00 150.00 pracket for separate display module 115.00 150.00 pracket for separate display module 115.00 138.00 pracket for separate display module 1139.00 139.00 pracket for separate display module 1139.00 139.00 for motros with gears N/C 139.00 for motros with gears N/C 190.00 rear suspension N/C 51.00 running lights N/C 75.00 uurning lights N/C 75.00 uurning lights N/C 75.00 or or 0.3 cm (8 in.) x 4.1 cm (1/4 in.) x 7.6 cm (3 in.) N/C <	1 -type extension		
nidline bracket for joystick control N/C 190.00 oreath control bracket 357.00 357.00 bin control bracket 357.00 357.00 read control bracket 150.00 150.00 pracket for separate display module 115.00 115.00 bin control bib 220.00 220.00 control bracket N/C 138.00 oracket for separate display module N/C 139.00 other set is an and the set is set in the set in the set is set in the set is			
sreath control bracket 357.00 357.00 chin control bracket 357.00 357.00 chin control bracket 150.00 150.00 pracket for separate display module 115.00 115.00 chin control bib 220.00 220.00 control bib 220.00 220.00 control bracket N/C 1350.00 thin control bib 220.00 220.00 control bracket N/C 139.00 thin control bracket N/C 139.00 sear suspension N/C 119.00 Types of wheels : standard forks N/C 55.00 eration of the searce of the sea			
hin control bracket 357.00 357.00 read control bracket 150.00 150.00 pracket for separate display module 115.00 125.00 thin control bib 220.00 220.00 sontroller N/C 1358.00 J-brush motors with gears N/C 1139.00 MC 139.00 rear suspension N/C furti-tip rollers N/C 60.00 neavy-duty base 557.00 N/A ear suspension N/C 119.00 Pypes of wheels : 1 1 standard forks N/C 54.00 efflector strips N/C N/A uxiliary manual brakes N/C N/A uxiliary manual brakes M/C N/A sair 72.00 72.00 72.00 reach 72.00 72.00 72.00 72.00 reach 130.00 72.00 72.00 72.00 72.00 72.00 72.00 72.00 72.00 72.00 72.00 72.00 72			
nead control bracket 150.00 150.00 pracket for separate display module 115.00 115.00 bin control bib 220.00 220.00 controller N/C 1358.00 4-brush motors with gears N/C 1139.00 3/B motors with gears N/C 60.00 near-y-duty base 557.00 N/A ear suspension N/C 19.00 Fypes of wheels :			
racket for separate display module 115.00 (1500) chin control bib 220.00 220.00 20000 220.00 2010 20100 20100 20100 20100 20100 C/B motors with gears N/C 1139.00 mit-tip rollers N/C 60.00 reavy-duty base 557.00 N/A ear suspension N/C 119.00 Types of wheels : tandard forks N/C 54.00 reflector strips N/C 75.00 unning lights N/C 75.00 unning lights N/C 75.00 unning lights 1000 ach 45.00 cm (8 in.) x 5.1 cm (2 in.) N/C 55.00 ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) N/C 75.00 ront wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) N/C 75.00 ront wheels, inner tube tires, 35.6 cm (14 in.) x 7.0 cm (3 in.) N/C 75.00 ront wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 2000 ront wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 2000 ront wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 2000 ront wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 2000 ront wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 2000 ront wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 2000 ront wheels inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 2000 ront wheels inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 2000 ront wheels inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 2000 ront wheels inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 2000 ront wheels inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 2000 ront wheels inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 2000 ront wheels inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 2000 ront wheel rims N/C 43.000 rear wheel rims N/C 43.00 rear wheel r			
shin control bib220.00220.00controllerN/C1358.004brush motors with gearsN/C1139.00G/B motors with gearsN/C1139.00G/B motors with gearsN/C1139.00Inti-tip rollersN/C60.00neavy-duty base557.00N/Aear suspensionN/C119.00 Types of wheels : standard forksN/C54.00reflector stripsN/CN/Aie-down points for adapted transportN/C75.00unning lightsN/CN/Auuxiliary manual brakes30.00aar72.00aach45.00uuspension forks119.00ort on tweels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cort on tweels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C75.00ort ort wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C75.00pair90.0085.0090.00each118.00134.00ron twheel irmsN/C50.00ort wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)118.00aari118.00134.00ron twheel rimsN/C50.00aari95.00134.00aari95.00134.00aari95.00134.00aari95.00134.00aari109.00134.00	head control bracket		150.00
thin control bib220.00220.00controllerN/C1358.004-brush motors with gearsN/C1139.00G/B motors with gearsN/C1139.00G/B motors with gearsN/C1139.00Int-tip rollersN/C60.00neavy-duty base557.00N/Aear suspensionN/C119.00Types of wheels :standard forksN/CN/Areflector stripsN/CN/Aie-down points for adapted transportN/C75.00unning lightsN/CN/Aauritary manual brakes30.00aach45.00suspension forks130.00aach130.00ron twheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cron twheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C75.00ron twheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C75.00aari90.0085.0090.00each118.00134.00ron twheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)118.00aari134.00134.00ron twheel irmsN/C50.00aari134.00134.00ron twheel irmsN/C43.00aari118.00134.00aari95.00134.00aari95.00134.00aari95.00134.00aari109.00134.00	bracket for separate display module	115.00	115.00
controllerN/C1 358.001-brush motors with gearsN/C1 139.001-brush motors with gearsN/C1 139.00anti-tip rollersN/C60.00neavy-duty base557.00N/Aear suspensionN/C119.00Itypes of wheels :standard forksN/C54.00effector stripsN/CN/Aie-down points for adapted transportN/CN/Auxiliary manual brakesN/CN/Apair72.0055.00cach119.00119.00ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/C45.00uspension forks130.00119.00pair130.00119.00ront wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C40.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)118.0035.00aari118.00134.00134.00ront wheel rimsN/C43.00134.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)50.00134.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)50.00134.00rear wheel rimsN/C43.00134.00rear wheel rimsN/C43.00134.00rear wheel rimsN/C43.00134.00rear wheel rimsN/C43.00134.00rear wheel rimsN/C43.00134.00rear wheel rimsN/C43.00134.00 <td>chin control bib</td> <td>220.00</td> <td>220.00</td>	chin control bib	220.00	220.00
t-brush motors with gearsN/C1 139.00G/B motors with gearsN/C1 139.00G/B motors with gearsN/C1 139.00Init-tip rollersN/C60.00neavy-duty base557.00N/Arear suspensionN/C119.00 Types of wheels : standard forksN/Ceffector stripsN/CN/Aie-down points for adapted transportN/CN/Auxiliary manual brakesN/CN/Abair72.00200cach45.00cach119.00front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/C55.00fornt wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/C40.00for twheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C75.00for twheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C75.00for twheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C43.00for twheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)118.00134.00for twheel rimsN/C43.00134.00for twheel rimsN/C43.0050.00aach134.0050.00134.00for twheel rimsN/C50.00aach95.00134.00for twheel rimsN/C50.00aach95.00134.00for twheel rimsN/C50.00aach95.00134.00for twheel rims	controller	N/C	
G/B motors with gearsN/C1 139.00nnti-tip rollersN/C 60.00 neavy-duty base 557.00 N/Aear suspensionN/C 119.00 Types of wheels :standard forksN/C 54.00 relaxion of the second of the secon	4-brush motors with gears		
anti-tip rollersN/C 60.00 N/Aear suspensionN/CN/Aear suspensionN/CN/AtranspensionN/C119.00Types of wheels :standard forksN/CN/Aistandard forksN/CN/Aellector stripsN/CN/Aie-down points for adapted transportN/CN/Aie-down points for adapted transportN/CN/Auxiliary manual brakesN/CN/Aaair72.0020each45.00suspension forks119.00cond119.00ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/C55.00ront wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C40.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C75.00ront wheels, inner tube tires, 35.6 cm (14 in.) x 7.0 cm (2 ³ / ₄ in.)35.0025.00each118.0020.0020.00each118.0020.0020.00eachN/C43.0020.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)118.0020.00eachN/C43.0020.00rear wheels inserts for rear wheels95.0030.00ear wheel rimsN/C43.0030.00rinters inserts for front wheels35.0030.00ear wheel rimsN/C43.0030.00ear wheel rimsN/C43.0030.00ear			
nearly duty base557.00N/Arear suspensionN/C119.00Fypes of wheels :standard forksN/C54.00reflector stripsN/CN/Aie-down points for adapted transportN/C75.00unning lightsN/CN/Aair72.00each45.00bair130.00cach45.00cach119.00ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 10.2 cm (4 in.)N/Coar118.00cach134.00ront wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)oar118.00cach134.00ront wheel rimsN/Coar95.00oar95.00oar95.00oar95.00oar95.00oar95.00oar109.00			
ear suspensionN/C119.00Types of wheels : standard forksN/C54.00standard forksN/CN/Aie-down points for adapted transportN/CN/Aie-down points for adapted transportN/C75.00unning lightsN/CN/Aauxiliary manual brakesN/CN/Aauxiliary manual brakes45.00bair130.00cach19.00ron twheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 4.4 cm (1 ³ /4 in.)N/C40.00ron twheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C75.00or ar wheels, inner tube tires, 35.6 cm (14 in.) x 7.0 cm (2 ³ /4 in.)90.0050.00car wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)118.0050.00cach134.00134.00134.00ron twheel rimsN/C43.0050.00cach118.00134.00134.00car wheel rimsN/C50.0050.00car wheel rimsN/C50.00134.00ron twheel rimsN/C50.0050.00car wheel rimsN/C50.0050.00			
Image: Standard forksN/C54.00Standard forksN/CN/Aistandard forksN/CN/Aie-down points for adapted transportN/CN/Aie-down points for adapted transportN/CN/Aunning lightsN/CN/Aunning lightsN/CN/Aoair72.00Aeach45.00suspension forks119.00orn wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cfront wheels, inner tube tires, 5.2 cm (6 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 4.4 cm (1 ³ / ₄ in.)N/C cm (3 in.)or 20.3 cm (8 in.) x 5.6 cm (14 in.) x 7.6 cm (3 in.)N/Corn wheels, inner tube tires, 35.6 cm (14 in.) x 7 cm (2 ³ / ₄ in.)N/Cpair90.00each134.00ron wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)134.00ron wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)134.00ron wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)134.00ron wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)134.00ron wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)134.00rath134.00134.00rath130.00134.00rath95.00134.00rath95.00134.00rath95.00134.00rath95.00134.00rath95.00134.00rath95.00134.00rath95.00134.00 <td></td> <td></td> <td></td>			
tandard forksN/C54.00effector stripsN/CN/Aie-down points for adapted transportN/CN/Aunning lightsN/CN/Auxiliary manual brakesN/CN/Apair72.00N/Aaach45.00suspension forks130.00each119.00ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cfor twheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 4.4 cm (1 ¹ / ₄ in.)N/C cm (3 in.)ront wheels, inner tube tires, 22.9 cm (9 in.) x 7.6 cm (3 in.)N/Cront wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/Cpair90.00each85.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)118.00pair118.00rear wheel rimsN/C50.00ront wheel rimsN/C50.00ront wheel rimsN/C50.00ront wheel rimsN/C50.00rear wheel rimsN/C50.00tirless inserts for rear wheels95.00pair95.000pair95.000pair90.00rear wheels inserts for front wheels0pair109.00	real suspension	IN/C	119.00
reflector stripsN/CN/Aie-down points for adapted transportN/C75.00running lightsN/CN/Auxiliary manual brakesn/Apair72.00each45.00uspension forks130.00pair130.00ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 4.4 cm (1 ¹ / ₄ in.)N/C55.00ront wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C40.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C43.00ront wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)118.00134.00ront wheel rimsN/C43.00134.00ront wheel rimsN/C50.00134.00ront wheel rims109.00109.00109.00 <td>Types of wheels :</td> <td></td> <td></td>	Types of wheels :		
ie-down points for adapted transportN/C75.00unning lightsN/CN/Aunxiliary manual brakes72.00bair72.00back45.00suspension forks130.00bair130.00back119.00front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cfor the wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/Cfront wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/Cfront wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (2 i.)90.00bair90.00cach118.00cach134.00cach134.00cach134.00cach134.00cach134.00cach134.00cach134.00cach95.00bair95.00bair95.00bair95.00bair109.00			
numing lightsN/CN/Aauxiliary manual brakes72.00bair72.00each45.00suspension forks130.00bair130.00each119.00front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cfor twheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.)N/Cor 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.)N/Cor 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.)N/Cor 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.)N/Cor 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.)N/Cor 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.)N/Cor 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.)N/Cor 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.)N/Cor 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.)N/Cor 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.)N/Cor 20.4 cm109.00cach118.00cach118.00cach118.00cach118.00cach114.00front wheel rimsN/Cor 11ess inserts for rear wheelsor 11ess inserts for front wheelsor 11ess inserts for front wheelsor 11ess109.00			
nuxiliary manual brakes72.00bair72.00bach45.00suspension forks130.00bach119.00bront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cbront wheels, inner tube tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)N/Cbront wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)N/Cbront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cbront wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/Cbront wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm (2 ¹ / ₄ in.)90.00brair90.00brair118.00brair118.00brair118.00brair134.00front wheel rimsN/Cbrair95.00brair95.00brair95.00brair95.00brair109.00	tie-down points for adapted transport	N/C	75.00
bair 72.00 Each 45.00 bases bair 130.00 Each 119.00 Front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) N/C 55.00 Front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.) N/C 40.00 Front wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) N/C 75.00 Front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm (2 ³ / ₄ in.) 90.00 Each 85.00 Each 85.00 Each 118.00 Each 118.00 Each 118.00 Each 118.00 Each 118.00 Each 118.00 Each 118.00 Each 134.00 Front wheel rims N/C 43.00 Front wheel rims 118.00 Each 134.00 Front wheel rims 118.00 Each 134.00 Front wheel rims N/C 43.00 Each 134.00 Front wheel rims N/C 134.00 Front wheel rims N/C 134.00 Front wheel rims N/C 134.00 Each 134.00 Front wheel rims N/C 134.00 Front wheel rims N/C 134.00 Each N/C 134.00 Front wheel rims N/C 130.00 Each N	running lights	N/C	N/A
bair 72.00 Each 45.00 bases bair 130.00 Each 119.00 Front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) N/C 55.00 Front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.) N/C 40.00 Front wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) N/C 75.00 Front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm (2 ³ / ₄ in.) 90.00 Each 85.00 Each 85.00 Each 118.00 Each 118.00 Each 118.00 Each 118.00 Each 118.00 Each 118.00 Each 118.00 Each 134.00 Front wheel rims N/C 43.00 Front wheel rims 118.00 Each 134.00 Front wheel rims 118.00 Each 134.00 Front wheel rims N/C 43.00 Each 134.00 Front wheel rims N/C 134.00 Front wheel rims N/C 134.00 Front wheel rims N/C 134.00 Each 134.00 Front wheel rims N/C 134.00 Front wheel rims N/C 134.00 Each N/C 134.00 Front wheel rims N/C 130.00 Each N			
each 45.00 suspension forks130.00pair130.00each119.00front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 4.4 cm (1 ³ / ₄ in.)N/Cor 20.3 cm (8 in.) x 4.4 cm (1 ³ / ₄ in.)N/Cor 20.3 cm (8 in.) x 4.4 cm (1 ³ / ₄ in.)N/Cor 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 4.4 cm (1 ³ / ₄ in.)N/Cor 20.3 cm (8 in.) x 5.6 cm (14 in.) x 7.6 cm (3 in.)N/Cor 20.4 cm90.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)85.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)118.00each134.00cront wheel rimsN/Cstach134.00front wheel rimsN/Cstart95.00ear wheel rims95.00ear wheels inserts for rear wheelsN/Aair95.00ear wheels109.00		72.00	
pair130.00each119.00front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/Cfront wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)N/Cor 20.3 cm (8 in.) x 4.4 cm ($1^3/_4$ in.)N/Cear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/Cfront wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm ($2^3/_4$ in.)90.00pair90.00each85.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)pair118.00rear wheel rims134.00rear wheel rimsN/Csoair95.00airless inserts for rear wheels95.00airless inserts for front wheelsN/A	each		45.00
Participation119.00Front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/C 55.00 Front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)N/C 40.00 or 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.)N/C cm (3 in.)N/C 40.00 rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C 75.00 front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm ($2^{2}/_{4}$ in.) 90.00 85.00 pair90.00 85.00 each118.00 85.00 rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 118.00 34.00 pair118.00 134.00 134.00 pairN/C 50.00 50.00 achN/C 50.00 50.00 achN/C 50.00 50.00 achN/C 50.00 50.00 achN/C 50.00 50.00 ar wheel rims 95.00 N/A airless inserts for rear wheels 95.00 N/A airless inserts for front wheels 109.00 N/A	suspension forks	120.00	
Front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/C55.00Front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)N/C40.00or 20.3 cm (8 in.) x 4.4 cm $(1^3/_4$ in.)N/C cm (3 in.)N/C40.00or a wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C75.00Front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm $(2^3/_4$ in.)90.0085.00each85.0085.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)118.00134.00cach134.00134.00front wheel rimsN/C50.00airless inserts for rear wheels95.00N/Cairless inserts for front wheels95.00N/Aairless inserts for front wheels109.00109.00		130.00	
Front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)N/C 40.00 or 20.3 cm (8 in.) x 4.4 cm (1 ³ / ₄ in.)N 7.6 cm (3 in.)N/C 40.00 or ar wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C 75.00 Front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm (2 ³ / ₄ in.)90.00 85.00 each85.00 85.00 rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) 118.00 134.00 cach134.00 134.00 front wheel rimsN/C 50.00 airless inserts for rear wheels 95.00 N/C airless inserts for front wheels 95.00 N/A airless inserts for front wheels 109.00 N/A			
rear wheels, inner tube tires, $35.6 \text{ cm} (14 \text{ in.}) \times 7.6 \text{ cm} (3 \text{ in.})$ N/C75.00Front wheels, inner tube tires, $22.9 \text{ cm} (9 \text{ in.}) \times 7 \text{ cm} (2^3/_4 \text{ in.})$ 90.0085.00each85.0085.00rear wheels, inner tube tires, $35.6 \text{ cm} (14 \text{ in.}) \times 10.2 \text{ cm} (4 \text{ in.})$ 118.00134.00bair118.00134.00ceachN/C43.00front wheel rimsN/C50.00airless inserts for rear wheels95.00N/Aairless inserts for front wheels109.00109.00	front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)		
Front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm $(2^3/_4$ in.)90.00pair90.00each85.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)118.00pair118.00each134.00front wheel rimsN/Cfor twheel rimsN/Cairless inserts for rear wheels95.00pair95.00eachN/Aairless inserts for front wheels109.00			
beach85.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)118.00bair118.00cach134.00front wheel rimsN/Cfor wheel rimsN/Cbair95.00bair95.00bair95.00bair109.00	rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm $(2^{3}/_{4}$ in.)	N/C	75.00
rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.) pair 118.00 each 134.00 front wheel rims N/C 43.00 rear wheel rims N/C 50.00 airless inserts for rear wheels pair 95.00 each N/A airless inserts for front wheels pair 109.00	pair	90.00	
pair118.00each134.00front wheel rimsN/Cfor wheel rimsN/Cairless inserts for rear wheels50.00pair95.00eachN/Aairless inserts for front wheelsN/Apair109.00			85.00
back134.00Front wheel rimsN/C43.00rear wheel rimsN/C50.00airless inserts for rear wheels95.00eachN/AN/Aairless inserts for front wheels109.00		110.00	
Front wheel rimsN/C43.00rear wheel rimsN/C50.00airless inserts for rear wheels95.00eachN/Aairless inserts for front wheels109.00		118.00	
rear wheel rims N/C 50.00 airless inserts for rear wheels bair 95.00 each N/A airless inserts for front wheels bair 109.00			
airless inserts for rear wheels bair 95.00 N/A airless inserts for front wheels bair 109.00			
pair 95.00 each N/A airless inserts for front wheels pair 109.00		N/C	50.00
pair 95.00 each N/A airless inserts for front wheels pair 109.00	airless inserts for rear wheels		
each N/A hirless inserts for front wheels pair 109.00	pair	95.00	
airless inserts for front wheels Dair 109.00	each		N/A
pair 109.00			
		109.00	
	each	107.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
seat/back structure, reclining back with cylinder*	752.00	752.00
connecting cables for power reclining devices*	161.00	161.00
control system for one power accessory only*	461.00	695.00
control system for two power accessories*	327.00	798.00
control system for two additional accessories*	327.00	798.00
power rocker device, factory installed*	1 300.00	1 550.00
power elevating legrests, with individual control (requires TAC control module)*		
pair	1 435.00	
each	1 100100	3 190.00
TAC control module*	499.00	882.00
DEVICE FROM : ORTHOFAB INC.		
		PRI
POWERED WHEEL CHAIR, "PRIMA ML" MODEL		\$3 875
Basic Component(s)		
Body support system		
• supple seat and back, nylon		
• back heights : 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm	n (18 in.),	
48.3 cm (19 in.)	(10)	
• seat widths : 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm	(18 in.)	
• seat depths : 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm	(18 In.)	
• push handles		
 safety belt, auto-type front seat height : 47.0 cm (18¹/₂ in.); rear seat height : 4 	$12.8 \text{ cm} (17^{1}/\text{ in})$	
• from seat height $.47.0 \text{ cm}(107_2 \text{ m.})$, rear seat height $.4$	$1.0 \text{ cm}(177_4 \text{ m})$	

- modification of front seat height by + or -1.9 cm ($^{3}/_{4}$ in.), and rear seat height ٠ to 42.5 cm $(16^{3}/_{4} \text{ in.})$
- seat/back structure, angle-adjustable back
- · back spreader bar

Armrests

- "U"-type armrests, flip-back, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- straight armrest pads, short, long
- rigid clothing guards

Footrests

- 60° or 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- · padded calfrests, straight
- folding footplates, standard
- heel loops, length-adjustable

Drive system

- · conical-spherical extension
- battery charge display
- battery charger
- battery boxes, group U1
- direction joystick
- push-button switch
- joystick with integrated controller
- motors, 8.3 km/h (5.0 mph)
- swivel side bracket for joystick control
- anti-tip rollers

- · standard forks
- · tie-down points for adapted transport
- reflector strips
- front wheels, inner tube tires, 17.8 cm (7 in.) x 4.4 cm (1³/₄ in.), 20.3 cm (8 in.) x 5.1 cm (2 in.), 15.2 cm (6 in.) x 3.2 cm (1¹/₄ in.)
- rear wheels, inner tube tires, 25.4 cm (10 in.) x 7.6 cm (3 in.)
- rear wheel rims, front wheel rims
- auxiliary frame for motors

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
padded headrest, contoured	100.00	100.00
articulated headrest mounting, uniball	115.00	115.00
articulated headrest mounting	102.00	102.00
seat/back structure with angle-adjustable back	N/C	N/A
back spreader bar	N/C	N/A
supple back, nylon	N/C	64.00
supple back, tension-adjustable	69.00	133.00
rigid seat, flat	116.00	173.00
supple seat, nylon	N/C	57.00
modification of seat width to 48.3 cm (19 in.) or 50.8 cm (20 in.)	101.00	N/A
safety belt, velcro-type	27.00	62.00
safety belt, auto-type	N/C	35.00
safety belt, airplane-type	38.00	73.00
push handles	N/C	N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
modification of front seat height by $+ \text{ or } - 1.9 \text{ cm } (^{3}/_{4} \text{ in.})$		
and rear seat height to 42.5 cm $(16^3/_4 \text{ in.})$	N/C	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests : "U"-type armrests, flip-back, height-adjustable from 20.3 cm (8 in. to 30.5 cm (12 in.), short "U"-type armrests, flip-back, height-adjustable from 20.3 cm (8 in. to 30.5 cm (12 in.), long	N/C	94.00
pair each	52.00	120.00
straight armrest pads, short	N/C	120.00
straight armrest pads, long	N/C	15.00
contoured armrest pads, short pair	44.00	
each		34.00
contoured armrest pads, long pair	48.00	
each	10.00	39.00
modification of height of "U"-type armrests to over 30.5 cm (12 in		
or to under 20.3 cm (8 in.) rigid clothing guards	79.00 N/C	N/A N/A
Footrests : 70° footrests, tapered, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	102.00
60° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 60° or 70° footrests, parallel, detachable, swingaway, length-adjustab	N/C	102.00
from 35.6 cm (14 in.) to 48.3 cm (19 in.) elevating legrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)	29.00	N/A
pair each	166.00	185.00
elevating legrests, compensating mechanism, detachable, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair each	234.00	219.00
modification of footrest length to over 48.3 cm (19 in.)	79.00	NT/ A
or to under 35.6 cm (14 in.) padded calfrests, straight	/9.00 N/C	N/A 20.00
padded calfrests, straight	1000	20.00
pair	60.00	
each	55.00	50.00
double calf strap folding footplates, standard	55.00 N/C	55.00 16.00
folding footplates, aluminum	100	10.00
pair	40.00	
each folding footplates, oversized		36.00
pair	72.00	
each	. =. 30	52.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
footplates, standard size, angle-adjustable and depth-adjustable pair	72.00	52.00
each footplates, oversized, angle-adjustable and depth-adjustable		52.00
pair	78.00	
each	70.00	55.00
full-width footplate	168.00	200.00
heel loops, length-adjustable	N/C	11.00
toe loops		
pair	30.00	
each		15.00
front impact guard with rollers	26.00	
pair	36.00	10.00
each		18.00
Wheels and frame		
Types of drive systems :		
joystick control with integrated controller	N/C	980.00
battery charge display	N/C	N/A
battery charger	N/C	359.00
battery boxes, group U1	N/C	122.00
push-button switch	N/C	N/A
direction joystick	N/C	N/A
stick extension	19.00	27.00
ball extension	19.00	27.00
"T"-type extension	27.00	35.00
mushroom-shaped extension	19.00 N/C	27.00
conical-spherical extension swivel side bracket for joystick control	N/C N/C	8.00 202.00
motors, 8.3 km/h (5.0 mph)	N/C N/C	202.00 N/A
anti-tip rollers	N/C	N/A N/A
and up fonets	ive	10/14
Types of wheels :		
standard forks	N/C	38.00
auxiliary frame for motor	N/C	336.00
eflector strips	N/C	20.00
ie-down points for adapted transport auxiliary manual brakes	N/C	N/A
bair	106.00	
each	100.00	53.00
ear wheels, inner tube tires, 25.4 cm (10 in.) x 7.6 cm (3 in.)	N/C	84.00
Front wheels, inner tube tires, $20.3 \text{ cm} (8 \text{ in.}) \times 5.1 \text{ cm} (2 \text{ in.})$	140	01.00
or 15.2 cm (6 in.) x 3.2 cm $(1^{1}/_{4}$ in.)	N/C	46.00
Front wheels, inner tube tires, 17.8 cm (7 in.) x 4.4 cm $(1^{3}/_{4}$ in.)	N/C	46.00
airless inserts for front wheels	73.00	N/A
airless inserts for rear wheels	138.00	N/A
rear wheel rims	N/C	N/A
front wheel rims	N/C	N/A

DEVICE FROM : ORTHOFAB INC.

POWERED WHEEL CHAIR, "OASIS" MODEL

Basic Component(s)

Body support system

- rigid seat, flat
- back heights : 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.)
- rigid seat, flat
- seat widths : 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depths : 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- push handles
- safety belt, auto-type
- seat height : from $41.9 \text{ cm} (16^{1}/_{2} \text{ in.})$ to 50.8 cm (20 in.)
- adjustable seat bracket
- · centre of gravity adjustment from seat

Armrests

- "T"-type armrest, detachable, height-adjustable from 20.3 cm (8 in.) to 27.9 cm (11 in.), from 27.9 cm (11 in.) to 35.6 cm (14 in.), short
- straight armrest pads, short, long
- rigid clothing guards

Footrests

- 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests, straight
- folding footplates, standard
- heel loops, length-adjustable

Drive system

- programmable joystick control
- conical-spherical extension
- battery charge display
- · battery charger
- battery box, group 22, group 24
- direction joystick
- breath control (requires an interface)
- push-button switch
- PILOT + controller
- motors, 11.5 km/h (6.9 mph)
- side bracket for joystick control, swivel side bracket for joystick control
- · anti-tip rollers

PRICE

\$4 749.00

- · standard forks
- · tie-down points for adapted transport
- reflector strips
- running lights
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- modification of frame length
- · rear wheel rims
- front wheel rims
- rear suspension

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
padded headrest, contoured	100.00	100.00
articulated headrest mounting, uniball	115.00	115.00
articulated headrest mounting	102.00	102.00
adjustable seat bracket	N/C	127.00
seat/back structure with angle-adjustable back	750.00	750.00
reinforcement of seat/back structure	447.00	N/A
rigid back, flat	N/C	55.00
padded back, contoured, nylon	118.00	118.00
padded back, contoured, leatherette	118.00	118.00
padded seat, contoured, nylon	210.00	210.00
padded seat, contoured, leatherette	210.00	210.00
rigid seat, flat	N/C	55.00
rigid seat with plastic webbing	43.00	98.00
supple back, tension-adjustable	78.00	133.00
rigid back, contoured	195.00	250.00
supple back, nylon	9.00	64.00
centre of gravity adjustment from seat	N/C	N/A
modification of back height to 38.1 cm (15 in.), 50.8 cm (20 in.),		
53.3 cm (21 in.) or 55.9 cm (22 in.)	96.00	N/A
modification of seat depth to 38.1 cm (15 in.) or 48.3 cm (19 in.)	264.00	N/A
modification of seat depth to 50.8 cm (20 in.) or 53.3 cm (21 in.) modification of seat width to 48.3 cm (19 in.), 50.8 cm (20 in.),	500.00	N/A
53.3 cm (21 in.) or 55.9 cm (22 in.)	290.00	N/A
modification of seat height by $+ 2.5 \text{ cm} (1 \text{ in.}), + 5.1 \text{ cm} (2 \text{ in.})$		
or + 7.6 cm (3 in.)	285.00	N/A
safety belt, velcro-type	27.00	63.00
safety belt, auto-type	N/C	36.00
safety belt, airplane-type	38.00	74.00
push handles	N/C	N/A
seat cushion, flat, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, 7.6 cm (3 in.)	56.00	56.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests :		
"T"-type armrests, detachable, height-adjustable from 20.3 cm to 27.9 cm (11 in.) or from 27.9 cm (11 in.) to 35.6 cm (14 in.) "T"-type armrests, detachable, height-adjustable from 20.3 cm), short N/C (8 in.)	94.00
to 27.9 cm (11 in.) or from 27.9 cm (11 in.) to 35.6 cm (14 in.) pair), long 52.00	
each "I"-type armrests, height-adjustable from 25.4 cm (10 in.)	52.00	120.00
to 33.0 cm (13 in.), short pair	82.00	
each	82.00	135.00
straight armrest pads, short	N/C	12.00
straight armrest pads, long	N/C	15.00
contoured armrest pads, short	44.00	34.00
contoured armrest pads, long	48.00	39.00
modification of armrest height to under 20.3 cm (8 in.)	79.00	N/A
rigid clothing guards	N/C	N/A
Footrests :		
70° footrests, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	78.00
modification of footrest length to under 35.6 cm (14 in.)		
or to over 48.3 cm (19 in.) for 70° footrests	79.00	N/A
elevating legrests, detachable, swingaway, length-adjustable		
from 27.9 cm (11 in.) to 48.3 cm (19 in.)	214.00	
pair	214.00	195 00
each elevating legrests, compensating mechanism, length-adjustable		185.00
from 30.5 cm (12 in.) to 48.3 cm (19 in.)		
pair	240.00	
each	2.000	198.00
padded calfrests, straight	N/C	20.00
padded calfrests, contoured		
pair	60.00	
each		50.00
double calf strap	55.00	55.00
folding footplates, standard	N/C	36.00
folding footplates, oversized	28.00	
pair each	38.00	55.00
footplates, angle-adjustable and depth-adjustable, standard size	a	55.00
pair	32.00	
each	32.00	52.00
folding footplates, oversized		22.00
pair	32.00	
each		52.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
full-width footplate	171.00	243.00
heel loops, length-adjustable	N/C	11.00
toe loops		
pair	30.00	
each		15.00
front impact guard with rollers		
pair	36.00	
each		18.00
Wheels and frame		
Types of drive systems :		
programmable joystick control	N/C	492.00
compact joystick control	56.00	548.00
battery charge display	N/C	N/A
battery charger	N/C	359.00
battery box, group 22 or group 24	N/C	208.00
proportional chin control	631.00	631.00
non-proportional chin control (requires interface)	421.00	421.00
head control	1 059.00	1 059.00
breath control (requires interface)	N/C	N/A
laptray touch switch control (requires interface)	301.00	301.00
control with separate switches (requires interface) chin control bib	530.00 290.00	530.00 290.00
swivel mounting hardware for breath control	385.00	385.00
swivel mounting hardware for chin control	385.00	385.00
adapted controls interface	1 608.00	2 100.00
head control bracket	385.00	385.00
fixed bracket for separate display module	37.00	37.00
flexible bracket for separate display module	120.00	120.00
push-button switch	N/C	N/A
direction joystick	N/C	N/A
stick extension	19.00	27.00
ball extension	19.00	27.00
"T"-type extension	27.00	35.00
mushroom-shaped extension	19.00	27.00
conical-spherical extension	N/C	8.00
side bracket for joystick control	N/C	39.00
swivel side bracket for joystick control	N/C	202.00
swivel midline bracket for joystick control	85.00	287.00
modification of joystick control : switches and potentiometer	75.00	567.00
PILOT + controller	N/C	1 382.00
motors, 11.5 km/h (6.9 mph)	N/C	N/A
anti-tip rollers	N/C	60.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheel :		
standard forks	N/C	87.00
reflector strips	N/C N/C	20.00
1	N/C N/C	
running lights		N/A
ie-down points for adapted transport	N/C	N/A
nodification of frame length	N/C	N/A
rear suspension	N/C	N/A
ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	85.00
rear wheels, inner tube tires, $35.6 \text{ cm} (14 \text{ in.}) \times 7.6 \text{ cm} (3 \text{ in.})$ front wheels, inner tube tires, $22.9 \text{ cm} (9 \text{ in.}) \times 7 \text{ cm} (2^3/_4 \text{ in.})$	N/C	102.00
pair	89.00	
each		129.00
airless inserts for front wheels, 20.3 cm (8 in.) x 5.1 cm (2 in.)	133.00	N/A
front wheels, puncture-resistant tires, 22.9 cm (9 in.) x 7 cm $(2^{3}/_{4})$ in.		N/A
airless inserts for rear wheels	151.00	N/A
rear wheel rims	N/C	N/A
Front wheel rims	N/C	N/A
Component(s) under Special Consideration		
seat/back structure, reclining back with cylinder*	862.00	862.00
power reclining back, factory-installed*	1 145.00	1 545.00
bower rocker device, 45°, factory installed, including shroud* bower elevating legrests, length-adjustable from 30.5 cm (12 in.) o 48.3 cm (19 in.), with individual controls*	N/C	2 375.00
bair	1 259.00	
each		706.00
oower elevating legrests, length-adjustable from 30.5 cm (12 in.) o 48.3 cm (19 in.), with dual controls*		
pair	1 259.00	
each		706.00
control system for one power accessory only*	250.00	250.00
control system for four power accessories*	740.00	740.00
DEVICE FROM : ORTHOFAB INC.		PRIC
POWERED WHEEL CHAIR, "OASIS A600" MODEL		\$4 749.
Basic Component(s)		
Body support system • supple back, nylon • back heights : 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.)		
rigid seat, flat		

- seat widths : 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depths : 40.6 cm (16 in.), 43.2 cm (17 in.) 45.7 cm (18 in.)
- push handles
- safety belt, auto-type
- seat height : from $41.9 \text{ cm} (16^{1}/_{2} \text{ in.})$ to 50.8 cm (20 in.)
- adjustable seat bracket
- · centre of gravity adjustment from seat

Armrests

- "U"-type armrests, flip-back, height-adjustable from 22.9 cm (9 in.) to 30.5 cm (12 in.), short
- straight armrest pads, short, long
- rigid clothing guards

Footrests

- 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- · padded calfrests
- folding footplates, standard
- heel loops, length-adjustable

Drive system

- programmable joystick control
- conical-spherical extension
- battery charge display
- · battery charger
- battery box, group 22, group 24
- direction joystick
- breath control (requires an interface)
- · push-button switch
- PILOT + controller
- motors, 11.5 km/h (6.9 mph)
- side bracket for joystick control, swivel side bracket for joystick control
- anti-tip rollers

- standard forks
- · tie-down points for adapted transport
- reflector strips
- running lights
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- modification of length of frame
- · front wheel rims
- rear wheel rims
- · rear suspension

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
padded headrest, contoured	100.00	100.00
headrest, hammock-type	75.00	75.00
articulated headrest mounting, uniball	115.00	115.00
articulated headrest mounting	102.00	102.00
adjustable seat bracket	N/C	127.00
A600 seat/back structure with angle-adjustable back	544.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
supple back, nylon	N/C	64.00
supple back, tension-adjustable	69.00	133.00
rigid seat, flat	N/C	81.00
modification of height of non-reclining back to 50.8 cm (20 in.)	96.00	N/A
modification of seat depth to 48.3 cm (19 in.)	264.00	N/A
modification of seat width to 50.8 cm (20 in.)	290.00	N/A
modification of seat height by $+ 2.5 \text{ cm} (1 \text{ in.}), + 5.1 \text{ cm} (2 \text{ in.}),$		
or + 7.6 cm (3 in.)	285.00	N/A
safety belt, velcro-type	27.00	63.00
safety belt, auto-type	N/C	36.00
safety belt, airplane-type	38.00	74.00
push handles	N/C	N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
Armrests : "U"-type armrests, flip-back, height-adjustable from 22.9 cm (9 in. to 30.5 cm (12 in.), short "U"-type armrests, flip-back, height-adjustable from 22.9 cm (9 in. to 30.5 cm (12 in.), long straight armrest pads, short straight armrest pads, long contoured armrest pads, short pair each contoured armrest pads, long pair each rigid clothing guards modification of armrest height to under 22.9 cm (9 in.) or to over 30.5 cm (12 in.)	N/C	94.00 120.00 12.00 15.00 34.00 39.00 N/A N/A
Footrests : 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	102.00
70° footrests, parallel, detachable, swingaway, length-adjustable	20.00	27/1
from 35.6 cm (14 in.) to 48.3 cm (19 in.) elevating legrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)	29.00	N/A
pair each elevating footrests, compensating mechanism, detachable, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)	165.00	185.00
pair each	234.00	219.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
modification of legrest length to under 35.6 cm (14 in.)		
or to over 48.3 cm (19 in.)	79.00	N/A
padded calfrests	N/C	20.00
contoured calfrests		
pair	60.00	
each		50.00
double calf strap	55.00	55.00
folding footplates, standard	N/C	16.00
folding footplates, aluminum		
pair	41.00	
each		36.00
folding footplates, standard size, angle-adjustable and depth-adj		
pair	72.00	
each		52.00
folding footplates, oversized, angle adjustable and depth-adjus		
pair	79.00	
each		55.00
full-width footplate, angle-adjustable	168.00	200.00
heel loops, length-adjustable	N/C	11.00
toe loops	20.00	
pair	30.00	15.00
each		15.00
front impact guard with rollers	26.00	
pair	36.00	10.00
each		18.00
Wheels and frame		
Types of drive systems :		
programmable joystick control	N/C	492.00
compact joystick control	56.00	548.00
battery charge display	N/C	N/A
battery charger	N/C	359.00
battery box, group 22 or group 24	N/C	208.00
proportional chin control	631.00	631.00
non-proportional chin control (requires interface)	421.00	421.00
head control	1 059.00	1 059.00
breath control (requires interface)	N/C	N/A
laptray touch switch control (requires interface)	301.00	301.00
control with separate switches (requires interface)	530.00	530.00
adapted controls interface	1 608.00	2 100.00
chin control bib	290.00	290.00
swivel mounting hardware for breath control	385.00	385.00
swivel mounting hardware for chin control	385.00	385.00
head control bracket	385.00	385.00
bracket for separate display module	37.00	37.00
flexible bracket for separate display module	120.00	120.00
push-button switch	N/C	N/A

l. 135, No. 22

Part 2

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
lirection joystick	N/C	N/A
stick extension	19.00	27.00
ball extension	19.00	27.00
"T"-type extension	27.00	35.00
mushroom-shaped extension	19.00	27.00
conical-spherical extension	N/C	8.00
side bracket for joystick control	N/C	39.00
swivel side bracket for joystick control	N/C	202.00
swivel midline bracket for joystick control	85.00	287.00
modification of joystick control : switches and potentiometer	75.00	567.00
PILOT + controller	N/C	1 382.00
motors, 11.5 km/h (6.9 mph)	N/C	N/A
anti-tip rollers	N/C	60.00
Types of wheels :		
standard forks	N/C	87.00
reflector strips	N/C	20.00
running lights	N/C	N/A
tie-down points for adapted transport	N/C	N/A
modification of frame length	N/C	N/A
rear suspension	N/C	N/A
front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	85.00
rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm $(2^{3}/_{4}$ in.)	N/C	102.00
pair	89.00	
each	0,100	129.00
airless inserts for front wheels	133.00	N/A
airless inserts for rear wheels	151.00	N/A
airless inserts for 22.9 cm (9 in.) x 7.0 cm $(2^3/_4 \text{ in.})$ wheels	224.00	N/A
rear wheel rims	22 1.00 N/C	N/A
front wheel rims	N/C	N/A
Component(s) under Special Consideration		
A600 seat/back structure, reclining back with cylinder with a height of 45.7 cm (18 in.), 50.8 cm (20 in.), 55.9 cm (22 in.	.),	
61.0 cm (24 in.) or 66.0 cm (26 in.)*	699.00	699.00
power rocker device, 45°, factory-installed, including shroud*	N/C	2 375.00
control system for one power accessory only*	250.00	250.00
control system for four power accessories*	740.00	740.00

DEVICE FROM : SUNRISE MEDICAL CANADA INC.

POWERED WHEEL CHAIR, "QUICKIE S-525" MODEL

Basic Component(s)

Body support system

- supple seat and back, nylon
- seat/back structure, back : angle-adjustable from 86° to 102°
- suspension built into seat
- seat width : from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth : from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat height : from 45.7 cm (18 in.) to 53.3 cm (21 in.)
- back height : from 38.1 cm (15 in.) to 50.8 cm (20 in.)
- · push handles
- back spreader bar
- safety belt, auto-type, velcro-type

Armrests

- "T"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 30.5 cm (12 in.), short, long
- straight armrest pads, short, long
- padded armrest pads, short, long

Footrests

- 70° footrests, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 54.6 cm (21¹/₂ in.)
- 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- folding footplates, standard
- heel loops, length-adjustable
- contoured calfrests

Drive system

- programmable joystick control
- battery charge display
- · battery charger
- battery box, group 22
- toggle switch
- programmable controller
- motor, 11 km/h (6.5 mph), for standard base
- side bracket for joystick control, swivel side bracket for joystick control
- · anti-tip rollers

Wheels and frame

- · standard forks
- rear wheels, inner tube tires, 30.5 cm (12 in.) x 7.6 cm (3 in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- · tie-down points for adapted transport
- reflector strips
- rear wheel rims, front wheel rims

PRICE

\$4 885.00

Basic and Optional Component(s) Body support system	
Body support system	
Seat and back :	
headrest, small 90.00	93.00
	103.00
	107.00
	68.00
	207.00
	177.00
folding back 117.00	N/A
suspension built into seat N/C	N/A
	374.00
	462.00
I ····································	409.00
\mathbf{I}	189.00
	43.00
	137.50
	345.00
	299.00
modification of seat width to $48.3 \text{ cm} (19 \text{ in.})$ or to $50.8 \text{ cm} (20 \text{ in.})$ 288.00	N/A
modification of seat depth to 48.3 cm (19 in.) or to 50.8 cm (20 in.) 194.00 supple back, nylon N/C	N/A 69.00
supple back, nylonN/Csupple seat, nylonN/C	52.50
push handles N/C	52.50 N/A
push handles with 8° angle 22.00	N/A N/A
back spreader bar N/C	N/A N/A
seat cushion, flat, foam, 5.1 cm (2 in.) 56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.) 56.00	56.00
safety belt, auto-type N/C	41.00
safety belt, velcro-type N/C	28.00
	28.00
Armrests :	
"T"-type armrests, detachable, height-adjustable	
	132.00
"U"-type armrests, detachable, flip-back, height-adjustable	
from 24.1 cm ($9^{1}/_{2}$ in.) to 35.6 cm (14 in.), short or long	
pair 88.00	
	176.00
straight armrest pads, short N/C	15.00
straight armrest pads, long N/C	17.00
contoured armrest pads, short or long N/C	25.00
modification of "T"-type armrests from 15.2 cm (6 in.)	NT/A
to 24.8 cm $(9^{3}/_{4} in.)$ 80.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests :		
70° footrests, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 54.6 cm ($21^{1}/_{2}$ in.)	N/C	136.00
90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) 70° footrests, parallel, detachable, swingaway, heavy-duty,	N/C	136.00
length-adjustable from 29.2 cm $(11^{1}/_{2} \text{ in.})$ to 54.6 cm $(21^{1}/_{2} \text{ in.})$ modification of length of 90° footrests by 5.1 cm (2 in.) or by 10.2 cm (4 in.)	40.00	N/A
pair	30.00	
each		15.00
elevating legrests, detachable, swingaway	172.00	
pair each	172.00	222.00
padded calfrests	N/C	18.00
contoured calfrests		
pair	70.00	
each		53.00
ingle calf strap	18.00	18.00
louble calf strap	32.00	32.00
olding footplates, standard	N/C	48.00
folding footplates, oversized	71.00	
bair each	71.00	83.50
olding footplates, angle-adjustable and depth-adjustable, standar	d sizo	85.50
bair	51.00	
each	51.00	73.50
neel loops, length-adjustable	N/C	10.00
	100	10.00
Wheels and frame		
Types of drive systems :		
programmable joystick control	N/C	612.00
attery charge display	N/C	N/A
attery charger	N/C	373.00
attery box, group 22	N/C	117.00
roportional chin control (requires interface)	540.00	540.00
reath control (requires interface)	414.00	414.00
ead control (requires interface)	540.00	540.00
aptray touch switch control (requires interface)	305.00	305.00
ontrol with 5 separate switches (requires interface) dapted controls interface with integrated display module	583.00	583.00 1 403.00
uxiliary switch	$\begin{array}{r}1\ 403.00\\88.00\end{array}$	1 403.00 93.00
nodification of joystick control for auxiliary switch	117.00	93.00 729.00
oggle switch	N/C	729.00 N/A
bush-button switch	85.00	N/A N/A
		50.00
ball extension	50.00	יווור

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
stick extension	20.00	20.00
swivel side bracket for joystick control	N/C	183.00
swivel midline bracket for joystick control	158.00	341.00
side bracket for joystick control	N/C	72.00
preath control bracket	342.00	342.00
chin control bracket	342.00	342.00
nead control bracket	342.00	342.00
programmable controller	N/C	1 411.00
notors, 11 km/h (6.5 mph), for standard base	N/C N/C	950.00
	124.00	
heavy-duty frame or robust base	124.00	N/A
heavy-duty motors for persons over 250 lb.	76.00	
pair	/6.00	015.00
each		915.00
anti-tip rollers	N/C	N/A
centre of gravity adjustment	65.00	N/A
Types of wheels :		
standard forks	N/C	60.00
eflector strips	N/C	N/A
ie-down points for adapted transport	N/C	69.00
Front impact guard with rollers		
bair	36.00	
each		18.00
Front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
pair	22.00	
each	22.00	66.00
rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 in	.) N/C	55.00
rear wheels, inner tube tires, $30.5 \text{ cm} (12 \text{ in.}) \times 7.6 \text{ cm} (3 \text{ in.})$	N/C	141.00
Front wheel rims	N/C N/C	39.00
ear wheel rims	N/C N/C	127.00
airless inserts for rear wheels	132.00	N/A
airless inserts for front wheels	111.00	N/A N/A
	111.00	IN/A
auxiliary brakes, manual	51.00	
pair	51.00	10.00
each		42.00
wheel lock extensions	26.00	
pair	36.00	
each		18.00
Component(s) under Special Consideration		
control system for several power accessories (number : 8)*	599.00	599.00
connecting cables for power accessories, four plugs*	47.00	47.00

DEVICE FROM : SUNRISE MEDICAL CANADA INC.

POWERED WHEEL CHAIR, "QUICKIE S-646 SE" MODEL

Basic Component(s)

Body support system

- supple back, nylon
- rigid seat, flat
- seat/back structure, back : angle-adjustable from 84° to 124°
- · centre of gravity adjustment from seat
- seat width : from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth : from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat height : from 45.7 cm (18 in.) to 59.7 cm $(23^{1}/_{2} \text{ in.})$
- back height : from 38.1 cm (15 in.) to 50.8 cm (20 in.)
- push handles
- back spreader bar
- safety belt, auto-type, velcro-type
- · parallel seat rails

Armrests

- "T"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 30.5 cm (12 in.), short, long
- straight armrest pads, short, long
- · contoured armrest pads, short, long

Footrests

- 70° footrests, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 54.6 cm (21¹/₂ in.)
- 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- · padded calfrests
- folding footplates, standard
- heel loops, length-adjustable

Drive system

- programmable joystick control
- battery charge display
- battery charger
- battery box, group 22, group 24
- toggle switch
- programmable controller
- motors, 14.1 km/h (8.5 mph), for standard base
- · side bracket for joystick control, swivel side bracket for joystick control

Wheels and frame

- standard forks
- rear suspension
- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- tie-down points for adapted transport
- · reflector strips
- running lights
- · rear wheel rims, front wheel rims

PRICE

\$5 365.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
headrest, small	90.00	93.00
headrest, medium	96.00	103.00
headrest, large	102.00	107.00
articulated headrest mounting	154.00	168.00
seat/back structure, back : angle-adjustable from 84° to 124°	N/C	N/A
parallel seat rails	N/C	30.00
tapered seat rails		
pair	70.00	
each		65.00
padded back, contoured, fabric	305.00	374.00
padded back, contoured, leatherette	340.00	400.00
padded back, contoured, leathered, with rigid base	420.00	489.00
padded back, contoured, fabric, with rigid base	393.00	462.00
padded back, contoured, fabric, height of 53.3 cm (21 in.)		
to 61.0 cm (24 in.)	349.00	418.00
padded back, contoured, fabric, with rigid base,		
height of 53.3 cm (21 in.) to 61.0 cm (24 in.)	452.00	521.00
padded back, contoured, leatherette, height of 53.3 cm (21 in.)		
to 61.0 cm (24 in.)	380.00	449.00
padded back, contoured, leatherette, with rigid base,		
height of 53.3 cm (21 in.) to 61.0 cm (24 in.)	476.00	545.00
supple back, tension-adjustable	74.00	143.00
padded seat, contoured, fabric	247.00	299.00
padded seat, contoured, leatherette	322.00	345.00
modification of seat width to 48.3 cm (19 in.), 50.8 cm (20 in.),	022100	0.000
55.9 cm (22 in.) or 61.0 cm (24 in.)	389.00	N/A
modification of seat depth to 48.3 cm (19 in.), 50.8 cm (20 in.),		
53.3 cm (21 in.) or 55.9 cm (22 in.)	257.00	N/A
modification of back height from 53.3 cm (21 in.) to 61.0 cm (24 in		N/A
modification of seat height to 43.8 cm $(17^{1}/_{4} \text{ in.})$	284.00	N/A
supple back, nylon	N/C	69.00
rigid seat, flat	N/C	136.50
push handles	N/C	N/A
back spreader bar	N/C	N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, auto-type	N/C	41.00
safety belt, velcro-type	N/C N/C	28.00
centre of gravity adjustment from seat	N/C N/C	28.00 N/A
contro of gravity augustinent from seat	INC.	

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests :		
"T"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 30.5 cm (12 in.), short or long "U"-type armrests, detachable, flip-back, height-adjustable	N/C	132.00
from 24.1 cm (9 ¹ / ₂ in.) to 35.6 cm (14 in.), short or long pair	88.00	
each	88.00	176.00
straight armrest pads, short	N/C	15.00
straight armrest pads, long	N/C	17.00
contoured armrest pads, short or long	N/C	25.00
modification of the height of "T"-type armrests from 15.2 cm (6)	in.)	
to 24.8 cm $(9^{3}/_{4} \text{ in.})$	80.00	N/A
Footrests :		
70° footrests, detachable, swingaway, length-adjustable		
from 27.9 cm (11 in.) to 54.6 cm $(21^{1}/_{2} in.)$	N/C	136.00
90° footrests, detachable, swingaway, length-adjustable		
from 20.3 cm (8 in.) to 33.0 cm (13 in.)	N/C	136.00
70° footrests, heavy-duty, detachable, swingaway, length-adjustal		
from 29.2 cm (11 ¹ / ₂ in.) to 54.6 cm (21 ¹ / ₂ in.)	40.00	N/A
elevating legrests		
pair	172.00	222.00
each	NIC	222.00
padded calfrests	N/C	18.00
contoured calfrests	70.00	
pair each	70.00	53.00
single calf strap	18.00	18.00
double calf strap	32.00	32.00
folding footplates, standard	32.00 N/C	48.00
folding footplates, oversized	1000	40.00
pair	71.00	
each	/ 1000	83.50
folding footplates, angle-adjustable		
pair	51.00	
each		73.50
heel loops, length-adjustable	N/C	10.00
front impact guard with rollers		
poir	36.00	
pair each	50.00	18.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems :		
programmable joystick control	N/C	612.00
battery charge display	N/C	N/A
battery charger	N/C	373.00
battery box, group 22, group 24	N/C	N/A
proportional chin control (requires interface)	540.00	540.00
head control (requires interface)	540.00	540.00
laptray touch switch control (requires interface)	305.00	305.00
control with 5 separate switches (requires interface)	583.00	583.00
breath control (requires interface)	414.00	414.00
adapted controls interface with integrated display module	1 403.00	1 403.00
auxiliary switch	88.00	93.00
modification of joystick control for auxiliary switch	117.00	729.00
toggle switch	N/C	N/A
push-button switch	85.00	N/A
ball extension	50.00	50.00
"T"-type extension	50.00	50.00
stick extension	20.00	20.00
swivel side bracket for joystick control	N/C	183.00
swivel midline bracket for joystick control	158.00	341.00
side bracket for joystick control	N/C	72.00
breath control bracket	342.00	342.00
chin control bracket	342.00	342.00
head control bracket	342.00	342.00
programmable controller	N/C	1 540.00
motors, 14.1 km/h (8.5 mph), for standard base	N/C	1 090.00
high-torque transmission (heavy-duty)	273.00	N/A
Types of wheels :		
standard forks	N/C	84.00
reflector strips	N/C	N/A
running lights	N/C	N/A
tie-down points for adapted transport	N/C	66.00
rear suspension	N/C	N/A
suspension forks, up to 68 kg (150 lb.)	100.00	N/A
suspension forks, up to 114 kg (250 lb.)	116.00	N/A
suspension forks, up to 182 kg (400 lb.)	131.00	N/A
front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	66.00
front wheels, solid tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) front wheels, solid tires, 22.9 cm (9 in.) x 7.6 cm (3 in.)	N/C	61.00
pair	67.00	
each		94.50
front wheels, inner tube tires, 22.9 cm (9 in.) x 7.6 cm (3 in.)		
pair	67.00	
each		94.50

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) front wheel rims rear wheel rims	N/C N/C N/C	209.00 39.00 46.00
airless inserts for rear wheels manual auxiliary brakes	132.00	N/A
pair each wheel lock extensions	51.00 36.00	42.00 18.00
Component(s) under Special Consideration	50.00	10.00
control system for several power accessories (number : 8)* connecting cables for power accessories, four plugs* connecting cables for power accessories, one plug*	599.00 47.00 47.00	599.00 47.00 47.00
DEVICE FROM : PRIDE MOBILITY PRODUCTS CORP.		PRIC
POWERED WHEEL CHAIR, "BLAST" MODEL		\$5 723.0
Basic Component(s)		
 Body support system seat/back structure with angle-adjustable back seat widths : from 25.4 cm (10 in.) to 55.9 cm (22 in.), 61.0 cm seat depths : from 25.4 cm (10 in.) to 50.8 cm (20 in.), 61.0 cm seat height : from 45.7 cm (18 in.) to 50.8 cm (20 in.) back height : from 35.6 cm (14 in.) to 61.0 cm (24 in.) rigid seat, flat supple back, nylon push handles push bar safety belt, auto-type, velcro-type angle-adjustable back centre of gravity adjustment from seat 		
 Armrests "T"-type armrests, detachable, height-adjustable from 22.9 cm to 38.1 cm (15 in.), short, long, with clothing guards "I"-type armrests, short, long straight armrest pads, short, long contoured armrest pads, short, long rigid clothing guards for "T"-type armrests 	n (9 in.)	
 Footrests 60° or 70° footrests, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.) padded calfrests folding footplates, standard size, angle-adjustable folding footplates, oversigned angle adjustable 		

- folding footplates, oversized, angle-adjustable
- heel loops, length-adjustable
- heel loops, fixed

Drive system

- programmable joystick control with control system for 5 power accessories
- battery charge display
- stick extension
- onboard battery charger
- battery box, group 24
- programmable controler
- Reliance 702 HS motors, 14.1 km/h (8.5 mph)
- heavy-duty motors, 11.6 km/h (7 mph)
- side bracket for joystick control, swivel side bracket for joystick control
- anti-tip rollers

- standard forks
- rear suspension
- rear wheels, inner tube tires, 35.6 cm (14 in.)
- front wheels, inner tube tires, 22.9 cm (9 in.)
- tie-down points for adapted transport
- reflector strips
- rear wheel rims, front wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
padded headrest, contoured, small	60.00	170.00
padded headrest, contoured, large	60.00	170.00
articulated headrest mounting, uniball	100.00	290.00
seat/back structure with angle-adjustable back	N/C	550.00
angle-adjustable back	N/C	160.00
padded back, contoured, fabric or leatherette	280.00	340.00
padded back, contoured, fabric, with rigid base	280.00	340.00
padded back, contoured, fabric, with rigid base	390.00	470.00
padded seat, contoured, fabric	200.00	200.00
supple back, nylon	N/C	80.00
rigid seat, flat	N/C	40.00
push handles	N/C	40.00
push bar	N/C	85.00
safety belt, auto-type	N/C	26.00
safety belt, velcro-type	N/C	26.00
safety belt, airplane-type	24.00	50.00
centre of gravity adjustment from seat	N/C	N/A

Armrests :N/C80.00"T"-type armrests, short or longN/C80.00"T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.)N/C190.00to 38.1 cm (15 in.), short or long, with clothing guardsN/C190.00"U"-type armrests, detachable, flip-back, height-adjustable190.00290.00rom 22.9 cm (9 in.) to 38.1 cm (15 in.), short or long200.00290.00each290.00290.00200.00each10.0000290.00straight armrest pads, short or longN/C10.00supple clothing guards for "U"-type armrests60.00290.00each15.00200.00200.00each15.00200.00200.00each15.00200.00200.00each15.00200.00200.00each15.00200.00200.00each15.00200.00200.00rigid clothing guards for "U"-type armrestsN/C5.00Footrests :0° or 70° footrests, detachable, swingaway, length-adjustable70.00for 70.° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.)N/C70.00pair200.00200.00200.00each170.00200.00200.00each200.00200.00200.00each170.00200.00200.00each170.00200.00200.00each12.0012.00200.00each170.0012.00200		Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
$\begin{tabular}{ c c c c c } $$ "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 38.1 cm (15 in.), short or long, with clothing guards N/C 190.00 $$ "U"-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 38.1 cm (15 in.), short or long 200.00 $$ acch 290.00 $$ acch 290.00 $$ acch 290.00 $$ contoured armrest pads, short or long N/C 10.00 $$ contoured armrest pads, short or long N/C 10.00 $$ acch 60.00 $$ arms the adjustable from 21.9 cm (10 thing guards for "U"-type armrests $$ acch 10.00 $$ acch 15.00 $$ acch 170.00 $$ acc$			
to 38.1 cm (15 in.), short or long, with clothing guards N/C 190.00 "U"-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 38.1 cm (15 in.), short or long pair 200.00 each 290.00 straight armrest pads, short or long N/C 10.00 contoured armrest pads, short or long N/C 10.00 supple clothing guards for "U"-type armrests pair 60.00 each 60.00 each 15.00 rigid clothing guards for "U"-type armrests 15.00 rigid clothing guards for "T"-type armrests N/C 5.00 Footrests : 60° or 70° footrests, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.) N/C 70.00 70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.) pair 200.00 each 170.00 each 170.00 each 170.00 each 170.00 each 170.00 each 170.00 each 170.00	"I"-type armrests, short or long		80.00
pair200.00each290.00straight armrest pads, short or longN/Ccontoured armrest pads, short or longN/Csupple clothing guards for "U"-type armrestspair60.00each60.00rigid clothing guards for "U"-type armrestspair15.00each15.00rigid clothing guards for "T"-type armrestspair15.00each15.00rigid clothing guards for "T"-type armrestspair15.00each15.00rigid clothing guards for "T"-type armrestsN/C5.005.00Footrests : 60° or 70° footrests, detachable, swingaway, length-adjustablefrom 27.9 cm (11 in.) to 50.8 cm (20 in.)N/C70.0070.00pair200.00each170.00each170.00each170.00	to 38.1 cm (15 in.), short or long, with clothing guards "U"-type armrests, detachable, flip-back, height-adjustable		190.00
each290.00straight armrest pads, short or longN/C10.00contoured armrest pads, short or longN/C10.00supple clothing guards for "U"-type armrests 60.00 each 60.00 rigid clothing guards for "U"-type armrests 60.00 pair 60.00 each 15.00 each 15.00 rigid clothing guards for "T"-type armrests N/C pair 5.00 Footrests : 60° or 70° footrests, detachable, swingaway, length-adjustablefrom 27.9 cm (11 in.) to 50.8 cm (20 in.) N/C 70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.) 170.00 each 170.00 each 170.00 each 170.00 pair 200.00 each 170.00 each 170.00		200.00	
contoured armrest pads, short or longN/C10.00supple clothing guards for "U"-type armrests 60.00 each 60.00 rigid clothing guards for "U"-type armrests 15.00 pair 15.00 each 15.00 each 15.00 rigid clothing guards for "T"-type armrests N/C Footrests : 0° or 70° footrests, detachable, swingaway, length-adjustablefrom 27.9 cm (11 in.) to 50.8 cm (20 in.) N/C 70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.)to 50.8 cm (20 in.) 170.00 pair 200.00 each 170.00 pair 200.00 each 170.00 pair 200.00 each 170.00	each		
supple clothing guards for "U"-type armrests pair 60.00 each 60.00 rigid clothing guards for "U"-type armrests pair 15.00 each 15.00 rigid clothing guards for "T"-type armrests N/C 5.00 Footrests : 60° or 70° footrests, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.) N/C 70.00 70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.) N/C 70.00 70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.) 170.00 each 170.00 each 170.00 padded calfrests N/C 12.00			
pair 60.00 each 60.00 rigid clothing guards for "U"-type armrests 15.00 pair 15.00 each 15.00 rigid clothing guards for "T"-type armrests N/C Footrests : 60° or 70° footrests, detachable, swingaway, length-adjustablefrom 27.9 cm (11 in.) to 50.8 cm (20 in.) N/C 70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.) N/C to 50.8 cm (20 in.) 170.00 pair 200.00 each 170.00 pair 200.00 each 170.00 pair 200.00 each 170.00 pair 200.00 each 170.00		N/C	10.00
each 60.00 rigid clothing guards for "U"-type armrests 15.00 pair 15.00 each 15.00 rigid clothing guards for "T"-type armrests N/C Footrests : 60° or 70° footrests, detachable, swingaway, length-adjustablefrom 27.9 cm (11 in.) to 50.8 cm (20 in.) N/C 70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.) N/C to 50.8 cm (20 in.) 200.00 each 170.00 each 170.00 pair 200.00 each 170.00 pair 200.00 each 170.00 pair 200.00 each 170.00		(0.00	
rigid clothing guards for "U"-type armrestspair15.00each15.00rigid clothing guards for "T"-type armrestsN/C5.00Footrests : 60° or 70° footrests, detachable, swingaway, length-adjustablefrom 27.9 cm (11 in.) to 50.8 cm (20 in.)N/C 70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.)To 50.8 cm (20 in.)to 50.8 cm (20 in.)200.00pair200.00each170.00elevating legrests170.00pair200.00each170.00pair200.00		60.00	60.00
pair15.00each15.00rigid clothing guards for "T"-type armrestsN/C5.00Footrests : 60° or 70° footrests, detachable, swingaway, length-adjustablefrom 27.9 cm (11 in.) to 50.8 cm (20 in.)N/C 70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.)70.00to 50.8 cm (20 in.)200.00each170.00elevating legrests170.00pair200.00each170.00paided calfrestsN/C			00.00
each15.00rigid clothing guards for "T"-type armrestsN/C 5.00 Footrests : 60° or 70° footrests, detachable, swingaway, length-adjustablefrom 27.9 cm (11 in.) to 50.8 cm (20 in.)N/C 70.00 70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.) $1000000000000000000000000000000000000$		15.00	
rigid clothing guards for "T"-type armrests N/C 5.00 Footrests : 60° or 70° footrests, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.) N/C 70.00 70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.) pair 200.00 each 170.00 elevating legrests pair 200.00 each 170.00 padded calfrests N/C 12.00		12.00	15.00
Footrests : 60° or 70° footrests, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.) N/C 70.00 70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.) V/C 70.00 pair 200.00 200.00 each 170.00 pair 200.00 each 170.00 paided calfrests N/C		N/C	
$\begin{array}{cccc} 60^{\circ} \mbox{ or } 70^{\circ} \mbox{ footrests, detachable, swingaway, length-adjustable} \\ from 27.9 \mbox{ cm (11 in.) to } 50.8 \mbox{ cm (20 in.)} & N/C & 70.00 \\ 70^{\circ} \mbox{ footrests, heavy-duty, length-adjustable from } 27.9 \mbox{ cm (11 in.)} \\ to 50.8 \mbox{ cm (20 in.)} & 200.00 \\ each & 170.00 \\ elevating legrests & 200.00 \\ each & 170.00 \\ padded \mbox{ calfrests } & N/C & 12.00 \end{array}$			
from 27.9 cm (11 in.) to 50.8 cm (20 in.)N/C70.0070° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.)100100to 50.8 cm (20 in.)200.00170.00each170.001200elevating legrests170.00pair200.0012.00			
70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.) pair 200.00 each 170.00 elevating legrests pair 200.00 each 170.00 paided calfrests N/C			70.00
to 50.8 cm (20 in.) pair 200.00 each 170.00 elevating legrests pair 200.00 each 170.00 padded calfrests N/C 12.00			70.00
pair200.00each170.00elevating legrests200.00each170.00padded calfrestsN/C12.00		.)	
each170.00elevating legrests200.00each170.00padded calfrestsN/C12.00		200.00	
elevating legrests pair 200.00 each 170.00 padded calfrests N/C 12.00		200.00	170.00
pair 200.00 each 170.00 padded calfrests N/C 12.00			1,000
padded calfrests N/C 12.00		200.00	
single calf strap 45.00 45.00			
1 11 16 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
double calf strap45.0045.00folding for tabletN(C)70.00			
folding footplates, oversized, angle-adjustableN/C70.00folding footplates, standard size, angle-adjustableN/C70.00			
heel loops, length-adjustable N/C 10.00			
heel loops, fixed N/C 7.00			
Wheels and frame	*		
Types of drive systems :			
programmable joystick with control system for 5 power accessories N/C 725.00			
battery charge display N/C N/A			
onboard battery charger N/C 185.00			
battery box, group 24N/C66.00proportional chin control735.00735.00			
proportional chin control735.00735.00non-proportional chin control (requires interface)805.00805.00			
laptray touch switch control (requires display) 420.00 420.00			
control with separate switches (must use joystick control with inputs) 90.00 90.00			
foot control (requires interface) 1 130.00 1 130.00			
adapted controls interface or non-proportional controls interface 860.00 860.00			
stick extension N/C 10.00	stick extension		10.00
ball extension 30.00 40.00	ball extension	30.00	40.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
"T"-type extension	60.00	70.00
mushroom-shaped extension	40.00	50.00
conical-spherical extension	40.00	50.00
swivel side bracket for joystick control	N/C	160.00
side bracket for joystick control	N/C	12.00
bracket for separate display module	90.00	90.00
chin bib control	375.00	375.00
external charger, 8A	135.00	320.00
programmable controller	N/C	850.00
Reliance 702 HS motors, 14.1 km/h (8.5 mph)	N/C	850.00
heavy-duty motors, 11.6 km/h (7 mph)	N/C N/C	760.00
	N/C N/C	12.00
anti-tip rollers		
heavy-duty base	470.00	N/A
Types of wheels :		
standard forks	N/C	65.00
reflector strips	N/C	N/A
tie-down points for adapted transport	N/C	25.00
rear suspension	N/C	N/A
front wheels, inner tube tires, 22.9 cm (9 in.)	N/C	30.00
rear wheels, inner tube tires, 35.6 cm (14 in.)	N/C	80.00
front wheel rims	N/C	30.00
rear wheel rims	N/C	30.00
airless inserts for rear wheels	120.00	N/A
airless inserts for front wheels	120.00	N/A
Component(s) under Special Consideration		
seat/back structure, reclining back with cylinder*	400.00	950.00
DEVICE FROM : INVACARE CANADA INC.		PRIC
POWERED WHEEL CHAIR, "STORM PEDIATRIC" MODE	L	\$4 706.
Basic Component(s)		
Body support system		
• supple back, leatherette, nylon		
• back height : from 30.5 cm (12 in.) to 48.3 cm (19 in.)		
• rigid seat, flat		
• seat width : from 30.5 cm (12 in.) to 40.6 cm (16 in.)		
• seat depths : 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 cm (14 in.),		
38.1 cm (15 in.), 40.6 cm (16 in.)		
• seat heights : 44.5 cm $(17^{1}/_{2} \text{ in.})$, 50.2 cm $(19^{3}/_{4} \text{ in.})$		
• push handles		
• push bar		
• safety belt, auto-type		
• centre of gravity adjustment from seat		

• centre of gravity adjustment from seat

Armrests

- "U"-type armrests, detachable, flip-back, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short, long
- "U"-type armrests, fixed height, short, long
- straight armrest pads, short, long
- · contoured armrest pads, short, long
- rigid clothing guards built-into armrests

Footrests

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 44.5 cm (17¹/₂ in.), or 70° footrests, parallel, detachable, swingaway, length-adjustable from 29.8 cm (11³/₄ in.) to 43.2 cm (17 in.)
- 90° footrests, parallel, detachable, swingaway, length-adjustable from 12.7 cm (5 in.) to 20.3 cm (8 in.)
- 60° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 24.1 cm (9¹/₂ in.) to 36.8 cm (14¹/₂ in.), or 70° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 11.4 cm (4¹/₂ in) to 25.4 cm (10 in.)
- 70° footrests, tapered, detachable, swingaway, length-adjustable from 33.7 cm (13¹/₄ in.) to 43.8 cm (17¹/₄ in.)
- padded calfrests
- folding footplates, standard
- heel loops, non-adjustable
- heel loops, length-adjustable

Drive system

- programmable joystick control
- battery charge display
- battery charger
- battery boxes, group 22, group 24
- toggle switch
- direction joystick
- controller
- 4-brush motors with gears
- G/B motors with gears
- side bracket for joystick control, swivel side bracket for joystick control, midline bracket for joystick control
- anti-tip rollers

- reflector strips
- rear suspension
- standard forks
- running lights
- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.), 20.3 cm (8 in.) x 4.4 cm (1³/₄ in.)
- · tie-down points for adapted transport
- front wheel rims
- rear wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :	00.00	
padded headrest, flat	80.00	80.00
headrest, small	106.00	106.00
headrest, large	106.00	106.00
combined headrest/neckrest	106.00	106.00
fixed headrest mounting	53.00	53.00
articulated headrest mounting	122.00	122.00 566.00
seat/back structure with angle-adjustable back	566.00 299.00	299.00
padded back, contoured, fabric	399.00	399.00
padded back, contoured, leatherette padded seat, contoured, fabric	241.00	241.00
padded seat, contoured, leatherette	341.00	341.00
rigid seat, flat	N/C	75.00
centre of gravity adjustment from seat	N/C N/C	N/A
supple back, leatherette or nylon	N/C	58.00
push handles	N/C	40.00
push bar	N/C	58.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, auto-type	N/C	50.00
Armrests :		
"U"-type armrests, detachable, flip-back, height-adjustable		
from 20.3 cm (8 in.) to 30.5 cm (12 in.), short or long	N/C	115.00
"U"-type armrests, fixed height, short or long	N/C	96.00
modification of armrest height by -2.5 cm (1 in.)	179.00	N/A
straight armrest pads, short or long	N/C	26.00
contoured armrest pads, short or long	N/C	26.00
rigid clothing guards built into armrests	N/C	N/A
Footrests : 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13 ¹ / ₂ in.) to 44.5 cm (17 ¹ / ₂ in.), or 70° footrests, parallel, detachable, swingaway, length-adjustable from 29.8 cm (11 ³ / ₄ in.) to 43.2 cm (17 in.) 60° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 24.1 cm (9 ¹ / ₂ in.) to 36.8 cm (14 ¹ / ₂ in.)	N/C	81.00
or 70° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 11.4 cm (4 ¹ / ₂ in.) to 25.4 cm (10 in.) 90° footrests, parallel, detachable, swingaway, length-adjustable	N/C	135.00
from 12.7 cm (5 in.) to 20.3 cm (8 in.)	N/C	135.00
70° footrests, tapered, detachable, swingaway, length-adjustable from 33.7 cm ($13^{1}/_{4}$ in.) to 43.8 cm ($17^{1}/_{4}$ in.) elevating legrests, length-adjustable from 40.6 cm (16 in.) to 50.8 cm (20 in.)	N/C	135.00
pair each	230.00	196.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
		()
elevating legrests, compensating mechanism, detachable, swingaway, length-adjustable from 43.8 cm $(17^{1}/_{4} \text{ in.})$		
to 54.6 cm $(21^{1}/_{2} \text{ in.})$		
pair	230.00	
each		196.00
modification of length of elevating legrest by -2.5 cm (1 in.)		
or by – 5.1 cm (2 in.)		
pair	190.00	
each		190.00
padded calfrests	N/C	20.00
single calf strap	22.00	34.00
double calf strap	35.00	52.00
folding footplates, standard	N/C	40.00
folding footplates, oversized	20.00	
pair	39.00	(0.00
each		60.00
folding footplates, standard, angle-adjustable	72.00	
pair each	72.00	76.00
folding footplates, oversized, angle-adjustable		70.00
pair	72.00	
each	12.00	76.00
heel loops, non-adjustable	N/C	5.00
heel loops, length-adjustable	N/C	12.00
Wheels and frame		
Types of drive systems :		
programmable joystick control	N/C	479.00
compact joystick control (requires display)	340.00	819.00
heavy-duty joystick control (requires display and interface)	96.00	575.00
modification of joystick control, each	60.00	60.00
battery charge display	N/C	N/A
battery charger	N/C	401.00
battery box, group 22	N/C	185.00
battery box, group 24	N/C	201.00
touch pad control	214.00	693.00
control with separate switches (requires display and interface)	200.00	679.00
proportional chin control (requires display)	354.00	833.00
non-proportional chin control (requires display and interface) breath control	368.00	847.00 1 740.00
head control	$1\ 740.00\ 1\ 426.00$	1 905.00
laptray touch switch control (requires display)	1 159.00	1 636.00
foot control (requires display)	1 159.00	1 636.00
toggle switch	N/C	21.00
extension for toggle switches	96.00	96.00
emergency stop ribbon switch	25.00	25.00
adapted controls interface	692.00	692.00

non-proportional controls interface separate display module direction joystick stick extension ball extension "T"-type extension swivel side bracket for joystick control side bracket for joystick control midline bracket for joystick control breath control bracket chin control bracket bracket for separate display module chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport running lights	or replacement of wheel chair	replacement of component (unit price)
separate display module direction joystick stick extension ball extension "T"-type extension swivel side bracket for joystick control side bracket for joystick control midline bracket for joystick control breath control bracket chin control bracket head control bracket bracket for separate display module chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	692.00	692.00
direction joystick stick extension ball extension "T"-type extension swivel side bracket for joystick control side bracket for joystick control midline bracket for joystick control breath control bracket chin control bracket head control bracket bracket for separate display module chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	1 099.00	1 099.00
stick extension ball extension "T"-type extension swivel side bracket for joystick control side bracket for joystick control midline bracket for joystick control breath control bracket chin control bracket head control bracket bracket for separate display module chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	N/C	126.00
"T"-type extension swivel side bracket for joystick control side bracket for joystick control midline bracket for joystick control breath control bracket chin control bracket bracket for separate display module chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	19.00	19.00
swivel side bracket for joystick control side bracket for joystick control midline bracket for joystick control breath control bracket chin control bracket bracket for separate display module chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	5.00	5.00
side bracket for joystick control midline bracket for joystick control breath control bracket chin control bracket bracket for separate display module chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	19.00	19.00
side bracket for joystick control midline bracket for joystick control breath control bracket chin control bracket bracket for separate display module chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	N/C	250.00
midline bracket for joystick control breath control bracket chin control bracket head control bracket bracket for separate display module chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	N/C	12.00
breath control bracket chin control bracket head control bracket bracket for separate display module chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	N/C	190.00
chin control bracket head control bracket bracket for separate display module chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	357.00	357.00
head control bracket bracket for separate display module chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	357.00	357.00
bracket for separate display module chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	150.00	150.00
chin control bib controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	115.00	115.00
controller G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	220.00	220.00
G/B motors with gears 4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	N/C	1 358.00
4-brush motors with gears anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	N/C	1 139.00
anti-tip rollers Types of wheels : standard forks rear suspension reflector strips tie-down points for adapted transport	N/C	1 139.00
standard forks rear suspension reflector strips tie-down points for adapted transport	N/C	60.00
standard forks rear suspension reflector strips tie-down points for adapted transport		
rear suspension reflector strips tie-down points for adapted transport	N/C	54.00
reflector strips tie-down points for adapted transport	N/C N/C	119.00
tie-down points for adapted transport	N/C N/C	N/A
	N/C N/C	75.00
	N/C	N/A
auxiliary manual brakes	72.00	
pair	72.00	45.00
each		45.00
suspension forks	130.00	
pair	150.00	110.00
each front whools, somi proventio tires, 15.2 cm (6 in) x 5.1 cm (2 in)		119.00
front wheels, semi-pneumatic tires, $15.2 \text{ cm} (6 \text{ in.}) \times 5.1 \text{ cm} (2 \text{ in.})$	N/C	40.00
or 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4}$ in.)	N/C N/C	55.00
front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) rear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)	N/C	75.00
pair	118.00	
each		134.00
front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm $(2^3/_4 \text{ in.})$		
pair	90.00	
each		85.00
front wheel rims	N/C	43.00
rear wheel rims	N/C	50.00
airless inserts for rear wheels	100	20.00
pair	95.00	
each	22.00	N/A
airless inserts for front wheels		1 1/ / 1
pair	109.00	
each	107.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
control system for one power accessory only* control system for two power accessories* module for two additional power accessories* connecting cable for power reclining devices*	461.00 327.00 327.00 161.00	695.00 798.00 798.00 161.00
DEVICE FROM : ORTHOFAB INC.		PRICI
POWERED WHEEL CHAIR, "OASIS JR" MODEL		\$4 749.00
Basic Component(s)		
 Body support system rigid back, flat back height : from 27.9 cm (11 in.) to 45.7 cm (18 in. rigid seat, flat seat widths : 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 c 38.1 cm (15 in.), 40.6 cm (16 in.) seat depths : 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 c push handles safety belt, auto-type seat height : from 41.9 cm (16¹/₂ in.) to 50.8 cm (20 in centre of gravity adjustment from seat 	em (14 in.), em (14 in.), 38.1 cm (15 in.)	
 Armrests "T"-type armrests, detachable, height-adjustable from to 25.4 cm (10 in.), short straight armrest pads, short rigid clothing guards 	n 15.2 cm (6 in.)	
 Footrests 70° footrests, detachable, swingaway, length-adjustab to 33.0 cm (13 in.) padded calfrests, straight folding footplates, standard angle-adjustable footplates, included with 90° footres heel loops length-adjustable 		

• heel loops, length-adjustable

Drive system

- programmable joystick control
- conical-spherical extension
- battery charge display
- battery charger
- battery box, group 22, group 24
- direction joystick
- push-button switch
- PILOT + controller
- motors, 9.5 km/h (6 mph)
- side bracket for joystick control, swivel side bracket for joystick control
- breath control (requires interface)
- anti-tip rollers

- · standard forks
- · tie-down points for adapted transport
- · reflector strips
- running lights
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- modification of frame length, short or long version
- rear wheel rims, front wheel rims
- rear suspension

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
padded headrest, contoured	100.00	100.00
articulated headrest mounting, uniball	115.00	115.00
articulated headrest mounting	102.00	102.00
adjustable seat bracket	N/C	127.00
seat/back structure with angle-adjustable back	714.00	714.00
reinforced seat/back structure with angle-adjustable back	1 136.00	1 136.00
rigid back, flat	N/C	55.00
padded back, contoured, fabric	285.00	340.00
padded back, contoured, leatherette	285.00	340.00
thoracic support adapters		
pair	60.00	
each		60.00
rigid seat, flat	N/C	55.00
padded seat, contoured, fabric	230.00	282.00
padded seat, contoured, leatherette	230.00	282.00
centre of gravity adjustment from seat	N/C	N/A
modification of back height to over 45.7 cm (18 in.)	96.00	N/A
modification of seat depth to 25.4 cm (10 in.), 27.9 cm (11 in.) or 40.6 cm (16 in.)	264.00	N/A
modification of seat width to 20.3 cm (8 in.), 22.9 cm (9 in.), 25.4 cm (10 in.) or 27.9 cm (11 in.)	290.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
modification of seat height by $+ 2.5 \text{ cm} (1 \text{ in.}), + 5.1 \text{ cm} (2 \text{ in.})$		
or + 7.6 cm (3 in.)	285.00	N/A
safety belt, velcro-type	27.00	63.00
safety belt, auto-type	N/C	36.00
safety belt, airplane-type	38.00	74.00
push handles	N/C	102.00
Armrests :		
"T"-type armrests, detachable, height-adjustable from 15.2 cm (
to 25.4 cm (10 in.), short	N/C	148.00
straight armrest pads, short	N/C	12.00
rigid clothing guards	N/C	44.00
modification of armrest height to over 25.4 cm (10 in.)	79.00	N/A
Footrests :		
70° footrests, detachable, swingaway, length-adjustable		
from 17.8 cm (7 in.) to 33.0 cm (13 in.)	N/C	78.00
modification of footrest length from 35.6 cm (14 in.)		
to 48.3 cm (19 in.) for 70° or 90° footrests	79.00	N/A
90° footrests, detachable, swingaway, length-adjustable		
from 17.8 cm (7 in.) to 33.0 cm (13 in.)		
pair	140.00	
each		148.00
elevating footrests, compensating mechanism, detachable,		
length-adjustable from 30.5 cm (12 in.) to 48.3 cm (19 in.)	240.00	
pair	240.00	100.00
each	N/C	198.00
padded calfrests, straight	N/C	20.00 55.00
double calf strap	55.00 N/C	
folding footplates, standard folding footplates, angle-adjustable, standard size	N/C	36.00
pair	32.00	
each	52.00	52.00
folding footplates, oversized		52.00
pair	32.00	
each	02.00	52.00
angle-adjustable footplates, included with 90° footrests	N/C	N/A
oversized footplates, angle-adjustable and depth-adjustable		
pair	38.00	
each		55.00
full-width footplate	171.00	243.00
heel loops, length-adjustable	N/C	11.00
toe loops		
pair	30.00	
each		15.00
front impact guard with rollers		
pair	36.00	10.00
each		18.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frames		
Types of drive systems :		
programmable joystick control	N/C	492.00
compact joystick control	56.00	548.00
battery charge display	N/C	N/A
battery charger	N/C	359.00
battery box, group 22 or group 24	N/C	208.00
adapted controls interface	1 608.00	2 100.00
proportional chin control	631.00	631.00
non-proportional chin control (requires interface)	421.00	421.00
head control	1 059.00	1 059.00
breath control (requires interface)	N/C	N/A
laptray touch switch control (requires interface) control with separate switches (requires interface)	301.00 530.00	301.00 530.00
chin control bib	290.00	290.00
swivel mounting hardware for breath control	385.00	385.00
	385.00	385.00
swivel mounting hardware for chin control head control bracket	385.00	385.00
fixed bracket for separate display module	37.00	37.00
flexible bracket for separate display module	120.00	120.00
push-button switch	N/C	N/A
direction joystick	N/C N/C	N/A
stick extension	19.00	27.00
ball extension	19.00	27.00
"T"-type extension	27.00	35.00
mushroom-shaped extension	19.00	27.00
conical-spherical extension	N/C	8.00
modification of the joystick control : switches and potentiometer	75.00	567.00
side bracket for joystick control	N/C	39.00
swivel side bracket for joystick control	N/C	202.00
swivel midline bracket for joystick control	85.00	287.00
PILOT + controller	N/C	1382.00
motors, 9.5 km/h (6 mph)	N/C	N/A
anti-tip rollers	N/C	60.00
modification of frame length, short or long version	N/C	N/A
Types of wheels :		
standard forks	N/C	87.00
reflector strips	N/C	20.00
running lights	N/C	N/A
tie-down points for adapted transport	N/C	N/A
rear suspension	N/C	N/A
front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	85.00
rear wheels, inner tube tires, $35.6 \text{ cm} (14 \text{ in.}) \times 7.6 \text{ cm} (3 \text{ in.})$ front wheels, inner tube tires, $22.9 \text{ cm} (9 \text{ in.}) \times 7 \text{ cm} (2^3/_4 \text{ in.})$	N/C	102.00
pair	89.00	100.00
each	100.00	129.00
airless inserts for 20.3 cm (8 in) x 5.1 cm (2 in.) wheels	133.00	N/A
front wheels, puncture-resistant tires, 22.9 cm (9 in.) x 7 cm $(2^3/_4)$ in the side of the second		N/A
airless inserts for rear wheels	151.00 N/C	N/A
rear wheel rims	N/C	N/A
front wheel rims	N/C	N/A

Component(s) under Special Consideration

power rocker device, 45°, factory installed, including shroud* power elevating legrests, individual controls*	N/C	2 375.00
pair each	1 259.00	706.00
power elevating legrests, dual control* pair	1 259.00	100100
each control system for one power accessory only*	250.00	706.00 250.00
control system for four power accessories*	740.00	740.00

§4. Supplements for wheel chairs

CUSHIONS FOR WHEEL CHAIRS

contoured seat cushion, waterproof, with stretch fabric cover	205.00
contoured seat cushion with gel, waterproof, with stretch fabric cover	270.00
"COMBI"-type cushion or equivalent*	S.C.
"JAY"-type cushion or equivalent*	S.C.
gel cushion or equivalent*	S.C.
"ROHO" cushion or equivalent*	S.C.
special cushion*	S.C.

§5. Components for wheel chairs

TIRES AND INSERTS

FOR MANUAL WHEEL CHAIRS

SUPPLIER : ORTHOFAB INC.

tire, inner tube, standard pressure, 31.8 cm $(12^{1}/_{2} \text{ in.}) \times 5.7 \text{ cm} (2^{1}/_{4} \text{ in.})$	9.45
tire, inner tube, standard pressure, 50.8 cm (20 in.) x 3.5 cm $(1^3/_8 in.)$	8.50
tire, inner tube, standard pressure, 55.9 cm (22 in.) x 3.5 cm $(1^3/_8 in.)$	7.95
tire, inner tube, standard pressure, 61.0 cm (24 in.) x 3.2 cm (1 ¹ / ₄ in.)	7.25
tire, inner tube, standard pressure, 61.0 cm (24 in.) x 3.5 cm $(1^{3}/_{8} in.)$	7.95
tire, inner tube, standard pressure, 61.0 cm (24 in.) x 4.4 cm $(1^{3}/_{4} in.)$	9.95
tire, inner tube, standard pressure, 40.6 cm (16 in.) x 4.4 cm (1 ³ / ₄ in.)	9.95
tire, inner tube, standard pressure, 66.0 cm (26 in.) x 3.5 cm $(1^{3}/_{8} in.)$	8.95
tire, inner tube, high pressure, 50.8 cm (20 in.) x 2.5 cm (1 in.)	12.60
tire, inner tube, high pressure, 55.9 cm (22 in.) x 2.5 cm (1 in.)	12.60
tire, inner tube, high pressure, 61.0 cm (24 in.) x 2.5 cm (1 in.)	12.60
tire, inner tube, high pressure, 66.0 cm (26 in.) x 2.5 cm (1 in.)	12.60
tire, inner tube, 61.0 cm (24 in.) x 3.5 cm ($1^{3}/_{8}$ in.), all-terrain, rounded surface	12.75
tire, inner tube, 61.0 cm (24 in.) x 3.5 cm $(1^{3}/_{8} \text{ in.})$, all-terrain, rounded surface	9.50
solid tire, 20.3 cm (8 in.) x 2.5 cm (1 in.)	4.50
solid tire, 55.9 cm (22 in.) x 2.5 cm (1 in.)	10.87
solid tire, 61.0 cm (24 in.) x 2.5 cm (1 in.)	10.44
tire, inner tube, 15.2 cm (6 in.) x 3.2 cm $(1^{1}/_{4} in.)$	7.10
tire, inner tube, 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4} in.)$ (C-63)	6.60
tire, inner tube, 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4} in.)$	8.95
tire, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)	7.40
tire, inner tube, 18.8 cm (7 in.) x 4.4 cm ($1^{3}/_{4}$ in.)	8.15

tire, inner tube, 20.3 cm (8 in.) x 3.2 cm (1 ¹ / ₄ in.) (C-737)	6.60
semi-pneumatic tire, 12.7 cm (5 in.) x 2.5 cm (1 in.)	9.10
semi-pneumatic tire, 15.2 cm (6 in.) x 2.5 cm (1 in.)	9.10
semi-pneumatic tire, 20.3 cm (8 in.) x 2.5 cm (1 in.) (poly kik)	10.39
semi-pneumatic tire, 20.3 cm (8 in.) x 2.5 cm (1 in.) (poly pyramide)	10.02
semi-pneumatic tire, 55.9 cm (22 in.) x 2.5 cm (1 in.)	15.15
semi-pneumatic tire, 61.0 cm (24 in.) x 2.5 cm (1 in.)	15.95
semi-pneumatic tire, 66.0 cm (26 in.) x 2.5 cm (1 in.)	15.95
puncture-resistant tire, 15.2 cm (6 in.) x 3.2 cm $(1^{1}/_{4} in.)$	10.61
puncture-resistant tire, 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4} in.)$	11.00
puncture-resistant tire, 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4}$ in.)	12.50
puncture-resistant tire, 20.3 cm (8 in.) x 5.1 cm (2 in.)	14.00
puncture-resistant tire, 50.8 cm (20 in.) x 3.5 cm $(1^3/_8 in.)$	24.15
puncture-resistant tire, 55.9 cm (22 in.) x 3.5 cm $(1^3/_8 in.)$	24.15
puncture-resistant tire, 61.0 cm (24 in.) x 2.5 cm (1 in.)	19.90
puncture-resistant tire, 61.0 cm (24 in.) x 3.45 cm $(1^3/_8 in.)$	24.40
airless insert, 15.2 cm (6 in.) x 3.2 cm $(1^{1}/_{4} in.)$	11.08
airless insert, 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4} in.)$	12.20
airless insert, 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4} in.)$	14.80
airless insert, 50.8 cm (20 in.) x 3.5 cm $(1^{3}/_{8} in.)$	20.63
airless insert, 55.9 cm (22 in.) x 3.5 cm (1 ³ / ₈ in.)	20.63
airless insert, 61.0 cm (24 in.) x 3.2 cm (1 ¹ / ₄ in.)	20.63
airless insert, 61.0 cm (24 in.) x 3.5 cm (1 ³ / ₈ in.)	20.63
airless insert, 66.0 cm (26 in.) x 3.5 cm (1 ³ / ₈ in.)	31.93

TIRES AND INSERTS

FOR POWERED WHEEL CHAIRS

SUPPLIER : ORTHOFAB INC.

tire, inner tube, 33.0 cm (13 in.) x 10.2 cm (4 in.) (400-5)	16.70
tire, inner tube, 18.8 cm (7 in.) x 4.4 cm $(1^{3}/_{4} in.)$	8.15
tire, inner tube, 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4} in.)$	6.60
tire, inner tube, 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4} in.)$	8.95
tire, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)	7.40
tire, inner tube, 21.6 cm $(8^{1}/_{2} \text{ in.}) \times 5.3 \text{ cm} (2^{1}/_{8} \text{ in.})$	37.00
tire, inner tube, 20.3 cm (8 in.) x 7 cm $(2^3/_4$ in.)	9.14
tire, inner tube, 22.9 cm (9 in.) x 7 cm $(2^3/_4$ in.)	9.95
tire, inner tube, 25.4 cm (10 in.) x 7.6 cm (3 in.)	11.50
tire, inner tube, 30.5 cm (12 in.) x 7.6 cm (3 in.)	15.95
tire, inner tube, $31.8 \text{ cm} (12^{1}/_{2} \text{ in.}) \times 5.7 \text{ cm} (2^{1}/_{4} \text{ in.})$	9.45
tire, inner tube, $35.6 \text{ cm} (14 \text{ in.}) \times 5.7 \text{ cm} (2^{1}/_4 \text{ in.})$	12.50
tire, inner tube, 35.6 cm (14 in.) x 7.6 cm (3 in.), (300-8)	17.95
tire, inner tube, 35.6 cm (14 in.) x 10.2 cm (4 in.) (400-6)	15.00
tire, inner tube, $40 \text{ cm} (15^{3}/_{4} \text{ in.}) \ge 7 \text{ cm} (2^{3}/_{4} \text{ in.})$	58.00
tire, inner tube, $40.6 \text{ cm} (16 \text{ in.}) \times 5.7 \text{ cm} (2^{1}/_4 \text{ in.})$	11.90
tire, inner tube, 40.6.cm (16 in.) x 5.3 cm ($2^{1}/_{8}$ in.)	11.90
tire, inner tube, 45.7 cm (18 in.) x 5.7 cm ($2^{1}/_{4}$ in.)	12.45
tire, inner tube, 50.8 cm (20 in.) x 5.3 cm ($2^{1}/_{8}$ in.)	14.10
tire, inner tube, 50.8 cm (20 in.) x 5.7 cm ($2^{1}/_{4}$ in.)	12.45
semi-pneumatic tire, 20.3 cm (8 in.) x 4.4 cm $(1^3/_4 in.)$ (poly kik)	13.00

semi-pneumatic tire, 22.9 cm (9 in.) x 7 cm $(2^3/_4 \text{ in.})$	28.00
puncture-resistant tire, 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4} \text{ in.})$ (poly kik)	12.50
puncture-resistant tire, 22.9 cm (9 in.) x 7 cm $(2^3/_4 \text{ in.})$, $(280/250-4)$	37.40
puncture-resistant tire, 25.4 cm (10 in.) x 7.6 cm (3 in.)	48.90
puncture-resistant tire, 30.5 cm (12 in.) x 7.6 cm (3 in.)	35.50
puncture-resistant tire, 35.6 cm (14 in.) x 10.2 cm (4 in.)	53.00
puncture-resistant tire, 35.6 cm (14 in.) x 7.6 cm (3 in.)	67.70
puncture-resistant tire, 35.6 cm (14 in.) x 10.2 cm (4 in.), (400-6)	53.00
puncture-resistant tire, 50.8 cm (20 in.) x 5.3 cm ($2^{1}/_{8}$ in.)	29.00
puncture-resistant tire, 20.3 cm (8 in.) x 5.1 cm (2 in.)	14.00
puncture-resistant tire, 20.3 cm (8 in.) x 5.1 cm (2 in.) (poly kik)	13.50
airless insert, 20.3 cm (8 in.) x 3.2 cm (1 ¹ / ₄ in.)	12.20
airless insert, 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4} in.)$	14.80
airless insert, 31.8 cm $(12^{1}/_{2} \text{ in.}) \times 5.7 \text{ cm} (2^{1}/_{4} \text{ in.})$	24.00
airless insert, 35.6 cm (14 in.) x 5.7 cm $(2^{1}/_{4} in.)$	24.00
airless insert, 40.6 cm (16 in.) x 5.3 cm $(2^{1}/_{8} in.)$	27.00
airless insert, 45.7 cm (18 in.) x 5.7 cm ($2^{1}/_{4}$ in.)	23.00
airless insert, 50.8 cm (20 in.) x 5.3 cm $(2^{1}/_{8} in.)$	23.00
airless insert, 50.8 cm (20 in.) x 5.7 cm $(2^{1}/_{4} in.)$	23.00

BATTERIES

FOR POWERED WHEEL CHAIRS

SEALED LEAD BATTERIES (AQUEOUS-TYPE, DEEP CYCLE, NOMINAL VOLTAGE OF 12 VOLTS)

GROUP 22 :	Price including delivery of goods and their recovery after use
Model : 22NF-DC	56.16
Model : 22F-DC	60.24
GROUP 24 :	
Model : 24-DC	50.93
GROUP U1 :	
Model : U1-DC	44.67

DIVISION II POSITIONING BASES

DEVICE FROM: INVACARE CANADA INC.

POSITIONING BASE, ADULT, "SOLARA" MODEL

Basic Component(s)

Body support system

- seating height: from 42.5 cm $(16^{3}/_{4} \text{ in.})$ to 48.9 cm $(19^{1}/_{4} \text{ in.})$
- seat widths: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.)
- seat depths: 30.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.)
- back heights: 50.8 cm (20 in.), 61.0 cm (24 in.)
- rocker device for seat and back, from -10° to $+45^{\circ}$
- folding back, angle-adjustable
- push handles
- push handles, angle-adjustable
- safety belt, velcro-type, auto-type
- supple back, nylon, nylon cloth for supple back, reclining

Armrests

- "T"-type armrests, detachable, height-adjustable from 15.2 cm (6 in.), to 25.4 cm (10 in.) or from 20.3 cm (8 in.) to 35.6 cm (14 in.), short, long
- "U"-type armrests, fixed height, from 21.6 cm (8¹/₂ in.) to 31.8 cm (12¹/₂ in.), short, long
- "U"-type armrests, detachable, height-adjustable from 21.6 cm (8¹/₂ in.) to 31.8 cm (12¹/₂ in.), short, long
- "I"-type armrests, height-adjustable from 17.8 cm (7 in.) to 30.5 cm (12 in.), short, long
- straight armrest pads, short, long

Footrests

- 60° footrests, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 44.5 cm (17¹/₂ in.)
- 70° footrests, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 41.9 cm (16¹/₂ in.)
- padded calfrests
- heel loops, non-adjustable
- heel loops, length-adjustable
- folding footplates, standard

PRICE

\$1 713.00

Wheels and frame

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock
- · standard forks
- threaded axles, quick-release
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.)
- anti-tip rollers

straight armrest pads, short

- frame length: 73.7 cm (29 in.), 81.3 cm (32 in.), 86.4 cm (34 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.), 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.)
- **Price upon Price upon** initial purchase replacement of or replacement component of wheel chair (unit price) **Basic and Optional Component(s) Body support system** Seat and back: modification of seat width to 53.3 cm (21 in.) or 55.9 cm (22 in.) 59.00 N/A 95.00 49.00 rigid seat, flat rocker device for seat and back, from -10° to $+45^{\circ}$ N/C N/A push handles N/C 38.00 push handles, angle-adjustable N/C N/A safety belt, velcro-type N/C 40.00 safety belt, auto-type N/C 50.00

seat cushion, flat, foam, 5.1 cm (2 in.) 56.00 56.00 seat cushion, flat, foam, 7.6 cm (3 in.) 56.00 56.00 supple back, nylon N/C 50.00 nylon cloth for supple back, reclining N/C 75.00 folding back, angle-adjustable N/C N/A Armrests: "I"-type armrests, height-adjustable from 17.8 cm (7 in.) N/C to 30.5 cm (12 in.), short or long 98.00 "U"-type armrests, detachable, height-adjustable from 21.6 cm ($8^{1}/_{2}$ in.) to 31.8 cm ($12^{1}/_{2}$ in.), short or long N/C 98.00 "U"-type armrests, fixed height, from 21.6 cm $(8^{1}/_{2} \text{ in.})$ N/C to 31.8 cm $(12^{1}/_{2} \text{ in.})$, short or long 66.00 "T"-type armrests, detachable, height-adjustable from 15.2 cm (6 in.), to 25.4 cm (10 in.) or from 20.3 cm (8 in.) N/C to 35.6 cm (14 in.), short or long 125.00 N/C 26.00straight armrest pads, long

N/C

26.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
60° footrests, detachable, swingaway, length-adjustable		
from 34.3 cm $(13^{1}/_{2} \text{ in.})$ to 44.5 cm $(17^{1}/_{2} \text{ in.})$	N/C	81.00
70° footrests, detachable, swingaway, length-adjustable		
from 34.3 cm ($13^{1}/_{2}$ in.) to 41.9 cm ($16^{1}/_{2}$ in.)	N/C	81.00
90° footrests, detachable, swingaway, length-adjustable		
from 6.4 cm $(2^{1}/_{2} \text{ in.})$ to 23.5 cm $(9^{1}/_{4} \text{ in.})$	4.0.	
pair	107.00	125.00
each		135.00
60° footrests, MFX, detachable, swingaway, length-adjustable from 22.9 cm (9 in.) to 31.8 cm $(12^{1}/_{2} in.)$		
pair	144.00	
each	144.00	153.00
70° footrests, MFX, detachable, swingaway, length-adjustable		155.00
from 14.6 cm ($5^{3}/_{4}$ in.) to 29.8 cm ($11^{3}/_{4}$ in.)		
pair	144.00	
each		153.00
70° elevating legrests, tapered, detachable, swingaway,		
length-adjustable from 32.4 cm $(12^3/_4 \text{ in.})$ to 41.3 cm $(16^1/_4 \text{ in.})$		
pair	107.00	125.00
each		135.00
elevating legrests, detachable, swingaway, length-adjustable from 39.4 cm $(15^{1}/_{2} \text{ in.})$ to 50.8 cm (20 in.)		
pair	230.00	
each	230.00	196.00
elevating legrests, compensating mechanism		1,0,00
pair	151.00	
each		157.00
modification of legrest length by -2.5 cm (1 in.) or by -5.1 cm (2 i		190.00
padded calfrests	N/C	20.00
single calf strap	22.00	34.00
double calf strap	35.00	52.00
folding footplates, standard	N/C	40.00
folding footplates, angle-adjustable and depth-adjustable, standard size or oversized 18.4 cm $(7^{1}/_{4} \text{ in.})$		
pair	72.00	
each	72.00	76.00
oversized footplates		70.00
pair	39.00	
each		60.00
heel loops, non-adjustable	N/C	5.00
heel loops, length-adjustable	N/C	12.00
heel loops and ankle straps		
pair	32.00	14.00
each		16.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems: anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	34.00
plastic-coated or combined handrims pair	52.00	
each handrims with vertical or oblique projections	155.00	60.00
pair each anti-tip rollers	155.00 N/C	$112.00 \\ 48.00$
frame length, 73.7 cm (29 in.), 81.3 cm (32 in.) or 86.4 cm (34 in.)	N/C N/C	400.00
Wheel locks: standard wheel locks, push-to-lock wheel lock extensions	N/C	44.00
pair each	32.00	16.00
Types of forks : standard forks	N/C	50.00
Rear axles: threaded axles	N/C	16.00
quick-release axles	N/C	53.00
Types of wheels: rear mag wheels, standard pressure, 30.5 cm (12 in.) rear mag wheels, standard pressure, 50.8 cm (20 in.),	N/C	71.00
55.9 cm (22 in.) or 61.0 cm (24 in.) rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)	N/C	90.00
or 61.0 cm (24 in.) front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)	N/C	90.00
or 15.2 cm (6 in.)	N/C	40.00
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.)	N/C	52.00
front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.) front wheels, semi-pneumatic, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	70.00
pair each	56.00	68.00
front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.) pair	48.00	(1.05
each		64.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
contracture footrests, bilateral-angle adjustable* reclining back* heavy-duty frame* contracture footrests, one-piece*	176.00 496.00 322.00 176.00	265.00 776.00 N/A 265.00
DEVICE FROM: ORTHOFAB INC.		PRICE
POSITIONING BASE, ADULT, "TANGO" MODEL		\$1 669.00
Basic Component(s)		
 Body support system seat height: from 35.6 cm (14 in.) to 45.7 cm (18 in.) seat widths: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.) seat depths: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) folding back, angle-adjustable, height of 40.6 cm (16 in.) to 66.0 cm (26 in.) rocker device for seat and back, from – 5° to + 45° push handles safety belt, auto-type 		
 Armrests "U"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), short straight armrest pads, short, long rigid clothing guards 		
 Footrests 60° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) padded calfrests heel loops, length-adjustable folding footplates, standard 		

- · straight front frame
- standard wheel locks, push-to-lock
- high forks
- threaded axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.)
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.), 17.8 cm (7 in.), 15.2 cm (6 in.) x 2.5 cm (1 in.)
- anti-tip rollers
- smooth handrims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
headrest, hammock-style	75.00	75.00
padded headrest, contoured, nylon	100.00	100.00
rigid seat, flat	81.00	81.00
rocker device for seat and back, from -5° to $+45^{\circ}$	N/C	N/A
push handles	N/C	N/A
articulated headrest mounting	102.00	102.00
articulated headrest mounting, uniball	115.00	115.00
back tension bar with headrest mounting bracket	99.00	99.00
back tension bar	69.00	69.00
safety belt, velcro-type	27.00	63.00
safety belt, auto-type	N/C	36.00
safety belt, airplane-type	38.00	74.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
supple back, nylon	64.00	64.00
supple back, tension adjustable	133.00	133.00
folding back, angle-adjustable, height of 40.6 cm (16 in.)		
to 66.0 cm (26 in.)	N/C	N/A
Armrests: "U"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), short	N/C	94.00
"U"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), long	IVC	94.00
pair	52.00	
each		120.00
straight armrest pads, long	N/C	15.00
straight armrest pads, short contoured armrest pads, short	N/C	12.00
pair	44.00	
each	++.00	34.00
		54.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
contoured armrest pads, long		
pair	48.00	
each		39.00
modification of armrest height to under 25.4 cm (10 in.)	79.00	N/A
rigid clothing guards	N/C	N/A
Footrests :		
60° footrests, tapered, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	102.00
70° footrests, tapered, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	102.00
60° or 70° footrests, parallel, detachable, swingaway,		
length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)	29.00	N/A
90° footrests, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
pair	86.00	
each		145.00
elevating legrests, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
pair	165.00	
each		185.00
elevating legrests, compensating mechanism, detachable, swingaway	,	
length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
pair	234.00	
each		219.00
modification of footrest or legrest length to under 35.6 cm (14 in.)		
or to over 48.3 cm (19 in.)	79.00	N/A
padded calfrests	N/C	20.00
contoured calfrests		
pair	60.00	T O OO
each		50.00
double calf strap	55.00	55.00
folding footplates, standard	N/C	16.00
folding footplates, aluminum	11.00	
pair	41.00	26.00
each		36.00
standard footplates, angle-adjustable and depth-adjustable	72.00	
pair	72.00	52.00
each		52.00
oversized footplates, angle-adjustable and depth-adjustable	70.00	
pair	79.00	55.00
each	160.00	55.00
full-width footplate, angle-adjustable	168.00	200.00
front impact guard with rollers	26.00	
pair	36.00	10.00
each		18.00
toe loops	20.00	
pair	30.00	15.00
each	N/C	15.00 11.00
heel loops, length-adjustable		

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems :		
smooth handrims non-slip handrims	N/C	46.00
pair	84.00	
each	01.00	88.00
plastic-coated handrims		
pair	56.00	5 4.00
each combined handrims		74.00
pair	66.00	
each	00.00	79.00
front anti-tip rollers	N/C	46.00
optional flared frame	95.00	N/A
straight front frame	N/C	N/A
Wheel locks:		
standard, push-to-lock	N/C	53.00
wheel lock extensions, retractable		
pair	38.00	
each		19.00
wheel lock extensions, fixed pair	38.00	
each	50.00	19.00
anti-rollback brakes		
pair	86.00	
each		43.00
Types of forks :		
high forks	N/C	55.00
-		
Rear axles:	N/C	5.00
threaded axles	N/C	5.00
Types of wheels:		
rear mag wheels, standard pressure, 50.8 cm (20 in.), $55.0 \text{ cm} (22 \text{ in.}) = 61.0 \text{ cm} (24 \text{ in.})$		
55.9 cm (22 in.) or 61.0 cm (24 in.) pair	98.00	
each	20.00	123.00
rear mag wheels, standard pressure, 30.5 cm (12 in.)	N/C	74.00
rear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)		
pair	98.00	122.00
each rear mag wheels, solid tires, 30.5 cm (12 in.)		123.00
pair	68.00	
each	00100	108.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	60.00	
pair each	68.00	108.00
		106.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) spoked rear wheels, semi-pneumatic tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	74.00
pair each rear mag wheels, semi-pneumatic tires, 50.8 cm (20 in.),	68.00	108.00
55.9 cm (22 in.) or 61.0 cm (24 in.) pair each	128.00	138.00
front wheels, solid tires, 20.3 cm (8 in.), 17.8 cm (7 in.) or 15.2 cm (6 in.) x 2.5 cm (1 in.) front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.)	N/C	30.00
or 15.2 cm (6 in.) x 3.2 cm (1 ¹ / ₄ in.) pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.),	32.00	46.00
15.2 cm (6 in) or 12.7 cm (5 in.) x 3.8 cm $(1^{1}/_{2}$ in.) pair each	32.00	46.00
Component(s) under Special Consideration		
reclining back*	699.00	699.00
spoke guards* pair each	114.00	57.00
quick-release axles* pair each	76.00	43.00
DEVICE FROM: SUNRISE MEDICAL CANADA INC.		PRICE
POSITIONING BASE, ADULT, "QUICKIE TS" MODEL		\$1 790.00
Basic Component(s)		
 Body support system seat height: from 40.6 cm (16 in.) to 50.8 cm (20 in.) seat width: from 35.6 cm (14 in.) to 50.8 cm (20 in.) seat depth: from 35.6 cm (14 in.) to 55.9 cm (22 in.) rocker mechanism, from 0° to 45° safety belt, auto-type, velcro-type raised push handles angle-adjustable back back heights: 54.6 cm (21¹/₂ in.), 62.2 cm (24¹/₂ in.), 69.9 cm (27¹/₂ in.), with push handles 		

Armrests

- "T"-type armrests, detachable, height-adjustable from 26.0 cm $(10^{1}/_{4} \text{ in.})$ to 38.7 cm $(15^{1}/_{4} \text{ in.})$, short, long, with built-in clothing guards
- "L"-type armrests, height adjustable from 16.5 cm ($6^{1}/_{2}$ in.) to 33.0 cm (13 in.), short, long
- straight armrest pads, short, long
- tubular armrest pads

Footrests

- 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 37.5 cm (14³/₄ in.) to 43.8 cm (17¹/₄ in.)
- 70 footrests, tapered, detachable, swingaway, length-adjustable from 37.5 cm (14³/₄ in.) to 43.8 cm (17¹/₄ in.)
- 70°, 80°, 90° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- · padded calfrests
- padded calfrests for legrests with compensating mechanism
- heel loops, length-adjustable
- folding footplates, standard

- smooth handrims, 45.7 cm (18 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- fork stems, + 1.9 cm $({}^{3}/_{4}$ in.), + 3.8 cm $({}^{1}/_{2}$ in.)
- quick-release axles
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 15.2 cm (6 in.) x 3.2 cm (1¹/₄ in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- anti-tip rollers
- standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5¹/₄ in.); high forks 17.8 cm (7 in.), for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
headrest, small	90.00	93.00
headrest, medium	96.00	103.00
headrest, large	102.00	107.00
rigid seat, flat	47.00	89.00
rocker mechanism, from 0° to 45°	N/C	N/A
safety belt, velcro-type	N/C	28.00
safety belt, auto-type	N/C	41.00
safety belt, airplane-type	49.00	77.00
safety belt, airplane-type, padded	74.00	101.00
crossbar for headrest mounting	194.00	206.00
articulated headrest mounting	154.00	168.00
raised push handles	N/C	N/A
back height: 54.6 cm $(21^{1}/_{2} \text{ in.})$, 62.2 cm $(24^{1}/_{2} \text{ in.})$	140	1.011
or 69.9 cm $(27^{1}/_{2} \text{ in.})$, with push handles	N/C	N/A
folding back, angle-adjustable	N/C	N/A
Armrests :		
"U"-type armrests, detachable, height-adjustable		
from 24.1 cm (9 ¹ / ₂ in.) to 36.8 cm (14 ¹ / ₂ in.), short or long,		
with built-in clothing guards		
pair	132.00	
each		156.50
"T"-type armrests, detachable, height-adjustable		
from 26.0 cm ($10^{1}/_{4}$ in.) to 38.7 cm ($15^{1}/_{4}$ in.), short or long,		
with built-in clothing guards	N/C	132.00
"I"-type armrests, height-adjustable from 16.5 cm $(6^{1}/_{2} \text{ in.})$		
to 33.0 cm (13 in.), short or long	N/C	90.50
tubular armrest pads	N/C	2.00
straight armrest pads, long	N/C	17.00
straight armrest pads short	N/C	15.00
rigid clothing guards, detachable		
pair	90.00	
each		66.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests :		
70°, 80° or 90° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) 70° or 80° footrests, heavy-duty, detachable, non-flip-back	N/C	55.00
pair each	63.00	84.00
60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 37.5 cm ($14^{3}/_{4}$ in.) to 43.8 cm ($17^{1}/_{4}$ in.)	N/C	52.50
70° footrests, tapered, detachable, swingaway, length-adjustable from 37.5 cm (14 ³ / ₄ in.) to 43.8 cm (17 ¹ / ₄ in.) elevating legrests	N/C	52.50
pair each	105.00	105.00
elevating legrests, compensating mechanism pair each	194.00	149.50
modification of footrest length from 45.7 cm (18 in.) to 52.1 cm $(20^{1}/_{2} \text{ in.})$		
pair	30.00	20.00
each badded calfrests	N/C	29.00 18.00
calfrests for legrests with compensating mechanism contoured calfrests	N/C	39.00
pair	70.00	
each		53.00
single calf strap	18.00	18.00
folding footplates, standard folding footplates, standard size, angle-adjustable and depth-adjustable	N/C	48.00
pair each	51.00	73.50
90° legrests, from 20.3 cm (8 in.) to 33.0 cm (13 in.)		
pair	69.00	
each full-width footplate, angle-adjustable modification of length of detachable footrests by 5.1 cm (2 in.)	83.00	87.00 179.00
or by $10.2 \text{ cm} (4 \text{ in.})$		
pair	30.00	
each	00.00	15.00
full-width foot platform, 90°	89.00	185.00
heel loops, length-adjustable footrest mounting, from 17.8 cm (7 in.) to 34.3 cm $(13^{1}/_{2} \text{ in.})$	N/C	10.00
pair	54.00	
each		33.00

Wheels and frame Types of drive systems: smooth handrims, 45.7 cm (18 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) pair sand1 handrim for one-arm drive pair cach pair each pair each pair each pair each pair each standthandrims with oblique or vertical projections pair each anti-tip rollers trame with growth option 128.00 N/A heavy-duty frame: robust option (350 lb.) standard, push-to-lock or pull-to-lock pair standard, push-to-lock or pull-to-lock pair pair cach pair each standard, push-to-lock or pull-to-lock standard, push-to-lock or pull-to-lock pair pair cach tatt:-rollback brakes <		Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
smooth handrims, 45.7 cm (18 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) N/C 58.00 small handrim for one-arm drive pair 54.00 each N/A pair 54.00 each 85.00 handrims with oblique or vertical projections pair 88.00 each 102.00 anti-tip rollers N/C 22.00 tapered frame 128.00 N/A frame with growth option 128.00 N/A frame with growth option 128.00 N/A frame with growth option 350 lb.) 81.00 N/A one-arm drive for dual handrim 549.00 692.00 cach 44.00 44.00 44.00 front anti-tippers pair 55.00 each 27.50 Wheel locks : standard, push-to-lock or pull-to-lock N/C 39.00 anti-rollback brakes pair 26.00 each 33.00 wheel lock stensions pair 26.00 each 33.00 Wheel locks is standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 V_{4} in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 Rear axles: quick-release axles N/C 32.50	Wheels and frame		
$\begin{array}{cccccccccccccccccccccccccccccccccccc$			
pair54.00eachN/Aplastic-coated handrims, 45.7 cm (18 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)N/Apair54.00each85.00handrims with oblique or vertical projections102.00anti-tip rollersN/Ceach102.00anti-tip rollersN/Ctarger of frame128.00rame with growth option128.00heavy-duty frame : robust option (350 lb.)81.00seach55.00care holder44.00front anti-tippers27.50pair55.00each27.50Wheel locks:standard, push-to-lock or pull-to-lockanti-rollback brakes66.00pair26.00each33.00wheel locks: 15.2 cm (6 in.); short forks, 13.3 cm (5½ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheelsN/C15.2 cm (6 in.) and 20.3 cm (8 in.) wheelsN/C31.00Rear axles: quick-release axlesN/C32.50	55.9 cm (22 in.), 61.0 cm (24 in.)	N/C	58.00
plastic-coated handrims, 45.7 cm (18 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) pair 54.00 each 85.00 handrims with oblique or vertical projections pair 88.00 each 102.00 anti-tip rollers N/C 22.00 N/A frame with growth option 128.00 N/A frame with growth option 128.00 N/A frame with growth option (350 lb.) 81.00 N/A neavy-duty frame: robust option (350 lb.) 81.00 N/A one-arm drive for dual handrim 549.00 692.00 cane holder 44.00 44.00 from anti-tippers pair 55.00 each 27.50 Wheel locks : standard, push-to-lock or pull-to-lock N/C 39.00 anti-rollback brakes pair 66.00 each 33.00 wheel lock extensions pair 26.00 each 13.00 Types of forks : standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork stens, 1.9 cm (¹ / ₄ in.) or + 3.8 cm (1 ¹ / ₂ in.) N/C 16.00 Rear axles: quick-release axles N/C 32.50	pair	54.00	NI/A
pair54.00each85.00handrims with oblique or vertical projections88.00pair88.00each102.00anti-tip rollersN/Ctapered frame128.00with growth option128.00heavy-duty frame: robust option (350 lb.)81.00one-arm drive for dual handrim549.00one-arm drive for dual handrim549.00one-arm drive for dual handrim549.00gair55.00each27.50Wheel locks:standard, push-to-lock or pull-to-lockgair66.00each33.00wheel lock extensions33.00pair66.00each13.00Types of forks:standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5¼ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheelsN/Cfork sters, + 1.9 cm (¼ in.) or + 3.8 cm (1½ in.)N/Cguick-release axlesN/C32.50	plastic-coated handrims, 45.7 cm (18 in.), 50.8 cm (20 in.),		N/A
handrims with oblique or vertical projections pair 88.00 each 102.00 anti-tip rollers N/C 22.00 tapered frame 128.00 N/A frame with growth option 128.00 N/A heavy-duty frame : robust option (350 lb.) 81.00 N/A one-arm drive for dual handrim 549.00 692.00 cane holder 44.00 44.00 front anti-tippers 55.00 each 27.50 Wheel locks : standard, push-to-lock or pull-to-lock N/C 39.00 anti-rollback brakes 66.00 each 33.00 wheel lock extensions 72 pair 66.00 each 33.00 Types of forks : standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork stems, + 1.9 cm (¹ / ₄ in.) or + 3.8 cm (1 ¹ / ₂ in.) N/C 16.00 Rear axles : quick-release axles N/C 32.50	pair	54.00	85.00
each 102.00 anti-tip rollers N/C 22.00 tapered frame 128.00 N/A frame with growth option 128.00 N/A heavy-duty frame : robust option (350 lb.) 81.00 N/A one-arm drive for dual handrim 549.00 692.00 cane holder 44.00 44.00 front anti-tippers 27.50 Wheel locks : standard, push-to-lock or pull-to-lock N/C 39.00 anti-rollback brakes 66.00 as.00 as.00 pair 66.00 as.00 as.00 wheel lock stensions 26.00 as.00 as.00 pair 26.00 13.00 as.00 Types of forks: standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ^{1/4} , in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork stems, + 1.9 cm (¹ /4, in.) or + 3.8 cm (1 ¹ / ₂ in.) N/C 16.00 Rear axles: guick-release axles N/C 32.50			85.00
tapered frame 128.00 N/A frame with growth option 128.00 N/A heavy-duty frame : robust option (350 lb.) 81.00 N/A one-arm drive for dual handrim 549.00 692.00 cane holder 44.00 44.00 front anti-tippers 77.50 27.50 wheel locks: 77.50 27.50 standard, push-to-lock or pull-to-lock N/C 39.00 anti-rollback brakes 9 33.00 wheel lock extensions 26.00 20 each 26.00 20 each 13.00 20 Types of forks: 13.00 13.00 Forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork stems, + 1.9 cm (³ / ₄ in.) or + 3.8 cm (1 ¹ / ₂ in.) N/C 31.00 Rear axles: 9 N/C 32.50	1	88.00	102.00
frame with growth option 128.00 N/A heavy-duty frame : robust option (350 lb.) 81.00 N/A one-arm drive for dual handrim 549.00 692.00 cane holder 44.00 44.00 front anti-tippers 9 9 pair 55.00 27.50 Wheel locks : standard, push-to-lock or pull-to-lock N/C 39.00 anti-rollback brakes 66.00 33.00 wheel lock extensions 9 26.00 13.00 Types of forks : standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 Rear axles : quick-release axles N/C 32.50	anti-tip rollers	N/C	22.00
heavy-duty frame : robust option (350 lb.) 81.00 N/A one-arm drive for dual handrim 549.00 692.00 cane holder 44.00 44.00 front anti-tippers 75.00 27.50 Wheel locks : standard, push-to-lock or pull-to-lock N/C 39.00 anti-rollback brakes pair 66.00 each 26.00 each 26.00 Types of forks : standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 Rear axles: quick-release axles N/C 32.50	tapered frame	128.00	N/A
heavy-duty frame : robust option (350 lb.) 81.00 N/A one-arm drive for dual handrim 549.00 692.00 cane holder 44.00 44.00 front anti-tippers 75.00 27.50 Wheel locks : standard, push-to-lock or pull-to-lock N/C 39.00 anti-rollback brakes pair 66.00 each 26.00 each 26.00 Types of forks : standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 Rear axles: quick-release axles N/C 32.50	frame with growth option	128.00	N/A
cane holder 44.00 44.00 front anti-tippers 55.00 27.50 Wheel locks : standard, push-to-lock or pull-to-lockN/C 39.00 anti-rollback brakes 66.00 33.00 pair 66.00 $acch$ each 33.00 30.00 wheel lock extensions 26.00 13.00 Types of forks : standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheelsN/C 31.00 Rear axles: quick-release axlesN/C 32.50 32.50	heavy-duty frame: robust option (350 lb.)	81.00	N/A
front anti-tippers pair each55.0027.50Wheel locks : standard, push-to-lock or pull-to-lockN/C39.00anti-rollback brakes pair each66.0033.00wheel lock extensions pair each66.0033.00Wheel lock extensions pair each26.0013.00Types of forks : standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels fork stems, + 1.9 cm (³ / ₄ in.) or + 3.8 cm (1 ¹ / ₂ in.)N/C31.00Rear axles: quick-release axlesN/C32.50	one-arm drive for dual handrim	549.00	692.00
pair55.0027.50Wheel locks: standard, push-to-lock or pull-to-lockN/C39.00anti-rollback brakes pair66.0033.00each66.0033.00wheel lock extensions pair26.0013.00Types of forks: standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheelsN/C31.00Rear axles: quick-release axlesN/C32.50		44.00	44.00
each27.50Wheel locks : standard, push-to-lock or pull-to-lockN/C39.00anti-rollback brakes pair66.0033.00each 66.00 33.00wheel lock extensions pair26.0013.00Types of forks : standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheelsN/C31.00Rear axles : quick-release axlesN/C32.50		55.00	
standard, push-to-lock or pull-to-lockN/C 39.00 anti-rollback brakes66.00pair66.00each 33.00 wheel lock extensions 26.00 pair 26.00 each 13.00 Types of forks: standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheelsN/CN/C 31.00 Rear axles: quick-release axlesquick-release axlesN/C 32.50	1	55.00	27.50
anti-rollback brakes66.00pair66.00each33.00wheel lock extensions26.00pair26.00each13.00Types of forks: standard forks, 15.2 cm (6 in.); short forks, 13.3 cm ($5^{1}/_4$ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheelsN/C15.2 cm (6 in.) and 20.3 cm (8 in.) wheelsN/C31.00fork stems, + 1.9 cm ($^{3}/_4$ in.) or + 3.8 cm ($1^{1}/_2$ in.)N/C32.50	Wheel locks:		
pair 66.00 each 33.00 wheel lock extensions 26.00 pair 26.00 each 13.00 Types of forks: standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork stems, + 1.9 cm (³ / ₄ in.) or + 3.8 cm (1 ¹ / ₂ in.) N/C 16.00 Rear axles: quick-release axles N/C 32.50		N/C	39.00
wheel lock extensions 26.00 pair 26.00 each 13.00 Types of forks: standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork stems, + 1.9 cm ($^{3}/_{4}$ in.) or + 3.8 cm (1 ¹ / ₂ in.) N/C 32.50		66.00	
pair 26.00 each 13.00 Types of forks: standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork stems, + 1.9 cm ($^{3}/_{4}$ in.) or + 3.8 cm (1 ¹ / ₂ in.) N/C 31.00 Rear axles: quick-release axles N/C 32.50			33.00
each 13.00 Types of forks: standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C fork stems, + 1.9 cm ($^{3}/_{4}$ in.) or + 3.8 cm (1 ¹ / ₂ in.) Rear axles: quick-release axles N/C 32.50		26.00	
standard forks, 15.2 cm (6 in.); short forks, 13.3 cm $(5^{1}/_{4} \text{ in.})$; or high forks, 15.2 cm (6 in.); short forks, 13.3 cm $(5^{1}/_{4} \text{ in.})$; or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork stems, + 1.9 cm $(^{3}/_{4} \text{ in.})$ or + 3.8 cm $(1^{1}/_{2} \text{ in.})$ N/C 16.00 Rear axles: quick-release axles N/C 32.50			13.00
or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork stems, + 1.9 cm ($^{3}/_{4}$ in.) or + 3.8 cm ($1^{1}/_{2}$ in.) N/C 16.00 Rear axles: quick-release axles N/C 32.50			
15.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 31.00 fork stems, + 1.9 cm ($^{3}/_{4}$ in.) or + 3.8 cm ($1^{1}/_{2}$ in.) N/C 16.00 Rear axles: quick-release axles N/C 32.50			
fork stems, + $1.9 \text{ cm} ({}^{3}/_{4} \text{ in.}) \text{ or } + 3.8 \text{ cm} (1{}^{1}/_{2} \text{ in.})$ N/C 16.00 Rear axles:			
Rear axles: quick-release axlesN/C32.50			
quick-release axles N/C 32.50	fork stems, + 1.9 cm $({}^{3}/_{4}$ in.) or + 3.8 cm $({}^{1}/_{2}$ in.)	N/C	16.00
rear-wheel camber 112.00 N/A			
	rear-wheel camber	112.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
rear mag wheels, standard pressure, 30.5 cm (12 in.) rear mag wheels, standard pressure, 55.9 cm (22 in.)	N/C	126.00
or $61.0 \text{ cm} (24 \text{ in.})$	N/C	110.00
rear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C N/C	132.00
rear mag wheels, standard pressure, 40.6 cm (16 in.)		152.00
pair	32.00	
each		142.00
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	132.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	132.00
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.		
or 61.0 cm (24 in.)	N/C	149.00
spoked rear wheels, standard pressure, 45.7 cm (18 in.)	22.00	
pair	32.00	126.00
each front subcolo collidations 20.2 cm (0 in) y 2.5 cm (1 in)	NIC	126.00
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) front wheels, solid tires, 15.2 cm (6 in.)	N/C N/C	$\begin{array}{c} 61.00 \\ 60.00 \end{array}$
front wheels, solid tires, 15.2 cm (6 m.)	N/C N/C	46.00
front wheels, solid tiles, 12.7 cm (5 iii.) front wheels, inner tube, 15.2 cm (6 iii.) x 3.2 cm ($1^{1}/_{4}$ iii.)	N/C N/C	40.00 60.00
front wheels, inner tube, 10.2 cm (0 in.) x 5.2 cm (1 7_4 in.) front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	00.00
pair	47.00	
each	47.00	69.50
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm (1 ¹ / or 15.2 cm (6 in.) x 3.8 cm (1 ¹ / ₂ in.)	/ ₂ in.)	07.50
pair	80.00	
each		86.00
front wheels, semi-pneumatic tires, $20.3 \text{ cm} (8 \text{ in.}) \times 3.8 \text{ cm} (1^{1}/2)$		
pair	100.00	
each		96.00
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4} in.)$	N/C	61.00
Component(s) under Special Consideration		
reclining back, including tension bar*	414.00	N/A
spoke guards*		1.1/1.1
pair	67.00	
each	01.00	33.50
contracture footrests*	295.00	387.00
seat frame for contracture footrests*	128.00	N/A

DEVICE FROM: LES ÉQUIPEMENTS ADAPTÉS PHYSIPRO INC.

POSITIONING BASE, ADULT, "CARDINAL" MODEL

Basic Component(s)

Body support system

- folding back, angle-adjustable, height of 43.2 cm (17 in) to 55.9 cm (22 in.)
- seat structure, width-adjustable from 38.1 cm (15 in.) to 61.1 cm (24 in.), and depth-adjustable from 40.6 cm (16 in.) to 55.9 cm (22 in.)
- rocker device for seat and back, from -10° to $+35^{\circ}$
- seat height: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- "U"-shaped push handles, straight
- safety belt, velcro-type, auto-type

Armrests

- "T"-type armrests, detachable, flip-back, height-adjustable from 21.6 cm (8¹/₂ in.) to 34.3 cm (13¹/₂ in.), short, or "T"-type armrests, detachable, flip-back, height-adjustable from 29.2 cm (11¹/₂ in.) to 39.4 cm (15¹/₂ in.), long
- straight armrest pads, short, long
- rigid clothing guards

Footrests

- 60°, 70°, 75° footrests, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 40.6 cm (16 in.)
- heel loops, length-adjustable
- folding footplates, standard
- · padded calfrests
- modification of footrest length

Wheels and frame

- standard wheel locks, push-to-lock
- standard forks
- threaded axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)
- anti-tip rollers
- tie-down points for adapted transport
- smooth handrims for 50.8 cm (20 in.), 55.9 cm (22 in.) and 61.0 cm (24 in.) wheels

PRICE

\$1 760.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
"U"-shaped push handles, straight	N/C	N/A
safety belt, velcro-type	N/C	18.00
safety belt, auto-type	N/C	48.00
rocker device for seat and back, from -10° to $+35^{\circ}$	N/C	N/A
rigid seat, flat, grooved and adjustable	92.00	92.00
back tension bar	118.00	118.00
headrest, small, medium, large	95.00	95.00
headrest bracket	135.00	135.00
crossbar for headrest bracket	210.00	210.00
basic growth kit	78.00	78.00
folding back, angle-adjustable, height of 43.2 cm (17 in.)		
to 55.9 cm (22 in.)	N/C	N/A
Armrests :		
"T"-type armrests, detachable, flip-back, height-adjustable		
from 21.6 cm ($8^{1}/_{2}$ in.) to 34.3 cm ($13^{1}/_{2}$ in.), short, or		
"T"-type armrests, detachable, flip-back, height-adjustable		
from 29.2 cm $(11^{1}/_{2} \text{ in.})$ to 39.4 cm $(15^{1}/_{2} \text{ in.})$, long	N/C	186.00
straight armrest pads, short	N/C	26.00
straight armrest pads, long	N/C	28.00
rigid clothing guards	N/C	14.00
Footrests:		
60°, 70° or 75° footrests detachable, swingaway, length-adjustable	NIG	00.00
from 27.9 cm (11 in.) to 40.6 cm (16 in.)	N/C	99.00
90° footrests, detachable, swingaway, length-adjustable		
from 27.9 cm (11 in.) to 40.6 cm (16 in.)	(0.00	
pair	60.00	120.00
each		129.00
elevating legrests, detachable, swingaway, length-adjustable	376.30	
pair each	370.30	287.30
"H"-shaped calf strap	45.00	45.00
single calf strap	43.00	43.00
double calf strap	55.00	55.00
single calf strap, cushioned	80.00	80.00
double calf strap, cushioned	95.00	95.00
folding footplates, standard	95.00 N/C	40.00
folding footplates, standard		40.00
pair	70.00	
each	70.00	75.00
folding footplates, oversized, angle-adjustable and depth-adjustable	a	75.00
non-skid	υ,	
pair	100.00	
	100.00	90.00
each		

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
folding footplate, full-width, angle-adjustable and depth-adjust	able,	
non-skid	140.00	110.00
heel loops, length-adjustable	N/C	12.00
toe loops		
pair	20.00	22.00
each	N/C	22.00
modification of footrest length contoured calfrests	N/C	40.00
pair	36.00	
each	50.00	48.00
badded calfrests	N/C	30.00
Front impact guard with roller		
pair	80.00	
each		40.00
Wheels and frame		
Types of drive systems :		
neavy-duty frame	180.00	N/A
smooth handrims for 50.8 cm (20 in.), 55.9 cm (22 in.)	N/C	45.00
and 61.0 cm (24 in.) wheels plastic-coated handrims	N/C	45.00
pair	60.00	
each	00.00	75.00
ion-slip handrims		
pair	70.00	
each		80.00
andrims with vertical, oblique or horizontal projections		
pair	158.00	124.00
each	N/C	124.00 43.00
anti-tip rollers	IN/C	45.00
Wheel locks:		55.00
tandard, push-to-lock wheel lock extensions	N/C	55.00
bair	30.00	
each	20.00	15.00
nti-rollback brakes		
pair	104.00	
each		52.00
Types of forks :		
standard forks	N/C	56.00
	100	50.00
Rear axles:		
hreaded axles	N/C	6.00
blates with hardware for 50.8 cm (20 in.), 55.9 cm (22 in.)		
and 61.0 cm (24 in.) wheels		

and 61.0 cm (24 in.) wheels pair each

1804

78.00

156.00

Types of wheels: rear mag wheels, standard pressure, 30.5 cm (12 in.)	N/C	
rear mag wheels, standard pressure, 30.5 cm (12 in.)	N/C	
rear mag wheels, standard pressure, 50.8 cm (12 m.)		76.00
pair	98.00	
each rear mag wheels, standard pressure, 55.9 cm (22 in.)		125.00
or 61.0 cm (24 in.)		
pair	78.00	
each		115.00
rear mag wheels, solid tires, 30.5 cm (12 in.) pair	40.00	
each	10.00	96.00
rear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)		
pair each	78.00	115.00
rear mag wheels, solid tires, 50.8 cm (20 in.)		115.00
pair	98.00	
each		125.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.) pair	98.00	
each	90.00	125.00
spoked rear wheels, standard pressure, 55.9 cm (22 in.)		
pair each	78.00	115.00
spoked rear wheels, standard pressure, 61.0 cm (24 in.)		115.00
pair	78.00	
each		115.00
spoked rear wheels, solid tires, 50.8 cm (20 in.)	98.00	
each	20.00	125.00
spoked rear wheels, solid tires, 55.9 cm (22 in.)		
bair each	78.00	115.00
spoked rear wheels, solid tires, 61.0 cm (24 in.)		115.00
pair	78.00	
		115.00
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)	N/C	35.00
Front wheels, inner tube, $20.3 \text{ cm} (8 \text{ in.}) \times 5.1 \text{ cm} (2 \text{ in.})$	100	55.00
pair	60.00	1
each front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm (1 ¹ / ₄ in.)		65.00
or 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.)		
pair	40.00	
each	-)	55.00
Front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 ir pair	1.) 60.00	
each	00.00	65.00
Front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 17.8 cm (7 for 15.2 cm (6 in.) x 2.5 cm (1 in.)	in.)	
pair	40.00	
each		55.00

Part 2

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
quick-release axles* pair each	98.00	55.00
reclining back with cylinder* spoke guards*	280.00	280.00
pair each	90.00	45.00
DEVICE FROM: PRODUCT DESIGN GROUP INC.		
		PRICE
POSITIONING BASE, ADULT, "STELLAR" MODEL		\$1 746.14
Basic Component(s)		
 Body support system seat height: from 35.6 cm (14 in.) to 50.8 cm (20 in.) seat widths: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.) seat depths: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.) back height: from 45.7 cm (18 in.) to 58.4 cm (23 in.) rocker device for seat and back push handles safety belt, auto-type 		
 Armrests "T"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 40.6 cm (16 in.), short, long "L"-type armrests, short, long contoured armrest pads, short, long 		
 Footrests 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 33.0 cm (13 in.) to 48.3 cm (19 in.) padded calfrests heel loops, length-adjustable folding footplates, standard modification of length of footrests or legrests by + 5.1 cm (2 in.) 		

Wheels and frame

- standard wheel locks, push-to-lock, pull-to-lock
- standard forks, short forks
- · threaded axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 40.6 cm (16 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 30.5 cm (12 in.), 40.6 cm (16 in.),
- 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 12.7 cm (5 in.)
- anti-tip rollers
- anodized aluminum handrims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
rigid seat, flat	36.00	36.00
rocker device for seat and back	N/C	N/A
push handles	N/C	84.00
headrest bracket, fixed, universal	12.00	12.00
headrest extension, 25.4 cm (10 in.) high	60.00	60.00
attendant and user-controlled tilt	32.64	32.64
modification of seat width to 53.3 cm (21 in.) or to 55.9 cm (22 in.)		N/A
modification of seat depth to 53.3 cm (21 in.) or to 55.9 cm (22 in.)	96.00	96.00
safety belt, four-point	53.28	72.48
safety belt, auto-type	N/C	19.20
supple back, nylon	60.00	60.00
Armrests :		
"L"-type armrests, short, long "T"-type armrests, detachable, height-adjustable,	N/C	82.56
from 25.4 cm (10 in.) to 40.6 cm (16 in.), short, long	N/C	82.56
contoured armrest pads, long	N/C	9.60
contoured armrest pads, short	N/C	8.64
modification of armrest height by + 7.6 cm (3 in.)	23.52	23.52

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests :		
60° or 70 footrests, parallel, detachable, swingaway, length-adjustable from 33.0 cm (13 in.) to 48.3 cm (19 in.) 70° footrests, inward-pointing, detachable, swingaway,	N/C	70.80
length-adjustable from 33.0 cm (13 in.) to 48.3 cm (19 in.) pair	14.40	
each elevating legrests, detachable, swingaway, length-adjustable pair	170.40	78.00
each elevating legrests, compensating mechanism, detachable,	170.10	156.00
swingaway, length-adjustable pair	213.60	
each modification of length of footrests or legrests by + 5.1 cm (2 in.) padded calfrests	N/C N/C	177.60 30.24 19.20
single calf strap folding footplates, standard	23.52 N/C	23.52 17.28
folding footplates, oversized pair each	57.60	46.08
oversized footplates, angle-adjustable and depth-adjustable pair	74.40	40.08
each heel loops, length-adjustable	N/C	54.48 11.28
Wheels and frame		
Types of drive systems: anodized aluminum handrims	N/C	16.32
plastic-coated handrims pair	113.28	10102
each anti-tip rollers	N/C	41.80 31.20
Wheel locks:	N/C	42.24
standard, push-to-lock or pull-to-lock wheel lock extensions pair	N/C 28.80	42.24
each	20.00	14.40
Types of forks : standard forks	N/C	30.24
short forks	N/C	77.76
Rear axles: threaded axles	N/C	1.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
rear mag wheels, standard pressure, 40.6 cm (16 in),		
50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	114.72
rear mag wheels, standard pressure, 30.5 cm (12 in.)	N/C	68.64
rear mag wheels, solid tires, 30.5 cm (12 in.)	N/C	70.56
rear mag wheels, solid tires, 61.0 cm (24 in.)	N/C	104.16
rear mag wheels, solid tires, 40.6 cm (16 in.), 50.8 cm (20 in.),		
55.9 cm (22 in.)	N/C	96.48
front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm (1 ¹ / ₄ in.)	N/C	29.28
front wheels, solid tires, 12.7 cm (5 in.)	N/C	15.84
front wheels, solid tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
pair	60.00	
each		59.28
Component(s) under Special Consideration		
reclining back*	384.00	384.00
quick-release axles*		
pair	29.76	
each		15.84
DEVICE FROM: ADVANCED MOBILITY SYSTEMS CORI	PORATION	
		PRICE
		PRICE
POSITIONING BASE, ADULT, "TCR" MODEL		\$1 922.00
Basic Component(s)		
Body support system		
• seat height: from 38.1 cm (15 in.) to 44.5 cm $(17^{1}/_{2} \text{ in.})$		
• seat widths: 35.6 cm (14 in.), 40.6 cm (16 in.), 45.7 cm (18 in.),		
50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)		
• seat depth: from 35.6 cm (14 in.) to 50.8 cm (20 in.)		
• back height: from 45.7 cm (18 in.) to 61.0 cm (24 in.)		
 rocker device for seat and back 		
• push handles		
• safety belt, auto-type, velcro-type		
• rig seat, flat		
• rigid seat, contoured		
• rigid back		
• seat cushion, flat, foam, 5.1 cm (2 in.)		
• angle-adjustable back		
headrest with bracket		

· headrest with bracket

Armrests

- "T"-type armrests, detachable, height-adjustable from 20.3 cm (8 in.) to 35.6 cm (14 in.), long, with straight armrest pads
- rigid clothing guards
- armrest adjustment collars

Footrests

- 70° footrests, detachable, swingaway, length-adjustable from 41.9 cm (16¹/₂ in.) to 57.2 cm (22¹/₂ in.)
- folding footplates, standard, with adjustable heel loops
- folding footplates, angle-adjustable, with adjustable heel loops

Wheels and frame

- plastic-coated handrims
- standard wheel locks, push-to-lock
- standard forks, short forks
- threaded axles
- rear mag wheels, solid tires, 40.6 cm (16 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.), 12.7 cm (5 in.) x 3.2 cm (1¹/₄ in.)
- anti-tip rollers
- extended-range caster headtube mountings
- front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
headrest with bracket	N/C	206.00
rigid seat, flat	N/C	99.25
rigid seat, contoured	N/C	126.00
rocker device for seat and back	N/C	117.00
safety belt, velcro-type	N/C	37.80
safety belt, auto-type	N/C	45.00
seat cushion, flat, foam, 5.1 cm (2 in.)	N/C	99.00
angle-adjustable back	N/C N/C	123.00 165.40
rigid back	N/C N/C	165.40 N/A
push handles	N/C	IN/A
Armrests: "T"-type armrests, detachable, height-adjustable from 20.3 cm (8 in to 35.6 cm (14 in.), long, with straight armrest pads "T"-type armrests, detachable, height-adjustable from 20.3 cm (8 in to 25.6 cm (14 in.), abort with straight armrest pade	N/C	72.00
to 35.6 cm (14 in.), short, with straight armrest pads	75.60	
pair each	/3.00	109.80
armrest adjustment collars	N/C	15.00
rigid clothing guards	N/C N/C	22.00
iigia cioning gauras	100	22.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests :		
70° footrests, detachable, swingaway, length-adjustable from 41.9 cm ($16^{1}/_{2}$ in.) to 57.2 cm ($22^{1}/_{2}$ in.)	N/C	83.00
elevating legrests, compensating mechanism, with calfrests pair	145.00	
each	145.00	155.50
single calf strap	45.10	45.10
double calf strap	51.40	51.40
folding footplates, standard, with adjustable heel loops	N/C	21.00
folding footplates, angle-adjustable with adjustable heel loops	N/C	21.00
Wheels and frame		
Types of drive systems :		
plastic-coated handrims	N/C	N/A
anti-tip rollers	N/C	36.00
Wheel locks:		
standard wheel locks, push-to-lock wheel lock extensions	N/C	43.00
pair	102.00	
each	102.00	51.00
Types of forks :		
standard or short forks	N/C	37.00
extended-range caster headtube mountings	N/C	37.00
Rear axles :		
threaded axles	N/C	N/A
Types of wheels:		
rear mag wheels, solid tires, 40.6 cm (16 in.), 50.8 cm (20 in.),		
55.9 cm (22 in.), 61.0 cm (24 in.)	N/C	126.00
rear mag wheels, semi-pneumatic tires, 15.2 cm (6 in.)		
or 12.7 cm (5 in.) x 3.2 cm $(1^{1}/_{4} in.)$	N/C	47.00
front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm (1 ¹ / ₄ in.)	N/C	47.00
Component(s) under Special Consideration		
quick-release axles*		
pair	100.00	
each		50.00

DEVICE FROM: INVACARE CANADA INC.

POSITIONING BASE, CHILD, "SOLARA JR" MODEL

Basic Component(s)

Body support system

- seat height: from 42.5 cm $(16^{3}/_{4} \text{ in.})$ to 48.9 cm $(19^{1}/_{4} \text{ in.})$
- seat widths: 25.4 cm (10 in.), 27.9 cm (11 in.), 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.)
- seat depth: from 30.5 cm (12 in.) to 40.6 cm (16 in.)
- back heights: 50.8 cm (20 in.), 61.0 cm (24 in.)
- rocker device for seat and back, from -10° to $+45^{\circ}$
- · push handles
- push handle, angle-adjustable
- safety belt, velcro-type, auto-type
- · supple back, nylon
- supple back, nylon, reclining
- basic growth kit (once only during first three years from date of purchase, for first user)
- folding back, angle-adjustable

Armrests

- "T"-type armrests, detachable, height-adjustable from 15.2 cm (6 in.) to 25.4 cm (10 in.), from 20.3 cm (8 in.) to 35.6 cm (14 in.), short, long
- "U"-type armrests, fixed height, from 21.6 cm (8¹/₂ in.) to 31.8 cm (12¹/₂ in.), short, long
- "U"-type armrests, detachable, height-adjustable from 21.6 cm (8¹/₂ in.) to 31.8 cm (12¹/₂ in.), short, long
- "I"-type armrests, height-adjustable from 17.8 cm (7 in.) to 30.5 cm (12 in.), short, long
- straight armrest pads, short, long

Footrests

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 44.5 cm (17¹/₂ in.)
- 70° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in) to 41.9 cm (16¹/₂ in.)
- 90° footrests, parallel, detachable, swingaway, length-adjustable from 6.4 cm (2¹/₂ in.) to 23.5 cm (9¹/₄ in.)
- heel loops, non-adjustable
- heel loops, length-adjustable
- folding footplates, standard
- 60° footrests, MFX, detachable, swingaway, length-adjustable from 22.9 cm (9 in.) to 31.8 cm (12¹/₂ in.)
- 70° footrests, MFX, detachable, swingaway, length-adjustable from 14.6 cm (5³/₄ in.) to 29.8 cm (11³/₄ in.)

PRICE

\$1 713.00

Wheels and frame

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock
- · standard forks
- quick-release axles
- · threaded axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- anti-tip rollers
- frame length: 73.7 cm (29 in.), 81.3 cm (32 in.), 86.4 cm (34 in.)
- front wheels, inner tubes, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.)

Price u initial pu or replac of wheel	irchase cement	Price upon replacement of component (unit price)
--	-------------------	---

Basic and Optional Component(s)

Body support system

Seat and back :		
rigid seat, flat	49.00	95.00
rocker device for seat and back, from -10° to $+45^{\circ}$	N/C	N/A
push handles	N/C	38.00
push handles, angle-adjustable	N/C	N/A
safety belt, velcro-type	N/C	50.00
safety belt, auto-type	N/C	40.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
supple back, nylon	N/C	50.00
supple back, nylon, reclining	N/C	75.00
basic growth kit (once only during first three years from date		
of purchase, for first user)	N/C	N/A
folding back, angle-adjustable	N/C	N/A
Armrests :		
"U"-type armrests, detachable, height-adjustable from 21.6 cm $(8^{1}/_{2} \text{ in.})$		
to 31.8 cm $(12^{1}/_{2} \text{ in.})$, short or long	N/C	98.00
"U"-type armrests, fixed height, from 21.6 cm $(8^{1}/_{2} \text{ in.})$		
to 31.8 cm $(12^{1}/_{2} \text{ in.})$, short or long	N/C	66.00
"T"-type armrests, detachable, height-adjustable from 15.2 cm (6 in.)		
to 25.4 cm (10 in.), from 20.3 cm (8 in.) to 35.6 cm (14 in.),		
short or long	N/C	125.00
"I"-type armrests, height-adjustable from 17.8 cm (7 in.)		
to 30.5 cm (12 in.), short or long	N/C	98.00
straight armrest pads, long	N/C	26.00
straight armrest pads, short	N/C	26.00

pair

each

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests :		
60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13 ¹ / ₂ in.) to 44.5 cm (17 ¹ / ₂ in.)	N/C	81.00
70° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm ($13^{1}/_{2}$ in.) to 41.9 cm ($16^{1}/_{2}$ in.) 90° footrests, parallel, detachable, swingaway, length-adjustable	N/C	81.00
from 6.4 cm ($2^{1}/_{2}$ in.) to 23.5 cm ($9^{1}/_{4}$ in.) 60° footrests, MFX, detachable, swingaway, length-adjustable	N/C	135.00
from 22.9 cm (9 in.) to 31.8 cm $(12^{1}/_{2} \text{ in.})$ 70° footrests, MFX, detachable, swingaway, length-adjustable	N/C	153.00
from 14.6 cm ($5^{3}/_{4}$ in.) to 29.8 cm ($11^{3}/_{4}$ in.) 70° footrests, tapered, detachable, swingaway, length-adjustable	N/C	153.00
from 32.4 cm $(12^{3}/_{4} \text{ in.})$ to 41.3 cm $(16^{1}/_{4} \text{ in.})$	107.00	
each		135.00
single calf strap	22.00	34.00
double calf strap	35.00	52.00
folding footplates, standard folding footplates, angle-adjustable and depth-adjustable	N/C	40.00
pair 1 2 3 1 3	72.00	
each		76.00
neel loops, non-adjustable	N/C	5.00
neel loops, length-adjustable neel loops and ankle straps	N/C	12.00
bair	32.00	
each		16.00
Wheels and frame		
Types of drive systems : anodized aluminum handrims, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.) plastic-coated handrims	N/C	34.00
pair	52.00	60.00

155.00

N/C

N/C

N/C

32.00

N/C

55.9 cm (22 in.) or 61.0 cm (2 plastic-coated handrims pair each handrims with oblique or vertical projections each anti-tip rollers frame length: 73.7 cm (29 in.), 81.3 cm (32 in.) or 86.4 cm (34 in.) Wheel locks: standard wheel locks, push-to-lock wheel lock extensions pair

Types of forks:

standard forks

60.00

112.00

48.00

400.00

44.00

16.00

50.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Rear axles: threaded axles quick-release axles	N/C N/C	16.00 53.00
quier refease aries	100	55.00
Types of wheels: rear mag wheels, standard pressure, 30.5 cm (12 in.) rear mag wheels, standard pressure, 50.8 cm (20 in.),	N/C	71.00
55.9 cm (22 in.) or 61.0 cm (24 in.) rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)	N/C	90.00
or 61.0 cm (24 in.) front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.),	N/C	90.00
12.7 cm (5 in.), 15.2 cm (6 in.)	N/C	40.00
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4}$ in.) front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)	N/C	52.00
pair each	48.00	64.00
Component(s) under Special Consideration		
contracture footrest, bilateral-angle adjustable* reclining back*	176.00 496.00	265.00 776.00
DEVICE FROM: SUNRISE MEDICAL CANADA INC.		PRIC
POSITIONING BASE, CHILD, "ZIPPIE TS" MODEL		\$1 665.0
Basic Component(s)		
 Body support system back tension bar on folding base folding back, angle-adjustable back heights: 54.6 cm (21¹/₂ in.), 62.2 cm (24¹/₂ in.), 69.9 cm (27¹/₂ in.), with push handles seat width: from 25.4 cm (10 in.) to 40.6 cm (16 in.) seat depth: from 33.0 cm (13 in.) to 50.8 cm (20 in.) front seat height: from 40.6 cm (16 in.) to 51.4 cm (20¹/₄ in.) safety belt, velcro-type, auto-type raised push handle 		
 Armrests "T"-type armrests, detachable, height-adjustable from 23.5 cm (9¹/₄ in.) to 40.0 cm (15³/₄ in.), short, long "T"-type armrests, detachable, height-adjustable from 14.0 cm (5¹/₂ in.), 16.5 cm (6¹/₂ in.), 19.1 cm (7¹/₂ in.), short straight armrest pads short long 		

- straight armrest pads, short, longtubular armrest pads

Footrests

- 60°, 70° footrests, detachable, swingaway, length-adjustable from 31.1 cm (12¹/₄ in.) to 50.2 cm (19³/₄ in.)
- 70°, 80°, 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- 70°, 80°, 90° footrests, heavy-duty, detachable, non-flip-back
- heel loops, length-adjustable
- folding footplates, standard
- padded calfrests

Wheels and frame

- · anti-tip rollers
- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks 15.2 cm (6 in.); short forks, 13.3 cm (5¹/₄ in.); high forks 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- 17.8 cm (7 in.) forks for 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- fork stems, + 1.9 cm $({}^{3}/_{4}$ in.), + 3.8 cm $({}^{1}/_{2}$ in.)
- quick-release axles
- standard axle plate
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 15.2 cm (6 in.) x 3.2 cm (1¹/₄ in.)
- rocker device, 45°

Price upon	Price upon
initial purchase	replacement of
or replacement	component
of wheel chair	(unit price)

Basic and Optional Component(s)

Body support system

Seat and back:		
headrest, small	90.00	93.00
headrest, medium	96.00	103.00
headrest, large	102.00	107.00
articulated headrest mounting	154.00	168.00
transversal bar for headrest mounting, fixed frame	194.00	206.00
transversal bar for headrest mounting, folding frame	226.00	242.00
back tension bar on folding base	N/C	185.00
folding back, angle-adjustable	N/C	N/A
rigid seat, flat	121.00	126.00
raised push handle	N/C	N/A
back heights: 54.6 cm $(21^{1}/_{2} \text{ in.})$, 62.2 cm $(24^{1}/_{2} \text{ in.})$,		
69.9 cm $(27^{1}/_{2} \text{ in.})$, with push handles	N/C	N/A
safety belt, velcro-type	N/C	28.00
safety belt, auto-type	N/C	41.00
safety belt, airplane-type	49.00	77.00
safety belt, airplane-type, padded	74.00	101.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Ammanata		
Armrests: "T"-type armrests, detachable, height-adjustable from 23.5 cm (9 ¹ / ₄ in.) to 40.0 cm (15 ³ / ₄ in.), short or long	N/C	132.00
"T"-type armrests, detachable, height-adjustable, 14.0 cm ($5^{1}/_{2}$ in.), 16.5 cm ($6^{1}/_{2}$ in.), 19.1 cm ($7^{1}/_{2}$ in.), short "I"-type armrests, flip-back, height-adjustable from	N/C	155.00
16.5 cm ($6^{1}/_{2}$ in.) to 33.0 cm (13 in.), short or long		
pair	126.00	105.00
each		195.00
tubular armrest pads	N/C	2.00
straight armrest pads, long	N/C	17.00
straight armrest pads short rigid clothing guards	N/C	15.00
pair	90.00	
each	0.00	66.00
		00100
Footrests :		
60° or 70° footrests, detachable, swingaway, length-adjustable		
from 31.1 cm ($12^{1}/_{4}$ in.) to 50.2 cm ($19^{3}/_{4}$ in.)	N/C	53.00
70°, 80° or 90° footrests, detachable, swingaway, length-adjustable		
from 20.3 cm (8 in.) to 33.0 cm (13 in.)	N/C	55.00
70°, 80° or 90° footrests, heavy-duty, detachable, non-flip-back	N/C	80.00
90° elevating legrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)		
pair	69.00	
each	07.00	87.00
elevating legrests, detachable, swingaway, length-adjustable		01100
pair	105.00	
each		105.50
modification of footrest length from 48.3 cm (19 in.)		
to 52.1 cm $(20^{1}/_{2} \text{ in.})$	30.00	29.00
modification of footrest length by $+ 5.1 \text{ cm} (2 \text{ in.})$	20.00	15.00
or by $+10.2 \text{ cm} (4 \text{ in.})$	30.00	15.00
single calf strap	18.00 N/C	18.00 48.00
folding footplates, standard folding footplates, angle-adjustable, standard	IN/C	48.00
pair	51.00	
each	51.00	73.50
full-width footplate, angle-adjustable	83.00	179.00
full-width footplate, 90°, rigid	89.00	185.00
footrest mountings, from 17.8 cm (7 in.) to 34.3 cm $(13^{1}/_{2} \text{ in.})$		
pair	54.00	
each		33.00
heel loops, length-adjustable	N/C	10.00
padded calfrests	N/C	18.00
contoured calfrests	70.00	
pair each	70.00	53.00
00011		55.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems :		
one-arm dual handrim drive	546.00	688.00
anodized aluminum handrims, 50.8 cm (20 in.),	N/C	59.00
55.9 cm (22 in.) or 61.0 cm (24 in.) handrims with oblique or vertical projections	N/C	58.00
pair	88.00	
each	00.00	102.00
plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)		
pair	54.00	05.00
each non slin handrims $55.0 \text{ am} (22 \text{ in})$ or $61.0 \text{ am} (24 \text{ in})$		85.00
non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) pair	164.00	
each	101.00	140.00
plastic-coated handrims for one-arm drive	54.00	N/A
anti-tip rollers	N/C	22.00
front anti-tippers		
pair	55.00	27.50
each cane holder	44.00	$27.50 \\ 44.00$
optional folding base	105.00	44.00 N/A
rocker device, 45°	N/C	N/A
·		
Wheel locks:		
standard, push-to-lock or pull-to-lock	N/C	39.00
wheel lock extensions pair	26.00	
each	20.00	13.00
anti-rollback brakes		12.00
pair	66.00	
each		33.00
Types of forks : standard forks, $15.2 \text{ cm} (6 \text{ in.})$; short forks, $13.3 \text{ cm} (5^{1}/_{4} \text{ in.})$;		
or high forks 17.8 cm (7 in.), compatible with 12.7 cm (5 in.),		
15.2 cm (6 in.) and 20.3 cm (8 in.) wheels	N/C	31.00
17.8 cm (7 in.) forks for 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels	N/C	36.00
fork-locking mechanisms		
pair	44.00	•• • • •
each	NUC	22.00
fork stems, + 1.9 cm $(\frac{3}{4} \text{ in.})$ or + 3.8 cm $(1\frac{1}{2} \text{ in.})$	N/C	16.00
Rear axles:		
quick-release axles	N/C	32.50
axle extension plates		
pair	44.00	
each	1.1.0	50.00
standard axle plate	N/C	28.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
rear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C	132.00
rear mag wheels, standard pressure, 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	110.00
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	132.00
rear mag wheels, standard pressure, 30.5 cm (12 in.)	N/C	126.00
ear mag wheels, standard pressure, 40.6 cm (16 in.)		
bair	32.00	
each		142.00
Front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)	N/C	61.00
Front wheels, solid tires, 15.2 cm (6 in.)	N/C	60.00
Front wheels, solid tires, 12.7 cm (5 in.)	N/C	46.00
ront wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
bair	47.00	
each		69.50
Front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4} \text{ in.})$	N/C	61.00
Front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm $(1^{1}/_{4}$ in.)	N/C	60.00
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm (1 or 15.2 cm (6 in.) x 3.8 cm $(1^{1}/_{2}$ in.)	¹ / ₂ in.)	
bair	80.00	
each		86.00
Front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1	$1/_{2}$ in.)	
bair	100.00	
each		96.00

POSITIONING BASE, CHILD, "ROSSIGNOL" MODEL

Basic Component(s)

Body support system

- folding back, angle-adjustable, height of 43.2 cm (17 in.) to 55.9 cm (22 in.)
- seat structure, width-adjustable from 30.5 cm (12 in.) to 40.6 cm (16 in.) and depth-adjustable from 26.7 cm ($10^{1}/_{2}$ in.) to 40.6 cm (16 in.)
- rocker device for seat and back, from 10° to + 35°
- seat height: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- push handles
- safety belt, velcro-type, auto-type

Armrests

- "T"-type armrests, detachable, flip-back, height-adjustable from 19.1 cm (7¹/₂ in.) to 29.2 cm (11¹/₂ in.), short, or height-adjustable from 29.2 cm (11¹/₂ in.) to 39.4 cm (15¹/₂ in.), long
- straight armrest pads, short, long
- rigid clothing guards

PRICE

\$1 585.00

Footrests

- 60°, 70°, 75°, 90° footrests, detachable, swingaway, length-adjustable from 14.0 cm (5¹/₂ in.) to 31.8 cm (12¹/₂ in.)
- heel loops, length-adjustable
- folding footplates, standard
- padded calfrests

Wheels and frame

- standard wheel locks, push-to-lock
- · standard forks
- · threaded axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.),
- 15.2 cm (6 in.), 12.7 cm (5 in.)
- anti-tip rollers
- tie-down points for adapted transport
- smooth handrims for 50.8 cm (20 in.) and 55.9 cm (22 in.) wheels

Price upon initial purchase	Price upon replacement of
or replacement of wheel chair	component (unit price)

Basic and Optional Component(s)

Body support system

Seat and back :		
folding back, angle-adjustable, height of 43.2 cm (17 in.)		
to 55.9 cm (22 in.)	N/C	N/A
push handles	N/C	N/A
safety belt, velcro-type	N/C	18.00
safety belt, auto-type	N/C	48.00
rocker device for seat and back, from -10° to $+35^{\circ}$	N/C	N/A
rigid seat, flat	92.00	92.00
rigid back	92.00	92.00
headrest, small, medium, large	95.00	95.00
headrest bracket	135.00	135.00
crossbar for headrest bracket	210.00	210.00
back tension bar	118.00	118.00
basic growth kit	78.00	78.00
Armrests: "T"-type armrests, detachable, flip-back, height-adjustable from 10.1 am (71/ in) to 20.2 am (111/ in) short or		
from 19.1 cm $(7^{1}/_{2} \text{ in.})$ to 29.2 cm $(11^{1}/_{2} \text{ in.})$, short, or height-adjustable from 29.2 cm $(11^{1}/_{2} \text{ in.})$ to 39.4 cm $(15^{1}/_{2} \text{ in.})$, long	N/C	186.00
straight armrest pads, short	N/C N/C	26.00
	N/C N/C	28.00
straight armrest pads, long	N/C N/C	28.00 14.00
rigid clothing guards	IN/C	14.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests :		
60°, 70°, 75° or 90° footrests, detachable, swingaway,		
length-adjustable from 14.0 cm $(5^{1}/_{2} \text{ in.})$ to 31.8 cm $(12^{1}/_{2} \text{ in.})$ elevating legrests, detachable, swingaway, length-adjustable	N/C	99.00
pair	376.30	
each		287.30
padded calfrests	N/C	30.00
contoured calfrests		
pair	36.00	
each		48.00
single calf strap	43.00	43.00
double calf strap	55.00	55.00
single calf strap, cushioned	80.00	80.00
double calf strap, cushioned	95.00	95.00
"H-" shaped calf strap	45.00	45.00
front impact guard with roller	80.00	40.00
folding footplates, standard	N/C	40.00
folding footplates, angle-adjustable and depth-adjustable, non-skid		
pair	70.00	77.00
each		75.00
folding footplates, oversized, angle-adjustable and		
depth-adjustable, non-skid	100.00	
pair each	100.00	90.00
folding footplate, full-width, angle-adjustable and		90.00
depth-adjustable, non-skid	140.00	110.00
heel loops, length-adjustable	N/C	12.00
toe loops	N/C	12.00
pair	20.00	
each	20.00	22.00
cach		22.00
Wheels and frame		
Types of drive systems:		
smooth handrims for 50.8 cm (20 in.) and 55.9 cm (22 in.) wheels	N/C	45.30
plastic-coated handrims		
pair	60.00	
each		75.00
non-slip handrims		
pair	70.00	
each		80.00
handrims with vertical, oblique or horizontal projections		
pair	158.00	
each		124.00
anti-tip rollers	N/C	43.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks:		
standard, push-to-lock	N/C	55.00
wheel lock extensions pair	30.00	
each	50.00	15.00
anti-rollback brakes		10100
pair	104.00	
each		52.00
Types of forks :		
standard forks	N/C	56.00
Rear axles:		
threaded axles	N/C	6.00
plates with hardware for 50.8 cm (20 in.) and 55.9 cm (22 in.) wheels	156.00	78.00
Frame:		
tie-down points for adapted transport	N/C	N/A
heavy-duty frame	180.00	N/A
Types of wheels:		
rear mag wheels, standard pressure, 30.5 cm (12 in.)	N/C	76.00
rear mag wheels, standard pressure, 50.8 cm (20 in.)	(0.00	
pair each	68.00	125.00
cach		125.00
rear mag wheels, standard pressure, 55.9 cm (22 in.)	70.00	
pair each	78.00	115.00
rear mag wheels, solid tires, 50.8 cm (20 in.)		115.00
pair	98.00	
each		125.00
rear mag wheels, solid tires, 30.5 cm (12 in.)	40.00	
pair each	40.00	96.00
rear mag wheels, solid tires, 55.9 cm (22 in.)		90.00
pair	78.00	
each		115.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.)	00.00	
pair	98.00	125.00
each spoked rear wheels, standard pressure, 55.9 cm (22 in.)		125.00
pair	78.00	
each	, 0.00	115.00
spoked rear wheels, solid tires, 50.8 cm (20 in.)		•
pair	98.00	
each		125.00
spoked rear wheels, solid tires, 55.9 cm (22 in.)	78.00	
pair	/ 0.00	

 pair
 78.00

 each
 115.00

 front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.),
 15.2 cm (6 in.) or 12.7 cm (5 in.)

 N/C
 35.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4}$ in.)		
or 15.2 cm (6 in.) x 3.2 cm $(1^{1}/_{4} in.)$ pair	40.00	
each front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)		55.00
pair	60.00	65 00
each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)		65.00
pair each	60.00	65.00
front wheels, semi-pneumatic tires, 15.2 cm (6 in.), 17.8 cm (7 in.)		
or 20.3 cm (8 in.) x 2.5 cm (1 in.) pair	40.00	
each		55.00
Component(s) under Special Consideration		
quick-release axles*		
pair each	98.00	55.00
reclining back with cylinder* spoke guards*	280.00	280.00
pair	90.00	17.00
each		45.00
DIVISION III STROLLERS		
DEVICE		PRICE
"Buggy Major"-type stroller, including footrests and harness		(00.00
less than three years of age* three years of age and over		600.00 600.00
Available Component(s)		
padded seat		90.00
other components thoracic support		S.C. 96.00
chest pad		48.00
DURATION OF GUARANTEE: 12 months		
DEVICE		

Other strollers*

S.C.

Draft Regulations

Draft Regulation

An Act respecting collective agreement decrees (R.S.Q., c. D-2)

Automotive Services — Drummond and Mauricie regions — Amendments

Notice is hereby given, in accordance with section 5 of the Act respecting collective agreement decrees (R.S.Q., c. D-2), that the Minister of Labour has received an application from the contracting parties to amend the Decree respecting the automotive services industry in the Drummond and Mauricie regions (R.R.Q., 1981, c. D-2, r.45) and, that under sections 10 and 11 of the Regulations Act (R.S.Q., c. R-18.1), the Decree to amend the Decree respecting the automotive services industry in the Drummond and Mauricie regions, the text of which appears below, may be made by the Government upon the expiry of the 45 days following this publication.

The purpose of this draft regulation is to update the designation of one of the contracting parties and also the geographical designation of the territorial jurisdiction, to raise the wage rates of each of the trades, to add an item to the pay voucher, and to extend the term of the Decree.

To that end, it proposes to amend the designation of one of the union contracting parties, to update, following amendments to the territorial organization, the list of the municipalities whose territory is governed by the territorial jurisdiction of the Decree, to raise wage rates by about 3%, to prescribe a new item to be added to the employee's pay voucher and extend the term of the Decree until 31 December 2004, while maintaining the automatic renewal clause.

The consultation period will clarify the impact of the amendments sought. According to the 2002 annual report of the Comité paritaire de l'industrie de l'automobile de la Mauricie, the Decree governs 551 employers, 252 artisans and 2 757 employees.

Further information may be obtained by contacting Mr. Michel Roberge, Direction des politiques, de la construction et des décrets, ministère du Travail, 200, chemin Sainte-Foy, 6^e étage, Québec (Québec) G1R 5S1, telephone : (418) 528-9701, fax : (418) 528-0559, e-mail : michel.roberge@travail.gouv.qc.ca

Any interested person with comments to make is asked to send them in writing, before the expiry of that date, to the Deputy Minister of Labour, 200, chemin Sainte-Foy, 6^e étage, Québec (Québec) G1R 5S1.

ROGER LECOURT, Deputy Minister of Labour

Decree to amend the Decree respecting the automotive services industry in the Drummond and Mauricie region^{*}

An Act respecting collective agreement decrees (R.S.Q., c. D-2, s. 2 et 6.1)

1. Section 1.02 of the Decree respecting the automotive services industry in the Drummond and Mauricie regions is amended by substituting, in paragraph 2, "section locale 4511" for "section locale 4298".

2. Section 2.02 of the Decree is replaced by the following:

"2.02. Territorial jurisdiction : The Decree applies within the boundaries of the following regional county municipalities included in administrative regions 04 – Mauricie and 17 – Centre du Québec :

Region 04 - Mauricie

1° Ville de Shawinigan, Ville de Trois-Rivières.

2° Regional county municipality of Chenaux: Batiscan, Champlain, Parish of Notre-Dame-du-Mont-Carmel, Sainte-Anne-de-la-Pérade, Parish of Sainte-Geneviève-de-Batiscan, Saint-Luc-de-Vincennes, Parish of Saint-Maurice, Parish of Saint-Narcisse, Parish of Saint-Prosper, Saint-Stanislas.

^{*} The Decree respecting the automotive services industry in the Drummond and Mauricie regions (R.R.Q., 1981, c. D-2, r.45) was last amended by the Regulation made by Order in Council No. 560-2001 dated 9 May 2001 (2001, *G.O.* 2, 2282). For previous amendments, please refer to the *Tableau des modifications et Index sommaire*, Éditeur officiel du Québec, 2003, updated to 1 March 2003.

3° Regional county municipality of Maskinongé: Charette, Town of Louiseville, Maskinongé, Parish of Saint-Alexis-des-Monts, Sainte-Angèle-de-Prémont, Parish of Saint-Barnabé, Saint-Boniface, Saint-Édouardde-Maskinongé, Parish of Saint-Elie, Parish of Saint-Étienne-des-Grès, Parish of Saint-Justin, Parish of Saint-Léon-le-Grand, Saint-Mathieu-du-Parc, Saint-Paulin, Parish of Saint-Sévère, Parish of Sainte-Ursule, Yamachiche.

4° In the regional county municipality of Mékinac: Village of Grandes-Piles, Parish of Hérouxville, Parish of Lac-aux-Sables, Parish of Saint-Adelphe, Parish of Saint-Séverin, Sainte-Thècle, Town of Saint-Tite.

Region 17 - Centre du Québec

1. In the regional county municipality of Arthabaska: Parish of Saint-Samuel.

2. In the regional county municipality of Bécancour: Town of Bécancour, Lemieux, Manseau, Parish of Sainte-Cécile-de-Lévrard, Sainte-Marie-de-Blandford, Saint-Pierre-les-Becquets, Parish of Sainte-Sophie-de-Lévrard, Saint-Sylvère.

3. In the regional county municipality of Drummond: Ville de Drummondville, Durham-Sud, L'Avenir, Lefebvre, parish and village of Notre-Dame-du-Bon-Conseil, Parish of Sainte-Brigitte-des-Saults, Saint-Charles-de-Drummond, Saint-Cyrille-de-Wendover, Saint-Félix-de-Kinsey, Saint-Germain-de-Grantham, Parish of Saint-Joachim-de-Courval, Parish of Saint-Lucien, Parish of Saint-Majorique-de-Grantham, Town of Saint-Nicéphore, Wickham.

4. In the regional county municipality of Nicolet-Yamaska: Aston-Jonction, Grand-Saint-Esprit, Town of Nicolet, Village of Saint-Célestin, Saint-Célestin, Parish of Saint-Edmond-de-Grantham, Saint-Eugène, Sainte-Eulalie, Saint-Léonard-d'Aston, Sainte-Monique, Parish of Sainte-Perpétue, Saint-Wenceslas.".

3. Sections 6.01.1 and 6.01.2 of the Decree are revoked.

4. Section 8.01 of the Decree is amended by deleting, in paragraph 6, the words, "the father, mother".

5. Section 9.01 of the Decree is replaced by the following:

"9.01. The minimum hourly wage rates are the following:

Trades	As of (insert the date of the coming into force of the Decree)
1. clerk's helper: Grade 1 Grade 2 Grade 3 Grade 4	\$8.05 \$8.65 \$9.30 \$9.90;
2. apprentice:1st year2nd year3rd year4th year	\$8.25 \$8.80 \$9.30 \$9.80;
3. Journeyman: A B C	\$15.45 \$13.40 \$12.40;
4. Parts Clerk : Grade 1 Grade 2 Grade 3 Grade 4 Grade 5 Grade 6 Grade 7	\$8.05 \$8.65 \$9.30 \$9.90 \$10.55 \$11.15 \$11.75;
5. Messenger:	\$7.55;
6. Dismantler: Grade 1 Grade 2 Grade 3	\$8.25 \$8.80 \$9.55;
7. Washer:	\$7.35;
8. Semiskilled Worker: Grade 1 Grade 2 Grade 3	\$8.80 \$9.55 \$10.30;
9. Pump attendant:	\$7.30;
10. Service Attendant: Grade 1 Grade 2 Grade 3 Grade 4 Grade 5	\$8.00 \$8.50 \$9.05 \$9.55 \$10.05.".

6. Section 9.03 of the Decree is amended by inserting, after paragraph 6, the following:

"6.1 the number of hours for a general statutory holiday, paid, cumulated or replaced by a compensatory leave;".

7. Section 12.01 of the Decree is substituted by the following:

"12.01. The Decree remains in force until 31 December 2004. It is automatically renewed from year to year, unless the group constituting the employer contracting party or the union contracting party opposes it by sending a written notice to the Minister of Labour and to all the contracting parties comprising the employer contracting party or the union contracting party, during the month of June 2004 or during the month of June of any subsequent year.".

8. The Decree comes into force on the date of its publication in the *Gazette officielle du Québec*.

5749

Decisions

Decision, 25 April 2003

Election Act (R.S.Q., c. E-3.3)

Chief electoral officer — Electoral division of Champlain — Holding of a new election

WHEREAS order-in-council number 370-2003, issued on March 12, 2003, enjoined the chief electoral officer to hold general elections in Québec on April 14, 2003;

WHEREAS an election was held in accordance with the said order-in-council on April 14 in all electoral divisions, including the electoral division of Champlain;

WHEREAS a judicial recount took place in the electoral division of Champlain, under the chairmanship of Judge Richard Poudrier, a judge of the Court of Québec;

WHEREAS, on April 23, 2003, following the judicial recount, Judge Poudrier enumerated the votes expressed in favour of each candidate and certified the results of the poll;

WHEREAS, following the judicial recount, there was a tie vote between the first two candidates;

WHEREAS section 394 of the Election Act (R.S.Q., c. E-3.3) provides that, in the case of a tie vote, a new election must be held;

WHEREAS, pursuant to the provisions of the said section, nominations shall be filed not later than the second Monday following the day of the judge's decision, and the poll shall be held on the second subsequent Monday;

WHEREAS section 131 of the Election Act provides that, if polling day falls on a holiday, the poll shall be held on the following day;

WHEREAS, accordingly, nominations must be filed not later than 2:00 p.m. on May 5, 2003, at the office of the returning officer of the electoral division of Champlain, and the poll shall be held on May 20, 2003; WHEREAS section 394 of the Election Act does not provide for all the terms and conditions of the new election, and it is appropriate to adapt the provisions of the Act due to the exceptional circumstances of the tie vote;

WHEREAS section 490 of the Election Act allows the chief electoral officer to adapt a provision of the Act where he observes that, subsequent to an exceptional circumstance, it does not meet the demands of the situation;

WHEREAS the chief electoral officer has informed the authorized parties represented in the National Assembly of his intention to use the provisions of the said section, and has taken the steps required to inform the other authorized parties, the candidates and the electors in question;

The chief electoral officer, pursuant to the powers conferred upon him by section 490 of the Election Act, has decided to adapt the provisions of the Election Act as follows:

— The election period began on April 24, 2003, and shall end on May 20, 2003, at the time at which the polling stations close;

— For this election, there shall be no period during which publicity is prohibited pursuant to section 429.1 of the Election Act;

— Given that the deadlines stipulated in the Election Act must be adapted to suit the election period mentioned earlier, this shall be done by means of an election calendar published pursuant to section 133 of the said Act and attached to this decision;

— The manual of electors referred to in section 134 of the Election Act shall not be produced;

— Detainees shall vote by correspondence in accordance with the terms and conditions to be arranged with the authorities of the detention centres in question;

— The returning officer of the electoral division of Champlain shall be available for up to 480 hours for the purposes of the new election contemplated in this decision; — The following decisions made by the chief electoral officer during the election period ending on April 14, 2003, shall apply to the new election in the electoral division of Champlain:

- Decision of March 20, 2003, concerning the application of sections 3 and 340 of the Election Act (electors who have left their domicile for their own safety);

- Decision of April 8, 2003, concerning the exercise of the duties of officers assigned to the list of electors;

- Decision of April 11, 2003, concerning the remuneration of poll clerks; in this latter case, only the part of the decision establishing the remuneration of clerks shall apply.

This decision shall take effect on April 23, 2003.

MARCEL BLANCHET, Chief Electoral Officer and Chairman of the Commission de la représentation électorale

Québec 25 April 2003

	LE DIRECTEUR GÉNI DES ÉLECTIONS DU Q	Election Calendar			
	SUNDAY	MONDAY	TUESDAY		
	27 23 ¹⁹ day	28 22 [™] day - Lest day for the returning officer to inform the CEO, the political parties and candidates of places where the boards of revisors and advance poliing stations are established E - Lest day for recommendations of revisors and revising officers	29 21" day - Last day to appoint of revisors and revising officers - Last day to send to each address notices containing the information relating to the inscription on the list of electors, the revi- sion and the advance polling		
I	4 16 th day	 5 15th day Last day (2:00 p.m.) for filing nomination paper Posting up and transmitting of the notice of a poll to the candidates 	14 th day Last day for filing applications with the board of revisors Last day for the withdrawal of a candidate in order for his name not to appear on the ballot paper Revision of the list of electors entitled to vote outside Quebec Last day to file an application for striking with the board of revisors Last day to send the list of candidates to each elector entitled to vote outside Quebec Last day for recommendations of deputy returning officers, policiens, officers, office licets, officers, and circles, sofficers, of the lidentity verification panel		
l	11 9 th day - Mobile polling station in a hospital centre or a reception centre 9:00 a.m. to 1:00 p.m. - Advance polling 2:00 p.m. to 9:00 p.m. 2:00 p.m. to 9:00 p.m. - Sending by the returning officer of the list of electors who have voted in the advance polls to each candidate 18 2 nd day - Last day for the returning officer to send a reminder to each veling	12 8" day • Mobile polling station in a hospital centre or a reception centre 9:00 a.m. to 1:00 p.m. • Advance polling 2:00 p.m. to 9:00 p.m. • Sending by the returning officer of the list of electors who have voted in the advance polls to each candidate 19 1" day Holiday *	13 7 [™] day 20 POLLING DAY - 9:30 a.m. to 8:30 p.m. [5] - Publicity prohibited in the media		
	25	26 - Last day to apply for a judicial recount to a judge of the Court of Québec			

New election due to a tie vote in the electoral division of Champlain (EA 394 and 490)

Poll : May 20, 2003

	WEDNESDAY		THURSDAY		FRIDAY		SATURDAY
	Tie vote decided by a judge's decision Notice of a new election	-	26° day Opening of the main office of the returning officer 9:00 a.m. to 10:00 p.m. Beginning of publicity for political parties and candidates Production and transmission by the CE0 to the returning officer of the list of electors, the list of electors of the list of ove outside Québec, the list of electors for whom a veri- fication has been requested and the list of the addresses for which no electors' names are entered 19° day	25	25°° day 18°° day		24 th day First day (2:00 p.m.) for filing nomination paper 17 th day
30	j 200 usy First day for a private intervenor to file an application for authorization by the return- ing officer of his electoral division	-	First day of work of the boards of revisors which sit from 10:00 a.m. to 9:00 p.m. and receive applications from 11:00 a.m. to 9:00 p.m. ■ Revision of the list of electors entitled to vote outside Québec First day of work of the board of revisors Last day for receiving an application to exercise one's right to vote outside Québec	•	Last day to transmit to the returning ol- ficer a list of the electors who have become entitled to vote outside Québec since the new election notice and sending of this list by the returning officer to each candidate		
-	13 th day Special revision • First day of work of the special board of revisors which sit from 10:00 a.m. to 9:00 p.m. and receive applications from 11:00 a.m. to 9:00 p.m. Last day for a private intervenor to file an application for authorization by the returning officer of his electoral division		12 th day Revision • Last day of work of the boards of revisors Last day to apply for voting in a mobile poling station Last day for the returning officer to inform each candidate of places where polling sta- tions are established Last day for the returning officer to post and transmit to candidates the list of deputy returning officers, pol clerks, officers as- signed to the list of electors and members of the identity verification panel	9	11∾ day		10 th day Last day for the returning officer to transmit to each candidate the revised copies of the list of electors and the list of the electors who have become entilled to vote outside Québec since the new election notice Last day to transmit the list of the authoriz- ations granted to private intervenors by the returning officer to the political parties and candidates
14	6 th day Special revision Last day for filing applications with the special board of revisors	-	5 th day Special revision • Last day of work of the special board of revisors Revision of the list of electors entitled to vote outside Ouébec • Last day of work of the board of revisors	16	4* day Transmitting of an abstract of the changes made to the revised list of electors to each candidate by the returning officer	17	3 [∞] day
21	Addition of the votes at the main office of the returning officer	22		23		24]

Notices

Notice

Natural Heritage Conservation Act (2002, c. 74)

Annedda Nature Reserve — Recognition

Notice is hereby given, in keeping with article 58 of the Natural Heritage Conservation Act (2002, c. 74), that the Minister of the Environment has recognized as a nature reserve a private property, situated in the territory of the Municipality of Ulverton, Regional County Municipality of Le Val-Saint-François, known and designated as a part of the subdivision one of lot ninety-three (93-1) and as the subdivision eighteen of lot ninety-one (91-18) of the Durham Township land register, Richmond registry division. This property, which extends over 4,62 hectares, is more fully described in the plan and property description prepared and signed by Martin Paradis, land surveyor, on March 26, 2003, in his field note 4220.

The recognition takes effect on the date of the publication of this notice in the *Gazette officielle du Québec*.

ROBERT LEMIEUX, Assistant deputy minister for the industrial environment, climate change and sustainable development

5747

Notice

Natural Heritage Conservation Act (2002, c. 74)

Marais-Kergus Nature Reserve — Recognition

Notice is hereby given, in keeping with article 58 of the Natural Heritage Conservation Act (2002, c. 74), that the Minister of the Environment has recognized as a nature reserve a private property, situated in the territory of the Municipality of La Motte, Regional County Municipality of Abitibi, known and designated as lots 22 and 23 of Range 2 and a part of lots 25 and 26 of the aforementioned Range 2, as lots 23-A, 24-A and 25-A of Range 3 and a part of lots 23-B, 24-B and 25-B of the aforementioned Range 3, as a part of lot 23 of Range 4 and as a part of lots 22 and 23 of Range 5 of the La Motte Township land register, Abitibi registry division. This property, which extends over 301,1 hectares, is more fully described in the plan and property description prepared and signed by Claude Vincent, land surveyor, on March 19, 2003, in his field note 4339.

The recognition takes effect on the date of the publication of this notice in the *Gazette officielle du Québec*.

ROBERT LEMIEUX, Assistant deputy minister for the industrial environment, climate change and sustainable development

5748

Notice

Natural Heritage Conservation Act (2002, c. 74)

Pointe-de-la-Croix Nature Reserve — Recognition

Notice is hereby given, in keeping with article 58 of the Natural Heritage Conservation Act (2002, c. 74), that the Minister of the Environment has recognized as a nature reserve a private property, situated in the territory of the Municipality of Paroisse of Saint-François, Regional County Municipality of L'Île-d'Orléans, known and designated as a part of lot 105 of the Saint-François Parish land register, Québec registry division. This property, which extends over 12,1 hectares, is more fully described in the plan and property description prepared and signed by Mr. Yvon Létourneau, land surveyor, on March 27, 2003, in his field note 3 986.

This recognition takes effect on the date of the publication of this notice in the *Gazette officielle du Québec*.

LÉOPOLD GAUDREAU, Director of Ecological Heritage and Sustainable Development

5750

Index Statutory Instruments

Abbreviations: A: Abrogated, N: New, M: Modified

Regulations — Statutes	Page	Comments
Annedda Nature Reserve — Recognition (Natural Heritage Conservation Act, R.Q., 2002, c. 74)	1833	Notice
Automotive services — Drummond and Mauricie regions	1825	Draft
Chief electoral officer — Decision pursuant to the powers conferred upon him by section 490 of the Election Act, concerning the holding of a new election in the electoral division of Champlain	1829	Decision
Collective agreement decrees, An Act respecting — Automotive services — Drummond and Mauricie regions	1825	Draft
Devices which compensate for a physical deficiency	1699	Μ
Election Act — Chief electoral officer — Decision pursuant to the powers conferred upon him by section 490 of the Election Act, concerning the holding of a new election in the electoral division of Champlain	1829	Decision
Health Insurance Act — Devices which compensate for a physical deficiency (R.S.Q., c. A-29)	1699	Μ
Marais-Kergus Nature Reserve — Recognition	1833	Notice
Natural Heritage Conservation Act — Annedda Nature Reserve — Recognition	1833	Notice
Natural Heritage Conservation Act — Marais-Kergus Nature Reserve — Recognition	1833	Notice
Natural Heritage Conservation Act — Pointe-de-la-Croix Nature Reserve — Recognition	1834	Notice
Pointe-de-la-Croix Nature Reserve — Recognition	1834	Notice