# **Notice**

Health Insurance Act (R.S.Q., c. A-29)

# Devices which compensate for a physical deficiency — Amendments

Adoption by the Régie de l'assurance maladie du Québec of the Regulation to amend the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act on 16 May 2001

THE RÉGIE DE L'ASSURANCE MALADIE DU QUÉBEC,

CONSIDERING the fifth paragraph of section 3 and section 72.1 of the Health Insurance Act (R.S.Q., c. A-29; 1999, c. 89);

CONSIDERING the resolution of its board of directors CA-376-01-05 dated 16 May 2001, adopting the Regulation to amend the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act;

CONSIDERING that it is necessary to amend certain lists of locomotor and posture assists included in the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act:

GIVES NOTICE that it has adopted the Regulation to amend the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act, the text of which appears below.

Sillery, 17 May 2001

Duc Vu,

President and Director General of the Régie de l'assurance maladie du Québec

# Regulation to amend the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act \*

Health Insurance Act (R.S.Q., c. A-29, s. 3, 5th and 10th pars., and s. 72.1)

- **1.** The Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act is amended by substituting the Divisions in Schedule I to this Regulation for Divisions I, II and III of Part I of Chapter V of Title Two.
- **2.** This Regulation comes into force on 1 June 2001.

<sup>\*</sup> The Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act, made by Order in Council 612-94 dated 27 April 1994 (1994, *G.O.* 2, 1589), was last amended by the Regulation made by Order in Council 1047-2000 dated 30 August 2000 (2000, *G.O.* 2, 4544). For previous amendments, refer to the *Tableau des modifications et Index sommaire*, Éditeur officiel du Québec, 2000, updated to 1 November 2000.

#### **SCHEDULE 1**

#### CHAPTER V

LISTS

LOCOMOTOR AND POSTURE ASSISTS

#### PART I

LOCOMOTOR ASSISTS

#### **DIVISION I**

WHEEL CHAIRS

§1. Manual wheel chairs

#### DEVICE FROM: EVEREST & JENNINGS CANADA LTD.

**PRICE** 

# WHEEL CHAIR, "CLASSIC" MODEL

\$915.00

# **Basic Component(s)**

# **Body support system**

- supple back, nylon
- back height: from 31.8 cm  $(12^{1}/_{2} \text{ in.})$  to 50.8 cm (20 in.)
- front seating height: from 36.8 cm  $(14^{1}/_{2} \text{ in.})$  to 54.6 cm  $(21^{1}/_{2} \text{ in.})$
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.)
- supple seat, nylon
- safety belt, velcro-type, auto-type
- · push handles

#### **Armrests**

- "L"-type armrests, detachable, height-adjustable, from 15.2 cm (6 in.) to 25.4 cm (10 in.), short, long
- "U"-type armrests, detachable, fixed-height, short, long
- "U"-type armrests, detachable, height-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.), short, long
- straight armrest pads, short, long
- · tubular armrests
- clothing guards, flexible
- clothing guards, rigid and fixed

#### **Footrests**

- 70° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- · folding footplates
- heel loops, length-adjustable
- · padded calfrests

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- · standard wheel locks, push-to-lock
- forks, short, high
- · threaded axles
- rear mag wheels, spoked, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 17.8 cm (7 in.) X 2.5 cm (1 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
modification of supple seat depth to 35.6 cm (14 in.),		
38.1 cm (15 in.), 43.2 cm (17 in.) or to 48.3 cm (19 in.) modification of seat width to 48.3 cm (19 in.)	88.00	N/A
or 50.8 cm (20 in.)	122.00	N/A
modification of frame length for depths of 45.7 cm (18 in.)		
and 50.8 cm (20 in.)	113.00	N/A
supple back, nylon	N/C	72.00
supple seat, nylon	N/C	72.00
supple back, tension-adjustable	73.00	145.00
rigid seat, flat, all sizes	80.00	80.00
seat cushion, flat, foam, 5.1 cm (2 in.)	58.00	58.00
seat cushion, flat, foam, 7.6 cm (3 in.)	58.00	58.00
seat cushion, flat, foam, 10.2 cm (4 in.)	58.00	58.00
push handles	N/C	4.00
safety belt, velcro-type	N/C	23.00
safety belt, auto-type	N/C	28.00
safety belt, airplane-type	30.00	58.00
Armrests:		
"L"-type armrests, detachable, height-adjustable,		
from 15.2 cm (6 in.) to 25.4 cm (10 in.), short or long	N/C	68.00
"U"-type armrests, detachable, fixed-height, short or long "U"-type armrests, detachable, height-adjustable,	N/C	54.00
from 20.3 cm (8 in.) to 30.5 cm (12 in.), short or long	N/C	134.00
tubular armrests	N/C	6.00
straight armrest pads, short or long	N/C	13.00
clothing guards, rigid, straight or fender-style		
a pair	56.00	
each		75.00
clothing guards, flexible	N/C	21.00
rigid clothing guards, fixed	N/C	47.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
70° footrests, detachable, swingaway, length-adjustable,		
from 35.6 cm (14 in.) to 45.7 cm (18 in.)	N/C	103.00
elevating legrests, length-adjustable,		
from 35.6 cm (14 in.) to 45.7 cm (18 in.)		
a pair	310.00	
each		258.00
single calf strap	25.00	25.00
louble calf strap	48.00	48.00
padded calfrests	N/C	21.00
folding footplates	N/C	39.00
folding footplates, angle-adjustable	10.00	
n pair	126.00	400.00
each		102.00
folding footplates, oversized	54.00	
a pair	54.00	<i>56.</i> 00
each	N/C	56.00 12.00
neel loops, length-adjustable	N/C	12.00
modification of footrest length, from 48.3 cm (19 in.) o 50.8 cm (20 in.)	87.00	N/A
Wheels and frame Types of drive systems :		
anodized aluminum handrims, 50.8 cm (20 in.),		
55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	45.00
plastic-coated handrims	N/C	45.00
a pair	68.00	
each	00.00	79.00
non-slip handrims		75.00
a pair	86.00	
each		88.00
nandrims with vertical or oblique projections		
a pair	158.00	
each		124.00
combined handrims		
a pair	86.00	
each		88.00
Front anti-tip rollers		
n pair	88.00	44.0-
each	42.00	44.00
cane holder	43.00	43.00
Wheel locks:		
standard wheel locks, push-to-lock	N/C	57.00
standard wheel locks, pull-to-lock		
ı pair	30.00	
each		72.00
vheel lock extensions		
pair	26.00	40.0-
ach		13.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
anti-rollback brakes		
a pair	100.00	107.00
each swing-away brakes		107.00
a pair	30.00	
each		72.00
Types of forks:		
short forks	N/C	48.00
high forks	N/C	50.00
Rear axles: threaded axles	N/C	12.00
nreaded axies quick-release axles	N/C	12.00
a pair	80.00	
each		52.00
axle extension plates for amputee	40.00	
a pair	62.00	21.00
each		31.00
Types of wheels: rear mag wheels, solid tires, 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	85.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	00.00	
a pair each	80.00	125.00
spoked rear wheels, high pressure, 55.9 cm (22 in.),		123.00
61.0 cm (24 in.) or 66.0 cm (26 in.)		
a pair	90.00	
each		130.00
spoked rear wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	120.00
ear mag wheels, standard pressure, 50.8 cm (20 in.),	N/C	120.00
55.9 cm (22 in.) or 61.0 cm (24 in.)		
a pair	102.00	
each		118.00
spoked rear wheels, solid tires, 50.8 cm (20 in.) a pair	70.00	
a pan each	70.00	120.00
Front wheels, solid tires, 7.6 cm (3 in.)		120.00
a pair	44.00	
each		42.00
Front wheels, solid tires, 12.7 cm (5 in.)	44.00	
each	TT.00	42.00
Front wheels, solid tires, 17.8 cm (7 in.) X 2.5 cm (1 in.)	N/C	20.00
Front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.)		
or 15.2 cm (6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	44.00	
n pair	44.00	42.00
each		42.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, puncture-resistant tires, 15.2 cm (6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) a pair each	44.00	42.00
airless inserts for rear wheels, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) a pair each	60.00	42.00 N/A
rear puncture-resistant tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) a pair each	55.00	N/A
Component(s) under Special Consideration		
quick-release axles with lever mechanism * a pair each	70.00	87.00

# DEVICE FROM: EVEREST & JENNINGS CANADA LTD.

**PRICE** 

# WHEEL CHAIR, "EPIC" MODEL

\$1 195.00

# **Basic Component(s)**

#### **Body support system**

- back, height-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.), and angle-adjustable, from 3° to 12°
- front seating height: from 40.6 cm (16 in.) to 50.8 cm (20 in.)
- seat width: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.)
- supple seat and back, nylon
- push handles
- safety belt, velcro-type, auto-type

#### Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable, from 22.9 cm (9 in.) to 26.7 cm ( $10^{1/2}$  in.), short
- "U"-type armrests, detachable, flip-back, height-adjustable, from 24.1 cm (9<sup>1</sup>/<sub>2</sub> in.) to 34.3 cm (13<sup>1</sup>/<sub>2</sub> in.), short or long
- · straight armrest pads, short or long
- tubular armrests
- clothing guards, flexible
- clothing guards, rigid, detachable
- clothing guards, rigid, height-adjustable, built into flip-back armrests

#### **Footrests**

- 75° footrests, detachable, swingaway, length-adjustable, from 33.0 cm (13 in.) to 48.3 cm (19 in.)
- 80° footrests, "V"-shaped, detachable, swingaway, length-adjustable, from 33.0 cm (13 in.) to 48.3 cm (19 in.)
- folding footplates
- heel loops, length-adjustable
- padded calfrests

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- chrome handrims, 50.8 cm (20 in.),
   55.9 cm (22 in.), 61.0 cm (24 in.)
- · standard wheel locks, push-to-lock
- standard forks, short, very short
- · threaded axles
- rear mag wheels, spoked, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 15.2 cm (6 in.), 20.3 cm (8 in.) X 2.5 cm (1 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
supple back, tension-adjustable	73.00	145.00
modification of back height, from 25.4 cm (10 in.)		
to 33.0 cm (13 in.) or from 46.4 cm ( $18^{1}/_{4}$ in.)		
to 55.9 cm (22 in.)	52.00	N/A
modification of seat depth to 38.1 cm (15 in.),		
43.2 cm (17 in.) or 45.7 cm (18 in.)	113.00	N/A
modification of seat width to 48.3 cm (19 in.),	110.00	37/4
50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	119.00	N/A
push handles	N/C	5.00
supple back, nylon	N/C	72.00
supple seat, nylon	N/C	72.00
rigid seat, flat	80.00	80.00
seat cushion, flat, foam, 5.1 cm (2 in.)	58.00	58.00
seat cushion, flat, foam, 7.6 cm (3 in.)	58.00	58.00
safety belt, velcro-type	N/C	23.00
safety belt, auto-type	N/C	28.00
safety belt, airplane-type	30.00	58.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
"L"-type armrests, detachable, swingaway, height-adjustable,		
from 22.9 cm (9 in.) to 26.7 cm (10 <sup>1</sup> / <sub>2</sub> in.), short "U"-type armrests, detachable, flip-back, height-adjustable,	N/C	103.00
from 24.1 cm (9 $\frac{1}{2}$ in.) to 34.3 cm (13 $\frac{1}{2}$ in.),	N1/G	124.00
short or long	N/C	134.00
tubular armrests	N/C	5.00
straight armrest pads, short	N/C	13.00
straight armrest pads, long	N/C	13.00
clothing guards, flexible	N/C	21.00
clothing guards, rigid, detachable	N/C	42.00
clothing guards, rigid, height-adjustable, built into		
lip-back armrests	N/C	21.00
clothing guards, rigid, fender-style	56.00	75.00
Footrests:		
75° footrests, detachable, swingaway, length-adjustable,		
from 33.0 cm (13 in.) to 48.3 cm (19 in.)	N/C	103.00
80° footrests, "V"-shaped, detachable, swingaway,		
ength-adjustable, from 33.0 cm (13 in.) to 48.3 cm (19 in.)	N/C	103.00
elevating legrests, detachable, swingaway,		
ength-adjustable, from 44.5 cm $(17^{1}/_{2} \text{ in.})$		
o 54.6 cm (21½ in.) including padded calfrests		
n pair	310.00	
each		258.00
modification of footrest length	87.00	N/A
single calf strap	25.00	25.00
folding footplates	N/C	20.00
full-width footplate, angle-adjustable		
pair	140.00	
each		160.00
folding footplates, "1/3 - 2/3"-type, composite		
n pair	32.00	
each		36.00
neel loops, length-adjustable	N/C	12.00
padded calfrests	N/C	21.00
Wheels and frame		
Types of drive systems:		
andrims with vertical or oblique projections		
pair	136.00	
each		114.00
modized aluminum handrims, 50.8 cm (20 in.),		1100
55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	46.00
throme handrims, 50.8 cm (20 in.),	100	10.00
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	33.00
plastic-coated handrims	100	33.00
pair	62.00	
ach	02.00	77.00
acii		77.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front anti-tip rollers		
a pair	88.00	44.00
each cane holder	44.00	44.00 44.00
****		
Wheel locks: standard wheel locks, push-to-lock	N/C	69.00
wheel lock extensions		
a pair each	34.00	17.00
nnti-rollback brakes		17.00
a pair	84.00	110.00
each		110.00
Types of forks:	NI/C	24.00
standard forks, short or very short or very short ork-locking mechanisms	N/C	34.00
a pair	88.00	
each		44.00
Rear axles:	N/G	4.55
hreaded axles quick-release axles	N/C	4.75
a pair	79.00	
each		44.00
axle extension plates for amputee	72.00	
each	<b>7</b> 6 00	36.00
modification of rear wheel camber to 3°, 6°	56.00	28.00
Types of wheels:		
rear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	85.00
rear mag wheels, heavy-duty, solid tires or standard	IV/C	05.00
pressure, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.) a pair	80.00	
each		125.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)		
or 66.0 cm (26 in.)		
a pair each	80.00	125.00
each spoked rear wheels, solid tires, 50.8 cm (20 in.)		125.00
pair	70.00	420.00
each spoked rear wheels, solid tires, 55.9 cm (22 in.)		120.00
or 61.0 cm (24 in.)	N/C	120.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
spoked rear wheels, high pressure, 55.9 cm (22 in.),		
61.0 cm (24 in.) or 66.0 cm (26 in.)	00.00	
a pair each	90.00	130.00
	N/C	30.00
front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.) front wheels, solid tires, 15.2 cm (6 in.)	N/C N/C	20.00
front wheels, solid tries, 13.2 cm (6 in.) front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) or 20.3 cm (8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.)	IV/C	20.00
a pair	44.00	
each		42.00
front wheels, solid tires, 12.7 cm (5 in.)		
a pair	24.00	
each		32.00
front wheels, puncture-resistant tires,		
15.2 cm (6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)		
a pair	44.00	
each		42.00
airless inserts for rear wheels		
a pair	60.00	
each		N/A
Component(s) under Special Consideration		
spoke guards *		
a pair	81.00	
each	01.00	44.00
quick-release axles with lever mechanism *	87.00	87.00
quiek refeuse unies with fever meenumsm	07.00	07.00
DEVICE FROM: EVEREST & JENNINGS CANADA LTD.		

**PRICE** 

# WHEEL CHAIR, RECLINING OR SEMI-RECLINING BACK, "QURE" MODEL

\$1 455.00

# Basic Component(s)

# **Body support system**

- supple back, leatherette, standard sizes, special sizes
- reclining back, from 0° to 90°, height of 52.1 cm (20<sup>1</sup>/<sub>2</sub> in.)
- front seating height:  $47.6 \text{ cm} (18^{3}/_{4} \text{ in.}), 50.2 \text{ cm} (19^{3}/_{4} \text{ in.})$
- seat width: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 43.2 cm (17 in.)
- supple seat, leatherette, standard sizes, special sizes
- telescopic headrest
- safety belt, auto-type
- · push handles

#### **Armrests**

- "U"-type armrests, detachable, fixed-height of 24.8 cm (9<sup>3</sup>/<sub>4</sub> in.), short, long
- "U"-type armrests, detachable and height-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.), short, long
- straight armrest pads, short, long
- clothing guards, rigid

#### **Footrests**

- 70° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- folding footplates
- heel loops, length-adjustable
- padded calfrests

- chrome handrims, 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks for 20 cm (8 in.) wheels, short forks, high forks
- · threaded axles
- rear mag wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.)
- spreader bar

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
telescopic headrest	N/C	58.00
supple back, leatherette, special sizes	N/C	100.00
supple seat, leatherette, special sizes	N/C	100.00
modification of back height, more		
than 52.1 cm ( $20^{1}/_{2}$ in.)	107.00	N/A
modification of seat depth to 38.1 cm (15 in.)		
or 45.7 cm (18 in.)	288.00	N/A
modification of seat depth to 40.6 cm (16 in.)	133.00	N/A
modification of seating height to 34.9 cm (15 <sup>3</sup> / <sub>4</sub> in.)		
$42.5 \text{ cm } (16^3/_4 \text{ in.}), 45.1 \text{ cm } (17^3/_4 \text{ in.})$		
or $52.7 \text{ cm } (20^3/_4 \text{ in.})$	283.00	N/A
modification of seat width, more than 48.3 cm (19 in.)	283.00	N/A
supple back, leatherette	N/C	48.00
supple seat, leatherette	N/C	48.00
push handles	N/C	3.00
seat cushion, flat, foam, 5.1 cm (2 in.)	58.00	58.00
seat cushion, flat, foam, 7.5 cm (3 in.)	58.00	58.00
safety belt, auto-type	N/C	28.00
safety belt, airplane-type	30.00	58.00

**U*-type armrests, detachable, fixed height of 24.8 cm (9%, in.), short "V"-type armrests, detachable, fixed height of 24.8 cm (9%, in.), short "V"-type armrests, detachable, fixed height of 24.8 cm (9%, in.), long "N/C "52.00 "V"-type armrests, detachable and height-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.), short "N/C "118.00 "V"-type armrests, detachable and height-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.), long "N/C "18.00 straight armrest pads, short or long "N/C "13.00 modification of armrest height "8.500 "N/A "13.00 "N/C "13.00 modification of armrest height "8.500 "N/A "13.00 "N/C "1		Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
of 24.8 cm (9½, in.), short       N/C       58.00         'U"-type armrests, detachable, fixed height       N/C       52.00         'U"-type armrests, detachable and height-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.), short       N/C       118.00         'U"-type armrests, detachable and height-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.), long       N/C       118.00         "U"-type armrests, detachable and height-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.), long       N/C       13.00         modification of armrest height       85.00       N/A         clothing guards, rigid       N/C       20.00         Footrests:         Footrests:         Footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)       N/C       68.00         Footrests:         10° footrests, detachable, swingaway and length-adjustable, from 38.1 cm (15 in.)       N/C       68.00         clevating legrests, detachable, swingaway and length-adjustable, from 38.1 cm (15 in.)       160.00       160.00         ingle calf strap       21.00       21.00       21.00         obach       184.00       48.00       48.00         folding footplates, angle-adjustable       78.00       78.00         indiding footplates, non-skid       20.00	Armrests:		
**U**1********************************			
of 24.8 cm (9½, in.), long       N/C       52.00         'U"-type armrests, detachable and height-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.), short       N/C       118.00         'U"-type armrests, detachable and height-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.), long       N/C       13.00         straight armrest pads, short or long       N/C       13.00         modification of armrest height       85.00       N/A         clothing guards, rigid       N/C       20.00         Footrests:         Cottents, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)       N/C       68.00         elevating legrests, detachable, swingaway and length-adjustable, from 38.1 cm (15 in.)       N/C       68.00         elevating legrests, detachable, swingaway and length-adjustable, from 38.1 cm (15 in.)       160.00       21.00         o5 53.3 cm (21 in.) including padded calfrests       184.00       21.00       21.00         sach       120.00       21.00       21.00       21.00       21.00       21.00       21.00       21.00       21.00       21.00       21.00       21.00       22.00       28.00       28.00       28.00       28.00       28.00       28.00       28.00       28.00       28.00       28.00       28.00		N/C	58.00
**U**-type armrests, detachable and height-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.), short N/C 118.00 **U**-type armrests, detachable and height-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.), long N/C 13.00 **M**-C 13.00			
from 20.3 cm (8 in.) to 33.0 cm (13 in.), short		N/C	52.00
**U"-type armrests, detachable and height-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.), long			
from 20.3 cm (8 in.) to 33.0 cm (13 in.), long         N/C         118.00           straight armrest pads, short or long         N/C         13.00           modification of armrest height         85.00         N/A           clothing guards, rigid         N/C         20.00           Footrests:           70° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)         N/C         68.00           elevating legrests, detachable, swingaway and length-adjustable, from 38.1 cm (15 in.)         N/C         68.00           lelevating legrests, detachable, swingaway and length-adjustable, from 38.1 cm (15 in.)         184.00         160.00           ingle calf strap deach apair         21.00         21.00         21.00           ingle calf strap double calf		N/C	118.00
Straight armrest pads, short or long modification of armrest height straight armrest pads, short or long modification of armrest height straight			
Modification of armrest height   85.00   N/A			
Proof   Proo			
Footrests: 70° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.) 80° footrests, detachable, swingaway and length-adjustable, from 38.1 cm (15 in.) 80° 53.3 cm (21 in.) including padded calfrests 80° pair			
70° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)  20° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)  20° 53.3 cm (21 in.) including padded calfrests a pair 20° 53.3 cm (21 in.) including padded calfrests a pair 21.00 21	clothing guards, rigid	N/C	20.00
70° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)  20° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)  20° 53.3 cm (21 in.) including padded calfrests a pair 20° 53.3 cm (21 in.) including padded calfrests a pair 21.00 21	Eastwests.		
from 35.6 cm (14 in.) to 45.7 cm (18 in.)  from 35.6 cm (14 in.) to 45.7 cm (18 in.)  elevating legrests, detachable, swingaway and length-adjustable, from 38.1 cm (15 in.)  to 53.3 cm (21 in.) including padded calfrests  a pair  each  folloing calf strap  folding footplates  folding footplates, angle-adjustable  a pair  each  folding footplatess, oversized  a pair  each  folding footplatess, oversized  a pair  each  folding footplates, non-skid  a pair  each  folding footplates, non-skid  a pair  each  folding footplates, non-skid  a pair  each  folding footplates  f			
elevating legrests, detachable, swingaway and length-adjustable, from 38.1 cm (15 in.) 10 53.3 cm (21 in.) including padded calfrests a pair 21 184.00 21 10		N/C	68.00
length-adjustable, from 38.1 cm (15 in.) 10.53.3 cm (21 in.) including padded calfrests a pair 184.00 each single calf strap 10.00 double all strap 10.00 double all strap 10.00 double all strap 10.0		14/6	00.00
184.00   160.00   1			
184.00   160.00   1			
160.00   1		184.00	
single calf strap       21.00       21.00         double calf strap       48.00       48.00         folding footplates       N/C       18.00         folding footplates, angle-adjustable a pair       120.00       78.00         folding footplatess, oversized a pair       20.00       28.00         folding footplates, non-skid       28.00       28.00         folding footplates, non-skid a pair       20.00       28.00         foull-width footplate       64.00       82.00         foull-width footplate       64.00       82.00         neel loops, length-adjustable       N/C       12.00         foel loops       26.00       17.00         a pair       26.00       17.00         modification of footrest length       88.00       N/A         front impact guard with rollers       16.00       8.00         a pair       16.00       8.00		184.00	160.00
As 00   As 0		21.00	
folding footplates folding footplates, angle-adjustable a pair each folding footplatess, oversized a pair each folding footplatess, oversized a pair each folding footplatess, oversized a pair each folding footplates, non-skid each folding footplates, non-skid each each folding footplates, non-skid each  28.00 each each folding footplates, non-skid each  28.00 each each folding footplates, non-skid each  28.00 each each each each each each each each			
folding footplates, angle-adjustable       120.00         a pair       78.00         folding footplatess, oversized       20.00         a pair       20.00         each       28.00         folding footplates, non-skid       20.00         a pair       20.00         each       28.00         full-width footplate       64.00       82.00         neel loops, length-adjustable       N/C       12.00         toe loops       26.00       17.00         each       17.00       17.00         modification of footrest length       88.00       N/A         front impact guard with rollers       16.00       8.00			
a pair 120.00 each 78.00 folding footplatess, oversized 20.00 each 28.00 folding footplates, non-skid 28.00 folding footplates, non-skid 20.00 each 28.00 full-width footplate 64.00 82.00 each 64.00 82.00 each 78.00 full-width footplate 64.00 82.00 each 82.00 each 82.00 footplates, non-skid 88.00 N/A front impact guard with rollers a pair 16.00 each 88.00 N/A front impact guard with rollers 88.00 N/A front impact guard with rollers 88.00 N/A		11/C	10.00
78.00 Folding footplatess, oversized a pair each folding footplates, non-skid a pair a pair 20.00 each folding footplates, non-skid a pair 20.00 each full-width footplate foull-width footplate neel loops, length-adjustable foot loops a pair 26.00 each footplate footplates, non-skid footplate		120.00	
folding footplatess, oversized a pair 20.00 each 28.00 folding footplates, non-skid 20.00 each 20.0		120.00	78.00
a pair 20.00 each 28.00 folding footplates, non-skid a pair 20.00 each 28.00 full-width footplate 64.00 82.00 neel loops, length-adjustable N/C 12.00 toe loops a pair 26.00 each 17.00 modification of footrest length 68.00 N/A front impact guard with rollers a pair 16.00 each 88.00 N/A front impact guard with rollers a pair 88.00 N/A front impact guard with rollers a pair 88.00 N/A			78.00
28.00 folding footplates, non-skid a pair 20.00 each full-width footplate neel loops, length-adjustable toe loops a pair 26.00 each modification of footrest length front impact guard with rollers a pair 26.00 each 17.00 modification of sourcest length front impact guard with rollers a pair each 88.00 8.00		20.00	
folding footplates, non-skid a pair a pair 20.00 each full-width footplate heel loops, length-adjustable loops a pair a pair 26.00 each modification of footrest length front impact guard with rollers a pair a pair 48.00 N/A front impact guard with rollers a pair beach 16.00 8.00		20.00	28.00
a pair 20.00 each 28.00 full-width footplate 64.00 82.00 neel loops, length-adjustable N/C 12.00 toe loops a pair 26.00 each 17.00 modification of footrest length 88.00 N/A front impact guard with rollers a pair 16.00 each 8.00			20.00
geach       28.00         full-width footplate       64.00       82.00         neel loops, length-adjustable       N/C       12.00         toe loops       26.00         each       17.00         modification of footrest length       88.00       N/A         front impact guard with rollers       16.00         each       8.00		20.00	
full-width footplate 64.00 82.00 heel loops, length-adjustable N/C 12.00 hoe loops a pair 26.00 hoodification of footrest length front impact guard with rollers a pair 16.00 hoodification of seach 17.00 hoodification of seach 88.00 how hold impact guard with rollers a pair 16.00 hoodification of seach 8.00		20.00	28.00
neel loops, length-adjustable N/C 12.00 to loops a pair 26.00 arch 17.00 modification of footrest length front impact guard with rollers a pair 16.00 arch 16.00		64 00	
toe loops a pair 26.00 each modification of footrest length front impact guard with rollers a pair each 17.00 N/A front impact guard with rollers a pair each 8.00			
a pair 26.00 each 17.00 modification of footrest length 88.00 N/A front impact guard with rollers a pair 16.00 each 8.00		1 <b>V</b> / C	12.00
each modification of footrest length 88.00 N/A front impact guard with rollers a pair 16.00 8.00		26 00	
modification of footrest length front impact guard with rollers a pair each  16.00  8.00		20.00	17.00
front impact guard with rollers a pair 16.00 each 8.00		88 00	
a pair 16.00 8.00		00.00	11/11
each 8.00		16.00	
		10.00	ያ በበ
	padded calfrests	N/C	21.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems:		
plastic-coated handrims	40.00	
a pair	48.00	57.00
each handrims with vertical or oblique projections		57.00
a pair	160.00	
each	100.00	113.00
chrome handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	33.00
front anti-tippers		
a pair	72.00	
each	24.00	36.00
cane holder	34.00	34.00
Wheel locks:		
standard wheel locks, push-to-lock	N/C	24.00
standard wheel locks, pull-to-lock	N/C	24.00
wheel lock extensions		
a pair	24.00	12.00
each anti-rollback brakes		12.00
anti-tonback brakes a pair	78.00	
each	76.00	39.00
Types of forks:	27/6	• • • •
standard forks for 20.3 cm (8 in.) wheels	N/C	26.00
forks, short or high suspension forks	N/C	33.00
a pair	134.00	
each	131.00	93.00
fork-locking mechanisms		
a pair	72.00	
each		36.00
Rear axles:		
threaded axles	N/C	4.75
heavy-duty axles	62.00	N/A
forward axle displacement of 1.6 cm (5/8 in.)	62.00	N/A
Enomo		
Frame: double cross-bars	137.00	N/A
neavy-duty cross-bars	32.00	N/A N/A
Frame angle reinforcements	32.00	11/11
a pair	58.00	
each		N/A
spreader bar	N/C	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
rear mag wheels, solid tires, 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	84.00
front mag wheels, heavy-duty, solid tires or standard		
pressure, 55.9 cm (22 in.) or 61.0 cm (24 in.)		
a pair	82.00	
each		125.00
front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.)	N/C	24.00
front wheels, solid tires, 15.2 cm (6 in.)	N/C	20.00
front wheels, semi-pneumatic tires,		
20.3 cm (8 in.) X 4.4 cm ( $1^{3}/_{4}$ in.)	44.00	
a pair	44.00	42.00
each		42.00
front wheels, inner tube, 20.3 cm (8 in.) X 4.4 cm ( $1^{3}/_{4}$ in.) a pair	44.00	
each	44.00	42.00
front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.)		42.00
or 15.2 cm (6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)		
a pair	44.00	
each		42.00
airless inserts for rear wheels		
a pair	60.00	
each		N/A

# DEVICE FROM: EVEREST & JENNINGS CANADA LTD.

**PRICE** 

# WHEEL CHAIR, "QUR" MODEL

\$1 125.00

# Basic Component(s)

# **Body support system**

- supple back, leatherette, nylon
- supple back, leatherette, special sizes
- fixed back: height of 41.9 cm  $(16^{1}/_{2} in.)$
- front seating height:  $50.2 \text{ cm} (19^3/_4 \text{ in.}), 47.6 \text{ cm} (18^3/_4 \text{ in.})$
- seat width: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.)
- supple seat, leatherette, nylon
- supple seat, leatherette, special sizes
- safety belt, auto-type
- · push handles

#### Armrests

- "U"-type armrests, wraparound or not, detachable, fixed-height of 24.8 cm (9<sup>3</sup>/<sub>4</sub> in.), short, long
- "U"-type armrests, wraparound or not, detachable, height-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.), short, long
- "U"-type armrests, detachable, flip-back, height-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.), short, long
- · straight armrest pads, short, long
- · clothing guards, rigid

#### **Footrests**

- 70° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- · folding footplates
- heel loops, length-adjustable
- padded calfrests

- chrome handrims, 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks, short, long
- threaded axles
- rear mag wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:	160.00	<b>50.00</b>
telescopic headrest	169.00	58.00
supple back, leatherette, special sizes	N/C	100.00
supple seat, leatherette, special sizes	N/C	100.00
modification of back height to 36.8 cm $(14^{1}/_{2} \text{ in.})$ ,	107.00	NT/A
$47.0 \text{ cm } (18^{1/2} \text{ in.}) \text{ or } 52.1 \text{ cm } (20^{1/2} \text{ in.})$	107.00	N/A
modification of seat depth to 35.6 cm (14 in.),	200.00	DT/A
38.1 cm (15 in.), 45.7 cm (18 in.) or 48.3 cm (19 in.)	288.00	N/A
modification of seat depth to 43.2 cm (17 in.)	129.00	N/A
modification of seating height to $40.0 \text{ cm } (15^3/_4 \text{ in.}),$		
42.5 cm $(16^3/_4 \text{ in.})$ , 45.1 cm $(17^3/_4 \text{ in.})$ ,	202.00	37/4
$52.7 \text{ cm } (20^3/_4 \text{ in.}) \text{ or } 55.2 \text{ cm } (21^3/_4 \text{ in.})$	283.00	N/A
modification of seat width to 48.3 cm (19 in.),		
50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.),		
58.4 cm (23 in.) or 61.0 cm (24 in.)	283.00	N/A
modification of height of special back with welded handles	133.00	N/A
supple back, leatherette or nylon	N/C	48.00
supple seat, leatherette or nylon	N/C	48.00
push handles	N/C	3.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
seat cushion, flat, foam, 5.1 cm (2 in.)	58.00	58.00
seat cushion, flat, foam, 7.6 cm (3 in.)	58.00	58.00
safety belt, auto-type	N/C	28.00
safety belt, airplane-type	30.00	58.00
Armrests:		
"U"-type armrests, detachable, fixed height		
of 24.8 cm $(9^3/_4 \text{ in.})$ , short	N/C	58.00
"U"-type armrests, detachable, fixed height		
of 24.8 cm $(9^{3}/_{4} in.)$ , long	N/C	52.00
"U"-type armrests, wraparound, detachable,		
fixed height of 24.8 cm (9 <sup>3</sup> / <sub>4</sub> in.), short	N/C	78.00
"U"-type armrests, wraparound, detachable,		
fixed height of 24.8 cm (9 <sup>3</sup> / <sub>4</sub> in.), long	N/C	74.00
"U"-type armrests, detachable, height-adjustable,		
from 20.3 cm (8 in.) to 30.5 cm (12 in.), short	N/C	118.00
"U"-type armrests, detachable, height-adjustable,		
from 20.3 cm (8 in.) to 30.5 cm (12 in.), long	N/C	118.00
"U"-type armrests, wraparound, detachable,		
height-adjustable, from 20.3 cm (8 in.)		
to 30.5 cm (12 in.), short	N/C	118.00
"U"-type armrests, wraparound, detachable,		
height-adjustable, from 20.3 cm (8 in.)		
to 30.5 cm (12 in.), long	N/C	118.00
"U"-type armrests, detachable, flip-back,		
height-adjustable, from 20.3 cm (8 in.)		
to 30.5 cm (12 in.), short or long	N/C	118.00
straight armrest pads, short or long	N/C	13.00
modification of armrest height	85.00	N/A
clothing guards, rigid	N/C	20.00
Footrests:		
70° footrests, detachable, swingaway and length-adjustable,	NI/C	CO 00
from 35.6 cm (14 in.) to 45.7 cm (18 in.)	N/C	68.00
elevating legrests, detachable, swingaway and		
length-adjustable, from 35.6 cm (14 in.)		
to 53.3 cm (21 in.) including padded calfrests	194.00	
a pair	184.00	160.00
each	21.00	
single calf strap	21.00	21.00
double calf strap	48.00 N/C	48.00
folding footplates	N/C	18.00
folding footplates, angle-adjustable	120.00	
n pair	120.00	70.00
each		78.00
folding footplates, oversized	20.00	
n pair	20.00	20.00
each		28.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
folding footplates, non-skid		
a pair	20.00	
each	64.00	28.00
full-width footplate heel loops, length-adjustable	64.00 N/C	82.00 12.00
toe loops	14/6	12.00
a pair	26.00	
each		17.00
modification of footrest length	88.00	N/A
front impact guard with rollers	16.00	
a pair each	16.00	8.00
padded calfrests	N/C	21.00
1		
Wheels and frame		
Types of drive systems:	425.00	570.00
one-arm dual handrim drive plastic-coated handrims	435.00	570.00
a pair	48.00	
each		57.00
handrims with vertical or oblique projections		
a pair	160.00	112.00
each chrome handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	113.00 33.00
front anti-tip rollers	N/C	33.00
a pair	72.00	
each		36.00
cane holder	34.00	34.00
Wheel locks:		
standard wheel locks, push-to-lock	N/C	24.00
standard wheel locks, pull-to-lock	N/C	24.00
wheel lock extensions		
a pair	24.00	12.00
each anti-rollback brakes		12.00
anti-rondack drakes a pair	78.00	
each	, 0.00	39.00
Types of forks:	32/6	24.00
standard forks	N/C N/C	26.00 33.00
forks, short or high suspension forks	N/C	33.00
a pair	134.00	
each		93.00
fork-locking mechanisms		
a pair	72.00	24.63
each		36.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Rear axles:		
threaded axles	N/C	4.75
axle extension plates for amputee	00.00	
a pair	80.00	40.00
each		40.00
wheel converters for 55.9 cm (22 in.) and 61.0 cm (24 in.) wheels	68.00	
a pair each	08.00	34.00
forward axle displacement	62.00	N/A
neavy-duty axles, 1.6 cm (5/8 in.)	62.00	N/A N/A
icavy-duty dates, 1.0 cm (5/6 m.)	02.00	14/11
Frame:	4.00	37/1
double cross-bars	137.00	N/A
frame angle reinforcements	<b>50.00</b>	
a pair	58.00	NT/A
each	07.00	N/A
spreader bar neavy-duty cross-bars	97.00 32.00	N/A N/A
backpost reinforcement bracket	137.00	68.50
neavy-duty backposts	32.00	N/A
rear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.) rear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	84.00
a pair	82.00	127.00
each		125.00
rear mag wheels, heavy-duty, standard pressure, 55.9 cm (22 in.) or 61.0 cm (24 in.)		
a pair	82.00	
each	62.00	125.00
front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.)	N/C	24.00
front wheels, solid tires, 15.2 cm (6 in.)	N/C	20.00
front wheels, semi-pneumatic tires,		
$20.3 \text{ cm } (8 \text{ in.}) \text{ X } 4.4 \text{ cm } (1^{3}/_{4} \text{ in.})$		
a pair	44.00	
each		42.00
front wheels, inner tube, 20.3 cm (8 in.) X 4.4 cm $(1^{3}/_{4}$ in.)	44.00	
a pair	44.00	42.00
each		42.00
Front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) a pair	44.00	
a pan each	TT.00	42.00
front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.)		72.00
a pair	44.00	
each		42.00
irless inserts for rear wheels		
pair	60.00	
each		N/A

#### DEVICE FROM: INVACARE CANADA INC.

#### **PRICE**

# WHEEL CHAIR, "ACTION PATRIOT" MODEL

\$690.00

#### **Basic Component(s)**

# **Body support system**

- back, height-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seating height:  $47.6 \text{ cm} (18^{3}/_{4} \text{ in.}), 50.8 \text{ cm} (20 \text{ in.})$
- seat width: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.)
- · supple seat and back, nylon
- push handles
- safety belt, velcro-type, auto-type

#### Armrests

- "L"-type armrests, detachable, height-adjustable, from 18.4 cm (7<sup>1</sup>/<sub>4</sub> in.) to 23.5 cm (9<sup>1</sup>/<sub>4</sub> in.), short
- straight armrest pads, short, long; contoured armrest pads, short, long; tubular armrests
- · clothing guards, flexible

#### **Footrests**

- 60° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.); 70° footrests, detachable, swingaway, length-adjustable, from 33.0 cm (13 in.) to 43.2 cm (17 in.)
- folding footplates, standard or tubular
- heel loops, non-adjustable
- · heel loops, length-adjustable
- padded calfrests

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock
- · standard forks
- · threaded axles
- rear mag wheels, solid tires, 50.8 cm (20 in.),
   55.9 cm (22 in.), 61.0 cm (24 in.), standard pressure,
   50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 12.7 cm (5 in.), 15.2 cm (6 in.) or 20.3 cm (8 in.) X 2.5 cm (1 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
upple back, tension-adjustable	63.00	98.00
igid inner liner for back	63.00	98.00
nodification of seat depth to 45.7 cm (18 in.)	58.00	N/A
nodification of seating height to 41.9 cm $(16^{1}/_{2} \text{ in.})$ ,		
$3.2 \text{ cm } (17 \text{ in.}) \text{ or } 44.5 \text{ cm } (17^{1}/_{2} \text{ in.})$	228.00	N/A
nodification of seat width to 50.8 cm (20 in.)	115.00	N/A
nodification of back height to 50.8 cm (20 in.)	58.00	N/A
ush handles	N/C	37.00
apple back, nylon	N/C	35.00
apple seat, nylon	N/C	35.00
eat cushion, flat, foam, 5.1 cm (2 in.)	55.00	55.00
eat cushion, flat, foam, 7.6 cm (3 in.)	55.00	55.00
afety belt, velcro-type	N/C	20.00
afety belt, auto-type	N/C	30.00
armrests:		
L"-type armrests, detachable, height-adjustable,		
com 18.4 cm $(7^{1}/_{4} \text{ in.})$ to 23.5 cm $(9^{1}/_{4} \text{ in.})$ , short	N/C	53.00
U"-type armrests, detachable, flip-back, height-adjustable,		
rom 20.3 cm (8 in.) to 25.4 cm (10 in.) or		
com 25.4 cm (10 in.) to 35.6 cm (14 in.), short or long		
pair	82.00	
ach		94.00
ontoured armrest pads, short or long	N/C	26.00
ibular armrests	N/C	10.00
traight armrest pads, short	N/C	26.00
traight armrest pads, long	N/C	26.00
lothing guards, flexible	N/C	14.00
lothing guards, rigid, detachable	14/6	11.00
pair	59.00	
ach	37.00	44.00
ootrests:		
0° footrests, detachable, swingaway, length-adjustable,		
rom 35.6 cm (14 in.) to 48.3 cm (19 in.), or 70° footrests,		
etachable, swingaway, length-adjustable,		
rom 33.0 cm (13 in.) to 43.2 cm (17 in.)	N/C	78.00
	IN/C	70.00
0° footrests, "V"-shaped, detachable, swingaway,		
ength-adjustable, from 36.8 cm $(14^{1/2} \text{ in.})$ to 43.2 cm (17 in.)	102.00	
pair	102.00	100.00
ach		129.00
0° elevating legrests, detachable, swingaway,		
ength-adjustable, from 40.6 cm (16 in.)		
50.8 cm (20 in.)		
pair	210.00	
ach		183.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
elevating legrests, compensating mechanism		
a pair	210.00	
each		183.00
footrest extensions	<b>7</b> < 00	
a pair	76.00	20.00
each		38.00
modification of footrest length by - 2.5 cm (1 in.)		
or by - 5.1 cm (2 in.)	150.00	
n pair	150.00	75.00
each	NI/C	75.00
padded calfrests	N/C	17.00
single calf strap	43.00	43.00
louble calf strap	53.00 N/C	53.00
folding footplates, standard or tubular footplates, angle-adjustable	N/C	37.00
olding footplates, angle-adjustable a pair	72.00	
each	72.00	73.00
olding footplates, oversized		73.00
a pair	28.00	
each	28.00	51.00
neel loops, non-adjustable	N/C	3.00
neel loops, length-adjustable	N/C	10.00
oe loops	14,0	10.00
a pair	14.00	
each	11.00	7.00
neel loops and ankle straps		
pair	32.00	
each		16.00
Wheels and frame Types of drive systems :		10.00
nandrims with vertical or oblique projections		
a pair	155.00	
each		111.00
anodized aluminum handrims, 50.8 cm (20 in.),		
55.9 cm (22 in.), or 61.0 cm (24 in.)	N/C	33.00
plastic-coated handrims		
ı pair	52.00	
each		59.00
ront anti-tip rollers		
pair	95.00	
âch		48.00
ane holder	32.00	32.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks:		
standard wheel locks, push-to-lock	N/C	44.00
standard wheel locks, pull-to-lock a pair	32.00	
each	22111	60.00
wheel lock extensions	22.00	
a pair each	32.00	16.00
anti-rollback brakes		10.00
a pair	98.00	
each		93.00
Types of forks:		
standard forks	N/C	33.00
fork-locking mechanisms	06.00	
a pair each	96.00	48.00
Rear axles: threaded axles	N/C	15.00
quick-release axles	N/C	13.00
a pair	76.00	
each		53.00
Types of wheels:		
rear mag wheels, solid tires, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	42.00
rear mag wheels, standard pressure, 61.0 cm (24 in.) rear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C	69.00
or 55.9 cm (22 in.)	N/C	69.00
front wheels, solid tires, 12.7 cm (5 in.), 15.2 cm (6 in.)	1,0	0,.00
or 20.3 cm (8 in.) X 2.5 cm (1 in.)	N/C	23.00
front wheels, inner tube, 15.2 cm (6 in.) or 20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)		
a pair	32.00	
each	22.00	39.00
front wheels, semi-pneumatic tires,		
15.2 cm (6 in.) X 2.5 cm (1 in.)		
or 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair	54.00	
each	2 1.00	50.00
airless inserts for front wheels		
a pair	95.00	TAT / A
each airless inserts for rear wheels		N/A
a pair	99.00	
each		N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
spoke guards * a pair each	82.00	41.00
quick-release axles with lever mechanism *	76.00	11.00
a pair each	70.00	53.00

#### DEVICE FROM: INVACARE CANADA INC.

**PRICE** 

# WHEEL CHAIR, "ACTION XTRA" MODEL

\$795.00

# **Basic Component(s)**

# **Body support system**

- back, height-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seating height: 46.4 cm (18<sup>1</sup>/<sub>4</sub> in.), 47.0 cm (18<sup>1</sup>/<sub>2</sub> in.), 50.2 cm (19<sup>3</sup>/<sub>4</sub> in.), 50.8 cm (20 in.)
- seat width: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.)
- · supple seat and back, nylon
- · push handles
- safety belt, velcro-type, auto-type

#### Armrests

- "L"-type armrests, detachable, flip-back, height-adjustable, from 18.4 cm (7<sup>1</sup>/<sub>4</sub> in.) to 23.5 cm (9<sup>1</sup>/<sub>4</sub> in.), short
- · armrest pads, straight or contoured, short, long
- tubular armrests
- · clothing guards, flexible

# **Footrests**

- 60° or 80° footrests, fixed, length-adjustable, from 35.6 cm (14 in.) to 43.2 cm (17 in.)
- 60° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.); 70° footrests, detachable, swingaway, length-adjustable, from 33.0 cm (13 in.) to 43.2 cm (17 in.)
- · folding footplates, standard or tubular
- heel loops, non-adjustable
- heel loops, length-adjustable
- · padded calfrests

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- · standard wheel locks, push-to-lock
- · standard forks
- · threaded axles
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)
- optional rounded rear frame

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
supple back, tension-adjustable	63.00	98.00
modification of seat depth to 35.6 cm (14 in.),		
38.1 cm (15 in.), 43.2 cm (17 in.) or 45.7 cm (18 in.)	58.00	N/A
modification of seating height to 43.2 cm (17 in.),	220.00	37/4
45.1 cm $(17^{3}/_{4} \text{ in.})$ or 54.0 cm $(21^{1}/_{4} \text{ in.})$	228.00	N/A
modification of seat width to 48.3 cm (19 in.),	117.00	NT/A
50.8 cm (20 in.) or 55.9 cm (22 in.)	115.00	N/A N/A
modification of back height to 50.8 cm (20 in.)	58.00	37.00
push handles supple back, nylon	N/C N/C	35.00
supple seat, nylon	N/C N/C	35.00
seat cushion, flat, foam, 5.1 cm (2 in.)	55.00	55.00
seat cushion, flat, foam, 7.6 cm (3 in.)	55.00	55.00
safety belt, velcro-type	N/C	20.00
safety belt, auto-type	N/C	30.00
•	100	30.00
Armrests: "L"-type armrests, detachable, swingaway,		
height-adjustable, from 18.4 cm (7 <sup>1</sup> / <sub>4</sub> in.)		
to 23.5 cm ( $9^{1/4}$ in.), short	N/C	53.00
"U"-type armrests, detachable, flip-back,	14/6	33.00
height-adjustable, from 20.3 cm (8 in.)		
to 25.4 cm (10 in.) or from 25.4 cm (10 in.)		
to 35.6 cm (14 in.), short or long		
a pair	82.00	
each		94.00
"T"-type armrests, detachable, height-adjustable,		
from 12.7 cm (5 in.) to 20.3 cm (8 in.) or		
from 20.3 cm (8 in.) to 27.9 cm (11 in.)		
a pair	82.00	
each		94.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
ontoured armrest pads, short or long	N/C	26.00
ubular armrests	N/C	10.00
traight armrest pads, short	N/C	26.00
traight armrest pads, long	N/C	26.00
lothing guards, flexible	N/C	14.00
lothing guards, rigid, detachable		
pair	59.00	
ach		44.00
Footrests:		
60° footrests, detachable, swingaway, length-adjustable,		
rom 35.6 cm (14 in.) to 48.3 cm (19 in.);		
or 70° footrests, detachable, swingaway,		
ength-adjustable, from 33.0 cm (13 in.)		
o 43.2 cm (17 in.)	N/C	78.00
50° or 70° footrests, detachable, swingaway,		
ength-adjustable, from 24.8 cm (9 <sup>3</sup> / <sub>4</sub> in.)		
o 35.6 cm (14 in.)		
pair	138.00	
ach		147.00
'0° footrests, "V"-shaped, detachable, swingaway,		
ength-adjustable, from 36.8 cm $(14^{1}/_{2} \text{ in.})$		
o 43.2 cm (17 in.)		
pair	102.00	
ach		129.00
60° or 80° footrests, fixed, length-adjustable,		
rom 35.6 cm (14 in.) to 43.2 cm (17 in.)	N/C	67.00
50° elevating legrests, detachable, swingaway,		
ength-adjustable, from 40.6 cm (16 in.)		
o 50.8 cm (20 in.)		
pair	210.00	
ach		183.00
levating legrests, compensating mechanism		
pair	210.00	
each		183.00
nodification of length of elevating legrests,		
by -2.5 cm (1 in.) or by -5.1 cm (2 in.)		
pair	150.00	
ach		75.00
ootrest extensions		
pair	76.00	
ach		38.00
added calfrests	N/C	17.00
ingle calf strap	43.00	43.00
ouble calf strap	53.00	53.00
olding footplates, standard or tubular	N/C	37.00
olding footplates, angle-adjustable	1,, 0	37.00
pair	72.00	
ach	72.00	73.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
folding footplates, oversized		
a pair	28.00	
each	27/6	51.00
heel loops, non-adjustable	N/C	3.00
neel loops, length-adjustable	N/C	10.00
oe loops	15.00	
a pair each	15.00	8.00
neel loops and ankle straps		8.00
pair	32.00	
each	32.00	16.00
		10.00
Wheels and frame Types of drive systems :		
nandrims with vertical or oblique projections		
a pair	155.00	
each		111.00
nodized aluminum handrims, 50.8 cm (20 in.),		
55.9 cm (22 in.), or 61.0 cm (24 in.)	N/C	33.00
plastic-coated handrims		
n pair	52.00	<b>*</b> 0.00
each		59.00
ront anti-tip rollers	05.00	
a pair each	95.00	48.00
each cane holder	32.00	32.00
ane noider	32.00	32.00
Wheel locks:	27/0	44.00
tandard wheel locks, push-to-lock tandard wheel locks, pull-to-lock	N/C	44.00
pair	32.00	
each	2 = 10 0	60.00
wheel lock extensions		
pair	32.00	
ach		16.00
nti-rollback brakes		
pair	98.00	
ach		93.00
Types of forks:		
tandard forks	N/C	33.00
ork-locking mechanisms		
pair	100.00	=0.c-
ach		50.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Rear axles:		
threaded axles	N/C	15.00
quick-release axles a pair	76.00	
each	70.00	53.00
axle extension plates for amputee		
a pair	68.00	50.00
each		50.00
Frame:		
optional rounded rear frame	N/C	N/A
optional heavy-duty frame: 45.7 cm (18 in.) X 40.6 cm (16 in.), 45.7 cm (18 in.) X 45.7 cm (18 in.), 50.8 cm		
(20 in.) X 50.8 cm (20 in.), 50.8 cm (20 in.) X 55.9 cm		
(22 in.), 55.9 cm (22 in.) X 55.9 cm (22 in.)	257.00	N/A
Types of wheels:		
rear mag wheels, solid tires, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	42.00
rear mag wheels, standard pressure, 50.8 cm (20 in.),	N/C	60.00
55.9 cm (22 in.) or 61.0 cm (24 in.) spoked rear wheels, solid tires (KIK), 61.0 cm (24 in.)	N/C	69.00
a pair	82.00	
each		83.00
heavy-duty rear wheels, solid tires (KIK), 61.0 cm (24 in.)	104.00	
a pair each	104.00	94.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),		94.00
55.9 cm (22 in.) or 61.0 cm (24 in.)		
a pair	82.00	
each		83.00
spoked rear wheels, high pressure, 61.0 cm (24 in.) a pair	82.00	
each	02.00	83.00
spoked rear wheels, heavy-duty, standard		
pressure or high pressure, 61.0 cm (24 in.)	104.00	
a pair each	104.00	94.00
front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.),		94.00
15.2 cm (6 in.) or 12.7 cm (5 in.)	N/C	23.00
front wheels, semi-pneumatic, 15.2 cm (6 in.) X 2.5 cm		
(1 in.) or 20.3 cm (8 in.) X 5.1 cm (2 in.)	54.00	
a pair each	54.00	50.00
front wheels, inner tube, 15.2 cm (6 in.)		50.00
or 20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)		
a pair	32.00	20.00
each		39.00

\$1 075.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
airless inserts for front wheels	0.5.00	
a pair each	95.00	N/A
airless inserts for rear wheels		17/11
a pair each	99.00	N/A
Component(s) under Special Consideration		
spoke guards * a pair each	82.00	41.00
quick-release axles with lever mechanism * a pair each	76.00	53.00
DEVICE FROM: INVACARE INC.		
		PR

# Basic Component(s)

# **Body support system**

- back, height-adjustable, from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- seating height: from 42.5 cm (16<sup>3</sup>/<sub>4</sub> in.) to 50.8 cm (20 in.)

WHEEL CHAIR, "SPYDER" MODEL

- seat width: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.)
- supple seat and back, nylon
- push handles
- safety belt, velcro-type, auto-type

#### Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable, from 18.4 cm (7<sup>1</sup>/<sub>4</sub> in.) to 23.5 cm (9<sup>1</sup>/<sub>4</sub> in.), short
- · straight armrest pads, short, long
- tubular armrests
- clothing guards, flexible

#### **Footrests**

- 60° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.); 70° footrests, detachable, swingaway, length-adjustable, from 33.0 cm (13 in.) to 43.2 cm (17 in.)
- · folding footplates, standard or tubular
- heel loops, non-adjustable
- heel loops, length-adjustable
- padded calfrests

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- · standard wheel locks, push-to-lock
- · standard forks
- · threaded axles
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.) or 7.6 cm (3 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
supple back, tension-adjustable	63.00	98.00
modification of seat depth to 35.6 cm (14 in.),		
38.1 cm (15 in.), 43.2 cm (17 in.) or 45.7 cm (18 in.)	58.00	N/A
modification of seat width to 48.3 cm (19 in.)		
or 50.8 cm (20 in.)	115.00	N/A
modification of back height to 50.8 cm (20 in.)	58.00	N/A
push handles	N/C	37.00
supple back, nylon	N/C	35.00
supple seat, nylon	N/C	35.00
seat cushion, flat, foam, 5.1 cm (2 in.)	55.00	55.00
seat cushion, flat, foam, 7.6 cm (3 in.)	55.00	55.00
safety belt, velcro-type	N/C	20.00
safety belt, auto-type	N/C	30.00
Armrests:		
"L"-type armrests, detachable, swingaway,		
height-adjustable, from 18.4 cm (7 <sup>1</sup> / <sub>4</sub> in.)		
to 23.5 cm ( $9^{1}/_{4}$ in.), short	N/C	53.00
"T"-type armrests, detachable, height-adjustable,		
from 15.2 cm (6 in.) to 25.4 cm (10 in.)		
or from 20.3 cm (8 in.) to 35.6 cm (14 in.)		
a pair	82.00	
each		94.00
tubular armrests	N/C	10.00
straight armrest pads, short	N/C	26.00
straight armrest pads, long	N/C	26.00
clothing guards, flexible	N/C	14.00
clothing guards, rigid, detachable		
a pair	59.00	
each		44.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
60° footrests, detachable, swingaway, length-adjustable,		
from 35.6 cm (14 in.) to 48.3 cm (19 in.);		
or 70° footrests, detachable, swingaway,		
length-adjustable, from 33.0 cm (13 in.)	3716	=
to 43.2 cm (17 in.)	N/C	78.00
60° or 70° footrests, detachable, swingaway,		
ength-adjustable, from 24.8 cm $(9^3/_4 \text{ in.})$		
to 35.6 cm (14 in.) a pair	138.00	
each	138.00	147.00
70° footrests, "V"-shaped, detachable, swingaway,		147.00
ength-adjustable, from 36.8 cm ( $14^{1}/_{2}$ in.)		
o 43.2 cm (17 in.)		
a pair	102.00	
each	102.00	129.00
90° footrests, detachable, swingaway, length-adjustable,		
From 14.0 cm ( $5^{1}/_{2}$ in.) to 29.2 cm ( $11^{1}/_{2}$ in.)		
a pair	138.00	
each		147.00
60° elevating legrests, detachable, swingaway,		
ength-adjustable, from 40.6 cm (16 in.)		
o 50.8 cm (20 in.)		
ı pair	210.00	40000
each		183.00
modification of length of elevating legrests,		
by -2.5 cm (1 in.) or by -5.1 cm (2 in.)	150.00	
a pair each	150.00	75.00
ootrest extensions		73.00
oonest extensions a pair	76.00	
each	70.00	38.00
padded calfrests	N/C	17.00
single calf strap	43.00	43.00
louble calf strap	53.00	53.00
olding footplates, standard or tubular	N/C	37.00
folding footplates, angle-adjustable		
n pair	72.00	
each		73.00
olding footplates, oversized		
pair	28.00	
each		51.00
7.6 cm (3 in.) extension for 90° footrests		
ı pair	32.00	
each	37/2	16.00
neel loops, non-adjustable	N/C	3.00
neel loops, length-adjustable	N/C	10.00
oe loops	15.00	
pair	15.00	8.00
each		8.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
heel loops and ankle straps a pair each	32.00	16.00
Wheels and frame Types of drive systems:		
handrims with vertical or oblique projections a pair	155.00	111.00
each anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), or 61.0 cm (24 in.)	N/C	111.00 33.00
plastic-coated handrims a pair	52.00	33.00
each front anti-tip rollers	32.00	59.00
a pair each	95.00	48.00
cane holder	32.00	32.00
Wheel locks: standard wheel locks, push-to-lock	N/C	44.00
standard wheel locks, pull-to-lock a pair each	32.00	60.00
wheel lock extensions a pair	32.00	00.00
each anti-rollback brakes		16.00
a pair each	98.00	93.00
swing-away brakes a pair each	32.00	60.00
Types of forks:		00.00
standard forks fork-locking mechanisms	N/C	33.00
a pair each	100.00	50.00
Rear axles:	N/C	15.00
threaded axles quick-release axles	N/C	15.00
a pair each	76.00	53.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
rear mag wheels, solid tires, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	42.00
rear mag wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	69.00
spoked rear wheels, solid tires (KIK), 61.0 cm (24 in.)		
or 66.0 cm (26 in.) a pair	82.00	
each	82.00	83.00
rear wheels, heavy-duty, solid tires (KIK),		03.00
61.0 cm (24 in.) or 66.0 cm (26 in.)		
a pair	104.00	
each		94.00
spoked rear wheels, standard pressure,		
50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)		
or 66.0 cm (26 in.)	02.00	
a pair	82.00	02.00
each spoked rear wheels, high pressure, 61.0 cm (24 in.)		83.00
or 66.0 cm (26 in.)		
a pair	82.00	
each	02.00	83.00
spoked rear wheels, heavy-duty, standard pressure or		
high pressure, 61.0 cm (24 in.) or 66.0 cm (26 in.)		
a pair	104.00	
each		94.00
front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.),	N/C	22.00
15.2 cm (6 in.), 12.7 cm (5 in.) or 7.6 cm (3 in.)	N/C	23.00
front wheels, inner tube, 15.2 cm (6 in.) or 20.3 cm (8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.)		
a pair	32.00	
each	22.00	39.00
airless inserts for front wheels		
a pair	95.00	
each		N/A
airless inserts for rear wheels		
a pair	99.00	37/4
each		N/A
Component(s) under Special Consideration		
spoke guards *		
a pair	82.00	
each		41.00
quick-release axles with lever mechanism *		
a pair	76.00	<b>50.00</b>
each		53.00

#### DEVICE FROM: INVACARE CANADA INC.

PRICE

#### WHEEL CHAIR, "ACTION ALLEGRO" MODEL

\$1 075.00

#### **Basic Component(s)**

# **Body support system**

- back, height-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- front seating height: from 38.1 cm (15 in.) to 54.0 cm (21<sup>1</sup>/<sub>4</sub> in.)
- seat width: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- supple seat and back, nylon
- · push handles
- safety belt, velcro-type, auto-type

#### Armrests

- "I'-type armrests, flip-back, height-adjustable, from 12.7 cm (5 in.) to 25.4 cm (10 in.), short, long
- "U"-type armrests, height-adjustable, from 20.3 cm (8 in.) to 25.4 cm (10 in.) or from 25.4 cm (10 in.) to 35.6 cm (14 in.), long
- "T"-type armrests, detachable, height-adjustable, from 12.7 cm (5 in.) to 20.3 cm (8 in.) or from 20.3 cm (8 in.) to 27.9 cm (11 in.), short or long
- armrest pads, straight or contoured, short, long
- · tubular armrests
- · clothing guards, flexible

#### **Footrests**

- 60° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.); 70° footrests, detachable, swingaway, length-adjustable, from 33.0 cm (13 in.) to 43.2 cm (17 in.)
- · folding footplates, standard or tubular
- heel loops, non-adjustable
- heel loops, length-adjustable
- padded calfrests

- · depth-adjustable frame, folding
- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- · standard wheel locks, push-to-lock
- · standard forks
- · threaded axles
- rear mag wheels, solid tires, 50.8 cm (20 in.),
   55.9 cm (22 in.), 61.0 cm (24 in.), standard pressure,
   50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.), 7.6 cm (3 in.)

Basic and Optional Component(s)  Body support system Seat and back: supple back, tension-adjustable push handles supple back, nylon supple back, nylon supple seat, nylon seat cushion, flat, foam, 5.1 cm (2 in.) seat cushion, flat, foam, 7.6 cm (3 in.)  Body support system Scale and Optional Component(s)  63.00 N/C supple seat, nylon N/C seat cushion, flat, foam, 5.1 cm (2 in.) Scale and Optional Component(s)	98.00
Seat and back:  supple back, tension-adjustable push handles supple back, nylon supple seat, nylon seat cushion, flat, foam, 5.1 cm (2 in.) seat cushion, flat, foam, 7.6 cm (3 in.)  Solution  63.00 N/C N/C Solution N/C Solution	98 00
supple back, tension-adjustable push handles supple back, nylon supple seat, nylon seat cushion, flat, foam, 5.1 cm (2 in.) seat cushion, flat, foam, 7.6 cm (3 in.)  63.00 N/C N/C 55.00 55.00	98 00
push handles N/C supple back, nylon N/C supple seat, nylon N/C seat cushion, flat, foam, 5.1 cm (2 in.) 55.00 seat cushion, flat, foam, 7.6 cm (3 in.) 55.00	98 NN
supple back, nylon  supple seat, nylon  seat cushion, flat, foam, 5.1 cm (2 in.)  seat cushion, flat, foam, 7.6 cm (3 in.)  Solution  So	
supple seat, nylon Seat cushion, flat, foam, 5.1 cm (2 in.) Seat cushion, flat, foam, 7.6 cm (3 in.)  N/C S5.00 S5.00	36.00
seat cushion, flat, foam, 5.1 cm (2 in.) seat cushion, flat, foam, 7.6 cm (3 in.) 55.00	35.00
seat cushion, flat, foam, 7.6 cm (3 in.) 55.00	35.00
	55.00
2 1 1 1	55.00
afety belt, velcro-type N/C	20.00
afety belt, auto-type N/C	30.00
nodification of seat width to 48.3 cm (19 in.)	37/4
or 50.8 cm (20 in.) 115.00	N/A
Armrests:	
'T"-type armrests, detachable, height-adjustable,	
from 12.7 cm (5 in.) to 20.3 cm (8 in.)	
or from 20.3 cm (8 in.) to 27.9 cm (11 in.),	04.00
hort or long N/C	94.00
T'-type armrests, flip-back, height-adjustable,	<i>52</i> 00
From 12.7 cm (5 in.) to 25.4 cm (10 in.), short or long N/C	53.00
'U"-type armrests, height-adjustable, from 20.3 cm (8 in.) to 25.4 cm (10 in.) or from 25.4 cm (10 in.)	
to 35.6 cm (14 in.), long N/C	94.00
armrest pads, straight or contoured, short  N/C	26.00
armrest pads, straight or contoured, long N/C	26.00
ubular armrests N/C	10.00
clothing guards, flexible N/C	14.00
clothing guards, rigid, detachable	11.00
pair 59.00	
each	44.00
Footrests:	
60° footrests, detachable, swingaway, length-adjustable,	
from 35.6 cm (14 in.) to 48.3 cm (19 in); or $70^{\circ}$ footrests,	
detachable, swingaway, length-adjustable,	
from 33.0 cm (13 in.) to 43.2 cm (17 in.) N/C	78.00
50° or 70° footrests, detachable, swingaway,	
ength-adjustable, from 24.8 cm (9 <sup>3</sup> / <sub>4</sub> in.)	
o 35.6 cm (14 in.)	
pair 138.00	
each	147.00
70° footrests, "V"-shaped, detachable, swingaway,	
ength-adjustable, from 36.8 cm $(14^{1}/_{2} in.)$	
o 43.2 cm (17 in.)	
pair 102.00	
ach	129.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
0° footrests, detachable, swingaway, length-adjustable,		
rom 14.0 cm ( $5^{1}/_{2}$ in.) to 29.2 cm ( $11^{1}/_{2}$ in.)		
pair	138.00	=
ach		147.00
0° elevating legrests, detachable, swingaway, ength-adjustable, from 40.6 cm (16 in.)		
o 50.8 cm (20 in.)		
pair	210.00	
ach	210.00	183.00
.1 cm (2 in.) extensions		103.00
pair	76.00	
ach		38.00
.6 cm (3 in.) extension for 90° footrests	32.00	16.00
added calfrests	N/C	17.00
ingle calf strap	43.00	43.00
ouble calf strap	53.00	53.00
olding footplates, standard or tubular	N/C	37.00
olding footplates, angle-adjustable	72.00	
pair ach	72.00	73.00
olding footplates, oversized		75.00
pair	28.00	
ach	20.00	51.00
eel loops, non-adjustable	N/C	3.00
eel loops, length-adjustable	N/C	10.00
pe loops		
pair	15.00	
ach		8.00
eel loops and ankle straps	22.00	
pair ach	32.00	16.00
		10.00
Vheels and frame Types of drive systems:		
andrims with vertical or oblique projections		
pair	155.00	
ach		111.00
nodized aluminum handrims, 50.8 cm (20 in.),	NG	22.00
5.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	33.00
lastic-coated handrims	52.00	
pair ach	32.00	59.00
acn ront anti-tip rollers		39.00
pair	95.00	
ach	75.00	48.00
		. 5.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks:	N/C	44.00
standard wheel locks, push-to-lock standard wheel locks, pull-to-lock	N/C	44.00
a pair	32.00	
each wheel lock extensions		60.00
a pair	32.00	
each		16.00
anti-rollback brakes	08.00	
a pair each	98.00	93.00
Types of forks:		
standard forks	N/C	33.00
fork-locking mechanisms a pair	100.00	
each	100.00	50.00
Rear axles:	N/G	15.00
threaded axles quick-release axles	N/C	15.00
a pair	76.00	
each		53.00
axle extension plates for amputee a pair	68.00	
each	00.00	50.00
offset axle plates	60.00	
a pair each	68.00	50.00
Types of wheels:		
rear mag wheels, solid tires, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 (24 in.)	N/C	42.00
rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	69.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	82.00	
a pair each	62.00	83.00
spoked rear wheels, high pressure, 61.0 cm (24 in.)		22.30
a pair each	82.00	83.00
spoked rear wheels, solid tires (KIK), 61.0 cm (24 in.)		65.00
a pair	82.00	
each		83.00
front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 7.6 cm (3 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)	N/C	23.00
front wheels, semi-pneumatic tires, 15.2 cm	1,, 0	25.50
(6 in.) X 2.5 cm (1 in.) or 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair	54.00	

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, inner tube, 15.2 cm (6 in.) or 20.3 cm (8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) a pair each	32.00	39.00
airless inserts for front wheels a pair each	95.00	N/A
airless inserts for rear wheels a pair each	99.00	N/A
Component(s) under Special Consideration		
spoke guards * a pair each quick-release axles with lever mechanism *	82.00	41.00
a pair	76.00	52.00
each reclining back * multi-position fork bar *	438.00	53.00 438.00
each a pair	36.00	44.00

## **DEVICE FROM: INVACARE CANADA INC.**

**PRICE** 

# WHEEL CHAIR, "ACTION JR" MODEL

\$795.00

## Basic Component(s)

# **Body support system**

- back, height-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- front seating height:  $46.4 \text{ cm } (18^{1}/_4 \text{ in.})$ ,  $47.0 \text{ cm } (18^{1}/_2 \text{ in.})$ ,  $50.2 \text{ cm } (19^{3}/_4 \text{ in.})$ , or 50.8 cm (20 in.)
- seat width: 30.5 cm (12 in.), 32.5 cm (13 in.), 35.6 cm (14 in.)
- seat depth: 30.5 cm (12 in.), 35.6 cm (14 in.)
- supple seat and back, nylon
- push handles
- safety belt, velcro-type, auto-type

#### Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable, from 18.4 cm (7<sup>1</sup>/<sub>4</sub> in.) to 23.5 cm (9<sup>1</sup>/<sub>4</sub> in.), short
- armrest pads, straight or contoured, short, long
- · tubular armrests
- clothing guards, flexible

### **Footrests**

- 60°, 70° footrests, detachable, swingaway and length-adjustable, from 24.8 cm (9³/4 in.) to 35.6 cm (14 in.)
- 70° footrests, detachable, swingaway and length-adjustable, from 33.0 cm (13 in.) to 43.2 cm (17 in.)
- 60° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 90° footrests, length-adjustable, from 14 cm (5½ in.) to 29.2 cm (11½ in.)
- 90° footrests, fixed, for seat depths of 25.4 cm (10 in.) and 27.9 cm (11 in.)
- folding footplates, standard or tubular
- heel loops, non-adjustable
- heel loops, length-adjustable

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock
- · standard forks
- · threaded axles
- rear mag wheels, solid tires, 50.8 cm (20 in.),
  55.9 cm (22 in.), 61.0 cm (24 in.); standard pressure,
  50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)
- · optional rounded rear frame

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
upple back, tension-adjustable	63.00	98.00
nodification of seat depth to 25.4 cm (10 in.),		
27.9 cm (11 in.) or 33.0 cm (13 in.)	58.00	N/A
nodification of seating height to 43.2 cm (17 in.),		
$5.1 \text{ cm } (17^3/_4 \text{ in.}) \text{ or } 54.0 \text{ cm } (21^1/_4 \text{ in.})$	228.00	N/A
nodification of back height to 50.8 cm (20 in.)	58.00	N/A
supple back, nylon	N/C	35.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
supple seat, nylon	N/C	35.00
oush handles	N/C	37.00
eat cushion, flat, foam, 5.1 cm (2 in.)	55.00	55.00
eat cushion, flat, foam, 7.6 cm (3 in.)	55.00	55.00
afety belt, velcro-type	N/C	20.00
afety belt, auto-type	N/C	30.00
armrests:		
L"-type armrests, detachable, swingaway,		
eight-adjustable, from 18.4 cm $(7^{1}/_{4} in.)$		
23.5 cm (9 <sup>1</sup> / <sub>4</sub> in.), short	N/C	53.00
U"-type armrests, detachable, height-adjustable,		
rom 20.3 cm (8 in.) to 25.4 cm (10 in.) or		
rom 25.4 cm (10 in.) to 35.6 cm (14 in.),		
hort or long		
pair	82.00	
ach	02.00	94.00
T"-type armrests, detachable, height-adjustable,		7 <del>4</del> .00
rom 12.7 cm (5 in.) to 20.3 cm (8 in.) or		
rom 20.3 cm (8 in.) to 27.9 cm (11 in.)	92.00	
pair	82.00	04.00
ach	NG	94.00
lothing guards, flexible	N/C	14.00
lothing guards, rigid, detachable	<b>5</b> 0.00	
pair	59.00	
ach		44.00
rmrest pads, straight or contoured, short or long	N/C	26.00
ubular armrests	N/C	10.00
Cootrests:		
0° footrests, detachable, swingaway,		
ength-adjustable, from 35.6 cm (14 in.)		
o 48.3 cm (19 in.); or 70° footrests, detachable,		
wingaway, length-adjustable, from 33.0 cm (13 in.)		
0 43.2 cm (17 in.)	N/C	78.00
0° or 70° footrests, detachable, swingaway,		
ength-adjustable, from 24.8 cm (9 <sup>3</sup> / <sub>4</sub> in.)		
35.6 cm (14 in.)	N/C	147.00
0° footrests, length-adjustable, from		
4.0 cm ( $5^{1}/_{2}$ in.) to 29.2 cm ( $11^{1}/_{2}$ in.)	N/C	147.00
0° footrests, fixed, for seat depths of		
5.4 cm (10 in.) and 27.9 cm (11 in.)	N/C	78.00
0° tapered footrests, detachable, length-adjustable,	100	73.00
com 36.8 cm $(14^{1}/_{2} \text{ in.})$ to 43.2 cm $(17 \text{ in.})$	102.00	129.00
ingle calf strap	43.00	
		43.00
ouble calf strap	53.00 N/C	53.00
olding footplates, standard or tubular	N/C	37.00
olding footplates, angle-adjustable	72.00	
pair	72.00	<b>50</b> 00
nch		73.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
heel loops, length-adjustable heel loops, non-adjustable	N/C N/C	10.00 3.00
toe loops a pair each	15.00	8.00
pair ach	32.00	16.00
1.6 cm (3 in.) extensions for 90° footrests pair ach	32.00	16.00
5.1 cm (2 in.) extensions a pair each	76.00	38.00
Wheels and frame Types of drive systems :		
nandrims with vertical or oblique projections a pair each	155.00	111.00
plastic-coated handrims a pair each	52.00	59.00
nodized aluminum handrims, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) ront anti-tip rollers	N/C	33.00
pair ach	95.00	48.00
ane holder	32.00	32.00
Wheel locks: tandard wheel locks, push-to-lock tandard wheel locks, pull-to-lock	N/C	44.00
pair ach	32.00	60.00
wheel lock extensions pair ach	32.00	16.00
nti-rollback brakes pair ach	98.00	93.00
Types of forks: tandard forks	N/C	33.00
ork-locking mechanisms a pair each	100.00	50.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Rear axles:		
threaded axles	N/C	15.00
quick-release axles	76.00	
a pair each	70.00	53.00
axle extension plates for amputee		33.00
a pair	68.00	
each		50.00
Frame:		
optional rounded rear frame	N/C	N/A
Types of wheels:		
rear mag wheels, solid tires, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	42.00
rear mag wheels, standard pressure, 50.8 cm (20 in.),	N/G	<b>50.00</b>
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	69.00
spoked rear wheels, high pressure, 61.0 cm (24 in.) spoked rear wheels, standard pressure, 50.8 cm (20 in.),	82.00	83.00
55.9 cm (22 in.) or 61.0 cm (24 in.)	82.00	83.00
spoked rear wheels, solid tires (KIK), 61.0 cm (24 in.)	82.00	83.00
front wheels, solid tires, 12.7 cm (5 in.), 15.2 cm (6 in.)		
or 20.3 cm (8 in.) X 2.5 cm (1 in.)	N/C	23.00
front wheels, inner tube, 15.2 cm (6 in.) or 20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)		
a pair	32.00	
each	32.00	39.00
front wheels, semi-pneumatic tires,		
20.3 cm (8 in.) X 5.1 cm (2 in.)		
or 15.2 cm (6 in.) X 2.5 cm (1 in.)	54.00	
a pair each	54.00	50.00
airless inserts for front wheels		30.00
a pair	95.00	
each		N/A
airless inserts for rear wheels	00.00	
a pair each	99.00	N/A
		IV/A
Component(s) under Special Consideration		
spoke guards *	0.2.00	
a pair	82.00	41.00
each quick-release axles with lever mechanism *		41.00
a pair	76.00	
each	. 5.55	53.00

### DEVICE FROM: INVACARE CANADA INC.

**PRICE** 

### WHEEL CHAIR, "ACTION ALLEGRO, PEDIATRIC" MODEL

\$1 075.00

### **Basic Component(s)**

## **Body support system**

- back, height-adjustable, from 25.4 cm (10 in.) to 45.7 cm (18 in.)
- seating height: from 38.1 cm (15 in.) to 54.0 cm (21<sup>1</sup>/<sub>4</sub> in.)
- seat width: 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 cm (14 in.)
- seat depth: from 30.5 cm (12 in.) to 40.6 cm (16 in.)
- supple seat and back, nylon
- push handles
- safety belt, velcro-type, auto-type

### **Armrests**

- "I"-type armrests, flib-back and height-adjustable, from 12.7 cm (5 in.) to 25.4 cm (10 in.), short, long
- "U"-type armrests, detachable and height-adjustable, from 20.3 cm (8 in.) to 25.4 cm (10 in.) or from 25.4 cm (10 in.) to 35.6 cm (14 in.), long
- "T"-type armrests, detachable and height-adjustable, from 12.7 cm (5 in.) to 20.3 cm (8 in.) or from 20.3 cm (8 in.) to 27.9 cm (11 in.), short or long
- armrest pads, straight or contoured, short, long
- · clothing guards, flexible
- tubular armrests

#### **Footrests**

- 60° or 70° footrests, detachable, swingaway and length-adjustable, from 24.8 cm (9³/4 in.) to 35.6 cm (14 in.)
- 70° footrests, detachable, swingaway and length-adjustable, from 33.0 cm (13 in.) to 43.2 cm (17 in.)
- 60° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 90° footrests, length-adjustable, from 14.0 cm (5<sup>1</sup>/<sub>2</sub> in.) to 29.2 cm (11<sup>1</sup>/<sub>2</sub> in.)
- 70° footrests, tapered, length-adjustable from 36.8 cm (14<sup>1</sup>/<sub>2</sub> in.) to 43.2 cm (17 in.)
- · folding footplates, standard or tubular
- heel loops, non-adjustable
- heel loops, length-adjustable

- depth-adjustable frame, folding, with angle-adjustable back
- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock
- · standard forks
- · threaded axles
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.); standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.), 12.7 cm (5 in.), 7.6 cm (3 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:	40.00	
supple back, tension-adjustable	63.00	98.00
supple back, nylon	N/C	35.00
upple seat, nylon	N/C	35.00
oush handles	N/C	37.00
eat cushion, flat, foam, 5.1 cm (2 in.)	55.00	55.00
eat cushion, flat, foam, 7.6 cm (3 in.)	55.00	55.00
afety belt, velcro-type	N/C	20.00
safety belt, auto-type	N/C	30.00
Armrests:		
"T"-type armrests, detachable and height-adjustable,		
from 12.7 cm (5 in.) to 20.3 cm (8 in.) or from		
20.3 cm (8 in.) to 27.9 cm (11 in.), short or long	N/C	94.00
'U"-type armrests, detachable and height-adjustable,		
From 20.3 cm (8 in.) to 25.4 cm (10 in.) or		
from 25.4 cm (10 in.) to 35.6 cm (14 in.), long	N/C	94.00
T'-type armrests, flip-back and height-adjustable,		
from 12.7 cm (5 in.) to 25.4 cm (10 in.), short or long	N/C	53.00
clothing guards, flexible	N/C	14.00
clothing guards, rigid, detachable		
ı pair	59.00	
each		44.00
armrest pads, straight or contoured, short or long	N/C	26.00
ubular armrests	N/C	10.00
Footrests:		
50° footrests, detachable, swingaway and		
ength-adjustable, from 35.6 cm (14 in.)		
o 48.3 cm (19 in.); or 70° footrests, detachable,		
wingaway and length-adjustable, from 33.0 cm (13 in.)		
o 43.2 cm (17 in.)	N/C	78.00
5 15.2 cm (17 m.)	11/	, 5.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
60° or 70° footrests, detachable, swingaway,		
ength-adjustable, from 24.8 cm (9 <sup>3</sup> / <sub>4</sub> in.)		
o 35.6 cm (14 in.)	N/C	147.00
0° footrests, length-adjustable, from 14.0 cm (5½ in.)		
o 29.2 cm $(11^{1}/_{2} in.)$	N/C	147.00
'0° footrests, tapered, length-adjustable,		
from 36.8 cm ( $14^{1}/_{2}$ in.) to 43.2 cm (17 in.)	N/C	129.00
ingle calf strap	43.00	43.00
louble calf strap	53.00	53.00
olding footplates, standard or tubular	N/C	37.00
olding footplates, angle-adjustable	<b>53</b> .00	
pair	72.00	72.00
ach	N/C	73.00
neel loops, length-adjustable	N/C	10.00
neel loops, non-adjustable	N/C	3.00
oe loops	15.00	
pair	15.00	0.00
each neel loops and ankle straps		8.00
	32.00	
pair ach	32.00	16.00
7.6 cm (3 in.) extensions for 90° footrests		10.00
pair	32.00	
each	32.00	16.00
6.1 cm (2 in.) extenstions for footrests		10.00
pair	76.00	
each		38.00
Wheels and frame		
Types of drive systems:		
andrims with vertical or oblique projections	155.00	
pair	155.00	111.00
ach		111.00
plastic-coated handrims	52.00	
pair	52.00	59.00
each nodized aluminum handrims, 50.8 cm (20 in.),		39.00
5.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	33.00
	IN/C	33.00
ront anti-tip rollers	95.00	
pair each	73.00	48.00
ane holder	32.00	32.00
uno notuei	32.00	52.00
Wheel locks:		
tandard wheel locks, push-to-lock	N/C	44.00
tandard wheel locks, pull-to-lock		
pair	32.00	
ach		60.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
wheel lock extensions a pair each	32.00	16.00
anti-rollback brakes a pair each	98.00	93.00
Types of forks: standard forks	N/C	33.00
ork-locking mechanisms pair each	100.00	50.00
Rear axles: hreaded axles	N/C	15.00
pair ach	76.00	53.00
xle extension plates for amputee pair ach	68.00	50.00
offset axle plates a pair each	68.00	50.00
Express of wheels:  ear mag wheels, solid tires, 50.8 cm (20 in.),  55.9 cm (22 in.) or 61.0 (24 in.)  ear mag wheels, standard pressure,	N/C	42.00
60.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) poked rear wheels, standard pressure or	N/C	69.00
igh pressure, 61.0 cm (24 in.) pair ach poked rear wheels, standard pressure,	82.00	83.00
0.8 cm (20 in.) or 55.9 cm (22 in.) pair ach	82.00	83.00
poked rear wheels, solid tires (KIK), 61.0 cm (24 in.) pair ach	82.00	83.00
ront wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm 1 <sup>1</sup> / <sub>4</sub> in.), 7.6 cm (3 in.), 12.7 cm (5 in.), 15.2 cm (6 in.) ront wheels, inner tube, 15.2 cm (6 in.)	N/C	23.00
r 20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) pair ach	32.00	39.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
ront wheels, semi-pneumatic tires, 15.2 cm		
6 in.) X 2.5 cm (1 in.) or 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair	54.00	<b>-</b> 0.00
each uirless inserts for front wheels		50.00
pair	95.00	
each uirless inserts for rear wheels		N/A
a pair	99.00	
each		N/A
Component(s) under Special Consideration		
poke guards *		
pair	82.00	41.00
ach uick-release axles with lever mechanism*		41.00
pair	76.00	<b>52</b> .00
ach eclining back with cylinder *	438.00	53.00 438.00

### **DEVICE FROM: ORTHOFAB INC.**

### **PRICE**

# WHEEL CHAIR, "PRIMA" MODEL

\$1 048.00

## Basic Component(s)

### **Body support system**

- supple back, nylon
- back, height-adjustable, from 38.1 cm (15 in.) to 45.7 cm (18 in.)
- seat-to-back angle: adjustable to 90°, 96°
- backposts, straight or at an 8° angle at 20.3 cm (8 in.)
- seat width: from 35.6 cm (14 in.) to 55.9 cm (22 in.)
- seat depth: 40.6 cm (16 in.)
- supple seat, nylon
- front seating height: from 45.7 cm (18 in.) to 50.8 cm (20 in.)
- safety belt, auto-type
- push handles

- "L"-type armrests, detachable, swingaway, height-adjustable, from 12.7 cm (5 in.) to 25.4 cm (10 in.) or from 22.9 cm (9 in.) to 30.5 cm (12 in.), short
- · straight armrest pads, short, long
- · tubular armrests
- clothing guards, flexible

- 60° footrests, "V"-shaped, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.); 70° footrests, "V"-shaped, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests
- folding footplates, tubular
- heel loops, length-adjustable

- · anodized aluminum handrims
- standard wheel locks, push-to-lock
- standard forks, high forks
- · threaded axles
- spoked rear wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 17.8 cm (7 in.) or 20.3 cm (8 in.) X 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
supple back, tension-adjustable	64.00	124.00
rigid seat, flat, all sizes	109.00	163.00
modification of back height to 33.0 cm (13 in.),		
35.6 cm (14 in.) or from 48.3 cm (19 in.)		
o 55.9 cm (22 in.)	97.00	N/A
nodification of seat depth to 35.6 cm (14 in.),		
38.1 cm (15 in.), 43.2 cm (17 in.), 45.7 cm (18 in.),		
48.3 cm (19 in.) or 50.8 cm (20 in.)	101.00	N/A
modification of seating height: decrease of		
$3.2 \text{ cm } (1^{1}/_{4} \text{ in.}) \text{ or } 5.7 \text{ cm } (2^{1}/_{4} \text{ in.})$	208.00	N/A
supple back, nylon	N/C	60.00
upple seat, nylon	N/C	54.00
oush handles	N/C	N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	52.00	52.00
eat cushion, flat, foam, 7.6 cm (3 in.)	52.00	52.00
afety belt, velcro-type	27.00	62.00
safety belt, auto-type	N/C	35.00
safety belt, airplane-type	38.00	73.00
backposts, straight or at an 8° angle at 20.3 cm (8 in.)	N/C	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
'L"-type armrests, detachable, swingaway,		
neight-adjustable, from 12.7 cm (5 in.)		
to 25.4 cm (10 in.) or from 22.9 cm (9 in.)		
to 30.5 cm (12 in.), short	N/C	48.00
'L"-type armrests, detachable, swingaway,		
neight-adjustable, from 12.7 cm (5 in.)		
to 25.4 cm (10 in.) or from 22.9 cm (9 in.)		
o 30.5 cm (12 in.), long	20.00	
a pair	30.00	62.00
each		63.00
'U"-type armrests, detachable, flip-back,		
neight-adjustable, from 20.3 cm (8 in.) to 27.9 cm (11 in.)		
or from 22.9 cm (9 in.) to 30.3 cm (12 in.), with transfer		
assists and rigid clothing guards, short a pair	98.00	
each	76.00	97.00
'U"-type armrests, detachable, flip-back,		71.00
neight-adjustable, from 20.3 cm (8 in.)		
to 27.9 cm (11 in.) or from 22.9 cm (9 in.)		
to 30.5 cm (12 in.), with transfer assists and rigid		
clothing guards, long		
a pair	144.00	
each		120.00
'U"-type armrests, for angle-adjustable back,		
neight-adjustable, from 20.3 cm (8 in.)		
to 27.9 cm (11 in.), short		
a pair	98.00	
each		135.00
'U"-type armrests, for angle-adjustable back,		
neight-adjustable, from 20.3 cm (8 in.)		
o 27.9 cm (11 in.), long	144.00	
a pair each	144.00	160.00
ubular armrests	N/C	7.00
contoured armrest pads, long	N/C	7.00
a pair	78.00	
each	70.00	53.00
contoured armrest pads, short		33.00
a pair	74.00	
each		51.00
straight armrest pads, long	N/C	14.00
straight armrest pads, short	N/C	11.00
clothing guards, flexible	N/C	35.00
clothing guards, rigid, detachable		
pair	60.00	
ach		65.00
nodification of height of "U"-type armrests, to under		
20.3 cm (8 in.) or to over 30.5 cm (12 in.)	72.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
60° footrests, detachable, swingaway and		
ength-adjustable, from 35.6 cm (14 in.)		
to 48.3 cm (19 in.)	27.00	
a pair each	27.00	N/A
70° footrests, detachable, swingaway and		IN/A
ength-adjustable, from 35.6 cm (14 in.)		
o 48.3 cm (19 in.)		
a pair	27.00	
each		N/A
50° footrests, "V"-shaped, detachable, swingaway		
and length-adjustable, from 35.6 cm (14 in.)		
o 48.3 cm (19 in.)	N/C	97.00
70° footrests, "V"-shaped, detachable, swingaway		
and length-adjustable, from 35.6 cm (14 in.)	N/G	0= 00
o 48.3 cm (19 in.)	N/C	97.00
elevating legrests, compensating mechanism,		
letachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
pair	234.00	
ach	23 1.00	214.00
elevating legrests, detachable, swingaway and		2100
ength-adjustable, from 35.6 cm (14 in.)		
o 48.3 cm (19 in.)		
ı pair	150.00	
each		172.00
contoured calfrests	-1.00	
n pair	54.00	47.00
each	N/C	47.00 20.00
padded calfrests modification of footrest or legrest length to	N/C	20.00
ander 35.6 cm (14 in.) or to over 48.3 cm (19 in.)	72.00	N/A
olding footplates, oversized	72.00	14/11
pair	38.00	
ach		35.00
olding footplates, tubular	N/C	16.00
olding footplates, oversized, angle-adjustable,		
on-skid		
pair	74.00	<b>**</b>
each		53.00
olding footplates, angle-adjustable, non-skid	64.00	
pair ach	04.00	48.00
ull-width footplate, angle-adjustable	138.00	48.00 170.00
louble calf strap	50.00	50.00
neel loops, length-adjustable	N/C	10.00
oe loops	1,, 0	10.00
pair	30.00	
ach		15.00
ront impact guard with rollers		
pair	32.00	
ach		16.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Frame		
folding mechanism with double cross-bars	204.00	N/A
angle-adjustable back	98.00	N/A
ack spreader bar	65.00	65.00
Types of drive systems:		
on-slip handrims		
pair	60.00	
ach		74.00
lastic-coated handrims		
pair	52.00	
ach		70.00
nodized aluminum handrims	N/C	44.00
ombined handrims		
pair	60.00	
each		74.00
ront anti-tip rollers		
pair	84.00	
ach		42.00
ane holder	36.00	36.00
Wheel locks:		
standard wheel locks, push-to-lock	N/C	50.00
etractable wheel lock extensions		
pair	33.00	
each		16.00
ixed wheel lock extensions		
pair	40.00	
ach		20.00
nti-rollback brakes		
pair	80.00	
ach		40.00
Types of forks:		
tandard forks	N/C	36.00
nigh forks	N/C	55.00
Fork stems, $+ 1.6 \text{ cm} (\frac{5}{8} \text{ in.}) \text{ or } - 3.2 \text{ cm}$	00.00	<b>3</b> = 1 .
1 <sup>1</sup> / <sub>4</sub> in.)	89.00	N/A
Rear axles:		
hreaded axles	N/C	5.00
uick-release axles		
pair	68.00	
ach		39.00
xle extension plates for amputee		
pair	63.00	
ach		39.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
spoked rear wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.) rear mag wheels, solid tires, 55.9 cm (22 in.)	N/C	70.00
or 61.0 cm (24 in.) a pair each	98.00	119.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)		
a pair each rear mag wheels, standard pressure,	68.00	104.00
50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 (24 in.)	98.00	
a pair each spoked rear wheels, heavy-duty, solid tires,	98.00	119.00
55.9 cm (22 in.) or 61.0 cm (24 in.) a pair each	154.00	147.00
spoked rear wheels, heavy-duty, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)		
a pair each	154.00	147.00
rear wheels, heavy-duty, high pressure, 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)		
a pair each rear mag wheels, semi-pneumatic tires,	154.00	147.00
50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	120.00	
a pair each spoked rear wheels, semi-pneumatic tires,	128.00	134.00
50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) a pair	30.00	
each spoked rear wheels, heavy-duty, semi-pneumatic tires, 55.9 cm (22 in.)	23.33	85.00
or 61.0 cm (24 in.) a pair each	184.00	162.00
Front wheels, solid tires, 17.8 cm (7 in.) or 20.3 cm (8 in.) X 2.5 cm (1 in.),	22.0	
12.7 cm (5 in.), 15.2 cm (6 in.)	N/C	29.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.), 20.3 cm (8 in.) X 5.1 cm (2 in.) or 15.2 cm (6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)		
a pair each	30.00	44.00
front wheels, inner tube, 17.8 cm (7 in.) X 4.4 cm ( $1^{3}/_{4}$ in.) a pair each	30.00	44.00
airless inserts for front wheels a pair each	73.00	N/A
airless inserts for rear wheels a pair each	79.00	N/A
Component(s) under Special Consideration spoke guards * a pair each	114.00	57.00

### **DEVICE FROM: ORTHOFAB INC.**

**PRICE** 

## WHEEL CHAIR, "CONCERTO" MODEL

\$869.00

## Basic Component(s)

# **Body support system**

- supple back, nylon
- back, height-adjustable, from 38.1 cm (15 in.) to 45.7 cm (18 in.), and angle-adjustable
- seat width: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.)
- rigid seat, flat
- seating height: from 41.9 cm  $(16^{1}/_{2} \text{ in.})$  to 50.8 cm (20 in.)
- safety belt, auto-type
- push handles

- "U"-type armrests, flip-back, height-adjustable, from 22.9 cm (9 in.) to 30.5 cm (12 in.), with transfer assists and built-in rigid clothing guards, short
- straight armrest pads, short, long

- 70° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- folding footplates
- heel loops, length-adjustable
- · padded calfrests

- anodized aluminum handrims
- standard wheel locks, push-to-lock
- high forks
- threaded axles
- spoked rear wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
upple back, tension-adjustable	64.00	124.00
igid seat, flat	N/C	163.00
nodification of seat depth to 43.2 cm (17 in.)		
or 45.7 cm (18 in.)	101.00	N/A
nodification of back height, from 48.3 cm (19 in.)		
o 55.9 cm (22 in.)	97.00	N/A
nodification of seating height		
decrease of 3.8 cm $(1^{1/2} in.)$	36.00	N/A
upple back, nylon	N/C	60.00
ack spreader bar	65.00	65.00
ush handles	N/C	50.00
eat cushion, flat, foam, 5.1 cm (2 in.)	52.00	52.00
eat cushion, flat, foam, 7.6 cm (3 in.)	52.00	52.00
afety belt, velcro-type	27.00	62.00
afety belt, auto-type	N/C	35.00
afety belt, airplane-type	38.00	73.00
armrests:		
U"-type armrests, flip-back, height-adjustable,		
rom 22.9 cm (9 in.) to 30.5 cm (12 in.), with transfer		
ssists and built-in rigid clothing guards, short	N/C	135.00
U"-type armrests, flip-back, height-adjustable,		
rom 22.9 cm (9 in.) to 30.5 cm (12 in.), with transfer		
ssists and built-in rigid clothing guards, long		
pair	51.00	
ach		160.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
modification of armrest height to under		
20.3 cm (8 in.) or to over 30.5 cm (12 in.)	72.00	N/A
straight armrest pads, long	N/C	14.00
straight armrest pads, short	N/C	11.00
Footrests:		
70° footrests, detachable, swingaway,		
length-adjustable, from 35.6 cm (14 in.)		
to 48.3 cm (19 in.)	N/C	97.00
60° elevating legrests, detachable, swingaway,		
length-adjustable, from 35.6 cm (14 in.)		
to 48.3 cm (19 in.) a pair	150.00	
each	130.00	172.00
elevating legrests, compensating mechanism,		172.00
detachable, swingaway and length-adjustable,		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
a pair	234.00	
each		214.00
modification of footrest or legrest length to		
under 35.6 cm (14 in.) or to over 48.3 cm (19 in.)	72.00	N/A
padded calfrests	N/C	20.00
contoured calfrests		
a pair	54.00	47.00
each	50.00	47.00
double calf strap	50.00 N/C	50.00
folding footplates full-width footplate, folding and angle-adjustable	N/C	16.00
a pair	138.00	
each	138.00	170.00
folding footplates, oversized and angle-adjustable,		170.00
anti-skid		
a pair	74.00	
each		53.00
folding footplates, angle-adjustable and anti-skid		
a pair	64.00	
each		48.00
heel loops, length-adjustable	N/C	10.00
toe loops	20.00	
a pair	30.00	1,5,00
each	22.00	15.00
front impact guard with rollers	32.00	16.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems:		
plastic-coated handrims	<b>~~</b> 00	
a pair	52.00	70.00
each		70.00
combined handrims	60.00	
a pair each	60.00	74.00
anodized aluminum handrims	N/C	44.00
non-slip handrims	60.00	74.00
front anti-tip rollers	00.00	7 1.00
a pair	84.00	
each		42.00
cane holder	36.00	36.00
Wheel locks:		
standard wheel locks, push-to-lock	N/C	50.00
fixed wheel lock extensions	40.00	
a pair each	40.00	20.00
each retractable wheel lock extensions		20.00
a pair	33.00	
each	33.00	16.00
anti-rollback brakes		10.00
a pair	80.00	
each		40.00
There are a find from the contract of the cont		
Types of forks:	N/C	55.00
high forks	N/C	33.00
Rear axles:		
threaded axles	N/C	5.00
quick-release axles		
â pair	68.00	
each		39.00
Types of wheels:		
spoked rear wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	70.00
rear mag wheels, solid tires, 55.9 cm (22 in.)	98.00	119.00
rear mag wheels, solid tires, 61.0 cm (24 in.)	98.00	119.00
spoked rear wheels, standard pressure,	70.00	117.00
50.8 cm (20 in.) or 55.9 cm (22 in.)		
a pair	68.00	
each		104.00
spoked rear wheels, standard pressure, 61.0 cm (24 in.)		
a pair	68.00	
each		104.00

**PRICE** 

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
rear mag wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	0.0.00	
a pair	98.00	110.00
each (20 i		119.00
rear mag wheels, semi-pneumatic tires, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.) a pair	128.00	
each	128.00	134.00
spoked rear wheels, semi-pneumatic tires, 50.8 cm (20 in.),		134.00
55.9 cm (22 in.) or 61.0 cm (24 in.)		
a pair	30.00	
each		85.00
front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.)	N/C	29.00
front wheels, solid tires, 12.7 cm (5 in.) or 15.2 cm (6 in.)	N/C	29.00
front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.)		
a pair	30.00	
each		44.00
front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.)	20.00	
a pair	30.00	44.00
each airless inserts for front wheels		44.00
a pair	73.00	
each	75.00	N/A
airless inserts for rear wheels		14/71
a pair	79.00	
each		N/A
Component(s) under Special Consideration		
spoke guards *		
a pair	114.00	
each		57.00
		27.00

## DEVICE FROM: SUNRISE MEDICAL CANADA INC.

WHEEL CHAIR, "BREEZY 600" MODEL \$790.00

# **Basic Component(s)**

# **Body support system**

- supple back, nylon
- back height: from 40.6 cm (16 in.) to 48.3 cm (19 in.)
- supple seat, nylon, padded nylon
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.)
- front seating height: from 40.6 cm (16 in.) to 50.8 cm (20 in.)
- safety belt, velcro-type, auto-type
- push handles

### **Armrests**

- "L"-type armrests, swingaway, detachable, height-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- · straight armrest pads, short, long
- · tubular armrests
- clothing guards, flexible

### **Footrests**

- 60°, 70° footrests, detachable, swingaway and length-adjustable, from 33.0 cm (13 in.) to 45.7 cm (18 in.)
- folding footplates
- heel loops, length-adjustable

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- · standard wheel locks, push-to-lock, pull-to-lock
- standard forks, short forks
- · threaded axles
- axle extension plates for amputee
- rear mag wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
<b>Body support system Seat and back:</b> modification of seating height, from 33.0 cm (13 in.) to 39.4 cm $(15^{1/2} \text{ in.})$ or from 40.6 cm (16 in.)		
to 45.7 cm (18 in.) on hemi frame modification of seat width to 48.3 cm (19 in.)	60.00	N/A
or 50.8 cm (20 in.)	70.00	N/A
modification of seat depth to 45.7 cm (18 in.)	74.50	N/A
supple back, tension-adjustable	70.00	129.00
supple back, nylon	N/C	59.00
supple seat, nylon	N/C	50.50
supple seat, padded nylon	N/C	47.25
seat cushion, flat, foam, 5.1 cm (2 in.)	53.00	53.00
seat cushion, flat, foam, 7.6 cm (3 in.)	53.00	53.00
seat cushion, flat, foam, 10.2 cm (4 in.)	53.00	53.00
push handles	N/C	34.00
safety belt, velcro-type	N/C	26.25
safety belt, auto-type	N/C	39.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
"L"-type armrests, swingaway, detachable,		
height-adjustable, from 20.3 cm (8 in.)		
to 30.5 cm (12 in.), short	N/C	81.00
"U"-type armrests, flip-back, detachable,		
height-adjustable, from 22.9 cm (9 in.)		
to 33.0 cm (13 in.), short or long	02.00	
a pair	92.00	127.00
each	N/C	127.00
ubular armrests	N/C N/C	1.60 14.00
straight armrest pads, short straight armrest pads, long	N/C N/C	15.75
clothing guards, flexible	N/C N/C	20.00
clothing guards, rigid, built into armrests	86.00	63.00
biotimig guards, rigid, built into armiests	00.00	05.00
Footrests:		
60° armrests, detachable, swingaway and		
length-adjustable, from 33.0 cm (13 in.)		
to 45.7 cm (18 in.)	N/C	49.00
70° armrests, detachable, swingaway and		
ength-adjustable, from 33.0 cm (13 in.)	N/C	71.00
to 45.7 cm (18 in.)	N/C	71.00
elevating legrests, detachable, swingaway,		
length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.), with padded calfrests		
a pair	91.00	
each	71.00	94.50
elevating legrests, compensating mechanism,		74.50
letachable, swingaway, length-adjustable		
i pair	175.00	
each		136.50
single calf strap	17.00	17.00
louble calf strap	30.50	47.50
Folding footplates	N/C	46.00
folding footplates, angle-adjustable		
ı pair	49.00	
each		70.50
folding footplates, oversized	60.00	
a pair	68.00	00.00
each	NI/C	80.00
neel loops, length-adjustable nodification of footrest length, from 45.7 cm (18 in.)	N/C	9.50
o 52.1 cm ( $20^{1}/_{2}$ in.)	20.00	10.00
0 52.1 Cm (20 / <sub>2</sub> m.)	20.00	10.00
Wheels and frame		
Types of drive systems:		
one-arm dual handrim drive	376.00	492.00
anodized aluminum handrims, 50.8 cm (20 in.),	N/C	<b>77.00</b>
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	55.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
plastic-coated handrims for one-arm drive plastic-coated handrims	51.00	N/A
a pair each	51.00	80.50
nandrims with vertical or oblique projections a pair each	38.00	74.00
ront anti-tip rollers a pair each	41.00	20.50
cane holder	42.00	42.00
Wheel locks: standard wheel locks, push-to-lock or pull-to-lock wheel lock extensions	N/C	37.00
n pair each anti-rollback brakes	25.00	12.50
pair ach	63.00	31.50
Types of forks: tandard forks	N/C	29.50
hort forks	N/C	35.00
Rear axles: hreaded axles puick-release axles	N/C	17.00
pair each	61.00	47.50
axle extension plates for amputee	N/C	29.50
Eypes of wheels: ear mag wheels, solid tires, 55.9 cm (22 in.)	NG	105.00
or 61.0 cm (24 in.) ear mag wheels, solid tires, 50.8 cm (20 in.) pair	N/C 36.00	105.00
ach ear mag wheels, standard pressure,	30.00	123.00
5.9 cm (22 in.) or 61.0 cm (24 in.) pair ach	42.00	126.00
ear mag wheels, standard pressure, 50.8 cm (20 in.)	78.00	
ach ront wheels, solid tires, 12.7 cm (5 in.)	N/C	144.00 43.50
Front wheels, solid tires, 20.3 cm 8 in.) X 2.5 cm (1 in.)	N/C	58.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, solid tires, 15.2 cm (6 in.) front wheels, semi-pneumatic tires, 12.7 cm (5 in.) X 3.8 cm ( $1^{1/2}$ in.) or 15.2 cm (6 in.) X 3.8 cm ( $1^{1/2}$ in.)	N/C	57.00
a pair each front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	76.50	81.75
a pair each airless inserts for 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) rear wheels	29.00	58.00
a pair each  Component(s) under Special Consideration	91.00	N/A
spoke guards * a pair each	64.00	32.00

# DEVICE FROM: SUNRISE MEDICAL CANADA INC.

**PRICE** 

# WHEEL CHAIR, "QUICKIE LXI" MODEL

\$1 050.00

## Basic Component(s)

### **Body support system**

- supple back, nylon
- back height: from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- front seating height: from 40.0 cm (15<sup>3</sup>/<sub>4</sub> in.) to 54.6 cm (21<sup>1</sup>/<sub>2</sub> in.)
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.)
- supple seat, nylon
- safety belt, velcro-type, auto-type
- push handles
- backposts, at an 8° angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.)

- "L"-type armrests, detachable, swingaway, height-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- straight armrest pads, short, long
- · tubular armrests
- clothing guards, flexible

- 60°, 70° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 90° footrests, detachable, swingaway, length-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- folding footplates
- folding footplates, tubular
- heel loops, length-adjustable

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- · standard wheel locks, push-to-lock, pull-to-lock
- standard forks, 15 cm (6 in.); short forks,
   13.3 cm (5<sup>1</sup>/<sub>4</sub> in.); high forks, 17.8 cm (7 in.);
   compatible with 12.7 cm (5 in.), 15.2 cm (6 in.)
   and 20.3 cm (8 in.) wheels; high forks
   for 20.3 cm (8 in.) X 5.1 cm (2 in.) wheels
- fork stems,  $+ 1.9 \text{ cm} (\frac{3}{4} \text{ in.}), + 3.8 \text{ cm} (\frac{1}{2} \text{ in.})$
- · threaded axles
- front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)
- rear mag wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
modification of seat depth to 35.6 cm (14 in.)	20.00	37/4
or 38.1 cm (15 in.)	38.00	N/A
modification of seat width to 48.3 cm (19 in.)	00.00	NT/A
or 50.8 cm (20 in.)	90.00	N/A
modification of seat depth to 43.2 cm (17 in.) or 45.7 cm (18 in.)	64.00	N/A
supple back, nylon	N/C	59.00
supple back, hylon supple back, tension-adjustable	70.00	129.00
supple seat, nylon	N/C	50.50
seat cushion, flat, foam, 5.1 cm (2 in.)	53.00	53.00
seat cushion, flat, foam, 7.6 cm (3 in.)	53.00	53.00
seat cushion, flat, foam, 10.2 cm (4 in.)	53.00	53.00
push handles	N/C	21.00
backposts, at an 8° angle from 35.6 cm (14 in.)		
to 48.3 cm (19 in.)	N/C	26.00
safety belt, velcro-type	N/C	26.25
safety belt, auto-type	N/C	39.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
L"-type armrests, detachable, swingaway,		
eight-adjustable, from 20.3 cm (8 in.)		
o 30.5 cm (12 in.), short	N/C	81.00
U"-type armrests, detachable, flip-back,		
eight-adjustable, from 22.9 cm (9 in.)		
o 33.0 cm (13 in.), short or long		
pair	97.00	
ach		129.50
T"-type armrests, detachable,		
eight-adjustable, from 22.9 cm (9 in.)		
o 35.6 cm (14 in.), short or long		
pair	132.00	
ach		147.00
ubular armrests	N/C	1.60
traight armrest pads, short	N/C	14.00
traight armrest pads, long	N/C	15.75
lothing guards, rigid		
pair	86.00	
ach		63.00
lothing guards, flexible	N/C	20.00
Cootrests:		
0° or 70° footrests, detachable, swingaway,		
ength-adjustable, from 35.6 cm (14 in.)		
o 48.3 cm (19 in.)	N/C	50.00
0° footrests, "V"-shaped, detachable,		
wingaway and length-adjustable,		
rom 35.6 cm (14 in.) to 48.3 cm (19 in.)		
pair	27.00	
ach		63.50
0° footrests, detachable, swingaway and		
ength-adjustable, from 20.3 cm (8 in.)		
o 33.0 cm (13 in.)	N/C	50.00
levating legrests	100.00	100.00
levating legrests, compensating mechanism		
pair	185.00	
ach	1-00	142.50
ingle calf strap	17.00	17.00
ouble calf strap	30.50	47.50
olding footplates	N/C	46.00
olding footplates, angle-adjustable		
nd depth-adjustable		
pair	49.00	
ach		70.50
olding footplates, tubular	N/C	46.00
olding footplates, full-width, angle-adjustable olding footplates, oversized	79.00	171.00
pair	68.00	
pan		

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
heel loops, length-adjustable modification of footrest length, from	N/C	9.50
48.3 cm (19 in.) to 52.1 cm (20 <sup>1</sup> / <sub>2</sub> in.) modification of footrest mounting, from	29.00	28.00
17.8 cm (7 in.) to 34.3 cm (13½ in.)	51.50 51.50	31.50
each Front floor rollers		31.50
n pair each	52.50	26.25
modification of length of $90^{\circ}$ footrest by $+5.1$ cm (2 in.) or by $+10.2$ cm (4 in.)	29.00	14.50
Wheels and frame Types of drive systems:		
one-arm dual handrim drive anodized aluminum handrims, 50.8 cm (20 in.),	446.00	533.00
55.9 cm (22 in.) or 61.0 cm (24 in.) plastic-coated handrims	N/C	55.00
a pair each nandrims with 61.0 cm (24 in.) vertical or	51.00	80.50
blique projections pair ach	38.00	74.00
plastic-coated handrims, one-arm drive front anti-tip rollers	51.00	N/A
a pair	41.00	20.50
rane holder ront floor rollers	42.00	42.00
n pair each	52.50	26.25
Wheel locks: tandard wheel locks, push-to-lock or pull-to-lock	N/C	37.00
vheel lock extensions pair ach	25.00	12.50
nti-rollback brakes pair ach	63.00	31.50

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of forks:		
standard forks, 15 cm (6 in.); short forks,		
13.3 cm (5 <sup>1</sup> / <sub>4</sub> in.); or high forks 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.)		
and 20.3 cm (8 in.) wheels	N/C	29.50
standard forks for 20.3 cm (8 in.) X 5.1 cm (2 in.)		
wheels fork-locking mechanisms	N/C	32.00
a pair	42.00	
each	.2.00	21.00
fork stems, $+ 1.9 \text{ cm} (\sqrt[3]{4} \text{ in.}) \text{ or } + 3.8 \text{ cm} (1\sqrt[1]{2} \text{ in.})$	N/C	15.00
Rear axles:		
threaded axles	N/C	10.50
quick-release axles a pair	41.00	
each	11.00	31.00
axle extension plates for amputee	64.00	N/A
Types of wheels:		
rear mag wheels, solid tires, 50.8 cm (20 in.)	42.00	
a pair each	42.00	126.00
rear mag wheels, solid tires, 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	126.00
rear mag wheels, standard pressure, 50.8 cm (20 in.) a pair	42.00	
each	42.00	126.00
rear mag wheels, standard pressure, 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	105.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)		
a pair	42.00	
each		126.00
spoked rear wheels, high pressure, 61.0 cm (24 in.) a pair	42.00	
each	42.00	126.00
spoked rear wheels, solid tires, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	74.00	
a pair each	74.00	142.00
front wheels, solid tires, 15.2 cm (6 in.)	N/C	57.00
front wheels, solid tires, 12.7 cm (5 in.)	N/C	43.50
front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.)	N/C	58.00
front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm ( $1\frac{1}{4}$ in.) front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm ( $1\frac{1}{4}$ in.)	N/C N/C	58.00 57.50
front wheels, inner tube, 13.2 cm (8 in.) X 5.2 cm (1 /4 ii.)	1 <b>V</b> /C	57.30
a pair	45.00	
each		66.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, semi-pneumatic tires,		
12.7 cm (5 in.) X 3.8 cm ( $1\frac{1}{2}$ in.) or 15.2 cm		
(6 in.) X 3.8 cm (1 <sup>1</sup> / <sub>2</sub> in.)	76.50	
a pair each	70.30	81.75
rich virless inserts for 20.3 cm (8 in.) X 5.1 cm (2 in.)		61.73
a pair	106.00	
each		N/A
nirless inserts for 50.8 cm (20 in.) mag wheels		
a pair	89.00	<b>N</b> T / A
each airless inserts for 55.9 cm (22 in.) or 61.0 cm (24 in.)		N/A
nag wheels		
nag wheels	50.00	
each		N/A
nirless inserts for 50.8 cm (20 in.), 55.9 cm (22 in.),		
61.0 cm (24 in.) spoked rear wheels	00.00	
a pair	90.00	NT/A
each		N/A
Component(s) under Special Consideration		
spoke guards *		
pair	64.00	
each		32.00
uick-release axles with lever mechanism *	61.00	
apair ach	01.00	61.50
acii		01.50
DEVICE FROM: SUNRISE MEDICAL CANADA INC.		
		PRI

## WHEEL CHAIR, ADULT, "QUICKIE 2" MODEL

\$1 315.00

# Basic Component(s) **Body support system**

- supple back, nylon
- back height: from 21.6 cm (8<sup>1</sup>/<sub>2</sub> in.) to 47.0 cm  $(18^{1}/_{2} in.)$
- supple seat, nylon
- seat width: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- seat depth: 40.6 cm (16 in.)
- front seating height: from 38.7 cm (15½ in.) to 54.6 cm  $(21^{1}/_{2} in.)$
- first increase in size of wheel chair includes: seat, back, footrests, front frame and cross-bars (once only during first 3 years, for first user)
- safety belt, velcro-type, auto-type
- push handles

#### Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- straight armrest pads, short, long, tubular armrests
- clothing guards, flexible

#### **Footrests**

- 60°, 70° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70° footrests, "V"-shaped, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- · folding footplates
- folding footplates, tubular
- heel loops, length-adjustable

- anodized aluminum handrims, 50.8 cm (20 in.),
   55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- · standard wheel locks, push-to-lock, pull-to-lock
- standard forks, 15 cm (6 in.); short forks,
   13.3 cm (5<sup>1</sup>/<sub>4</sub> in.); high forks, 17.8 cm (7 in.);
   compatible with 12.7 cm (5 in.), 15.2 cm (6 in.)
   and 20.3 cm (8 in.) wheels
- high forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) X 5.1 cm (2 in.) wheels
- fork stems,  $+1.9 \text{ cm} (\frac{3}{4} \text{ in.})$ ,  $+3.8 \text{ cm} (\frac{1}{2} \text{ in.})$
- quick-release axles
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure,
  50.8 cm (20 in.), 55.9 cm (22 in.),
  61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear mag wheels, standard pressure,
   50.8 cm (20 in.),
   55.9 cm (22 in.),
   61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.),
   55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
folding back, angle-adjustable and		
depth-adjustable	99.00	N/A
supple back, tension-adjustable	70.00	129.00
backposts, at an 8° angle at 20.3 cm (8 in.),		
with handles		
ı pair	13.00	
each		25.00
supple back, nylon	N/C	59.00
pack spreader bar	120.00	N/A
packposts, angle-adjustable from		
-3° to +15°, 3 positions	112.50	N/A
supple seat, nylon	N/C	50.50
nodification of seat depth to 35.6 cm (14 in.),		
38.1 cm (15 in.), 43.2 cm (17 in.) or 45.7 cm (18 in.)	37.50	N/A
modification of back height, from 48.3 cm (19 in.)		
o 55.9 cm (22 in.)	95.00	N/A
first increase in size of wheel chair includes:		
seat, back, footrests, front frame and cross-bars		
(once only, during first 3 years, for first user)	N/C	N/A
oush handles	N/C	18.50
seat cushion, flat, foam, 5.1 cm (2 in.)	53.00	53.00
seat cushion, flat, foam, 7.6 cm (3 in.)	53.00	53.00
seat cushion, flat, foam, 10.2 cm (4 in.)	53.00	53.00
safety belt, velcro-type	N/C	26.25
safety belt, auto-type	N/C	39.00
Armrests:		
'L''-type armrests, detachable, swingaway,		
height-adjustable, from 20.3 cm (8 in.)		
to 30.5 cm (12 in.), short	N/C	89.00
'T"-type armrests, detachable,	14/6	07.00
height-adjustable, from 22.9 cm (9 in.)		
to 35.6 cm (14 in.), short or long		
a pair	73.50	
each	73.30	125.75
'U"-type armrests, detachable, flip-back,		123.73
neight-adjustable, from 22.9 cm (9 in.)		
o 33.0 cm (13 in.), short or long		
a pair	66.00	
a pan each	00.00	122.00
eacn 'I"-type armrests, flip-back, height-adjustable,		122.00
1 -type armrests, imp-back, neight-adjustable,		
from $22.2 \text{ cm} (8^{3/4} \text{ in.})$ to $34.9 \text{ cm} (13^{3/4} \text{ in.})$ ,		
vailable with depth-adjustable seat only	277.00	
ı pair	277.00	
each		227.50

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
tubular armrests	N/C	1.60
straight armrest pads, long	N/C	15.75
straight armrest pads, short	N/C	14.00
clothing guards, flexible	N/C	20.00
clothing guards, rigid		
a pair	86.00	
each		63.00
Footrests:		
60° or 70° footrests, detachable, swingaway		
and length-adjustable, from 35.6 cm (14 in.)		
to 48.3 cm (19 in.)	N/C	50.00
70° footrests, "V"-shaped, detachable,		
swingaway and length-adjustable,	37/6	<b>=</b> 0.00
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	50.00
70° or 80° footrests, fixed, heavy-duty	60.00	
a pair	60.00	90.00
each		80.00
elevating legrests, compensating mechanism, detachable, swingaway and length-adjustable		
	185.00	
a pair each	183.00	142.50
elevating legrests, detachable, swingaway and		142.50
length-adjustable, from 35.6 cm (14 in.)		
to 48.3 cm (19 in.), with padded calfrests		
a pair	100.00	
each		100.00
single calf strap	17.00	17.00
double calf strap	30.50	47.50
folding footplates	N/C	46.00
folding footplates, angle-adjustable		
a pair	49.00	
each		70.50
folding footplates, tubular	N/C	46.00
folding footplates, oversized		
a pair	68.00	22.22
each	<b>5</b> 0.00	80.00
full-width footplate, folding, angle-adjustable	79.00	171.00
front floor rollers	52.50	
a pair	52.50	26.25
each	NI/C	26.25
heel loops, length-adjustable	N/C	9.50
modification of footrest length, from	20.00	20.00
48.3 cm (19 in.) to 52.1 cm ( $20^{1}/_{2}$ in.)	29.00	28.00
raised footplate mountings, from 17.8 cm (7 in.)		
to $34.3 \text{ cm} (13^{1}/_{2} \text{ in.})$ in length	51.50	
a pair	31.30	31.50
each		31.30

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Frame optional heavy-duty frame, 45.7 cm (18 in.)		
o 55.9 cm (22 in.) wide extra-long frame for depths of 48.3 cm (19 in.)	324.00	N/A
and 50.8 cm (20 in.)	48.00	N/A
Types of drive systems:		
one-arm dual handrim drive	520.00	655.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	55.00
nandrims with vertical or oblique projections	38.00	
each	20.00	74.00
plastic-coated handrims a pair	51.00	
each	31.00	80.50
non-slip handrims	04.00	
a pair each	84.00	97.00
plastic-coated handrims for one-arm drive	51.00	N/A
front anti-tip rollers a pair	41.00	
each	41.00	20.50
cane holder	42.00	42.00
Wheel locks:	NG	27.00
standard wheel locks, push-to-lock or pull-to-lock wheel lock extensions, 15.2 cm (6 in.)	N/C	37.00
a pair	25.00	
each anti-rollback brakes		12.50
a pair	63.00	
each		31.50
Types of forks:		
standard forks, 15 cm (6 in.); short forks, 13.3 cm (5 <sup>1</sup> / <sub>4</sub> in.); or high forks, 17.8 cm (7 in.);		
compatible with 12.7 cm (5 in.), 15.2 cm (6 in.)		
and 20.3 cm (8 in.) wheels	N/C	29.50
nigh forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) X 5.1 cm (2 in.) wheels	N/C	34.00
fork-locking mechanisms	11/0	54.00
a pair	42.00	21.00
each fork stems, + 1.9 cm ( $\frac{3}{4}$ in.) or + 3.8 cm ( $\frac{1}{2}$ in.)	N/C	21.00 15.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Rear axles:		
quick-release axles	N/C	31.00
axle extension plates for amputee a pair	40.00	
each	40.00	67.25
curved multi-position plates		07.23
a pair	26.50	
each		60.50
Types of wheels:		
spoked rear wheels, solid tires, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	142.00
spoked rear wheels, standard pressure,		
50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)	N/C	126.00
or 66.0 cm (26 in.) spoked rear wheels, high pressure, 61.0 cm (24 in.)	N/C	120.00
or 66.0 cm (26 in.)	N/C	126.00
spoked rear wheels, heavy-duty, standard pressure	14/6	120.00
or high pressure, 61.0 cm (24 in.)	116.00	
a pair	116.00	184.00
each rear mag wheels, solid tires, 50.8 cm (20 in.),		164.00
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	126.00
rear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C	126.00
rear mag wheels, standard pressure, 55.9 cm (22 in.)	14,0	120.00
or 61.0 cm (24 in.)	N/C	105.00
front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.)	N/C	58.00
front wheels, solid tires, 15.2 cm (6 in.)	N/C	57.00
front wheels, solid tires, 12.7 cm (5 in.)	N/C	43.50
front wheels, inner tube, 20.3 cm (8 in.) X 5.1 cm (2 in.)		
a pair	45.00	44.00
each		66.00
front wheels, inner tube, 20.3 cm	N/C	50.00
(8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) front wheels, inner tube, 15.2 cm	N/C	58.00
(6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	N/C	57.50
front wheels, semi-pneumatic tires, 12.7 cm (5 in.)	14/	57.50
or 15.2 cm (6 in.) X 3.8 cm ( $1^{1}/_{2}$ in.)		
a pair	76.50	
each		81.75
front wheels, semi-pneumatic tires,		
12.7 cm (5 in.) X 5.1 cm (2 in.)		
a pair	62.00	
each		74.50
Front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 3.8 cm ( $1\frac{1}{2}$ in.)		
a pair	95.00	
each		91.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
airless inserts for 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) rear wheels a pair each airless inserts for 20.3 cm (8 in.) X 5.1 cm (2 in.)	51.00	N/A
front wheels a pair each	106.00	N/A
Component(s) under Special Consideration		
spoke guards * a pair each	64.00	32.00
quick-release axles with lever mechanism * a pair each	61.00	61.50
nulti-position fork bar * a pair each	184.00	115.00

## DEVICE FROM: SUNRISE MEDICAL CANADA INC.

**PRICE** 

# WHEEL CHAIR, ADULT, "QUICKIE 2 HP" MODEL

\$1 415.00

## Basic Component(s)

### **Body support system**

- supple back, nylon
- back height: from 21.6 cm (8<sup>1</sup>/<sub>2</sub> in.) to 47.0 cm (18<sup>1</sup>/<sub>2</sub> in.)
- supple seat, nylon
- seat width: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- seat depth: 40.6 cm (16 in.)
- front seating height: from 43.8 cm (17<sup>1</sup>/<sub>4</sub> in.) to 54.6 cm (21<sup>1</sup>/<sub>2</sub> in.)
- safety belt, velcro-type, auto-type
- push handles

- "L"-type armrest, detachable, swingaway, height-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- · straight armrest pads, short, long, tubular armrests
- · clothing guards, flexible

- 60°, 70° footrests, parallel, fixed, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- folding footplates
- folding footplates, tubular
- heel loops, length-adjustable

- anodized aluminum handrims, 50.8 cm (20 in.),
   55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- · standard wheel locks, push-to-lock, pull-to-lock
- standard forks, 15.2 cm (6 in.); short forks,
   13.3 cm (5<sup>1</sup>/<sub>4</sub> in.); high forks, 18.8 cm (7 in.);
   compatible with 12.7 cm (5 in.), 15.2 cm (6 in.)
   and 20.3 cm (8 in.) wheels
- high forks, 18.8 cm (7 in.), compatible with 20.3 cm (8 in.) X 5.1 cm (2 in.) wheels
- fork stems,  $+ 1.9 \text{ cm} (\frac{3}{4} \text{ in.}), + 3.8 \text{ cm} (\frac{11}{2} \text{ in.})$
- quick-release axles
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20 cm (8 in.) X 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
supple back, tension-adjustable	70.00	129.00
backposts, at an 8° angle from 31.8 cm		
$(12^{1/2} \text{ in.})$ to 45.7 cm (18 in.), with handles		
a pair	13.00	
each		25.00
back spreader bar	120.00	N/A
backposts, angle-adjustable from -3° à + 15°, 3 positions	112.50	N/A
supple back, nylon	N/C	59.00
supple seat, nylon	N/C	50.50
modification of seat depth to 35.6 cm (14 in.),		
38.1 cm (15 in.), 43.2 cm (17 in.) or 45.7 cm (18 in.)	45.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
nodification of back height, from 48.3 cm (19 in.)		
o 55.9 cm (22 in.)	95.00	N/A
oush handles	N/C	18.50
eat cushion, flat, foam, 5.1 cm (2 in.)	53.00	53.00
eat cushion, flat, foam, 7.6 cm (3 in.)	53.00	53.00
eat cushion, flat, foam, 10.2 cm (4 in.)	53.00	53.00
afety belt, velcro-type	N/C	26.25
afety belt, auto-type	N/C	39.00
Armrests:		
'L"-type armrests, detachable, swingaway,		
neight-adjustable, from 20.3 cm (8 in.)		
o 30.5 cm (12 in.), short	N/C	89.00
'T"-type armrests, detachable, height-adjustable,		
from 22.9 cm (9 in.) to 35.6 cm (14 in.),		
short or long		
ı pair	73.50	
each		125.75
'U"-type armrests, detachable, flip-back,		
neight-adjustable, from 22.9 cm (9 in.)		
o 33.0 cm (13 in.), short or long		
ı pair	66.00	
each		122.00
ubular armrests	N/C	1.60
traight armrest pads, long	N/C	15.75
traight armrest pads, short	N/C	14.00
clothing guards, flexible	N/C	20.00
clothing guards, rigid		
pair	86.00	
ach		63.00
Footrests:		
50° or 70° footrests, parallel, fixed,		
ength-adjustable, from 35.6 cm (14 in.)		
o 48.3 cm (19 in.)	N/C	41.00
ingle calf strap	17.00	17.00
louble calf strap	30.50	47.50
folding footplates	N/C	46.00
olding footplates, angle-adjustable		
pair	49.00	
ach		70.50
olding footplates, tubular	N/C	46.00
olding footplates, oversized		
pair	68.00	
ach		80.00
ull-width footplate, folding and angle-adjustable	79.00	171.00
ront floor rollers		-, -,00
pair	52.50	
F "	C = . C C	26.25

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
heel loops, length-adjustable	N/C	9.50
modification of footrest length, from 48.3 cm (19 in.) to 52.1 cm ( $20^{1}/_{2}$ in.) raised footplate mounting, from 18.8 cm (7 in.) to 34.3 cm ( $13^{1}/_{2}$ in.) in length	29.00	28.00
a pair each	51.50	31.50
Wheels and frame Frame optional heavy-duty frame, 45.7 cm (18 in.)		
to 55.9 cm (22 in.) wide extra-long frame for depths of 48.3 cm (19 in.)	324.00	N/A
and 50.8 cm (20 in.)	48.00	N/A
Types of drive systems: one-arm dual handrim drive	520.00	650.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) nandrims with vertical or oblique projections	N/C	55.00
a pair each	38.00	74.00
plastic-coated handrims a pair each	51.00	80.50
non-slip handrims a pair each	84.00	97.00
plastic-coated handrims for one-arm drive Front anti-tip rollers	51.00	N/A
a pair	41.00	20.50
cane holder	42.00	42.00
Wheel locks: standard wheel locks, push-to-lock or pull-to-lock swing-away brakes	N/C	37.00
a pair each	23.00	48.50
wheel lock extensions, 15.2 cm (6 in.) a pair each	25.00	12.50
anti-rollback brakes a pair each	63.00	31.50

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of forks:		
standard forks, 15.2 cm (6 in.); short forks,		
13.3 cm (5 <sup>1</sup> / <sub>4</sub> in.); or high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.)		
and 20.3 cm (8 in.) wheels	N/C	29.50
high forks, 17.8 cm (7 in.), compatible with	1,, 5	27.30
20.3 cm (8 in.) X 5.1 cm (2 in.) wheels	N/C	34.00
fork-locking mechanisms		
a pair	42.00	21.00
each	N/C	21.00 15.00
Fork stems, + 1.9 cm ( $^{3}/_{4}$ in.) or + 3.8 cm ( $^{1}/_{2}$ in.)	N/C	13.00
Rear axles:		
quick-release axles	N/C	31.00
quick-release heavy-duty axles		
a pair	94.00	70.00
each		78.00
axle extension plates for amputee	40.00	
each	40.00	67.25
curved multi-position plates		
a pair	26.50	
each		60.50
Types of wheels:		
spoked rear wheels, solid tires, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	142.00
spoked rear wheels, standard pressure,		
50.8 cm (20 in.), 55.9 cm (22 in.),	37/0	4.4.00
51.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	126.00
spoked rear wheels, high pressure, 51.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	126.00
spoked rear wheels, heavy-duty, standard	IN/C	120.00
pressure or high pressure, 61.0 cm (24 in.)		
pair	116.00	
each		184.00
rear mag wheels, solid tires, 50.8 cm (20 in.),	33/6	10 4 6 6
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	126.00
ear mag wheels, standard pressure, 50.8 cm (20 in.) ear mag wheels, standard pressure,	N/C	126.00
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	105.00
Front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.)	N/C	58.00
Front wheels, solid tires, 15.2 cm (6 in.)	N/C	57.00
ront wheels, solid tires, 12.7 cm (5 in.)	N/C	43.50
ront wheels, solid tires, 7.6 cm (3 in.)		
pair	37.00	<b>23</b> 63
each		62.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, inner tube, 20.3 cm (8 in.) X 5.1 cm (2 in.)		
a pair	45.00	
each		66.00
front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm ( $1\frac{1}{4}$ in.)	N/C	58.00
front wheels, inner tube, $15.2 \text{ cm } (6 \text{ in.}) \text{ X } 3.2 \text{ cm } (1\frac{1}{4} \text{ in.})$ airless inserts for 20.3 cm (8 in.) X 5.1 cm (2 in.)	N/C	57.50
front wheels	106.00	
a pair	106.00	NT/A
each front wheels, semi-pneumatic tires, 12.7 cm		N/A
(5 in.) X 3.8 cm ( $1^{1}/_{2}$ in.) or 15.2 cm		
(6 in.) X 3.8 cm ( $1\frac{7}{2}$ in.) of 13.2 cm		
a pair	76.50	
each	, 0.50	81.75
front wheels, semi-pneumatic tires,		01.75
20.3 cm (8 in.) X 3.8 cm ( $1^{1/2}$ in.)		
a pair	95.00	
each		91.00
front wheels, semi-pneumatic tires,		
12.7 cm (5 in.) X 5.1 cm (2 in.)		
a pair	62.00	
each		74.50
airless inserts for 50.8 cm (20 in.), 55.9 cm		
(22 in.) or 61.0 cm (24 in.) rear wheels		
a pair	51.00	
each		N/A
Component(s) under Special Consideration		
cnoko guarda *		
spoke guards *	64.00	
a pair each	04.00	32.00
each quick-release axles with lever mechanism *		32.00
a pair	61.00	
each	01.00	61.50
multi-position fork bar *	184.00	115.00
main-position fork oar	107.00	113.00

### DEVICE FROM: SUNRISE MEDICAL CANADA INC.

**PRICE** 

## WHEEL CHAIR, CHILD, "QUICKIE 2" MODEL

\$1 315.00

## **Basic Component(s)**

## **Body support system**

- supple back, nylon
- back height: from 21.6 cm  $(8^{1}/_{2} \text{ in.})$  to 47.0 cm  $(18^{1}/_{2} \text{ in.})$
- supple seat, nylon
- seat width: from 27.9 cm (11 in.) to 38.1 cm (15 in.)
- seat depth: 30.5 cm (12 in.), 35.6 cm (14 in.)
- front seating height: from 43.8 cm (17<sup>1</sup>/<sub>4</sub> in.) to 54.6 cm (21<sup>1</sup>/<sub>2</sub> in.)
- first increase in size of wheel chair includes: seat, back, footrests, front frame and cross-bars (once only, during first 3 years, for first user)
- safety belt, velcro-type, auto-type
- · push handles

### **Armrests**

- "L"-type armrests, detachable, swingaway, height-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- · straight armrest pads, short, long
- · tubular armrests
- · clothing guards, flexible

- 60°, 70° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 90° footrests, detachable, swingaway, length-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- 70°, 80° footrests, detachable, swingaway, length-adjustable, from 15.2 cm (6 in.) to 30.5 cm (12 in.)
- heel loops, length-adjustable
- folding footplates
- folding footplates, tubular

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- · standard wheel locks, push-to-lock or pull-to-lock
- standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5<sup>1</sup>/<sub>4</sub> in.); high forks, 17.8 cm (7 in.); standard forks, 17.8 cm (7 in.) for 20.3 cm (8 in.) X 5.1 cm (2 in.) wheels
- fork stems,  $+ 1.9 \text{ cm} (\frac{3}{4} \text{ in.}), + 3.8 \text{ cm} (\frac{11}{2} \text{ in.})$
- · quick-release axles
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
folding back, angle-adjustable and		
depth-adjustable	99.00	N/A
back spreader bar	120.00	N/A
supple back, tension-adjustable	70.00	129.00
supple back, nylon	N/C	59.00
supple seat, nylon	N/C	50.50
modification of seat depth to 25.4 cm (10 in.),		
27.9 cm (11 in.) or 33.0 cm (13 in.)	37.50	N/A
modification of seat width to 40.6 cm (16 in.)	100.00	N/A
first increase in size of wheel chair includes:		
seat, back, footrests, front frame and cross-bars		
(once only, during first 3 years, for first user)	N/C	N/A
modification of back height, from 48.3 cm (19 in.)		
to 55.9 cm (22 in.)	95.00	N/A
backposts, angle-adjustable from $-3^{\circ}$ to $+15^{\circ}$ ,		
3 positions	112.00	N/A
backposts, at an 8° angle, from 31.8 cm (12½ in.)		
to $47.0 \text{ cm} (18^{1}/_{2} \text{ in.})$	13.00	25.00
oush handles	N/C	18.50

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
seat cushion, flat, foam, 5.1 cm (2 in.) seat cushion, flat, foam, 7.6 cm (3 in.) seat cushion, flat, foam, 10.2 cm (4 in.) safety belt, velcro-type	53.00 53.00 53.00 N/C	53.00 53.00 53.00 26.25
safety belt, veleto-type	N/C	39.00
Armrests: "L"-type armrests, detachable, swingaway, height-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.), short	N/C	89.00
"T"-type armrests, detachable, height-adjustable, from 19.1 cm ( $7^{1}/_{2}$ in.) to 30.5 cm (12 in.), short or long		07.00
a pair each "U"-type armrests, detachable, flip-back, height-adjustable, from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long	73.50	125.75
a pair each "I"-type armrests, flip-back, height-adjustable, from 22.2 cm (8 <sup>3</sup> / <sub>4</sub> in.) to 34.9 cm (13 <sup>3</sup> / <sub>4</sub> in.), short	66.00	122.00
a pair each	277.00	227.50
tubular armrests	N/C	1.60
straight armrest pads, long	N/C	15.75
straight armrest pads, short	N/C	14.00
clothing guards, flexible clothing guards, rigid	N/C	20.00
a pair each	86.00	63.00
<b>Footrests:</b> 70° or 80° footrests, fixed, heavy-duty		
a pair each 60° or 70° footrests, detachable, swingaway,	60.00	80.00
length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.) 90° footrests, detachable, swingaway,	N/C	50.00
length-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.) 70° or 80° footrests, detachable, swingaway,	N/C	50.00
length-adjustable, from 15.2 cm (6 in.) to 30.5 cm (12 in.) elevating legrests, compensating mechanism	N/C	52.00
a pair each	185.00	142.50

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
90° elevating legrests, detachable, swingaway,		
length-adjustable, from 20.3 cm (8 in.)		
to 33.0 cm (13 in.)		
a pair	66.00	
each		83.00
elevating legrests, detachable, swingaway,		
length-adjustable	400.00	
a pair	100.00	400.00
each		100.00
modification of footrest length, from	-1 -0	24.70
7.8 cm (7 in.) to 34.3 cm $(13^{1}/_{2} \text{ in.})$	51.50	31.50
modification of length of 90° footrest,		
by $+5.1$ cm (2 in.) or by $+10.2$ cm (4 in.)	20.00	
a pair	29.00	14.70
each	17.00	14.50
single calf strap	17.00	17.00
double calf strap	30.50	47.50
folding footplates	N/C	46.00
folding footplates, tubular	N/C	46.00
folding footplates, angle-adjustable	40.00	
a pair	49.00	70.50
each		70.50
folding footplates, oversized	69.00	
a pair each	68.00	80.00
each full-width footplate, angle-adjustable	79.00	171.00
heel loops, length-adjustable	N/C	9.50
front floor rollers	N/C	9.50
a pair	52.50	
each	32.30	26.25
caen		20.23
Wheels and frame		
Types of drive systems:	520.00	655.00
one-arm dual handrim drive	520.00	655.00
anodized aluminum handrims, 50.8 cm	NIC	55.00
(20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	55.00
handrims with oblique or vertical projections	29.00	
a pair	38.00	74.00
each plastic-coated handrims, 50.8 cm (20 in.),		74.00
55.9 cm (22 in.), 61.0 cm (24 in.)	51.00	
a pair each	31.00	80.50
non-slip handrims, 55.9 cm (22 in.), 61.0 cm (24 in.)		60.30
*	84.00	
a pair each	04.00	97.00
plastic-coated handrims for one-arm drive	51.00	
plastic-coated nandrims for one-arm drive front anti-tip rollers	31.00	N/A
	41.00	
a pair each	41.00	20.50
eacn cane holder	42.00	42.00
and notice	42.00	42.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks: standard wheel locks, push-to-lock or pull-to-lock wheel lock extensions, 15.2 cm (6 in.)	N/C	37.00
a pair each	25.00	12.50
nti-rollback brakes pair ach	63.00	31.50
Types of forks: tandard forks, 15.2 cm (6 in.); short forks,		
$3.3 \text{ cm } (5^{1}/_{4} \text{ in.})$ ; or high forks, 17.8 cm (7 in.)	N/C	29.50
tandard forks, 17.8 cm (7 in.), for 20.3 cm 8 in.) X 5.1 cm (2 in.) wheels	N/C	34.00
ork-locking mechanisms pair	42.00	
ach ork stems, $+ 1.9 \text{ cm} (\sqrt[3]{4} \text{ in.}) \text{ or } + 3.8 \text{ cm} (1^{1}/2 \text{ in.})$	N/C	21.00 15.00
Rear axles:		
uick-release axles xle extension plates for amputee	N/C	31.00
pair ach	40.00	67.25
eurved plates a pair	26.50	
each		60.50
Types of wheels: poked rear wheels, solid tires,		
50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) spoked rear wheels, standard pressure,	N/C	142.00
0.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	126.00
poked rear wheels, high pressure, 61.0 cm (24 in.)	N/C	126.00
ear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C	126.00
ear mag wheels, standard pressure, 5.9 cm (22 in.) or 61.0 cm (24 in.) ear mag wheels, solid tires, 50.8 cm (20 in.),	N/C	105.00
(5.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	126.00
Front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.)	N/C	58.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, solid tires, 15 cm (6 in.) front wheels, solid tires, 12.7 cm (5 in.)) front wheels, inner tube, 20.3 cm (8 in.) X 5.1 cm (2 in.)	N/C N/C	57.00 43.50
a pair each	45.00	66.00
Front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm ( $1^{1/4}$ in.) front wheels, inner tube, 15.2 cm	N/C	58.00
(6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) front wheels, semi-pneumatic tires, 12.7 cm (5 in.) X 3.8 cm ( $1^{1}/_{2}$ in.) or 15.2 cm	N/C	57.50
(6 in.) X 3.8 cm (1 <sup>1</sup> / <sub>2</sub> in.) a pair each	76.50	81.75
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) X 5.1 cm (2 in.) a pair	62.00	01.75
each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 3.8 cm (1½ in.)		74.50
n pair each airless inserts for 20.3 cm (8 in.) X 5.1 cm	95.00	91.00
(2 in.) front wheels a pair each airless inserts for 50.8 cm (20 in.), 55.9 cm	106.00	N/A
(22 in.) or 61.0 cm (24 in.) rear wheels a pair each	51.00	N/A
Component(s) under Special Consideration		
spoke guards * a pair each	64.00	32.00
quick-release axles with lever mechanism * a pair each	61.00	61.50

### DEVICE FROM: SUNRISE MEDICAL CANADA INC.

**PRICE** 

## WHEEL CHAIR, CHILD, "ZIPPIE GS" MODEL

\$1 375.00

### **Basic Component(s)**

## **Body support system**

- supple back, nylon
- folding back, angle-adjustable and height-adjustable
- back height: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- · rigid seat, flat, adjustable
- seat width: from 25.4 cm (10 in.) to 40.6 cm (16 in.)
- seat depth: from 25.4 cm (10 in.) to 45.7 cm (18 in.)
- front seating height: from 40.6 cm (16 in.) to 47.0 cm (18<sup>1</sup>/<sub>2</sub> in.)
- first increase in size of wheel chair includes: rigid or folding cross-bars (once only, during first 3 years, for first user)
- safety belt, velcro-type, auto-type
- push handles
- backposts with push handles at 55.2 cm (21<sup>3</sup>/<sub>4</sub> in.),
   62.9 cm (24<sup>3</sup>/<sub>4</sub> in.) or 70.5 cm (27<sup>3</sup>/<sub>4</sub> in.)

#### Armrests

- "T"-type armrests, detachable, height-adjustable, from 19.1 cm (7<sup>1</sup>/<sub>2</sub> in.) to 30.5 cm (12 in.), short, long
- · straight armrest pads, short, long
- · tubular armrests

- 60°, 70° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 90° footrests, detachable, swingaway, length-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- 70°, 80° footrests, detachable, swingaway, length-adjustable, from 15.2 cm (6 in.) to 30.5 cm (12 in.)
- 70°, 80°, 90° footrests, heavy-duty, detachable, non flip-back
- heel loops, length-adjustable
- · folding footplates

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock or pull-to-lock
- standard forks, 15.2 cm (6 in.); short forks,
   13.3 cm (5<sup>1</sup>/<sub>4</sub> in.); high forks 17.8 cm (7 in.);
   compatible with 12.7 cm (5 in.), 15.2 cm (6 in.)
   and 20.3 cm (8 in.) wheels
- fork stems,  $+ 1.9 \text{ cm} (\frac{3}{4} \text{ in.}) + 3.8 \text{ cm} (\frac{11}{2} \text{ in.})$
- quick-release axles
- spoked rear wheels, solid tires, 50.8 cm (20 in.),
   55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.),
   55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
headrest, small	86.00	89.00
headrest, medium	91.00	98.00
headrest, large	97.00	102.00
transversal bar for headrest mounting (folding)	215.00	230.00
articulated headrest mounting	147.00	160.00
ransversal bar for headrest mounting (rigid)	185.00	196.00
folding back, angle-adjustable and height-adjustable	N/C	N/A
supple back, tension-adjustable	70.00	129.00
supple back, nylon	N/C	59.00
rigid seat, flat, adjustable	N/C	120.00
first increase in size of wheel chair includes:		
rigid and folding cross-bars (once only, during		
first 3 years, for first user)	N/C	N/A
push handles	N/C	N/A
push handles, adjustable by 15.2 cm (6 in.),		
swingaway	75.00	N/A
backposts, with push handles at 55.2 cm (21 <sup>3</sup> / <sub>4</sub> in.),		
$62.9 \text{ cm } (24^{3}/_{4} \text{ in.}) \text{ or } 70.5 \text{ cm } (27^{3}/_{4} \text{ in.})$	N/C	N/A
back spreader bar	120.00	N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	53.00	53.00
seat cushion, flat, foam, 7.6 cm (3 in.)	53.00	53.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
safety belt, velcro-type	N/C	26.25
safety belt, auto-type	N/C	39.00
safety belt, airplane-type	47.00	73.25
safety belt, airplane-type, padded	70.00	96.25
Armrests:		
"T"-type armrests, detachable, height-adjustable, from 19.1 cm ( $7\frac{1}{2}$ in.) to 30.5 cm (12 in.),		
short or long	N/C	125.75
"I"-type armrests, flip-back, height-adjustable,	N/C	123.73
from 16.5 cm ( $6^{1}/_{2}$ in.) to 33.0 cm (13 in.), short, long		
a pair	120.00	
each	120.00	185.75
tubular armrests	N/C	1.60
straight armrest pads, long	N/C	15.75
straight armrest pads, short	N/C	14.00
clothing guards, rigid		
a pair	86.00	
each		63.00
Footrests:		
60° or 70° footrests, detachable, swingaway,		
length-adjustable, from 35.6 cm (14 in.)		
to 48.3 cm (19 in.)	N/C	50.00
90° footrests, detachable, swingaway,		
length-adjustable, from 20.3 cm (8 in.)		
to 33.0 cm (13 in.)	N/C	50.00
70° or 80° footrests, detachable, swingaway,		
length-adjustable, from 15.2 cm (6 in.)	N/G	<b>72</b> 00
to 30.5 cm (12 in.)	N/C	52.00
70°, 80° or 90° footrests, heavy-duty,	N/C	76.00
detachables, non flip-back	N/C	76.00
elevating legrests, compensating mechanism	185.00	
a pair each	183.00	142.50
90° elevating legrests, detachable, swingaway,		142.30
length-adjustable, from 20.3 cm (8 in.)		
to 33.0 cm (13 in.)		
a pair	66.00	
each	30.00	83.00
elevating legrests, detachable, swingaway,		22.30
length-adjustable		
a pair	100.00	
each		100.00
modification of footrest length, from 48.3 cm		
(19 in.) to 52.1 cm $(20^{1}/_{2} in.)$	29.00	28.00
modification of length of 90° footrest, by + 5.1 cm		
(2 in.) or by +10.2 cm (4 in.)		

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
single calf strap	17.00	17.00
folding footplates	N/C	46.00
folding footplates, angle-adjustable	40.00	
a pair	49.00	70.50
each full-width footplate, angle-adjustable	79.00	70.50 171.00
full-width footplate, angic-adjustable	85.00	177.00
footrest mounting, from 17.8 cm (7 in.)		
to 34.3 cm $(13^{1}/_{2} \text{ in.})$		
a pair	51.50	
each	NG	31.50
heel loops, length-adjustable	N/C	9.50
Wheels and frame		
Types of drive systems:	500.00	
one-arm dual handrim drive	520.00	655.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	55.00
nandrims with oblique or vertical projections	N/C	33.00
a pair	38.00	
each		74.00
plastic-coated handrims, 50.8 cm (20 in.),		
55.9 cm (22 in.), 61.0 cm (24 in.)	51.00	
a pair each	51.00	80.50
non-slip handrims, 55.9 cm (22 in.), 61.0 cm (24 in.)		80.30
a pair	84.00	
each		97.00
plastic-coated handrims for one-arm drive	51.00	N/A
front anti-tip rollers		
a pair	41.00	20.50
each eane holder	42.00	20.50 42.00
cane noider	42.00	42.00
Wheel locks:		
standard wheel locks, push-to-lock or pull-to-lock	N/C	37.00
wheel lock extensions, 15.2 cm (6 in.)	25.00	
each	23.00	12.50
anti-rollback brakes		12.30
a pair	63.00	
each		31.50
Types of forks:		
standard forks, 15.2 cm (6 in.); short forks,		
13.3 cm (5 <sup>1</sup> / <sub>4</sub> in.); or high forks,17.8 cm (7 in.);		
compatible with 12.7 cm (5 in.), 15.2 cm (6 in.)		
and 20.3 cm (8 in.) wheels	N/C	29.50
ork-locking mechanism	12.00	
pair	42.00	21.00
each	N/C	21.00 15.00
Fork stems, $+ 1.9 \text{ cm} (\sqrt[3]{4} \text{ in.}) \text{ or } + 3.8 \text{ cm} (1\sqrt[1]{2} \text{ in.})$	N/C	15.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Rear axles:		
quick-release axles	N/C	31.00
Types of wheels:		
spoked rear wheels, solid tires, 50.8 cm		
(20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) spoked rear wheels, standard pressure, 50.8 cm	N/C	142.00
(20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	126.00
poked rear wheels, high pressure,		
51.0 cm (24 in.)	N/C	126.00
ear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C	126.00
ear mag wheels, standard pressure,	1,, 5	120.00
55.9 cm (22 in.)	NG	107.00
or 61.0 cm (24 in.) ear mag wheels, solid tires, 50.8 cm (20 in.),	N/C	105.00
65.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	126.00
rear mag wheels, standard pressure,		
80.5 cm (12 in.)	N/C	120.00
ear mag wheels, standard pressure, 40.6 cm (16 in.)		
pair	30.00	
each		135.00
Front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.)	N/C	58.00
Front wheels, solid tires, 15.2 cm (6 in.)	N/C	57.00
Front wheels, solid tires, 12.7 cm (5 in.)	N/C	43.50
Front wheels, inner tube, 20.3 cm		
8 in.) X 5.1 cm (2 in.)	45.00	
each	13.00	66.00
ront wheels, inner tube, 20.3 cm		
8 in.) $\times 3.2$ cm ( $1^{1}/_{4}$ in.)	N/C	58.00
Front wheels, inner tube, 15.2 cm 6 in.) X 3.2 cm $(1^{1}/_{4} \text{ in.})$	N/C	57.50
Front wheels, semi-pneumatic tires,	1,, 0	27.60
$2.7 \text{ cm } (5 \text{ in.}) \text{ X } 3.8 \text{ cm } (1^{1}/_{2} \text{ in.})$		
or 15.2 cm (6 in.) X 3.8 cm (1 <sup>1</sup> / <sub>2</sub> in.)	76.50	
a pair each	70.30	81.75
ront wheels, semi-pneumatic tires,		
$20.3 \text{ cm } (8 \text{ in.}) \text{ X } 3.8 \text{ cm } (1^{1}/_{2} \text{ in.})$	05.00	
i pair ach	95.00	91.00
airless inserts for 20.3 cm (8 in.) X 5.1 cm		71.00
2 in.) front wheels		
n pair	106.00	<b>%</b> T / A
each airless inserts for 30.5 cm (12 in.),		N/A
50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.) rear wheels		
pair	51.00	<b>N</b> T / A
each		N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
spoke guards * a pair each	64.00	32.00

§2. Lightweight manual wheel chairs

## DEVICE FROM: EVEREST & JENNINGS CANADA LTD.

**PRICE** 

# LIGHTWEIGHT MANUAL WHEEL CHAIR, "CHAMPION 3000" MODEL

\$1 420.00

# Basic Component(s)

# **Body support system**

- folding back, height adjustable, from 33.0 cm (13 in.) to 40.6 cm (16 in.) and angle-adjustable, from – 10° to + 20°
- seat width: from 35.6 cm (14 in.)
- to 45.7 cm (18 in.)
- front seating height: from 48.3 cm (19 in.) to 53.3 cm (21 in.)
- seat depths: 38.1 cm (15 in.), 40.0 cm (15<sup>3</sup>/<sub>4</sub> in.), 41.9 cm (16<sup>1</sup>/<sub>2</sub> in.), 43.8 cm (17<sup>1</sup>/<sub>4</sub> in.)
- short frame, allowing seat depths of 38.1 cm (15 in.) to 43.8 cm (17<sup>1</sup>/<sub>4</sub> in.) (4 positions)
- supple seat and back, nylon
- safety belt, auto-type
- · push handles

### **Armrests**

- "L"-type armrests, detachable, swingaway, height-adjustable, from 20.3 cm (8 in.) to 25.4 cm (10 in.), short
- clothing guards, flexible; clothing guards, rigid, fixed, straight
- · tubular armrests

- 75° footrests, parallel, fixed, length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- 75°, 85° footrests, "V"-shaped, fixed, length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- · full-width footplate, fixed
- single calf strap

- anodized aluminum handrims, 50.8 cm (20 in.),
   55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- · standard wheel locks, push-to-lock
- high forks
- · quick-release axles
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, heavy-duty, standard pressure, high pressure, 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 12.7 cm (5 in.) X 2.5 cm (1 in.)
- rear wheel camber, 0°, 3°

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
supple back, ballistic nylon	66.00	138.00
supple back, tension-adjustable	72.00	145.00
folding back, height adjustable, from 33.0 cm		
(13 in.) to 40.6 cm (16 in.) and angle-adjustable		
from - $10^{\circ}$ to + $20^{\circ}$	N/C	N/A
modification of back height, from 20.3 cm (8 in.)		
to 30.5 cm (12 in.) or from 43.2 cm (17 in.)		
to 50.8 cm (20 in.)	52.00	N/A
modification of seat width to 33.0 cm (13 in.),		
48.3 cm (19 in.) or 50.8 cm (20 in.)	118.00	N/A
modification of rear seating height	118.00	N/A
short frame, allowing seat depths of 38.1 cm		
(15 in.) to 43.8 cm $(17^{1}/_{4} \text{ in.})$ , (4 positions)	N/C	N/A
long frame	108.00	N/A
extra long frame	206.00	N/A
modification of seat depth to 48.3 cm (19 in.)		
or 50.8 cm (20 in.)	52.00	N/A
push handles	N/C	24.00
supple back, nylon	N/C	72.00
supple seat, nylon	N/C	72.00
stabilizer bar	93.00	93.00
bolt-on push handles		
a pair	36.00	
each		42.00
growth kit, width or depth	N/A	375.00
seat cushion, flat, foam, 5.1 cm (2 in.)	58.00	58.00
seat cushion, flat, foam, 7.5 cm (3 in.)	58.00	58.00
seat cushion, flat, foam, 10 cm (4 in.)	58.00	58.00
safety belt, auto-type	N/C	28.00
safety belt, airplane-type	30.00	58.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
"L"-type armrests, detachable, swingaway,		
height-adjustable, from 20.3 cm (8 in.)		
to 25.4 cm (10 in.), short	N/C	68.00
tubular armrests	N/C	6.00
straight armrest pads, short	13.00	13.00
clothing guards, rigid, detachable, straight		
or fender-style		
pair	56.00	
ach	21/6	75.00
lothing guards, flexible	N/C	21.00
lothing guards, rigid, fixed, straight	N/C	47.00
Cootrests:		
75° fixed footrests, parallel, length-adjustable,		
from 35.6 cm (14 in.) to 45.7 cm (18 in.)	N/C	N/A
5° or 85° footrests, "V"-shaped, fixed,		
ength-adjustable, from 35.6 cm (14 in.)	3716	27/1
o 45.7 cm (18 in.)	N/C	N/A
00° footrests, "V"-shaped, fixed,		
ength-adjustable, from 35.6 cm (14 in.)	102.00	NT/A
o 45.7 cm (18 in.)	103.00 N/C	N/A 25.00
ingle calf strap louble calf strap	46.00	48.00
full-width footplate, fixed	N/C	95.00
full-width footplate, inxed	50.00	145.00
nodification of footrest length	87.00	N/A
aised footrests with full-width footplate,	07.00	14/11
ingle-adjustable and depth-adjustable	121.00	216.00
ront floor roller	31.00	31.00
		2 2.00
Wheels and frame Types of drive systems :		
andrims with oblique or vertical projections		
ı pair	158.00	
ach		124.00
lastic-coated handrims		
pair	68.00	=
ach		79.00
anodized aluminum handrims, 50.8 cm (20 in.),	NI/O	45.00
5.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	45.00
on-slip handrims	86.00	
pair ach	80.00	88.00
acn ombined handrims		00.00
pair	86.00	
ach	30.00	88.00
ront anti-tip rollers		00.00
pair	88.00	
ach	30.00	44.00
ane holder	43.00	43.00
and notice	13.00	13.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks:		
standard wheel locks, push-to-lock standard wheel locks, pull-to-lock	N/C	57.00
a pair	30.00	
each swing-away brakes		72.00
a pair	30.00	
each		72.00
wheel lock extensions a pair	26.00	
each	20.00	13.00
nti-rollback brakes		
ı pair ach	100.00	107.00
acii		107.00
Types of forks:		
short forks a pair	20.00	
each		60.00
nigh forks	N/C	50.00
ork-locking mechanisms a pair	88.00	
each	00.00	100.00
ong fork stems	95.00	N/A
Rear axles:		
quick-release axles	N/C	51.00
centre of gravity adjustment, by + 2.5 cm (1 in.) or by + 5.1 cm (2 in.)		
pair	62.00	
each	N/G	93.00
ear wheel camber, 0°, 3° ear wheel camber, 6°, 9° or 12°	N/C 45.00	150.00 195.00
car wheel camber, 0, 7 or 12	43.00	175.00
Wheels and frame		
Types of wheels: ear mag wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	118.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	125.00
poked rear wheels, heavy-duty, standard pressure,	IN/C	123.00
51.0 cm (24 in.)	N/C	140.00
poked rear wheels, high pressure, 55.9 cm (22 in.), 1.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	130.00
poked rear wheels, heavy-duty, high pressure,	IN/C	130.00
51.0 cm (24 in.)	N/C	140.00
poked rear wheels, heavy-duty, standard pressure r high pressure, 66.0 cm (26 in.)		
pair	50.00	
ach		165.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, solid tires, 7.6 cm (3 in.)		
a pair	44.00	
each		42.00
front wheels, solid tires, 12.7 cm	3716	• • • • •
(5 in.) X 2.5 cm (1 in.)	N/C	20.00
front wheels, inner tube, 15.2 cm		
(6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	44.00	
a pair	44.00	42.00
each		42.00
front wheels, semi-pneumatic tires,		
17.8 cm (7 in.) X 2.5 cm (1 in.) or 15.2 cm (6 in.) X 2.5 cm (1 in.)		
a pair	44.00	
each	44.00	44.00
front wheels, semi-pneumatic tires, 12.7 cm		11.00
(5 in.) X 5.1 cm (2 in.)		
a pair	84.00	
each		62.00
rear puncture-resistant tires		
a pair	55.00	
each		N/A
Component(s) under Special Consideration		
spoke guards *		
a pair	72.00	
each		36.00
quick-release axles with lever mechanism *		
a pair	70.00	
each		87.00
DEVICE FROM: INVACARE CANADA INC.		
DETICE I ROMA IN THOMAS CHAMPINE INC.		

**PRICE** 

# LIGHTWEIGHT MANUAL WHEEL CHAIR, "ACTION PRO-T" MODEL

\$1 296.00

# Basic Component(s)

# **Body support system**

- folding back, height adjustable, from 30.5 cm (12 in.) to 50.8 cm (20 in.)
- supple seat and back, nylon
- front seating height: from 41.3 cm (16<sup>1</sup>/<sub>4</sub> in.) to 57.2 cm (22<sup>1</sup>/<sub>2</sub> in.)
- seat width: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.)
- safety belt, velcro-type, auto-type
- · back handlebar
- · push handles

#### Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable, from 18.4 cm (7<sup>1</sup>/<sub>4</sub> in.) to 23.5 cm (9<sup>1</sup>/<sub>4</sub> in.), short
- straight armrest pads, short, long
- · contoured armrest pads, short, long
- tubular armrests
- · clothing guards, flexible

### **Footrests**

- 70°, 80° footrests, fixed, parallel or pointing inwards, length-adjustable, from 40.0 cm (15<sup>3</sup>/<sub>4</sub> in.) to 48.3 cm (19 in.)
- folding footplates, standard or tubular, fixed footplate
- single calf strap
- padded calfrests
- heel loops, non-adjustable
- heel loops, length-adjustable

- anodized aluminum handrims, 50.8 cm (20 in.),
   55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- swing-away brakes or standard wheel locks, push-to-lock
- standard forks compatible with 7.6 cm (3 in.), 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- threaded axles, quick-release axles
- spoked rear wheels, standard pressure, 55.9 cm (22 in.)
- spoked rear wheels, standard pressure, high pressure, 61.0 cm (24 in.)
- spoked rear wheels, heavy-duty, high pressure, 61.0 cm (24 in.)
- rear mag wheels, standard pressure, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, solid tires (KIK), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.), 7.6 cm (3 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
<b>Body support system Seat and back:</b> modification of seat width to 48.3 cm (19 in.),		
50.8 cm (20 in.) or 55.9 cm (22 in.)	115.00	N/A
modification of seat depth to 50.8 cm (20 in.) or 55.9 cm (22 in.) modification of rear seating height with	58.00	N/A
personalized angle frame option	161.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
heavy-duty frame	257.00	N/A
folding back, height adjustable, from 30.5 cm		
(12 in.) to 50.8 cm (20 in.)	N/C	N/A
supple back, tension-adjustable	63.00	98.00
oolt-on push handles		
pair	66.00	
ach		37.00
ush handles	N/C	37.00
ack handlebar	N/C	52.00
upple back, nylon	N/C	35.00
upple seat, nylon	N/C	35.00
eat cushion, flat, foam, 5.1 cm (2 in.)	55.00	55.00
eat cushion, flat, foam, 7.6 cm (3 in.)	55.00	55.00
afety belt, velcro-type	N/C	20.00
afety belt, auto-type	N/C	30.00
Armrests:		
L"-type armrests, detachable, swingaway,		
eight-adjustable, from 18.4 cm (7 <sup>1</sup> / <sub>4</sub> in.)		
23.5 cm (9 <sup>1</sup> / <sub>4</sub> in.) short	N/C	53.00
T"-type armrests, detachable, height-adjustable,		
com 12.7 cm (5 in.) to 20.3 cm (8 in.) or 20.3 cm		
8 in.) to 27.9 cm (11 in.), short or long	82.00	94.00
lothing guards, flexible	N/C	14.00
lothing guards, rigid, detachable	59.00	44.00
ıbular armrests	N/C	10.00
rmrest pads, straight or contoured, short or long	N/C	26.00
Cootrests:		
0° or 80° footrests, fixed, parallel or pointing inwards,		
ength-adjustable, from $40.0 \text{ cm} (15^3/_4 \text{ in.})$		
o 48.3 cm (19 in.)	N/C	N/A
0° footrests, detachable, swingaway,		
ength-adjustable, from 35.6 cm (14 in.)		
o 48.3 cm (19 in.); or 70° footrests, detachable,		
wingaway, length-adjustable, from 33.0 cm (13 in.)		
0 43.2 cm (17 in.)	122.00	
pair	133.00	<b>5</b> 0.00
ach		78.00
V"-shaped footrests, detachable, swingaway,		
ength-adjustable, from 36.8 cm (14 <sup>1</sup> / <sub>2</sub> in.)		
9 43.2 cm (17 in.)	100.00	
pair	199.00	120.00
ach		129.00
0° or 70° footrests, detachable, swingaway,		
ength-adjustable, from 24.8 cm (9 <sup>3</sup> / <sub>4</sub> in.)		
35.6 cm (14 in.)		
pair	271.00	
ach		147.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
modification of footrest length by more		
than 5.1 cm (2 in.)	76.00	38.00
60° elevating legrests, detachable, swingaway,		
ength-adjustable, from 40.6 cm (16 in.) o 50.8 cm (20 in.)		
o 30.8 cm (20 m.) 1 pair	210.00	
ach	210.00	183.00
nodification of legrest length, by 2.5 cm		103.00
1 in.) or by 5.1 cm (2 in.)	150.00	150.00
added calfrests	N/C	17.00
ingle calf strap	N/C	43.00
ouble calf strap	53.00	53.00
ixed footplate	N/C	24.00
olding footplates, standard or tubular	N/C	37.00
olding footplates, angle-adjustable		
pair	72.00	<b></b>
ach		73.00
olding footplates, oversized	29.00	
pair	28.00	<b>5</b> 1.00
ach	N/C	51.00 3.00
eel loops, non-adjustable eel loops, length-adjustable	N/C N/C	10.00
pe loops	N/C	10.00
pair	15.00	
ach	15.00	8.00
eel loops and ankle straps		
pair	32.00	
âch		16.00
Wheels and frame		
Types of drive systems:		
andrims with vertical or oblique projections		
pair	155.00	
ach		111.00
nodized aluminum handrims, 50.8 cm (20 in.),	3.716	
5.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	33.00
lastic-coated handrims	52.00	
pair ach	53.00	59.00
acn ront anti-tip rollers		39.00
pair	95.00	
pan ach	93.00	48.00
ront floor rollers	41.00	41.00
011/11/01 1011/10	11.00	11.00

andard wheel locks, push-to-lock andard wheel locks, pull-to-lock 32.00 60.00 wing-away brakes N/C 44.00 heel lock extensions pair 32.00 and not have been been been been been been been be		Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
andard wheel locks, pull-to-lock ving-away brakes pair ving-away brakes ving-aw	Wheel locks:		
wing_away brakes         N/C         44.00           heel lock extensions         32.00         16.00           pair         32.00         16.00           tit-rollback brakes         98.00         93.00           pair         98.00         93.00           ypes of forks:         32.00         33.00           sch         N/C         33.00           xt-locking mechanisms         N/C         33.00           pair         100.00         50.00           ear axles:         100.00         50.00           ear axles:         100.00         50.00           ear axles:         80.00         68.00           cick-release axles         N/C         68.00           de extension plates for amputee         80.00           22 in.) or 61.0 cm (24 in.)         N/C	standard wheel locks, push-to-lock	N/C	44.00
wing-away brakes heel lock extensions pair 32.00 ch 16.00 threel lock extensions pair 32.00 ch 16.00 threel lock extensions pair 32.00 ch 16.00 threel lock brakes 15.00 pair 98.00 ch 93.00 ch		32.00	60.00
heel lock extensions pair 32.00 and tit-rollback brakes pair 98.00 and tit-rollback brakes pair 98.00 and 20.3 cm (8 in.) wheels N/C 33.00 and 20.3 cm (8 in.) wheels N/C 33.00 and pair 100.00 and pair		N/C	44.00
pair (1500 thirt-rollback brakes (1500 thirt-rollback brak	heel lock extensions		
ich tit-rollback brakes pair 98.00  spes of forks: andard forks for 7.6 cm (3 in.), 12.7 cm (5 in.), 5.2 cm (6 in.) and 20.3 cm (8 in.) wheels N/C 33.00  rk-locking mechanisms pair 100.00  ear axles: readed axles ick-release axles de extension plates for amputee pair 68.00 ich 50.00  spes of wheels: ar mag wheels, standard pressure, 55.9 cm 22 in.) or 61.0 cm (24 in.) ar mag wheels, solid tires, 55.9 cm (22 in.) 61.0 cm (24 in.) N/C 83.00  obcked rear wheels, standard pressure or high ressure, 61.0 cm (24 in.) pair 82.00 ich 83.00 boked rear wheels, solid tires (KIK), 61.0 cm (24 in.) pair 82.00 ich 83.00 boked rear wheels, solid tires (KIK), 66.0 cm (26 in.) pair 82.00 pair 106.00 cm (26 in.)		32.00	
pair (ch	ach		16.00
ypes of forks: andard forks for 7.6 cm (3 in.), 12.7 cm (5 in.), 5.2 cm (6 in.) and 20.3 cm (8 in.) wheels	nti-rollback brakes		
ypes of forks: andard forks for 7.6 cm (3 in.), 12.7 cm (5 in.), 5.2 cm (6 in.) and 20.3 cm (8 in.) wheels	pair	98.00	
andard forks for 7,6 cm (3 in.), 12.7 cm (5 in.), 5.2 cm (6 in.) and 20.3 cm (8 in.) wheels  rk-locking mechanisms  pair  100.00  ear axles:  readed axles  N/C  15.00  rkl-locking mechanisms  pair  readed axles  readed axles  N/C  15.00  rkl-locking mechanisms  N/C  15.00  rear axles:  readed axles  readed axles  N/C  15.00  rear axles:  readed axles  N/C  15.00  rear axles:  readed axles  N/C  15.00  rear axles:  readed axles  N/C  16.00  rear	ach		93.00
andard forks for 7,6 cm (3 in.), 12.7 cm (5 in.), 5.2 cm (6 in.) and 20.3 cm (8 in.) wheels  rk-locking mechanisms  pair  100.00  ear axles:  readed axles  N/C  15.00  rkl-locking mechanisms  pair  readed axles  readed axles  N/C  15.00  rkl-locking mechanisms  N/C  15.00  rear axles:  readed axles  readed axles  N/C  15.00  rear axles:  readed axles  N/C  15.00  rear axles:  readed axles  N/C  15.00  rear axles:  readed axles  N/C  16.00  rear			
andard forks for 7,6 cm (3 in.), 12.7 cm (5 in.), 5.2 cm (6 in.) and 20.3 cm (8 in.) wheels  rk-locking mechanisms  pair  100.00  ear axles:  readed axles  N/C  15.00  rkl-locking mechanisms  pair  readed axles  readed axles  N/C  15.00  rkl-locking mechanisms  N/C  15.00  rear axles:  readed axles  readed axles  N/C  15.00  rear axles:  readed axles  N/C  15.00  rear axles:  readed axles  N/C  15.00  rear axles:  readed axles  N/C  16.00  rear	ypes of forks:		
rk-locking mechanisms pair 100.00 cch 50.00  ear axles: readed axles N/C 15.00 cick-release axles N/C 53.00 cle extension plates for amputee pair 68.00  ypes of wheels: ar mag wheels, standard pressure, 55.9 cm (22 in.) or 61.0 cm (24 in.) coked rear wheels, standard pressure or high ressure, 61.0 cm (24 in.) coked rear wheels, standard pressure or high ressure, 66.0 cm (26 in.) pair 82.00 coked rear wheels, solid tires (KIK), 61.0 cm (24 in.) coked rear wheels, solid tires (KIK), 66.0 cm (26 in.) pair 82.00 coked rear wheels, solid tires (KIK), 66.0 cm (24 in.) coked rear wheels, solid tires (KIK), 66.0 cm (24 in.) coked rear wheels, solid tires (KIK), 66.0 cm (26 in.) pair 82.00 coked rear wheels, solid tires (KIK), 66.0 cm (24 in.) coked rear wheels, solid tires (KIK), 66.0 cm (24 in.) coked rear wheels, solid tires (KIK), 67.0 cm (24 in.) coked rear wheels, solid tires (KIK), 67.0 cm (24 in.) coked rear wheels, solid tires (KIK), 67.0 cm (24 in.) coked rear wheels, solid tires (KIK), 67.0 cm (24 in.) coked rear wheels, solid tires, 67.0 cm (24 in.) coked rear wheels, heavy-duty, standard pressure chigh pressure, 67.0 cm (24 in.) coked rear wheels, heavy-duty, standard pressure chigh pressure, 67.0 cm (26 in.)	andard forks for 7.6 cm (3 in.), 12.7 cm (5 in.),		
rk-locking mechanisms pair 100.00 cch 50.00  ear axles: readed axles N/C 15.00 cick-release axles N/C 53.00 cle extension plates for amputee pair 68.00  ypes of wheels: ar mag wheels, standard pressure, 55.9 cm (22 in.) or 61.0 cm (24 in.) coked rear wheels, standard pressure or high ressure, 61.0 cm (24 in.) coked rear wheels, standard pressure or high ressure, 66.0 cm (26 in.) pair 82.00 coked rear wheels, solid tires (KIK), 61.0 cm (24 in.) coked rear wheels, solid tires (KIK), 66.0 cm (26 in.) pair 82.00 coked rear wheels, solid tires (KIK), 66.0 cm (24 in.) coked rear wheels, solid tires (KIK), 66.0 cm (24 in.) coked rear wheels, solid tires (KIK), 66.0 cm (26 in.) pair 82.00 coked rear wheels, solid tires (KIK), 66.0 cm (24 in.) coked rear wheels, solid tires (KIK), 66.0 cm (24 in.) coked rear wheels, solid tires (KIK), 67.0 cm (24 in.) coked rear wheels, solid tires (KIK), 67.0 cm (24 in.) coked rear wheels, solid tires (KIK), 67.0 cm (24 in.) coked rear wheels, solid tires (KIK), 67.0 cm (24 in.) coked rear wheels, solid tires, 67.0 cm (24 in.) coked rear wheels, heavy-duty, standard pressure chigh pressure, 67.0 cm (24 in.) coked rear wheels, heavy-duty, standard pressure chigh pressure, 67.0 cm (26 in.)		N/C	33.00
ear axles: readed axles readed	ork-locking mechanisms		
ear axles: readed axles readed	pair	100.00	
readed axles	ach		50.00
readed axles			
tick-release axles de extension plates for amputee pair 68.00 cle extension plates for amputee pair 68.00 cle ch 50.00 cle	Rear axles:		
Section   Sect	hreaded axles		15.00
pair 68.00  ypes of wheels: ar mag wheels, standard pressure, 55.9 cm (22 in.) or 61.0 cm (24 in.)	uick-release axles	N/C	53.00
Solid   Soli	xle extension plates for amputee		
ypes of wheels: ar mag wheels, standard pressure, 55.9 cm (22 in.) or 61.0 cm (24 in.) ar mag wheels, solid tires, 55.9 cm (22 in.) (61.0 cm (24 in.) (61.0 cm (26 in.) (61.0	pair	68.00	
ar mag wheels, standard pressure, 55.9 cm (22 in.) or 61.0 cm (24 in.) Ar mag wheels, solid tires, 55.9 cm (22 in.) Ar mag wheels, solid tires, 55.9 cm (22 in.) Ar mag wheels, solid tires, 55.9 cm (22 in.) Ar mag wheels, standard pressure or high Ar mag wheels, solid tires (KIK), 61.0 cm (24 in.) Ar mag wheels, solid tires (KIK), 66.0 cm (26 in.) Ar mag wheels, solid tires (KIK), 66.0 cm (26 in.) Ar mag wheels, solid tires, 61.0 cm (24 in.) Ar mag wheels, beavy-duty, standard pressure Ar high pressure, 61.0 cm (24 in.) Ar mag wheels, heavy-duty, standard pressure Ar high pressure, 66.0 cm (26 in.) Ar mag wheels, heavy-duty, standard pressure Ar high pressure, 66.0 cm (26 in.) Ar mag wheels, heavy-duty, standard pressure Ar high pressure, 66.0 cm (26 in.)	ach		50.00
ar mag wheels, standard pressure, 55.9 cm (22 in.) or 61.0 cm (24 in.) Ar mag wheels, solid tires, 55.9 cm (22 in.) Ar mag wheels, solid tires, 55.9 cm (22 in.) Ar mag wheels, solid tires, 55.9 cm (22 in.) Ar mag wheels, standard pressure or high Ar mag wheels, solid tires (KIK), 61.0 cm (24 in.) Ar mag wheels, solid tires (KIK), 66.0 cm (26 in.) Ar mag wheels, solid tires (KIK), 66.0 cm (26 in.) Ar mag wheels, solid tires, 61.0 cm (24 in.) Ar mag wheels, beavy-duty, standard pressure Ar high pressure, 61.0 cm (24 in.) Ar mag wheels, heavy-duty, standard pressure Ar high pressure, 66.0 cm (26 in.) Ar mag wheels, heavy-duty, standard pressure Ar high pressure, 66.0 cm (26 in.) Ar mag wheels, heavy-duty, standard pressure Ar high pressure, 66.0 cm (26 in.)			
22 in.) or 61.0 cm (24 in.)   N/C   69.00     aar mag wheels, solid tires, 55.9 cm (22 in.)     61.0 cm (24 in.)   N/C   42.00     ooked rear wheels, standard pressure or high ressure, 61.0 cm (24 in.)   N/C   83.00     ooked rear wheels, standard pressure or high ressure, 66.0 cm (26 in.)     pair   82.00     ooked rear wheels, solid tires (KIK), 61.0 cm (24 in.)   N/C   83.00     ooked rear wheels, solid tires (KIK), 66.0 cm (26 in.)     pair   82.00     ooked rear wheels, solid tires (KIK), 66.0 cm (26 in.)     pair   82.00     ooked rear wheels, solid tires, 61.0 cm (24 in.)     ooked rear wheels, solid tires, 61.0 cm (24 in.)     ooked rear wheels, heavy-duty, standard pressure     ooked rear wheels, heav			
ar mag wheels, solid tires, 55.9 cm (22 in.)  61.0 cm (24 in.)  76.10 cm (24 in.)  82.00  83.00  83.00  83.00  83.00  83.00  83.00  82.00  83.00		N/C	<b>60.00</b>
106.00 cm (24 in.)		N/C	69.00
poked rear wheels, standard pressure or high ressure, 61.0 cm (24 in.)  poked rear wheels, standard pressure, 55.9 cm (22 in.)  poked rear wheels, standard pressure or high ressure, 66.0 cm (26 in.)  pair  pair  poked rear wheels, solid tires (KIK), 61.0 cm (24 in.)  poked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  pair  poked rear wheels, solid tires, 61.0 cm (24 in.)  poked rear wheels, solid tires, 61.0 cm (24 in.)  poked rear wheels, solid tires, 61.0 cm (24 in.)  poked rear wheels, heavy-duty, standard pressure  high pressure, 61.0 cm (24 in.)  poked rear wheels, heavy-duty, standard pressure  high pressure, 66.0 cm (26 in.)		N/C	42.00
ressure, 61.0 cm (24 in.)  roked rear wheels, standard pressure, 55.9 cm (22 in.)  roked rear wheels, standard pressure or high ressure, 66.0 cm (26 in.)  pair  roked rear wheels, solid tires (KIK), 61.0 cm (24 in.)  roked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  pair  roked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  pair  roked rear wheels, solid tires, 61.0 cm (24 in.)  roked rear wheels, solid tires, 61.0 cm (24 in.)  roked rear wheels, solid tires, 61.0 cm (24 in.)  roked rear wheels, heavy-duty, standard pressure		N/C	42.00
boked rear wheels, standard pressure, 55.9 cm (22 in.)  boked rear wheels, standard pressure or high  ressure, 66.0 cm (26 in.)  pair  boked rear wheels, solid tires (KIK), 61.0 cm (24 in.)  boked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  pair  boked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  pair  boked rear wheels, solid tires, 61.0 cm (24 in.)  conduction  c		N/C	92.00
poked rear wheels, standard pressure or high ressure, 66.0 cm (26 in.)  pair 82.00  ach soked rear wheels, solid tires (KIK), 61.0 cm (24 in.)  pair 82.00  soked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  pair 82.00  ach soked rear wheels, solid tires, 61.0 cm (24 in.)  ref6.0 cm (26 in.)  pair 106.00  ach soked rear wheels, heavy-duty, standard pressure high pressure, 61.0 cm (24 in.)  ref6.0 cm (26 in.)  N/C 95.00  soked rear wheels, heavy-duty, standard pressure high pressure, 66.0 cm (26 in.)			
ressure, 66.0 cm (26 in.)  pair  82.00  83.00  soked rear wheels, solid tires (KIK), 61.0 cm (24 in.)  pair  82.00  soked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  pair  82.00  83.00  83.00  83.00  83.00  83.00  83.00  80.00		N/C	83.00
pair 82.00 sich 83.00 soked rear wheels, solid tires (KIK), 61.0 cm (24 in.) N/C 83.00 soked rear wheels, solid tires (KIK), 66.0 cm (26 in.) pair 82.00 sich 83.00 seavy-duty rear wheels, solid tires, 61.0 cm (24 in.) re 66.0 cm (26 in.) pair 106.00 sich 95.00 soked rear wheels, heavy-duty, standard pressure high pressure, 61.0 cm (24 in.) re 66.0 cm (26 in.) N/C 95.00 soked rear wheels, heavy-duty, standard pressure high pressure, 66.0 cm (26 in.)			
sch  ooked rear wheels, solid tires (KIK), 61.0 cm (24 in.)  ooked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  pair  och  eavy-duty rear wheels, solid tires, 61.0 cm (24 in.)  re 66.0 cm (26 in.)  pair  ooked rear wheels, heavy-duty, standard pressure  re high pressure, 61.0 cm (24 in.)  ooked rear wheels, heavy-duty, standard pressure  re high pressure, 66.0 cm (26 in.)  N/C  95.00  ooked rear wheels, heavy-duty, standard pressure  re high pressure, 66.0 cm (26 in.)		92.00	
poked rear wheels, solid tires (KIK), 61.0 cm (24 in.) poked rear wheels, solid tires (KIK), 66.0 cm (26 in.) pair pair pair pair poked (26 in.) pair poked (26 in.) pair poked (26 in.) pair poked (26 in.) pair poked rear wheels, heavy-duty, standard pressure high pressure, 61.0 cm (24 in.) poked rear wheels, heavy-duty, standard pressure high pressure, 66.0 cm (26 in.) N/C poked rear wheels, heavy-duty, standard pressure high pressure, 66.0 cm (26 in.)		82.00	92.00
poked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  pair 82.00 83.00 eavy-duty rear wheels, solid tires, 61.0 cm (24 in.) 66.0 cm (26 in.)  pair 106.00 ech 106.0		N/C	
pair 82.00  ach 83.00 eavy-duty rear wheels, solid tires, 61.0 cm (24 in.)  66.0 cm (26 in.)  pair 106.00  ach 95.00  ack 95.00  boked rear wheels, heavy-duty, standard pressure  high pressure, 61.0 cm (24 in.) N/C 95.00  boked rear wheels, heavy-duty, standard pressure  high pressure, 66.0 cm (26 in.)		N/C	83.00
83.00 eavy-duty rear wheels, solid tires, 61.0 cm (24 in.) e 66.0 cm (26 in.) pair pair 106.00 ech ooked rear wheels, heavy-duty, standard pressure high pressure, 61.0 cm (24 in.) ooked rear wheels, heavy-duty, standard pressure high pressure, 66.0 cm (26 in.)		92.00	
eavy-duty rear wheels, solid tires, 61.0 cm (24 in.)  7 66.0 cm (26 in.)  Pair  106.00  106.00  95.00  Poked rear wheels, heavy-duty, standard pressure  Thigh pressure, 61.0 cm (24 in.)  Poked rear wheels, heavy-duty, standard pressure  Thigh pressure, 66.0 cm (26 in.)		82.00	92.00
r 66.0 cm (26 in.) pair 106.00 sch 95.00 soked rear wheels, heavy-duty, standard pressure r high pressure, 61.0 cm (24 in.) N/C 95.00 soked rear wheels, heavy-duty, standard pressure r high pressure, 66.0 cm (26 in.)			83.00
pair 106.00 sch 95.00 soked rear wheels, heavy-duty, standard pressure high pressure, 61.0 cm (24 in.) N/C 95.00 soked rear wheels, heavy-duty, standard pressure high pressure, 66.0 cm (26 in.)			
och 95.00 boked rear wheels, heavy-duty, standard pressure high pressure, 61.0 cm (24 in.) N/C 95.00 boked rear wheels, heavy-duty, standard pressure high pressure, 66.0 cm (26 in.)		106.00	
ooked rear wheels, heavy-duty, standard pressure high pressure, 61.0 cm (24 in.) ooked rear wheels, heavy-duty, standard pressure high pressure, 66.0 cm (26 in.)		100.00	05.00
r high pressure, 61.0 cm (24 in.) N/C 95.00 poked rear wheels, heavy-duty, standard pressure high pressure, 66.0 cm (26 in.)			95.00
ooked rear wheels, heavy-duty, standard pressure thigh pressure, 66.0 cm (26 in.)		NI/C	05.00
high pressure, 66.0 cm (26 in.)		N/C	95.00
pair 106.00		106.00	
		106.00	05.00
95.00	ach		95.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.) or 7.6 cm (3 in.) front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm	N/C	23.00
(1 <sup>1</sup> / <sub>4</sub> in.) or 15.2 cm (6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) a pair each	32.00	39.00
airless inserts for front wheels a pair each airless inserts for rear wheels	95.00	N/A
arriess inserts for rear wheels a pair each	99.00	N/A
Component(s) under Special Consideration		
spoke guards * a pair each	82.00	41.00
quick-release axles with lever mechanism * a pair each	76.00	53.00
DEVICE FROM: INVACARE CANADA INC.		

#### **DEVICE FROM: INVACARE CANADA INC.**

**PRICE** 

# LIGHTWEIGHT MANUAL WHEEL CHAIR, "ACTION A-6/F-6" MODEL

\$1 296.00

# Basic Component(s)

# **Body support system**

- folding back, height adjustable, from 20.3 cm (8 in.) to 50.8 cm (20 in.)
- supple seat and back, nylon
- front seating height: from 43.2 cm (17 in.) to 54.6 cm (21<sup>1</sup>/<sub>2</sub> in.)
- seat width: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.)
- safety belt, velcro-type, auto-type
- frame length: 69.8 cm (27 7/8 in.)
- · back spreader bar
- bolt-on push handles

## **Armrests**

- "L"-type armrests, detachable, swingaway, height-adjustable, from 18.4 cm (7<sup>1</sup>/<sub>4</sub> in.) to 23.5 cm (9<sup>1</sup>/<sub>4</sub> in.), short
- · tubular armrests
- straight armrest pads, short, long
- · contoured armrest pads, short, long
- clothing guards, flexible

#### **Footrests**

- 85° footrests, fixed, pointing inwards or tapered, length-adjustable, from 41.3 cm (16<sup>1</sup>/<sub>4</sub> in.) to 51.4 cm (20<sup>1</sup>/<sub>4</sub> in.), in steps proportional to front seating height
- tubular footplate, fixed
- full-width footplate, angle-adjustable
- single calf strap

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- swing-away brakes, standard wheel locks, push-to-lock
- standard forks
- quick-release axles
- spoked rear wheels, standard pressure, 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.)
- spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.)
- rear mag wheels, standard pressure, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, solid tires (KIK), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.),
   15.2 cm (6 in.), 12.7 cm (5 in.), 7.6 cm (3 in.)
- double camber tubes for the following angles:  $0^{\circ}$ ,  $3^{\circ}$ ,  $6^{\circ}$ ,  $9^{\circ}$  or  $12^{\circ}$

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system Seat and back:		
modification of seat width to 48.3 cm (19 in.)		
or 50.8 cm (20 in.)	115.00	N/A
modification of seat depth to 45.7 cm (18 in.),		
48.3 cm (19 in.) or 50.8 cm (20 in.)	58.00	N/A
folding back, height adjustable, from		
20.3 cm (8 in.) to 50.8 cm (20 in.)	N/C	N/A
supple back, tension-adjustable	63.00	98.00
bolt-on push handles	N/C	37.00
back tension bar	N/C	52.00
supple back, nylon	N/C	35.00
supple seat, nylon	N/C	35.00
seat cushion, flat, foam, 5.1 cm (2 in.)	55.00	55.00
seat cushion, flat, foam, 7.6 cm (3 in.)	55.00	55.00
safety belt, velcro-type	N/C	20.00
safety belt, auto-type	N/C	30.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
"L"-type armrests, detachable, swingaway,		
height-adjustable, from 18.4 cm (7 <sup>1</sup> / <sub>4</sub> in.)		
to $23.5 \text{ cm } (9^{1}/_{4} \text{ in.}), \text{ short}$	N/C	53.00
"T"-type armrests, detachable,		
height-adjustable, from 12.7 cm (5 in.) to 20.3 cm (8 in.) or from 20.3 cm (8 in.)		
to 27.9 cm (11 in.), short or long	82.00	94.00
clothing guards, flexible	N/C	14.00
clothing guards, rigid, detachable	59.00	44.00
tubular armrests	N/C	10.00
armrest pads, straight or contoured, short or long	N/C	26.00
Footrests:		
85° footrests, pointing inwards or tapered,		
fixed, length-adjustable, from 41.3 cm (16 <sup>1</sup> / <sub>4</sub> in.)		
to 51.4 cm $(20^{1}/_{4} \text{ in.})$ , in steps proportional		
to front seating height	N/C	N/A
single calf strap	N/C	43.00
double calf strap	53.00	53.00
tubular footplate, fixed	N/C	50.00
full-width footplate, angle-adjustable	N/C	66.00
Wheels and frame		
Types of drive systems:		
handrims with vertical or oblique projections	155.00	
a pair each	155.00	111.00
anodized aluminum handrims, 50.8 cm (20 in.),		111.00
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	33.00
plastic-coated handrims	14/6	33.00
a pair	53.00	
each		59.00
front anti-tip rollers		
a pair	95.00	
each	44.00	48.00
front floor roller	41.00	41.00
Wheel locks:		
standard wheel locks, push-to-lock	N/C	44.00
standard wheel locks, pull-to-lock	32.00	60.00
swing-away brakes	N/C	44.00
wheel lock extensions	22.00	
a pair each	32.00	16.00
each anti-rollback brakes		16.00
a pair	98.00	
each	70.00	93.00
		75.00

Rear axles: quick-release axles axle extension plates for amputee a pair each double camber tubes for the following angles: 0°, 3°, 6°, 9° or 12°  Types of wheels: rear mag wheels, standard pressure, 55.9 cm (22 in.) or 61.0 cm (24 in.) spoked rear wheels, standard pressure or high pressure, 66.0 cm (26 in.) a pair each spoked rear wheels, solid tires (KIK), 61.0 cm (24 in.) spoked rear wheels, solid tires (KIK), 66.0 cm (26 in.) a pair each spoked rear wheels, solid tires (KIK), 66.0 cm (26 in.) a pair each spoked rear wheels, solid tires (KIK), 66.0 cm (26 in.) a pair each spoked rear wheels, solid tires (KIK), 66.0 cm (26 in.) a pair each spoked rear wheels, solid tires (KIK), 66.0 cm (26 in.) a pair each spoked rear wheels, solid tires (KIK), 66.0 cm (26 in.) a pair each spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.) a pair each spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.) a pair each spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.) a pair each spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.) a pair each spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.) a pair each spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.) a pair each spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (26 in.) a pair each	upon ement ponent price)
quick-release axles  Ix pair  Ix pair	33.00
a pair bach bach double camber tubes for the following angles:  December 20, 3°, 6°, 9° or 12°  N/C  Iypes of wheels:  rear mag wheels, standard pressure, 55.9 cm (22 in.) or 61.0 cm (24 in.)  rear mag wheels, solid tires, 55.9 cm (22 in.)  or 61.0 cm (24 in.)  rear wheels, standard pressure, 55.9 cm (22 in.) or 61.0 cm (24 in.)  spoked rear wheels, standard pressure or high pressure, 66.0 cm (26 in.)  a pair  apair  apair  spoked rear wheels, high pressure, 61.0 cm (24 in.)  a pair  spoked rear wheels, solid tires (KIK), 61.0 cm (24 in.)  a pair  spoked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  a pair  apair  spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.)  a pair  spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.)  a pair  spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.)  a pair  spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.)  a pair  spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.)  a pair  nother the following angles:  N/C  spoked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.)  a pair  nother the following angles:  N/C  spoked rear wheels, heavy-duty, standard pressure or high pressure, 66.0 cm (26 in.)  a pair  a pair  nother the following angles:  N/C	53.00
Pryse of wheels:  ear mag wheels, standard pressure, 55.9 cm 22 in.) or 61.0 cm (24 in.)  Protect mag wheels, solid tires, 55.9 cm (22 in.)  or 61.0 cm (24 in.)  or 61.0 cm (24 in.)  or 61.0 cm (24 in.)  proked rear wheels, standard pressure, 55.9 cm  22 in.) or 61.0 cm (24 in.)  N/C  proked rear wheels, standard pressure or high  or essure, 66.0 cm (26 in.)  a pair  pair  poked rear wheels, high pressure, 61.0 cm (24 in.)  poked rear wheels, high pressure, 61.0 cm (24 in.)  poked rear wheels, solid tires (KIK), 61.0 cm (24 in.)  poked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  a pair  poked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.)  a pair  poked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.)  a pair  poked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (26 in.)  a pair  poked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (26 in.)  a pair  poked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (26 in.)  a pair  poked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (26 in.)  a pair  N/C  and  106.00	50.00
ear mag wheels, standard pressure, 55.9 cm  22 in.) or 61.0 cm (24 in.)  ear mag wheels, solid tires, 55.9 cm (22 in.)  or 61.0 cm (24 in.)  poked rear wheels, standard pressure, 55.9 cm  22 in.) or 61.0 cm (24 in.)  poked rear wheels, standard pressure or high  oressure, 66.0 cm (26 in.)  pair  each  poked rear wheels, high pressure, 61.0 cm (24 in.)  pair  each  poked rear wheels, solid tires (KIK), 61.0 cm (24 in.)  poked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  a pair  each  poked rear wheels, heavy-duty, standard pressure or  high pressure, 61.0 cm (24 in.)  a pair  poked rear wheels, heavy-duty, standard pressure or  high pressure, 66.0 cm (26 in.)  a pair  local  poked rear wheels, heavy-duty, standard pressure or  high pressure, 66.0 cm (26 in.)  a pair  local	25.00
or 61.0 cm (24 in.) poked rear wheels, standard pressure, 55.9 cm 22 in.) or 61.0 cm (24 in.) poked rear wheels, standard pressure or high pressure, 66.0 cm (26 in.) pair pair poked rear wheels, high pressure, 61.0 cm (24 in.) poked rear wheels, high pressure, 61.0 cm (24 in.) poked rear wheels, solid tires (KIK), 61.0 cm (24 in.) poked rear wheels, solid tires (KIK), 66.0 cm (26 in.) pair pair pair poked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.) poked rear wheels, heavy-duty, standard pressure or high pressure, 66.0 cm (26 in.) poked rear wheels, heavy-duty, standard pressure or high pressure, 66.0 cm (26 in.) poked rear wheels, heavy-duty, standard pressure or high pressure, 66.0 cm (26 in.)	69.00
22 in.) or 61.0 cm (24 in.) poked rear wheels, standard pressure or high pressure, 66.0 cm (26 in.) pair pair poked rear wheels, high pressure, 61.0 cm (24 in.) pair poked rear wheels, high pressure, 61.0 cm (24 in.) poked rear wheels, solid tires (KIK), 61.0 cm (24 in.) poked rear wheels, solid tires (KIK), 66.0 cm (26 in.) pair pair poked rear wheels, heavy-duty, standard pressure or high pressure, 61.0 cm (24 in.) poked rear wheels, heavy-duty, standard pressure or high pressure, 66.0 cm (26 in.) poked rear wheels, heavy-duty, standard pressure or high pressure, 66.0 cm (26 in.) poked rear wheels, heavy-duty, standard pressure or high pressure, 66.0 cm (26 in.)	42.00
pair 82.00  ach  poked rear wheels, high pressure, 61.0 cm (24 in.)  pair N/C  ach  poked rear wheels, solid tires (KIK), 61.0 cm (24 in.)  pair 82.00  ach  poked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  pair 82.00  ach  poked rear wheels, heavy-duty, standard pressure or igh pressure, 61.0 cm (24 in.)  pair N/C  ach  poked rear wheels, heavy-duty, standard pressure or igh pressure, 66.0 cm (26 in.)  pair N/C  ach  poked rear wheels, heavy-duty, standard pressure or igh pressure, 66.0 cm (26 in.)  pair 106.00	83.00
pair N/C ach poked rear wheels, solid tires (KIK), 61.0 cm (24 in.) poked rear wheels, solid tires (KIK), 66.0 cm (26 in.) pair 82.00 ach poked rear wheels, heavy-duty, standard pressure or igh pressure, 61.0 cm (24 in.) pair N/C ach poked rear wheels, heavy-duty, standard pressure or igh pressure, 66.0 cm (26 in.) pair 106.00	83.00
poked rear wheels, solid tires (KIK), 61.0 cm (24 in.)  poked rear wheels, solid tires (KIK), 66.0 cm (26 in.)  pair  ach  poked rear wheels, heavy-duty, standard pressure or  igh pressure, 61.0 cm (24 in.)  pair  N/C  ach  poked rear wheels, heavy-duty, standard pressure or  igh pressure, 66.0 cm (26 in.)  pair  106.00	
pair 82.00  ach poked rear wheels, heavy-duty, standard pressure or igh pressure, 61.0 cm (24 in.) pair N/C  ach poked rear wheels, heavy-duty, standard pressure or igh pressure, 66.0 cm (26 in.) pair 106.00	83.00 83.00
igh pressure, 61.0 cm (24 in.)  pair  N/C  ach  poked rear wheels, heavy-duty, standard pressure or  igh pressure, 66.0 cm (26 in.)  pair  106.00	83.00
poked rear wheels, heavy-duty, standard pressure or igh pressure, 66.0 cm (26 in.) pair 106.00	
pair 106.00	95.00
neavy-duty rear wheels, solid tires, 61.0 cm (24 in.) or 66.0 cm (26 in.)	95.00
pair 106.00 ach	95.00
ont wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm	23.00
	39.00
irless inserts for rear wheels pair 99.00	
ach irless inserts for front wheels 95.00	N/A N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
spoke guards * a pair each	82.00	41.00
quick-release axles with lever mechanism * a pair each	76.00	53.00

### DEVICE FROM: EVEREST & JENNINGS CANADA LTD.

**PRICE** 

## LIGHTWEIGHT MANUAL WHEEL CHAIR, "CHAMPION 3000 PEDIATRIC" MODEL

\$1 265.00

## **Basic Component(s)**

## **Body support system**

- folding back, height adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.), from 33.0 cm (13 in.) to 40.6 cm (16 in.) and angle-adjustable, from - 10° to + 20°
- seat width: from 25.4 cm (10 in.) to 35.6 cm (14 in.)
- seating height: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: 30.5 cm (12 in.), 32.4 cm (12<sup>3</sup>/<sub>4</sub> in.), 34.3 cm (13<sup>1</sup>/<sub>2</sub> in.), 36.2 cm (14<sup>1</sup>/<sub>4</sub> in.), 38.1 cm (15 in.)
- adjustable frame, allowing seat depths of 30.5 cm (12 in.) to 38.1 cm (15 in.)
- · supple back and seat, nylon
- safety belt, auto-type
- push handles

### **Armrests**

- "L"-type armrests, detachable, swingaway, height-adjustable, from 10.2 cm (4 in.) to 17.8 cm (7 in.), short
- clothing guards, flexible
- clothing guards, rigid, fixed, straight
- · tubular armrests

- 75° footrests, parallel, fixed, length-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- full-width footplate, fixed
- single calf strap

- anodized aluminum handrims
- standard wheel locks, push-to-lock
- · short forks, high forks
- quick-release axles
- rear mag wheels, standard pressure,
   50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure,
   50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, high pressure, 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 12.7 cm (5 in.)
- rear wheel camber, 0°, 3°

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
supple back, tension-adjustable	73.00	145.00
folding back, height adjustable, from 20.3 cm		
(8 in.) to 30.5 cm (12 in.) or from 33.0 cm (13 in.)		
to 40.6 cm (16 in.) and angle-adjustable		
from - $10^{\circ}$ to + $20^{\circ}$	N/C	N/A
modification of back height, from 43.2 cm		37/1
(17 in.) to 50.8 cm (20 in.)	52.00	N/A
modification of seat width to 38.1 cm (15 in.)	110.00	37/4
or 40.6 cm (16 in.)	118.00	N/A
modification of seat depth to 25.4 cm (10 in.)	64.00	NT/A
or 27.9 cm (11 in.)	64.00	N/A
adjustable frame allowing seat depths of 30.5 cm	N/C	N/A
(12 in.) to 38.1 cm (15 in.)	N/C N/C	72.00
supple back, nylon supple seat, nylon	N/C N/C	72.00
pack, ballistic nylon	66.00	138.00
stabilizer bar	93.00	93.00
oush handles	N/C	24.00
bolt-on push handles	34.00	41.00
growth kit	N/A	375.00
seat cushion, flat, foam, 5.1 cm (2 in.)	58.00	58.00
seat cushion, flat, foam, 7.6 cm (3 in.)	58.00	58.00
seat cushion, flat, foam, 10.2 cm (4 in.)	58.00	58.00
safety belt, auto-type	N/C	28.00
safety belt, airplane-type	30.00	58.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
"L"-type armrests, detachable, swingaway,		
height-adjustable, from 10.2 cm (4 in.)		
to 17.8 cm (7 in.), short	N/C	68.00
tubular armrests	N/C	6.00
straight armrest pads, short	12.00	
a pair	13.00	12.00
each		13.00
clothing guards, rigid, detachable, straight		
or fender-style	56.00	
i pair ach	30.00	75.00
elothing guards, flexible	N/C	21.00
clothing guards, rigid, fixed, straight	N/C	47.00
Journa Bundo, 11gra, 11Aou, struight	10/0	77.00
Footrests:		
75° footrests, parallel, fixed, length-adjustable,		
from 20.3 cm (8 in.) to 33.0 cm (13 in.)	N/C	N/A
ull-width footplate, fixed	N/C	95.00
ull-width footplate, flip-back	55.00	150.00
ull-width footplate, raised, angle-adjustable		
and depth-adjustable	121.00	216.00
olding footplates, raised, angle-adjustable		
and depth-adjustable	120.00	
pair	120.00	155.00
ach	N/C	155.00
ingle calf strap louble calf strap	23.00	25.00 48.00
ront floor roller	31.00	31.00
nodification of footrest length	87.00	N/A
nouncation of footiest length	87.00	11/14
Wheels and frame		
Types of drive systems:		
nodized aluminum handrims	N/C	45.00
plastic-coated handrims		
pair	68.00	
each		79.00
non-slip handrims	0.5.00	
pair	86.00	00.00
ach		88.00
andrims with oblique or vertical projections	158.00	
pair	158.00	124.00
ach ombined handrims		124.00
pair	86.00	
ach	80.00	88.00
ront anti-tip rollers		00.00
pair	88.00	
ach	00.00	44.00
ane holder	43.00	43.00
ine notice	45.00	45.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks:		
standard wheel locks, push-to-lock swing-away brakes	N/C	57.00
n pair	30.00	<b>72</b> 00
each standard wheel locks, pull-to-lock		72.00
n pair	30.00	
each wheel lock extensions		72.00
a pair	26.00	
each		13.00
anti-rollback brakes a pair	100.00	
each		107.00
Types of forks:		
short forks	N/C	60.00
nigh forks	N/C	50.00
ong fork stems fork-locking mechanisms	95.00	N/A
ı pair	88.00	400.00
each		100.00
Rear axles:		
quick-release axles ixle extension plates for amputee	N/C	51.00
a pair	62.00	
each	N/C	93.00
rear wheel camber, 0° or 3° rear wheel camber, 6°, 9° or 12°	N/C 45.00	150.00 195.00
Wheels and frame		2,2,0
Types of wheels:		
rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.),		
51.0 cm (24 in.)	N/C	118.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	125.00
spoked rear wheels, heavy-duty, standard pressure, 61.0 cm (24 in.)		
ressure, 61.0 cm (24 m.) r pair	30.00	
each		140.00
spoked rear wheels, high pressure, 55.9 cm 22 in.) or 61.0 cm (24 in.)	N/C	130.00
poked rear wheels, heavy-duty, high	100	150.00
oressure, 61.0 cm (24 in.) a pair	30.00	
	20.00	

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, solid tires, 7.6 cm (3 in.)		
a pair	44.00	
each	3719	42.00
front wheels, solid tires, 12.7 cm (5 in.)	N/C	20.00
front wheels, inner tube, 15.2 cm		
(6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	44.00	
a pair each	44.00	42.00
front wheels, semi-pneumatic tires, 12.7 cm		72.00
(5 in.) X 5.1 cm (2 in.)		
a pair	84.00	
each		62.00
front wheels, semi-pneumatic tires, 15.2 cm		
(6 in.) X 2.5 cm (1 in.)	44.00	
a pair	44.00	12.00
each airless inserts for rear wheels		42.00
a pair	60.00	
each	00.00	N/A
puncture-resistant rear tires		14/21
a pair	55.00	
each		N/A
Component(s) under Special Consideration		
spoke guards *		
a pair	72.00	
each		36.00
quick-release axles with lever mechanism *		
a pair	70.00	o= 6=
each		87.00
§3. Power wheel chairs		

## DEVICE FROM: EVEREST & JENNINGS CANADA LTD.

**PRICE** 

# POWER WHEEL CHAIR "QUEST" MODEL

\$4 025.00

# Basic Component(s)

# **Body support system**

- supple seat and back, nylon
- seat width: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.)
- back height: from 41.9 cm  $(16^{1}/_{2} \text{ in.})$  to 49.5 cm  $(19^{1}/_{2} \text{ in.})$
- seating height: from 44.5 cm  $(17^{1}/_{2} \text{ in.})$  to 49.5 cm  $(19^{1}/_{2} \text{ in.})$
- · push handles
- safety belt, auto-type

#### Armrests

- "U"-type armrests, detachable, fixed height of 22.9 cm (9 in.), short, long
- "U"-type armrests, detachable and height-adjustable, from 21.6 cm (8½ in.) to 34.3 cm (13½ in.), short, long
- "U"-type armrests, detachable, flip-back and fixed height of 22.9 cm (9 in.), short, long
- "U"-type armrests, detachable, flip-back and height-adjustable, from 21.6 cm (8½ in.) to 34.3 cm (13½ in.), short, long
- straight armrest pads, short, long
- rigid clothing guards

#### **Footrests**

- 70° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- 70° footrests, "V"-shaped, detachable, swingaway and length-adjustable, from 43.2 cm (17 in.) to 50.8 cm (20 in.)
- · padded calfrests
- folding footplates
- · folding footplates, oversized
- heel loops, length-adjustable

# **Drive systems**

- remote hand control with built-in programmable DL50 modulator
- · battery charger
- battery box, group 22, group U1toggle switch
- ball extension
- programmable PG8 controller (if joystick control for separate controller)
- battery charge display
- · Framco motors
- side bracket for joystick control
- swivel side bracket for joystick control
- front anti-tip rollers

- reflector strips or reflectors
- tie-down points for adapted transport
- · standard forks
- rear wheels, inner tube tires, 30.5 cm (12 in.) X 5.7 cm ( $2^{1}/_{4}$  in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 4.4 cm (1<sup>3</sup>/<sub>4</sub> in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) X 4.4 cm  $(1^{3}/_{4}$  in.)
- front wheel rims, rear wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, contoured	145.00	145.00
fixed headrest mounting	93.00	93.00
articulated headrest mounting	155.00	155.00
supple back, tension-adjustable	73.00	145.00
supple back, nylon	N/C	72.00
supple seat, nylon	N/C	72.00
rigid seat, flat	80.00	80.00
nodification of seat width to 50.8 cm (20 in.)	140.00	N/A
nodification of seat depth to 45.7 cm (18 in.)	105.00	N/A
eat cushion, flat, foam, 5.1 cm (2 in.)	58.00	58.00
eat cushion, flat, foam, 7.6 cm (3 in.)	58.00	58.00
eat cushion, flat, foam, 10.2 cm (4 in.)	58.00	58.00
oush handles	N/C	N/A
afety belt, auto-type	N/C	28.00
afety belt, airplane-type	30.00	58.00
Armrests: "U"-type armrests, detachable, flip-back and height-adjustable, from 21.6 cm (8½ in.) to 34.3 cm (13½ in.), short or long "U"-type armrests, detachable, fixed height of 22.9 cm (9 in.), short "U"-type armrests, detachable, fixed height of 22.9 cm (9 in.), long "U"-type armrests, detachable and height-adjustable, from 21.6 cm (8½ in.) to 34.3 cm (13½ in.), short or long "U"-type armrests, detachable, flip-back and fixed height of 22.9 cm (9 in.), short "U"-type armrests, detachable, flip-back and fixed height of 22.9 cm (9 in.), short "U"-type armrests, detachable, flip-back and fixed height of 22.9 cm (9 in.), long modification of armrest height armrest pads, straight, short or long rigid clothing guards	N/C N/C N/C N/C N/C N/C N/C N/C N/C 88.00 N/C N/C	118.00 79.00 75.00 118.00 79.00 75.00 N/A 13.00 20.00
Footrests: 70° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)	N/C	105.00
70° footrests, "V"-shaped, detachable, swingaway,	14/0	103.00
ength-adjustable, from 43.2 cm (17 in.) to 50.8 cm (20 in.) elevating legrests, detachable, swingaway and ength-adjustable, from 40.6 cm (16 in.) to 50.8 cm (20 in.)	N/C	105.00
a pair each	160.00	185.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
padded calfrests, straight	N/C	21.00
single calf strap	21.00	21.00
double calf strap	48.00	48.00
folding footplates	N/C	25.00
folding footplates, angle-adjustable		
a pair	112.00	
each		81.00
folding footplates, oversized	N/C	26.00
heel loops, length-adjustable	N/C	12.00
modification of footrest length	88.00	N/A
front impact guard with rollers	30.00	11/11
a pair	16.00	
each	10.00	8.00
Wheels and frame		0.00
Types of drive systems:		
joystick control with integrated programmable		4 40 7 00
DL50 controller	N/C	1 495.00
standard joystick control with separate,		
programmable PG8 controller	365.00	695.00
pattery charge display	N/C	N/A
pattery charger	N/C	350.00
pattery boxes, group 22	N/C	177.00
battery boxes, group U1	N/C	260.00
adapted controls interface	1 150.00	1 150.00
separate display for adapted controls	199.00	199.00
toggle switch	N/C	N/A
stick extension	18.00	21.00
pall extension	N/C	3.00
'T"-type extension	39.00	42.00
side bracket for joystick control	N/C	71.00
swivel side bracket for joystick control	N/C	295.00
midline bracket for joystick control	85.00	380.00
PG8 programmable controller (if joystick control		
for separate controller)	N/C	1 650.00
Framco motors	N/C	845.00
front anti-tip rollers	N/C	38.00
reflector strips or reflectors	N/C	N/A
tie-down points for adapted transport	N/C	N/A
Types of wheels:		
standard forks	N/C	34.00
suspension forks		
a pair	138.00	
each		103.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
rear wheels, inner tube tires,		
$30.5 \text{ cm} (12 \text{ in.}) \text{ X } 5.7 \text{ cm} (2^{1}/_{4} \text{ in.})$	N/C	105.00
front wheels, semi-pneumatic tires,		
20.3 cm (8 in.) X $4.4$ cm ( $1^{3}/_{4}$ in.)	N/C	62.00
front wheels, inner tube tires,		
20.3 cm (8 in.) X 4.4 cm $(1^{3}/_{4} in.)$	N/C	62.00
front wheel rims	N/C	50.00
rear wheel rims	N/C	42.00
airless inserts for rear wheels		
a pair	105.00	
each		N/A
Rebuilt parts		
		Maximum pric
joystick control with integrated controller		785.00
Framco motor		575.00
battery charger		240.00

# DEVICE FROM: EVEREST & JENNINGS CANADA LTD.

#### **PRICE**

520.00

785.00

# POWER WHEEL CHAIR, "SABRE LTD" MODEL

joystick control with battery charge display

\$3 575.00

### **Basic Component(s)**

#### **Body support system**

- supple back, nylon
- · rigid seat, flat

Z-51 controller

- seat width: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- back height: from 38.1 cm (15 in.) to 48.3 cm (19 in.)
- seat and back structure; angle-adjustable back
- seating height:  $44.5 \text{ cm} (17^{1}/_{2} \text{ in.}), 49.5 \text{ cm} (19^{1}/_{2} \text{ in.})$
- push handles
- safety belt, auto-type

### Armrests

- "U"-type armrests, detachable and height-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.), short, long
- "U"-type armrests, flip-back and height-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.), short, long
- "U"-type armrests, detachable, fixed height of 22.9 cm (9 in.), short, long
- contoured armrest pads, short, long
- · straight armrest pads, short, long
- rigid clothing guards

#### **Footrests**

- detachable footrests, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- "V"-shaped footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- padded calfrests, straight
- · folding footplates, standard or aluminum
- heel loops, length-adjustable

### **Drive systems**

- joystick control with integrated controller
- · battery charger
- battery box, group 22
- ball extension
- · toggle switch
- programmable controller (if joystick control for separate controller)
- standard motors, G.T. motors, heavy-duty motors
- side bracket for joystick control
- swivel side bracket for joystick control
- · bracket for adapted controls
- front anti-tip rollers

- · standard forks
- tie-down points for adapted transport
- rear wheels, inner tube tires, 35.6 cm (14 in.) X 6.4 cm (2<sup>1</sup>/<sub>2</sub> in.), 35.6 cm (14 in.) X 8.9 cm (3<sup>1</sup>/<sub>2</sub> in.), 33.0 cm (13 in.) X 10.2 cm (4 in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 4.4 cm (1<sup>3</sup>/<sub>4</sub> in.)
- front wheels, inner tube tires,
   20.3 cm (8 in.) X 4.4 cm (1<sup>3</sup>/<sub>4</sub> in.)
- rear wheel rims, for 35.6 cm (14 in.) X 6.4 cm (2<sup>1</sup>/<sub>2</sub> in.), 35.6 cm (14 in.) X 8.9 cm (3<sup>1</sup>/<sub>2</sub> in.) and 33.0 cm (13 in.) X 10.2 cm (4 in.) wheels
- · front wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, contoured	145.00	145.00
fixed headrest mounting	93.00	93.00
articulated headrest mounting	155.00	155.00
supple back, tension-adjustable	73.00	145.00
supple back, nylon	N/C	72.00
padded back, contoured, fabric	288.00	360.00
seat and back structure; angle-adjustable back	N/C	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
modification of seat width to		
48.3 cm (19 in.) or 50.8 cm (20 in.)	250.00	N/A
rigid seat, flat	N/C	N/A
padded seat, contoured, fabric	280.00	350.00
seat cushion, flat, foam, 5.1 cm (2 in.)	58.00	58.00
seat cushion, flat, foam, 7.6 cm (3 in.)	58.00	58.00
seat cushion, flat, foam, 10.2 cm (4 in.)	58.00	58.00
push handles	N/C	N/A
safety belt, auto-type	N/C	28.00
safety belt, airplane-type	30.00	58.00
Armrests:		
'U"-type armrests, flip-back and height-adjustable,		
from 20.3 cm (8 in.) to 30.5 cm (12 in.), short or long	N/C	118.00
'U"-type armrests, detachable and height-adjustable,		
from 20.3 cm (8 in.) to 30.5 cm (12 in.), short or long	N/C	118.00
'U"-type armrests, detachable, fixed height of		
22.9 cm (9 in.), short	N/C	52.00
'U"-type armrests, detachable, fixed height of		
22.9 cm (9 in.), long	N/C	58.00
armrest pads, contoured, short or long	N/C	27.00
armrest pads, straight, short or long	N/C	13.00
modification of armrest height	88.00	N/A
rigid clothing guards	N/C	20.00
rgid Clothing guards	14/0	20.00
Footrests:		
detachable footrests, swingaway and length-adjustable,	N/C	110.00
from 35.6 cm (14 in.) to 45.7 cm (18 in.)	N/C	118.00
'V"-shaped footrests, detachable, swingaway and		
ength-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)	N/C	118.00
elevating legrests, detachable, swingaway and		
ength-adjustable, from 35.6 cm (14 in.) to 58.4 cm (23 in.)		
ı pair	152.00	
each		194.00
padded calfrests, straight	N/C	21.00
single calf strap	21.00	21.00
double calf strap	48.00	48.00
folding footplates, standard or aluminum	N/C	25.00
olding footplates, angle-adjustable	- " -	
a pair	112.00	
each	112.00	81.00
Folding footplates, oversized		01.00
olding rootpiates, oversized	14.00	
rach	17.00	32.00
		32.00
oversized footplates, plastic coated	20.00	
n pair	30.00	40.00
each	N/G	40.00
neel loops, length-adjustable	N/C	12.00
nodification of footrest length	88.00	N/A
ront impact guard with rollers		
ı pair	16.00	
each		8.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems:		
joystick control with integrated controller	N/C	1 430.00
standard joystick control for separate controller	395.00	650.00
battery charger	N/C	350.00
battery box, group 22	N/C	225.00
separate display for adapted controls, LED	795.00	795.00
separate display for adapted controls, LCD	1 250.00	1 250.00
pracket for adapted controls	N/C	N/A
Adapted controls:		
proportional chin-control (mini-control)	1 120.00	1 120.00
proportional head control	1 575.00	1 575.00
midline proportional control (mini commande)	895.00	895.00
preath control	1 335.00	1 335.00
short throw switch chin control (Tash)	725.00	725.00
head control, micro-switch	1 375.00	1 375.00
short throw switch midline control (Tash)	550.00	550.00
switch foot control	725.00	725.00
switch midline control, heavy-duty	425.00	425.00
side switch control, heavy-duty	350.00	350.00
disc control, 5.1 cm (2 in.), with centre switch	330.00	330.00
Penta control (5 switches on 5.1 cm [2 in] diameter disc), bracketle		310.00
interface (5-in-1) (used with Mono switch)	200.00	200.00
proportional mini-control	665.00	665.00
electrical interference filter for other than E & J components	20.00	20.00
Short-throw joystick template:		
35% - circular	23.00	23.00
50% - circular	23.00	23.00
60% - circular	23.00	23.00
75% - circular	23.00	23.00
50% X 35% - eliptical	23.00	23.00
75% X 35% - eliptical	23.00	23.00
100% X 35% - eliptical	23.00	23.00
75% X 50% - eliptical	23.00	23.00
100% X 50% - eliptical	23.00	23.00
100% X 75% - eliptical	23.00	23.00
35% X 50% - eliptical	23.00	23.00
35% X 75% - eliptical	23.00	23.00
35% X 100% - eliptical	23.00	23.00
50% X 75% - eliptical	23.00	23.00
50% X 100% - eliptical	23.00	23.00
75% X 100% - eliptical	23.00	23.00
cross-shaped model	23.00	23.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Switch (with adapter):		
micro-lite, flexible, 22.9 cm (9 in.)	260.00	260.00
micro-lite, flexible, 30.5 cm (12 in.)	260.00	260.00
flexible, 12.7 cm (5 in.), adjustable to 22.9 cm (9 in.)	260.00	260.00
flexible, 17.8 cm (7 in.), adjustable to 30.5 cm (12 in.)	260.00	260.00
flexible, 12.7 cm (5 in.), adjustable to 30.5 cm (12 in.),	270.00	270.00
for head control	270.00	270.00
flexible, 17.8 cm (7 in.), adjustable to 30.5 cm (12 in.),		
for head control	270.00	270.00
micro-lite, 30.5 cm (12 in.), for head control	270.00	270.00
Various switch accessories:		
disc switch (mono) for 5-in-1 box	190.00	190.00
pressure switch (mono), 17.8 cm (7 in.), for 5-in-1 box	150.00	150.00
flexible switch (mono), 12.7 cm (5 in.), for 5-in-1 box	150.00	150.00
flexible switch (mono), 17.8 cm (7 in.), for 5-in-1 box	150.00	150.00
micro-switch (mono), for 5-in-1 box	142.00	142.00
relay box for ECU	200.00	200.00
switch cable (5 positions)	90.00	90.00
interface cable for E & J	215.00	215.00
"U"-shaped bracket for disc	70.00	70.00
flexible bracket, 1.6 cm ( $^{1}/_{2}$ in.), for switch adjustment stem	80.00	80.00
complete bracket and collar for disc switch	135.00	135.00
toggle switch	N/C	N/A
stick extension	18.00	21.00
ball extension	N/C	3.00
"T"-type extension	39.00	42.00
side bracket for joystick control	N/C	71.00
swivel side bracket for joystick control	N/C	295.00
midline bracket for joystick control	85.00	380.00
programmable controller (if joystick control	83.00	300.00
for separate controller)	N/C	1 505.00
	N/C N/C	
standard motors		965.00
G.T. motors	N/C	965.00
heavy-duty motors	N/C	965.00
front anti-tip rollers	N/C	38.00
ie-down points for adapted transport	N/C	16.00
auxiliary brakes, manual	60.00	
a pair	68.00	<b>70.00</b>
each		50.00
Types of wheels:		
standard forks	N/C	34.00
suspension forks		
a pair	138.00	
each		103.00
rear wheels, inner tube tires, 35.6 cm (14 in.) X 6.4 cm ( $2^{1}/_{2}$ in.)	N/C	110.00
rear wheels, inner tube tires, 35.6 cm (14 in.) X 8.9 cm ( $3\frac{1}{2}$ in.)	N/C	195.00
rear wheels, inner tube tires, heavy-duty,	11/0	193.00
	N/C	205.00
33.0 cm (13 in.) X 10.2 cm (4 in.) front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 4.4 cm ( $1^{3}$ / <sub>4</sub> in		
from wheels, seini-pheumatic tires, 20.3 cm (8 in.) $\lambda$ 4.4 cm (1 $^{-7}/_4$ in	.) N/C	62.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, inner tube tires, 20.3 cm (8 in.) X 4.4 cm (1 <sup>3</sup> / <sub>4</sub> in.)	N/C	62.00
front wheel rims	N/C	N/A
rear wheel rims for 35.6 cm (14 in.) X 8.9 cm ( $3^{1}/_{2}$ in.) wheels airless inserts for 35.6 cm (14 in.) X 8.9 cm ( $3^{1}/_{2}$ in.) wheels	N/C	62.00
pair	150.00	
each airless inserts for 35.6 cm (14 in.) X 6.4 cm (2 <sup>1</sup> / <sub>2</sub> in.) rear wheels a pair	105.00	N/A
each airless inserts for 33.0 cm (13 in.) X 10.2 cm (4 in.) rear wheels	103.00	N/A
ı pair ach	180.00	N/A
rear wheel rims, for 35.6 cm (14 in.) X 6.4 cm ( $2^{1}/_{2}$ in.) wheels	N/C	47.00
rear wheel rims, for 33.0 cm (13 in.) X 10.2 cm (4 in.) wheels	N/C	100.00

# Rebuilt parts

controller with hand control	775.00
Framco motor, standard	695.00
Framco G.T. motor	695.00
Framco motor, heavy-duty	695.00
battery charger	240.00
joystick control with battery charge display, Curtis or P & G	495.00
Z-51 controller	775.00

### DEVICE FROM: EVEREST & JENNINGS CANADA LTD.

**PRICE** 

Maximum price

# POWER WHEEL CHAIR, "LANCER 2000" MODEL

\$4 625.00

## Basic Component(s)

### **Body support system**

- supple back, nylon
- back height: from 36.8 cm  $(14^{1}/_{2} \text{ in.})$  to 55.9 cm (22 in.)
- seating height: from 44.5 cm  $(17^{1}/_{2} \text{ in.})$  to 53.3 cm (21 in.)
- seat width, with standard or extra-long structure: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- seat width, with reinforced structure: 55.9 cm (22 in.), 58.4 cm (23 in.), 61.0 cm (24 in.)
- seat depth, with standard or reinforced structure: from 38.1 cm (15 in.) to 48.3 cm (19 in.)
- seat depth, with extra-long structure: 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.)
- · rigid seat, flat
- push handles
- back handlebar
- · safety belt, auto-type

#### Armrests

- "U"-type armrests, detachable, fixed height of 22.9 cm (9 in.), short, long
- "U"-type armrests, detachable and height-adjustable, from 22.9 cm (9 in.) to 30.5 cm (12 in.), short, long
- "U"-type armrests, detachable, flip-back and height-adjustable, from 21.6 cm (8½ in.) to 34.3 cm (13½ in.), short, long
- straight armrest pads, short, long
- contoured armrest pads, short, long
- rigid clothing guards

#### **Footrests**

- detachable footrests, swingaway and length-adjustable, from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- "V"-shaped footrests, detachable, swingaway and length-adjustable, from 38.1 cm (15 in.) to 48.3 cm (19 in.)
- folding footplates, standard
- folding footplates, aluminum, short, long
- padded calfrests, straight
- heel loops, length-adjustable

### **Drive system**

- · standard joystick control
- battery charger
- battery charge display
- battery boxes, group 22, group 24
- ball extension
- programmable controller
- standard motors, G.T. motors, heavy-duty motors
- side bracket for joystick control
- swivel side bracket for joystick control
- front anti-tip rollers
- adapted control bracket

- reflector strips
- standard forks
- tie-down points for adapted transport
- rear wheels, inner tube tires, 35.6 cm (14 in.) X 8.9 cm ( $3^{1}/_{2}$  in.)
- rear wheels, heavy-duty, inner tube tires, 33.0 cm (13 in.) X 10.2 cm (4 in.)
- elastomer rear wheel suspension
- front wheels, inner tube tires, 20.3 cm (8 in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) X 5.1 cm (2 in.)
- adjustment of centre of gravity from base
- · rear wheel rims, steel
- rear wheel rims, for 33.0 cm (13 in.) X 10.2 cm (4 in.) wheels
- front wheel rims, plastic
- front wheel rims, for 22.9 cm (9 in.) wheels

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, contoured, fabric	145.00	145.00
fixed headrest mounting	93.00	93.00
articulated headrest mounting	155.00	155.00
supple back, nylon	N/C	72.00
supple back, tension-adjustable	73.00	145.00
padded back, contoured, fabric	288.00	360.00
rigid seat, flat	N/C	N/A
seat/back structure; back, angle-adjustable,		
from $-5^{\circ}$ to $+15^{\circ}$	595.00	N/A
reinforced seat/back structure, fixed-angle back,		
width of 55.9 cm (22 in.), 58.4 cm (23 in.) and	4 00 7 00	37/1
51.0 cm (24 in.)	1 025.00	N/A
seat/back structure for depths of 48.3 cm (19 in.),		
50.8 cm (20 in.) and 53.3 cm (21 in.), with back	600.00	37/4
angle-adjustable, from -5° to + 15°	690.00	N/A
padded seat, contoured, fabric	280.00	350.00
seat cushion, flat, foam, 5.1 cm (2 in.)	58.00	58.00
seat cushion, flat, foam, 7.6 cm (3 in.)	58.00	58.00
seat cushion, flat, foam, 10.2 cm (4 in.)	58.00	58.00
safety belt, auto-type	N/C	28.00
safety belt, airplane-type	30.00	58.00
push handles	N/C	5.00
oack handlebar	N/C	N/A
Armrests:		
"U"-type armrests, detachable, fixed height	N/C	52.00
of 22.9 cm (9 in.), short	N/C	52.00
"U"-type armrests, detachable, fixed height	N/C	<b>50.00</b>
of 22.9 cm (9 in.), long	N/C	58.00
"U"-type armrests, detachable and height-adjustable, from 22.9 cm (9 in.) to 30.5 cm (12 in.), short	N/C	118.00
	N/C	118.00
'U"-type armrests, detachable and height-adjustable, from 22.9 cm (9 in.) to 30.5 cm (12 in.), long	N/C	118.00
'U"-type armrests, detachable, flip-back and	IN/C	118.00
neight-adjustable, from 21.6 cm ( $8^{1}/_{2}$ in.) to	NI/C	110 00
34.3 cm (13½ in.), short or long	N/C	118.00
armrest pads, straight, short or long	N/C	13.00
armrest pads, contoured, short or long	N/C	27.00
modification of armrest height	88.00 N/C	N/A
rigid clothing guards	N/C	20.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
detachable footrests, swingaway and length-adjustable,		
from 35.6 cm (14 in.) to 45.7 cm (18 in.) "V"-shaped footrests, detachable, swingaway and	N/C	118.00
length-adjustable, from 38.1 cm (15 in.) to 48.3 cm (19 in.) elevating legrests, detachable, swingaway and	N/C	118.00
length-adjustable, from 45.7 cm (18 in.) to 58.4 cm (23 in.)		
a pair	152.00	
each		194.00
padded calfrests, straight	N/C	21.00
ingle calf strap	21.00	21.00
louble calf strap	48.00	48.00
olding footplates, standard	N/C	25.00
olding footplates, oversized		
i pair	14.00	
each	10	32.00
oversized footplates, plastic-coated		32.00
a pair	30.00	
each	30.00	40.00
folding footplates, aluminum, short or long	N/C	25.00
olding footplates, angle-adjustable	IV/C	23.00
oldring rootprates, angre-adjustable 1 pair	112.00	
each	112.00	81.00
	N/C	12.00
neel loops, length-adjustable nodification of footrest length	88.00	N/A
	88.00	IN/A
Front impact guard	16.00	
n pair	16.00	0.00
each		8.00
Wheels and frame Types of drive systems:		
	N/C	650.00
standard joystick control	N/C N/C	
pattery charge display		N/A 350.00
pattery charger	N/C	
pattery boxes ,group 22	N/C	225.00
pattery boxes, group 24	N/C	171.00
eparate display for adapted controls, LED	795.00	795.00
eparate display for adapted controls, LCD	1 250.00	1 250.00
Adapted controls: Merlin		
proportional chin-control (mini-control)	1 120.00	1 120.00
proportional head control	1 575.00	1 575.00
proportional midline control (mini-control)	895.00	895.00
preath control	1 335.00	1 335.00
hort throw switch chin control (Tash)	725.00	725.00
ead control, micro-switch	1 375.00	1 375.00
hort throw switch central control (Tash)	550.00	550.00
witch foot control	725.00	725.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
switch central control, heavy-duty	425.00	425.00
side switch control, heavy-duty	350.00	350.00
disc control, 5.1 cm (2 in.), with central switch	330.00	330.00
Penta control (5 switches on 5.1 cm [2 in.]		
liameter disc), bracketless	310.00	310.00
nterface (5-in-1) (used with Mono switch)	200.00	200.00
proportional mini control	665.00	665.00
electrical interference filter for other		
han E & J components	20.00	20.00
Short-throw joystick template :		
35% - round	23.00	23.00
50% - round	23.00	23.00
60% - round	23.00	23.00
75% - round	23.00	23.00
50% X 35% - eliptical	23.00	23.00
75% X 35% - eliptical	23.00	23.00
100% X 35% - eliptical	23.00	23.00
75% X 50% - eliptical	23.00	23.00
00% X 50% - eliptical	23.00	23.00
100% X 75% - eliptical	23.00	23.00
35% X 50% - eliptical	23.00	23.00
35% X 75% - eliptical	23.00	23.00
35% X 100% - eliptical	23.00	23.00
50% X 75% - eliptical	23.00	23.00
50% X 100% - eliptical	23.00	23.00
75% X 100% - eliptical	23.00	23.00
cross-shaped model	23.00	23.00
Switch (with adapter):		
nicro-lite, flexible, 22.9 cm (9 in.)	260.00	260.00
nicro-lite, flexible, 30.5 cm (12 in.)	260.00	260.00
lexible, 12.7 cm (5 in.), adjustable		
o 22.9 cm (9 in.)	260.00	260.00
lexible, 17.8 cm (7 in.), adjustable		
o 30.5 cm (12 in.)	260.00	260.00
Texible, 12.7 cm (5 in.), adjustable		
o 30.5 cm (12 in.), for head control	270.00	270.00
lexible, 17.8 cm (7 in.), adjustable		
o 30.5 cm (12 in.), for head control	270.00	270.00
nicro-lite, 30.5 cm (12 in.), for head control	270.00	270.00
Various switch accessories:		
lisc switch (mono), for 5-in-1 box	190.00	190.00
pressure switch (mono), 17.8 cm (7 in.), for 5-in-1 box	150.00	150.00
lexible switch (mono), 12.7 cm (5 in.), for 5-in-1 box	150.00	150.00
lexible switch (mono), 17.8 cm (7 in.), for 5-in-1 box	150.00	150.00
nicro-switch (mono), for 5-in-1 box	142.00	142.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
relay box for ECU	200.00	200.00
switch cable (5 positions)	90.00	90.00
interface cable for E & J	215.00	215.00
"U"-shaped bracket for disc	70.00	70.00
lexible bracket, 1.6 cm ( $\frac{1}{2}$ in.), for switch adjustment stem	80.00	80.00
complete bracket and collar for disc switch	135.00	135.00
stick extension	18.00	21.00
T"-type extension	39.00	42.00
pall extension	N/C	3.00
ide bracket for joystick control	N/C	71.00
wivel side bracket for joystick control	N/C	295.00
midline bracket for joystick control	85.00	380.00
dapted control bracket	N/C	N/A
programmable controller	N/C	1 505.00
standard motors	N/C	965.00
G.T. motors	N/C	965.00
neavy-duty motors	N/C	965.00
Frame: iie-down points for adapted transport reflector strips or reflectors Front anti-tip rollers relastomer rear wheel suspension rentre of gravity adjustment from base rentre of gravity adjustment from seat, depth of 38.1 cm (15 in.) reane holder	N/C N/C N/C N/C N/C 105.00 35.00	15.00 N/A N/A N/A N/A N/A 35.00
Types of forks:	N/C	76.00
tandard forks	N/C	76.00
neavy-duty forks	58.00	
a pair each	38.00	105.00
Types of wheels: front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) front wheels, semi-pneumatic tires,	N/C	62.00
22.9 cm (9 in.) X 5.7 cm (2 <sup>1</sup> / <sub>4</sub> in.)	32.00	
a pair each	32.00	78.00
	N/C	
Front wheels, inner tube tires, 20.3 cm (8 in.)	N/C	62.00
ear wheels, inner tube tires,	NI/C	120.00
35.6 cm (14 in.) X 8.9 cm (3½ in.)	N/C	130.00
ear wheels, heavy-duty, inner tube tires,	NI/C	100.00
33.0 cm (13 in.) X 10.2 cm (4 in.)	N/C	100.00
ear wheel rims, steel	N/C	124.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheel rims, plastic	N/C	50.00
rear wheel rims, for 33.0 cm (13 in.) X 10.2 cm (4 in.) wheels front wheels, semi-pneumatic tires,	N/C	135.00
15.2 cm (6 in.) X 5.1 cm (2 in.)	N/C	60.00
front wheel rims, for 22.9 cm (9 in.) wheels airless inserts for 35.6 cm (14 in.) X 7.6 cm (3 in.) rear wheels	N/C	60.00
a pair	150.00	
each		N/A
airless inserts for 33.0 cm (13 in.) X 10.2 cm (4 in.) rear wheels a pair	180.00	
each	100.00	N/A
auxiliary brakes, manual	68.00	
a pair each	08.00	50.00
Component(s) under Special Consideration		
reclining back with cylinder *	395.00	N/A
FOX suspension *	185.00	N/A
Rebuilt parts		
		Maximum price
joystick control with battery charge display, Curtis or P & G		495.00
Curtis or P & G controller		775.00
Framco motor, standard G.T. motor or heavy-duty motor		695.00 695.00
3.1. motor of neary daty motor		373.00

## **DEVICE FROM: INVACARE CANADA INC.**

**PRICE** 

## POWER WHEEL CHAIR, "STORM" MODEL

\$4 525.00

## Basic Component(s)

## **Body support system**

- supple back, leatherette, nylon
- rigid seat, flat
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seating height:  $45.1 \text{ cm} (17^{3}/_{4} \text{ in.}), 50.8 \text{ cm} (20 \text{ in.})$
- back height: from 40.6 cm (16 in.) to 48.3 cm (19 in.)
- · push handles
- push bar
- safety belt, auto-type
- · centre of gravity adjustment from seat

#### Armrests

- "U"-type armrests, detachable, flip-back and height-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.), short, long
- · straight armrest pads, short, long
- contoured armrest pads, short, long
- rigid clothing guards, built into armrests

#### **Footrests**

- 60° footrests, detachable, swingaway and length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.); 70° footrests, detachable, swingaway and length-adjustable, from 33.0 cm (13 in.) to 43.2 cm (17 in.)
- 70° footrests, "V"-shaped, detachable, swingaway and length-adjustable, from 38.7 cm (15<sup>1</sup>/<sub>4</sub> in.) to 43.2 cm (17 in.)
- 60°, 70° footrests, detachable, swingaway and length-adjustable, from 24.8 cm (9³/4 in.) to 35.6 cm (14 in.)
- · padded calfrests
- folding footplates, standard
- heel loops, non-adjustable
- heel loops, length-adjustable

### **Drive system**

- · programmable joystick control
- battery charge display
- battery charger
- battery box, group 22, group 24
- toggle switch
- direction joystick
- controller
- 4-brush motors
- 4-brush motors with gears
- G/B motors
- side bracket for joystick control, swivel side bracket for joystick control
- midline bracket for joystick control, swivel midline bracket for joystick control
- front anti-tip rollers
- · rear suspension

- · reflector strips
- standard forks
- rear wheels, inner tube tires, 35.6 cm (14 in.) X 7.6 cm (3 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) X 5.1 cm (2 in.), 20.3 cm (8 in.) X 4.4 cm (1<sup>3</sup>/<sub>4</sub> in.)
- tie-down points for adapted transport
- running lights
- front wheel rims, for 22.9 cm (9 in.) X 7 cm  $(2^{3}/_{4}$  in.) wheels
- · rear wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, flat	80.00	80.00
small headrest	106.00	106.00
arge headrest	106.00	106.00
combined headrest/neckrest	106.00	106.00
neadrest mounting, fixed	53.00	53.00
headrest mounting, articulated	122.00	122.00
seat/back structure; back, angle-adjustable	545.00	545.00
padded back, contoured, leatherette	388.00	388.00
padded back, contoured, fabric	288.00	288.00
padded back, contoured, fabric, non-standard sizes	364.00	364.00
badded back, contoured, leatherette, non-standard sizes	464.00 232.00	464.00 232.00
padded seat, contoured, fabric padded seat, contoured, fabric, non-standard sizes	306.00	306.00
padded seat, contoured, leatherette	332.00	332.00
padded seat, contoured, leatherette, non-standard sizes	406.00	406.00
rigid seat, flat	N/C	57.00
modification of back height to 50.8 cm (20 in.),	14/6	37.00
53.3 cm (21 in.), 55.9 cm (22 in.),		
58.4 cm (23 in.) or 61.0 cm (24 in.)	89.00	82.00
modification of seat depth to 48.3 cm (19 in.)	07.00	02.00
or 50.8 cm (20 in.)	255.00	N/A
modification of seat depth to 53.3 cm (21 in.)	200.00	1,712
or 55.9 cm (22 in.)	530.00	N/A
modification of seat width to 48.3 cm (19 in.),		- 11 - 1
50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	260.00	N/A
modification of seat width to 58.4 cm (23 in.)		
or 61.0 cm (24 in.)	348.00	N/A
modification of seating height to 55.2 cm (21 <sup>3</sup> / <sub>4</sub> in.)	134.00	N/A
centre of gravity adjustment from seat	N/C	N/A
supple back, nylon	N/C	56.00
supple back, leatherette	N/C	56.00
push handles	N/C	37.00
push bar	N/C	48.00
seat cushion, flat, foam, 5.1 cm (2 in.)	55.00	55.00
seat cushion, flat, foam, 7.6 cm (3 in.)	55.00	55.00
safety belt, auto-type	N/C	30.00
safety belt, airplane-type	33.00	63.00

Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
N/C	163.00
	26.00
	N/A
109.00	N/A
27/6	=
N/C	78.00
NI/C	120.00
N/C	129.00
N/C	147.00
14/6	147.00
210.00	
	183.00
234.00	
	195.00
72.00	
/2.00	26.00
	36.00
150.00	N/A
	17.00
	43.00
	53.00
	37.00
	2
28.00	
	51.00
72.00	
	73.00
78.00	<b>5</b> 4.00
	76.00
	initial purchase or replacement of wheel chair  N/C N/C N/C N/C 109.00  N/C N/C 210.00  234.00  72.00  150.00 N/C 43.00 53.00 N/C 28.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
heel loops, non-adjustable	N/C	3.00
heel loops, length-adjustable	N/C	10.00
toe loops		
a pair	15.00	
each		8.00
Wheels and frame		
Types of drive systems:		
programmable joystick control	N/C	461.00
ouch pad control	214.00	675.00
compact joystick control (requires display)	340.00	801.00
neavy-duty joystick control (requires display and interface)	35.00	496.00
nodification of joystick control, each	60.00	60.00
pattery charge display	N/C	N/A
pattery charger	N/C	360.00
attery boxes, group 24	N/C	150.00
attery box, group 22	N/C	196.00
ontrol with separate switches (requires display and interface)	200.00	661.00
roportional chin control (requires display)	340.00	801.00
on-proportional chin control (requires display and interface)	354.00	815.00
reath control	1 887.00	2 348.00
ead control	1 426.00	1 887.00
aptray touch switch control (requires display)	1 159.00	1 620.00
oot control (requires display)	1 159.00	1 620.00
oggle switch	N/C	20.00
dapted controls interface	1 100.00	1 100.00
eparate display module	1 063.00	1 063.00
lirection joystick	N/C	119.00
tick extension	18.00	18.00
all extension	5.00	5.00
T"-type extension	18.00	18.00
wivel side bracket for joystick control	N/C	231.00
wivel state of acket for joystick control wivel bracket for central joystick control	N/C N/C	231.00
ide bracket for joystick control	N/C N/C	10.00
nidline bracket for joystick control	N/C N/C	89.00
reath control bracket	357.00	357.00
hin control bracket	357.00	357.00
ead control bracket	150.00	150.00
hin control bib	220.00 N/C	220.00
ontroller	N/C	1 358.00
-brush motors	N/C	522.00
-brush motors with gears	N/C	1 139.00
G/B motors	N/C	1 139.00
ront anti-tip rollers	N/C	60.00
eavy-duty base	557.00	N/A
ear suspension	N/C	60.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
centre of gravity adjustment from base	37.00	N/A
reflector strips	N/C	N/A
tie-down points for adapted transport	N/C	60.00
running lights	N/C	N/A
Types of wheels:		
standard forks	N/C	40.00
suspension forks for 20.3 cm (8 in.) wheels		
a pair	109.00	
each		94.00
front wheels, inner tube tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)	N/C	55.00
front wheels, semi-pneumatic tires,		
15.2 cm (6 in.) X 5.1 cm (2 in.) or	N/G	40.00
20.3 cm (8 in.) X 4.4 cm (1 <sup>3</sup> / <sub>4</sub> in.)	N/C	40.00
rear wheels, inner tube tires,	N/C	67.00
35.6 cm (14 in.) X 7.6 cm (3 in.) front wheels, inner tube tires,	N/C	07.00
22.9 cm (9 in.) X 7 cm $(2^{3}/_{4}$ in.)		
a pair	90.00	
each	70.00	85.00
rear wheels, inner tube tires,		05.00
35.6 cm (14 in.) X 10.2 cm (4 in.)		
a pair	118.00	
each		129.00
front wheel rims for 22.9 cm (9 in.) X 7 cm ( $2^{3}/_{4}$ in.) wheels	N/C	43.00
rear wheel rims	N/C	50.00
airless inserts for rear wheels		
a pair	147.00	
each		N/A
airless inserts for front wheels	100.00	
a pair	109.00	NT/A
each		N/A
Component(s) under Special Consideration		
seat-back structure, reclining back with cylinder *	807.00	807.00
connecting cables for power reclining devices *	163.00	163.00
control system for 1 power accessory only *	547.00	547.00
control system for several power accessories *	632.00	632.00
power rocker device, factory installed *	1 250.00	1 450.00

#### **PRICE**

### POWER WHEEL CHAIR, "GRIZZLY A600" MODEL

\$4 480.00

#### **Basic Component(s)**

## **Body support system**

- supple back, nylon
- back height: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.)
- · rigid seat, flat
- seat width: 35.6 cm (14 in.), 40.6 cm (16 in.), 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- push handles
- safety belt, auto-type
- seating height: from 43.2 cm (17 in.) to 52.1 cm ( $20^{1}/_{2}$  in.)
- · adjustable seat bracket

#### Armrests

- "U"-type armrests, flip-back, height-adjustable, from 22.9 cm (9 in.) to 30.5 cm (12 in.), short
- straight armrest pads, short, long

#### **Footrests**

- 70° footrests, parallel or tapered, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests
- folding footplates
- heel loops, length-adjustable

### **Drive system**

- programmable joystick control
- conical-spherical extension
- battery charge display
- · battery charger
- battery box, group 22, group 24
- direction joystick including a conical-spherical extension
- breath control (requires an interface)
- push-button switch
- controller, PILOT +
- motors, 8.3 km/h
- side bracket for joystick control, swivel side bracket for joystick control

- · standard forks
- tie-down points for adapted transport
- reflector strips
- running lights
- front wheels, inner tube tires, 25.4 cm (10 in.) X 7.6 cm (3 in.)
- rear wheels, inner tube tires, 25.4 cm (10 in.) X 7.6 cm (3 in.)
- front anti-tip rollers
- centre of gravity adjustment
- · rear wheel rims, front wheel rims

Stock and Optional Component(s)   Stock   St	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
seaf and back :		
added headrest, contoured, leatherette eadrest, hammock-type riculated, hammock-type riculated headrest mounting, uniball riculated headrest mounting djustable seat bracket N/C 120.00  800 seat/back structure; back, angle-adjustable 0 - 5°, 0°, + 5°, + 10°, + 15° 115.00  115.00  115.00  115.00  115.00  115.00  115.00  120.00		
eadrest, hammock-type 75.00 75.00 riticulated headrest mounting, uniball 115.00 115.00 115.00 riticulated headrest mounting 95.00 95.00 95.00 95.00 glustable seat bracket N/C 120.00 (doubtable seat bracket S/C, v, + 5*, + 10*, + 15* S/C, + 5*, + 10*, + 15* S/C, + 5*, + 10*, - 15* S/C, + 5*, - 10*, - 15* S/C, - 12* S/C, - 10* S/C, - 12* S/C, -		
rticulated headrest mounting, uniball 115.00 115.00 95.00 95.00 95.00 1600 seat/back structure; back, angle-adjustable 5-5; 0°, +5°, +1°, +1°, +15° 514.00 514.00 upple back, nylon upple back, tension-adjustable 64.00 124.00 124.00 104.00 12		
rticulated headrest mounting dijustable seat bracket		
djustable seat bracket 6.600 seat/back structure; back, angle-adjustable 0.5°, 0°, +5°, +10°, +15° 0.5°, 0°, +5°, +10°, +15° 0.5°, 0°, +5°, +10°, +15° 0.500 maple back, nylon 0.5°, 0°, +5°, +10°, +15° 0.500 maple back, nylon 0.500 maple back, tension-adjustable 0.500 maple back, tension-adjustable 0.500 maple back, tension-adjustable 0.500 maple back, tension-adjustable 0.500 maple 0.500		
x500 seat/back structure; back, angle-adjustable op-5°, 0°, + 5°, + 10°, + 15°         514.00         514.00         514.00         124.00         upple back, nylon         N/C         60.00         124.00         inches of the part of th		
52-5°, 0°, + 5°, + 10°, + 15° 514,00 154,00	N/C	120.00
upple back, nylon upple back, tension-adjustable igid seat, flat nordification of height of non-reclining back 5 0.8 cm (20 in.) nodification of seat depth to 48.3 cm (19 in.) nodification of seat width to 50.8 cm (20 in.) nodification of seat width to 50.8 cm (20 in.) nodification of seat width to 50.8 cm (20 in.) nodification of seat width to 50.8 cm (20 in.) nodification of seat width to 50.8 cm (20 in.) nodification of seating height by 2.5 cm (1 in.), + 5.1 cm (2 in.), or + 7.6 cm (3 in.) 265.00 N/A nafety belt, tuto-type 27.00 Afety belt, auto-type 38.00 N/C 35.00 nafety belt, auto-type 38.00 N/C N/A nafety belt, auto-type 38.00 N/C N/A natety belt, airplane-type 38.00 N/C N/C N/A natety belt, airplane-type 38.00 N/C N/C N/A natety belt, auto-type 38.00 N/C N/C N/A natety belt, airplane-type 38.00 N/C N/C N/A natety belt, airplane-type 38.00 N/C N/C N/A natety belt, airplane-type 38.00 N/C N/C N/C N/A natety belt, airplane-type 38.00 N/C N/C N/C N/A natety belt, airplane-type 38.00 N/C N/C N/A natety belt, airplane-type 38.00 N/C N/C N/C N/A natety belt, airplane-		
upple back, ténsion-adjustable (64.00 124.00 gid seat, flat (77.00 notification of height of non-reclining back (77.00 notification of height of non-reclining back (77.00 notification of seat depth to 48.3 cm (19 in.) (77.00 notification of seat width to 50.8 cm (20 in.) (77.00 notification of seat width to 50.8 cm (20 in.) (77.00 notification of seat width to 50.8 cm (20 in.) (77.00 notification of seating height by (77.00 notification of seating height polymer (77.00 notification of seating height polymer (77.00 notification of seating height polymer (77.00 notification of notification notification of notification		
rigid seat, flat odification of height of non-reclining back of 50.8 cm (20 in.)		
Todification of height of non-reclining back   Section		
25.0.8 cm (20 in.) 265.00 27.00 27.00 265.00 27.00 262.00 27.00 262.00 27.00 27.00 27.00 27.00 27.00 28.00 28.00 28.00 28.00 29.00 20.00 20.00 20.00 20.00 20.00 20.00 20.0	N/C	77.00
Anodification of seat depth to 48.3 cm (19 in.)   240.00   N/A		
Notification of seat width to 50.8 cm (20 in.)   245.00   N/A	84.00	N/A
2.5 cm (1 in.), + 5.1 cm (2 in.), or + 7.6 cm (3 in.)   265.00   N/A afety belt, velcro-type   27.00   62.00   afety belt, auto-type   N/C   35.00   afety belt, auto-type   N/C   35.00   afety belt, airplane-type   38.00   73.00   ush handles   N/C   N/A   eat cushion, flat, foam, 5.1 cm (2 in.)   52.00   52.00   52.00	240.00	N/A
2.5 cm (1 in.), + 5.1 cm (2 in.), or + 7.6 cm (3 in.)  265.00  Afety belt, velcro-type  27.00  35.00  Afety belt, airplane-type  38.00  37.300  ush handles  N/C  N/A  eat cushion, flat, foam, 5.1 cm (2 in.)  N/C  N/A  eat cushion, flat, foam, 5.1 cm (2 in.)  N/C  N/A  eat cushion, flat, foam, 5.1 cm (2 in.)  N/C  N/A  eat cushion, flat, foam, 5.1 cm (2 in.)  N/C  N/A  eat cushion, flat, foam, 5.1 cm (2 in.)  N/C  N/C  135.00  Levating armrests, flip-back and height-adjustable, rom 22.9 cm (9 in.) to 30.5 cm (12 in.), short  N/C  N/C  11.00  N/C  11.00  N/C  11.00  N/C  12.00  N/A  N/C  N/C  135.00  160.00  N/C  11.00  N/C  12.00  N/A  N/C  135.00  160.00  172.00  N/A  172.00  N/A  172.00  N/A  172.00  Levating legrests, detachable, swingaway and ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair  ach  172.00  Levating footrests, compensating mechanism, etachable, length-adjustable, from  5.6 cm (14 in.) to 48.3 cm (19 in.)  pair  234.00	245.00	N/A
afety belt, velcro-type afety belt, auto-type Afety belt, airplane-type Based of Sa.00 Associated and some state of the state		
afety belt, auto-type afety belt, airplane-type afety belt, airplane-t	265.00	N/A
afety belt, airplane-type ush handles N/C N/A eat cushion, flat, foam, 5.1 cm (2 in.)  N/C N/A eat cushion, flat, foam, 5.1 cm (2 in.)  N/C N/A eat cushion, flat, foam, 5.1 cm (2 in.)  N/C N/A eat cushion, flat, foam, 5.1 cm (2 in.)  N/C N/C 135.00  Learnests:  U"-type armrests, flip-back and height-adjustable, rom 22.9 cm (9 in.) to 30.5 cm (12 in.), short N/C	27.00	62.00
N/C   N/A	N/C	35.00
N/C   N/A	38.00	73.00
### Countriests:    Countriests	N/C	N/A
U"-type armrests, flip-back and height-adjustable, rom 22.9 cm (9 in.) to 30.5 cm (12 in.), short  N/C  135.00  U"-type armrests, flip-back and height-adjustable, rom 22.9 cm (9 in.) to 30.5 cm (12 in.), long  51.00  160.00  rmrest pads, straight, short  R/C  11.00  rmrest pads, straight, long  nodification of armrest height to under 22.9 cm (9 in.)  r to over 30.5 cm (12 in.)  N/C  N/A  Sootrests:  0° footrests, parallel or tapered, detachable, wingaway, length-adjustable, from 35.6 cm (14 in.)  248.3 cm (19 in.)  N/C  97.00  levating legrests, detachable, swingaway and ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair  ach  levating footrests, compensating mechanism, etachable, length-adjustable, from  5.6 cm (14 in.) to 48.3 cm (19 in.)  pair  234.00	52.00	52.00
rom 22.9 cm (9 in.) to 30.5 cm (12 in.), short  U"-type armrests, flip-back and height-adjustable, rom 22.9 cm (9 in.) to 30.5 cm (12 in.), long  The straight, short  The straight, long		
U"-type armrests, flip-back and height-adjustable, rom 22.9 cm (9 in.) to 30.5 cm (12 in.), long 51.00 160.00 rmrest pads, straight, short N/C 11.00 rmrest pads, straight, long N/C 14.00 addification of armrest height to under 22.9 cm (9 in.) 72.00 N/A roover 30.5 cm (12 in.) 72.00 N/A  Sootrests:  0° footrests, parallel or tapered, detachable, wingaway, length-adjustable, from 35.6 cm (14 in.) N/C 97.00 levating legrests, detachable, swingaway and ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair 150.00 ach 172.00 levating footrests, compensating mechanism, etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.) pair 234.00		
rom 22.9 cm (9 in.) to 30.5 cm (12 in.), long  rmrest pads, straight, short  rmrest pads, straight, long  nodification of armrest height to under 22.9 cm (9 in.)  r to over 30.5 cm (12 in.)  rot over 30.5 cm (14 in.)  rot over 30.5 cm (1	N/C	135.00
rom 22.9 cm (9 in.) to 30.5 cm (12 in.), long  rmrest pads, straight, short  rmrest pads, straight, long  nodification of armrest height to under 22.9 cm (9 in.)  r to over 30.5 cm (12 in.)  rot over 30.5 cm (14 in.)  rot over 30.5 cm (1		
rmrest pads, straight, long nodification of armrest height to under 22.9 cm (9 in.)  r to over 30.5 cm (12 in.)  72.00  N/A   Sootrests:  0° footrests, parallel or tapered, detachable, wingaway, length-adjustable, from 35.6 cm (14 in.)  0 48.3 cm (19 in.)  150.00  levating legrests, detachable, swingaway and ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair  150.00  ach  levating footrests, compensating mechanism, etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.)  pair  234.00	51.00	160.00
rmrest pads, straight, long nodification of armrest height to under 22.9 cm (9 in.)  r to over 30.5 cm (12 in.)  72.00  N/A   Sootrests:  0° footrests, parallel or tapered, detachable, wingaway, length-adjustable, from 35.6 cm (14 in.)  0 48.3 cm (19 in.)  150.00  levating legrests, detachable, swingaway and ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair  150.00  ach  levating footrests, compensating mechanism, etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.)  pair  234.00	N/C	11.00
modification of armrest height to under 22.9 cm (9 in.) or to over 30.5 cm (12 in.)  72.00  N/A  Sootrests:  0° footrests, parallel or tapered, detachable, wingaway, length-adjustable, from 35.6 cm (14 in.) or 48.3 cm (19 in.) levating legrests, detachable, swingaway and ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair  150.00  ach levating footrests, compensating mechanism, etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.) pair  234.00	N/C	14.00
r to over 30.5 cm (12 in.)  72.00  N/A  Sootrests:  0° footrests, parallel or tapered, detachable, wingaway, length-adjustable, from 35.6 cm (14 in.)  0 48.3 cm (19 in.)  10 48.3 cm (19 in.)  11 150.00  11 172.00  11 172.00  12 18 18 18 18 18 18 18 18 18 18 18 18 18		
0° footrests, parallel or tapered, detachable, wingaway, length-adjustable, from 35.6 cm (14 in.) 0 48.3 cm (19 in.) N/C 97.00 levating legrests, detachable, swingaway and ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair 150.00 ach levating footrests, compensating mechanism, etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.) pair 234.00	72.00	N/A
wingaway, length-adjustable, from 35.6 cm (14 in.)  o 48.3 cm (19 in.)  levating legrests, detachable, swingaway and ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair  ach  levating footrests, compensating mechanism, etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.)  pair  234.00		
wingaway, length-adjustable, from 35.6 cm (14 in.)  o 48.3 cm (19 in.)  levating legrests, detachable, swingaway and ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair  ach  levating footrests, compensating mechanism, etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.)  pair  234.00		
248.3 cm (19 in.) N/C 97.00 levating legrests, detachable, swingaway and ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair ach levating footrests, compensating mechanism, etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.) pair 234.00		
levating legrests, detachable, swingaway and ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair ach levating footrests, compensating mechanism, etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.) pair 234.00	N/C	97.00
ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair ach levating footrests, compensating mechanism, etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.) pair 234.00		
pair ach 150.00 172.00 levating footrests, compensating mechanism, etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.) pair 234.00		
ach 172.00 levating footrests, compensating mechanism, etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.) pair 234.00	150.00	
levating footrests, compensating mechanism, etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.) pair 234.00	- 3.44	172.00
etachable, length-adjustable, from 5.6 cm (14 in.) to 48.3 cm (19 in.) pair 234.00		1.2.50
5.6 cm (14 in.) to 48.3 cm (19 in.) pair 234.00		
pair 234.00		
	234 00	
	23 1.00	214.00
ucii		initial purchase or replacement of wheel chair  100.00 75.00 115.00 95.00 N/C 514.00 N/C 64.00 N/C 84.00 240.00 245.00 27.00 N/C 38.00 N/C 52.00  N/C 51.00 N/C 51.00 N/C 51.00 N/C 51.00 N/C 51.00 N/C 51.00 N/C T2.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
modification of length of footrests or		
legrests to under 35.6 cm (14 in.) or		
to over 48.3 cm (19 in.)	72.00	N/A
padded calfrests, straight	N/C	20.00
double calf strap	50.00	50.00
folding footplates, standard	N/C	16.00
folding footplates, aluminum		
a pair	38.00	
each		35.00
folding footplates, angle-adjustable		
a pair	64.00	
each		48.00
folding footplates, oversized		
a pair	64.00	
each		48.00
oversized footplates, angle-adjustable		
a pair	74.00	
each		53.00
full-width footplate	138.00	170.00
heel loops, length-adjustable	N/C	10.00
toe loops		
a pair ¯	30.00	
each		15.00
front impact guard with rollers		
a pair	32.00	
each		16.00
Wheels and frame		
Types of drive systems:		
programmable joystick control	N/C	434.00
compact joystick control	51.00	485.00
pattery charge display	N/C	N/A
battery charger	N/C	339.00
battery box, group 22 or group 24	N/C	196.00
proportional chin control	631.00	631.00
non-proportional chin control (requires interface)	421.00	421.00
nead control	1 059.00	1 059.00
breath control (requires interface)	N/C	N/A
aptray touch switch control (requires interface)	301.00	301.00
control with 5 separate switches (requires interface)	530.00	530.00
chin control bib	290.00	290.00
swivel mounting hardware for breath control	357.00	357.00
swivel mounting hardware for chin control	357.00	357.00
adapted controls interface	1 520.00	1 954.00
nead control bracket	357.00	357.00
fixed bracket for separate display	34.00	34.00
flexible bracket for separate display	110.00	110.00
push-button switch	N/C	N/A
direction joystick, including a		
conical-spherical extension	N/C	239.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
stick extension	17.00	25.00
ball extension	17.00	25.00
"T"-type extension	25.00	33.00
mushroom-shaped extension	17.00	25.00
conical-spherical extension	N/C	8.00
side bracket for joystick control	N/C	35.00
swivel side bracket for joystick control	N/C	190.00
swivel midline bracket for joystick control	78.00	268.00
PILOT + controller	N/C	1 280.00
motors, 8.3 km/h	N/C	N/A
front anti-tip rollers	N/C	57.00
reflector strips	N/C	18.00
running lights	N/C	N/A
tie-down points for adapted transport	N/C	N/A
centre of gravity adjustment from seat	N/C	N/A
Types of wheels:		
standard forks	N/C	82.00
front wheels, inner tube tires,		
25.4 cm (10 in.) X 7.6 cm (3 in.)	N/C	80.00
rear wheels, inner tube tires,		
25.4 cm (10 in.) X 7.6 cm (3 in.)	N/C	80.00
front wheels, inner tube tires,		
22.9 cm (9 in.) X 7 cm ( $2^{3}/_{4}$ in.)		
a pair	84.00	
each		122.00
front wheels, puncture-resistant tires,		
25.4 cm (10 in.) X 7.6 cm (3 in.)	124.00	N/A
front wheels, puncture-resistant tires,		
22.9 cm (9 in.) X 7 cm ( $2^{3}/_{4}$ in.)	208.00	N/A
rear wheels, puncture-resistant tires,		
25.4 cm (10 in.) X 7.6 cm (3 in.)	124.00	N/A
rear wheel rims	N/C	31.00
front wheel rims	N/C	30.00
Component(s) under Special Consideration		
A600 seat/back structure, reclining back with cylinder,		
with a height of 45.7 cm (18 in.), 50.8 cm (20 in.),		
55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) *	699.00	699.00
power reclining back, factory-installed *	1 045.00	1 445.00
power rocker device, 22°, including control system *	995.00	1 395.00
control system for 1 power accessory only *	240.00	240.00
control system for 4 power accessories *	670.00	670.00

#### **PRICE**

### POWER WHEEL CHAIR, "GRIZZLY" MODEL

\$4 480.00

### **Basic Component(s)**

### **Body support system**

- · rigid seat, flat
- back height: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.)
- rigid seat, flat
- seat width: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- push handles
- safety belt, auto-type
- seating height: from 43.2 cm (17 in.) to 52.1 cm ( $20^{1}/_{2}$  in.)
- adjustable seat bracket

#### Armrests

- "T"-type armrest, detachable, height-adjustable, from 20.3 cm (8 in.) to 27.9 cm (11 in.), from 27.9 cm (11 in.) to 35.6 cm (14 in.), short, long
- · straight armrest pads, short, long

#### **Footrests**

- 70° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests, straight
- folding footplates
- · heel loops, length-adjustable

#### **Drive system**

- · programmable joystick control
- conical-spherical extension
- battery charge display
- · battery charger
- battery box, group 22, group 24
- direction joystick with conical-spherical extension
- breath control (requires an interface)
- push-button switch
- PILOT + controller
- motors, 8.3 km/h
- side bracket for joystick control, swivel side bracket for joystick control

- · standard forks
- tie-down points for adapted transport
- reflector strips
- running lights
- front wheels, inner tube tires, 25.4 cm (10 in.) X 7.6 cm (3 in.)
- rear wheels, inner tube tires, 25.4 cm (10 in.) X 7.6 cm (3 in.)
- front anti-tip rollers
- · centre of gravity adjustment from seat
- rear wheel rims, front wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, contoured, leatherette	100.00	100.00
articulated headrest mounting, uniball	115.00	115.00
articulated headrest mounting	95.00	95.00
adjustable seat bracket	N/C	120.00
seat/back structure; back,		
angle-adjustable,		
to $-5^{\circ}$ , $0^{\circ}$ , $+5^{\circ}$ , $+10^{\circ}$ , $+15^{\circ}$	714.00	714.00
reinforcement of seat/back structure	422.00	N/A
rigid seat, flat	N/C	52.00
padded back, contoured, fabric	285.00	337.00
padded back, contoured, leatherette	285.00	337.00
rigid seat, flat	N/C	52.00
padded seat, contoured, fabric	230.00	282.00
badded seat, contoured, leatherette	230.00	282.00
modification of back height to 38.1 cm (15 in.),		
50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	89.00	N/A
modification of seat depth to 38.1 cm (15 in.)		
or 48.3 cm (19 in.)	240.00	N/A
modification of seat depth to 50.8 cm (20 in.)		
or 53.3 cm (21 in.)	500.00	N/A
modification of seat width to 48.3 cm (19 in.),		
50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	245.00	N/A
modification of seating height by	2.0.00	11/11
+ 2.5  cm  (1  in.), + 5.1  cm  (2  in.)  or  + 7.6  cm  (3  in.)	265.00	N/A
safety belt, velcro-type	27.00	62.00
safety belt, auto-type	N/C	35.00
safety belt, airplane-type	38.00	73.00
bush handles	N/C	70.00
push hundres	14/6	70.00
Armrests:		
"T"-type armrests, detachable, height-adjustable,		
from 20.3 cm (8 in.) to 27.9 cm (11 in.) or		
from 27.9 cm (11 in.) to 35.6 cm (14 in.), short or long	N/C	135.00
'I''-type armrests, height-adjustable, from		
25.4 cm (10 in.) to 33.0 cm (13 in.), short		
a pair	82.00	
each		176.00
armrest pads, straight, short	N/C	11.00
armrest pads, straight, long	N/C	14.00
urmrest pads, contoured, short	74.00	51.00
modification of armrest height to under 20.3 cm (8 in.)	72.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
70° footrests, detachable, swingaway, length-adjustable,		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	73.00
modification of footrest length from 18.8 cm (7 in.)		
to 33.0 cm (13 in.)	72.00	N/A
modification of footrest length to over 48.3 cm (19 in.)	72.00	N/A
elevating legrests, detachable, swingaway and		
length-adjustable, from 27.9 cm (11 in.) to 48.3 cm (19 in.)		
a pair	198.00	
each		172.00
elevating legrests, compensating mechanism,		
length-adjustable, from 30.5 cm (12 in.) to 48.3 cm (19 in.)	240.00	
a pair	240.00	102.00
each	N/C	193.00
padded calfrests, straight	N/C	20.00
padded calfrests, contoured double calf strap	54.00 50.00	47.00 50.00
folding footplates, standard	30.00 N/C	35.00
folding footplates, standard	N/C	33.00
a pair	26.00	
each	20.00	48.00
folding footplates, angle-adjustable		10.00
a pair	26.00	
each		48.00
oversized footplates, angle-adjustable		
a pair	36.00	
each		53.00
full-width footplate	156.00	226.00
neel loops, length-adjustable	N/C	10.00
toe loops		
a pair	30.00	
each		15.00
front impact guard with rollers	22.00	
a pair	32.00	16.00
each		16.00
Wheels and frame		
Types of drive systems:		
programmable joystick control	N/C	434.00
compact joystick control	51.00	485.00
battery charge display	N/C	N/A
battery charger	N/C	339.00
pattery box, group 22 or group 24	N/C	196.00
proportional chin control	631.00	631.00
non-proportional chin control (requires interface)	421.00	421.00
nead control	1 059.00	1 059.00
breath control (requires interface)	N/C	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
laptray touch switch control (requires interface)	301.00	301.00
control with 5 separate switches (requires interface)	530.00	530.00
adapted controls interface	1 520.00	1 954.00
chin control bib	290.00	290.00
swivel mounting hardware for breath control	357.00	357.00
swivel mounting hardware for chin control	357.00	357.00
nead control bracket	357.00	357.00
ixed bracket for separate display	34.00	34.00
lexible bracket for separate display	110.00	110.00
bush-button switch	N/C	N/A
lirection joystick, including a conical-spherical extension	N/C	239.00
stick extension	17.00	25.00
pall extension	17.00	25.00
'T"-type extension	25.00	33.00
nushroom-shaped extension	17.00	25.00
conical-spherical extension	N/C	8.00
ide bracket for joystick control	N/C	35.00
wivel side bracket for joystick control	N/C	190.00
wivel midline bracket for joystick control	78.00	268.00
PILOT + controller	N/C	1280.00
notors, 8.3 km/h	N/C	N/A
ront anti-tip rollers	N/C	57.00
reflector strips	N/C	18.00
unning lights	N/C	N/A
ie-down points for adapted transport	N/C	N/A
centre of gravity adjustment from seat	N/C	N/A
Types of wheels:		0.00
standard forks	N/C	82.00
ront wheels, inner tube tires, 25.4 cm (10 in.) X 7.6 cm (3 in.)	N/C	80.00
ear wheels, inner tube tires, 25.4 cm (10 in.) X 7.6 cm (3 in.) front wheels, inner tube tires, 22.9 cm (9 in.) X 7 cm $(2^{3}/_{4}$ in.)	N/C	80.00
pair	84.00	1.00
each		122.00
ront wheels, puncture-resistant tires,		
25.4 cm (10 in.) X 7.6 cm (3 in.)	124.00	N/A
ront wheels, puncture-resistant tires,		
$22.9 \text{ cm } (9 \text{ in.}) \text{ X 7 cm } (2^{3}/_{4} \text{ in.})$	208.00	N/A
ear wheels, puncture-resistant tires,		
25.4 cm (10 in.) X 7.6 cm (3 in.)	124.00	N/A
ear wheel rims	N/C	31.00
ront wheel rims	N/C	30.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
seat-back structure, reclining back with cylinder *	799.00	799.00
power reclining back, factory-installed *	1 045.00	1 445.00
power rocker device, 22°, including control system * power elevating legrests, length-adjustable, from 30.5 cm (12 in.) to 48.3 cm (19 in.), with dual or individual controls *	995.00	1 395.00
a pair	1 166.00	
each		656.00
control system for 1 power accessory only *	240.00	240.00
control system for 4 power accessories *	670.00	670.00
DEVICE FROM: ORTHOFAB INC.		

**PRICE** 

# POWER WHEEL CHAIR, "KAMELEON A600" MODEL

\$4 480.00

### **Basic Component(s)**

### **Body support system**

- supple back, nylon
- back height: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.)
- rigid seat, flat
- seat width: 35.6 cm (14 in.), 40.6 cm (16 in.), 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- push handles
- · safety belt, auto-type
- seating height: from 41.9 cm  $(16^{1}/_{2} \text{ in.})$  to 50.8 cm (20 in.)
- adjustable seat bracket

### Armrests

- "U"-type armrests, flip-back, height-adjustable, from 22.9 cm (9 in.) to 30.5 cm (12 in.), short
- straight armrest pads, short, long

#### **Footrests**

- 70° footrests, parallel or tapered, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests
- · folding footplates, standard
- heel loops, length-adjustable

### **Drive system**

- programmable joystick control
- conical-spherical extension
- battery charge display
- battery charger
- battery box, group 22, group 24
- direction joystick including a conical-spherical extension
- breath control (requires an interface)
- push-button switch
- PILOT + controller
- motors, 11.5 km/h
- side bracket for joystick control, swivel side bracket for joystick control

- standard forks for 20.3 cm (8 in.) and 22.9 cm (9 in.) wheels
- tie-down points for adapted transport
- reflector strips
- · running lights
- front wheels, inner tube tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)
- rear wheels, inner tube tires, 35.6 cm (14 in.) X 7.6 cm (3 in.)
- front anti-tip rollers
- centre of gravity adjustment from seat
- modification of frame length, short or long version
- rear wheel rims
- · front wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, contoured	100.00	100.00
headrest, hammock-type	75.00	75.00
articulated headrest mounting, uniball	115.00	115.00
articulated headrest mounting	95.00	95.00
adjustable seat bracket	N/C	120.00
A600 seat/back structure; back, angle-adjustable,		
to $-5^{\circ}$ , $0^{\circ}$ , $+5^{\circ}$ , $+10^{\circ}$ , $+15^{\circ}$	514.00	514.00
supple back, nylon	N/C	60.00
supple back, tension-adjustable	64.00	124.00
rigid seat, flat	N/C	77.00
modification of height of non-reclining back		
to 50.8 cm (20 in.)	84.00	N/A
modification of seat depth to 48.3 cm (19 in.)	240.00	N/A
modification of seat width to 50.8 cm (20 in.) modification of seating height by + 2.5 cm (1 in.),	245.00	N/A
+ 5.1 cm (2 in.) or + 7.6 cm (3 in.)	265.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
safety belt, velcro-type	27.00	62.00
safety belt, auto-type	N/C	35.00
safety belt, airplane-type	38.00	73.00
oush handles	N/C	N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	52.00	52.00
Armrests:		
'U"-type armrests, flip-back, height-adjustable,		
From 22.9 cm (9 in.) to 30.5 cm (12 in.), short	N/C	135.00
'U"-type armrests, flip-back, height-adjustable,		
from 22.9 cm (9 in.) to 30.5 cm (12 in.), long	51.00	160.00
armrest pads, straight, short	N/C	11.00
armrest pads, straight, long	N/C	14.00
nodification of armrest height to under 22.9 cm (9 in.)	14/6	14.00
or to over 30.5 cm (12 in.)	72.00	N/A
	72.00	14/11
F <b>ootrests:</b> 70° footplates, parallel or tapered, detachable,		
swingaway, length-adjustable, from 35.6 cm (14 in.)		
to 48.3 cm (19 in.)	N/C	97.00
elevating legrests, detachable, swingaway and	14/6	27.00
ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
pair	150.00	
	130.00	172.00
each		172.00
elevating footrests, compensating mechanism, detachable,		
ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
ı pair	234.00	
each		214.00
modification of legrest length to under 35.6 cm (14 in.)		
or to over 48.3 cm (19 in.)	72.00	N/A
padded calfrests, straight	N/C	20.00
louble calf strap	50.00	50.00
folding footplates, standard	N/C	16.00
olding footplates, aluminum		
pair	38.00	
ach		35.00
olding footplates, angle-adjustable		
pair	64.00	
each	J	48.00
olding footplates, oversized		70.00
ording rootpiates, oversized	64.00	
a pair each	04.00	48.00
		40.00
oversized footplates, angle-adjustable	74.00	
pair	74.00	£2.00
ach	120.00	53.00
ull-width footplate	138.00	170.00
neel loops, length-adjustable	N/C	10.00
oe loops		
pair	30.00	
ach		15.00
ront impact guard with rollers		
pair	32.00	
ach		16.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems:		
programmable joystick control	N/C	434.00
compact joystick control	51.00	485.00
battery charge display	N/C	N/A
battery charger	N/C	339.00
battery box, group 22 or group 24	N/C	196.00
proportional chin control	631.00	631.00
non-proportional chin control (requires interface)	421.00	421.00
nead control	1 059.00	1 059.00
preath control (requires interface)	N/C	N/A
aptray touch switch control (requires interface)	301.00	301.00
control with 5 separate switches (requires interface)	530.00	530.00
adapted controls interface	1 520.00	1 954.00
chin control bib	290.00	290.00
swivel mounting hardware for breath control	357.00	357.00
swivel mounting hardware for chin control	357.00	357.00
nead control bracket	357.00	357.00
ixed bracket for separate display	34.00	34.00
lexible bracket for separate display	110.00	110.00
bush-button switch	N/C	N/A
direction joystick, including a conical-spherical extension	N/C	239.00
tick extension	17.00	25.00
pall extension	17.00	25.00
'T"-type extension	25.00	33.00
nushroom-shaped extension	17.00	25.00
conical-spherical extension	N/C	8.00
side bracket for joystick control	N/C	35.00
swivel side bracket for joystick control	N/C	190.00
swivel midline bracket for joystick control	78.00	268.00
PILOT + controller	N/C	1 280.00
motors, 11.5 km/h	N/C	N/A
ront anti-tip rollers	N/C	57.00
eflector strips	N/C	18.00
running lights	N/C	N/A
ie-down points for adapted transport	N/C	N/A
centre of gravity adjustment from seat	N/C N/C	N/A N/A
modification of frame length, short or long version	N/C	N/A
Types of wheels:		
standard forks for 20.3 cm (8 in.) and 22.9 cm (9 in.) wheels	N/C	82.00
Front wheels, inner tube tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)	N/C	80.00
ear wheels, inner tube tires, 35.6 cm (14 in.) X 7.6 cm (3 in.) ront wheels, inner tube tires, 22.9 cm (9 in.) X 7 cm ( $2^{3}/_{4}$ in.)	N/C	98.00
n pair	84.00	4.5.5.5
each		122.00
front wheels, puncture-resistant tires,	124.00	NT / A
20.3 cm (8 in.) X 5.1 cm (2 in.) front wheels, puncture-resistant tires,	124.00	N/A
22.9 cm (9 in.) X 7 cm $(2^{3}/_{4}$ in.)	208.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
rear wheels, puncture-resistant tires,		
35.6 cm (14 in.) X 7.6 cm (3 in.)	138.00	N/A
rear wheel rims	N/C	63.00
front wheel rims	N/C	30.00
Component(s) under Special Consideration		
A600 seat/back structure, reclining back with cylinder,		
height of 45.7 cm (18 in.), 50.8 cm (20 in.),		
55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) *	699.00	699.00
power reclining back, factory-installed *	1 045.00	1 445.00
power rocker device, 45°, factory-installed *	1 395.00	2 185.00
control system for 1 power accessory only *	240.00	240.00
control system for 4 power accessories *	670.00	670.00

**PRICE** 

## POWER WHEEL CHAIR, "KAMELEON" MODEL

\$4 480.00

## Basic Component(s)

### **Body support system**

- rigid seat, flat
- back height: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.)
- rigid seat, flat
- seat width: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- push handles
- safety belt, auto-type
- seating height: from 41.9 cm  $(16^{1}/_{2} \text{ in.})$  to 50.8 cm (20 in.)
- · adjustable seat bracket

## Armrests

- "T"-type armrests, detachable, height-adjustable, from 20.3 cm (8 in.) to 27.9 cm (11 in.), from 27.9 cm (11 in.) to 35.6 cm (14 in.), short, long
- straight armrest pads, short, long

#### **Footrests**

- 70° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests, straight
- · folding footplates, standard
- heel loops, length-adjustable

### **Drive system**

- programmable joystick control
- conical-spherical extension
- battery charge display
- battery charger
- battery box, group 22, group 24
- direction joystick including a conical-spherical extension
- breath control (requires an interface)
- push-button switch
- PILOT + controller
- motors, 11.5 km/h
- side bracket for joystick control, swivel side bracket for joystick control

- standard forks for 20.3 cm (8 in.) and 22.9 cm (9 in.) wheels
- tie-down points for adapted transport
- · reflector strips
- · running lights
- front wheels, inner tube tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)
- rear wheels, inner tube tires, 35.6 cm (14 in.) X 7.6 cm (3 in.)
- front anti-tip rollers
- centre of gravity adjustment from seat
- modification of frame length, short or long version
- · rear wheel rims
- · front wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, contoured	100.00	100.00
articulated headrest mounting, uniball	115.00	115.00
articulated headrest mounting	95.00	95.00
adjustable seat bracket	N/C	120.00
seat and back structure; back, angle-adjustable, to		
$-5^{\circ}, 0^{\circ}, +5^{\circ}, +10^{\circ}, +15^{\circ}$	714.00	714.00
reinforcement of seat/back structure	422.00	N/A
rigid seat, flat	N/C	52.00
padded back, contoured, fabric	285.00	337.00
padded back, contoured, leatherette	285.00	337.00
rigid seat, flat	N/C	52.00
padded seat, contoured, fabric	230.00	282.00
padded seat, contoured, leatherette	230.00	282.00
modification of back height to 38.1 cm (15 in.),		
50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	89.00	N/A
modification of seat depth to 38.1 cm (15 in.)		
or 48.3 cm (19 in.)	240.00	N/A
modification of seat depth to 50.8 cm (20 in.)		
or 53.3 cm (21 in.)	500.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
modification of seat width to 48.3 cm (19 in.),		
50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.) modification of seating height by	245.00	N/A
+2.5  cm(+1  in.), +5.1  cm(+2  in.)  or  +7.6  cm(+3  in.)	265.00	N/A
safety belt, velcro-type	27.00	62.00
safety belt, auto-type	N/C	35.00
safety belt, airplane-type	38.00	73.00
bush handles	N/C	70.00
Armrests:		
T"-type armrests, detachable, height-adjustable,		
from 20.3 cm (8 in.) to 27.9 cm (11 in.) or	N/C	127.00
from 27.9 cm (11 in.) to 35.6 cm (14 in.), short or long	N/C	135.00
T'-type armrests, height-adjustable,		
from 25.4 cm (10 in.) to 33.0 cm (13 in.), short	82.00	
ı pair each	82.00	176.00
urmrest pads, straight, short	N/C	11.00
rmrest pads, straight, short	N/C	14.00
urmrest pads, straight, long	74.00	51.00
nodification of armrest height to under 20.3 cm (8 in.)	72.00	N/A
F <b>ootrests:</b> 70° footrests, detachable, swingaway, ength-adjustable, from 35.6 cm (14 in.)	1119	
o 48.3 cm (19 in.) nodification of footrest length, from 18.8 cm (7 in.)	N/C	73.00
o 33.0 cm (13 in.)	72.00	N/A
elevating legrests, detachable, swingaway and ength-adjustable, from 27.9 cm (11 in.) o 48.3 cm (19 in.)		
o 46.5 cm (19 m.) 1 pair	198.00	
each	176.00	172.00
elevating legrests, compensating mechanism, ength-adjustable, from 30.5 cm (12 in.) to 48.3 cm (19 in.)		172.00
a pair	240.00	
ach	2 10.00	193.00
padded calfrests, straight	N/C	20.00
padded calfrests, contoured	1,, 2	20.00
pair	54.00	
ach		47.00
ouble calf strap	50.00	50.00
olding footplates, standard	N/C	35.00
versized footplates, angle-adjustable		
pair	36.00	
ach		53.00
olding footplates, angle-adjustable	•	
pair	26.00	40.00
ach		48.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
folding footplates, oversized		
a pair	26.00	
each		48.00
full-width footplate	156.00	226.00
heel loops, length-adjustable	N/C	10.00
toe loops		
a pair	30.00	
each		15.00
Front impact guard with rollers		
a pair	32.00	
each		16.00
Wheels and frame		
Types of drive systems:		
programmable joystick control	N/C	434.00
compact joystick control	51.00	485.00
pattery charge display	N/C	N/A
pattery charger	N/C	339.00
pattery box, group 22 or group 24	N/C	196.00
proportional chin control	631.00	631.00
non-proportional chin control (requires interface)	421.00	421.00
nead control	1 059.00	1 059.00
preath control (requires interface)	N/C	N/A
aptray touch switch control (requires interface)	301.00	301.00
control with 5 separate switches (requires interface)	530.00	530.00
chin control bib	290.00	290.00
wivel mounting hardware for breath control	357.00	357.00
wivel mounting hardware for chin control	357.00	357.00
dapted controls interface	1 520.00	1 954.00
nead control bracket	357.00	357.00
ixed bracket for separate display	34.00	34.00
lexible bracket for separate display	110.00	110.00
bush-button switch	N/C	N/A
lirection joystick, including a conical-spherical extension	N/C	239.00
tick extension	17.00	25.00
pall extension	17.00	25.00
T"-type extension	25.00	33.00
nushroom-shaped extension	17.00	25.00
conical-spherical extension	N/C	8.00
ide bracket for joystick control	N/C	35.00
wivel side bracket for joystick control	N/C	190.00
wivel midline bracket for joystick control	78.00	268.00
PILOT + controller	N/C	1280.00
notors, 11.5 km/h.	N/C	N/A
ront anti-tip rollers	N/C	57.00
eflector strips	N/C	18.00
unning lights	N/C	N/A
ie-down points for adapted transport	N/C	N/A
centre of gravity adjustment from seat	N/C	N/A
nodification of frame length, short or long version	N/C	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
standard forks for 20.3 cm (8 in.) and		
22.9 cm (9 in.) wheels	N/C	82.00
front wheels, inner tube tires,		
20.3 cm (8 in.) X 5.1 cm (2 in.)	N/C	80.00
rear wheels, inner tube tires,	N/G	00.00
35.6 cm (14 in.) 7.6 cm (3 in.)	N/C	98.00
front wheels, inner tube tires,		
22.9 cm (9 in.) X 7 cm (2 <sup>3</sup> / <sub>4</sub> in.)	94.00	
a pair each	84.00	122.00
		122.00
front wheels, puncture-resistant tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)	124.00	N/A
front wheels, puncture-resistant tires,	124.00	1 <b>1/</b> /A
22.9 cm (9 in.) X 7 cm ( $2^{3}/_{4}$ in.)	208.00	N/A
rear wheels, puncture-resistant tires,	200.00	14/11
35.6 cm (14 in.) X 7.6 cm (3 in.)	138.00	N/A
rear wheel rims	N/C	63.00
front wheel rims	N/C	30.00
Component(s) under Special Consideration		
seat/back structure, reclining back with cylinder *	799.00	799.00
power reclining back, factory-installed *	1 045.00	1 445.00
power rocker device, 45°, factory-installed *	1 395.00	2 185.00
power elevating legrests, individual controls *		
a pair	1 166.00	
each		656.00
power elevating legrests, dual control *	4.4.4.00	
a pair	1 166.00	2# 2 OO
each	240.00	656.00
control system for 1 power accessory only *	240.00	240.00
control system for 4 power accessories *	670.00	670.00

#### **PRICE**

### POWER WHEEL CHAIR, "PRIMA ML" MODEL

\$3 875.00

### **Basic Component(s)**

### **Body support system**

- · supple seat and back, nylon
- back height: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.)
- seat width: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- push handles
- safety belt, auto-type
- front seating height: 47.0 cm (18<sup>1</sup>/<sub>2</sub> in.); rear seating height: 43.8 cm (17<sup>1</sup>/<sub>4</sub> in.)
- modification of front seating height by + or 1.9 cm (<sup>3</sup>/<sub>4</sub> in.), and back seating height to 42.5 cm (16<sup>3</sup>/<sub>4</sub> in.)
- back, angle-adjustable
- · back spreader bar

#### Armrests

- "U"-type armrests, flip-back, height-adjustable, from 20.3 cm (8 in.) to 27.9 cm (11 in.), short
- · straight armrest pads, short, long

#### **Footrests**

- 60°, 70° footrests, parallel or tapered, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests, straight
- folding footplates, standard
- · heel loops, length-adjustable

### **Drive system**

- joystick control with integrated controller
- · conical-spherical extension
- battery charge display
- battery charger
- battery boxes, group U1
- direction joystick including a conical-spherical extension
- push-button switch
- controller
- motors
- · swivel side bracket for joystick control

#### Wheels and frame

- standard forks
- · tie-down points for adapted transport
- reflector strips
- front wheels, inner tube tires,

20.3 cm (8 in.) X 5.1 cm (2 in.),

17.8 cm (7 in.) X 4.4 cm  $(1^{3}/_{4} in.)$ ,

15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$  in.)

- rear wheels, inner tube tires, 25.4 cm (10 in.) X 7.6 cm (3 in.)
- front anti-tip rollers
- rear wheel rims, front wheel rims
- · auxiliary frame for motors

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, contoured	100.00	100.00
articulated headrest mounting, uniball	115.00	115.00
articulated headrest mounting	95.00	95.00
back, angle-adjustable	N/C	N/A
back spreader bar	N/C	N/A
supple back, nylon	N/C	60.00
supple back, tension-adjustable	64.00	124.00
rigid seat, flat	109.00	163.00
supple seat, nylon	N/C	54.00
modification of seat width to 48.3 cm (19 in.)		
or 50.8 cm (20 in.)	101.00	N/A
safety belt, velcro-type	27.00	62.00
safety belt, auto-type	N/C	35.00
safety belt, airplane-type	38.00	73.00
oush handles	N/C	N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	52.00	52.00
seat cushion, flat, foam, 7.6 cm (3 in.)	52.00	52.00
modification of front seating height by		
+ or -1.9 cm ( $^{3}/_{4}$ in.), and back seating		
height to 42.5 cm $(16^{3}/_{4} \text{ in.})$	N/C	N/A
Armrests:		
"U"-type armrests, flip-back, height-adjustable,		
from 20.3 cm (8 in.) to 27.9 cm (11 in.), short	N/C	135.00
"U"-type armrests, flip-back, height-adjustable,		
from 20.3 cm (8 in.) to 27.9 cm (11 in.), long		
a pair	51.00	
each		160.00
armrest pads, straight, short	N/C	11.00
armrest pads, straight, long	N/C	14.00
modification of armrest height to over		
30.5 cm (12 in.) or to under 20.3 cm (8 in.)	72.00	N/A
Footrests:		
70° footrests, parallel or tapered, detachable,		
swingaway, length-adjustable, from 35.6 cm (14 in.)		
to 48.3 cm (19 in.)	N/C	97.00
60° footrests, parallel or tapered, detachable,		
swingaway, length-adjustable, from 35.6 cm (14 in.)		
to 48.3 cm (19 in.)	N/C	97.00
elevating legrests, detachable, swingaway and		20
ength-adjustable, from 35.6 cm (14 in.) to		
48.3 cm (19 in.)		
a pair	150.00	
each	120.00	172.00
WO11		172.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
elevating footrests, compensating mechanism,		
detachable, length-adjustable, from		
35.6 cm (14 in.) to 48.3 cm (19 in.)		
a pair	234.00	• 4 4 00
each		214.00
modification of footrest length to over	72.00	NT/A
48.3 cm (19 in.) or to under 35.6 cm (14 in.)	72.00	N/A
padded calfrests, straight	N/C	20.00
padded calfrests, contoured	54.00	
a pair each	34.00	47.00
louble calf strap	50.00	50.00
Folding footplates, standard	N/C	16.00
Folding footplates, aluminum	14, 6	10.00
a pair	38.00	
each	20.00	35.00
folding footplates, angle-adjustable		
a pair	64.00	
each		48.00
folding footplates, oversized		
a pair	64.00	
each		48.00
oversized footplates, angle-adjustable		
a pair	74.00	<b>**</b>
each	120.00	53.00
full-width footplate	138.00	170.00
neel loops, length-adjustable	N/C	10.00
oe loops	20.00	
n pair	30.00	15.00
each Front impact guard with rollers		15.00
i pair	32.00	
each	32.00	16.00
acii		10.00
Wheels and frame		
Types of drive systems:		
oystick control with integrated controller	N/C	1 280.00
pattery charge display	N/C	N/A
pattery charger	N/C	339.00
pattery boxes, group U1	N/C	116.00
bush-button switch	N/C	N/A
lirection joystick, including a conical-spherical extension	N/C	239.00
tick extension	17.00	25.00
pall extension	17.00	25.00
T"-type extension	25.00	33.00
nushroom-shaped extension	17.00	25.00
onical-spherical extension	N/C	8.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
swivel side bracket for joystick control	N/C	190.00
controller	N/C	N/A
motors	N/C	N/A
auxiliary frame for motors	N/C	320.00
front anti-tip rollers	N/C	42.00
reflector strips	N/C	18.00
tie-down points for adapted transport auxiliary brakes, manual	N/C	N/A
a pair each	100.00	50.00
Types of wheels:		
standard forks	N/C	36.00
rear wheels, inner tube tires,		
25.4 cm (10 in.) X 7.6 cm (3 in.) front wheels, inner tube tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) or	N/C	80.00
15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) front wheels, inner tube tires,	N/C	44.00
17.8 cm (7 in.) X 4.4 cm ( $1^{3}/_{4}$ in.)	N/C	44.00
front wheels, puncture-resistant tires rear wheels, puncture-resistant tires,	73.00	N/A
25.4 cm (10 in.) X 7.6 cm (3 in.)	124.00	N/A
rear wheel rims	N/C	31.00
front wheel rims	N/C	N/A

### DEVICE FROM: SUNRISE MEDICAL CANADA INC.

PRICE

# POWER WHEEL CHAIR, "QUICKIE S-525" MODEL

\$4 650.00

# **Basic Component(s)**

# **Body support system**

- supple seat and back, nylon
- seat/back structure; back, angle-adjustable
- suspension built into seat
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seating height: from 45.7 cm (18 in.) to 53.3 cm (21 in.)
- back height: from 38.1 cm (15 in.) to 50.8 cm (20 in.)
- push handles
- back spreader bar
- safety belt, auto-type, velcro-type

## **Armrests**

- "T"-type armrests, detachable, height-adjustable, from 19.1 cm (7½ in.) to 27.9 cm (11 in.), short, long
- straight armrest pads, short, long
- · contoured armrest pads, short, long

#### **Footrests**

- 70° footrests, detachable, swingaway, length-adjustable, from 27.9 cm (11 in.) to 44.5 cm (17<sup>1</sup>/<sub>2</sub> in.), from 45.7 cm (18 in.) to 54.6 cm (21<sup>1</sup>/<sub>2</sub> in.)
- folding footplates, standardheel loops, length-adjustable
- · contoured calfrests

## **Drive system**

- · programmable joystick control
- battery charge display
- battery charger
- battery box, group 22
- toggle switch
- programmable controller
- motor, 11 km/h (6.5 mph), for standard base
- side bracket for joystick control, swivel side bracket for joystick control

- · standard forks
- rear wheels, inner tube tires, 30.5 cm (12 in.) X 5.7 cm ( $2^{1}/_{4}$  in.)
- front anti-tip rollers
- front wheels, inner tube tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)
- tie-down points for adapted transport
- reflector strips
- rear wheel rims, front wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
headrest, small	86.00	89.00
headrest, medium	91.00	98.00
neadrest, large	97.00	102.00
articulated headrest mounting	147.00	160.00
ransversal bar for headrest mounting	185.00	197.00
seat/back structure; back, angle-adjustable	N/C	633.00
folding back	111.00	N/A
suspension built into seat	N/C	N/A
suspension for weight of more than 114 kg (250 lb.)	112.00	N/A
padded back, contoured, fabric	290.00	356.00
padded back, contoured, fabric, with rigid base	374.00	440.00
supple back, tension-adjustable	70.00	136.00
padded seat, contoured, fabric	235.00	285.00
modification of seat width to 48.3 cm (19 in.)		
or to 50.8 cm (20 in.)	274.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
modification of seat depth to 48.3 cm (19 in.)		
or to 50.8 cm (20 in.)	185.00	N/A
supple back, nylon	N/C	66.00
supple seat, nylon	N/C	50.00
push handles	N/C	N/A
back spreader bar	N/C	N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	53.00	53.00
seat cushion, flat, foam, 7.6 cm (3 in.)	53.00	53.00
safety belt, auto-type	N/C	39.00
safety belt, velcro-type	N/C	26.50
Armrests: "T"-type armrests, detachable, height-adjustable, from 19.1 cm (7½ in.) to 27.9 cm (11 in.), short or long "U"-type armrests, detachable, flip-back, height-adjustable, from 24.1 cm (9½ in.) to 35.6 cm (14 in.), short or long	N/C	126.00
a pair	84.00	
each	84.00	168.00
armrest pads, straight, short	N/C	14.00
armrest pads, straight, long	N/C	15,75
armrest pads, straight, long	N/C N/C	24.00
Footrests: 70° footrests, detachable, swingaway, length-adjustable, from 27.9 cm (11 in.)		
to $44.5 \text{ cm} (17^{1}/_{2} \text{ in.}) \text{ or from } 45.7 \text{ cm} (18 \text{ in.})$		
so $54.6 \text{ cm} (21^{1}/_{2} \text{ in.})$	N/C	130.00
90° footrests, length-adjustable,		
From 15.2 cm (6 in.) to 27.9 cm (11 in.)		
a pair	85.00	
each		172.50
nodification of length of 90° footrest by 5.1 cm (2 in.) or by 10.2 cm (4 in.)		
a pair	29.00	
each	27.00	14.50
elevating legrests, detachable, swingaway,		14.50
length-adjustable, from 40.6 cm (16 in.) to		
50.8 cm (20 in.), with calfrests		
a pair	164.00	
each	104.00	212.00
contoured calfrests	N/C	33.00
single calf strap	17.00	17.00
louble calf strap	30.50	47.50
olding footplates, standard	30.30 N/C	46.00
olding footplates, standard olding footplates, oversized	IN/C	40.00
	68.00	
pair	08.00	80.00
each olding footplates, angle-adjustable		00.00
olding footplates, angle-adjustable	49.00	
ach	49.00	70.50
acii ieel loops, length-adjustable	N/C	10.00
icer roops, religiir-aujustable	IN/C	10.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems:		
programmable joystick control	N/C	583.00
pattery charge display	N/C	N/A
pattery charger	N/C	355.00
pattery box, group 22	N/C	111.00
proportional chin control (requires interface)	514.00	514.00
reath control (requires interface)	394.00	394.00
ead control (requires interface)	514.00	514.00
aptray touch switch control (requires interface)	290.00	290.00
ontrol with 5 separate switches (requires interface)	555.00	555.00
dapted controls interface	1 336.00	1 336.00
uxiliary switch	84.00	89.00
nodification of joystick control for auxiliary switch	111.00	694.00
oggle switch	N/C	N/A
all extension	47.50	47.50
T"-type extension	47.50	47.50
wivel side bracket for joystick control	N/C	174.00
wivel midline bracket for joystick control	150.00	324.00
de bracket for joystick control	N/C	69.00
reath control bracket	325.00	325.00
hin control bracket	325.00	325.00
ead control bracket	325.00	325.00
rogrammable controller	N/C	1 344.00
notors, 11 km/h (6.5 mph), for standard base	N/C N/C	730.00
eavy-duty base	118.00	N/A
	72.00	766.00
notors for heavy-duty base cont anti-tip rollers	72.00 N/C	766.00 N/A
	62.00	N/A N/A
entre of gravity adjustment	N/C	
eflector strips	N/C N/C	N/A 63.00
e-down points for adapted transport	N/C	63.00
ypes of wheels:	NIG	<b>55</b> .00
tandard forks	N/C	57.00
ont wheels, inner tube tires,	37/6	40.00
0.3 cm (8 in.) X 5.1 cm (2 in.)	N/C	63.00
ear wheels, inner tube tires,	37/6	404.00
$0.5 \text{ cm} (12 \text{ in.}) \text{ X } 5.7 \text{ cm} (2^{1}/_{4} \text{ in.})$	N/C	134.00
ont wheel rims	N/C	37.00
ar wheel rims	N/C	65.00
rless inserts for rear wheels		
pair	126.00	
ach		N/A
rless inserts for front wheels		
pair	106.00	
ach		N/A
uxiliary brakes, manual		
pair	49.00	
ach		40.00
heel lock extensions	34.00	17.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
control system for several power accessories (number: 8) *	570.00	570.00
connecting cables for power accessories, 4 plugs *	45.00	45.00
connecting cables for power accessories, 1 plug *	45.00	45.00
DEVICE FROM: SUNRISE MEDICAL CANADA INC.		
		PRIC

## POWER WHEEL CHAIR, "QUICKIE S-626" MODEL

\$5 110.00

# Basic Component(s)

#### **Body support system**

- supple back, nylon
- rigid seat, flat
- seat/back structure; back, angle-adjustable
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: from 35.6 cm (14 in.) to 45.7 cm (18 in.))
- seating height: from 45.7 cm (18 in.) to 53.3 cm (21 in.)
- back height: from 38.1 cm (15 in.) to 50.8 cm (20 in.)
- push handles
- back spreader bar
- safety belt, auto-type, velcro-type

#### Armrests

- "T"-type armrests, detachable, height-adjustable, from 19.1 cm (7<sup>1</sup>/<sub>2</sub> in.) to 27.9 cm (11 in.), short, long
- straight armrest pads, short, long
- · contoured armrest pads, short, long

#### **Footrests**

- 70° footrests, detachable, swingaway, length-adjustable, from 27.9 cm (11 in.) to 54.6 cm (21½ in.)
- · contoured calfrests
- · folding footplates, standard
- · heel loops, length-adjustable

#### **Drive system**

- · programmable joystick control
- battery charge display
- battery charger
- battery box, group 22, group 24
- toggle switch
- programmable controller
- motors 12 km/h (7 mph) for standard base
- side bracket for joystick control, swivel side bracket for joystick control

- · standard forks
- · rear suspension
- rear wheels, inner tube tires, 35.6 cm (14 in.) X 7.6 cm (3 in.)
- front anti-tip rollers
- front wheels, inner tube tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)
- tie-down points for adapted transport
- · reflector strips
- centre of gravity adjustment
- rear wheel rims, front wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
headrest, small	86.00	89.00
headrest, medium	91.00	98.00
headrest, large	97.00	102.00
articulated headrest mounting	147.00	160.00
transversal bar for headrest mounting	185.00	197.00
seat/back structure; back, angle-adjustable	N/C	N/A
padded back, contoured, fabric	290.00	356.00
padded back, contoured, fabric, with rigid base	374.00	440.00
padded back, contoured, fabric, height of		
53.3 cm (21 in.) to 61.0 cm (24 in.)	332.00	398.00
padded back, contoured, fabric, with rigid base,		
height of 53.3 cm (21 in.) to 61.0 cm (24 in.)	430.00	496.00
supple back, tension-adjustable	70.00	136.00
padded seat, contoured, fabric	235.00	285.00
modification of seat width to 48.3 cm (19 in.),		
50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	370.00	N/A
modification of seat depth to 48.3 cm (19 in.),		
50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)	245.00	N/A
modification of back height,		
53.3 cm (21 in.) to 61.0 cm (24 in.)	77.00	N/A
modification of seating height,		
$44.5 \text{ cm } (17^{1}/_{2} \text{ in.})$	270.00	N/A
supple back, nylon	N/C	66.00
rigid seat, flat	N/C	130.00
push handles	N/C	N/A
back spreader bar	N/C	N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	53.00	53.00
seat cushion, flat, foam, 7.6 cm (3 in.)	53.00	53.00
safety belt, auto-type	N/C	39.00
safety belt, velcro-type	N/C	26,25

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
"T"-type armrests, detachable, height-adjustable, from 19.1 cm (7 <sup>1</sup> / <sub>2</sub> in.) to 27.9 cm (11 in.), short or long "U"-type armrests, detachable, flip-back, height-adjustable, from 24.1 cm (9 <sup>1</sup> / <sub>2</sub> in.)	N/C	126.00
to 35.6 cm (14 in.), short or long a pair	84.00	
each	84.00	168.00
armrest pads, straight, short	N/C	14.00
armrest pads, straight, long	N/C N/C	15,75
armrest pads, straight, long	N/C	24.00
innest pads, contoured, short or long	N/C	24.00
Footrests:		
70° footrests, detachable, swingaway, length-adjustable, from 27.9 cm (11 in.)		
to 54.6 cm $(21\frac{1}{2} in.)$	N/C	130.00
elevating legrests, with calfrests	N/C	130.00
a pair	164.00	
each	104.00	212.00
contoured calfrests	N/C	33.00
single calf strap	17.00	17.00
double calf strap	30.50	47.50
folding footplates, standard	N/C	46.00
Folding footplates, oversized	- " -	
a pair	68.00	
each		80.00
folding footplates, angle-adjustable		
a pair	49.00	
each		70.50
neel loops, length-adjustable	N/C	10.00
Wheels and frame		
Types of drive systems:		
programmable joystick control	N/C	583.00
pattery charge display	N/C	N/A
pattery charger	N/C	355.00
pattery box, group 22, group 24	N/C	N/A
proportional chin control (requires interface)	514.00	514.00
nead control (requires interface)	514.00	514.00
aptray touch switch control (requires interface)	290.00	290.00
control with 5 separate switches (requires interface)	555.00	555.00
preath control (requires interface)	394.00	394.00
adapted controls interface	1 336.00	1 336.00
auxiliary switch	84.00	89.00
modification of joystick control for auxiliary switch	111.00	694.00
oggle switch	N/C	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
ball extension	47.50	47.50
"T"-type extension	47.50	47.50
swivel side bracket for joystick control	N/C	174.00
swivel midline bracket for joystick control	150.00	324.00
side bracket for joystick control	N/C	69.00
breath control bracket	325.00	325.00
chin control bracket	325.00	325.00
head control bracket	325.00	325.00
programmable controller	N/C	1 344.00
motors, 12 km/h (7.0 mph), for standard base	N/C	780.00
high-torque transmission (heavy-duty)	260.00	N/A
front anti-tip rollers	N/C	N/A
centre of gravity adjustment	N/C	N/A
reflector strips	N/C	N/A
tie-down points for adapted transport	N/C	63.00
rear suspension	N/C	N/A
Types of wheels:	27/0	00.00
standard forks	N/C	80.00
suspension forks, 68 kg (150 lb.)	95.00	N/A
suspension forks, 114 kg (250 lb.)	110.00	N/A
suspension forks, 182 kg (400 lb.) front wheels, inner tube tires,	125.00	N/A
20.3 cm (8 in.) X 5.1 cm (2 in.) front wheels, solid tires,	N/C	63.00
20.3 cm (8 in.) X 5.1 cm (2 in.)	N/C	58.00
front wheels, solid tires, 22.9 cm (9 in.) X 7.6 cm (3 in.)		
a pair	64.00	
each		90.00
front wheels, inner tube tires, 22.9 cm (9 in.) X 7.6 cm (3 in.)		
a pair	64.00	
each	04.00	90.00
rear wheels, inner tube tires,		70.00
35.6 cm (14 in.) X 7.6 cm (3 in.)	N/C	199.00
front wheel rims	N/C N/C	37.00
rear wheel rims	N/C	44.00
airless inserts for rear wheels	126.00	
a pair	126.00	AT/A
each auxiliary brakes, manual		N/A
	40.00	
a pair	49.00	40.00
each wheel lock extensions	34.00	40.00 17.00
	2 1.00	17.00
Component(s) under Special Consideration		
control system for several power accessories (number: 8) *	570.00	570.00
connecting cables for power accessories, 4 plugs *	45.00	45.00
connecting cables for power accessories, 1 plug *	45.00	45.00

#### **DEVICE FROM: INVACARE CANADA INC:**

**PRICE** 

### POWER WHEEL CHAIR, "ACTION STORM PEDIATRIC" MODEL

\$4 525.00

#### **Basic Component(s)**

## **Body support system**

- supple back, leatherette, nylon
- back height-adjustable, from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- · rigid seat, flat
- seat width: from 30.5 cm (12 in.) to 40.6 cm (16 in.)
- seat depth: 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.)
- seating height:  $45.1 \text{ cm} (17^{3}/_{4} \text{ in.}), 50.8 \text{ cm} (20 \text{ in.})$
- push handles
- · push bar
- safety belt, auto-type
- · centre of gravity adjustment from seat

#### Armrests

- "U"-type armrests, detachable, flip-back, height-adjustable, from 17.8 cm (7 in.) to 25.4 cm (10 in.), short, long
- · straight armrest pads, short, long
- rigid clothing guards, built-into armrests

#### **Footrests**

- 60° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.); 70° footrests, detachable, swingaway, length-adjustable, from 33.0 cm (13 in.) to 43.2 cm (17 in.)
- 90° footrests, detachable, swingaway, length-adjustable, from 14.0 cm (5½ in.) to 29.2 cm (11½ in.)
- 60°, 70° footrests, detachable, swingaway, length-adjustable, from 24.8 cm (9³/4 in.) to 35.6 cm (14 in.)
- 70° footrests, tapered, detachable, swingaway, length-adjustable, from 38.7 cm (15<sup>1</sup>/<sub>4</sub> in.) to 43.2 cm (17 in.)
- · padded calfrests
- folding footplates, standard
- heel loops, non-adjustable
- heel loops, length-adjustable

## **Drive system**

- programmable joystick control
- battery charge display
- battery charger
- battery box, group 22
- toggle switch
- · direction joystick
- controller
- · G/B motors
- side bracket for joystick control, swivel side bracket for joystick control
- midline bracket for joystick control, swivel midline bracket for joystick control
- front anti-tip rollers
- · rear suspension
- front wheel rims, 22.9 cm (9 in.) X 7 cm (2<sup>3</sup>/<sub>4</sub> in.)
- rear wheel rims, 35.6 cm (14 in.) X 7.6 cm (3 in.)

- reflector strips
- · standard forks
- running lights
- rear wheels, inner tube tires, 35.6 cm (14 in.) X 7.6 cm (3 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)
- front wheels, semi-pneumatic tires,
   15.2 cm (6 in.) X 5.1 cm (2 in.),
   20.3 cm (8 in.) X 4.4 cm (1<sup>3</sup>/<sub>4</sub> in.)
- tie-down points for adapted transport

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, flat	80.00	80.00
headrest, small	106.00	106.00
headrest, large	106.00	106.00
combined headrest/neckrest	106.00	106.00
fixed headrest mounting	53.00	53.00
articulated headrest mounting	122.00	122.00
seat/back structure; back, angle-adjustable	545.00	545.00
padded back, contoured, fabric	288.00	288.00
padded back, contoured, leatherette	388.00	388.00
padded seat, contoured, fabric	232.00	232.00
padded seat, contoured, leatherette	332.00	332.00
rigid seat, flat	N/C	57.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
centre of gravity adjustment from seat	N/C	N/A
supple back, leatherette or nylon	N/C	56.00
push handles	N/C	37.00
push bar	N/C	48.00
seat cushion, flat, foam, 5.1 cm (2 in.)	55.00	55.00
seat cushion, flat, foam, 7.6 cm (3 in.)	55.00	55.00
safety belt, auto-type	N/C	30.00
safety belt, airplane-type	33.00	63.00
Armrests:		
'U"-type armrests, detachable, flip-back,		
neight-adjustable, from 17.8 cm (7 in.)		
o 25.4 cm (10 in.), short or long	N/C	163.00
armrest pads, straight, short or long	N/C	26.00
rigid clothing guards, built into armrests	N/C	N/A
Footrests:		
60° footrests, detachable, swingaway,		
ength-adjustable, from 35.6 cm (14 in.)		
o 48.3 cm (19 in.); 70° footrests, detachable,		
wingaway, length-adjustable, from		
33.0 cm (13 in.) to 43.2 cm (17 in.)	N/C	78.00
50° or 70° footrests, detachable, swingaway,		
ength-adjustable, from 24.8 cm (9 <sup>3</sup> / <sub>4</sub> in.)		
o 35.6 cm (14 in.)	N/C	147.00
90° footrests, detachable, swingaway,		
ength-adjustable, from $14.0 \text{ cm } (5^{1}/_{2} \text{ in.})$		
o 29.2 cm (11 <sup>1</sup> / <sub>2</sub> in.)	N/C	147.00
70° footrests, tapered, detachable, swingaway,		
ength-adjustable, from 38.7 cm (15 <sup>1</sup> / <sub>4</sub> in.)		
o 43.2 cm (17 in.)	N/C	129.00
elevating legrests, length-adjustable,		
From 40.6 cm (16 in.) to 50.8 cm (20 in.)		
ı pair	210.00	
each		183.00
elevating legrests, compensating mechanism,		
ength-adjustable, from 43.8 cm (17 <sup>1</sup> / <sub>4</sub> in.)		
so $54.6 \text{ cm} (21^{1}/_{2} \text{ in.})$		
ı pair	234.00	
each		195.00
nodification of elevating legrest length		
oy -2.5 cm (1 in.) or -5.1 cm (2 in.)	150.00	N/A
padded calfrests	N/C	17.00
ingle calf strap	43.00	43.00
louble calf strap	53.00	53.00
olding footplates, standard	N/C	37.00
olding footplates, angle-adjustable		
pair	72.00	
ach		73.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
extension tubes, 5.1 cm (2 in.)	72.00	36.00
heel loops, non-adjustable	N/C	3.00
heel loops, length-adjustable	N/C	10.00
toe loops		
a pair	15.00	
each		8.00
Wheels and frame		
Types of drive systems:		
programmable joystick control	N/C	461.00
touch pad control	214.00	675.00
compact joystick control (requires display)	340.00	801.00
heavy-duty joystick control (requires display and interface)	35.00	496.00
modification of joystick control, each	60.00	60.00
battery charge display	N/C	N/A
battery charger	N/C N/C	360.00
battery box, group 22	N/C	196.00
control with separate switches (requires display and interface)	200.00	661.00
proportional chin control (requires display)	340.00	801.00
non-proportional chin control (requires display)	354.00	815.00
breath control	1 887.00	2 348.00
head control	1 426.00	1 887.00
laptray touch switch control (requires display)	1 159.00	1 620.00
	1 159.00	1 620.00
foot control (requires display)	N/C	20.00
toggle switch	1 100.00	1 100.00
adapted controls interface		
separate display module	1 063.00	1 063.00
direction joystick stick extension	N/C 18.00	119.00
		18.00
oall extension	5.00	5.00
"T"-type extension	18.00 N/C	18.00
swivel side bracket for joystick control		231.00
swivel bracket for central joystick control	N/C	231.00
side bracket for joystick control	N/C	10.00
midline bracket for joystick control	N/C	89.00
breath control bracket	357.00	357.00
chin control bracket	357.00	357.00
head control bracket	150.00	150.00
chin control bib	220.00	220.00
controller	N/C	1 358.00
G/B motors	N/C	1 161.00
front anti-tip rollers	N/C	60.00
rear suspension	N/C	60.00
reflector strips	N/C	N/A
tie-down points for adapted transport	N/C	60.00
running lights	N/C	N/A
centre of gravity adjustment from base	37.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
standard forks	N/C	40.00
suspension forks for 20.3 cm (8 in.) wheels		
ı pair	109.00	
each		94.00
ront wheels, semi-pneumatic tires,		
15.2 cm (6 in.)X 5.1 cm (2 in.) or		
$20.3 \text{ cm } (8 \text{ in.}) \text{ X } 4.4 \text{ cm } (1^{3}/_{4} \text{ in.})$	N/C	40.00
Front wheels, inner tube tires,	100	10.00
20.3 cm (8 in.) X 5.1 cm (2 in.)	N/C	55.00
ear wheels, inner tube tires,	14/6	33.00
35.6 cm (14 in.) X 7.6 cm (3 in.)	N/C	70.00
Front wheels, inner tube tires,	14/6	70.00
22.9 cm (9 in.) X 7 cm $(2^{3}/_{4}$ in.)		
1 pair	90.00	
each	90.00	85.00
Front wheel rims, 22.9 cm (9 in.) X 7 cm $(2^{3}/_{4}$ in.)	N/C	43.00
rear wheel rims, 35.6 cm (14 in.) X 7.6 cm (3 in.)	N/C	50.00
irless inserts for rear wheels	IN/C	30.00
	1.47.00	
n pair	147.00	NT/A
each		N/A
irless inserts for front wheels	100.00	
ı pair	109.00	3.T / A
each		N/A
Component(s) under Special Consideration		
control system for 1 power accessory only *	547.00	547.00
control system for several power accessories *	632.00	632.00
connecting cable for power reclining devices *	163.00	163.00

# **DEVICE FROM: ORTHOFAB INC.**

**PRICE** 

# POWER WHEEL CHAIR, "KAMELEON JR" MODEL

\$4 480.00

# Basic Component(s)

# **Body support system**

- · rigid back
- back height: from 27.9 cm (11 in.) to 45.7 cm (18 in.)
- rigid seat, flat
- seat width: 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.)
- seat depth: 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.)
- · push handles
- safety belt, auto-type
- seating height: from 41.9 cm  $(16^{1}/_{2} \text{ in.})$  to 50.8 cm (20 in.)
- adjustable seat bracket

#### Armrests

- "T"-type armrests, detachable, height-adjustable, from 15.2 cm (6 in.) to 25.4 cm (10 in.), short
- · armrest pads, straight, short
- rigid clothing guards

#### **Footrests**

- 70° footrests, detachable, swingaway, length-adjustable, from 17.8 cm (7 in.) to 33.0 cm (13 in.)
- padded calfrests, straight
- · folding footplates, standard
- angle-adjustable footplates, included with 90° footrests
- heel loops, length-adjustable

### **Drive system**

- · programmable joystick control
- · conical-spherical extension
- battery charge display
- battery charger
- battery box, group 22, group 24
- · direction joystick including a conical-spherical extension
- · push-button switch
- PILOT + controller
- motors, 9.5 km/h (6mph)
- · side bracket for joystick control, swivel side bracket for joystick control
- breath control (requires interface)

- standard forks for 20.3 cm (8 in.) and 22.9 cm (9 in.) wheels
- tie-down points for adapted transport
- reflector strips
- running lights
- front wheels, inner tube tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)
- rear wheels, inner tube tires, 35.6 cm (14 in.) X 7.6 cm (3 in.)
- front anti-tip rollers
- · centre of gravity adjustment from seat
- modification of frame length, short or long version
- rear wheel rims, front wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, contoured	100.00	100.00
articulated headrest mounting, uniball	115.00	115.00
articulated headrest mounting	95.00	95.00
adjustable seat bracket	N/C	120.00
seat and back structure; back, angle-adjustable	714.00	714.00
reinforced seat/backstructure, with angle-adjustable back	1 136.00	1 136.00
rigid back	N/C	52.00
padded back, contoured, fabric	285.00	337.00

horacic support adapters pair (acc)		Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
pair	padded back, contoured, leatherette	285.00	337.00
	thoracic support adapters		
igid seat, flat	a pair	60.00	
Section   Sect	each		60.00
230.00   282.00   2	rigid seat, flat		52.00
modification of back height to over 45.7 cm (18 in.) modification of seat depth to 25.4 cm (10 in.), 7.7 9 cm (11 in.) or 40.6 cm (16 in.) modification of seat width to 20.3 cm (8 in.), 22.9 cm (9 in.), 25.4 cm (10 in.) or 29 cm (11 in.) 22.9 cm (9 in.), 25.4 cm (10 in.) or 27.9 cm (11 in.) 22.9 cm (9 in.), 25.4 cm (10 in.) or 27.9 cm (11 in.) 22.9 cm (9 in.), 25.4 cm (10 in.) or 27.9 cm (11 in.) 265.00 N/A modification of seating height by + 2.5 cm (1 in.), 5.1 cm (2 in.) or + 7.6 cm (3 in.) 265.00 N/A mafety belt, veltro-type 27.00 62.00 afety belt, auto-type N/C 35.00 afety belt, auto-type 38.00 73.00 mush handles N/C 98.00  Armrests:  T**-type armrests, detachable, height-adjustable, rom 15.2 cm (6 in.) to 25.4 cm (10 in.), short N/C 11.00 igid clothing guards N/C 11.00 igid clothing guards N/C 11.00 igid clothing guards N/C 11.00 nodification of armrest height to over 25.4 cm (10 in.) N/A  **Potrests:**  10° footrests, detachable, swingaway, ength-adjustable, from 17.8 cm (7 in.) to 33.0 cm (13 in.) N/C 04.3 cm (19 in.) for 70° or 90° footrests value (19 in.) for 70° or 90° footrests value (19 in.) for 70° or 90° footrests ach 138.00 added calfrests, straight N/C 20.00 odding footplates, standard N/C 35.00 olding footplates, angle-adjustable tpair 26.00 added calfrests, straight N/C 20.00 olding footplates, angle-adjustable tpair ach olding footplates, oversized tpair teach	padded seat, contoured, fabric	230.00	
modification of seat depth to 25.4 cm (10 in.), 7.9 cm (11 in.) or 40.6 cm (16 in.)  12.9 cm (21 in.) or 40.6 cm (16 in.)  12.9 cm (9 in.), 25.4 cm (10 in.) or 27.9 cm (11 in.)  12.9 cm (9 in.), 25.4 cm (10 in.) or 27.9 cm (11 in.)  12.9 cm (9 in.), 25.4 cm (10 in.) or 27.9 cm (11 in.)  12.5 cm (2 in.) or +7.6 cm (3 in.)  12.5 cm (3 in.) or +7.6 cm (7 in.) or +	padded seat, contoured, leatherette	230.00	282.00
27.9 cm (11 in.) or 40.6 cm (16 in.)   240.00   N/A   240.00   N/A   240.00   N/A   240.00   N/A   240.00   N/A   245.00   N/C   35.00   245.00	modification of back height to over 45.7 cm (18 in.)	84.00	N/A
27.9 cm (11 in.) or 40.6 cm (16 in.)   240.00   N/A   240.00   N/A   240.00   N/A   240.00   N/A   240.00   N/A   245.00   N/C   35.00   245.00	modification of seat depth to 25.4 cm (10 in.),		
modification of seat width to 20.3 cm (8 in.), 22.9 cm (9 in.), 25.4 cm (10 in.) or 27.9 cm (11 in.)  modification of seating height by + 2.5 cm (1 in.), 265.00  N/A modification of seating height by + 2.5 cm (1 in.), 265.00  modification of seating height by + 2.5 cm (1 in.), 265.00  M/A markety belt, unit or + 7.6 cm (3 in.)  modification of seating height by + 2.5 cm (1 in.), 265.00  M/A markety belt, autro-type 27.00  modification of seating height by 1.5 cm (3 in.)  modification type 38.00  M/C 35.00  M/C 35.00  M/C 98.00  MArmrests:  T"-type armrests, detachable, height-adjustable, 70 m 15.2 cm (6 in.) to 25.4 cm (10 in.), short N/C 11.00  modification of armrest height to over 25.4 cm (10 in.) 72.00  M/A modification of armrest height to over 25.4 cm (10 in.) 72.00  M/A modification of footrest length, from 35.6 cm (14 in.) 72.00  M/A modification of footrest length, from 35.6 cm (14 in.) 73.00  modification of footrest length, from 35.6 cm (14 in.) 73.00  modification of footrest length, from 35.6 cm (14 in.) 73.00  modification of footrest length, from 35.6 cm (14 in.) 73.00  modification of footrest length, from 35.6 cm (14 in.) 73.00  modification of footrest length, from 35.6 cm (14 in.) 73.00  modification of footrest length, from 35.6 cm (14 in.) 74.00  modification of footrest length, from 35.6 cm (14 in.) 74.00  modification of footrest length, from 35.6 cm (14 in.) 74.00  modification of footrest length, from 35.6 cm (14 in.) 74.00  modification of footrest length, from 35.6 cm (14 in.) 75.00  modification of footrest length, from 35.6 cm (14 in.) 75.00  modification of footrest length, from 35.6 cm (14 in.) 75.00  modification of footrest length, from 35.6 cm (14 in.) 75.00  modification of footrest length, from 35.6 cm (14 in.) 75.00  modification of footrest length, from 35.6 cm (14 in.) 75.00  modification of footrest length, from 35.6 cm (14 in.) 75.00  modification of footrest length, from 35.6 cm (14 in.) 75.00  modification of footrest length, from 35.6 cm (14 in.) 75.00  modification o		240.00	N/A
12.9 cm (9 in.), 25.4 cm (10 in.) or 27.9 cm (11 in.)   245.00   N/A modification of seating height by + 2.5 cm (1 in.),   265.00   N/A afety belt, velcro-type   27.00   62.00   62.00   afety belt, velcro-type   N/C   35.00   afety belt, airplane-type   N/C   35.00   afety belt, airplane-type   N/C   98.00   N/A   38.00   73.00   afety belt, airplane-type   N/C   98.00   N/C   98.00   N/C   98.00   N/C   N/C   148.00   N/A   N/C   N/A   N/C   N/A   N/C   N/A   N/C   N/A   N/C   N/A			
modification of seating height by + 2.5 cm (1 in.), + 5.1 cm (2 in.) or + 7.6 cm (3 in.) 265.00 N/A afety belt, velcro-type 27.00 62.00 afety belt, auto-type N/C 35.00 afety belt, auto-type N/C 35.00 afety belt, auto-type 38.00 73.00 wish handles N/C 98.00 73.00 afety belt, airplane-type 38.00 73.00 afety belt, airplane-type 38.00 73.00 wish handles N/C 98.00 N/C	22.9 cm (9 in.), 25.4 cm (10 in.) or 27.9 cm (11 in.)	245.00	N/A
F. J. Cm (2 in.) or + 7.6 cm (3 in.)  afety belt, veltor-otype 27.00 26.00 27.00 27.00 28.	modification of seating height by $+2.5$ cm (1 in.),		
Section   Sect		265.00	N/A
Section   Sect			
Section   138.00		N/C	
Search   S			
Armrests:  T"-type armrests, detachable, height-adjustable, from 15.2 cm (6 in.) to 25.4 cm (10 in.), short  T"-type armrests, detachable, height-adjustable, from 15.2 cm (6 in.) to 25.4 cm (10 in.), short  T"-type armrests, detachable, short  T"-type armrests pads, straight, short  T"-type armrest pads, straight, short  T"-type armrest pads, straight, short  T"-type armrest pads, straight, short  T"-type armrests pads, straight, short  T"-type armrests pads, straight to over 25.4 cm (10 in.)  T"-type armrest pads, straight  T"-type armrests, detachable, swingaway, and to a 3.0 cm (13 in.)  T"-type armrests, detachable, swingaway, and to a 3.0 cm (13 in.)  T"-type armrests, detachable, swingaway, and to a 3.0 cm (13 in.)  T"-type armrests, detachable, swingaway, and to a 3.0 cm (14 in.)  T"-type armrests, detachable, swingaway, and to a 3.0 cm (14 in.)  T"-type armrests, detachable, swingaway, and to a 3.0 cm (14 in.)  T"-type armrests, detachable, swingaway, and to a 3.0 cm (14 in.)  T"-type armrests, detachable, swingaway, and to a 3.0 cm (14 in.)  T"-type armrests, detachable, swingaway, and to a 3.0 cm (14 in.)  T"-type armrests and			
rmrest pads, straight, short igid clothing guards N/C N/C 44.00 modification of armrest height to over 25.4 cm (10 in.)  Footrests:  To footrests, detachable, swingaway, ength-adjustable, from 17.8 cm (7 in.) to 33.0 cm (13 in.) modification of footrest length, from 35.6 cm (14 in.) o 48.3 cm (19 in.) for 70° or 90° footrests from 17.8 cm (7 in.) to 33.0 cm (13 in.) a pair pair pair pair pair pair pair pair	Armrests: "T"-type armrests, detachable, height-adjustable,	N/G	1.10.00
rigid clothing guards			
N/A   Proof			
Footrests:  70° footrests, detachable, swingaway, ength-adjustable, from 17.8 cm (7 in.) to 33.0 cm (13 in.)  10° footrests, detachable, from 17.8 cm (7 in.) to 33.0 cm (13 in.)  10° footrests, detachable, from 35.6 cm (14 in.)  10° footrests, detachable, swingaway, length-adjustable, from 17.8 cm (7 in.) to 33.0 cm (13 in.)  10° pair  130.00  138.00  138.00  148.3 cm (19 in.)  150 pair  150 p			
70° footrests, detachable, swingaway, ength-adjustable, from 17.8 cm (7 in.) to 33.0 cm (13 in.)  10° footrests, detachable, from 35.6 cm (14 in.)  10° 48.3 cm (19 in.) for 70° or 90° footrests  10° footrests, detachable, swingaway, length-adjustable, from 17.8 cm (7 in.) to 33.0 cm (13 in.)  10° pair  130.00  138.00  138.00  138.00  138.00  139.00  139.00  130.00	modification of armrest height to over 25.4 cm (10 in.)	72.00	N/A
ength-adjustable, from 17.8 cm (7 in.) to 33.0 cm (13 in.)  nodification of footrest length, from 35.6 cm (14 in.)  o 48.3 cm (19 in.) for 70° or 90° footrests  72.00  N/A  20° footrests, detachable, swingaway, length-adjustable, from 17.8 cm (7 in.) to 33.0 cm (13 in.)  a pair  ach  belevating footrests, compensating mechanism, letachable, length-adjustable, from 30.5 cm (12 in.)  a pair  ach  coach  coa	Footrests:		
modification of footrest length, from 35.6 cm (14 in.) o 48.3 cm (19 in.) for 70° or 90° footrests 72.00 N/A 00° footrests, detachable, swingaway, length-adjustable, from 17.8 cm (7 in.) to 33.0 cm (13 in.) a pair tach tach tach televating footrests, compensating mechanism, letachable, length-adjustable, from 30.5 cm (12 in.) o 48.3 cm (19 in.) tapair tach tach tach tach tach tach tach tach			
0 48.3 cm (19 in.) for 70° or 90° footrests   72.00   N/A		N/C	73.00
200° footrests, detachable, swingaway, length-adjustable, from 17.8 cm (7 in.) to 33.0 cm (13 in.)  1 pair 130.00  Each 138.00  Elevating footrests, compensating mechanism, letachable, length-adjustable, from 30.5 cm (12 in.)  10 48.3 cm (19 in.)  10 apair 240.00  Each 193.00  Each 193.00  Each 193.00  Each 193.00  Eolding footplates, straight N/C 20.00  Eolding footplates, standard N/C 35.00  Eolding footplates, angle-adjustable apair 26.00  Eolding footplates, oversized 48.00  Eolding footplates, oversized 26.00	nodification of footrest length, from 35.6 cm (14 in.)		
rom 17.8 cm (7 in.) to 33.0 cm (13 in.) a pair  to pair  to pair  to pair  130.00  138.00  138.00  138.00  138.00  138.00  138.00  138.00  138.00  138.00  138.00  138.00  138.00  138.00  138.00  190	to 48.3 cm (19 in.) for 70° or 90° footrests	72.00	N/A
a pair each each elevating footrests, compensating mechanism, eletachable, length-adjustable, from 30.5 cm (12 in.) each each each each each each each each	90° footrests, detachable, swingaway, length-adjustable,		
a pair each each elevating footrests, compensating mechanism, eletachable, length-adjustable, from 30.5 cm (12 in.) each each each each each each each each	From 17.8 cm (7 in.) to 33.0 cm (13 in.)		
teach elevating footrests, compensating mechanism, eletachable, length-adjustable, from 30.5 cm (12 in.) to 48.3 cm (19 in.) to pair each each each each each each each each		130.00	
detachable, length-adjustable, from 30.5 cm (12 in.)	each		138.00
detachable, length-adjustable, from 30.5 cm (12 in.)			
o 48.3 cm (19 in.) a pair 240.00 each 193.00 badded calfrests, straight N/C 20.00 double calf strap 50.00 50.00 folding footplates, standard N/C 35.00 folding footplates, angle-adjustable apair 26.00 folding footplates, oversized 48.00 folding footplates, oversized 26.00			
a pair cach cach cadded calfrests, straight colding footplates, standard colding footplates, angle-adjustable cach colding footplates, oversized			
teach padded calfrests, straight padded calfrest		240.00	
padded calfrests, straight N/C 20.00 double calf strap 50.00 50.00 50.00 folding footplates, standard N/C 35.00 folding footplates, angle-adjustable apair 26.00 48.00 folding footplates, oversized apair 26.00			193.00
double calf strap  folding footplates, standard  folding footplates, angle-adjustable  a pair  folding footplates, oversized		N/C	
folding footplates, standard folding footplates, angle-adjustable a pair folding footplates, angle-adjustable a pair folding footplates, oversized a pair folding footplates, oversized a pair folding footplates, oversized for pair for footplates, oversized for pair for footplates, oversized for pair for footplates, oversized for			
folding footplates, angle-adjustable a pair each folding footplates, oversized a pair 26.00 48.00 26.00	Folding footplates, standard		
a pair 26.00 each 48.00 folding footplates, oversized 26.00		10,0	33.00
Asiach 48.00 folding footplates, oversized 26.00		26.00	
folding footplates, oversized a pair 26.00	ogch	20.00	48.00
pair 26.00			70.00
		26.00	
	each	20.00	48.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
angle-adjustable footplates, included with 90° footrests oversized footplates, angle-adjustable	N/C	N/A
a pair	36.00	
each		53.00
full-width footplate	156.00	226.00
heel loops, length-adjustable	N/C	10.00
toe loops		
a pair	30.00	
each		15.00
front impact guard with rollers		13.00
a pair	32.00	
each	32.00	16.00
Cacii		10.00
Wheels and frame		
Types of drive systems:		
programmable joystick control	N/C	434.00
compact joystick control	51.00	485.00
battery charge display	N/C	N/A
battery charger	N/C	339.00
battery box, group 22 or group 24	N/C	196.00
proportional chin control	631.00	631.00
non-proportional chin control (requires interface)	421.00	421.00
head control	1 059.00	1 059.00
breath control (requires interface)	N/C	N/A
laptray touch switch control (requires interface)	301.00	301.00
control with 5 separate switches (requires interface)	530.00	530.00
chin control bib	290.00	290.00
swivel mounting hardware for breath control	357.00	357.00
swivel mounting hardware for chin control	357.00	357.00
head control bracket	357.00	357.00
fixed bracket for separate display	34.00	34.00
flexible bracket for separate display	110.00	110.00
push-button switch	N/C	N/A
direction joystick, including a	14,0	11/11
conical-spherical extension	N/C	239.00
stick extension	17.00	25.00
ball extension	17.00	25.00
"T"-type extension	25.00	33.00
mushroom-shaped extension	17.00	25.00
conical-spherical extension	N/C	8.00
side bracket for joystick control	N/C	35.00
swivel side bracket for joystick control	N/C N/C	190.00
swivel side bracket for joystick control	78.00	268.00
PILOT + controller	N/C	1280.00
notors, 9.5 km/h (6 mph)	N/C N/C	N/A
	N/C N/C	57.00
Front anti-tip rollers	N/C N/C	18.00
reflector strips	N/C N/C	18.00 N/A
running lights		
ie-down points for adapted transport	N/C	N/A
centre of gravity adjustment from seat	N/C	N/A
modification of frame length, short or long version	N/C	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
standard forks for 20.3 cm (8 in.) and 22.9 cm (9 in.) wheels	N/C	82.00
front wheels, inner tube tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)	N/C	80.00
rear wheels, inner tube tires, 35.6 cm (14 in.) X 7.6 cm (3 in.) front wheels, inner tube tires, 22.9 cm (9 in.) X 7 cm $(2^{3}/_{4}$ in.)	N/C	98.00
a pair	84.00	4.00
each		122.00
front wheels, puncture-resistant tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)	124.00	N/A
front wheels, puncture-resistant tires,	124.00	N/A
22.9 cm (9 in.) X 7 cm ( $2^{3}/_{4}$ in.)	208.00	N/A
rear wheels, puncture-resistant tires,	200.00	11/12
35.6 cm (14 in.) X 7.6 cm (3 in.)	138.00	N/A
rear wheel rims	N/C	63.00
front wheel rims	N/C	30.00
Component(s) under Special Consideration		
power rocker device, 45°, factory installed *	1 395.00	2 185.00
power elevating legrests, individual controls * a pair	1 166.00	
each	1 100.00	656.00
power elevating legrests, dual control *		050.00
a pair	1 166.00	
each		656.00
control system for 1 power accessory only *	240.00	240.00
control system for 4 power accessories *	670.00	670.00
<b>§4.</b> Wheel chair accessories		
CUSHIONS FOR WHEEL CHAIRS		
		UNIT PRICE
Comfort mate xtra cushion, widths of 35.6cm (14 in.), 40.6 cm (16 in.), 45.7 cm (18 in.), 50.8 cm (20 in.) or 55.9 cm (22 in.); depths of 35.6cm (14 in.),		
40.6 cm (16 in.), 45.7 cm (18 in.) or 50.8 cm (20 in.)		80.00
"BOTTOMLINE"-type cushion or equivalent		95.00
"ORTHOFAB" contoured cushion		180.00
"ORTHOFAB" contoured cushion with gel		230.00
"COMBI"-type cushion or equivalent * "JAY"-type cushion or equivalent *		S.C. S.C.
gel cushion or equivalent *		S.C. S.C.
"ROHO" cushion or equivalent *		S.C.
special cushion *		S.C.
-		

# §5. Wheel chair accessories

# TIRES

# FOR MANUAL WHEEL CHAIRS

# SUPPLIER: ORTHOFAB INC.

Inner tube tire, standard pressure, 50.8 cm (20 in.) X 3.5 cm ( $1^{3}/_{8}$ in.)	8.09
Inner tube tire, standard pressure, 55.9 cm (22 in.) X 3.5cm (1 <sup>3</sup> / <sub>8</sub> in.)	7.23
Inner tube tire, standard pressure, 61.0 cm (24 in.) X 3.2 cm ( $1\frac{1}{4}$ in.)	7.23
Inner tube tire, standard pressure, 61.0 cm (24 in.) X 3.5 cm ( $1^{3}/_{8}$ in.)	7.23
Inner tube tire, standard pressure, 61.0 cm (24 in.) X 4.4 cm ( $1^{3}/_{4}$ in.)	10.41
Inner tube tire, standard pressure, 40.6 cm (16 in.) X 4.4 cm ( $1^{3}/_{4}$ in.)	9.95
Inner tube tire, standard pressure, $66.0 \text{ cm} (26 \text{ in.}) \text{ X } 3.5 \text{ cm} (1^{3}/_{8} \text{ in.})$	8.62
Inner tube tire, high pressure, 50.8 cm (20 in.) X 2.5 cm (1 in.)	12.32
Inner tube tire, high pressure, 55.9 cm (22 in.) X 2.5 cm (1 in.)	11.68
Inner tube tire, high pressure, 61.0 cm (24 in.) X 2.5 cm (1 in.)	11.52
Inner tube tire, high pressure, 66.0 cm (26 in.) X 2.5 cm (1 in.)	12.32
	12.32
Inner tube tire 61.0 cm (24 in.) X 3.5 cm ( $1^{3}/_{8}$ in.),	
all-terrain, rounded surface	11.77
Inner tube tire, $61.0 \text{ cm } (24 \text{ in.}) \text{ X } 3.5 \text{ cm } (1^{3}/_{8} \text{ in.}),$	
all-terrain, rounded smooth surface	9.47
Solid tire, 20.3 cm (8 in.) X 2.5 cm (1 in.)	4.50
Solid tire, 55.9 cm (22 in.) X 2.5 cm (1 in.)	10.87
Solid tire, 61.0 cm (24 in.) X 2.5 cm (1 in.)	10.44
Inner tube tire, 15.2 cm (6 in.) X 3.2 cm ( $^{1}$ / <sub>4</sub> in.)	6.96
Inner tube tire, 20.3 cm (8 in.) X 3.2 cm ( $1\frac{1}{4}$ in.) (C-63)	5.99
Inner tube tire, 20.3 cm (8 in.) X 4.4 cm ( $1^{3}/_{4}$ in.)	9.14
Inner tube tire, 20.3 cm (8 in.) X 5.1 cm (2 in.)	6.48
Inner tube tire, 18.8 cm (7 in.) X 4.4 cm ( $1^{3}/_{4}$ in.)	7.95
Inner tube tire, 20.3 cm (8 in.) X 3.2 cm ( $^{1}$ / <sub>4</sub> in.) (C-737)	5.99
Semi-pneumatic tire, 12.7 cm (5 in.) X 2.5 cm (1 in.)	9.10
	9.10
Semi-pneumatic tire, 15.2 cm (6 in.) X 2.5 cm (1 in.)	
Semi-pneumatic tire, 20.3 cm (8 in.) X 2.5 cm (1 in.) (poly kik)	10.39
Semi-pneumatic tire, 20.3 cm (8 in.) X 2.5 cm (1 in.) (poly pyramide)	10.02
Semi-pneumatic tire, 55.9 cm (22 in.) X 2.5 cm (1 in.)	15.15
Semi-pneumatic tire, 61.0 cm (24 in.) X 2.5 cm (1 in.)	15.15
Semi-pneumatic tire, 66.0 cm (26 in.) X 2.5 cm (1 in.)	15.40
Puncture-resistant tire, $15.2 \text{ cm}$ (6 in.) X $3.2 \text{ cm}$ ( $1\frac{1}{4} \text{ in.}$ )	10.61
Puncture-resistant tire, 20.3 cm (8 in.) X 3.2 cm ( $1\frac{1}{4}$ in.)	10.61
Puncture-resistant tire, 20.3 cm (8 in.) X 4.4 cm ( $1^{3}/_{4}$ in.)	14.05
Puncture-resistant tire, 20.3 cm (8 in.) X 5.1 cm (2 in.)	15.31
	24.15
Puncture-resistant tire, 50.8 cm (20 in.) X 3.5 cm ( $1^{3}/_{8}$ in.)	
Puncture-resistant tire, 55.9 cm (22 in.) X 3.5 cm ( $1^{3}$ / <sub>8</sub> in.)	24.15
Puncture-resistant tire, 61.0 cm (24 in.) X 2.5 cm (1 in.)	19.90
Puncture-resistant tire, 61.0 cm (24 in.) X 3.45 cm ( $1^{3}$ / <sub>8</sub> in.)	24.40
Airless insert, 15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.)	11.08
Airless insert, 20.3 cm (8 in.) X 3.2 cm ( $\frac{1}{4}$ in.)	12.20
Airless insert, 20.3 cm (8 in.) X 4.4 cm $(1^{3}/_{4} in.)$	14.80
Airless insert, 50.8 cm (20 in.) X 3.5cm ( $1^{3}/_{8}$ in.)	20.63
Airless insert, 55.9 cm (22 in.) X 3.5 cm $(1^{3}/_{8}$ in.)	20.63
Airless insert, 61.0 cm (24 in.) X 3.2 cm ( $1^{1}/_{4}$ in.)	20.63
Airless insert, 61.0 cm (24 in.) X 3.5 cm ( $\frac{13}{8}$ in.)	20.63
Airless insert, 66.0 cm (26 in.) X 3.5 cm ( $1^{3}/_{8}$ in.)	31.93

# TIRES

# FOR POWER WHEEL CHAIRS

# SUPPLIER: ORTHOFAB INC.

Input tube time $19.9 \text{ cm} (7 \text{ in}) \text{ V} A A \text{ cm} (13/\text{ in})$	8.75
Inner tube tire, 18.8 cm (7 in.) X 4.4 cm ( $1^{3}/_{4}$ in.) Inner tube tire, 20.3 cm (8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.)	5.99
Inner tube tire, 20.3 cm (8 in.) X 4.4 cm ( $1\frac{3}{4}$ in.)	9.14
Inner tube tire, 20.3 cm (8 in.) X 5.1 cm (2 in.)	6.48
Inner tube tire, 20.5 cm (8 ll.) X 5.1 cm (2 ll.)  Inner tube tire, 21.6 cm (8 $\frac{1}{2}$ in.) X 5.3 cm (2 $\frac{1}{8}$ in.)	37.00
	9.14
Inner tube tire, 20.3 cm (8 in.) X 7 cm $(2^{3}/_{4}$ in.)	9.14 9.14
Inner tube tire, 22.9 cm (9 in.) X 7 cm $(2^{3}/_{4}$ in.)	
Inner tube tire, 25.4 cm (10 in.) X 7.6 cm (3 in.)	11.02
Inner tube tire, 30.5 cm (12 in.) X 7.6 cm (3 in.)	15.91
Inner tube tire, 31.8 cm $(12^{1/2} \text{ in.}) \times 5.7$ cm $(2^{1/4} \text{ in.})$	8.93
Inner tube tire, 35.6 cm (14 in.) $\times$ 5.7 cm (2 <sup>1</sup> / <sub>4</sub> in.)	12.50
Inner tube tire, (300-8) 35.6 cm (14 in.) X 7.6 cm (3 in.)	17.52
Inner tube tire, 35.6 cm (14 in.) X 10.2 cm (4 in.)	15.98
Inner tube tire, $40 \text{ cm } (15^{3}/_{4} \text{ in.}) \text{ X 7 cm } (2^{3}/_{4} \text{ in.})$	53.00
Inner tube tire, $40.6 \text{ cm} (16 \text{ in.}) \times 5.7 \text{ cm} (2^{1}/_{4} \text{ in.})$	11.90
Inner tube tire, $40.6 \text{ cm} (16 \text{ in.}) \times 5.3 \text{ cm} (2^{1}/_{8} \text{ in.})$	14.10
Inner tube tire, 45.7 cm (18 in.) X 5.7 cm ( $2^{1}/_{4}$ in.)	12.45
Inner tube tire, 50.8 cm (20 in.) X 5.3 cm ( $2^{1}/_{8}$ in.)	14.10
Inner tube tire, $50.8 \text{ cm} (20 \text{ in.}) \text{ X } 5.7 \text{ cm} (2^{1}/_{4} \text{ in.})$	12.45
Semi-pneumatic tire, 20.3 cm (8 in.) X 4.4 cm $(1^{3}/_{4} in.)$ (poly kik)	14.05
Semi-pneumatic tire, 22.9 cm (9 in.) X 7 cm $(2^{3}/_{4}$ in.)	29.80
Puncture-resistant tire, 20.3 cm (8 in.) X 4.4 cm ( $1^{3}/_{4}$ in.) (poly kik)	12.70
Puncture-resistant tire, $(280/250-4)$ 22.9 cm (9 in.) X 7 cm $(2^{3}/_{4}$ in.)	37.40
Puncture-resistant tire, 25.4 cm (10 in.) X 7.6 cm (3 in.)	48.90
Puncture-resistant tire, 30.5 cm (12 in.) X 7.6 cm (3 in.)	35.50
Puncture-resistant tire, 35.6 cm (14 in.) X 10.2 cm (4 in.)	59.00
Puncture-resistant tire, 35.6 cm (14 in.) X 7.6 cm (3 in.)	67.70
Puncture-resistant tire, (400-6) 35.6 cm (14 in.) X 10.2 cm (4 in.)	59.00
Puncture-resistant tire, 50.8 cm (20 in.) X 5.3 cm ( $2^{1}/_{8}$ in.)	36.20
Puncture-resistant tire, 20.3 cm (8 in.) X 5.1 cm (2 in.)	15.31
Puncture-resistant tire, 20.3 cm (8 in.) X 5.1 cm (2 in.) (poly kik)	13.95
Airless insert, 20.3 cm (8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.)	12.20
Airless insert, 20.3 cm (8 in.) X 4.4 cm ( $1^{3}/_{4}$ in.)	14.80
Airless insert, 31.8 cm $(12^{1}/_{2} \text{ in.}) \times 5.7 \text{ cm } (2^{1}/_{4} \text{ in.})$	29.90
Airless insert, 35.6 cm (14 in.) $\dot{X}$ 5.7 cm (2 $\frac{1}{4}$ in.)	23.95
Airless insert, 40.6 cm (16 in.) X 5.3 cm ( $2^{1/8}$ in.)	27.98
Airless insert, 45.7 cm (18 in.) X 5.7 cm ( $2^{1}/_{4}$ in.)	23.95
Airless insert, 50.8 cm (20 in.) X 5.3 cm ( $2^{1}/_{8}$ in.)	27.98
Airless insert, 50.8 cm (20 in.) X 5.7 cm ( $2^{1}/_{4}$ in.)	22.95

#### **BATTERIES**

#### FOR POWER WHEEL CHAIRS

#### SEALED LEAD BATTERIES

## (AQUEOUS-TYPE, DEEP CYCLE, NOMINAL TENSION OF 12 VOLTS)

Price including delivery of goods and their recovery after use

#### **GROUP 22:**

Model: 22NF-DC 56.16

Model: 22F-DC 60.24

**GROUP 24:** 

Model: 24-DC 50.93

**GROUP U1:** 

Model: U1-DC 44.67

DIVISION II

POSITIONING BUGGIES

#### **DEVICE FROM: INVACARE CANADA INC.**

**PRICE** 

# POSITIONING BUGGY, ADULT, "SOLARA" MODEL

\$1 648.00

#### **Basic Component(s)**

### **Body support system**

- seating height: from 42.5 cm  $(16^{3}/_{4} \text{ in.})$  to 48.9 cm  $(19^{1}/_{4} \text{ in.})$
- seat width: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.),45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.)
- seat depth: 30.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.)
- back height: 50.8 cm (20 in.), 61.0 cm (24 in.)
- rocker device for seat and back
- · push handles
- angle-adjustable push handles, stroller handle
- safety belt, velcro-type, auto-type

#### Armrests

- "T"-type armrests, detachable, height-adjustable, from 12.7 cm (5 in.), to 20.3 cm (8 in.) or from 20.3 cm (8 in.) to 27.9 cm (11 in.), short, long
- "U"-type armrests, detachable, height-adjustable, from 21.6 cm (8½ in.) to 31.8 cm (12½ in.), short, long
- straight armrest pads, short, long

#### **Footrests**

- 60° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70° footrests, detachable, swingaway, length-adjustable, from 33.0 cm (13 in.) to 43.2 cm (17 in.)
- 90° footrests, detachable, swingaway, length-adjustable, from 14.0 cm (5<sup>1</sup>/<sub>2</sub> in.) to 29.2 cm (11<sup>1</sup>/<sub>2</sub> in.)
- 60°, 70° footrests, detachable, swingaway, length-adjustable, from 24.8 cm (9³/4 in.) to 35.6 cm (14 in.)
- 70° footrests, "V"-shaped, detachable, swingaway, length-adjustable, from 36.8 cm (14<sup>1</sup>/<sub>2</sub> in.) to 43.2 cm (17 in.)
- padded calfrests
- heel loops, non-adjustable
- heel loops, length-adjustable
- folding footplates, standard or tubular

- · anodized aluminum handrims
- standard wheel locks, push-to-lock
- · standard forks
- threaded axles, quick-release
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)
- front wheels, solid tires, 15.2 cm (6 in.), 20.3 cm (8 in.)
- front anti-tip rollers

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
modification of seat width to 53.3 cm (21 in.) or to 55.9 cm (22 in.)	72.00	N/A
rigid seat, flat	57.00	57.00
rigid seat, drop-mounted, 5.1 cm (2 in.)	57.00	57.00
rocker device for seat and back	N/C	N/A
stroller handle	N/C	105.00
push handles	N/C	37.00
push handle, angle-adjustable	N/C	175.00
safety belt, velcro-type	N/C	20.00
safety belt, auto-type	N/C	30.00
seat cushion, flat, foam, 5.1 cm (2 in.)	55.00	55.00
seat cushion, flat, foam, 7.6 cm (3 in.)	55.00	55.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
"U"-type armrests, detachable, height-adjustable,		
from 21.6 cm $(8^{1}/_{2} \text{ in.})$ to 31.8 cm $(12^{1}/_{2} \text{ in.})$ ,		
short or long	N/C	94.00
"T"-type armrests, detachable, height-adjustable,		
from 12.7 cm (5 in.) to 20.3 cm (8 in.) or	N/C	04.00
from 20.3 cm (8 in.) to 27.9 cm (11 in.) straight armrest pads, long	N/C N/C	94.00 26.00
straight armrest pads, long straight armrest pads, short	N/C N/C	26.00
straight armiest paus, short	N/C	20.00
Footrests:		
60° footrests, detachable, swingaway, length-adjustable,	N/C	70.00
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	78.00
70° footrests, detachable, swingaway, length-adjustable, from 33.0 cm (13 in.) to 43.2 cm (17 in.)	N/C	78.00
90° footrests, detachable, swingaway and length-adjustable,	N/C	78.00
from 14.0 cm ( $5^{1}/_{2}$ in.) to 29.2 cm $11^{1}/_{2}$ in.)	N/C	147.00
60° or 70° footrests, detachable, swingaway,	100	117.00
length-adjustable, from 24.8 cm (9 <sup>3</sup> / <sub>4</sub> in.) to		
35.6 cm (14 in.)	N/C	147.00
70° footrests, "V"-shaped, detachable, swingaway,		
length-adjustable, from 36.8 cm $(14^{1}/_{2} \text{ in.})$		
to 43.2 cm (17 in.)	N/C	129.00
elevating legrests, detachable, swingaway,		
length-adjustable, from 40.6 cm (16 in.) to 50.8 cm (20 in.)		
a pair	210.00	
each	210.00	183.00
elevating legrests, compensating mechanism		103.00
a pair	210.00	
each		183.00
modification of legrest length by - 2.5 cm (1 in.)		
or by - 5.1 cm (2 in.)	150.00	N/A
padded calfrests	N/C	17.00
single calf strap	43.00	43.00
double calf strap	53.00 N/C	53.00
folding footplates, standard or tubular folding footplates, angle-adjustable and	N/C	37.00
depth-adjustable		
a pair	72.00	
each	. 2.00	73.00
folding footplates, oversized		
a pair	28.00	
each		51.00
neel loops, non-adjustable	N/C	3.00
heel loops, length-adjustable	N/C	10.00
heel loops and ankle straps	22.00	
a pair	32.00	16.00
each		16.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems:	N/G	22.00
anodized aluminum handrims plastic-coated handrims	N/C	33.00
a pair	52.00	
each	N/C	59.00 48.00
front anti-tip rollers	N/C	46.00
Wheel locks:	N/G	44.00
standard wheel locks, push-to-lock wheel lock extensions	N/C	44.00
a pair	32.00	
each		16.00
Types of forks:		
standard forks	N/C	40.00
Rear axles:		
threaded axles	N/C	15.00
quick-release axles	N/C	53.00
Types of wheels:		
rear mag wheels, standard pressure, 30.5 cm (12 in.) rear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C	52.00
or 55.9 cm (22 in.)	N/C	69.00
rear mag wheels, solid tires, 50.8 cm (20 in.)	NG	42.00
or 55.9 cm (22 in.) front wheels, solid tires, 20.3 cm (8 in.)	N/C	42.00
or 15.2 cm (6 in.)	N/C	23.00
front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) front wheels, semi-pneumatic tires,	32.00	39.00
20.3 cm (8 in.) X 5.1 cm (2 in.)		
a pair	54.00	<b>7</b> 0.00
each front wheels, semi-pneumatic tires,		50.00
15.2 cm (6 in.) X 5.1 cm (2 in.)		
a pair each	50.00	50.00
airless inserts for 20.3 cm (8 in.) front wheels		30.00
a pair	95.00	27/1
each airless inserts for rear wheels		N/A
a pair	99.00	
each		N/A
Component(s) under Special Consideration		
contracture footrests, bilateral-angle adjustable *	243.00	321.00
reclining back *	438.00	718.00
heavy-duty frame *	322.00	N/A

#### **DEVICE FROM: ORTHOFAB INC.**

#### **PRICE**

# POSITIONING BUGGY, ADULT, "PRIMA SI" MODEL

\$1 598.00

#### **Basic Component(s)**

## **Body support system**

- seating height: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat width: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.)
- seat depth: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.)
- back height: from 40.6 cm (16 in.) to 66.0 cm (26 in.)
- · rocker device for seat and back
- push handles
- safety belt, auto-type

#### Armrests

- "U"-type armrests, detachable, height-adjustable, from 25.4 cm (10 in.) to 35.6 cm (14 in.), short
- straight armrest pads, short, long

#### **Footrests**

- 60° footrests, parallel or tapered, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70° footrests, parallel or tapered, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests
- heel loops, length-adjustable
- · folding footplates, standard

- · standard wheel locks, push-to-lock
- · high forks
- threaded axles
- spoked rear wheels, standard pressure,
   50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.), 17.8 cm (7 in.), 15.2 cm (6 in.)
- front anti-tip rollers

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:	00	<b></b> 00
headrest, hammock-style	75.00	75.00
padded headrest, contoured, leatherette	100.00	100.00
rigid seat, flat	77.00	77.00
ocker device for seat and back	N/C	N/A
oush handles	N/C	N/A
polt-on push handles	75.00	
n pair	75.00	75.00
each	27.00	75.00
safety belt, velcro-type	27.00	62.00
safety belt, auto-type	N/C	35.00
safety belt, airplane-type seat cushion, flat, foam, 5.1 cm (2 in.)	38.00	73.00
seat cushion, flat, foam, 7.6 cm (3 in.)	52.00 52.00	52.00 52.00
	60.00	60.00
supple back, nylon supple back, tension adjustable	124.00	124.00
supple back, tension aujustable	124.00	124.00
Armrests:		
"U"-type armrests, detachable, height-adjustable,		
from 25.4 cm (10 in.) to 35.6 cm (14 in.), short	N/C	135.00
'U"-type armrests, detachable, height-adjustable,		
from 25.4 cm (10 in.) to 35.6 cm (14 in.), long	<b>7.</b> 1.00	
a pair	51.00	
each	27/6	160.00
straight armrest pads, long	N/C	14.00
straight armrest pads short	N/C	11.00
modification of armrest height to under 25.4 cm (10 in.)	72.00	N/A
Footrests:		
60° footrests, parallel or tapered, detachable,		
swingaway, length-adjustable, from 35.6 cm (14 in.)	NIG	07.00
to 48.3 cm (19 in.)	N/C	97.00
70° footrests, parallel or tapered, detachable,		
swingaway, length-adjustable, from 35.6 cm (14 in.)	NI/C	07.00
o 48.3 cm (19 in.)	N/C	97.00
90° footrests, detachable, swingaway, length-adjustable,		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	96.00	
n pair	86.00	1 40 00
each		140.00
elevating legrests, detachable, swingaway,		
ength-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)	150.00	
n pair	150.00	172.00
each		172.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
elevating legrests, compensating mechanism,		
detachable, swingaway, length-adjustable,		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
a pair	234.00	• 4 4 00
each		214.00
modification of footrest or legrest height to	72.00	NT/A
ander 35.6 cm (14 in.) or to over 48.3 cm (19 in.)	72.00	N/A
padded calfrests	N/C	20.00
contoured calfrests	54.00	
n pair	54.00	47.00
each louble calf strap	50.00	50.00
folding footplates, standard	N/C	16.00
olding footplates, standard	IV/C	10.00
i pair	38.00	
each	36.00	35.00
olding footplates, angle-adjustable and depth-adjustable		33.00
i pair	64.00	
each		48.00
oversized footplates, angle-adjustable and depth-adjustable		
a pair	74.00	
each		53.00
full-width footplate, angle-adjustable	138.00	170.00
Front impact guard with rollers		
a pair	32.00	
each		16.00
oe loops	20.00	
n pair	30.00	15.00
each	N/C	15.00
neel loops, length-adjustable	N/C	10.00
Wheels and frame		
Types of drive systems:		
smooth handrims		
a pair	88.00	
each		44.00
non-slip handrims		
a pair	148.00	
each		74.00
plastic-coated handrims		
ı pair	140.00	
each		70.00
combined handrims		
pair	148.00	
ach		74.00
ront anti-tip rollers	N/C	42.00
optional flared frame	95.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks:		
standard, push-to-lock	N/C	50.00
wheel lock extensions, retractable a pair	33.00	
each	33.00	16.00
wheel lock extensions, fixed		
a pair	40.00	
each		20.00
Types of forks:		
nigh forks	N/C	55.00
Rear axles:		
hreaded axles	N/C	5.00
quick-release axles	40.00	
a pair	68.00	39.00
each		39.00
Types of wheels:		
rear mag wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	30.00	
each	30.00	119.00
rear mag wheels, solid tires, 55.9 cm (22 in.)		
or 61.0 cm (24 in.)		
n pair	30.00	110.00
each spoked rear wheels, standard pressure,		119.00
50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	104.00
spoked rear wheels, solid tires, 50.8 cm (20 in.),	1,, 0	1000
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	70.00
poked rear wheels, semi-pneumatic tires,		
0.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	30.00	
i pair ach	30.00	85.00
ear mag wheels, semi-pneumatic tires,		03.00
50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)		
ı pair	60.00	
each		134.00
Front wheels, solid tires, 20.3 cm (8 in.), 17.8 cm (7 in.) or 15.2 cm (6 in.)	N/C	29.00
ront wheels, inner tube,	N/C	29.00
20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.),		
7.8 cm (7 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) or		
$5.2 \text{ cm } (6 \text{ in.}) \text{ X } 3.2 \text{ cm } (1^{1}/_{4} \text{ in.})$		
pair	30.00	44.00
each irless inserts for front wheels		44.00
pair	73.00	
ach	, 3.00	N/A
irless inserts for rear wheels		
pair	79.00	***
each		N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
reclining back *	699.00	699.00
spoke guards * a pair	114.00	
each		57.00

# DEVICE FROM: LES ÉQUIPEMENTS ADAPTÉS PHYSIPRO INC.

**PRICE** 

# POSITIONING BUGGY, ADULT, "CARDINAL" MODEL

\$1 760.00

## **Basic Component(s)**

#### **Body support system**

- folding back, angle-adjustable, height of 50.8 cm (20 in.)
- seat structure, width-adjustable, from 38.1 cm (15 in.) to 50.8 cm (20 in.), and depth-adjustable, from 40.6 cm (16 in.) to 55.9 cm (22 in.)
- rocker device for seat and back, from -10° to 35°
- seating height: 45.7 cm (18 in.)
- frame length: 88.9 cm (35 in.)
- push handles
- safety belt, velcro-type, auto-type

#### Armrests

- "U"-type armrests, detachable, flip-back, height-adjustable, from 20.3 cm (8 in.) to 38.1 cm (15 in.), short, long
- straight armrest pads, short, long
- · clothing guards, rigid

#### **Footrests**

- 60°, 70°, 75° footrests, detachable, swingaway, length-adjustable, from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- heel loops, length-adjustable
- · folding footplates, standard
- modification of footrest length

- · standard wheel locks, push-to-lock
- · standard forks
- · threaded axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)
- front anti-tip rollers
- tie-down points for adapted transport

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
folding back, height of 50.8 cm (20 in.)	N/C	N/A
push handles	N/C	N/A
safety belt, velcro-type	N/C	18.00
safety belt, auto-type	N/C	48.00
rocker device for seat and back, from $-10^{\circ}$ to $35^{\circ}$	N/C	N/A
Armrests:		
"U"-type armrests, detachable, flip-back,		
neight-adjustable, from 20.3 cm (8 in.)		
to 38.1 cm (15 in.), short or long	N/C	186.00
straight armrest pads, short	N/C	26.00
straight armrest pads, long	N/C	28.00
clothing guards, rigid	N/C	14.00
Footrests:		
60°, 70° or 75° footrests detachable, swingaway,		
ength-adjustable, from 30.5 cm (12 in.)		
to 45.7 cm (18 in.)	N/C	99.00
90° footrests, detachable, swingaway,		
ength-adjustable, from 25.4 cm (10 in.) to 40.6 cm (16 in.)		
a pair	60.00	
each		129.00
elevating legrests, detachable, swingaway,		
ength-adjustable		
a pair	376.00	
each		287.30
single calf strap	43.00	43.00
double calf strap	55.00	55.00
single calf strap, cushioned	80.00	80.00
double calf strap, cushioned	95.00	95.00
folding footplates, standard	N/C	40.00
folding footplates, angle-adjustable and		
depth-adjustable, non-skid		
a pair	70.00	
each		75.00
folding footplates, oversized, angle-adjustable and		
lepth-adjustable, non-skid		
n pair	100.00	
each		90.00
folding footplates, full-width, angle-adjustable and		
depth-adjustable, non-skid	140.00	110.00
neel loops, length-adjustable	N/C	12.00
oe loops		
ı pair	20.00	
each		22.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
modification of footrest length	N/C	40.00
padded calfrests a pair each	70.00	35.00
Wheels and frame Types of drive systems:		
smooth handrims a pair each	80.00	40.00
plastic-coated handrims a pair each	120.00	60.00
non-slip handrims a pair	120.00	
each front anti-tip rollers	N/C	60.00 43.00
Wheel locks: standard, push-to-lock	N/C	55.00
wheel lock extensions a pair each	30.00	15.00
Types of forks: standard forks	N/C	56.00
forks for 20.3 cm (8 in.) X 5.1 cm (2 in.) wheels a pair	18.00	
each		65.00
Rear axles: threaded axles	N/C	6.00
quick-release axles a pair each	98.00	55.00
Types of wheels: rear mag wheels, standard pressure, 30.5 cm (12 in.) rear mag wheels, standard pressure, 50.8 cm (20 in.),	N/C	60.00
55.9 cm (22 in.) or 61.0 cm (24 in.) a pair each	74.00	97.00
rear mag wheels, solid tires, 61.0 cm (24 in.) a pair each	30.00	75.00
rear mag wheels, solid tires, 30.5 cm (12 in.) a pair each	50.00	85.00

a pair acach 64.00 each 64.00 rear mag wheels, solid tires, 50.8 cm (20 in.) a pair 74.00 a pair		Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
each rear mag wheels, solid tires, 50.8 cm (20 in.) a pair apair a	rear mag wheels, solid tires, 55.9 cm (22 in.)		
rear mag wheels, solid tires, 50.8 cm (20 in.)  a pair  a pair	a pair	8.00	
a pair each spoked rear wheels, standard pressure, 50.8 cm (20 in.) a pair apair apa			64.00
each spoked rear wheels, standard pressure, 50.8 cm (20 in.) a pair a pa		74.00	
spoked rear wheels, standard pressure, 50.8 cm (20 in.) a pair b pair a pair b	• .	74.00	07.00
a pair each spoked rear wheels, standard pressure, 55.9 cm (22 in.) a pair each spoked rear wheels, standard pressure, 61.0 cm (24 in.) a pair each spoked rear wheels, standard pressure, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 50.8 cm (20 in.) a pair each spoked rear wheels, solid tires, 55.9 cm (22 in.) a pair each spoked rear wheels, solid tires, 55.9 cm (22 in.) a pair each spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.) front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1½ in.) a pair each front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1½ in.) a pair each front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1½ in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1¼ in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1¼ in.) a pair each spoked rear wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1¼ in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, solid tires, 55.00 cm (8 in.) X 3.2 cm (1¼ in.) a pair each spoked rear wheels, solid tires, 55.9 cm (22 in.) a pair each spoked rear wheels, solid tires, 55.9 cm (22 in.) a pair each spoked rear wheels, solid tires, 55.9 cm (22 in.) a pair each spoked rear wheels, inner tube, 55.0 cm (8 in.) X 3.2 cm (1¼ in.) a pair each spoked rear wheels, inner tube, 55.0 cm (8 in.) X 3.2 cm (1¼ in.) a pair each spoked			97.00
each spoked rear wheels, standard pressure, 55.9 cm (22 in.) a pair a pa		21.00	
spoked rear wheels, standard pressure, 55.9 cm (22 in.) a pair a pair each spoked rear wheels, standard pressure, 61.0 cm (24 in.) a pair each spoked rear wheels, standard pressure, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 50.8 cm (20 in.) a pair b pair		31.00	70.00
a pair each 92.00 spoked rear wheels, standard pressure, 61.0 cm (24 in.)  a pair 41.00 each 80.00 spoked rear wheels, solid tires, 50.8 cm (20 in.)  a pair 39.00 each 79.00 spoked rear wheels, solid tires, 55.9 cm (22 in.)  a pair 48.00 each 84.00 spoked rear wheels, solid tires, 55.9 cm (22 in.)  a pair 48.00 each 84.00 spoked rear wheels, solid tires, 61.0 cm (24 in.)  a pair 59.00 each 89.00 front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.) N/C 24.00 front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1½ in.) a pair each 12.00 each 13.00 front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1½ in.) each 13.00 each 15.2 cm (6 in.) X 3.2 cm (1½ in.) each 15.2 cm (6 in.) X 3.2 cm (1½ in.) each 15.00 each 15.0 cm (6 in.) X 3.2 cm (1¼ in.) each 15.2 cm (6 in.) X 3.2 cm (1¼ in.) each 15.2 cm (6 in.) X 3.2 cm (1¼ in.) each 15.2 cm (6 in.) X 3.2 cm (1¼ in.) each 15.2 cm (6 in.) X 3.2 cm (1¼ in.) each 15.2 cm (6 in.) X 3.2 cm (1¼ in.) each 15.2 cm (6 in.) X 3.2 cm (1¼ in.) each 15.2 cm (6 in.) X 3.2 cm (1¼ in.) each 15.2 cm (6 in.) X 3.2 cm (1¼ in.) each 15.2 cm (6 in.) X 3.2 cm (1¼ in.) each 15.2 cm (6 in.) X 3.2 cm (1¼ in.) each 15.2 cm (6 in.) X 3.2 cm (1¼ in.) each 15.2 cm (6 in.) X 3.2 cm (1¼ in.) each 15.2 cm (6 in.) X 3.2 cm (1¼ in.) front wheels a pair each 15.00 e			79.00
each spoked rear wheels, standard pressure, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 50.8 cm (20 in.) a pair each spoked rear wheels, solid tires, 55.9 cm (22 in.) a pair each spoked rear wheels, solid tires, 55.9 cm (22 in.) a pair each spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 59.00 each front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.) N/C 24.00 front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) solid tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.0 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.0 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.0 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.0 cm (8 in.) X 3.2 cm (1 in.) a pair each solid tires, 20.0 cm (8 in.) X 3.2 cm (1		38 00	
spoked rear wheels, standard pressure, 61.0 cm (24 in.) a pair b profit wheels, solid tires, 55.9 cm (22 in.)  a pair b profit wheels, solid tires, 61.0 cm (24 in.) a pair b profit wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), b profit wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) b profit wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) b profit wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) b profit wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) b profit wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 in.) b profit wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 in.) b profit wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 in.) b profit wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 in.) b profit wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 in.) b profit wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 in.) b profit wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) b profit profit wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) b profit profit wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) b profit profit wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 3.2 cm (1 in.) b profit profit profit wheels a pair b profit profit profit wheels a pair b profit profit profit profit profit wheels a pair b profit profit profit profit profit wheels a pair b profit		30.00	79.00
a pair each each spoked rear wheels, solid tires, 50.8 cm (20 in.) a pair each spoked rear wheels, solid tires, 55.9 cm (22 in.) a pair each spoked rear wheels, solid tires, 55.9 cm (22 in.) a pair each spoked rear wheels, solid tires, 55.9 cm (22 in.) a pair each spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.) N/C 24.00 front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) or 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) or 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) or 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) front wheels a pair each solution front wheels, semi-pneumatic tires, 20.3 cm (6 in.) X 3.2 cm (1 1/4 in.) front wheels, a pair			, ,
each spoked rear wheels, solid tires, 50.8 cm (20 in.) a a pair 39.00 spoked rear wheels, solid tires, 55.9 cm (22 in.) 48.00 each 79.00 spoked rear wheels, solid tires, 55.9 cm (22 in.) 48.00 each 84.00 spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair 59.00 each 89.00 front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 12.7 cm (5 in.) N/C 24.00 front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1½ in.) a pair a pair 12.00 a pair 12.00 each 12.00 a pair 12.00 each 12.00 e		41.00	
a pair each spoked rear wheels, solid tires, 55.9 cm (22 in.) a pair each spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.) front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 \(\frac{1}{4}\) in.) a pair each spoked rear wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 \(\frac{1}{4}\) in.) a pair each spoked rear wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 \(\frac{1}{4}\) in.) a pair each spoked rear wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 \(\frac{1}{4}\) in.) a pair each spoked rear wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 \(\frac{1}{4}\) in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each spoked rear wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 \(\frac{1}{4}\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(\frac{1}{4}\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(\frac{1}{4}\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(\frac{1}{4}\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(\frac{1}{4}\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(\frac{1}{4}\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(\frac{1}{4}\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(\frac{1}{4}\)	each		80.00
each spoked rear wheels, solid tires, 55.9 cm (22 in.)  a pair 48.00 each 84.00 spoked rear wheels, solid tires, 61.0 cm (24 in.)  a pair 59.00 each 89.00 front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 12.7 cm (5 in.) N/C 24.00 front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.)  a pair 12.00 each 13.00	spoked rear wheels, solid tires, 50.8 cm (20 in.)		
spoked rear wheels, solid tires, 55.9 cm (22 in.) a pair each spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.) front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) or 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair	a pair	39.00	
a pair each seach spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.) front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.) a pair each front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.) or 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each a pair each  110.00 each 79.00 airless inserts for 20.3 cm (8 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.) or 15.2 cm (6 in.) X 3.2 cm (1 \(^{1}\lambda_4\) in.)	each		79.00
each spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair 59.00 seach 59.00 front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 59.00 front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) a pair 24.00 front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) a pair 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) front wheels, inner tube, 20.3 cm (6 in.) X 3.2 cm (1 1/4 in.) front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair 62.00 front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) front wheels inserts for 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) front wheels a pair 55.00 front wheels inserts for 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) front wheels a pair 56.00 front wheels a pair 56.00 front wheels a pair 56.00 front wheels 66.00			
spoked rear wheels, solid tires, 61.0 cm (24 in.) a pair each front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.) N/C 24.00 front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1½ in.) a pair each 70.20 cm (8 in.) X 5.1 cm (2 in.) a pair each 50.25 front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1½ in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1½ in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1½ in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front S. 2 cm (6 in.) X 3.2 cm (1½ in.) a pair each 55.00 front sheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) 55.00 front sheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) 55.00 front sheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) 55.00 front sheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (5 in.) 55.00 front sheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (5 in.) 55.00 front sheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (5 in.) 55.00 front sheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (5 in.) 55.00 front sheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (5 in.) 55.00 front sheels, s		48.00	
a pair each front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.) front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) or 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) or 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) or 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) front wheels a pair each  56.00 N/A	each		84.00
each front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.) front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) or 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each a pair each  110.00 each front wheels, inner tube, 15.2 cm (1 1/4 in.) or 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) or 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) front wheels a pair each  56.00  N/A		<b>50.00</b>	
front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)  front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) or 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each arpair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each arpair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, inserts for 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) or 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) front wheels a pair each  56.00  N/A		59.00	00.00
15.2 cm (6 in.), 12.7 cm (5 in.)  front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.)  a pair each front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.)  or 20.3 cm (8 in.) X 5.1 cm (2 in.)  a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.)  a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.)  a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)  a pair each  110.00  79.00  airless inserts for 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.)  or 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) front wheels a pair each  56.00  N/A			89.00
front wheels, solid tires, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.)  a pair each front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) or 20.3 cm (8 in.) X 5.1 cm (2 in.)  a pair each front wheels, inner tube, 20.3 cm (6 in.) X 3.2 cm (1 1/4 in.)  a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.)  a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.)  a pair each 110.00  79.00  atriless inserts for 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) or 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) front wheels a pair each  56.00  N/A		N/C	24.00
a pair each front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) or 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each 110.00 each 79.00 airless inserts for 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) or 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) front wheels a pair each 56.00		IN/C	24.00
each front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) or 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) a pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each 110.00  79.00 airless inserts for 20.3 cm (8 in.) X 3.2 cm (1 1/4 in.) or 15.2 cm (6 in.) X 3.2 cm (1 1/4 in.) front wheels a pair each  56.00		12.00	
front wheels, inner tube, $20.3 \text{ cm } (8 \text{ in.}) \text{ X } 3.2 \text{ cm } (1^{1}/_4 \text{ in.})$ or $20.3 \text{ cm } (8 \text{ in.}) \text{ X } 5.1 \text{ cm } (2 \text{ in.})$ a pair 52.50 each 50.25 front wheels, inner tube, $15.2 \text{ cm } (6 \text{ in.}) \text{ X } 3.2 \text{ cm } (1^{1}/_4 \text{ in.})$ apair 62.00 each 55.00 front wheels, semi-pneumatic tires, 20.3 cm $(8 \text{ in.}) \text{ X } 5.1 \text{ cm } (2 \text{ in.})$ a pair 110.00 each 79.00 airless inserts for $20.3 \text{ cm } (8 \text{ in.}) \text{ X } 3.2 \text{ cm } (1^{1}/_4 \text{ in.})$ or $15.2 \text{ cm } (6 \text{ in.}) \text{ X } 3.2 \text{ cm } (1^{1}/_4 \text{ in.})$ front wheels a pair 56.00 each N/A		12.00	30.00
or 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair 52.50 each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) a pair 62.00 each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair a pair 110.00 each 79.00 airless inserts for 20.3 cm (8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) or 15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) front wheels a pair each 55.00			20.00
a pair 52.50 each 50.25 front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) a pair 62.00 each 55.00 front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair 110.00 each 79.00 airless inserts for 20.3 cm (8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) or 15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) front wheels a pair 56.00 N/A			
each front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) a pair 62.00 each 55.00 front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair 110.00 each 79.00 airless inserts for 20.3 cm (8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) or 15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) front wheels a pair 56.00 each N/A		52.50	
a pair 62.00 seach 55.00 front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair 110.00 seach 79.00 airless inserts for 20.3 cm (8 in.) X 3.2 cm ( $^{1}$ /4 in.) or 15.2 cm (6 in.) X 3.2 cm ( $^{1}$ /4 in.) front wheels a pair 56.00 seach	each		50.25
each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each 110.00 each 79.00 airless inserts for 20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) or 15.2 cm (6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) front wheels a pair each  55.00  79.00	front wheels, inner tube, 15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.)		
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) X 5.1 cm (2 in.) a pair 110.00 each 79.00 airless inserts for 20.3 cm (8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) or 15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) front wheels a pair 56.00 each N/A	a pair	62.00	
20.3 cm (8 in.) X 5.1 cm (2 in.) a pair each 79.00 airless inserts for 20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) or 15.2 cm (6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) front wheels a pair each  110.00 79.00 N/A	each		55.00
a pair each 79.00 airless inserts for 20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) or 15.2 cm (6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) front wheels a pair each  110.00 79.00 79.00 N/A	front wheels, semi-pneumatic tires,		
each 79.00 airless inserts for 20.3 cm (8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) or 15.2 cm (6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) front wheels a pair each  56.00 N/A		110.00	
airless inserts for 20.3 cm (8 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) or 15.2 cm (6 in.) X 3.2 cm ( $1^{1}/_{4}$ in.) front wheels a pair 56.00 each		110.00	70.00
or $15.2~{\rm cm}$ (6 in.) X $3.2~{\rm cm}$ (1 $^{1}/_{4}$ in.) front wheels a pair 56.00 each			/9.00
a pair 56.00 each N/A			
each N/A		56.00	
		50.00	N/A
wirious misorius ron 20.3 cm (0 m.) /x 3.1 cm (2 m.)			11/71
front wheels			
a pair 108.00		108.00	
	each	100.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
airless inserts for 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) rear wheels a pair each	70.00	N/A
Component(s) under Special Consideration		
reclining back with cylinder *	280.00	280.00
spoke guards * a pair	84.00	12.00
each		42.00

#### DEVICE FROM: EVEREST& JENNINGS CANADA LTD.

**PRICE** 

# POSITIONING BUGGY, CHILD, "K-SHARK" MODEL

\$1 695.00

# Basic Component(s)

## **Body support system**

- folding back, angle-adjustable, height of 25.4 cm (10 in.) to 40.6 cm (16 in.)
- seating height: from 43.2 cm (17 in.) to 55.9 cm (22 in.)
- seat width: from 25.4 cm (10 in.) to 40.6 cm (16 in.)
- seat depth: from 25.4 cm (10 in.) to 40.6 cm (16 in.), from 43.2 cm (17 in.) to 50.8 cm (20 in.)
- · rocker device for seat and back
- · push handles integrated into backposts
- safety belt, auto-type

### **Armrests**

- "T"-type armrests, height-adjustable, short, long
- straight armrest pads, short, long

#### **Footrests**

- 75° footrests, detachable, swingaway, length-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.)
- 90° footrests, detachable, swingaway, length-adjustable, from 20.3 cm (8 in.) to 30.5 cm (12 in.)
- · folding footplates, standard
- 90° footplate, full-width

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.)
- · standard wheel locks, push-to-lock
- foot-activated wheel locks
- · high forks
- · threaded axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires (urethane), 50.8 cm (20 in.), 55.9 cm (22 in.)
- spoked rear wheels, standard pressure, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)
- front wheels, solid tires, 12.7 cm (5 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.)
- front anti-tip rollers

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
folding back, angle-adjustable, height of		
25.4 cm (10 in.) to 40.6 cm (16 in.)	N/C	N/A
push handles integrated into backposts	N/C	N/A
safety belt, auto-type	N/C	29.00
seat cushion, flat, foam, 5.1 cm (2 in.)	58.00	58.00
seat cushion, flat, foam, 7.6 cm (3 in.)	58.00	58.00
adjustable seat and back	95.00	95.00
rocker device for seat and back	N/C	N/A
Armrests:		
"T"-type armrests, height-adjustable, short and long	N/C	171.00
straight armrest pads short	N/C	13.00
straight armrest pads, long	N/C	13.00
Footrests:		
75° footrests, detachable, swingaway,		
length-adjustable, from 20.3 cm (8 in.) to		
30.5 cm (12 in.)	N/C	103.00
90° footrests, detachable, swingaway,		
length-adjustable, from 20.3 cm (8 in.) to		
30.5 cm (12 in.)	N/C	119.00
modification of footrest length	87.00	N/A
folding footplates, standard	N/C	36.00
90° footplate, full-width	N/C	140.00
angle-adjustable footplates		
a pair	69.00	
each		105.00
full-width footplate, angle-adjustable	124.00	98.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
<b>Types of drive systems:</b> anodized aluminum handrims, 50.8 cm (20 in.) or 55.9 cm (22 in.)	N/C	45.00
plastic-coated handrims a pair each	68.00	79.00
handrims with vertical projections, 61.0 cm (24 in.) a pair each	158.00	124.00
handrims with oblique projections, 61.0 cm (24 in.) a pair	158.00	
each front anti-tip rollers	N/C	124.00 44.00
Wheel locks: standard wheel locks, push-to-lock standard wheel locks, pull-to-lock	N/C	54.00
a pair each	16.00	52.00
wheel lock extensions a pair each	38.00	39.00
anti-rollback brakes a pair	106.00	
each foot-activated wheel locks	N/C	53.00 N/A
Types of forks: high forks	N/C	50.00
fork-locking mechanisms a pair each	88.00	44.00
Rear axles: threaded axles	N/C	12.00
quick-release axles	80.00	12.00
a pair each	ou.uu	52.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
rear mag wheels, standard pressure,		
30.5 cm (12 in.)	N/C	85.00
rear mag wheels, standard pressure,		
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	118.00
rear mag wheels, solid tires (urethane),		
50.8 cm (20 in.) or 55.9 cm (22 in.)	N/C	118.00
spoked rear wheels, standard pressure,		
50.8 cm (20 in.) or 55.9 cm (22 in.)	N/C	125.00
spoked rear wheels, solid tires, 50.8 cm (20 in.)		
or 55.9 cm (22 in.)	N/C	120.00
front wheels, semi-pneumatic tires,		
12.7 cm (5 in.) X 5.1 cm (2 in.)	80.00	60.00
front wheels, semi-pneumatic tires, 15.2 cm (6 in.)	N/C	20.00
front wheels, solid tires, 12.7 cm (5 in.)	N/C	20.00
front wheels, inner tube,		
20.3 cm (8 in.) X 4.4 cm $(1^{3}/_{4}$ in.),		
$20.3 \text{ cm } (8 \text{ in.}) \text{ X } 3.2 \text{ cm } (1^{1}/_{4} \text{ in.}) \text{ or}$		
15.2 cm (6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)		
a pair	44.00	
each		42.00
airless inserts for 50.8 cm (20 in.) or 55.9 cm (22 in.) rear wheels		
a pair	60.00	27/1
each		N/A

### DEVICE FROM: INVACARE CANADA INC.

**PRICE** 

# POSITIONING BUGGY, CHILD, "ACTION ORBIT" MODEL

\$1 602.00

# **Basic Component(s)**

### **Body support system**

- folding back, height of 50.8 cm (20 in.)
- seating height: from 41.9 cm  $(16^{1}/_{2} \text{ in.})$  to 52.1 cm  $(20^{1}/_{2} \text{ in.})$
- seat width: 25.4 cm (10 in.), 27.9 cm (11 in.), 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.)
- seat depth: from 25.4 cm (10 in.) to 40.6 cm (16 in.)
- frame length: 96.5 cm (38 in.)
- · rocker device for seat and back
- · push handles
- angle-adjustable push handle, raised push handle
- safety belt, velcro-type, auto-type

#### **Armrests**

- "I"-type armrests, flip-back, height-adjustable, from 18.4 cm (7<sup>1</sup>/<sub>4</sub> in.) to 23.5cm (9<sup>1</sup>/<sub>4</sub> in.), short, long
- straight armrest pads, short, long
- · tubular armrests

#### **Footrests**

- 90° footrests, detachable, swingaway, length-adjustable, from 14.0 cm (5½ in.) to 29.2 cm (11½ in.)
- 60°, 70° footrests, length-adjustable, from 24.8 cm (9³/4 in.) to 35.6 cm (14 in.)
- 60° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70° footrests, detachable, swingaway, length-adjustable, from 33.0 cm (13 in.) to 43.2 cm (17 in.)
- 70° footrests, "V"-shaped, detachable, swingaway, length-adjustable, from 36.8 cm (14¹/₂ in.) to 43.2 cm (17 in.)
- heel loops, length non-adjustable
- heel loops, length-adjustable
- · folding footplates, standard

### Wheels and frame

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- · standard wheel locks, push-to-lock
- · standard forks
- quick-release axles
- rear mag wheels, standard pressure,
   30.5 cm (12 in.) X 5.7 cm (2<sup>1</sup>/<sub>4</sub> in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.),
   55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)
- front anti-tip rollers

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
folding back, height of 50.8 cm (20 in.)	N/C	N/A
rocker device for seat and back	N/C	N/A
rigid seat, flat	57.00	57.00
push handles	N/C	37.00
safety belt, velcro-type	N/C	20.00
safety belt, auto-type	N/C	30.00
angle-adjustable push handle	N/C	175.00
raised push handle	N/C	105.00
seat cushion, flat, foam, 5.1 cm (2 in.)	55.00	55.00
seat cushion, flat, foam, 7.6 cm (3 in.)	55.00	55.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
"I"-type armrests, flip-back, height-adjustable,		
from 18.4 cm $(7^{1}/_{4} \text{ in.})$ to 23.5 cm $(9^{1}/_{4} \text{ in.})$ ,		
short or long	N/C	53.00
"T"-type armrests, detachable, height-adjustable,		
from 12.7 cm (5 in.) to 20.3 cm (8 in.) or from		
20.3 cm (8 in.) to 27.9 cm (11 in.), short or long a pair	82.00	
each	82.00	94.00
straight armrest pads, short	N/C	26.00
straight armrest pads, short	N/C	26.00
tubular armrests	N/C	10.00
would will obto	1,00	10.00
Footrests:		
60° footrests, detachable, swingaway,		
length-adjustable, from 35.6 cm (14 in.)		
to 48.3 cm (19 in.), or 70° footrests, detachable,		
swingaway, length-adjustable from 33.0 cm (13 in.) to 43.2 cm (17 in.)	N/C	78.00
90° footrests, detachable, swingaway,	N/C	78.00
length-adjustable, from 14.0 cm ( $5^{1}/_{2}$ in.)		
to 29.2 cm $(11^{1/2} in.)$	N/C	147.00
70° footrests, "V"-shaped, detachable, swingaway,	1,70	117.00
length-adjustable, from 36.8 cm $(14^{1/2} \text{ in.})$		
to 43.2 cm (17 in.)	N/C	129.00
60° or 70° footrests, length-adjustable, from 24.8 cm		
$(9^{3}/_{4} \text{ in.})$ to 35.6 cm (14 in.)	N/C	147.00
single calf strap	43.00	43.00
folding footplates, standard	N/C	37.00
folding footplates, angle-adjustable	72.00	
a pair	72.00	72.00
each	N/C	73.00
heel loops, non-adjustable heel loops, length-adjustable	N/C N/C	3.00 10.00
heel loops and ankle straps	N/C	10.00
a pair	32.00	
each	32.00	16.00
Wheels and frame		
Types of drive systems:		
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	22.00
handrims with oblique or vertical projections	IN/C	33.00
a pair	155.00	
each	155.00	111.00
plastic-coated handrims		111.00
a pair	52.00	
each		59.00
front anti-tip rollers	N/C	48.00
growth kit	N/A	125.00

	of wheel chair	replacement of component (unit price)
Wheel locks:		
standard wheel locks, push-to-lock	N/C	44.00
wheel lock extensions a pair	32.00	
each	32.00	16.00
Types of forks:	NG	22.00
standard forks	N/C	33.00
Rear axles:		
quick-release axles	N/C	53.00
Types of wheels:		
rear mag wheels, standard pressure, 30.5 cm		
$(12 \text{ in.}) \times 5.7 \text{ cm} (2^{1}/_{4} \text{ in.})$	N/C	52.00
rear mag wheels, standard pressure, 50.8 cm		
(20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	69.00
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	42.00
front wheels, solid tires, 20.3 cm (8 in.),	14/6	42.00
15.2 cm (6 in.) or 12.7 cm (5 in.)	N/C	23.00
front wheels, inner tube, 20.3 cm		
(8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	32.00	
a pair each	32.00	39.00
front wheels, inner tube, 15.2 cm		37.00
$(6 \text{ in.}) \times 3.2 \text{ cm} (1^{1}/_{4} \text{ in.})$		
a pair	32.00	20.00
each airless inserts for 20.3 cm (8 in.) front wheels		39.00
a pair	95.00	
each	20.00	N/A
airless inserts for rear wheels		
a pair	99.00	<b>T</b> .T / A
each		N/A
Component(s) under Special Consideration		
contracture footrest, bilateral-angle adjustable *	243.00	321.00
reclining back *	438.00	718.00

# DEVICE FROM: LES ÉQUIPEMENTS ADAPTÉS PHYSIPRO INC.

**PRICE** 

## POSITIONING BUGGY, CHILD, "ROSSIGNOL" MODEL

\$1 585.00

## **Basic Component(s)**

## **Body support system**

- folding back, angle-adjustable, height of 50.8 cm (20 in.)
- seat structure, width-adjustable, from 25.4 cm (10 in.) to 40.6 cm (16 in.) and depth-adjustable, from 27.9 cm (11 in.) to 40.6 cm (16 in.)
- · rocker device for seat and back
- seating height: 45.7 cm (18 in.)
- push handles
- safety belt, velcro-type, auto-type

#### Armrests

- "U"-type armrests, detachable, flip-back, height-adjustable, from 17.8 cm (7 in.) to 27.9 cm (11 in.), short, long
- straight armrest pads, short, long
- clothing guards, rigid

#### **Footrests**

- 60°, 70°, 75°, 90° footrests, detachable, swingaway, length-adjustable, from 17.8 cm (7 in.) to 33.0 cm (13 in.)
- heel loops, length-adjustable
- folding footplates, standard
- modification of footrest length

#### Wheels and frame

- standard wheel locks, push-to-lock
- · standard forks
- · threaded axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)
- front anti-tip rollers
- tie-down points for adapted transport

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
folding back, angle-adjustable, height	NIG	37/4
of 50.8 cm (20 in.)	N/C	N/A
push handles safety belt, velcro-type	N/C N/C	N/A
safety belt, veicro-type	N/C N/C	18.00 48.00
cocker device for seat and back	N/C N/C	48.00 N/A
ocker device for seat and back	IV/C	IN/A
Armrests:		
'U"-type armrests, detachable, flip-back,		
neight-adjustable, from 17.8 cm (7 in.)	N/G	106.00
o 27.9 cm (11 in.), short or long	N/C	186.00
straight armrest pads short	N/C N/C	26.00
straight armrest pads long	N/C N/C	28.00 14.00
clothing guards, rigid	N/C	14.00
Footrests:		
$50^{\circ}$ , $70^{\circ}$ , $75^{\circ}$ or $90^{\circ}$ footrests, detachable,		
wingaway, length-adjustable, from 17.8 cm		
7 in.) to 33.0 cm (13 in.)	N/C	99.00
elevating legrests, detachable,		
wingaway, length-adjustable	25.60	
pair	376.60	207.20
each		287.30
padded calfrests	70.00	
a pair each	70.00	35.00
ingle calf strap	43.00	43.00
louble calf strap	55.00	55.00
ingle calf strap, cushioned	80.00	80.00
louble calf strap, cushioned	95.00	95.00
Folding footplates, standard	N/C	40.00
Folding footplates, angle-adjustable and	1,, 0	
lepth-adjustable, non-skid		
pair	70.00	
each		75.00
olding footplates, oversized, angle-adjustable		
nd depth-adjustable, non-skid		
pair	100.00	
ach		90.00
olding footplates, full-width, angle-adjustable		
nd depth-adjustable, non-skid	140.00	110.00
eel loops, length-adjustable	N/C	12.00
pe loops		
pair	20.00	
ach		22.00
nodification of footrest length	N/C	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems: mooth handrims		
nicon nandrinis . pair	80.00	
ach		40.00
lastic-coated handrims	120.00	
pair ach	120.00	60.00
on-slip handrims		00.00
pair	120.00	
ach	27/0	60.00
ont anti-tip rollers	N/C	43.00
Vheel locks:		
andard, push-to-lock	N/C	55.00
heel lock extensions	20.00	
pair ach	30.00	15.00
acii		15.00
ypes of forks:		
tandard forks	N/C	56.00
orks for 20.3 cm (8 in.) X 5.1 cm (2 in.) wheels pair	18.00	
ach	18.00	65.00
Rear axles:	NIC	c 00
nreaded axles uick-release axles	N/C	6.00
pair	98.00	
ach		55.00
9		
Chassis: e-down points for adapted transport	N/C	N/A
e down points for adapted transport	14/6	IV/A
ypes of wheels:		
ear mag wheels, standard pressure,	NI/C	<i>c</i> 0.00
0.5 cm (12 in.) ear mag wheels, standard pressure,	N/C	60.00
0.8 cm (20 in.) or 55.9 cm (22 in.)		
pair	74.00	
ach		97.00
ear mag wheels, solid tires, 50.8 cm (20 in.)	74.00	
pair ach	/4.00	97.00
ar mag wheels, solid tires, 30.5 cm (12 in.)		71.00
pair	50.00	
ach		85.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
rear mag wheels, solid tires, 55.9 cm (22 in.)		
a pair	8.00	
each		64.00
spoked rear wheels, standard pressure,		
50.8 cm (20 in.)		
a pair	31.00	
each		79.00
spoked rear wheels, standard pressure,		
55.9 cm (22 in.)		
ı pair	38.00	
each		79.00
spoked rear wheels, solid tires, 50.8 cm (20 in.)		
ı pair	39.00	
each		79.00
spoked rear wheels, solid tires, 55.9 cm (22 in.)		
a pair	48.00	
each		84.00
Front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm		
1 in.), 15.2 cm (6 in.) or 12.7 cm (5 in.)	N/C	24.00
Front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm		
(1 <sup>1</sup> / <sub>4</sub> in.), 20.3 cm (8 in.) X 5.1 cm (2 in.)		
a pair	53.00	
each		50.00
Front wheels, inner tube, 15.2 cm		
6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	42.00	
n pair	62.00	
each		55.00
Front wheels, semi-pneumatic tires, 20.3 cm		
8 in.) X 5.1 cm (2 in.)	110.00	
ı pair	110.00	<b>5</b> 0.00
each		79.00
Front wheels, solid tires, 20.3 cm		
8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	12.00	
n pair	12.00	20.00
each		30.00
airless inserts for 20.3 cm (8 in.) X 3.2 cm		37/4
$1^{1/4}$ in.) or 15.2 cm (6 in.) X 3.2 cm ( $1^{1/4}$ in.) front wheels	<b>7</b> < 00	N/A
pair	56.00	37/4
each		N/A
airless inserts for 20.3 cm (8 in.) X 5.1 cm		
2 in.) front wheels	100.00	
ı pair	108.00	37/4
each		N/A
irless inserts for 30.5 cm (12 in.), 50.8 cm (20 in.)		
or 55.9 cm (22 in.) rear wheels	70.00	
pair	70.00	****
each		N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
reclining back with cylinder * spoke guards, 55.9 cm (22 in.) *	280.00	280.00
a pair each	84.00	42.00

### DEVICE FROM: SUNRISE MEDICAL CANADA INC.

**PRICE** 

# POSITIONING BUGGY, CHILD, "ZIPPIE TS" MODEL

\$1,600.00

## **Basic Component(s)**

# **Body support system**

- folding back, angle-adjustable
- backposts with push handles at 54.6 cm (21<sup>1</sup>/<sub>2</sub> in.), 62.2 cm (24<sup>1</sup>/<sub>2</sub> in.), 69.9 cm (27<sup>1</sup>/<sub>2</sub> in.)
- seat width: from 25.4 cm (10 in.) to 40.6 cm (16 in.)
- seat depth: from 33.0 cm (13 in.) to 50.8 cm (20 in.)
- front seating height: from 41.3 cm (16<sup>1</sup>/<sub>4</sub> in.) to 47.6 cm (18<sup>3</sup>/<sub>4</sub> in.)
- safety belt, velcro-type, auto-type
- growth kit, including cross-bars (once only, during first 3 years, for first user)
- stroller handle

### **Armrests**

- "T"-type armrests, detachable, height-adjustable, from 19.1 cm (7<sup>1</sup>/<sub>2</sub> in.) to 30.5 cm (12 in.), short, long
- · straight armrest pads, short, long
- tubular armrests

# **Footrests**

- 90° footrests, fixed, length-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- 60°, 70° footrests, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70°, 80°, 90° footrests, detachable, swingaway, length-adjustable, from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- 70°, 80°, 90° footrests, heavy-duty, detachable, non flip-back
- heel loops, length-adjustable
- folding footplates

### Wheels and frame

- front anti-tip rollers
- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks 15.2 cm (6 in.); short forks,
   13.3 cm (5<sup>1</sup>/<sub>4</sub> in.); high forks 17.8 cm (7 in.);
   compatible with 12.7 cm (5 in.), 15.2 cm (6 in.)
   and 20.3 cm (8 in.) wheels
- 17.8 cm (7 in.) forks for 20.3 cm (8 in.) X 5.1 cm (2 in.) wheels
- fork stems,  $+ 1.0 \text{ cm} (\frac{3}{4} \text{ in.}), + 3.8 \text{ cm} (\frac{11}{2} \text{ in.})$
- quick-release axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.),
   55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) X 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.) X 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
headrest, small	86.00	89.00
headrest, medium	91.00	98.00
headrest, large	97.00	102.00
articulated headrest mounting	147.00	160.00
transversal bar for headrest mounting	185.00	196.00
folding back, angle-adjustable	N/C	N/A
rigid seat, flat, adjustable	115.00	120.00
growth kit including cross-bars (once only,		
during first 3 years, for first user)	N/C	N/A
back handles, adjustable by 15.2 cm (6 in.),		
swivel	75.00	N/A
stroller handle	N.S.	64.00
backposts with push handles at 54.6 cm		
$(21^{1/2} \text{ in.}), 62.2 \text{ cm } (24^{1/2} \text{ in.}), 69.9 \text{ cm } (27^{1/2} \text{ in.})$	N/C	N/A
safety belt, velcro-type	N/C	26.25
safety belt, auto-type	N/C	39.00
safety belt, airplane-type	47.00	73.25
safety belt, airplane-type, padded	70.00	96.25

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
'T"-type armrests, detachable, height-adjustable,		
from 19.1 cm ( $7^{1}/_{2}$ in.) to 30.5 cm (12 in.),		
short or long	N/C	125.75
T"-type armrests, flip-back, height-adjustable,		
from 16.5 cm ( $6^{1/2}$ in.) to 33.0 cm (13 in.),		
hort or long	120.00	
pair ach	120.00	105 75
acn ubular armrests	N/C	185.75 1.60
traight armrest pads, long	N/C N/C	15.75
traight armrest pads, long traight armrest pads short	N/C	14.00
lothing guards, rigid	IV/C	14.00
pair	86.00	
ach	00.00	63.00
		00.00
Footrests:		
00° footrests, fixed, length-adjustable, from		
20.3 cm (8 in.) to 33.0 cm (13 in.)	N/C	N/A
50° or 70° footrests, detachable, swingaway,		
ength-adjustable, from 35.6 cm (14 in.)		
o 48.3 cm (19 in.)	N/C	50.00
70°, 80° or 90° footrests, detachable,		
wingaway, length-adjustable, from 20.3 cm	N/C	<b>50</b> .00
8 in.) to 33.0 cm (13 in.)	N/C	52.00
70°, 80° or 90° footrests, heavy-duty,	N/C	76.00
letachable, non flip-back	N/C	76.00
0° elevating legrests, detachable, wingaway, length-adjustable, from		
0.3 cm (8 in.) to 33.0 cm (13 in.)		
pair	66.00	
ach	00.00	83.00
elevating legrests, detachable, swingaway		03.00
nd length-adjustable		
pair	100.00	
ach		100.00
nodification of footrest length from 48.3 cm		
19 in.) to 52.1 cm $(20^{1}/_{2} \text{ in.})$	29.00	28.00
nodification of length of 90° footrests		
y + 5.1  cm  (2  in.)  or by  +10.2  cm  (4  in.)	29.00	14.50
nodification of fixed footrest length to		
7.6 cm (3 in.) or 12.7 cm (5 in.)	29.00	14.50
ingle calf strap	17.00	17.00
olding footplates	N/C	46.00
olding footplates, angle-adjustable	40.00	
pair	49.00	70.50
ach		70.50

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
full-width footplate, angle-adjustable full-width footplate, rigid footrest mountings, from 17.8 cm (7 in.)	79.00 85.00	171.00 177.00
to 34.3 cm $(13^{1}/_{2}$ in.) a pair	51.50	24.70
each neel loops, length-adjustable	N/C	31.50 9.50
Wheels and frame Types of drive systems :		
one-arm dual handrim drive anodized aluminum handrims, 50.8 cm (20 in.),	520.00	655.00
55.9 cm (22 in.) or 61.0 cm (24 in.) nandrims with oblique or vertical projections	N/C	55.00
a pair	38.00	74.00
plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) a pair each	51.00	80.50
non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) a pair	84.00	97.00
each plastic-coated handrims for one-arm drive front anti-tip rollers front anti-tippers	51.00 N/C	N/A 20.50
a pair each	52.50	26.25
cane holder	42.00	42.00
Wheel locks: standard, push-to-lock or pull-to-lock wheel lock extensions, 15.2 cm (6 in.)	N/C	37.00
a pair each anti-rollback brakes	25.00	12.50
a pair each Foot-activated wheel locks	63.00	31.50
a pair each	20.00	94.00
Types of forks: tandard forks, 15.2 cm (6 in.); short forks, 3.3 cm $(5^{1}/_{4} \text{ in.})$ ; or high forks 17.8 cm (7 in.);		
compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels	N/C	29.50
7.8 cm (7 in.) forks for 20.3 cm (8 in.) X 5.1 cm 2 in.) wheels	N/C	34.00
ork-locking mechanisms a pair each	42.00	21.00
fork stems, $+ 1.0 \text{ cm} (\frac{3}{4} \text{ in.}) \text{ or } + 3.8 \text{ cm} (\frac{1^{1}}{2} \text{ in.})$	N/C	15.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Rear axles:		
quick-release axles	N/C	31.00
axle extension plates		
a pair	42.00	
each		48.00
Types of wheels:		
rear mag wheels, standard pressure,		
50.8 cm (20 in.)	N/C	126.00
rear mag wheels, standard pressure, 55.9 cm		
(22 in.) or 61.0 cm (24 in.)	N/C	105.00
rear mag wheels, solid tires, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	126.00
rear mag wheels, standard pressure,		
30.5 cm (12 in.)	N/C	120.00
rear mag wheels, standard pressure,		
40.6 cm (16 in.)		
a pair	30.00	105.00
each		135.00
front wheels, solid tires, 20.3 cm	N/C	<b>50.00</b>
(8 in.) X 2.5 cm (1 in.)	N/C	58.00
front wheels, solid tires, 15.2 cm (6 in.) front wheels, solid tires, 12.7 cm (5 in.)	N/C	57.00
	N/C	43.50
front wheels, inner tube, 20.3 cm (8 in.) X 5.1 cm (2 in.)		
a pair	45.00	
each	43.00	66.00
front wheels, inner tube, 20.3 cm		00.00
(8 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	N/C	58.00
front wheels, inner tube, 15.2 cm	14/6	30.00
(6 in.) X 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	N/C	57.50
front wheels, semi-pneumatic tires,	1,70	57.60
12.7 cm (5 in.) X 3.8 cm ( $1^{1}/_{2}$ in.)		
or 15.2 cm (6 in.) X 3.8 cm ( $1^{1}/_{2}$ in.)		
a pair	76.50	
each		81.75
front wheels, semi-pneumatic tires, 20.3 cm		
$(8 \text{ in.}) \text{ X } 3.8 \text{ cm } (1^{1}/_{2} \text{ in.})$		
a pair	95.00	
each		91.00
airless inserts for 20.3 cm (8 in.) X 5.1 cm		
(2 in.) front wheels	10.100	
a pair	106.00	
each		N/A
airless inserts for 30.5 cm (12 in.), 50.8 cm		
20 in.), 55.9 cm (22 in.) and 61.0 cm (24 in.)		
ear wheels	<b>71.00</b>	
n pair	51.00	<b>NT/A</b>
each		N/A

4269

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
spoke guards * a pair each	64.00	32.00
DIVISION III STROLLERS		
DEVICE		PRICE
"Buggy Major"-type stroller, including footrests		
less than 3 years of age * 3 years of age and over		460.00 460.00
Available Component(s)		
intermediate support seat padded seat rigid back harness other components		93.00 69.60 46.00 34.80 S.C.
WARRANTY PERIOD: 12 months		
DEVICE		
Other strollers *		S.C.