# Regulations and other acts

# **Notice RAMQ 001-2003**

Health Insurance Act (R.S.Q., c. A-29)

# Devices which compensate for a physical deficiency — Amendments

Regulation dated 21 May 2003, made by the Régie de l'assurance maladie du Québec to amend the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act

THE RÉGIE DE L'ASSURANCE MALADIE DU QUÉBEC,

CONSIDERING the fifth paragraph of section 3 and section 72.1 of the Health Insurance Act (R.S.Q., c. A-29);

CONSIDERING that it is necessary to amend certain lists of locomotor and posture assists contained in the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act;

GIVES NOTICE

THAT the Régie, by resolution of its board of directors, CA-399-03-09 dated 21 May 2003, made the Regulation to amend the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act, the text of which appears below.

Québec, 21 May 2003

André-Gaétan Corneau, Secretary General of the Régie de l'assurance maladie du Québec

# Regulation to amend the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act\*

Health Insurance Act (R.S.Q., c. A-29, s. 3, 5th and 10th pars. and s. 72.1)

- **1.** The Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act is amended by replacing Divisions I, II and III of Part I of Chapter V of Title Two by the Divisions appearing in Schedule I to this Regulation.
- **2.** This Regulation comes into force on 1 June 2003.

<sup>\*</sup> The Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act, made by Order in Council 612-94 dated 27 April 1994 (1994, G.O. 2, 1589), was last amended by the regulation made by Order in Council 999-2002 dated 28 August 2002 (2002, G.O. 2, 4729). For previous amendments, refer to the *Tableau des modifications et Index sommaire*, Éditeur officiel du Québec, 2003, updated to 1 March 2003.

# SCHEDULE I

# CHAPTER V

LISTS

LOCOMOTOR AND POSTURE ASSISTS

#### PART I

LOCOMOTOR ASSISTS

# **DIVISION I**

WHEEL CHAIRS

§1. Manual wheel chairs

DEVICE FROM: INVACARE CANADA INC.

PRICE

# MANUAL WHEEL CHAIR, "MVP" MODEL

\$1 150.00

# **Basic Component(s)**

# **Body support system**

- fixed back, height-adjustable from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- seat heights:  $37.5 \text{ cm} (14^3/_4 \text{ in.}), 54.0 \text{ cm} (21^1/_4 \text{ in.})$
- seat width: from 38.1 cm (15 in.) to 45.7 cm (18 in.)
- seat depth: from 33.0 cm (13 in.) to 45.7 cm (18 in.)
- · supple seat and back, nylon
- push handles
- safety belt, velcro-type, auto-type

# Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 25.4 cm (10 in.), short
- armrest pads, straight, contoured, long, short
- tubular armrest pads
- · clothing guards, flexible, rigid
- "U"-type armrests, detachable, flip-back, height-adjustable, short, long, from 25.4 cm (10 in.) to 35.6 cm (14 in.)
- "L"-type armrests, height-adjustable, short, long, from 12.7 cm (5 in.) to 25.4 cm (10 in.)

# **Footrests**

- 60° footrests, detachable, swingaway, length-adjustable from 37.5 cm (14³/₄ in.) to 47.0 cm (18¹/₂ in.), or 70° footrests, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 47.0 cm (18¹/₂ in.)
- · folding footplates, standard
- full-width footplate, tubular
- heel loops, non-adjustable
- · heel loops, length-adjustable
- padded calfrests

- · anodized aluminum handrims
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks, short
- threaded axles
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- heavy-duty rear wheels, solid tires, 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.), 7.6 cm (3 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 3.8 cm (1½ in.), 10.2 cm (4 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic or Optional Component(s)		
Body support system		
Seat and back:		
supple back, tension-adjustable	63.00	99.00
rigid seat, flat, lowered	140.00	176.00
modification of seat depth to 48.3 cm (19 in.), 50.8 cm (20 in.),		
53.3 cm (21 in.) or 55.9 cm (22 in.)	175.00	N/A
modification of seat width to 48.3 cm (19 in.), 50.8 cm (20 in.)		
or 55.9 cm (22 in.)	175.00	N/A
modification of back height to 50.8 cm (20 in.)	32.00	N/A
oush handles	N/C	38.00
supple back, nylon	N/C	36.00
back, angle-adjustable	64.00	N/A
supple seat, nylon	N/C	36.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, velcro-type	N/C	40.00
safety belt, auto-type	N/C	50.00
Armrests:		
"L"-type armrests, detachable, swingaway, height-adjustable	NIG	## OO
from 20.3 cm (8 in.) to 25.4 cm (10 in.), short	N/C	55.00
"U"-type armrests, detachable, flip-back, height-adjustable	NIC	00.00
from 25.4 cm (10 in.) to 35.6 cm (14 in.), short or long	N/C	98.00
'T"-type armrests, detachable, height-adjustable		
from 15.2 cm (6 in.) to 25.4 cm (10 in.) or from 20.3 cm (8 in.)		
o 35.6 cm (14 in.), short or long	1.40.00	
pair	140.00	105.00
each		125.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
"I"-type armrests, height-adjustable from 12.7 cm (5 in.)		
to 25.4 cm (10 in.), short or long	N/C	98.00
contoured armrest pads, short or long	N/C	26.00
tubular armrest pads	N/C	10.00
straight armrest pads, short	N/C	26.00
straight armrest pads, short straight armrest pads, long	N/C	26.00
clothing guards, flexible	N/C	15.00
clothing guards, rigid	N/C	46.00
<b>Footrests:</b> 60° footrests, detachable, swingaway, length-adjustable from 37.5 cm $(14^3/_4 \text{ in.})$ to 47.0 cm $(18^1/_2 \text{ in.})$ , or 70° footrests, detachable, swingaway, length-adjustable from 34.3 cm $(13^1/_2 \text{ in.})$ to 47.0 cm $(18^1/_2 \text{ in.})$ 70° footrests, tapered, detachable, swingaway, length-adjustable from 40.0 cm $(15^3/_4 \text{ in.})$ to 50.2 cm $(19^3/_4 \text{ in.})$	N/C	81.00
pair	107.00	
each		135.00
60° or 80° fixed footrests, length-adjustable from 37.5 cm (14 <sup>3</sup> / <sub>4</sub> in	.)	
to $47.0 \text{ cm } (18^{1}/_{2} \text{ in.})$	•,	
pair	167.00	
each	107.00	167.00
90° footrests, detachable, swingaway, length-adjustable from 12.7 cm (5 <sup>1</sup> / <sub>4</sub> in.) to 26.0 cm (10 <sup>1</sup> / <sub>4</sub> in.)	107.00	107.00
pair	107.00	125.00
each $60^{\circ}$ footrests, MFX, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 38.1 cm (15 in.), or $70^{\circ}$ footrests, MFX, detachable, swingaway, length-adjustable from 34.3 cm ( $13^{1}/_{2}$ in.) to $47.0$ cm ( $18^{1}/_{2}$ in.)		135.00
pair	144.00	
each		153.00
elevating legrests, detachable, swingaway, length-adjustable from 38.7 cm (15 <sup>1</sup> / <sub>4</sub> in.) to 54.0 cm (21 <sup>1</sup> / <sub>4</sub> in.)		
pair	230.00	
each		196.00
elevating legrests, compensating mechanism, from 40.6 cm (16 in.)	)	
to 53.3 cm (21 in.)		
pair	151.00	
each		157.00
modification of legrest length by – 2.5 cm (1 in.)		
or by $-5.1$ cm (2 in.)		
pair	190.00	
each	170.00	190.00
padded calfrests	N/C	20.00
	22.00	35.00
single calf strap		
double calf strap	34.00	52.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
folding footplates, standard	N/C	40.00
full-width footplate, tubular	N/C	120.00
full-width footplate, tubular, plastic-coated	30.00	150.00
full-width footplate, angle-adjustable, depth-adjustable	72.00	192.00
footplates, angle-adjustable, depth-adjustable, standard		
or oversized, 18.4 cm $(7^1/_4 \text{ in.})^{-1}$		
pair	72.00	
each		76.00
folding footplates, oversized		
pair	39.00	
each		60.00
heel loops, non-adjustable	N/C	5.00
heel loops, length-adjustable	N/C	12.00
Wheels and frame		
Types of drive systems:		
handrims with vertical or oblique projections	4.7.00	
pair	155.00	44.00
each	NG	112.00
anodized aluminum handrims	N/C	34.00
plastic-coated handrims	<b>52</b> .00	
pair	52.00	60.00
each		60.00
combined handrims	52.00	
pair	52.00	60.00
each		60.00
anti-tip rollers	05.00	
pair each	95.00	48.00
each cane holder	32.00	32.00
cane noticer	32.00	32.00
Wheel locks:		
standard, push-to-lock	N/C	44.00
standard, pull-to-lock	N/C	44.00
wheel lock extensions	100	11.00
pair	32.00	
each		16.00
anti-rollback brakes		
pair	98.00	
each	20.00	93.00
scissor-type wheel locks		,
pair	55.00	
each		72.00
Types of forks:		
orks, standard or short	N/C	49.00
ork-locking mechanisms		
pair	100.00	
each		50.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Rear axles:		
threaded axles	N/C	15.00
extension plates for amputee pair each	42.00	21.00
Frame: heavy-duty frame	232.00	N/A
Types of wheels:		
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	90.00
rear mag wheels, standard pressure, 50.8 cm (20 in.),	N/C	00.00
55.9 cm (22 in.) or 61.0 cm (24 in.) heavy-duty wheels, solid tires, 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C n.) N/C	90.00 126.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),	1.7	120.00
55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	126.00
spoked rear wheels, high pressure, 61.0 cm (24 in.) or 66.0 cm (26 heavy-duty wheels, standard pressure, high pressure, solid tires, 61.0 cm (24 in.) or 66.0 cm (26 in.)	5 in.) N/C	126.00
pair	79.00	
each	,,,,,	165.00
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.) or 7.6 cm (3 in.) front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)	N/C	40.00
pair each	50.00	65.00
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 4.4 cm (1 <sup>3</sup> / <sub>4</sub>		
pair each	40.00	60.00
front wheels, solid tires, 20.3 cm (8 in.) x 3.8 cm (1½ in.), 10.2 cm (4 in.), 12.7 cm (5 in.) or 15.2 cm (6 in.)	N/C	40.00
front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.) pair	60.00	
each front wheels, inner tube, 15.2 cm (6 in.) or 20.3 cm (8 in.) x 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	00.00	70.00
pair each	25.00	52.00
Component(s) under Special Consideration		
spoke guards*		
pair	82.00	
each		41.00
quick-release axles with lever mechanism* pair	76.00	
each	70.00	53.00

# DEVICE FROM: ORTHOFAB INC.

# **PRICE**

# MANUAL WHEEL CHAIR, "PRIMA" MODEL

\$1 098.00

# **Basic Component(s)**

# **Body support system**

- supple back, nylon
- back, height-adjustable from 38.1 cm (15 in.) to 45.7 cm (18 in.)
- seat-back angle: 90°, 96°
- telescopic backposts, 8° at 20.3 cm (8 in.), 0°
- seat width: from 35.6 cm (14 in.) to 55.9 cm (22 in.)
- seat depth: 40.6 cm (16 in.)
- supple seat, nylon
- front seat height: from 45.7 cm (18 in.) to 50.8 cm (20 in.)
- · safety belt, auto-type
- push handles

#### Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable from 22.9 cm (9 in.) to 30.5 cm (12 in.), long
- · straight armrest pads, short, long
- · rigid clothing guards, detachable

#### **Footrests**

- 60° or 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests
- folding footplates, tubular
- heel loops, length-adjustable

- · anodized aluminum handrims
- standard brakes, push-to-lock
- standard forks, high forks
- · threaded axles
- spoked rear wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.), 17.8 cm (7 in.)
- plates for amputee

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic or Optional Component(s)		
Body support system		
Seat and back: supple back, tension-adjustable rigid seat, flat modification of back height to 33.0 cm (13 in.), 35.6 cm (14 in.)	69.00 116.00	133.00 173.00
or 48.3 cm (19 in.) to 55.9 cm (22 in.)	99.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
contoured headrest, nylon	100.00	100.00
rticulated headrest mounting, uniball	115.00	115.00
back spreader bar with headrest support	99.00	99.00
nodification of seat depth to 35.6 cm (14 in.), 38.1 cm (15 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 in nodification of seat height to less 45.7 cm (18 in.) down	in.) 101.00	N/A
o 34.3 cm (13 <sup>1</sup> / <sub>2</sub> in.)	208.00	N/A
upple back, nylon	N/C	64.00
upple seat, nylon	N/C	57.00
bush handles	N/C	N/A
eat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
eat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
afety belt, velcro-type	27.00	63.00
afety belt, auto-type	N/C	36.00
afety belt, airplane-type	38.00	74.00
elescopic backposts, 8° at 20.3 cm (8 in.) or 0°	N/C	N/A
Armrests:  "L"-type armrests, detachable, swingaway, height-adjustable from 22.9 cm (9 in.) to 30.5 cm (12 in.), long "U"-type armrests, detachable, flip-back, height-adjustable from 20.3 cm (8 in.) to 27.9 cm (11 in.) or from 22.9 cm (9 in.) to 30.3 cm (12 in.) with transfer assists and rigid clothing guards, si	N/C	48.00
rom 20.3 cm (8 in.) to 27.9 cm (11 in.) or from 22.9 cm (9 in.) to 30.5 cm (12 in.) with transfer assists and rigid clothing guards, so that the same state of the same state	92.00	94.00
air	144.00	
ach		120.00
ontoured armrest pads, long	40.00	
oair	48.00	20.00
ach		39.00
contoured armrest pads, short	44.00	
oair	44.00	24.00
ach	N/C	34.00
traight armrest pads, long	N/C	15.00
traight armrest pads, short	N/C	12.00
igid clothing guards, detachable	N/C	65.00
nodification of "U"-type armrest height to under 20.3 cm (8 in.) of over 30.5 cm (12 in.)	or	

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
60° footrests, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	29.00	N/A
70° footrests, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	29.00	N/A
60° footrests, tapered, detachable, swingaway, length-adjustable	27/6	40000
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	102.00
70° footrests, tapered, detachable, swingaway, length-adjustable	N/C	102.00
from 35.6 cm (14 in.) to 48.3 cm (19 in.) elevating legrests, compensating mechanism, detachable, swingaw	N/C	102.00
length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)	ay,	
pair	234.00	
each	2000	219.00
elevating legrests, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
pair	166.00	
each		185.00
contoured calfrests	(0.00	
pair	60.00	50.00
each padded calfrests	N/C	20.00
modification of footrest or legrest length to under 35.6 cm (14 in.)	14/6	20.00
or to over 48.3 cm (19 in.)	79.00	N/A
folding footplates, oversized		
pair	40.00	
each		36.00
folding footplates, tubular	N/C	16.00
oversized footplates, angle-adjustable	<b>7</b> 0.00	
pair	78.00	55.00
each standard footplates, angle-adjustable		55.00
pair	72.00	
each	72.00	52.00
full-width footplate, angle-adjustable	168.00	200.00
double calf strap	55.00	55.00
heel loops, length-adjustable	N/C	11.00
toe loops		
pair	30.00	4 # 60
each		15.00
front impact guard with rollers	36.00	
pair each	30.00	18.00
Cucii		10.00
Wheels and frame		
folding mechanism with double crossbars	257.00	N/A
angle-adjustable back	98.00	N/A
back spreader bar	69.00	69.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of drive systems:		
non-slip handrims		
pair <sup>1</sup>	84.00	
each		88.00
andrims, plastic-coated		
pair	56.00	
ach		74.00
nodized aluminum handrims	N/C	46.00
ombined handrims		
air	66.00	
ach		79.00
nti-tip rollers		
air	92.00	
ach	40.00	46.00
ane holder	40.00	40.00
VI1 11		
Wheel locks: tandard, push-to-lock	N/C	53.00
etractable wheel lock extensions	N/C	33.00
air	38.00	
ach	36.00	19.00
ixed wheel lock extensions		17.00
vair	38.00	
ach	36.00	19.00
nti-rollback brakes		17.00
air	86.00	
ach	00.00	43.00
Types of forks:		
tandard forks	N/C	38.00
igh forks	N/C	55.00
Rear axles:	NIG	<b>7</b> 00
nreaded axles	N/C	5.00
uick-release axles	76.00	
air	76.00	42.00
ach	N/C	43.00 N/A
lates for amputee	N/C	IN/A
ypes of wheels:		
poked rear wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	74.00
ear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)	1470	7 7.00
air	98.00	
ach	,	123.00
boked rear wheels, standard pressure, 50.8 cm (20 in.),		120.00
5.9 cm (22 in.) or 61.0 cm (24 in.)		
air	68.00	
ach		108.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
rear mag wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 (24 in.)	00.00	
pair each	98.00	123.00
neavy-duty rear wheels, solid tires, 55.9 cm (22 in.) or 61.0 (24 in.)		123.00
pair	154.00	
each	15 1.00	151.00
heavy-duty rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)		
pair	154.00	
each		151.00
neavy-duty rear wheels, high pressure, 55.9 cm (22 in.),		
61.0 cm (24 in.) or 66.0 cm (26 in.)	154.00	
oair	154.00	151.00
each rear mag wheels, semi-pneumatic tires, 50.8 cm (20 in.),		151.00
55.9 cm (22 in.) or 61.0 cm (24 in.)		
oair	128.00	
each		138.00
spoked rear wheels, semi-pneumatic tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)		
pair	68.00	
each		108.00
heavy-duty spoked rear wheels, semi-pneumatic tires,		
55.9 cm (22 in.) or 61.0 cm (24 in.)	154.00	
oair each	154.00	151.00
Front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.),		131.00
12.7 cm (5 in.), 15.2 cm (6 in.) or 17.8 cm (7 in.)	N/C	30.00
Front wheels, inner tube, $20.3 \text{ cm } (8 \text{ in.}) \times 3.2 \text{ cm } (1^{1}/_{4} \text{ in.})$	14/6	30.00
or 15.2 cm (6 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)		
pair	32.00	
each		46.00
front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
pair	32.00	46.00
each		46.00
Front wheels, inner tube, 17.8 cm (7 in.) x 4.4 cm ( $1^{3}/_{4}$ in.)	22.00	
oair each	32.00	46.00
Front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm ( $1^{1}/_{2}$ in	)	40.00
15.2 cm (6 in.) x 3.8 cm ( $1\frac{1}{2}$ in.) or 12.7 cm (5 in.) x 3.8 cm ( $1\frac{1}{2}$ in		
pair	32.00	
each		46.00
Component(s) under Special Consideration		
spoke guards*	114.00	
oair	114.00	57.00
each		57.00

# DEVICE FROM: SUNRISE MEDICAL CANADA INC.

PRICE

# MANUAL WHEEL CHAIR, "QUICKIE LXI" MODEL

\$1 095.00

# **Basic Component(s)**

# **Body support system**

- · supple back, nylon
- back height: from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- front seat height: from  $40.0 \text{ cm} (15^3/_4 \text{ in.})$  to  $54.6 \text{ cm} (21^1/_2 \text{ in.})$
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.)
- supple seat, nylon
- · safety belt, velcro-type, auto-type
- push handles
- backposts, at an 8° angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.)

#### Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- straight armrest pads, short, long
- tubular armrest pads
- · flexible clothing guards

#### **Footrests**

- 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- folding footplates, standard
- folding footplates, tubular
- · heel loops, length-adjustable

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5<sup>1</sup>/<sub>4</sub> in.), high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels, high forks, 17.8 cm (7 in.), for 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- fork stems, + 1.9 cm ( $\frac{3}{4}$  in.), + 3.8 cm ( $\frac{11}{2}$  in.)
- · threaded axles
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)
- rear mag wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)

Seat and back		Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Seat and back:         Immodification of seat depth to 35.6 cm (14 in.) or 38.1 cm (15 in.)         40.00         N/A           modification of seat depth to 43.2 cm (19 in.) or 50.8 cm (20 in.)         95.00         N/A           modification of seat depth to 43.2 cm (17 in.) or 45.7 cm (18 in.)         67.00         N/A           supple back, nylon         N/C         62.00           supple back, tension-adjustable         74.00         136.00           supple seat, nylon         N/C         53.00           seat cushion, flat, foam, 5.1 cm (2 in.)         56.00         56.00           seat cushion, flat, foam, 5.1 cm (2 in.)         56.00         56.00           seat cushion, flat, foam, 10.2 cm (4 in.)         56.00         56.00           seat cushion, flat, foam, 10.2 cm (4 in.)         N/C         22.00           backposts, at an 8° angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.)         N/C         22.00           safety belt, auto-type         N/C         28.00           safety belt, auto-type         N/C         28.00           "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short         N/C         85.00           "U"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair         102.00         136.00           each </td <td>Basic and Optional Component(s)</td> <td></td> <td></td>	Basic and Optional Component(s)		
modification of seat depth to 35.6 cm (14 in.) or 38.1 cm (15 in.) 40.00 N/A modification of seat width to 48.3 cm (19 in.) or 50.8 cm (20 in.) 95.00 N/A supple back, nylon Seat depth to 43.2 cm (17 in.) or 45.7 cm (18 in.) 67.00 N/A supple back, tension-adjustable 74.00 136.00 Supple back, tension-adjustable 74.00 136.00 Supple seat, nylon N/C 35.00 Seat cushion, flat, foam, 5.1 cm (2 in.) 56.00 56	Body support system		
modification of seat width to 48.3 cm (19 in.) or 50.8 cm (20 in.)	Seat and back:		
modification of seat depth to 43.2 cm (17 in.) or 45.7 cm (18 in.)  supple back, nylon  supple back, nylon  supple back, tension-adjustable  supple seat, nylon  supple seat, nylon  supple seat, nylon  seat cushion, flat, foam, 5.1 cm (2 in.)  seat cushion, flat, foam, 5.1 cm (2 in.)  seat cushion, flat, foam, 10.2 cm (4 in.)  backposts, at an 8' angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.)  safety belt, velcro-type  safety belt, auto-type  Armrests:  "L"-type armrests, detachable, swingaway, height-adjustable from 22.9 cm (9 in.) to 30.5 cm (12 in.), short from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long pair each  "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair each  "T"-type armrest pads straight armrest pads, short  tubular armrest pads, short  tubular armrest pads, short  tubular armrest pads, short  from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair each  straight armrest pads, short  from 22.9 cm (9 in.) to 35.6 cm (14 in.) short or long pair each  straight armrest pads, short  from 25.6 cm (14 in.) to 48.3 cm (19 in.)  Footrests:  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair each  90.00  cach  60.00  clothing guards, flexible  Footrests:  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair each  90° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair each  105.00  Footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)  80° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)			
supple back, raylon         N/C         62.00           supple back, tension-adjustable         74.00         136.00           supple back, tension-adjustable         74.00         136.00           supple back, tension-adjustable         N/C         33.00           seat cushion, flat, foam, 5.1 cm (2 in.)         56.00         56.00           seat cushion, flat, foam, 10.2 cm (4 in.)         56.00         56.00           seat cushion, flat, foam, 10.2 cm (4 in.)         N/C         22.00           backposts, at an 8° angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.)         N/C         27.00           safety belt, velcro-type         N/C         28.00           safety belt, uclot-type         N/C         24.00           Armrests.         N/C         24.00           Armrests.         N/C         28.00           "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short or long         N/C         85.00           pair         102.00         102.00         102.00         102.00         102.00         102.00         102.00         102.00         102.00         102.00         102.00         102.00         102.00         102.00         102.00         102.00         102.00         102.00         102.00			
supple back, tension-adjustable     74,00     136,00       supple seat, nylon     N/C     53,00       seat cushion, flat, foam, 5.1 cm (2 in.)     56,00     56,00       seat cushion, flat, foam, 7.6 cm (3 in.)     56,00     56,00       seat cushion, flat, foam, 10.2 cm (4 in.)     56,00     56,00       push handles     N/C     22,00       backposts, at an 8° angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.)     N/C     27,00       safety belt, velcro-type     N/C     41,00       Armrests, detachable, swingaway, height-adjustable from 22.9 cm (8 in.) to 30.5 cm (12 in.), short     N/C     85,00       "L"-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long pair     102.00       each     136,00       "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair     139,00       each     15,00       straight armrest pads     N/C     2.00       straight armrest pads, long     N/C     15,00       straight armrest pads, long     N/C     15,00       straight armrest pads, long     N/C     21,00       Footrests:       60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)     N/C     53.00       Footrests, det			
supple seat, nylon       N/C       53.00         seat cushion, flat, foam, 5.1 cm (2 in.)       56.00       56.00         seat cushion, flat, foam, 7.6 cm (3 in.)       56.00       56.00         seat cushion, flat, foam, 10.2 cm (4 in.)       56.00       56.00         bush handles       N/C       22.00         backposts, at an 8° angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.)       N/C       27.00         safety belt, velcro-type       N/C       41.00         Armrests;         "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short       N/C       85.00         "U"-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long pair       102.00       102.00         each       136.00       "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair       139.00       154.50         each       15.00       17.00       17.00       17.00       17.00       17.00         each       15.00       N/C       2.00       17.00       17.00       17.00       17.00       17.00       17.00       17.00       17.00       17.00       17.00       17.00       17.00       17.00       17.00       17.00       17.00			
seaf cushion, flat, foam, 5.1 cm (2 in.)  seat cushion, flat, foam, 7.6 cm (3 in.)  seat cushion, flat, foam, 7.6 cm (3 in.)  seat cushion, flat, foam, 10.2 cm (4 in.)  beach control of the cushion, flat, foam, 10.2 cm (4 in.)  seat cushion, flat, foam, 5.6 cm (14 in.) to 48.3 cm (19 in.)  N/C  22.00  backposts, at an 8° angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.)  N/C  23.00  Armrests:  "L"-type armrests, detachable, swingaway, height-adjustable from 22.0 cm (8 in.) to 30.5 cm (12 in.), short  "U"-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long pair  each  "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair  each  "T"-type armrest pads  N/C  15.00  straight armrest pads, short  N/C  15.00  straight armrest pads, long  clothing guards, rigid  pair  each  90.00  each  South flexible  N/C  17.00  clothing guards, flexible  Footrests:  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  N/C  15.00  Footrests  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair  each  90° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair  28.00  each  90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)  each  90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)  each  90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)			
seat cushion, flat, foam, 7.6 cm (3 in.) seat cushion, flat, foam, 10.2 cm (4 in.) seat cushion, flat, foam, 10.2 cm (14 in.) seat cushion, flat, foam, 10.2 cm (15 in.) seat cushion, flat foam, 10.2 cm (15 in.) seat cushion, flat, foam, 10.2 cm (15 i			
seat cushion, flat, foam, 10.2 cm (4 in.) 56.00 yush handles N/C 22.00 bush handles N/C 22.00 backposts, at an 8° angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 27.00 safety belt, velcro-type N/C 28.00 safety belt, electro-type N/C 41.00 N/C 41.00  **Armrests:**  "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short N/C 85.00 "U"-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long pair 102.00 each 136.00 "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair each 154.50 tubular armrest pads N/C 2.00 straight armrest pads, short N/C 15.00 straight armrest pads, short N/C 15.00 straight armrest pads, nigid pair each N/C 17.00 clothing guards, rigid pair each N/C 21.00  **Footrests:**  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00  **Footrests:**  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00  **Pootrests:**  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00  **Pootrests:**  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00  **Pootrests:**  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00  **Pootrests:**  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00  **Pootrests:**  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00  **Pootrests:**  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00  **Pootrests:**  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 35.0 cm (15 in.) to 35.0 cm (15 in.			
push handles			
backposts, at an 8° angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 27.00 safety belt, velcro-type N/C 28.00 safety belt, velcro-type N/C 41.00  Armrests:  "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short N/C 85.00  "U"-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long pair 102.00 each 136.00  "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair 139.00 each 154.50 tubular armrest pads N/C 2.00 straight armrest pads, short N/C 15.00 straight armrest pads, long N/C 17.00 clothing guards, rigid pair 90.00 each 66.00 clothing guards, flexible N/C 21.00  Footrests:  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00  70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00  90° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00  90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (14 in.) to 33.0 cm (13 in.) enclose the suingaway in the suingaway			
safety belt, velcro-type     N/C     28.00       safety belt, auto-type     N/C     41.00       Armrests:			
Armrests   T."-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short			
Armrests: "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short "U"-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long pair each "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair each "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair each short straight armrest pads short straight armrest pads, long clothing guards, rigid pair each short straight armrest pads, long clothing guards, flexible  Footrests: 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair each short straight armrest, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair each short straight swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) 80° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) 80° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) 80° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) 80° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) 80° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) 80° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)			
"L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short "U"-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long pair acch 136.00 "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair acch 139.00 each 139.00 each 139.00 each 154.50 tubular armrest pads N/C 2.00 straight armrest pads, short N/C 15.00 straight armrest pads, long N/C 17.00 clothing guards, rigid pair 90.00 each 66.00 clothing guards, flexible N/C 21.00  Footrests:  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair 28.00 each 67.00 90° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair 28.00 each 67.00 90° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 30.0 cm (18 in.) to 33.0 cm (	•		
from 20.3 cm (8 in.) to 30.5 cm (12 in.), short			
"U"-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long pair 102.00 each 136.00 "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair 139.00 each 154.50 tubular armrest pads N/C 2.00 straight armrest pads, short N/C 15.00 straight armrest pads, long N/C 17.00 clothing guards, rigid pair 90.00 each 66.00 clothing guards, flexible N/C 21.00  Footrests:  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00 reach 28.00 each 66.00 clothing straight armrest, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00 reach 28.00 each 66.00 clothing straight adjustable from 35.6 cm (14 in.) to 33.0 cm (13 in.) N/C 53.00 elevating legrests pair 105.00	"L"-type armrests, detachable, swingaway, height-adjustable		
from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long pair each 136.00 "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair each 139.00 each 154.50 tubular armrest pads N/C 2.00 straight armrest pads, short N/C 15.00 straight armrest pads, long N/C 17.00 clothing guards, rigid pair each 90.00 each 66.00 clothing guards, flexible N/C 21.00  Footrests:  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair each 28.00 each 67.00 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) N/C 53.00 elevating legrests pair 105.00		N/C	85.00
pair each 102.00  "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair 139.00 each 154.50 tubular armrest pads N/C 2.00 straight armrest pads, short N/C 15.00 straight armrest pads, long N/C 17.00 clothing guards, rigid pair 90.00 each 66.00 clothing guards, flexible N/C 21.00  Footrests: 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair each 28.00 each 50° or 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair 28.00 each 67.00 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) N/C 53.00 elevating legrests pair 105.00			
each "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair and pair armrest pads armrest pads armrest pads, short armrest pads, long taright armrest pads, long taright armrest pads, rigid pair appair and pair appair and pair appair and pair appair and pair appair appa		102.00	
"T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair each 139.00 each 154.50 tubular armrest pads N/C 2.00 straight armrest pads, short N/C 15.00 straight armrest pads, long N/C 15.00 straight armrest pads, long N/C 17.00 clothing guards, rigid pair 90.00 each 66.00 clothing guards, flexible N/C 21.00 Footrests:  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair 28.00 each 67.00 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) N/C 53.00 elevating legrests pair 105.00	•	102.00	126.00
from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long pair each 154.50 tubular armrest pads N/C 2.00 straight armrest pads, short N/C straight armrest pads, long N/C clothing guards, rigid pair each clothing guards, flexible  Footrests: 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair each Pootrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair each Pootrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) each N/C 53.00 elevating legrests pair 105.00			136.00
pair each tubular armrest pads 154.50 tubular armrest pads N/C 2.00 straight armrest pads, short N/C 15.00 straight armrest pads, long N/C 17.00 clothing guards, rigid pair 90.00 each 66.00 clothing guards, flexible N/C 21.00  Footrests: 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair 28.00 each 67.00 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) N/C 53.00 elevating legrests pair 105.00			
tubular armrest pads		120.00	
tubular armrest pads straight armrest pads, short straight armrest pads, short straight armrest pads, long clothing guards, rigid pair each clothing guards, flexible  Footrests:  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair pair pair 28.00 pair each from 20.3 cm (8 in.) to 33.0 cm (13 in.) elevating legrests pair  105.00		139.00	154.50
straight armrest pads, short straight armrest pads, long straight armrest pads, long clothing guards, rigid pair each clothing guards, flexible  Footrests:  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair pair 28.00 each 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) elevating legrests pair 105.00		N/C	
straight armrest pads, long clothing guards, rigid pair pair 90.00 each clothing guards, flexible  Footrests:  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) Pair pair pair pair pair pair pair pair p			
clothing guards, rigid pair 90.00 each 66.00 clothing guards, flexible N/C 21.00  Footrests: 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair 28.00 each 67.00 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) N/C 53.00 elevating legrests pair 105.00			
pair 90.00 each 66.00 clothing guards, flexible N/C 21.00  Footrests: 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair 28.00 each 67.00 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) N/C 53.00 elevating legrests pair 105.00		100	17.00
each clothing guards, flexible N/C 21.00  Footrests:  60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00  70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair 28.00  each 67.00  90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) N/C 53.00  elevating legrests  pair 105.00		90.00	
Footrests: 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) N/C 53.00 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) pair 28.00 each 67.00 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) N/C 53.00 elevating legrests pair 105.00	each		66.00
60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair  28.00  each  67.00  90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)  elevating legrests pair  105.00	clothing guards, flexible	N/C	21.00
60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair  28.00  each  67.00  90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)  elevating legrests pair  105.00			
from 35.6 cm (14 in.) to 48.3 cm (19 in.)  70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair  28.00  each  90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)  elevating legrests  pair  N/C  53.00  70° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)  N/C  53.00	Footrests:		
70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair 28.00  each 67.00  90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) N/C 53.00  elevating legrests  pair 105.00		3710	<b>7.0</b> 0.0
from 35.6 cm (14 in.) to 48.3 cm (19 in.)  pair  each  90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)  elevating legrests pair  105.00		N/C	53.00
pair 28.00 each 67.00 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) N/C 53.00 elevating legrests pair 105.00			
each 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) elevating legrests pair  105.00		20.00	
90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) N/C 53.00 elevating legrests pair 105.00		28.00	67.00
from 20.3 cm (8 in.) to 33.0 cm (13 in.)  elevating legrests pair  N/C  53.00			07.00
elevating legrests pair 105.00		N/C	53.00
pair 105.00		IV/C	33.00
		105.00	
	each	103.00	105.50

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
elevating legrests, compensating mechanism		
pair	194.00	
each		150.00
single calf strap	18.00	18.00
double calf strap	32.00	32.00
folding footplates, standard	N/C	48.00
folding footplates, angle-adjustable		
pair	51.00	
each		73.50
folding footplates, tubular	N/C	48.00
folding footplates, full-width, angle-adjustable folding footplates, oversized	83.00	179.00
pair	71.00	
each		83.50
heel loops, length-adjustable	N/C	10.00
modification of footrest length from 48.3 cm (19 in.)		
to 52.1 cm $(20^{1}/_{2} in.)$	30.00	29.00
modification of footrest mounting from 17.8 cm (7 in.)	<b>-</b> 4.00	
to 34.3 cm $(13^{1}/_{2} \text{ in.})$	54.00	33.00
modification of length of 90° footrest by + 5.1 cm (2 in.) or by + 10.2 cm (4 in.)	30.00	15.00
Wheels and frame		
Types of drive systems:		
one-arm dual handrim drive	468.00	560.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	58.00
plastic-coated handrims		
pair	54.00	
each		85.00
handrims with vertical or oblique projections		
pair	88.00	
each		102.00
small plastic-coated handrim for one-arm drive	54.00	112.00
anti-tip rollers		
pair	43.00	
each	4.4.00	21.50
cane holder	44.00	44.00
Wheel locks:		
standard wheel locks, push-to-lock or pull-to-lock	N/C	39.00
wheel lock extensions		
pair	26.00	
each		13.00
anti-rollback brakes		
oair	66.00	
each		33.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of forks:		
standard forks, 15.2 cm (6 in.), short forks, 13.3 cm ( $5^{1}/_{4}$ in.)		
or high forks 17.8 cm (7 in.), compatible with 12.7 cm (5 in.),	N/C	21.00
15.2 cm (6 in.) and 20.3 cm (8 in.) wheels nigh forks, 17.8 cm (7 in.), for 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels	N/C N/C	31.00 34.00
fork-locking mechanisms	N/C	34.00
pair	44.00	
each		22.00
Fork stems, + 1.9 cm ( $^{3}/_{4}$ in.) or + 3.8 cm ( $^{1}/_{2}$ in.)	N/C	16.00
Rear axles:		
hreaded axles	N/C	11.00
puick-release axles	42.00	
oair each	43.00	32.50
extension plates for amputee	64.00	N/A
Types of wheels:		
rear mag wheels, solid tires, 50.8 cm (20 in.)		
pair	44.00	
each	3710	132.00
rear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	132.00
rear mag wheels, standard pressure, 50.8 cm (20 in.)	44.00	
each	44.00	132.00
rear mag wheels, standard pressure, 55.9 cm (22 in.)		132.00
or 61.0 cm (24 in.)	N/C	110.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)		
pair	44.00	122.00
each		132.00
spoked rear wheels, high pressure, 61.0 cm (24 in.)	44.00	
each	44.00	132.00
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)		132.00
or 61.0 cm (24 in.)		
pair	78.00	
each		149.00
Front wheels, solid tires, 15.2 cm (6 in.)	N/C	60.00
front wheels, solid tires, 12.7 cm (5 in.)	N/C	46.00
Front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4} \text{ in.})$	N/C N/C	61.00 61.00
ront wheels, inner tube, $20.3 \text{ cm} (8 \text{ in.}) \times 3.2 \text{ cm} (174 \text{ in.})$ ront wheels, inner tube, $15.2 \text{ cm} (6 \text{ in.}) \times 3.2 \text{ cm} (1^{1}/_{4} \text{ in.})$	N/C N/C	60.00
ront wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)	11/0	00.00
pair	47.00	
each		69.50
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm ( $1\frac{1}{2}$ in.) or 15.2 cm (6 in.) x 3.8 cm ( $1\frac{1}{2}$ in.)	)	
pair	80.00	
each		86.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
spoke guards* pair each quick-release axles with lever mechanism* pair each	67.00 64.00	33.50 64.50
DEVICE FROM: SUNRISE MEDICAL CANADA INC.		PRICE
MANUAL WHEEL CHAIR, ADULT, "QUICKIE 2" MODEL	•	\$1 370.00

# **Basic Component(s)**

# **Body support system**

- supple back, nylon
- back height: from 21.6 cm  $(8^{1}/_{2} \text{ in.})$  to 47.0 cm  $(18^{1}/_{2} \text{ in.})$
- supple seat, nylon
- seat width: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- seat depth: 40.6 cm (16 in.)
- front seat height: from  $38.7 \text{ cm} (15^{1}/_{4} \text{ in.})$  to  $54.6 \text{ cm} (21^{1}/_{2} \text{ in.})$
- growth kit including: seat, back, footrests, front frame and crossbars (once only during first three years from date of purchase, for first user)
- safety belt, velcro-type, auto-type
- · push handles

# **Armrests**

- "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- straight armrest pads, short, long
- · tubular armrest pads
- · clothing guards, flexible

#### **Footrests**

- 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70° or 80° footrests, detachable, swingaway, length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.)
- padded calfrests
- padded calfrests, for elevating legrests, compensating mechanism
- folding footplates, standard
- folding footplates, tubular
- heel loops, length-adjustable

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5<sup>1</sup>/<sub>4</sub> in.); high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- high forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.)
- wheelsfork stems,  $+ 1.9 \text{ cm} (\frac{3}{4} \text{ in.}), + 3.8 \text{ cm} (\frac{1}{2} \text{ in.})$
- quick-release axles
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)
- rear wheel camber, 3°, 6°, 9°
- adjustable axle plates
- adjustable axle plates, compensated

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
folding back, angle-adjustable	104.00	N/A
supple back, tension-adjustable	74.00	136.00
backposts, at an $8^{\circ}$ angle, from 31.8 cm ( $12^{1}/_{2}$ in.) to 47.0 cm ( $18^{1}/_{2}$	in.)	
pair	14.00	
each		26.00
supple back, nylon	N/C	62.00
back spreader bar	126.00	N/A
backposts, angle-adjustable from $-3^{\circ}$ to $+15^{\circ}$ , 3 positions	118.00	N/A
supple seat, nylon	N/C	53.00
modification of seat depth to 35.6 cm (14 in.), 38.1 cm (15 in.),		
43.2 cm (17 in.) or 45.7 cm (18 in.)	39.00	N/A
modification of back height from 48.3 cm (19 in.) to 55.9 cm (22 in growth kit including: seat, back, footrests, front frame and crossba		N/A
(once only during first three years from date of purchase, for first u	iser) N/C	N/A
push handles	N/C	19.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
seat cushion, flat, foam, 10.2 cm (4 in.)	56.00	56.00
safety belt, velcro-type	N/C	28.00
safety belt, auto-type	N/C	41.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
L"-type armrests, detachable, swingaway, height-adjustable		
from 20.3 cm (8 in.) to 30.5 cm (12 in.), short	N/C	93.00
"T"-type armrests, detachable, height-adjustable		
from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long	77.00	
oair each	77.00	131.50
'U''-type armrests, detachable, flip-back, height-adjustable		131.30
from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long		
pair	69.00	
each	0,100	127.50
'U"-type armrests, flip-back, height-adjustable from 22.9 cm	(9 in.)	
o 33.0 cm. (13 in.) for angle-adjustable back, short	`	
pair	160.00	
each		173.00
1"-type armrests, flip-back, height-adjustable from 22.2 cm (8	3 <sup>3</sup> / <sub>4</sub> in.)	
o 34.9 cm (13 <sup>3</sup> / <sub>4</sub> in.), short	201.00	
oair	291.00	220.50
each ubular armrest pads	N/C	238.50 2.00
straight armrest pads, short	N/C N/C	15.00
clothing guards, flexible	N/C	21.00
clothing guards, rigid	100	21.00
pair	90.00	
each		66.00
744		
Footrests:		
60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	53.00
70° footrests, tapered, detachable, swingaway, length-adjustab		33.00
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	53.00
70° or 80° fixed footrests, heavy-duty	100	23.00
pair	63.00	
each		84.50
70° or 80° footrests, detachable, swingaway, length-adjustable		
from 15.2 cm (6 in.) to 30.5 cm (12 in.)	N/C	55.00
elevating legrests, compensating mechanism, detachable	101.00	
pair	194.00	150.00
each		150.00
elevating legrests, detachable	105.00	
air ach	103.00	105.50
padded calfrests	N/C	18.00
contoured calfrests	100	10.00
pair	70.00	
ach		53.00
padded calfrests, for elevating legrests, compensating mechani	sm N/C	39.00
ingle calf strap	18.00	18.00
louble calf strap	32.00	32.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
folding footplates, standard	N/C	48.00
folding footplates, angle-adjustable	<b>51.00</b>	
pair each	51.00	73.50
folding footplates, tubular	N/C	48.00
folding footplates, oversized	TV/C	70.00
pair	71.00	
each		83.50
full-width footplate, folding, angle-adjustable	83.00	179.00
heel loops, length-adjustable	N/C	10.00
modification of footrest length from 48.3 cm (19 in.)	20.00	20.00
to 52.1 cm $(20^{1}/_{2} \text{ in.})$	30.00	29.00
raised footplate mountings, from 17.8 cm (7 in.) to 34.3 cm (13½ in.) in length		
pair	54.00	
each	2	33.00
front impact guard with rollers		
pair	36.00	
each		18.00
Wheels and frame		
Frame:		
optional heavy-duty frame, 45.7 cm (18 in.)		
to 55.9 cm (22 in.) wide, 350-lb. capacity	360.00	N/A
extra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 i		N/A
Types of drive systems:	546.00	600.00
one-arm dual handrim drive anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.),	546.00	688.00
61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	58.00
handrims with vertical or oblique projections, 61.0 cm (24 in.)	1,70	20.00
pair	88.00	
each		102.00
plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.),		
61.0 cm (24 in.) or 66.0 cm (26 in.)	54.00	
pair	54.00	95.00
each non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.)		85.00
pair	164.00	
each	101.00	140.00
small plastic-coated handrim for one-arm drive	54.00	N/A
anti-tip rollers		
pair	43.00	
each	44.00	21.50
cane holder	44.00	44.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks:		
standard wheel locks, push-to-lock or pull-to-lock wheel lock extensions	N/C	39.00
oair each	26.00	13.00
nti-rollback brakes		13.00
air ach	66.00	33.00
wheel locks, push-to-lock or pull-to-lock, unilateral control	124.00	N/A
Types of forks:		
tandard forks, 15 cm (6 in.), short forks, 13.3 cm ( $5^{1/4}$ in.) or high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.),		
15.2 cm (6 in.) and 20.3 cm (8 in.) wheels	N/C	31.00
high forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels	N/C	36.00
ork-locking mechanisms	44.00	
pair each	44.00	22.00
ork stems, + 1.9 cm ( $^{3}/_{4}$ in.) or + 3.8 cm ( $^{1}/_{2}$ in.) nulti-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.)	N/C	16.00
and 20.3 cm (8 in.) wheels	N/C	54.00
Rear axles:		
quick-release axles extension plates for amputee	N/C	32.50
pair	42.00	<b>-</b> 4.00
each curved multi-position plates		71.00
pair	28.00	64.00
each ear wheel camber, 3°, 6°, 9°	N/C	64.00 N/A
xle plates	N/C	50.00
ixle plates, compensated	N/C	63.00
Types of wheels:		
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	149.00
poked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	132.00
poked rear wheels, high pressure, 61.0 cm (24 in.)		
or 66.0 cm (26 in.) ear wheels, heavy-duty, standard pressure	N/C	132.00
or high pressure, 61.0 cm (24 in.)	122.60	
air ach	122.00	193.00
ear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)	N/C	
or 61.0 cm (24 in.)	N/C	132.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
rear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C	132.00
rear mag wheels, standard pressure, 55.9 cm (22 in.) or 61.0 cm (2	24 in.) N/C	110.00
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)	N/C	61.00
front wheels, solid tires, 15.2 cm (6 in.)	N/C	60.00
front wheels, solid tires, 12.7 cm (5 in.) front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	46.00
pair	47.00	
each		69.50
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)	N/C	61.00
front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm ( $1^{1}/_{4}$ in.) front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm ( $1^{1}/_{2}$ i	N/C n.)	60.00
or $15.2 \text{ cm } (6 \text{ in.}) \times 3.8 \text{ cm } (1^{1}/_{2} \text{ in.})$	22.22	
pair	80.00	0 ( 0 0
each		86.00
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 in.)		
pair	65.00	
each		78.50
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm ( $1^{1}/_{2}$ i		
pair	100.00	
each		96.00
Component(s) under Special Consideration		
spoke guards*		
pair	67.00	
each	22	33.50
quick-release axles with lever mechanism*		22.50
pair	64.00	
each	01.00	64.50
		2 .700
DEVICE FROM: SUNRISE MEDICAL CANADA INC.		PRI
MANUAL WHEEL CHAIR, ADULT, "QUICKIE 2 HP" MOD	DEL.	\$1 475

# **Basic Components**

# **Body support system**

- supple back, nylon
- back height: from 21.6 cm  $(8^{1}/_{2} \text{ in.})$  to 47.0 cm  $(18^{1}/_{2} \text{ in.})$
- supple seat, nylon
- seat width: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- seat depth: 40.6 cm (16 in.)
- front seat height: from 43.8 cm  $(17^{1}/_{4} \text{ in.})$  to 54.6 cm  $(21^{1}/_{2} \text{ in.})$
- safety belt, velcro-type, auto-type
- · push handles

#### Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- straight armrest pads, short, long
- tubular armrest pads
- flexible clothing guards

#### **Footrests**

- 60° or 70° fixed footrests, parallel, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- folding footplates, standard
- · folding footplates, tubular
- heel loops, length-adjustable

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5<sup>1</sup>/<sub>4</sub> in.), high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- high forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- fork stems,  $+ 1.9 \text{ cm} (\frac{3}{4} \text{ in.}), + 3.8 \text{ cm} (\frac{1}{2} \text{ in.})$
- quick-release axles
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)
- rear wheel camber, 3°, 6°, 9°
- adjustable axle plates
- adjustable axle plates, compensated

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic or Optional Component(s)		
Body support system		
Seat and back:		
supple back, tension-adjustable	74.00	136.00
backposts, at an 8° angle, from 31.8 cm (12½ in.)		
to $47.0 \text{ cm } (18^{1}/_{2} \text{ in.})$ , with handles	14.00	
pair	14.00	26.00
each	126.00	26.00
back spreader bar	126.00	N/A
backposts, angle-adjustable from -3° à + 15°, 3 positions	118.00 N/C	N/A 62.00
supple back, nylon	N/C N/C	53.00
supple seat, nylon modification of seat depth to 35.6 cm (14 in.), 38.1 cm (15 in.),	N/C	33.00
43.2 cm (17 in.) or 45.7 cm (18 in.)	47.00	N/A
modification of back height from 48.3 cm (19 in.) to 55.9 cm (22 in		N/A
bush handles	N/C	19.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
seat cushion, flat, foam, 10.2 cm (4 in.)	56.00	56.00
safety belt, velcro-type	N/C	28.00
safety belt, auto-type	N/C	41.00
Armrests:		
"L"-type armrests, detachable, swingaway, height-adjustable		
from 20.3 cm (8 in.) to 30.5 cm (12 in.), short	N/C	93.00
"T"-type armrests, detachable, height-adjustable		
from 22.9 cm (9 in.) to 35.6 cm (14 in.), short or long	<b>55</b> 00	
pair	77.00	121.50
each		131.50
"U"-type armrests, detachable, flip-back, height-adjustable		
from 22.9 cm (9 in.) to 33.0 cm (13 in.), short or long	69.00	
pair each	09.00	127.50
"U"-type armrests, detachable, flip-back, height-adjustable		127.30
for angle-adjustable back, from 22.9 cm (9 in.)		
to 33.0 cm (13 in.), short		
pair	160.00	
each	100.00	173.00
tubular armrest pads	N/C	2.00
straight armrest pads, long	N/C	17.00
straight armrest pads, short	N/C	15.00
clothing guards, flexible	N/C	21.00
clothing guards, rigid		
pair	90.00	
each		66.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
60° or 70° fixed footrests, parallel, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	43.00
single calf strap	18.00	18.00
double calf strap	32.00	32.00
folding footplates, standard	N/C	48.00
folding footplates, angle-adjustable		
oair	51.00	
each		73.50
folding footplates, tubular	N/C	48.00
folding footplates, oversized		
pair	71.00	
each		83.50
full-width footplate, folding, angle-adjustable	83.00	179.00
neel loops, length-adjustable	N/C	10.00
modification of footrest length from 48.3 cm (19 in.)		
to 52.1 cm $(20^{1}/_{2} in.)$	30.00	29.00
raised footplate mounting, from 18.8 cm (7 in.)		
to 34.3 cm $(13^{1}/_{2} in.)$ in length		
pair	54.00	
each		33.00
Wheels and frame		
Ename		
Frame:		
optional heavy-duty frame, 45.7 cm (18 in.) to 55.9 cm (22 in.) wide, 350-lb. capacity	360.00	N/A
extra-long frame for depths of 48.3 cm (19 in.)	300.00	IN/A
	50.00	N/A
and 50.8 cm (20 in.)	30.00	IN/A
Types of drive systems:		
	<b>=</b> 4 < 0.0	
one-arm dual handrim drive	546.00	688.00
	546.00	688.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.),	,	
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)		688.00 58.00
one-arm dual handrim drive anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) handrims with vertical or oblique projections, 61.0 cm (24 in.) pair	,	
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	, N/C	
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) nandrims with vertical or oblique projections, 61.0 cm (24 in.) pair each	, N/C	58.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) handrims with vertical or oblique projections, 61.0 cm (24 in.) pair	, N/C	58.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) nandrims with vertical or oblique projections, 61.0 cm (24 in.) pair each plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	, N/C	58.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) handrims with vertical or oblique projections, 61.0 cm (24 in.) or each plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair each	, N/C 88.00	58.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) handrims with vertical or oblique projections, 61.0 cm (24 in.) or each plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair each	, N/C 88.00 54.00	58.00 102.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) handrims with vertical or oblique projections, 61.0 cm (24 in.) pair each plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair each non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.)	, N/C 88.00	58.00 102.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) handrims with vertical or oblique projections, 61.0 cm (24 in.) pair each plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair each non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) pair each	, N/C 88.00 54.00 164.00	58.00 102.00 85.00 140.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) handrims with vertical or oblique projections, 61.0 cm (24 in.) pair each plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair each non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) pair each	, N/C 88.00 54.00	58.00 102.00 85.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) handrims with vertical or oblique projections, 61.0 cm (24 in.) pair each plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair each non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) pair	, N/C 88.00 54.00 164.00	58.00 102.00 85.00 140.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) nandrims with vertical or oblique projections, 61.0 cm (24 in.) pair each plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair each non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) pair each small plastic-coated handrim for one-arm drive each small plastic-coated handrim for one-arm drive each each one-arm drive	, N/C 88.00 54.00 164.00	58.00 102.00 85.00 140.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) handrims with vertical or oblique projections, 61.0 cm (24 in.) pair each plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.) pair each hon-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.) pair each small plastic-coated handrim for one-arm drive	, N/C 88.00 54.00 164.00 54.00	58.00 102.00 85.00 140.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks:		
standard wheel locks, push-to-lock or pull-to-lock scissor-type wheel locks	N/C	39.00
pair	24.00	
each		51.00
wheel lock extensions pair	26.00	
each	20.00	13.00
wheel locks, push-to-lock or pull-to-lock, unilateral control anti-rollback brakes	124.00	N/A
pair	66.00	
each		33.00
Types of forks: standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5 <sup>1</sup> / <sub>4</sub> in.) or high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.),		
15.2 cm (6 in.) and 20.3 cm (8 in.) wheels high forks, 17.8 cm (7 in.), compatible	N/C	31.00
with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels	N/C	36.00
fork-locking mechanisms	44.00	
pair each	44.00	22.00
fork stems, + 1.9 cm ( $^{3}/_{4}$ in.) or + 3.8 cm ( $^{1}/_{2}$ in.)	N/C	16.00
multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.)		
and 20.3 cm (8 in.) wheels	N/C	54.00
Rear axles:		
quick-release axles	N/C	32.50
heavy-duty axles pair	99.00	
each	<i>77.</i> 00	82.00
extension plates for amputee		
pair	42.00	71.00
each curved multi-position plates		71.00
pair	28.00	
each		64.00
rear wheel camber, 3°, 6°, 9°	N/C	N/A
adjustable axle plates	N/C	50.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.	)	
or 61.0 cm (24 in.)	N/C	149.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),		
55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	132.00
spoked rear wheels, high pressure, 61.0 cm (24 in.)		
or 66.0 cm (26 in.)	N/C	132.00
rear wheels, heavy-duty, standard pressure		
or high pressure, 61.0 cm (24 in.)	400.00	
pair	122.00	40000
each		193.00
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)	NIG	122.00
or 61.0 cm (24 in.)	N/C	132.00
rear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C	132.00
rear mag wheels, standard pressure, 55.9 cm (22 in.)	NIC	110.00
or 61.0 cm (24 in.)	N/C	110.00
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)	N/C N/C	61.00 60.00
front wheels, solid tires, 15.2 cm (6 in.)	N/C N/C	
front wheels, solid tires, 12.7 cm (5 in.) front wheels, solid tires, 7.6 cm (3 in.)	N/C	46.00
pair	39.00	
each	39.00	65.50
front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)		05.50
pair	47.00	
each	17.00	69.50
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)	N/C	61.00
front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm ( $^{1}$ / $^{4}$ in.)	N/C	60.00
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm (1 <sup>1</sup> /		
or 15.2 cm (6 in.) x 3.8 cm ( $1^{1}/_{2}$ in.)		
pair	80.00	
each		86.00
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1 <sup>1</sup> /	2 in.)	
pair	100.00	
each		96.00
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 i	n.)	
pair	65.00	
each		78.50
Component(s) under Special Consideration		
•		
spoke guards*		
pair	67.00	
each		33.50
quick-release axles with lever mechanism*		
pair	64.00	
each		64.50

# **DEVICE FROM: INVACARE CANADA INC.**

**PRICE** 

# MANUAL WHEEL CHAIR, "MVP JR" MODEL

\$1 150.00

# **Basic Component(s)**

# **Body support system**

- fixed back, height-adjustable from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- front seat height: from  $37.5 \text{cm} (14^3/_4 \text{ in.})$  to  $54.0 \text{ cm} (21^1/_4 \text{ in.})$
- seat widths: 30.5 cm (12 in.), 32.5 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.)
- seat depth: from 30.5 cm (12 in.) to 40.6 cm (16 in.)
- · supple seat and back, nylon
- push handles
- safety belt, velcro-type, auto-type
- growth kit (once only during first three years from date of purchase, for first user)

#### Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 25.4 cm (10 in.), short
- "U"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long
- "L"-type armrests, height-adjustable from 12.7 cm (5 in.) to 25.4 cm (10 in.), short, long
- · armrest pads, straight, contoured, short, long
- tubular armrest pads
- clothing guards, flexible, rigid, detachable

#### Footrests:

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 37.5 cm (14<sup>3</sup>/<sub>4</sub> in.) to 47.0 cm (18<sup>1</sup>/<sub>2</sub> in.)
- 70° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 47.0 cm (18¹/₂ in.)
- 90° footrests, length-adjustable from 13.3 cm ( $5^{1}/_{4}$  in.) to 26.0 cm ( $10^{1}/_{4}$  in.)
- 60° footrests, MFX, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 38.1 cm (15 in.)
- 70° footrests, MFX, detachable, swingaway, length-adjustable from 34.3 cm (13<sup>1</sup>/<sub>2</sub> in.) to 47.0 cm (18<sup>1</sup>/<sub>2</sub> in.)
- padded calfrests
- folding footplates, standard
- full-width footplate, tubular
- heel loops, non-adjustable
- heel loops, length-adjustable

- · anodized aluminum handrims
- standard brakes, push-to-lock, pull-to-lock
- standard forks, short
- threaded axles
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), standard pressure, 40.6 cm (16 in.), 45.7 cm (18 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear wheel camber,  $0^{\circ}$ ,  $3^{\circ}$ ,  $5^{\circ}$ ,  $8^{\circ}$
- spoked rear wheels, high pressure, solid tires, 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 7.6 cm (3 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 3.8 cm (1<sup>1</sup>/<sub>2</sub> in.), 10.2 cm (4 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic or Optional Component(s)		
Body support system		
Seat and back:		
supple back, tension-adjustable	63.00	99.00
back, angle-adjustable	64.00	N/A
modification of seat height to 50.8 cm (20 in.)	32.00	N/A
supple back, nylon	N/C	36.00
rigid seat, flat, lowered 35.6 cm (14 in.) and more	140.00	176.00
supple seat, nylon	N/C	36.00
push handles	N/C	38.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, velcro-type	N/C	50.00
safety belt, auto-type	N/C	40.00
growth kit (once only during first three years from date		
of purchase, for first user)	N/C	N/A
Armrests:		
"L"-type armrests, detachable, swingaway, height-adjustable		
from 20.3 cm (8 in.) to 25.4 cm (10 in.), short "U"-type armrests, detachable, height-adjustable	N/C	55.00
from 25.4 cm (10 in.) to 35.6 cm (14 in.), short or long "T"-type armrests, detachable, height-adjustable	N/C	98.00
from 15.2 cm (6 in.) to 25.4 cm (10 in.) or from 20.3 cm (8 in.) to 35.6 cm (14 in.), short or long		
` ''	140.00	
pair each	140.00	125.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
"I"-type armrests, height-adjustable from 12.7 cm (5 in.)		
to 25.4 cm (10 in.), short or long	N/C	98.00
clothing guards, flexible	N/C	15.00
clothing guards, rigid, detachable	N/C	46.00
armrest pads, straight or contoured, short or long	N/C	26.00
tubular armrest pads	N/C	10.00
Footrests :		
60° or 80° fixed footrests, parallel, length-adjustable		
from 37.5 cm $(14^{3}/_{4} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$		
oair	167.00	
each		167.00
60° footrests, parallel, detachable, swingaway, length-adjustable		
from 37.5 cm $(14^{3}/_{4} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$ , or 70° footrests,		
parallel, detachable, swingaway, length-adjustable		
from 34.3 cm $(13^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$	N/C	81.00
60° footrests, MFX, detachable, swingaway, length-adjustable		
from 27.9 cm (11 in.) to 38.1 cm (15 in.)	N/C	153.00
90° footrests, length-adjustable from 13.3 cm (5 <sup>1</sup> / <sub>4</sub> in.)		
to $26.0 \text{ cm} (10^{1}/_{4} \text{ in.})$	N/C	135.00
70° footrests, MFX, detachable, swingaway, length-adjustable		
from 34.3 cm $(13^{1}/_{2} \text{ in.})$ to 47 cm $(18^{1}/_{2} \text{ in.})$	N/C	153.00
70° footrests, tapered, detachable, length-adjustable		
from 40.0 cm $(15^3/_4 \text{ in.})$ to 50.2 cm $(19^3/_4 \text{ in.})$		
pair	107.00	
each		135.00
elevating legrests, from 38.7 cm $(15^3/_4 \text{ in.})$ to 54.0 cm $(21^1/_4 \text{ in.})$		
pair	230.00	
each		196.00
padded calfrests	N/C	20.00
single calf strap	22.00	35.00
double calf strap	34.00	52.00
modification of length of elevating legrests by $-2.5$ cm (1 in.)		
or by – 5.1 cm (2 in.)	190.00	190.00
folding footplates, standard	N/C	40.00
oversized footplates		
pair	39.00	
each		60.00
neel loops, length-adjustable	N/C	12.00
neel loops, non-adjustable	N/C	5.00
full-width footplate, tubular, plastic-coated	30.00	150.00
full-width footplate, angle-adjustable, depth-adjustable	72.00	192.00
full-width footplate, tubular	N/C	120.00
footplates, angle-adjustable, depth-adjustable,		
standard or oversized		
pair	72.00	
each		76.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems: handrims with oblique or vertical projections pair each plastic-coated handrims	155.00	112.00
pair	52.00	
each anodized aluminum handrims combined handrims	N/C	60.00 34.00
pair each	52.00	60.00
anti-tip rollers eair each	95.00	48.00
cane holder	32.00	32.00
Wheel locks: tandard, push-to-lock or pull-to-lock	N/C	44.00
cissor-type wheel locks pair each	55.00	72.00
wheel lock extensions oair ach	32.00	16.00
nti-rollback brakes air ach	98.00	93.00
Types of forks: orks, standard or short	N/C	49.00
ork-locking mechanisms pair pach	100.00	50.00
Rear axles : hreaded axles	N/C	15.00
uick-release axles air ach	76.00	53.00
xtension plates for amputee air	42.00	
ach		21.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Frame: rear wheel camber, 0°, 3°, 5°, 8°	N/C	N/A
Types of wheels:		
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)	27/0	
or 61.0 cm (24 in.)	N/C	90.00
rear mag wheels, standard pressure, 40.6 cm (16 in.),	) N/G	00.00
45.7 cm (18 in.), 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in		90.00
spoked rear wheels, high pressure, 61.0 cm (24 in.)	N/C	126.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	126.00
spoked rear wheels, solid tires, 61.0 cm (24 in.)	N/C N/C	126.00
heavy-duty wheels, standard pressure, high pressure, solid tires,	N/C	120.00
61.0 cm (24 in.)		
pair	79.00	
each	77.00	165.00
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.),		100.00
7.6 cm (3 in.), 12.7 cm (5 in.) or 15.2 cm (6 in.)	N/C	40.00
front wheels, solid tires, 20.3 cm (8 in.) x 3,8 cm ( $1\frac{1}{2}$ in.),		
10.2 cm (4 in.), 12.7 cm (5 in.) or 15.2 cm (6 in.)	N/C	40.00
front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)		
or 20.3 cm (8 in.) x 3.2 cm $(1^{1}/_{4} in.)$		
pair	25.00	
each		52.00
front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)		
pair	48.00	
each		64.00
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4}$ in		
pair	56.00	60.00
each		68.00
Component(s) under Special Consideration		
spoke guards*		
pair	82.00	
each	02.00	41.00
quick-release axles with lever mechanism*		71.00
pair	76.00	
each	. 5.56	53.00

# DEVICE FROM: SUNRISE MEDICAL CANADA INC.

#### PRICE

# MANUAL WHEEL CHAIR, CHILD, "QUICKIE 2" MODEL

\$1 370.00

# **Basic Component(s)**

# **Body support system**

- supple back, nylon
- back height: from 21.6 cm  $(8^{1}/_{2} \text{ in.})$  to 47.0 cm  $(18^{1}/_{2} \text{ in.})$
- supple seat, nylon
- seat width: from 27.9 cm (11 in.) to 38.1 cm (15 in.)
- seat depth: 30.5 cm (12 in.), 35.6 cm (14 in.)
- front seat height: from 43.8 cm  $(17^{1}/_{4} \text{ in.})$  to 54.6 cm  $(21^{1}/_{2} \text{ in.})$
- growth kit including: seat, back, footrests, front frame and crossbars (once only during first three years from date of purchase, for first user)
- safety belt, velcro-type, auto-type
- · push handles

#### Armrests

- "L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- · straight armrest pads, short, long
- · tubular armrest pads
- clothing guards, flexible

#### **Footrests**

- 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- 70° or 80° footrests, detachable, swingaway, length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.)
- padded calfrests
- padded calfrests for legrests, compensating mechanism
- · heel loops, length-adjustable
- folding footplates, standard
- folding footplates, tubular

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock or pull-to-lock
- standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5<sup>1</sup>/<sub>4</sub> in.), high forks,
   17.8 cm (7 in.), for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- standard forks, 17.8 cm (7 in.) for 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- fork stems, + 1.9 cm ( $\frac{3}{4}$  in.), + 3.8 cm ( $\frac{11}{2}$  in.)
- multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- · quick-release axles

- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)
- rear wheel camber, 3°, 6°, 9°
- adjustable axle plates
- · adjustable axle plates, compensated

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic or Optional Component(s)		
Body support system		
Seat and back:		
folding back, angle-adjustable	104.00	N/A
back spreader bar	126.00	N/A
supple back, tension-adjustable	74.00	136.00
supple back, nylon	N/C	62.00
supple seat, nylon	N/C	53.00
modification of seat depth to 25.4 cm (10 in.), 27.9 cm (11 in.)		
or 33.0 cm (13 in.)	39.00	N/A
modification of seat width to 40.6 cm (16 in.)	105.00	N/A
growth kit including: seat, back, footrests, front frame and crossbars		
(once only during first three years from date of purchase, for first user		N/A
modification of back height from 48.3 cm (19 in.) to 55.9 cm (22 in.)		N/A
backposts, angle-adjustable from $-3^{\circ}$ to $+15^{\circ}$ , 3 positions	118.00	N/A
backposts, at an $8^{\circ}$ angle, from 31.8 cm ( $12^{1}/_{2}$ in.) to 47.0 cm ( $18^{1}/_{2}$ in.)		
pair	14.00	
each		26.00
push handles	N/C	19.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
seat cushion, flat, foam, 10.2 cm (4 in.)	56.00	56.00
safety belt, velcro-type	N/C	28.00
safety belt, auto-type	N/C	41.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests :		
"L"-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short "T"-type armrests, detachable, height-adjustable	N/C	93.00
from 19.1 cm ( $7^{1}/_{2}$ in.) to 30.5 cm (12 in.), short or long pair each	77.00	131.50
"U"-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short for angle-adjustable back pair each	160.00	173.00
"I"-type armrests, flip-back, height-adjustable from 22.2 cm (8 <sup>3</sup> / <sub>4</sub> in.) to 34.9 cm (13 <sup>3</sup> / <sub>4</sub> in.), short pair	291.00	173.00
each	291.00	238.50
tubular armrest pads	N/C	2.00
straight armrest pads, long	N/C	17.00
straight armrest pads, short	N/C	15.00
clothing guards, flexible clothing guards, rigid	N/C	21.00
pair	90.00	
each	70.00	66.00
Footrests:		
70° or 80° footrests, heavy-duty		
pair	63.00	
each		84.50
60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	53.00
90° footrests, detachable, swingaway, length-adjustable	N/C	33.00
from 20.3 cm (8 in.) to 33.0 cm (13 in.)	N/C	53.00
70° or 80° footrests, detachable, swingaway, length-adjustable	N/C	55.00
from 15.2 cm (6 in.) to 30.5 cm (12 in.) elevating legrests, compensating mechanism	N/C	55.00
pair	194.00	
each		150.00
90° elevating legrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)		
pair	69.00	
each	52.00	87.50
elevating legrests, detachable, swingaway, length-adjustable		
pair	105.00	
each		105.50
modification of footrest length from 17.8 cm (7 in.)	<b>5</b> 4.00	22.00
to 34.3 cm $(13^{1}/_{2} \text{ in.})$ modification of length of 90° footrests by + 5.1 cm (2 in.)	54.00	33.00
or by + 10.2 cm (4 in.)		
pair	30.00	
each		15.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
padded calfrests	N/C	18.00
contoured calfrests		
pair	70.00	
each		53.00
padded calfrests for legrests, compensating mechanism	N/C	39.00
single calf strap	18.00	18.00
double calf strap	32.00	32.00
folding footplates, standard	N/C	48.00
folding footplates, tubular	N/C	48.00
olding footplates, angle-adjustable		
pair	51.00	
each		73.50
folding footplates, oversized		
pair	71.00	
each		83.50
full-width footplate, angle-adjustable	83.00	179.00
full-width foot platform, 90°	89.00	185.00
neel loops, length-adjustable	N/C	10.00
ront floor rollers		
pair	55.00	
each	22.00	27.50
Front impact guard with rollers		27.50
pair	36.00	
each	30.00	18.00
Wheels and frame		10.00
Types of drive systems :		
one-arm dual handrim drive	546.00	688.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.)	2 .0.00	000.00
or 61.0 cm (24 in.)	N/C	58.00
nandrims with oblique or vertical projections, 61.0 cm (24 in.)	14.0	23.00
pair	88.00	
each		102.00
plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.)		102.00
or 61.0 cm (24 in.)		
pair	54.00	
each	31.00	85.00
non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.)		03.00
oair	164.00	
each	107.00	140.00
small plastic-coated handrim for one-arm drive	54.00	N/A
	J+.UU	IV/A
unti-tip rollers	43.00	
air	45.00	21.50
each eane holder	44.00	21.50
and notice	44.00	44.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks :		
standard wheel locks, push-to-lock or pull-to-lock	N/C	39.00
wheel lock extensions pair	26.00	
each	20.00	13.00
anti-rollback brakes		
pair	66.00	22.00
each wheel locks, push-to-lock or pull-to-lock, unilateral control	124.00	33.00 N/A
Types of forks :		
standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5 <sup>1</sup> / <sub>4</sub> in.)		
or high forks, 17.8 cm (7 in.), for 12.7 cm (5 in.), 15.2 cm (6 in.)	NIC	21.00
and 20.3 cm (8 in.) wheels standard forks, 17.8 cm (7 in.),	N/C	31.00
for 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels	N/C	36.00
fork-locking mechanisms		
pair	44.00	22.00
each fork stems, $+ 1.9 \text{ cm} (\frac{3}{4} \text{ in.}) \text{ or } + 3.8 \text{ cm} (\frac{1}{2} \text{ in.})$	N/C	22.00 16.00
multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.)	IV/C	10.00
and 20.3 cm (8 in.) wheels	N/C	54.00
Rear axles :		
quick-release axles	N/C	32.50
extension plates for amputee pair	42.00	
each	12.00	71.00
curved plates		
pair	28.00	64.00
each rear wheel camber, 3°, 6°, 9°	N/C	64.00 N/A
adjustable axle plates	N/C N/C	50.00
adjustable axle plates, compensated	N/C	63.00
Types of wheels:		
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	149.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.),	N/C	122.00
55.9 cm (22 in.) or 61.0 cm (24 in.) spoked rear wheels, high pressure, 61.0 cm (24 in.)	N/C N/C	132.00 132.00
ear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C N/C	132.00
ear mag wheels, standard pressure, 55.9 cm (22 in.)	100	132.00
or 61.0 cm (24 in.)	N/C	110.00
ear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)	3770	
or 61.0 cm (24 in.)	N/C	132.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)	N/C	61.00
front wheels, solid tires, 15.2 cm (6 in.)	N/C	60.00
front wheels, solid tires, 12.7 cm (5 in.)	N/C	46.00
Front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
pair	47.00	
each		69.50
Front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)	N/C	61.00
ront wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm ( $1^{1}/_{4}$ in.) ront wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm ( $1^{1}/_{2}$ ir	N/C 1.)	60.00
or 15.2 cm (6 in.) x 3.8 cm ( $1^{1}/_{2}$ in.)		
pair	80.00	
each		86.00
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 in.)		
pair	65.00	
each		78.50
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm ( $1^{1}/_{2}$ ir		
pair	100.00	
each		96.00
Component(s) under Special Consideration		
spoke guards*		
pair	67.00	
each		33.50
uick-release axles with lever mechanism*		
pair	64.00	
each		64.50
DEVICE FROM: SUNRISE MEDICAL CANADA INC.		
DEVICE PROME: SUNRISE MEDICAL CANADA INC.		PRI
MANUAL WHEEL CHAIR, CHILD, "ZIPPIE GS" MODEL		\$1 430

# Basic Component(s)

## **Body support system**

- supple back, nylon
- folding back, angle-adjustable and height-adjustable
- back height: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- rigid seat, flat, adjustable
- seat width: from 25.4 cm (10 in.) to 40.6 cm (16 in.)
- seat depth: from 25.4 cm (10 in.) to 45.7 cm (18 in.)
- front seat height: from 35.6 cm (14 in.) to 47.6 cm (18<sup>3</sup>/<sub>4</sub> in.)
- safety belt, velcro-type, auto-type
- push handles
- backposts with push handles at 55.2 cm (21<sup>3</sup>/<sub>4</sub> in.), 62.9 cm (24<sup>3</sup>/<sub>4</sub> in.) or 70.5 cm (27<sup>3</sup>/<sub>4</sub> in.)

#### Armrests

- "T"-type armrests, detachable, height-adjustable from 19.1 cm (7<sup>1</sup>/<sub>2</sub> in.) to 30.5 cm (12 in.), short, long
- "T"-type armrests, detachable, height-adjustable to 14.0 cm (5<sup>1</sup>/<sub>2</sub> in.), 16.5 cm (6<sup>1</sup>/<sub>2</sub> in.), 19.1 cm (7<sup>1</sup>/<sub>2</sub> in.), short
- straight armrest pads, short, long
- tubular armrest pads

#### **Footrests**

- 60° or 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.), parallel
- 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.), parallel
- 70° or 80° footrests, detachable, swingaway, length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.), parallel
- 70°, 80° or 90° footrests, heavy-duty, detachable, non-flip-back
- heel loops, length-adjustable
- folding footplates, standard
- padded calfrests for elevating legrests, compensating mechanism
- · padded calfrests

- · optional rigid frame
- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5<sup>1</sup>/<sub>4</sub> in.), high forks 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- fork stems,  $+ 1.9 \text{ cm} (^{3}/_{4} \text{ in.})$ ,  $+ 3.8 \text{ cm} (^{1}/_{2} \text{ in.})$
- quick-release axles
- rear wheel camber, from 0° to 6°
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic or Optional Component(s)		
Body support system		
Seat and back :		
headrest, small	90.00	93.00
headrest, medium	96.00	103.00
headrest, large	102.00	107.00
transversal bar for headrest mounting (folding)	226.00	242.00
articulated headrest mounting	154.00	168.00
transversal bar for headrest mounting (rigid)	194.00	206.00
folding back, angle-adjustable and height-adjustable	N/C	N/A
supple back, tension-adjustable	74.00	136.00
supple back, nylon	N/C	62.00
rigid seat, flat, adjustable	N/C	126.00
push handles	N/C	N/A
backposts, with push handles at 55.2 cm (21 <sup>3</sup> / <sub>4</sub> in.), 62.9 cm (24 <sup>3</sup> / <sub>4</sub> in.		27/1
or at $70.5 \text{ cm} (27^3/_4 \text{ in.})$	N/C	N/A
back spreader bar	126.00	N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, velcro-type	N/C	28.00
safety belt, auto-type	N/C	41.00
safety belt, airplane-type	49.00	77.00
safety belt, airplane-type, padded	74.00	102.00
Armrests: "T"-type armrests, detachable, height-adjustable		
from 19.1 cm ( $7^{1}/_{2}$ in.) to 30.5 cm (12 in.), short or long	N/C	132.00
"1"-type armrests, flip-back, height-adjustable from 16.5 cm (6 <sup>1</sup> / <sub>2</sub> ir to 33.0 cm (13 in.), short, long		132.00
pair	126.00	
each		195.00
"T"-type armrests, detachable, height-adjustable		
from 14.0 cm ( $5^{1}/_{2}$ in.) to 16.5 cm ( $6^{1}/_{2}$ in.)		
and to 19.1 cm $(7^1/2 \text{ in.})$ , short	N/C	155.00
tubular armrest pads	N/C	2.00
straight armrest pads, long	N/C	17.00
straight armrest pads, short	N/C	15.00
clothing guards, rigid		
pair	90.00	
each		66.00
Footrests:		
60° or 70° footrests, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	53.00
90° footrests, detachable, swingaway, length-adjustable		
from 20.3 cm (8 in.) to 33.0 cm (13 in.)	N/C	55.00
70° or 80° footrests, detachable, swingaway, length-adjustable		
from 15.2 cm (6 in.) to 30.5 cm (12 in.)	N/C	55.00
70°, 80° or 90° footrests, heavy-duty, detachable, non-flip-back	N/C	84.50

elevating legrests, compensating mechanism pair each		of component (unit price)
pair		
each	194.00	
		150.00
90° elevating legrests, detachable, swingaway, length-adjustable		
from 20.3 cm (8 in.) to 33.0 cm (13 in.)	60.00	
pair each	69.00	87.50
each elevating legrests, detachable, swingaway, length-adjustable		87.30
pair	105.00	
each	103.00	105.50
padded calfrests	N/C	18.00
contoured calfrests	1,, 0	10.00
pair	70.00	
each		53.00
padded calfrests for elevating legrests, compensating mechanism	N/C	39.00
modification of footrest length from 48.3 cm (19 in.)	20.00	20.00
to 52.1 cm $(20^{1}/_{2} \text{ in.})$	30.00	29.00
modification of length of 90° footrests by + 5.1 cm (2 in.)	20.00	15.00
or by + 10.2 cm (4 in.) single calf strap	30.00 18.00	15.00 18.00
folding footplates, standard	N/C	48.00
folding footplates, angle-adjustable	100	10.00
pair	51.00	
each		73.50
full-width footplate, angle-adjustable	83.00	179.00
full-width footplate, rigid	89.00	185.00
footrest mounting, from 17.8 cm (7 in.) to $34.3$ cm ( $13^{1}/_{2}$ in.)	~	
pair	54.00	22.00
each heel loops, length-adjustable	N/C	33.00 10.00
leer loops, length-adjustable	N/C	10.00
Wheels and frame		
Types of drive systems : one-arm dual handrim drive	546.00	688.00
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.)	2.0.00	000.00
or 61.0 cm (24 in.)	N/C	58.00
nandrims with oblique or vertical projections		
pair	88.00	
each		102.00
plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	54.00	
oair each	54.00	85.00
non-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.)		05.00
pair	164.00	
each	• •	140.00
small plastic-coated handrim for one-arm drive	54.00	N/A
anti-tip rollers		
pair	43.00	
each	44.00	21.50
cane holder optional rigid frame	44.00 N/C	44.00
andonal rivid frame	N/C	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks: standard wheel locks, push-to-lock or pull-to-lock wheel lock extensions, 15.2 cm (6 in.)	N/C	39.00
pair each	26.00	13.00
anti-rollback brakes pair pach	66.00	33.00
Types of forks: tandard forks, 15.2 cm (6 in.), short forks, 13.3 cm (5 <sup>1</sup> / <sub>4</sub> in.) or high forks, 17.8 cm (7 in.), compatible with 12.7 cm (5 in.),		
5.2 cm (6 in.) and 20.3 cm (8 in.) wheels ork-locking mechanism	N/C	31.00
ork-locking mechanism pair pach	44.00	22.00
Fork stems, + 1.9 cm ( $^{3}/_{4}$ in.) or + 3.8 cm ( $^{1}/_{2}$ in.)	N/C	16.00
Rear axles :	NG	22.50
quick-release axles rear wheel camber, 0° to 6°	N/C N/C	32.50 N/A
Types of wheels:		
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) spoked rear wheels, standard pressure, 50.8 cm (20 in.),	N/C	149.00
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	132.00
poked rear wheels, high pressure, 61.0 cm (24 in.)	N/C	132.00
ear mag wheels, standard pressure, 50.8 cm (20 in.) ear mag wheels, standard pressure, 55.9 cm (22 in.)	N/C	132.00
or 61.0 cm (24 in.) ear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)	N/C	110.00
or 61.0 cm (24 in.)	N/C	132.00
ear mag wheels, standard pressure, 30.5 cm (12 in.) ear mag wheels, standard pressure, 40.6 cm (16 in.)	N/C	126.00
air	32.00	
ach	X	142.00
ront wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)	N/C	61.00
ront wheels, solid tires, 15.2 cm (6 in.) ront wheels, solid tires, 12.7 cm (5 in.)	N/C N/C	60.00 46.00
ront wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)		40.00
pair	47.00	60.70
each		69.50

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.) front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm ( $1^{1}/_{4}$ in.) front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm ( $1^{1}/_{2}$ in or 15.2 cm (6 in.) x 3.8 cm ( $1^{1}/_{2}$ in.)	N/C N/C	61.00 60.00
pair each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1½ in.)	80.00	86.00
pair each	100.00	96.00
Component(s) under Special Consideration		
spoke guards* pair each	67.00	33.50

§2. Lightweight manual wheel chairs

# **DEVICE FROM: INVACARE CANADA INC.**

**PRICE** 

## LIGHTWEIGHT MANUAL WHEEL CHAIR, "A-4/F4" MODEL

\$1 438.00

## **Basic Component(s)**

### **Body support system**

- folding back, height adjustable from 20.3 cm (8 in.) to 50.8 cm (20 in.)
- supple seat and back, nylon
- front seat height: from 43.2 cm (17 in.) to 53.3 cm (21 in.)
- seat width: from 30.5 cm (12 in.) to 50.8 cm (20 in.)
- seat depth: from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- safety belt, velcro-type, auto-type
- · push handles, bolt-on or integrated

## **Armrests**

- "L"-type armrests, detachable, swingaway, height-adjustable from 22.9 cm (9 in.) to 27.9 cm (11 in.), short
- · tubular armrest pads
- · straight armrest pads, short, long
- clothing guards, flexible, rigid

## **Footrests**

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 37.5 cm (14³/₄ in.) to 47.0 cm (18¹/₂ in.), or 70° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 47.0 cm (18¹/₂ in.)
- 80° fixed footrests, pointing inwards, tapered, length-adjustable from 28.6 cm (11<sup>1</sup>/<sub>4</sub> in.) to 51.4 cm (20<sup>1</sup>/<sub>4</sub> in.)
- · folding footplates, standard
- full-width footplate, tubular, one-piece
- full-width footplate, angle-adjustable, depth-adjustable
- single calf strap

- · anodized aluminum handrims
- swing-away brakes, standard, push-to-lock, pull-to-lock
- standard forks, short
- quick-release axles
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear wheels, heavy-duty, standard pressure, high pressure, solid tires, 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear mag wheels, standard pressure, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, solid tires, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- front wheels, solid tires, 7.6 cm (3 in.), 10.2 cm (4 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 2.5 cm (1 in.), 10.2 cm (4 in.) x 2.5 cm (1 in.)
- double camber tubes for the following angles :  $0^{\circ}$ ,  $3^{\circ}$ ,  $6^{\circ}$ ,  $9^{\circ}$  or  $12^{\circ}$

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic or Optional Component(s)		
Body support system		
Seat and back :		
modification of seat width to 53.3 cm (21 in.) or 55.9 cm (22 in.)	51.00	N/A
modification of seat depth to 50.8 cm (20 in.) or 55.9 cm (22 in.)	51.00	N/A
Folding back, height adjustable from 20.3 cm (8 in.) to 50.8 cm (20 in		N/A
supple back, tension-adjustable	63.00	99.00
bush handles, bolt-on or integrated	N/C	38.00
bush handles, quick-release supple back, nylon	63.00 N/C	69.00 36.00
supple back, hylon	N/C N/C	36.00
eat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, velcro-type	N/C	40.00
safety belt, auto-type	N/C	50.00
Armrests:		
"L"-type armrests, detachable, swingaway, height-adjustable	NIC	55.00
from 22.9 cm (9 in.) to 27.9 cm (11 in.), short	N/C	55.00
"T"-type armrests, detachable, height-adjustable from 15.2 cm (6 in.) to 25.4 cm (10 in.) or from 20.3 cm (8 in.)		
10 35.6 cm (14 in.), short or long		
pair	140.00	
each	110.00	125.00
clothing guards, flexible	N/C	15.00
clothing guards, rigid	N/C	46.00
clothing guards, fold-away, non-detachable		
pair	64.00	
each		46.00
ubular armrest pads	N/C	10.00
armrest pads, straight, short or long	N/C	26.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
80° fixed footrests, pointing inwards or tapered,		
from 28.6 cm (11 $\frac{1}{4}$ in.) to 51.4 cm (20 $\frac{1}{4}$ in.)	N/C	N/A
60° footrests, parallel, detachable, swingaway, length-adjustab	le	
from 37.5 cm $(14^3/_4 \text{ in.})$ to 47.0 cm $(18^1/_2 \text{ in.})$ , or 70° footrests, parallel, detachable, swingaway, length-adjustable		
from 34.3 cm $(13^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$	N/C	81.00
70° footrests, tapered, detachable, swingaway, length-adjustab		01.00
from 40.0 cm ( $15^{3}/_{4}$ in.) to 50.2 cm ( $19^{3}/_{4}$ in.)		
pair	107.00	
each		135.00
60° footrests, MFX, parallel, detachable, swingaway, length-adj		
from 27.9 cm (11 in.) to 38.1 cm (15 in.), or 70° footrests, MF	X,	
parallel, detachable, swingaway, length-adjustable		
from 34.3 cm $(13^{1}/_{2} in.)$ to 47.0 cm $(18^{1}/_{2} in.)$	144.00	
pair each	144.00	153.00
single calf strap	N/C	35.00
double calf strap	34.00	52.00
folding footplates, standard	N/C	40.00
full-width footplate, tubular, one-piece	N/C	120.00
over-sized footplates		
pair	39.00	
each		60.00
footplates, standard, angle-adjustable, depth-adjustable	<b>52</b> 00	
pair	72.00	76.00
each full-width footplate, angle-adjustable, depth-adjustable	N/C	76.00 192.00
run-widin 100tpiate, angie-adjustable, deptil-adjustable	IVC	192.00
Wheels and frame		
Types of drive systems :		
handrims with vertical or oblique projections	155.00	
pair each	155.00	112.00
anodized aluminum handrims	N/C	34.00
plastic-coated or combined handrims	100	51.00
pair	52.00	
each		60.00
anti-tip rollers		
pair	95.00	
each	•0.00	48.00
front floor roller	29.00	29.00
quick-release push handles	63.00	69.00
cane holder	32.00	32.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks:		
standard wheel locks, push-to-lock or pull-to-lock scissor-type wheel locks	N/C N/C	44.00 72.00
anti-rollback brakes pair	98.00	02.00
each modification of frame in order to install swingaway footrests	474.00	93.00 N/A
Types of forks:		
forks, standard or short	N/C	49.00
Rear axles:		
quick-release axles	N/C	53.00
double camber tubes for the following angles: 0°, 3°, 6°, 9° or 12°	N/C	101.00
rear wheel camber	49.00	101.00
Types of wheels:		
rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in		22.22
or 61.0 cm (24 in.)	N/C	90.00
rear mag wheels, solid tires, 50.8 (20 in.), 55.9 cm (22 in.)	N/C	00.00
or 61.0 cm (24 in.)	N/C	90.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) or 66.0 cm (26 in.)	N/C	126.00
spoked rear wheels, high pressure, 61.0 cm (24 in.) or 66.0 cm (26 in		126.00
spoked rear wheels, solid tires, 61.0 cm (24 in.) or 66.0 cm (26 in.)	.) N/C N/C	126.00
heavy-duty rear wheels, solid tires, standard or high pressure, 61.0 cm. (24 in.) or 66.0 cm (26 in.)	14/C	120.00
pair	N/C	
each	140	165.00
front wheels, solid tires, 15.2 cm (6 in.), 12.7 cm (5 in.)		100.00
or 7.6 cm (3 in.)	N/C	40.00
front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)		
pair	25.00	
each		52.00
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 2.5 cm (1 in.)	NUG	40.00
or 10.2 cm (4 in.) x 2.5 cm (1 in.)	N/C	40.00
front wheels, solid tires, 7.6 cm (3 in.), 10.2 cm (4 in.), 12.7 cm (5 in		40.00
or 15.2 cm (6 in.)	N/C	40.00
Component(s) under Special Consideration		
spoke guards*		
pair	82.00	
each		41.00
quick-release axles with lever mechanism*	76.00	
pair	76.00	52.00
each		53.00

## DEVICE FROM: SUNRISE MEDIAL CANADA INC.

PRICE

# LIGHTWEIGHT MANUAL WHEEL CHAIR, "QUICKIE R2" MODEL

\$1 350.00

### **Basic Component(s)**

## **Body support system**

- folding back, height adjustable from 20.3 cm (8 in.) to 50.8 cm (20 in.)
- supple seat and back, nylon
- front seat height: from 43.2 cm (17 in.) to 55.56 cm ( $21^{7}/_{8}$  in.)
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- safety belt, velcro-type, auto-type
- · push handles, bolt-on or integrated

#### Armrests

- "L"-type armrests, for fixed frame, for adjustable frame, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- tubular armrest pads
- · clothing guards, flexible, rigid

#### **Footrests**

- 80° fixed footrests, pointing inwards, length-adjustable from 40.0 cm (15<sup>3</sup>/<sub>4</sub> in.) to 52.7 cm (20<sup>3</sup>/<sub>4</sub> in.)
- full-width footplate, angle-adjustable
- single calf strap

- anodized aluminum handrims, 61.0 cm (24 in.), 66.0 cm (26 in.)
- swing-away brakes, standard, push-to-lock or pull-to-lock
- standard forks, 10.8 cm (4<sup>1</sup>/<sub>4</sub> in.) for 7.6 cm (3 in.), 10.2 cm (4 in.) and 12.7 cm (5 in.) wheels
- forks, 13.3 cm (5<sup>1</sup>/<sub>4</sub> in.)
- short forks, 8.3 cm  $(3^{1}/_{4} in.)$  for 7.6 cm (3 in.) and 10.2 cm (4 in.) wheels
- high forks, 12.1 cm (4<sup>3</sup>/<sub>4</sub> in.) for 7.6 cm (3 in.), 10.2 cm (4 in.) and 12.7 cm (5 in.) wheels
- long stems,  $+1.9 \text{ cm} (\frac{3}{4} \text{ in.})$ ,  $+3.8 \text{ cm} (\frac{11}{2} \text{ in.})$
- quick-release axles
- rear wheels, spoked, standard pressure, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear wheels, heavy-duty, standard pressure, high pressure, 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 61.0 cm (24 in.)
- front wheels, solid tires, 12.7 cm (5 in.), 10.2 cm (4 in.), 7.6 cm (3 in.)
- rear wheel camber, simple, 4°, 8°, 16°
- rear wheel camber, double, 0° and 12°, 3° and 12°

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic or Optional Component(s)		
Body support system		
Seat and back: modification of seat width to 48.3 cm (19 in.) or 50.8 cm (20 in.) modification of seat width to 33.0 cm (13 in.) modification of seat depth to 25.4 cm (10 in.) folding back, height adjustable from 20.3 cm (8 in.) to 50.8 cm (20 supple back, tension-adjustable push handles, bolt-on push handles, integrated supple back, nylon supple seat, nylon seat cushion, flat, foam, 5.1 cm (2 in.) seat cushion, flat, foam, 7.6 cm (3 in.) safety belt, velcro-type safety belt, auto-type	680.00 400.00	N/A N/A N/A N/A 139.00 27.00 24.00 65.00 53.00 56.00 56.00 28.00 41.00
Armrests: "L"-type armrests, for fixed frame, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short "L"-type armrests, for adjustable frame, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short clothing guards, flexible clothing guards, rigid tubular armrest pads	N/C N/C N/C N/C N/C	54.00 58.00 15.00 51.00 2.00
<b>Footrests :</b> 80° fixed footrests, pointing inwards, length-adjustable from 40.0 cm $(15^3/_4 \text{ in.})$ to 52.7 cm $(20^3/_4 \text{ in.})$ single calf strap double calf strap full-width footplate, angle-adjustable footplate spacer, 5.1 cm $(2 \text{ in.})$ , $10.2 \text{ cm } (4 \text{ in.})$ or $15.2 \text{ cm } (6 \text{ in.})$ anti-tip rollers	N/C N/C 14.00 N/C 20.00 28.00	N/A 18.00 32.00 108.00 10.00 28.00
Wheels and frame		
Types of drive systems: handrims with vertical or oblique projections, 61.0 cm (24 in.) or 66.0 cm (26 in.) pair each anodized aluminum handrims, 61.0 cm (24 in.) or 66.0 cm (26 in.) plastic-coated handrims, 61.0 cm (24 in.) or 66.0 cm (26 in.) pair	88.00 .) N/C 54.00	102.00 58.00
each	5 1.00	85.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
non-slip handrims, 61.0 cm (24 in.)		
pair	164.00	
each		140.00
anti-tip rollers	42.00	
oair each	43.00	21.50
nodification of angle of fixed frame	570.00	N/A
djustable frame option	145.00	N/A
Vheel locks :		
tandard wheel locks, push-to-lock	N/C	58.50
tandard wheel locks, pull-to-lock	N/C	58.50
cissor-type wheel locks	N/C	72.00
wheel lock extensions		
pair	26.00	
ach		13.00
nti-rollback brakes	62.00	
oair each	02.00	31.00
acii		31.00
Types of forks:		
orks, $13.3 \text{ cm } (5^{1}/_{4} \text{ in.})$	N/C	31.00
tandard forks, 10.8 cm ( $4^{1}/_{4}$ in.) for 7.6 cm (3 in.), 10.2 cm (4 in.)	N/C	25.00
nd 12.7 cm (5 in.) wheels hort forks, 8.3 cm (3 <sup>1</sup> / <sub>4</sub> in.) for 7.6 cm (3 in.)	N/C	35.00
and 10.2 cm (4 in.) wheels	N/C	40.00
igh forks, 12.1 cm ( $4^{3}/_{4}$ in.), for 7.6 cm (3 in.), 10.2 cm (4 in.)	1,, 0	
and 12.7 cm (5 in.) wheels	N/C	31.00
ong stems, $+1.9 \text{ cm} ({}^{3}/_{4} \text{ in.}) \text{ or } +3.8 \text{ cm} ({}^{1}/_{2} \text{ in.})$	N/C	16.00
Rear axles :		
uick-release axles	N/C	32.50
ear wheel camber, simple, 4°, 8° or 16°	N/C	76.50
ouble camber tubes for the following angles: 0°, 3°, 6°, 9° or 12°	NIC	112.50
ear wheel camber, double, 0° and 12° or 3° and 12° other rear wheel cambers	N/C 46.00	112.50 N/A
diet teat wheet cambers	40.00	IN/A
Types of wheels:		
ear mag wheels, standard pressure, 61.0 cm (24 in.)	N/C	110.00
poked rear wheels, standard pressure, 61.0 cm (24 in.)	MG	122.00
or 66.0 cm (26 in.)	N/C	132.00
poked rear wheels, high pressure, 61.0 cm (24 in.) or 66.0 cm (26 in. eavy-duty rear wheels, standard pressure or high pressure,	) N/C	132.00
1.0 cm (24 in.)	N/C	193.00
neavy-duty rear wheels, standard pressure or high pressure,	14/6	173.00
6.0 cm (26 in.)		
air	55.00	
ach		220.00
ront wheels, solid tires, 12.7 cm (5 in.), 10.2 cm (4 in.)	NIC	16.60
r 7.6 cm (3 in.)	N/C	46.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 in.) pair each	65.00	78.50
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm (1 $^{1}$ / $_{2}$ in pair each	80.00	86.00
front wheels, semi-pneumatic tires, 10.2 cm (4 in.) pair each	24.00	70.00
Component(s) under Special Consideration		
spoke guards* pair each	67.00	33.50
quick-release axles with lever mechanism* pair each	64.00	64.50
neavy-duty axles* pair each	99.00	82.00

## §3. Powered wheel chairs

# **DEVICE FROM: INVACARE CANADA INC.**

**PRICE** 

# POWERED WHEEL CHAIR, "STORM ARROW" MODEL

\$4 706.00

# Basic Component(s)

# **Body support system**

- supple back, leatherette, nylon
- rigid seat, flat
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depths: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat height:  $44.5 \text{ cm} (17^{1}/_{2} \text{ in.}) \text{ to } 50.2 \text{ cm} (19^{3}/_{4} \text{ in.})$
- back height: from 30.5 cm (12 in.) to 48.3 cm (19 in.)
- · push handles
- push bar
- safety belt, auto-type
- · centre of gravity adjustment from seat

## **Armrests**

- "U"-type armrests, detachable, flip-back, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short, long
- "U"-type armrests, fixed height, short, long
- · armrest pads, straight, contoured, short, long
- rigid clothing guards, built into armrests

#### **Footrests**

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13<sup>1</sup>/<sub>2</sub> in.) to 44.5 cm (17<sup>1</sup>/<sub>2</sub> in.), or 70° footrests, parallel, detachable, swingaway, length-adjustable from 29.8 cm (11<sup>3</sup>/<sub>4</sub> in.) to 43.2 cm (17 in.)
- 70° footrests, tapered, detachable, swingaway, length-adjustable from 33.7 cm (13<sup>1</sup>/<sub>4</sub> in.) to 43.8 cm (17<sup>1</sup>/<sub>4</sub> in.)
- padded calfrests
- folding footplates, standard
- heel loops, non-adjustable
- · heel loops, length-adjustable

# **Drive system**

- programmable joystick control
- battery charge display
- battery charger
- battery box, group 22, group 24
- toggle switch
- · direction joystick
- controller
- 4-brush motors with gears
- G/B motors with gears
- side bracket for joystick control, swivel side bracket for joystick control, midline bracket for joystick control
- · anti-tip rollers

- reflector strips
- standard forks
- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.), 20.3 cm (8 in.) x 4.4 cm (1<sup>3</sup>/<sub>4</sub> in.)
- · tie-down points for adapted transport
- running lights
- · front wheel rims
- · rear wheel rims
- · rear suspension

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, flat	80.00	80.00
small headrest	106.00	106.00
large headrest	106.00	106.00
combined headrest/neckrest	106.00	106.00
headrest mounting, fixed	53.00	53.00
headrest mounting, articulated	122.00	122.00
seat/back structure with angle-adjustable back	566.00	566.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
padded back, contoured, leatherette	399.00	399.00
padded back, contoured, fabric	299.00	299.00
padded back, contoured, fabric, non-standard sizes	379.00	379.00
padded back, contoured, leatherette, non-standard sizes	479.00	479.00
padded seat, contoured, fabric	241.00	241.00
padded seat, contoured, fabric, non-standard sizes	318.00	318.00
padded seat, contoured, leatherette	341.00	341.00
padded seat, contoured, leatherette, non-standard sizes	422.00	422.00
rigid seat, flat	N/C	75.00
modification of back height to 50.8 cm (20 in.), 53.3 cm (21 in.),	100	73.00
55.9 cm (22 in.), 58.4 cm (23 in.) or 61.0 cm (24 in.)	89.00	85.00
modification of seat depth to 48.3 cm (19 in.) or to 50.8 cm (20 in.)		N/A
modification of seat depth to 30.5 cm (12 in.), 33.0 cm (13 in.),		
35.6 cm (14 in.) or 38.1 cm (15 in.)	62.00	N/A
modification of seat depth to 53.3 cm (21 in.) or to 55.9 cm (22 in.) modification of seat width to 48.3 cm (19 in.), 50.8 cm (20 in.),	225.00	N/A
53.3 cm (21 in.) or 55.9 cm (22 in.)	225.00	N/A
modification of seat width to 58.4 cm (23 in.) or 61.0 cm (24 in.)	277.00	N/A
modification of seat height to 54.6 cm (21½ in.)	134.00	N/A
centre of gravity adjustment from seat	N/C	N/A
supple back, nylon	N/C	58.00
supple back, leatherette	N/C	58.00
push handles	N/C	40.00
push bar	N/C	58.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, auto-type	N/C	50.00
Armrests:		
"U"-type armrests, detachable, flip-back, height-adjustable		
from 20.3 cm (8 in.) to 30.5 cm (12 in.), short or long	N/C	115.00
"U"-type armrests, fixed height, short, long	N/C	96.00
padded armrests, straight or contoured, short, long	N/C	26.00
rigid clothing guards built into armrests	N/C	N/A
modification of armrest height by – 2.5 cm (1 in.)	179.00	N/A
Footrests:		
60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13½ in.) to 44.5 cm (17½ in.), or 70° footrests, parallel, detachable, swingaway, length-adjustable		
from 29.8 cm (11 <sup>3</sup> / <sub>4</sub> in.) to 43.2 cm (17 in.) 70° footrests, tapered, detachable, swingaway, length-adjustable	N/C	81.00
from 33.7 cm (13 <sup>1</sup> / <sub>4</sub> in.) to 43.8 cm (17 <sup>1</sup> / <sub>4</sub> in.) 60° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 24.1 cm (9 <sup>1</sup> / <sub>2</sub> in.) to 36.8 cm (14 <sup>1</sup> / <sub>2</sub> in.), or 70° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 11.4 cm (4 <sup>1</sup> / <sub>2</sub> in.) to 25.4 cm (10 in.)	N/C	135.00
pair	107.00	
each	107.00	135.00
Cacii		133.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
90° elevating legrests, detachable, swingaway, length-adjustable		
from 12.7 cm (5 in.) to 20.3 cm (8 in.)		
pair	107.00	427.00
each		135.00
elevating legrests, detachable, swingaway, length-adjustable from 40.6 cm (16 in.) to 50.8 cm (20 in.)		
pair	230.00	
each		196.00
elevating legrests with compensating mechanism, detachable, swingaway, length-adjustable from 43.8 cm (17 <sup>1</sup> / <sub>4</sub> in.)		
to 54.6 cm (21 <sup>1</sup> / <sub>2</sub> in.)		
pair	230.00	
each		196.00
modification of elevating legrest length by – 2.5 cm (1 in.)		
or by – 5.1 cm (2 in.)	190.00	190.00
padded calfrests	N/C	20.00
single calf strap	22.00	34.00
double calf strap	35.00	52.00
folding footplates, standard	N/C	40.00
folding footplates, oversized pair	39.00	
each	37.00	60.00
folding footplates, standard, angle-adjustable		00.00
pair	72.00	
each		76.00
folding footplates, oversized, angle-adjustable		
pair	72.00	
each		76.00
heel loops, non-adjustable	N/C	5.00
heel loops, length-adjustable	N/C	12.00
Wheels and frame		
Types of drive systems: programmable joystick control	N/C	479.00
compact joystick control (requires display)	340.00	819.00
neavy-duty joystick control (requires display and interface)	96.00	575.00
modification of joystick control, each	60.00	60.00
pattery charge display	N/C	N/A
pattery charger	N/C	401.00
pattery boxes, group 24	N/C	201.00
pattery box, group 22	N/C	185.00
ouch pad control	214.00	693.00
control with separate switches (requires display and interface)	200.00	679.00
proportional chin control (requires display)	354.00	833.00
non-proportional chin control (requires display and interface)	368.00	847.00
oreath control	1 740.00	1 740.00
nead control	1 426.00 1 159.00	1 905.00
antrovy touch syvitah control (magnines dismlay)	1 1 19 00	1 636.00
laptray touch switch control (requires display) foot control (requires display) toggle switch	1 159.00 1 159.00 N/C	1 636.00 21.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
mergency stop ribbon switch	25.00	75.00
dapted controls interface	692.00	692.00
ion-proportional controls interface	692.00	692.00
eparate display module	1 099.00	1 099.00
lirection joystick	N/C	126.00
tick extension	19.00	19.00
all extension	5.00	5.00
T"-type extension	19.00	19.00
	N/C	250.00
wivel side bracket for joystick control		
ide bracket for joystick control	N/C	12.00
nidline bracket for joystick control	N/C	190.00
reath control bracket	357.00	357.00
hin control bracket	357.00	357.00
ead control bracket	150.00	150.00
racket for separate display module	115.00	115.00
hin control bib	220.00	220.00
ontroller	N/C	1 358.00
-brush motors with gears	N/C	1 139.00
G/B motors with gears	N/C	1 139.00
nti-tip rollers	N/C	60.00
eavy-duty base	557.00	N/A
ear suspension	N/C	119.00
•	N/C	119.00
Types of wheels:	NI/C	54.00
tandard forks	N/C	54.00
eflector strips	N/C	N/A
e-down points for adapted transport	N/C	75.00
unning lights	N/C	N/A
uxiliary manual brakes		
air	72.00	
ach		45.00
uspension forks		
air	130.00	
ach		119.00
ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	55.00
ront wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)		
$r 20.3 \text{ cm } (8 \text{ in.}) \times 4.4 \text{ cm } (1^{3}/_{4} \text{ in.})$	N/C	40.00
ear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)	N/C	75.00
ront wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm ( $2^3$ / <sub>4</sub> in.)	IV.C	73.00
	00.00	
air	90.00	05.00
ach		85.00
ear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)	110.00	
air	118.00	
ach		134.00
ont wheel rims	N/C	43.00
ear wheel rims	N/C	50.00
irless inserts for rear wheels		
	95.00	
air		37/4
air ach		N/A
ach		N/A
	109.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
seat/back structure, reclining back with cylinder*	752.00	752.00
connecting cables for power reclining devices*	161.00	161.00
control system for one power accessory only*	461.00	695.00
control system for two power accessories*	327.00	798.00
control system for two additional accessories*	327.00	798.00
power rocker device, factory installed* power elevating legrests, with individual control (requires TAC control module)*	1 300.00	1 550.00
pair	1 435.00	
each		3 190.00
TAC control module*	499.00	882.00

### **DEVICE FROM: ORTHOFAB INC.**

### **PRICE**

# POWERED WHEEL CHAIR, "PRIMA ML" MODEL

\$3 875.00

# **Basic Component(s)**

# **Body support system**

- supple seat and back, nylon
- back heights: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.)
- seat widths: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depths: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- · push handles
- safety belt, auto-type
- front seat height:  $47.0 \text{ cm} (18^{1}/_{2} \text{ in.})$ ; rear seat height:  $43.8 \text{ cm} (17^{1}/_{4} \text{ in.})$
- modification of front seat height by + or − 1.9 cm (<sup>3</sup>/<sub>4</sub> in.), and rear seat height to 42.5 cm (16<sup>3</sup>/<sub>4</sub> in.)
- seat/back structure, angle-adjustable back
- · back spreader bar

#### Armrests

- "U"-type armrests, flip-back, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- · straight armrest pads, short, long
- · rigid clothing guards

# **Footrests**

- 60° or 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- · padded calfrests, straight
- folding footplates, standard
- heel loops, length-adjustable

# **Drive system**

- conical-spherical extension
- battery charge display
- battery charger
- battery boxes, group U1
- · direction joystick
- · push-button switch
- joystick with integrated controller
- motors, 8.3 km/h (5.0 mph)
- swivel side bracket for joystick control
- · anti-tip rollers

- · standard forks
- · tie-down points for adapted transport
- reflector strips
- front wheels, inner tube tires, 17.8 cm (7 in.) x 4.4 cm (1<sup>3</sup>/<sub>4</sub> in.), 20.3 cm (8 in.) x 5.1 cm (2 in.), 15.2 cm (6 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)
- rear wheels, inner tube tires, 25.4 cm (10 in.) x 7.6 cm (3 in.)
- · rear wheel rims, front wheel rims
- · auxiliary frame for motors

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, contoured	100.00	100.00
articulated headrest mounting, uniball	115.00	115.00
articulated headrest mounting	102.00	102.00
seat/back structure with angle-adjustable back	N/C	N/A
back spreader bar	N/C	N/A
supple back, nylon	N/C	64.00
supple back, tension-adjustable	69.00	133.00
rigid seat, flat	116.00	173.00
supple seat, nylon	N/C	57.00
modification of seat width to 48.3 cm (19 in.) or 50.8 cm (20 in.)	101.00	N/A
safety belt, velcro-type	27.00	62.00
safety belt, auto-type	N/C	35.00
safety belt, airplane-type	38.00	73.00
oush handles	N/C	N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.) modification of front seat height by $+$ or $-1.9$ cm ( $^{3}/_{4}$ in.)	56.00	56.00
and rear seat height to 42.5 cm $(16^3/_4 \text{ in.})$	N/C	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
'U"-type armrests, flip-back, height-adjustable from 20.3 cm (8 in.)		
to 30.5 cm (12 in.), short	N/C	94.00
'U"-type armrests, flip-back, height-adjustable from 20.3 cm (8 in.)		
o 30.5 cm (12 in.), long	52.00	
oair each	52.00	120.00
straight armrest pads, short	N/C	12.00
straight armrest pads, long	N/C	15.00
contoured armrest pads, short	1400	13.00
pair	44.00	
each		34.00
contoured armrest pads, long		
pair	48.00	
each		39.00
modification of height of "U"-type armrests to over 30.5 cm (12 in.)		27/4
or to under 20.3 cm (8 in.)	79.00	N/A
rigid clothing guards	N/C	N/A
Footrests :		
70° footrests, tapered, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	102.00
60° footrests, tapered, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	102.00
50° or 70° footrests, parallel, detachable, swingaway, length-adjustable		27/4
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	29.00	N/A
elevating legrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
oair	166.00	
each	100.00	185.00
elevating legrests, compensating mechanism, detachable,		105.00
ength-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
pair	234.00	
each		219.00
modification of footrest length to over 48.3 cm (19 in.)		
or to under 35.6 cm (14 in.)	79.00	N/A
padded calfrests, straight	N/C	20.00
padded calfrests, contoured	60.00	
oair each	60.00	50.00
louble calf strap	55.00	55.00
Folding footplates, standard	N/C	16.00
Folding footplates, aluminum	100	10.00
pair	40.00	
each		36.00
olding footplates, oversized		
pair	72.00	
each		52.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
footplates, standard size, angle-adjustable and depth-adjustable		
pair	72.00	
each		52.00
footplates, oversized, angle-adjustable and depth-adjustable		
pair	78.00	
each	4.50.00	55.00
full-width footplate	168.00	200.00
neel loops, length-adjustable	N/C	11.00
oe loops	20.00	
pair	30.00	17.00
each		15.00
ront impact guard with rollers	26.00	
pair	36.00	10.00
each		18.00
Wheels and frame		
Types of drive systems :		
oystick control with integrated controller	N/C	980.00
pattery charge display	N/C	N/A
pattery charger	N/C	359.00
pattery boxes, group U1	N/C	122.00
bush-button switch	N/C	N/A
lirection joystick	N/C	N/A
stick extension	19.00	27.00
pall extension	19.00	27.00
'T"-type extension	27.00	35.00
nushroom-shaped extension	19.00	27.00
conical-spherical extension	N/C	8.00
swivel side bracket for joystick control	N/C	202.00
motors, 8.3 km/h (5.0 mph)	N/C	N/A
anti-tip rollers	N/C	N/A
Types of wheels:		
standard forks	N/C	38.00
nuxiliary frame for motor	N/C	336.00
eflector strips	N/C	20.00
ie-down points for adapted transport uxiliary manual brakes	N/C	N/A
pair	106.00	
each		53.00
rear wheels, inner tube tires, 25.4 cm (10 in.) x 7.6 cm (3 in.) ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	84.00
or 15.2 cm (6 in.) x 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	N/C	46.00
front wheels, inner tube tires, 17.8 cm (7 in.) x 4.4 cm ( $1^{3}/_{4}$ in.)	N/C	46.00
irless inserts for front wheels	73.00	N/A
irless inserts for rear wheels	138.00	N/A
ear wheel rims	N/C	N/A
Front wheel rims	N/C	N/A

### **DEVICE FROM: ORTHOFAB INC.**

### **PRICE**

# POWERED WHEEL CHAIR, "OASIS" MODEL

\$4 749.00

## **Basic Component(s)**

### **Body support system**

- rigid seat, flat
- back heights: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.)
- · rigid seat, flat
- seat widths: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depths: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- · push handles
- safety belt, auto-type
- seat height: from 41.9 cm  $(16^{1}/_{2} \text{ in.})$  to 50.8 cm (20 in.)
- adjustable seat bracket
- · centre of gravity adjustment from seat

#### Armrests

- "T"-type armrest, detachable, height-adjustable from 20.3 cm (8 in.) to 27.9 cm (11 in.), from 27.9 cm (11 in.) to 35.6 cm (14 in.), short
- straight armrest pads, short, long
- rigid clothing guards

#### **Footrests**

- 70° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests, straight
- folding footplates, standard
- · heel loops, length-adjustable

### **Drive system**

- programmable joystick control
- conical-spherical extension
- battery charge display
- · battery charger
- battery box, group 22, group 24
- direction joystick
- breath control (requires an interface)
- push-button switch
- PILOT + controller
- motors, 11.5 km/h (6.9 mph)
- side bracket for joystick control, swivel side bracket for joystick control
- · anti-tip rollers

- · standard forks
- tie-down points for adapted transport
- · reflector strips
- running lights
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- modification of frame length
- · rear wheel rims
- · front wheel rims
- · rear suspension

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
padded headrest, contoured	100.00	100.00
articulated headrest mounting, uniball	115.00	115.00
articulated headrest mounting	102.00	102.00
adjustable seat bracket	N/C	127.00
seat/back structure with angle-adjustable back	750.00	750.00
reinforcement of seat/back structure	447.00	N/A
rigid back, flat	N/C	55.00
padded back, contoured, nylon	118.00	118.00
padded back, contoured, leatherette	118.00	118.00
padded seat, contoured, nylon	210.00	210.00
padded seat, contoured, leatherette	210.00	210.00
rigid seat, flat	N/C	55.00
rigid seat with plastic webbing	43.00	98.00
supple back, tension-adjustable	78.00	133.00
igid back, contoured	195.00	250.00
supple back, nylon	9.00	64.00
centre of gravity adjustment from seat	N/C	N/A
modification of back height to 38.1 cm (15 in.), 50.8 cm (20 in.),		
53.3 cm (21 in.) or 55.9 cm (22 in.)	96.00	N/A
modification of seat depth to 38.1 cm (15 in.) or 48.3 cm (19 in.)	264.00	N/A
modification of seat depth to 50.8 cm (20 in.) or 53.3 cm (21 in.) modification of seat width to 48.3 cm (19 in.), 50.8 cm (20 in.),	500.00	N/A
53.3 cm (21 in.) or 55.9 cm (22 in.)	290.00	N/A
modification of seat height by $+2.5 \text{ cm } (1 \text{ in.}), +5.1 \text{ cm } (2 \text{ in.})$	2,0.00	- 1,112
or + 7.6 cm (3 in.)	285.00	N/A
safety belt, velcro-type	27.00	63.00
afety belt, auto-type	N/C	36.00
afety belt, airplane-type	38.00	74.00
oush handles	N/C	N/A
teat cushion, flat, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, 7.6 cm (3 in.)	56.00	56.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
"T"-type armrests, detachable, height-adjustable from 20.3 cm (8		
to 27.9 cm (11 in.) or from 27.9 cm (11 in.) to 35.6 cm (14 in.), sl		94.00
"T"-type armrests, detachable, height-adjustable from 20.3 cm (8		
to 27.9 cm (11 in.) or from 27.9 cm (11 in.) to 35.6 cm (14 in.), lo		
pair	52.00	120.00
each		120.00
"I"-type armrests, height-adjustable from 25.4 cm (10 in.)		
to 33.0 cm (13 in.), short	82.00	
each	82.00	135.00
straight armrest pads, short	N/C	12.00
straight armrest pads, short	N/C	15.00
contoured armrest pads, short	44.00	34.00
contoured armrest pads, long	48.00	39.00
modification of armrest height to under 20.3 cm (8 in.)	79.00	N/A
rigid clothing guards	N/C	N/A
T		
<b>Footrests:</b> 70° footrests, detachable, swingaway, length-adjustable		
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	78.00
modification of footrest length to under 35.6 cm (14 in.)	14/6	70.00
or to over 48.3 cm (19 in.) for 70° footrests	79.00	N/A
elevating legrests, detachable, swingaway, length-adjustable	7,7,00	1,112
from 27.9 cm (11 in.) to 48.3 cm (19 in.)		
pair	214.00	
each		185.00
elevating legrests, compensating mechanism, length-adjustable		
from 30.5 cm (12 in.) to 48.3 cm (19 in.)		
pair	240.00	
each		198.00
padded calfrests, straight	N/C	20.00
padded calfrests, contoured	60.00	
pair	60.00	<b>70.00</b>
each	55.00	50.00
double calf strap	55.00 N/C	55.00 36.00
folding footplates, standard	IN/C	30.00
folding footplates, oversized pair	38.00	
each	30.00	55.00
footplates, angle-adjustable and depth-adjustable, standard size		55.00
pair	32.00	
each	32.00	52.00
folding footplates, oversized		32.00
pair	32.00	
		52.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
full-width footplate	171.00	243.00
heel loops, length-adjustable	N/C	11.00
toe loops		
pair	30.00	
each		15.00
front impact guard with rollers		
pair	36.00	
each		18.00
Wheels and frame		
Types of drive systems :		
programmable joystick control	N/C	492.00
compact joystick control	56.00	548.00
battery charge display	N/C	N/A
battery charger	N/C	359.00
battery box, group 22 or group 24	N/C	208.00
proportional chin control	631.00	631.00
non-proportional chin control (requires interface)	421.00	421.00
head control	1 059.00	1 059.00
breath control (requires interface)	N/C	N/A
laptray touch switch control (requires interface)	301.00	301.00
control with separate switches (requires interface)	530.00	530.00
chin control bib	290.00	290.00
swivel mounting hardware for breath control	385.00	385.00
swivel mounting hardware for chin control	385.00	385.00
adapted controls interface	1 608.00	2 100.00
head control bracket	385.00	385.00
fixed bracket for separate display module	37.00	37.00
flexible bracket for separate display module	120.00	120.00
push-button switch	N/C	N/A
direction joystick	N/C	N/A
stick extension	19.00	27.00
ball extension	19.00	27.00
"T"-type extension	27.00	35.00
mushroom-shaped extension	19.00	27.00
conical-spherical extension	N/C	8.00
side bracket for joystick control	N/C	39.00
swivel side bracket for joystick control	N/C	202.00
swivel midline bracket for joystick control	85.00	287.00
modification of joystick control: switches and potentiometer	75.00	567.00
PILOT + controller	N/C	1 382.00
motors, 11.5 km/h (6.9 mph)	N/C	N/A
anti-tip rollers	N/C	60.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheel :		
standard forks	N/C	87.00
reflector strips	N/C	20.00
running lights	N/C	N/A
tie-down points for adapted transport	N/C	N/A
modification of frame length	N/C	N/A
rear suspension	N/C	N/A
front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	85.00
rear wheels, inner tube tires, $25.6 \text{ cm}$ (6 iii.) x $7.6 \text{ cm}$ (3 iii.) front wheels, inner tube tires, $22.9 \text{ cm}$ (9 iii.) x $7 \text{ cm}$ ( $2^3l_4$ iii.)	N/C	102.00
pair	89.00	
each	07.00	129.00
airless inserts for front wheels, 20.3 cm (8 in.) x 5.1 cm (2 in.)	133.00	N/A
front wheels, puncture-resistant tires, 22.9 cm (9 in.) x 7 cm ( $2^{3}/_{4}$ )		N/A
airless inserts for rear wheels	151.00	N/A
rear wheel rims	N/C	N/A
front wheel rims	N/C	N/A
Component(s) under Special Consideration		
seat/back structure, reclining back with cylinder*	862.00	862.00
power reclining back, factory-installed*	1 145.00	1 545.00
power rechang back, factory installed, including shroud* power elevating legrests, length-adjustable from 30.5 cm (12 in.) to 48.3 cm (19 in.), with individual controls*	N/C	2 375.00
pair	1 259.00	
each		706.00
power elevating legrests, length-adjustable from 30.5 cm (12 in.) to 48.3 cm (19 in.), with dual controls*		
pair	1 259.00	
each		706.00
control system for one power accessory only*	250.00	250.00

# **DEVICE FROM: ORTHOFAB INC.**

**PRICE** 

# POWERED WHEEL CHAIR, "OASIS A600" MODEL

\$4 749.00

# Basic Component(s)

# **Body support system**

- supple back, nylon
- back heights: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.)
- rigid seat, flat
- seat widths: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depths: 40.6 cm (16 in.), 43.2 cm (17 in.) 45.7 cm (18 in.)
- push handles
- safety belt, auto-type
- seat height: from  $41.9 \text{ cm} (16^{1}/_{2} \text{ in.})$  to 50.8 cm (20 in.)
- adjustable seat bracket
- · centre of gravity adjustment from seat

#### Armrests

- "U"-type armrests, flip-back, height-adjustable from 22.9 cm (9 in.) to 30.5 cm (12 in.), short
- · straight armrest pads, short, long
- rigid clothing guards

#### **Footrests**

- 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests
- folding footplates, standard
- · heel loops, length-adjustable

## **Drive system**

- · programmable joystick control
- conical-spherical extension
- battery charge display
- · battery charger
- battery box, group 22, group 24
- direction joystick
- breath control (requires an interface)
- push-button switch
- PILOT + controller
- motors, 11.5 km/h (6.9 mph)
- side bracket for joystick control, swivel side bracket for joystick control
- anti-tip rollers

- · standard forks
- · tie-down points for adapted transport
- reflector strips
- running lights
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- modification of length of frame
- · front wheel rims
- · rear wheel rims
- · rear suspension

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
padded headrest, contoured	100.00	100.00
headrest, hammock-type	75.00	75.00
articulated headrest mounting, uniball	115.00	115.00
articulated headrest mounting	102.00	102.00
adjustable seat bracket	N/C	127.00
A600 seat/back structure with angle-adjustable back	544.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
supple back, nylon	N/C	64.00
supple back, tension-adjustable	69.00	133.00
rigid seat, flat	N/C	81.00
modification of height of non-reclining back to 50.8 cm (20 in.)	96.00	N/A
nodification of seat depth to 48.3 cm (19 in.)	264.00	N/A
nodification of seat width to 50.8 cm (20 in.)	290.00	N/A
nodification of seat height by $+2.5$ cm $(1 in.)$ , $+5.1$ cm $(2 in.)$ ,		
r + 7.6  cm  (3  in.)	285.00	N/A
afety belt, velcro-type	27.00	63.00
afety belt, auto-type	N/C	36.00
afety belt, airplane-type	38.00	74.00
ush handles	N/C	N/A
eat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
eat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
Armrests:		
U"-type armrests, flip-back, height-adjustable from 22.9 cm (9 in.)		
30.5 cm (12 in.), short	N/C	94.00
U"-type armrests, flip-back, height-adjustable from 22.9 cm (9 in.		
30.5 cm (12 in.), long	52.00	120.00
traight armrest pads, short	N/C	12.00
traight armrest pads, long	N/C	15.00
ontoured armrest pads, short	4.4.00	
air	44.00	24.00
ach		34.00
ontoured armrest pads, long	40.00	
air	48.00	
ach		39.00
gid clothing guards	N/C	N/A
nodification of armrest height to under 22.9 cm (9 in.)	<b>7</b> 0.00	37/4
r to over 30.5 cm (12 in.)	79.00	N/A
ootrests:		
0° footrests, tapered, detachable, swingaway, length-adjustable rom 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	102.00
0° footrests, parallel, detachable, swingaway, length-adjustable	IV/C	102.00
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	29.00	N/A
levating legrests, detachable, swingaway, length-adjustable	49.00	IN/A
om 35.6 cm (14 in.) to 48.3 cm (19 in.)		
air	165.00	
arr ach	103.00	185.00
evating footrests, compensating mechanism, detachable,		165.00
ength-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
air	234.00	
arr ach	434.00	219.00
acii		219.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
modification of legrest length to under 35.6 cm (14 in.)		
or to over 48.3 cm (19 in.)	79.00	N/A
padded calfrests	N/C	20.00
contoured calfrests		
pair	60.00	
each		50.00
double calf strap	55.00	55.00
folding footplates, standard	N/C	16.00
folding footplates, aluminum		
pair	41.00	
each		36.00
folding footplates, standard size, angle-adjustable and depth-ac	ljustable	
pair	72.00	
each		52.00
folding footplates, oversized, angle adjustable and depth-adju	ıstable	
pair	79.00	
each		55.00
full-width footplate, angle-adjustable	168.00	200.00
heel loops, length-adjustable	N/C	11.00
toe loops		
pair	30.00	
each		15.00
front impact guard with rollers		
pair	36.00	
each		18.00
Wheels and frame		
Types of drive systems:		
programmable joystick control	N/C	492.00
compact joystick control	56.00	548.00
battery charge display	N/C	N/A
battery charger	N/C	359.00
battery box, group 22 or group 24	N/C	208.00
proportional chin control	631.00	631.00
non-proportional chin control (requires interface)	421.00	421.00
head control	1 059.00	1 059.00
breath control (requires interface)	N/C	N/A
laptray touch switch control (requires interface)	301.00	301.00
control with separate switches (requires interface)	530.00	530.00
adapted controls interface	1 608.00	2 100.00
chin control bib	290.00	290.00
swivel mounting hardware for breath control	385.00	385.00
swivel mounting hardware for chin control	385.00	385.00
head control bracket	385.00	385.00
bracket for separate display module	37.00	37.00
flexible bracket for separate display module	120.00	120.00
push-button switch	N/C	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
direction joystick	N/C	N/A
stick extension	19.00	27.00
ball extension	19.00	27.00
"T"-type extension	27.00	35.00
mushroom-shaped extension	19.00	27.00
conical-spherical extension	N/C	8.00
side bracket for joystick control	N/C	39.00
swivel side bracket for joystick control	N/C	202.00
swivel midline bracket for joystick control	85.00	287.00
modification of joystick control: switches and potentiometer	75.00	567.00
PILOT + controller	N/C	1 382.00
motors, 11.5 km/h (6.9 mph)	N/C	N/A
anti-tip rollers	N/C	60.00
Types of wheels:		
standard forks	N/C	87.00
reflector strips	N/C	20.00
running lights	N/C	N/A
tie-down points for adapted transport	N/C	N/A
modification of frame length	N/C	N/A
rear suspension	N/C	N/A
front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	85.00
rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm $(2^3/_4 \text{ in.})$	N/C	102.00
pair	89.00	
each	0,00	129.00
airless inserts for front wheels	133.00	N/A
airless inserts for rear wheels	151.00	N/A
airless inserts for 22.9 cm (9 in.) x 7.0 cm ( $2^{3}/_{4}$ in.) wheels	224.00	N/A
rear wheel rims	N/C	N/A
front wheel rims	N/C	N/A
Component(s) under Special Consideration		
A600 seat/back structure, reclining back with cylinder with a height of 45.7 cm (18 in.), 50.8 cm (20 in.), 55.9 cm (22 in.)	,	
61.0 cm (24 in.) or 66.0 cm (26 in.)*	699.00	699.00
power rocker device, 45°, factory-installed, including shroud*	N/C	2 375.00
control system for one power accessory only*	250.00	250.00
control system for four power accessories*	740.00	740.00

### **DEVICE FROM: SUNRISE MEDICAL CANADA INC.**

#### PRICE

# POWERED WHEEL CHAIR, "QUICKIE S-525" MODEL

\$4 885.00

## **Basic Component(s)**

## **Body support system**

- · supple seat and back, nylon
- seat/back structure, back : angle-adjustable from 86° to 102°
- suspension built into seat
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat height: from 45.7 cm (18 in.) to 53.3 cm (21 in.)
- back height: from 38.1 cm (15 in.) to 50.8 cm (20 in.)
- · push handles
- · back spreader bar
- safety belt, auto-type, velcro-type

#### Armrests

- "T"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 30.5 cm (12 in.), short, long
- · straight armrest pads, short, long
- padded armrest pads, short, long

#### **Footrests**

- 70° footrests, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 54.6 cm (21<sup>1</sup>/<sub>2</sub> in.)
- 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- folding footplates, standard
- heel loops, length-adjustable
- · contoured calfrests

### **Drive system**

- · programmable joystick control
- battery charge display
- · battery charger
- battery box, group 22
- toggle switch
- programmable controller
- motor, 11 km/h (6.5 mph), for standard base
- side bracket for joystick control, swivel side bracket for joystick control
- anti-tip rollers

- · standard forks
- rear wheels, inner tube tires, 30.5 cm (12 in.) x 7.6 cm (3 in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- tie-down points for adapted transport
- reflector strips
- rear wheel rims, front wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
headrest, small	90.00	93.00
headrest, medium	96.00	103.00
headrest, large	102.00	107.00
articulated headrest mounting	154.00	168.00
transversal bar for headrest mounting	195.00	207.00
seat/back structure, back : angle-adjustable from 86° to 102°	N/C	477.00
folding back	117.00	N/A
suspension built into seat	N/C	N/A
padded back, contoured, fabric	305.00	374.00
padded back, contoured, fabric, with rigid base	393.00	462.00
padded back, contoured, leatherette	340.00	409.00
padded back, contoured, leatherette, with rigid base	420.00	489.00
supple back, tension-adjustable	74.00	143.00
rigid seat, flat	85.00	137.50
padded seat, contoured, leatherette	322.00	345.00
padded seat, contoured, fabric	247.00	299.00
modification of seat width to 48.3 cm (19 in.) or to 50.8 cm (20 in.)		N/A
modification of seat depth to 48.3 cm (19 in.) or to 50.8 cm (20 in.)		N/A
supple back, nylon	N/C	69.00
supple seat, nylon	N/C	52.50
push handles	N/C	N/A
push handles with 8° angle	22.00	N/A
back spreader bar	N/C	N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, auto-type	N/C	41.00
safety belt, velcro-type	N/C	28.00
Armrests:		
"T"-type armrests, detachable, height-adjustable		
from 25.4 cm (10 in.) to 30.5 cm (12 in.), short or long "U"-type armrests, detachable, flip-back, height-adjustable	N/C	132.00
from 24.1 cm (9 <sup>1</sup> / <sub>2</sub> in.) to 35.6 cm (14 in.), short or long		
pair	88.00	
each	00.00	176.00
	N/C	15.00
straight armrest pads, short straight armrest pads, long	N/C N/C	17.00
contoured armrest pads, short or long	N/C N/C	25.00
modification of "T"-type armrests from 15.2 cm (6 in.)	N/C	23.00
	80.00	N/A
to 24.8 cm (9 <sup>3</sup> / <sub>4</sub> in.)	80.00	1 <b>N</b> /A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests :		
70° footrests, detachable, swingaway, length-adjustable		
from 27.9 cm (11 in.) to 54.6 cm $(21^{1}/_{2} \text{ in.})$	N/C	136.00
90° footrests, detachable, swingaway, length-adjustable		
from 20.3 cm (8 in.) to 33.0 cm (13 in.)	N/C	136.00
70° footrests, parallel, detachable, swingaway, heavy-duty,	40.00	27/1
length-adjustable from 29.2 cm $(11\frac{1}{2} \text{ in.})$ to 54.6 cm $(21\frac{1}{2} \text{ in.})$	40.00	N/A
modification of length of 90° footrests by 5.1 cm (2 in.)		
or by 10.2 cm (4 in.)	30.00	
oair each	30.00	15.00
elevating legrests, detachable, swingaway		15.00
pair	172.00	
each	172.00	222.00
padded calfrests	N/C	18.00
contoured calfrests		
oair	70.00	
each		53.00
single calf strap	18.00	18.00
double calf strap	32.00	32.00
folding footplates, standard	N/C	48.00
folding footplates, oversized	71.00	
oair each	71.00	92.50
each folding footplates, angle-adjustable and depth-adjustable, standa	rd siza	83.50
olding rootpiates, angie-adjustable and depth-adjustable, standa Dair	51.00	
each	31.00	73.50
heel loops, length-adjustable	N/C	10.00
Wheels and frame		
The state of the s		
Types of drive systems:		
programmable joystick control	N/C	612.00
pattery charge display	N/C	N/A
pattery charger	N/C	373.00
pattery box, group 22 proportional chin control (requires interface)	N/C 540.00	117.00 540.00
oreath control (requires interface)	414.00	414.00
nead control (requires interface)	540.00	540.00
aptray touch switch control (requires interface)	305.00	305.00
control with 5 separate switches (requires interface)	583.00	583.00
dapted controls interface with integrated display module	1 403.00	1 403.00
nuxiliary switch	88.00	93.00
nodification of joystick control for auxiliary switch	117.00	729.00
oggle switch	N/C	N/A
bush-button switch	85.00	N/A
pall extension	50.00	50.00
'T"-type extension	50.00	50.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
stick extension	20.00	20.00
swivel side bracket for joystick control	N/C	183.00
swivel midline bracket for joystick control	158.00	341.00
side bracket for joystick control	N/C	72.00
preath control bracket	342.00	342.00
chin control bracket	342.00	342.00
nead control bracket	342.00	342.00
programmable controller	N/C	1 411.00
notors, 11 km/h (6.5 mph), for standard base	N/C	950.00
neavy-duty frame or robust base	124.00	N/A
neavy-duty motors for persons over 250 lb.		
pair	76.00	
each		915.00
anti-tip rollers	N/C	N/A
centre of gravity adjustment	65.00	N/A
Types of wheels:		
standard forks	N/C	60.00
reflector strips	N/C	N/A
tie-down points for adapted transport	N/C	69.00
Front impact guard with rollers		
pair	36.00	
each		18.00
front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
pair	22.00	
each		66.00
rear wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	55.00
rear wheels, inner tube tires, 30.5 cm (12 in.) x 7.6 cm (3 in.)	N/C	141.00
front wheel rims	N/C	39.00
rear wheel rims	N/C	127.00
airless inserts for rear wheels	132.00	N/A
nirless inserts for front wheels	111.00	N/A
auxiliary brakes, manual	<b>51.00</b>	
pair	51.00	40.00
each		42.00
wheel lock extensions	26.00	
pair	36.00	10.00
each		18.00
Component(s) under Special Consideration		
control system for several power accessories (number : 8)*	599.00	599.00
connecting cables for power accessories, four plugs*	47.00	47.00
connecting cables for power accessories, one plug*	47.00	47.00

### DEVICE FROM: SUNRISE MEDICAL CANADA INC.

#### PRICE

# POWERED WHEEL CHAIR, "QUICKIE S-646 SE" MODEL

\$5 365.00

## **Basic Component(s)**

## **Body support system**

- · supple back, nylon
- rigid seat, flat
- seat/back structure, back : angle-adjustable from 84° to 124°
- · centre of gravity adjustment from seat
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat height: from 45.7 cm (18 in.) to 59.7 cm (23<sup>1</sup>/<sub>2</sub> in.)
- back height: from 38.1 cm (15 in.) to 50.8 cm (20 in.)
- push handles
- back spreader bar
- safety belt, auto-type, velcro-type
- · parallel seat rails

#### Armrests

- "T"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 30.5 cm (12 in.), short, long
- straight armrest pads, short, long
- · contoured armrest pads, short, long

#### **Footrests**

- 70° footrests, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 54.6 cm (21<sup>1</sup>/<sub>2</sub> in.)
- 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- · padded calfrests
- folding footplates, standard
- heel loops, length-adjustable

## **Drive system**

- · programmable joystick control
- battery charge display
- battery charger
- battery box, group 22, group 24
- toggle switch
- programmable controller
- motors, 14.1 km/h (8.5 mph), for standard base
- side bracket for joystick control, swivel side bracket for joystick control

- · standard forks
- rear suspension
- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- tie-down points for adapted transport
- · reflector strips
- running lights
- rear wheel rims, front wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back :		
headrest, small	90.00	93.00
headrest, medium	96.00	103.00
headrest, large	102.00	107.00
articulated headrest mounting	154.00	168.00
seat/back structure, back : angle-adjustable from 84° to 124°	N/C	N/A
parallel seat rails	N/C	30.00
apered seat rails		
pair	70.00	
each		65.00
padded back, contoured, fabric	305.00	374.00
padded back, contoured, leatherette	340.00	400.00
badded back, contoured, leathered, with rigid base	420.00	489.00
badded back, contoured, fabric, with rigid base	393.00	462.00
padded back, contoured, fabric, height of 53.3 cm (21 in.)		
to 61.0 cm (24 in.)	349.00	418.00
padded back, contoured, fabric, with rigid base,		
height of 53.3 cm (21 in.) to 61.0 cm (24 in.)	452.00	521.00
padded back, contoured, leatherette, height of 53.3 cm (21 in.)	.02.00	521.00
to 61.0 cm (24 in.)	380.00	449.00
padded back, contoured, leatherette, with rigid base,	200.00	,
height of 53.3 cm (21 in.) to 61.0 cm (24 in.)	476.00	545.00
supple back, tension-adjustable	74.00	143.00
padded seat, contoured, fabric	247.00	299.00
padded seat, contoured, leatherette	322.00	345.00
modification of seat width to 48.3 cm (19 in.), 50.8 cm (20 in.),	322.00	313.00
55.9 cm (22 in.) or 61.0 cm (24 in.)	389.00	N/A
modification of seat depth to 48.3 cm (19 in.), 50.8 cm (20 in.),	307.00	1071
53.3 cm (21 in.) or 55.9 cm (22 in.)	257.00	N/A
modification of back height from 53.3 cm (21 in.) to 61.0 cm (24 in.)		N/A
modification of seat height to 43.8 cm (27 lm.) to 61.0 cm (24 lm.) modification of seat height to 43.8 cm (17 $^{1}$ / <sub>4</sub> in.)	284.00	N/A
supple back, nylon	N/C	69.00
rigid seat, flat	N/C	136.50
bush handles	N/C	N/A
pash handles back spreader bar	N/C N/C	N/A N/A
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, auto-type	36.00 N/C	41.00
	N/C N/C	28.00
safety belt, velcro-type		
centre of gravity adjustment from seat	N/C	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests :		
"T"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 30.5 cm (12 in.), short or long "U"-type armrests, detachable, flip-back, height-adjustable from 24.1 cm (01/ in.) to 35.6 cm (14 in.) short or long	N/C	132.00
from 24.1 cm (9 $\frac{1}{2}$ in.) to 35.6 cm (14 in.), short or long	88.00	
pair each	88.00	176.00
	N/C	
straight armrest pads, short	N/C	15.00
straight armrest pads, long	N/C	17.00
contoured armrest pads, short or long	N/C	25.00
modification of the height of "T"-type armrests from 15.2 cm (		
to $24.8 \text{ cm } (9^3/_4 \text{ in.})$	80.00	N/A
Footrests :		
70° footrests, detachable, swingaway, length-adjustable		
from 27.9 cm (11 in.) to 54.6 cm ( $21^{1}/_{2}$ in.)	N/C	136.00
90° footrests, detachable, swingaway, length-adjustable		
From 20.3 cm (8 in.) to 33.0 cm (13 in.)	N/C	136.00
70° footrests, heavy-duty, detachable, swingaway, length-adjus		150.00
From 29.2 cm ( $11^{1}/_{2}$ in.) to 54.6 cm ( $21^{1}/_{2}$ in.)	40.00	N/A
elevating legrests	40.00	IV/A
	172.00	
oair	172.00	222.00
each	NIG	222.00
padded calfrests	N/C	18.00
contoured calfrests		
pair	70.00	
each		53.00
single calf strap	18.00	18.00
double calf strap	32.00	32.00
folding footplates, standard	N/C	48.00
folding footplates, oversized		
pair	71.00	
each		83.50
olding footplates, angle-adjustable		03.50
vair	51.00	
each	31.00	73.50
neel loops, length-adjustable	N/C	10.00
	IN/C	10.00
ront impact guard with rollers	26.00	
pair	36.00	10.00
each		18.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems :		
programmable joystick control	N/C	612.00
pattery charge display	N/C	N/A
pattery charger	N/C	373.00
pattery box, group 22, group 24	N/C	N/A
proportional chin control (requires interface)	540.00	540.00
nead control (requires interface)	540.00	540.00
aptray touch switch control (requires interface)	305.00	305.00
control with 5 separate switches (requires interface)	583.00	583.00
reath control (requires interface)	414.00	414.00
dapted controls interface with integrated display module	1 403.00	1 403.00
uxiliary switch	88.00	93.00
nodification of joystick control for auxiliary switch	117.00	729.00
oggle switch	N/C	N/A
bush-button switch	85.00	N/A
all extension	50.00	50.00
T"-type extension	50.00	50.00
tick extension	20.00	20.00
wivel side bracket for joystick control	N/C	183.00
wivel midline bracket for joystick control	158.00	341.00
ide bracket for joystick control	N/C	72.00
oreath control bracket	342.00	342.00
hin control bracket	342.00	342.00
nead control bracket	342.00	342.00
programmable controller	N/C	1 540.00
notors, 14.1 km/h (8.5 mph), for standard base	N/C	1 090.00
igh-torque transmission (heavy-duty)	273.00	N/A
Types of wheels:		
tandard forks	N/C	84.00
eflector strips	N/C	N/A
unning lights	N/C	N/A
e-down points for adapted transport	N/C	66.00
ear suspension	N/C	N/A
uspension forks, up to 68 kg (150 lb.)	100.00	N/A
uspension forks, up to 114 kg (250 lb.)	116.00	N/A
uspension forks, up to 182 kg (400 lb.)	131.00	N/A
cont wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	66.00
cont wheels, solid tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) cont wheels, solid tires, 22.9 cm (9 in.) x 7.6 cm (3 in.)	N/C	61.00
air	67.00	
ach		94.50
ront wheels, inner tube tires, 22.9 cm (9 in.) x 7.6 cm (3 in.)	67.00	
air	67.00	04.50
ach		94.50

\$5 723.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)	N/C	209.00
front wheel rims	N/C	39.00
rear wheel rims	N/C	46.00
airless inserts for rear wheels manual auxiliary brakes	132.00	N/A
pair	51.00	
each		42.00
wheel lock extensions	36.00	18.00
Component(s) under Special Consideration		
control system for several power accessories (number : 8)*	599.00	599.00
connecting cables for power accessories, four plugs*	47.00	47.00
connecting cables for power accessories, one plug*	47.00	47.00
DEVICE FROM: PRIDE MOBILITY PRODUCTS CORP.		
		PRI

# Basic Component(s)

# **Body support system**

• seat/back structure with angle-adjustable back

POWERED WHEEL CHAIR, "BLAST" MODEL

- seat widths: from 25.4 cm (10 in.) to 55.9 cm (22 in.), 61.0 cm (24 in.)
- seat depths: from 25.4 cm (10 in.) to 50.8 cm (20 in.), 61.0 cm (24 in.)
- seat height: from 45.7 cm (18 in.) to 50.8 cm (20 in.)
- back height: from 35.6 cm (14 in.) to 61.0 cm (24 in.)
- · rigid seat, flat
- supple back, nylon
- · push handles
- push bar
- safety belt, auto-type, velcro-type
- angle-adjustable back
- · centre of gravity adjustment from seat

#### Armrests

- "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) to 38.1 cm (15 in.), short, long, with clothing guards
- "I"-type armrests, short, long
- straight armrest pads, short, long
- · contoured armrest pads, short, long
- rigid clothing guards for "T"-type armrests

- 60° or 70° footrests, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.)
- · padded calfrests
- folding footplates, standard size, angle-adjustable
- folding footplates, oversized, angle-adjustable
- heel loops, length-adjustable
- heel loops, fixed

## **Drive system**

- programmable joystick control with control system for 5 power accessories
- battery charge display
- stick extension
- · onboard battery charger
- battery box, group 24
- programmable controler
- Reliance 702 HS motors, 14.1 km/h (8.5 mph)
- heavy-duty motors, 11.6 km/h (7 mph)
- side bracket for joystick control, swivel side bracket for joystick control
- · anti-tip rollers

- · standard forks
- · rear suspension
- rear wheels, inner tube tires, 35.6 cm (14 in.)
- front wheels, inner tube tires, 22.9 cm (9 in.)
- tie-down points for adapted transport
- reflector strips
- rear wheel rims, front wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back: padded headrest, contoured, small padded headrest, contoured, large articulated headrest mounting, uniball seat/back structure with angle-adjustable back angle-adjustable back padded back, contoured, fabric or leatherette padded back, contoured, fabric, with rigid base padded back, contoured, fabric, with rigid base padded seat, contoured, fabric supple back, nylon rigid seat, flat push handles push bar safety belt, auto-type safety belt, velcro-type safety belt, airplane-type centre of gravity adjustment from seat	60.00 60.00 100.00 N/C N/C 280.00 280.00 390.00 200.00 N/C N/C N/C N/C N/C N/C N/C	170.00 170.00 290.00 550.00 160.00 340.00 340.00 470.00 200.00 80.00 40.00 40.00 85.00 26.00 26.00 50.00 N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
"I"-type armrests, short or long "T"-type armrests, detachable, height-adjustable from 22.9 cm (9 in	N/C	80.00
to 38.1 cm (15 in.), short or long, with clothing guards "U"-type armrests, detachable, flip-back, height-adjustable	N/C	190.00
from 22.9 cm (9 in.) to 38.1 cm (15 in.), short or long pair	200.00	
each	200.00	290.00
straight armrest pads, short or long	N/C	10.00
contoured armrest pads, short or long	N/C N/C	10.00
supple clothing guards for "U"-type armrests	TV/C	10.00
pair	60.00	
each	00.00	60.00
rigid clothing guards for "U"-type armrests		00.00
pair	15.00	
each	13.00	15.00
rigid clothing guards for "T"-type armrests	N/C	5.00
rigid trouming guards for 1 type armitons	1,,0	2.00
Footrests:		
60° or 70° footrests, detachable, swingaway, length-adjustable		
from 27.9 cm (11 in.) to 50.8 cm (20 in.)	N/C	70.00
70° footrests, heavy-duty, length-adjustable from 27.9 cm (11 in.)		
to 50.8 cm (20 in.)		
pair	200.00	
each		170.00
elevating legrests		
pair	200.00	
each		170.00
padded calfrests	N/C	12.00
single calf strap	45.00	45.00
double calf strap	45.00	45.00
folding footplates, oversized, angle-adjustable	N/C	70.00
folding footplates, standard size, angle-adjustable	N/C	70.00
heel loops, length-adjustable	N/C	10.00
heel loops, fixed	N/C	7.00
Wheels and frame		
TD 61.		
Types of drive systems:	NIC	705.00
programmable joystick with control system for 5 power accessories		725.00
battery charge display	N/C	N/A 185.00
onboard battery charger	N/C N/C	
battery box, group 24	735.00	66.00 735.00
proportional chin control (requires interface)		
non-proportional chin control (requires interface) laptray touch switch control (requires display)	805.00 420.00	805.00 420.00
control with separate switches (must use joystick control with inputs)		90.00
foot control (requires interface)	1 130.00	1 130.00
adapted controls interface or non-proportional controls interface	860.00	860.00
stick extension	N/C	10.00
ball extension	30.00	40.00
Uali Cachsiuli	30.00	40.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
"T"-type extension	60.00	70.00
mushroom-shaped extension	40.00	50.00
conical-spherical extension	40.00	50.00
swivel side bracket for joystick control	N/C	160.00
side bracket for joystick control	N/C	12.00
pracket for separate display module	90.00	90.00
chin bib control	375.00	375.00
external charger, 8A	135.00	320.00
programmable controller	N/C	850.00
Reliance 702 HS motors, 14.1 km/h (8.5 mph)	N/C	850.00
neavy-duty motors, 11.6 km/h (7 mph)	N/C	760.00
inti-tip rollers	N/C	12.00
neavy-duty base	470.00	N/A
Types of wheels:		
standard forks	N/C	65.00
reflector strips	N/C	N/A
ie-down points for adapted transport	N/C	25.00
ear suspension	N/C	N/A
front wheels, inner tube tires, 22.9 cm (9 in.)	N/C	30.00
ear wheels, inner tube tires, 35.6 cm (14 in.)	N/C	80.00
ront wheel rims	N/C	30.00
rear wheel rims	N/C	30.00
airless inserts for rear wheels	120.00	N/A
airless inserts for front wheels	120.00	N/A
Component(s) under Special Consideration		
seat/back structure, reclining back with cylinder*	400.00	950.00
DEVICE FROM . INVACARE CANADA INC		

#### **DEVICE FROM: INVACARE CANADA INC.**

**PRICE** 

# POWERED WHEEL CHAIR, "STORM PEDIATRIC" MODEL

\$4 706.00

# Basic Component(s)

# **Body support system**

- supple back, leatherette, nylon
- back height: from 30.5 cm (12 in.) to 48.3 cm (19 in.)
- rigid seat, flat
- seat width: from 30.5 cm (12 in.) to 40.6 cm (16 in.)
- seat depths: 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.)
- seat heights:  $44.5 \text{ cm} (17^{1}/_{2} \text{ in.}), 50.2 \text{ cm} (19^{3}/_{4} \text{ in.})$
- push handles
- push bar
- safety belt, auto-type
- · centre of gravity adjustment from seat

#### Armrests

- "U"-type armrests, detachable, flip-back, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short, long
- "U"-type armrests, fixed height, short, long
- straight armrest pads, short, long
- · contoured armrest pads, short, long
- rigid clothing guards built-into armrests

#### **Footrests**

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13<sup>1</sup>/<sub>2</sub> in.) to 44.5 cm (17<sup>1</sup>/<sub>2</sub> in.), or 70° footrests, parallel, detachable, swingaway, length-adjustable from 29.8 cm (11<sup>3</sup>/<sub>4</sub> in.) to 43.2 cm (17 in.)
- 90° footrests, parallel, detachable, swingaway, length-adjustable from 12.7 cm (5 in.) to 20.3 cm (8 in.)
- 60° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 24.1 cm (9½ in.) to 36.8 cm (14½ in.), or 70° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 11.4 cm (4½ in) to 25.4 cm (10 in.)
- 70° footrests, tapered, detachable, swingaway, length-adjustable from 33.7 cm (13¹/4 in.) to 43.8 cm (17¹/4 in.)
- · padded calfrests
- folding footplates, standard
- heel loops, non-adjustable
- · heel loops, length-adjustable

## **Drive system**

- · programmable joystick control
- battery charge display
- · battery charger
- battery boxes, group 22, group 24
- toggle switch
- direction joystick
- controller
- 4-brush motors with gears
- G/B motors with gears
- side bracket for joystick control, swivel side bracket for joystick control, midline bracket for joystick control
- anti-tip rollers

- reflector strips
- rear suspension
- standard forks
- · running lights
- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.), 20.3 cm (8 in.) x 4.4 cm (1<sup>3</sup>/<sub>4</sub> in.)
- tie-down points for adapted transport
- · front wheel rims
- · rear wheel rims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, flat	80.00	80.00
headrest, small	106.00	106.00
headrest, large	106.00	106.00
combined headrest/neckrest	106.00	106.00
fixed headrest mounting	53.00	53.00
articulated headrest mounting	122.00 566.00	122.00 566.00
seat/back structure with angle-adjustable back	299.00	299.00
padded back, contoured, fabric padded back, contoured, leatherette	399.00	399.00
padded seat, contoured, fabric	241.00	241.00
padded seat, contoured, leatherette	341.00	341.00
rigid seat, flat	N/C	75.00
centre of gravity adjustment from seat	N/C	N/A
supple back, leatherette or nylon	N/C	58.00
push handles	N/C	40.00
push bar	N/C	58.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
safety belt, auto-type	N/C	50.00
Armrests:		
"U"-type armrests, detachable, flip-back, height-adjustable	NIG	115.00
from 20.3 cm (8 in.) to 30.5 cm (12 in.), short or long	N/C	115.00
"U"-type armrests, fixed height, short or long	N/C	96.00
modification of armrest height by – 2.5 cm (1 in.)	179.00 N/C	N/A 26.00
straight armrest pads, short or long contoured armrest pads, short or long	N/C N/C	26.00
rigid clothing guards built into armrests	N/C N/C	20.00 N/A
	N/C	IV/A
<b>Footrests:</b> 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13 <sup>1</sup> / <sub>2</sub> in.) to 44.5 cm (17 <sup>1</sup> / <sub>2</sub> in.), or 70° footrests, parallel, detachable, swingaway, length-adjustable from 29.8 cm		
(11 <sup>3</sup> / <sub>4</sub> in.) to 43.2 cm (17 in.) 60° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 24.1 cm (9 <sup>1</sup> / <sub>2</sub> in.) to 36.8 cm (14 <sup>1</sup> / <sub>2</sub> in.) or 70° footrests, MFX, parallel, detachable, swingaway,	N/C	81.00
length-adjustable from 11.4 cm (4½ in.) to 25.4 cm (10 in.) 90° footrests, parallel, detachable, swingaway, length-adjustable	N/C	135.00
from 12.7 cm (5 in.) to 20.3 cm (8 in.) 70° footrests, tapered, detachable, swingaway, length-adjustable	N/C	135.00
from 33.7 cm $(13^1/_4 \text{ in.})$ to 43.8 cm $(17^1/_4 \text{ in.})$ elevating legrests, length-adjustable from 40.6 cm (16 in.)	N/C	135.00
to 50.8 cm (20 in.) pair each	230.00	196.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
elevating legrests, compensating mechanism, detachable,		
swingaway, length-adjustable from 43.8 cm (17 <sup>1</sup> / <sub>4</sub> in.)		
to 54.6 cm (21 <sup>1</sup> / <sub>2</sub> in.)	220.00	
pair	230.00	106.00
each		196.00
modification of length of elevating legrest by $-2.5$ cm (1 in.) or by $-5.1$ cm (2 in.)		
pair	190.00	
each	190.00	190.00
padded calfrests	N/C	20.00
single calf strap	22.00	34.00
double calf strap	35.00	52.00
folding footplates, standard	N/C	40.00
folding footplates, oversized	100	40.00
pair	39.00	
each	37.00	60.00
folding footplates, standard, angle-adjustable		00.00
pair	72.00	
each		76.00
folding footplates, oversized, angle-adjustable		,
pair	72.00	
each		76.00
heel loops, non-adjustable	N/C	5.00
heel loops, length-adjustable	N/C	12.00
Wheels and frame		
Types of drive systems:		
programmable joystick control	N/C	479.00
compact joystick control (requires display)	340.00	819.00
heavy-duty joystick control (requires display and interface)	96.00	575.00
modification of joystick control, each	60.00	60.00
battery charge display	N/C	N/A
battery charger	N/C	401.00
battery box, group 22	N/C	185.00
battery box, group 24	N/C 214.00	201.00
touch pad control	200.00	693.00
control with separate switches (requires display and interface)	354.00	679.00 833.00
proportional chin control (requires display) non-proportional chin control (requires display and interface)	368.00	
breath control		847.00 1 740.00
head control	1 740.00 1 426.00	1 905.00
laptray touch switch control (requires display)	1 159.00	1 636.00
foot control (requires display)	1 159.00	1 636.00
toggle switch	N/C	21.00
extension for toggle switches	96.00	96.00
	25.00	25.00
emergency stop ribbon switch	7.3.00	/c).(N)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
non-proportional controls interface	692.00	692.00
separate display module	1 099.00	1 099.00
lirection joystick	N/C	126.00
etick extension	19.00	19.00
pall extension	5.00	5.00
T"-type extension	19.00	19.00
wivel side bracket for joystick control	N/C	250.00
ide bracket for joystick control	N/C	12.00
nidline bracket for joystick control	N/C	190.00
oreath control bracket	357.00	357.00
chin control bracket	357.00	357.00
nead control bracket	150.00	150.00
	115.00	115.00
oracket for separate display module	220.00	220.00
controller	220.00 N/C	1 358.00
G/B motors with gears	N/C	1 139.00
l-brush motors with gears	N/C	1 139.00
anti-tip rollers	N/C	60.00
Types of wheels:	N/C	54.00
standard forks	N/C	54.00
ear suspension	N/C	119.00
eflector strips	N/C	N/A
ie-down points for adapted transport	N/C	75.00
running lights	N/C	N/A
uxiliary manual brakes	72.00	
pair	72.00	47.00
each		45.00
suspension forks	120.00	
pair	130.00	440.00
each		119.00
Front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 i		40.00
or 20.3 cm (8 in.) x 4.4 cm ( $1^{3}/_{4}$ in.)	N/C	40.00
Front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	55.00
ear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) ear wheels, inner tube tires, 35.6 cm (14 in.) x 10.2 cm (4 in.)	N/C	75.00
pair	118.00	
each		134.00
Front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm (2 <sup>3</sup> / <sub>4</sub> in.)		
pair	90.00	
each		85.00
Front wheel rims	N/C	43.00
ear wheel rims	N/C	50.00
airless inserts for rear wheels	100	20.00
pair	95.00	
each	75.00	N/A
uirless inserts for front wheels		IVA
pair	109.00	

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
control system for one power accessory only* control system for two power accessories* module for two additional power accessories* connecting cable for power reclining devices*	461.00 327.00 327.00 161.00	695.00 798.00 798.00 161.00

# **DEVICE FROM: ORTHOFAB INC.**

**PRICE** 

# POWERED WHEEL CHAIR, "OASIS JR" MODEL

\$4 749.00

# Basic Component(s)

# **Body support system**

- · rigid back, flat
- back height: from 27.9 cm (11 in.) to 45.7 cm (18 in.)
- · rigid seat, flat
- seat widths: 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.)
- seat depths: 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.)
- push handles
- safety belt, auto-type
- seat height: from 41.9 cm  $(16^{1}/_{2} \text{ in.})$  to 50.8 cm (20 in.)
- · centre of gravity adjustment from seat

# **Armrests**

- "T"-type armrests, detachable, height-adjustable from 15.2 cm (6 in.) to 25.4 cm (10 in.), short
- straight armrest pads, short
- · rigid clothing guards

- 70° footrests, detachable, swingaway, length-adjustable from 17.8 cm (7 in.) to 33.0 cm (13 in.)
- · padded calfrests, straight
- folding footplates, standard
- angle-adjustable footplates, included with 90° footrests
- heel loops, length-adjustable

# **Drive system**

- programmable joystick control
- · conical-spherical extension
- battery charge display
- battery charger
- battery box, group 22, group 24
- · direction joystick
- push-button switch
- PILOT + controller
- motors, 9.5 km/h (6 mph)
- side bracket for joystick control, swivel side bracket for joystick control
- breath control (requires interface)
- anti-tip rollers

- · standard forks
- tie-down points for adapted transport
- · reflector strips
- · running lights
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- · modification of frame length, short or long version
- rear wheel rims, front wheel rims
- · rear suspension

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
padded headrest, contoured	100.00	100.00
articulated headrest mounting, uniball	115.00	115.00
articulated headrest mounting	102.00	102.00
adjustable seat bracket	N/C	127.00
seat/back structure with angle-adjustable back	714.00	714.00
reinforced seat/back structure with angle-adjustable back	1 136.00	1 136.00
rigid back, flat	N/C	55.00
padded back, contoured, fabric	285.00	340.00
padded back, contoured, leatherette	285.00	340.00
thoracic support adapters	60.00	
pair	60.00	60.00
each	NIG	60.00
rigid seat, flat	N/C	55.00
padded seat, contoured, fabric	230.00	282.00
padded seat, contoured, leatherette	230.00	282.00
centre of gravity adjustment from seat	N/C	N/A
modification of back height to over 45.7 cm (18 in.)	96.00	N/A
modification of seat depth to 25.4 cm (10 in.), 27.9 cm (11 in.)	264.00	N/A
or 40.6 cm (16 in.)	204.00	IN/A
modification of seat width to 20.3 cm (8 in.), 22.9 cm (9 in.), 25.4 cm (10 in.) or 27.9 cm (11 in.)	290.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
modification of seat height by + 2.5 cm (1 in.), + 5.1 cm (2 in.)		
or + 7.6 cm (3 in.)	285.00	N/A
safety belt, velcro-type	27.00	63.00
safety belt, auto-type	N/C	36.00
safety belt, airplane-type	38.00	74.00
push handles	N/C	102.00
Armrests :		
"T"-type armrests, detachable, height-adjustable from 15.2 cm	(6 in.)	
to 25.4 cm (10 in.), short	N/C	148.00
straight armrest pads, short	N/C	12.00
rigid clothing guards	N/C	44.00
modification of armrest height to over 25.4 cm (10 in.)	79.00	N/A
Footrests:		
70° footrests, detachable, swingaway, length-adjustable		
from 17.8 cm (7 in.) to 33.0 cm (13 in.)	N/C	78.00
modification of footrest length from 35.6 cm (14 in.) to 48.3 cm (19 in.) for 70° or 90° footrests	79.00	N/A
90° footrests, detachable, swingaway, length-adjustable	77.00	IV/A
from 17.8 cm (7 in.) to 33.0 cm (13 in.)		
oair	140.00	
each		148.00
elevating footrests, compensating mechanism, detachable,		
ength-adjustable from 30.5 cm (12 in.) to 48.3 cm (19 in.)		
pair	240.00	
each		198.00
padded calfrests, straight	N/C	20.00
double calf strap	55.00	55.00
folding footplates, standard	N/C	36.00
folding footplates, angle-adjustable, standard size		
pair	32.00	
each		52.00
folding footplates, oversized		
oair	32.00	
each		52.00
angle-adjustable footplates, included with 90° footrests	N/C	N/A
oversized footplates, angle-adjustable and depth-adjustable		
pair	38.00	
each		55.00
full-width footplate	171.00	243.00
neel loops, length-adjustable	N/C	11.00
oe loops		
pair	30.00	
each		15.00
ront impact guard with rollers		
pair	36.00	
each		18.00

Types of drive systems :   programmable joystick control   School   Schoo		Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
programmable joystick control 56.00 548.00 battery charge display N/C N/A battery charger N/C 359.00 battery charger N/C 359.00 battery bearger N/C 359.00 cadapted controls interface 1 608.00 2 100.00 dattery bearger 1 608.00 2 100.00 dattery box, group 22 or group 24 N/C 208.00 adapted controls interface 1 608.00 2 100.00 non-proportional chin control (requires interface) 421.00 421.00 head control breath control (requires interface) N/C N/A laptray touch switch control (requires interface) 301.00 301.00 control with separate switches (requires interface) 301.00 301.00 control with separate switches (requires interface) 300.00 301.00 control with separate switches (requires interface) 385.00 530.00 control with separate switches (requires interface) 385.00 385.00 swivel mounting hardware for breath control 385.00 385.00 swivel mounting hardware for chin control 385.00 385.00 385.00 swivel mounting hardware for chin control 385.00 385.00 385.00 skeed control bracket 385.00 385.00 385.00 385.00 flexed bracket for separate display module 37.00 37.00 120.00 push-button switch N/C N/A direction joystick N/C N/A direction joystick N/C N/A stick extension 19.00 27.00 120.00 push-button switch 19.00 27.00 35.00 27.00 modification of the joystick control : switches and potentiometer side bracket for joystick control : switches and potentiometer side bracket for joystick control : switches and potentiometer side bracket for joystick control : switches and potentiometer side bracket for joystick control : switches and potentiometer side bracket for joystick control : switches and potentiometer side bracket for joystick control : switches and potentiometer side bracket for joystick control : switches and potentiometer side bracket for joystick control : switches and potentiometer side bracket for joystick control : switches and potentiometer side bracket for joystick control : switches and potentiometer side bracket for joystick control : switches and potentiometer side bracket for joystick control : switches and potentio	Wheels and frames		
programmable joystick control 56.00 548.00 battery charge display N/C N/A battery charge of splay N/C	Types of drive systems :		
compact joystick control         56.00         548.00           battery charger display         N/C         359.00           battery box, group 22 or group 24         N/C         208.00           adapted controls interface         1608.00         2100.00           proportional chin control         631.00         631.00           non-proportional chin control (requires interface)         421.00         421.00           head control         1059.00         1059.00           breath control (requires interface)         N/C         N/A           laptray touch switch control (requires interface)         301.00         301.00           control with separate switches (requires interface)         530.00         530.00           control with separate switches (requires interface)         530.00         530.00           swivel mounting hardware for breath control         385.00         385.00           swivel mounting hardware for chin control         385.00         385.00           swivel mounting hardware for chin control         385.00         385.00           flexible bracket for separate display module         37.00         37.00           flexible bracket for separate display module         37.00         120.00           flexible bracket for separate display module         19.00 <t< td=""><td></td><td>N/C</td><td>492.00</td></t<>		N/C	492.00
battery charge display         N/C         359.00           battery box, group 22 or group 24         N/C         208.00           adapted controls interface         1 608.00         2 100.00           proportional chin control         631.00         631.00           non-proportional chin control (requires interface)         421.00         421.00           head control         1 059.00         1 059.00         1 059.00           breath control (requires interface)         N/C         N/A           laptray touch switch control (requires interface)         301.00         301.00           control with separate switches (requires interface)         530.00         530.00           control with separate switches (requires interface)         301.00         301.00           control with separate switches (requires interface)         330.00         530.00           control with separate switches (requires interface)         350.00         300.00           swivel mounting hardware for chin control         385.00         385.00           swivel mounting hardware for chin control         385.00         385.00           fixed bracket for separate display module         37.00         37.00           fixed bracket for separate display module         120.00         120.00           fixed bracket for separ	compact joystick control	56.00	548.00
battery charger		N/C	N/A
battery box, group 22 or group 24         N/C         208.00           adapted controls interface         1 608.00         2 100.00           proportional chin control         631.00         631.00           non-proportional chin control (requires interface)         1 059.00         1 059.00           head control         1 059.00         1 059.00           breath control (requires interface)         N/C         N/A           laptray touch switch control (requires interface)         301.00         301.00           control with separate switches (requires interface)         530.00         530.00           control obid         290.00         290.00           swivel mounting hardware for breath control         385.00         385.00           swivel mounting hardware for chin control         385.00         385.00           fixed bracket for separate display module         120.00         37.00           fixed bracket for separate display module         120.00         120.00           fixed bracket for separate display module         120.00         120.00           guishbutton switch         N/C         N/A           direction joystick         N/C         N/A           stile bracket for separate display module         120.00         27.00           ball extensi		N/C	
adapted controls interface         1 608.00         2 100.00           proportional chin control         631.00         631.00           non-proportional chin control (requires interface)         421.00         421.00           head control         1 059.00         1059.00           breath control (requires interface)         301.00         301.00           chaptray touch switch control (requires interface)         530.00         530.00           chin control bib         290.00         290.00           swivel mounting hardware for breath control         385.00         385.00           swivel mounting hardware for chin control         385.00         385.00           swivel mounting hardware for breath control         385.00         385.00           skivel mounting hardware for breath control         385.00         385.00           skivel mounting hardware for breath control         37.00<			
proportional chin control         631.00         631.00           non-proportional chin control (requires interface)         421.00         421.00           head control         1 059.00         1 059.00           breath control (requires interface)         N/C         N/A           aptray touch switch control (requires interface)         530.00         301.00           control with separate switches (requires interface)         530.00         530.00           chin control bib         290.00         290.00           swivel mounting hardware for breath control         385.00         385.00           swivel mounting hardware for chin control         385.00         385.00           head control bracket         385.00         385.00           fixed bracket for separate display module         120.00         120.00           push-button switch         N/C         N/A           direction joystick         N/C         N/A           stick extension         19.00         27.00           ball extension         19.00         27.00           "T"-type extension         27.00         35.00           mushroom-shaped extension         19.00         27.00           conical-spherical extension         N/C         8.00           sid			
Non-proportional chin control (requires interface)   1059.00   1			
head control         1 059,00         1 059,00           breath control (requires interface)         N/C         N/A           laptray touch switch control (requires interface)         301,00         301,00           control with separate switches (requires interface)         530,00         530,00           chin control bib         290,00         290,00           swivel mounting hardware for breath control         385,00         385,00           swivel mounting hardware for chin control         385,00         385,00           head control bracket         385,00         385,00           fixed bracket for separate display module         37,00         37,00           fixed bracket for separate display module         120,00         120,00           push-button switch         N/C         N/C           direction joystick         N/C         N/A           stick extension suitch         N/C         N/A           stick extension         19,00         27,00           ball extension         19,00         27,00           store extension         19,00         27,00           conical-spherical extension         N/C         8.00           conical-spherical extension         N/C         8.00           owide bracket for joystick			
breath control (requires interface)         N/C         N/A           laptray touch switch control (requires interface)         301.00         301.00           control with separate switches (requires interface)         530.00         530.00           chin control bib         290.00         290.00           swivel mounting hardware for breath control         385.00         385.00           swivel mounting hardware for chin control         385.00         385.00           fixed bracket for separate display module         37.00         37.00           fixed bracket for separate display module         120.00         120.00           mushroomshigh         N/C         8.00           mushroomshigh         N/C         8.00 <td></td> <td></td> <td></td>			
Laptray touch switch control (requires interface)   301.00   301.00   control with separate switches (requires interface)   530.00   530.00   530.00   290.00   290.00   290.00   swivel mounting hardware for breath control   385.00   38			
control with separate switches (requires interface)         530.00         530.00           chin control bib         290.00         290.00           swivel mounting hardware for breath control         385.00         385.00           swivel mounting hardware for chin control         385.00         385.00           fixed bracket         385.00         385.00           fixed bracket for separate display module         37.00         37.00           fixed bracket for separate display module         120.00         120.00           push-button switch         N/C         N/A           direction joystick         N/C         N/A           stick extension         19.00         27.00           ball extension         19.00         27.00           "T"-type extension         19.00         27.00           mushroom-shaped extension         19.00         27.00           onical-spherical extension         N/C         8.00           modification of the joystick control : switches and potentiometer         75.00         567.00           side bracket for joystick control         N/C         8.00           swivel side bracket for joystick control         85.00         287.00           swivel midline bracket for joystick control         85.00         287.00 <td>lantray touch switch control (requires interface)</td> <td></td> <td></td>	lantray touch switch control (requires interface)		
chin control bib         290.00         290.00           swivel mounting hardware for breath control         385.00         385.00           swivel mounting hardware for chin control         385.00         385.00           head control bracket         385.00         37.00           fixed bracket for separate display module         120.00         120.00           flexible bracket for separate display module         120.00         120.00           push-button switch         N/C         N/A           direction joystick         N/C         N/A           stick extension         19.00         27.00           ball extension         19.00         27.00           "T"-type extension         27.00         35.00           mushroom-shaped extension         19.00         27.00           conical-spherical extension         N/C         8.00           modification of the joystick control : switches and potentiometer         75.00         567.00           side bracket for joystick control         N/C         39.00           swivel midline bracket for joystick control         85.00         287.00           swivel midline bracket for joystick control         85.00         287.00           swivel midline bracket for joystick control         N/C         1382.	control with senarate switches (requires interface)		
swivel mounting hardware for breath control         385.00         385.00           swivel mounting hardware for chin control         385.00         385.00           head control bracket         385.00         385.00           fixed bracket for separate display module         37.00         120.00           push-button switch         N/C         N/A           direction joystick         N/C         N/A           stick extension         19.00         27.00           ball extension         19.00         27.00           ball extension         19.00         27.00           mushroom-shaped extension         19.00         27.00           conical-spherical extension         19.00         27.00           modification of the joystick control: switches and potentiometer         75.00         567.00           side bracket for joystick control         N/C         39.00           swivel side bracket for joystick control         N/C         39.00           swivel midline bracket for joystick control         85.00         287.00           swivel midline bracket for joystick control         N/C         39.00           swivel midline bracket for joystick control         85.00         287.00           motors, 9.5 km/h (6 mph)         N/C         N/C			
swivel mounting hardware for chin control         385.00         385.00           head control bracket         385.00         385.00           fixed bracket for separate display module         37.00         120.00           flexible bracket for separate display module         120.00         120.00           push-button switch         N/C         N/A           direction joystick         N/C         N/A           stick extension         19.00         27.00           ball extension         19.00         27.00           "T"-type extension         27.00         35.00           mushroom-shaped extension         19.00         27.00           mushroom-shaped extension         N/C         8.00           modification of the joystick control : switches and potentiometer         75.00         567.00           side bracket for joystick control         N/C         39.00           swivel side bracket for joystick control         N/C         202.00           swivel side bracket for joystick control         N/C         202.00           swivel side bracket for joystick control         N/C         202.00           swivel side bracket for joystick control         N/C         N/C           notors, 9.5 km/h (6 mph)         N/C         N/C         N/C			
head control bracket         385.00         385.00           fixed bracket for separate display module         37.00         37.00           flexible bracket for separate display module         120.00         120.00           push-button switch         N/C         N/A           direction joystick         N/C         N/A           stick extension         19.00         27.00           ball extension         19.00         27.00           "T"-type extension         19.00         27.00           mushroom-shaped extension         19.00         27.00           mushroom-shaped extension         19.00         27.00           modification of the joystick control : switches and potentiometer         75.00         567.00           side bracket for joystick control : switches and potentiometer         75.00         567.00           swivel side bracket for joystick control         N/C         39.00           swivel side bracket for joystick control         N/C         202.00           swivel midline bracket for joystick control         N/C         202.00           swivel midline bracket for joystick control         N/C         1382.00           PILOT + controller         N/C         N/C         N/A           notors, 9.5 km/h (6 mph)         N/C			
fixed bracket for separate display module         37.00         37.00           flexible bracket for separate display module         120.00         120.00           push-button switch         N/C         N/A           direction joystick         N/C         N/A           stick extension         19.00         27.00           ball extension         19.00         27.00           "T"-type extension         27.00         35.00           mushroom-shaped extension         19.00         27.00           modification of the joystick control: switches and potentiometer         75.00         567.00           side bracket for joystick control         N/C         39.00           swivel side bracket for joystick control         N/C         39.00           swivel midline bracket for joystick control         N/C         202.00           swivel midline bracket for joystick control         N/C         382.00           PILOT + controller         N/C         1382.00           motors, 9.5 km/h (6 mph)         N/C         N/C           motors, 9.5 km/h (6 mph)         N/C         N/C           motification of frame length, short or long version         N/C         N/A           Types of wheels:         Standard forks         N/C         N/C </td <td></td> <td></td> <td></td>			
flexible bracket for separate display module         120.00         120.00           push-button switch         N/C         N/A           direction joystick         N/C         N/A           stick extension         19.00         27.00           ball extension         19.00         27.00           "T"-type extension         27.00         35.00           mushroom-shaped extension         N/C         8.00           modification of the joystick control : switches and potentiometer         75.00         567.00           side bracket for joystick control         N/C         39.00           swivel midline bracket for joystick control         N/C         202.00           swivel midline bracket for joystick control         85.00         287.00           PILOT + controller         N/C         1382.00           motors, 9.5 km/h (6 mph)         N/C         N/C           motors, 9.5 km/h (6 mph)         N/C         N/C           motification of frame length, short or long version         N/C         N/A           Types of wheels :           standard forks         N/C         N/C         N/A           reflector strips         N/C         N/C         N/A           running lights         N/C <t< td=""><td></td><td></td><td></td></t<>			
push-button switch direction joystick $N/C$ $N/$			
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$			
stick extension         19.00         27.00           ball extension         19.00         27.00           "T"-type extension         27.00         35.00           mushroom-shaped extension         N/C         8.00           conical-spherical extension         N/C         8.00           modification of the joystick control : switches and potentiometer         75.00         567.00           side bracket for joystick control         N/C         39.00           swivel side bracket for joystick control         N/C         202.00           swivel midline bracket for joystick control         85.00         287.00           PILOT + controller         N/C         1382.00           motors, 9.5 km/h (6 mph)         N/C         N/C           anti-tip rollers         N/C         N/C           modification of frame length, short or long version         N/C         N/A           Types of wheels :           standard forks         N/C         87.00           reflector strips         N/C         20.00           running lights         N/C         N/A           tie-down points for adapted transport         N/C         N/A           rear wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)         N/C         N/C </td <td></td> <td></td> <td></td>			
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$			
"T"-type extension       27.00       35.00         mushroom-shaped extension       19.00       27.00         conical-spherical extension       N/C       8.00         modification of the joystick control : switches and potentiometer       75.00       567.00         side bracket for joystick control       N/C       39.00         swivel side bracket for joystick control       N/C       202.00         swivel midline bracket for joystick control       85.00       287.00         PILOT + controller       N/C       1382.00         motors, 9.5 km/h (6 mph)       N/C       N/C         anti-tip rollers       N/C       60.00         modification of frame length, short or long version       N/C       N/A         Types of wheels:         standard forks       N/C       87.00         reflector strips       N/C       20.00         running lights       N/C       N/A         tie-down points for adapted transport       N/C       N/A         rear suspension       N/C       N/A         front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)       N/C       N/C         north wheels, inner tube tires, 25.6 cm (14 in.) x 7.6 cm (3 in.)       N/C       102.00         front wheels, in			
mushroom-shaped extension19.0027.00conical-spherical extensionN/C8.00modification of the joystick control : switches and potentiometer75.00567.00side bracket for joystick controlN/C39.00swivel side bracket for joystick controlN/C202.00swivel midline bracket for joystick control85.00287.00PILOT + controllerN/C1382.00motors, $9.5 \text{ km/h}$ (6 mph)N/CN/Aanti-tip rollersN/C60.00modification of frame length, short or long versionN/CN/ATypes of wheels :standard forksN/C87.00reflector stripsN/C20.00running lightsN/CN/Atie-down points for adapted transportN/CN/Arear suspensionN/CN/Afront wheels, inner tube tires, $20.3 \text{ cm} (8 \text{ in.}) \times 5.1 \text{ cm} (2 \text{ in.})$ N/C85.00rear wheels, inner tube tires, $22.9 \text{ cm} (9 \text{ in.}) \times 7.6 \text{ cm} (3 \text{ in.})$ N/C102.00front wheels, inner tube tires, $22.9 \text{ cm} (9 \text{ in.}) \times 7.6 \text{ cm} (3^2/4 \text{ in.})$ 89.00			
conical-spherical extension N/C 8.00 modification of the joystick control : switches and potentiometer 75.00 567.00 side bracket for joystick control N/C 39.00 swivel side bracket for joystick control N/C 202.00 swivel midline bracket for joystick control 85.00 287.00 PILOT + controller N/C 1382.00 PILOT + controller N/C 1382.00 N/C			
modification of the joystick controlswitches and potentiometer75.00567.00side bracket for joystick controlN/C39.00swivel side bracket for joystick controlN/C202.00swivel midline bracket for joystick control85.00287.00PILOT + controllerN/C1382.00motors, 9.5 km/h (6 mph)N/CN/Aanti-tip rollersN/C60.00modification of frame length, short or long versionN/CN/ATypes of wheels:standard forksN/C87.00reflector stripsN/C20.00running lightsN/CN/Atie-down points for adapted transportN/CN/Arear suspensionN/CN/Afront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)N/C85.00rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)N/C102.00front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm $(2^{3}/_{4}$ in.)89.00			
side bracket for joystick control $N/C$ 39.00 swivel side bracket for joystick control $N/C$ 202.00 swivel midline bracket for joystick control $N/C$ 202.00 price of motors, 9.5 km/h (6 mph) $N/C$ 1382.00 motors, 9.5 km/h (6 mph) $N/C$ $N/C$ 39.00 modification of frame length, short or long version $N/C$ 60.00 modification of frame length, short or long version $N/C$			
swivel side bracket for joystick control 85.00 287.00 PILOT + controller N/C 1382.00 motors, 9.5 km/h (6 mph) N/C N/A anti-tip rollers N/C 60.00 modification of frame length, short or long version N/C N/A N/A N/C N/C N/A N/C N/C N/A N/C N/C N/A N/C			
swivel midline bracket for joystick control 85.00 287.00 PILOT + controller N/C 1382.00 motors, 9.5 km/h (6 mph) N/C N/A anti-tip rollers N/C 60.00 modification of frame length, short or long version N/C N/A N/A N/C N/A N/C N/A M/A N/C N/C N/A N/C N/A N/C N/C N/A N/C			
PILOT + controller motors, 9.5 km/h (6 mph) $N/C$ $N/C$ $N/A$ anti-tip rollers $N/C$			
motors, 9.5 km/h (6 mph) anti-tip rollers N/C nodification of frame length, short or long version  Types of wheels:  standard forks reflector strips N/C running lights N/C tie-down points for adapted transport rear suspension front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) pair  N/C N/A N/C			
anti-tip rollers $N/C$ $60.00$ modification of frame length, short or long version $N/C$ $N/C$ $N/A$ Types of wheels:  standard forks $N/C$ $87.00$ reflector strips $N/C$ $20.00$ running lights $N/C$ $N/A$ tie-down points for adapted transport $N/C$ $N/A$ rear suspension $N/C$ $N/A$ front wheels, inner tube tires, $20.3$ cm $(8 \text{ in.})$ x $5.1$ cm $(2 \text{ in.})$ $N/C$ $85.00$ rear wheels, inner tube tires, $20.3$ cm $(9 \text{ in.})$ x $7.6$ cm $(3 \text{ in.})$ $N/C$ $102.00$ front wheels, inner tube tires, $22.9$ cm $(9 \text{ in.})$ x $7$ cm $(2^{3}/_{4} \text{ in.})$ $89.00$			
modification of frame length, short or long version N/C N/A Types of wheels: standard forks N/C 87.00 reflector strips N/C 20.00 running lights N/C N/A tie-down points for adapted transport N/C N/A rear suspension N/C N/A front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) N/C 85.00 rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) N/C 102.00 front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm $(2^{3}/_{4}$ in.) pair 89.00			
Types of wheels:  standard forks  reflector strips  running lights  tie-down points for adapted transport  rear suspension  front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)  rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)  front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm $(2^{3}/_{4}$ in.)  pair  89.00			
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	modification of frame length, short or long version	N/C	N/A
reflector strips $N/C$ 20.00 running lights $N/C$ $N/C$ $N/C$ tie-down points for adapted transport $N/C$ $N/C$ $N/C$ rear suspension $N/C$ $N/C$ $N/C$ $N/C$ front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) $N/C$ 85.00 rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) $N/C$ 102.00 front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm $(2^{3}/_{4}$ in.) pair			a= aa
running lights N/C N/A tie-down points for adapted transport N/C N/A rear suspension N/C N/A N/C N/A front wheels, inner tube tires, $20.3 \text{ cm } (8 \text{ in.}) \text{ x } 5.1 \text{ cm } (2 \text{ in.})$ N/C 85.00 rear wheels, inner tube tires, $20.3 \text{ cm } (8 \text{ in.}) \text{ x } 7.6 \text{ cm } (3 \text{ in.})$ N/C 102.00 front wheels, inner tube tires, $22.9 \text{ cm } (9 \text{ in.}) \text{ x } 7 \text{ cm } (2^{3}/_{4} \text{ in.})$ pair 89.00			
tie-down points for adapted transport N/C N/A rear suspension N/C N/A N/C N/A front wheels, inner tube tires, $20.3 \text{ cm} (8 \text{ in.}) \times 5.1 \text{ cm} (2 \text{ in.})$ N/C 85.00 rear wheels, inner tube tires, $35.6 \text{ cm} (14 \text{ in.}) \times 7.6 \text{ cm} (3 \text{ in.})$ N/C 102.00 front wheels, inner tube tires, $22.9 \text{ cm} (9 \text{ in.}) \times 7 \text{ cm} (2^{3}/_{4} \text{ in.})$ pair 89.00			
rear suspension N/C N/A front wheels, inner tube tires, $20.3 \text{ cm} (8 \text{ in.}) \times 5.1 \text{ cm} (2 \text{ in.})$ N/C 85.00 rear wheels, inner tube tires, $35.6 \text{ cm} (14 \text{ in.}) \times 7.6 \text{ cm} (3 \text{ in.})$ N/C 102.00 front wheels, inner tube tires, $22.9 \text{ cm} (9 \text{ in.}) \times 7 \text{ cm} (2^{3}/_{4} \text{ in.})$ pair 89.00			
front wheels, inner tube tires, $20.3 \text{ cm } (8 \text{ in.}) \text{ x } 5.1 \text{ cm } (2 \text{ in.})$ rear wheels, inner tube tires, $35.6 \text{ cm } (14 \text{ in.}) \text{ x } 7.6 \text{ cm } (3 \text{ in.})$ front wheels, inner tube tires, $22.9 \text{ cm } (9 \text{ in.}) \text{ x } 7 \text{ cm } (2^3/_4 \text{ in.})$ pair $89.00$			
rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) N/C 102.00 front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm $(2^{3}/_{4}$ in.) pair 89.00	rear suspension		
front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm $(2^{3}/_{4}$ in.) pair 89.00			
pair 89.00		N/C	102.00
1		89.00	
each 129.00	each		129.00
airless inserts for 20.3 cm (8 in) x 5.1 cm (2 in.) wheels 133.00 N/A		133.00	
front wheels, puncture-resistant tires, 22.9 cm (9 in.) x 7 cm ( $2^{3}/_{4}$ in.) 224.00 N/A			
airless inserts for rear wheels  151.00  N/A			
rear wheel rims N/C N/A			
front wheel rims  N/C  N/A			

# Component(s) under Special Consideration

power rocker device, 45°, factory installed, including shroud*	N/C	2 375.00
power elevating legrests, individual controls*		
pair	1 259.00	
each		706.00
power elevating legrests, dual control*		
pair	1 259.00	
each		706.00
control system for one power accessory only*	250.00	250.00
control system for four power accessories*	740.00	740.00
control system for one power accessory only* control system for four power accessories*		

# §4. Supplements for wheel chairs

# **CUSHIONS FOR WHEEL CHAIRS**

contoured seat cushion, waterproof, with stretch fabric cover	205.00
contoured seat cushion with gel, waterproof, with stretch fabric cover	270.00
"COMBI"-type cushion or equivalent*	S.C.
"JAY"-type cushion or equivalent*	S.C.
gel cushion or equivalent*	S.C.
"ROHO" cushion or equivalent*	S.C.
special cushion*	S.C.

# §5. Components for wheel chairs

# TIRES AND INSERTS

# FOR MANUAL WHEEL CHAIRS

# SUPPLIER: ORTHOFAB INC.

tire, inner tube, standard pressure, 31.8 cm $(12^{1}/_{2} \text{ in.})$ x 5.7 cm $(2^{1}/_{4} \text{ in.})$	9.45
tire, inner tube, standard pressure, 50.8 cm (20 in.) x 3.5 cm ( $1^{3}$ / <sub>8</sub> in.)	8.50
tire, inner tube, standard pressure, 55.9 cm (22 in.) x 3.5 cm ( $1^{3}$ / <sub>8</sub> in.)	7.95
tire, inner tube, standard pressure, $61.0 \text{ cm} (24 \text{ in.}) \times 3.2 \text{ cm} (1\frac{1}{4} \text{ in.})$	7.25
tire, inner tube, standard pressure, $61.0 \text{ cm} (24 \text{ in.}) \text{ x } 3.5 \text{ cm} (1^{3}/_{8} \text{ in.})$	7.95
tire, inner tube, standard pressure, $61.0 \text{ cm} (24 \text{ in.}) \text{ x } 4.4 \text{ cm} (1^{3}/_{4} \text{ in.})$	9.95
tire, inner tube, standard pressure, $40.6 \text{ cm} (16 \text{ in.}) \times 4.4 \text{ cm} (1^3/_4 \text{ in.})$	9.95
tire, inner tube, standard pressure, 66.0 cm (26 in.) x 3.5 cm ( $1^{3}$ / <sub>8</sub> in.)	8.95
tire, inner tube, high pressure, 50.8 cm (20 in.) x 2.5 cm (1 in.)	12.60
tire, inner tube, high pressure, 55.9 cm (22 in.) x 2.5 cm (1 in.)	12.60
tire, inner tube, high pressure, 61.0 cm (24 in.) x 2.5 cm (1 in.)	12.60
tire, inner tube, high pressure, 66.0 cm (26 in.) x 2.5 cm (1 in.)	12.60
tire, inner tube, 61.0 cm (24 in.) x 3.5 cm ( $1^{3}$ / <sub>8</sub> in.), all-terrain, rounded surface	12.75
tire, inner tube, 61.0 cm (24 in.) x 3.5 cm (1 <sup>3</sup> / <sub>8</sub> in.), all-terrain, rounded surface	9.50
solid tire, 20.3 cm (8 in.) x 2.5 cm (1 in.)	4.50
solid tire, 55.9 cm (22 in.) x 2.5 cm (1 in.)	10.87
solid tire, 61.0 cm (24 in.) x 2.5 cm (1 in.)	10.44
tire, inner tube, 15.2 cm (6 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)	7.10
tire, inner tube, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.) (C-63)	6.60
tire, inner tube, 20.3 cm (8 in.) x 4.4 cm ( $1^{3}$ / <sub>4</sub> in.)	8.95
tire, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)	7.40
tire, inner tube, 18.8 cm (7 in.) x 4.4 cm ( $1^{3}/_{4}$ in.)	8.15

tire, inner tube, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.) (C-737)	6.60
semi-pneumatic tire, 12.7 cm (5 in.) x 2.5 cm (1 in.)	9.10
semi-pneumatic tire, 15.2 cm (6 in.) x 2.5 cm (1 in.)	9.10
semi-pneumatic tire, 20.3 cm (8 in.) x 2.5 cm (1 in.) (poly kik)	10.39
semi-pneumatic tire, 20.3 cm (8 in.) x 2.5 cm (1 in.) (poly pyramide)	10.02
semi-pneumatic tire, 55.9 cm (22 in.) x 2.5 cm (1 in.)	15.15
semi-pneumatic tire, 61.0 cm (24 in.) x 2.5 cm (1 in.)	15.95
semi-pneumatic tire, 66.0 cm (26 in.) x 2.5 cm (1 in.)	15.95
puncture-resistant tire, 15.2 cm (6 in.) x 3.2 cm ( $1\frac{1}{4}$ in.)	10.61
puncture-resistant tire, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)	11.00
puncture-resistant tire, 20.3 cm (8 in.) x 4.4 cm ( $1^{3}/_{4}$ in.)	12.50
puncture-resistant tire, 20.3 cm (8 in.) x 5.1 cm (2 in.)	14.00
puncture-resistant tire, 50.8 cm (20 in.) x 3.5 cm ( $\frac{13}{8}$ in.)	24.15
puncture-resistant tire, 55.9 cm (22 in.) x 3.5 cm ( $\frac{13}{8}$ in.)	24.15
puncture-resistant tire, 61.0 cm (24 in.) x 2.5 cm (1 in.)	19.90
puncture-resistant tire, 61.0 cm (24 in.) x 3.45 cm ( $1^3/_8$ in.)	24.40
airless insert, 15.2 cm (6 in.) x 3.2 cm ( $1\frac{1}{4}$ in.)	11.08
airless insert, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)	12.20
airless insert, 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4}$ in.)	14.80
airless insert, 50.8 cm (20 in.) x 3.5 cm ( $\frac{1}{8}$ in.)	20.63
airless insert, 55.9 cm (22 in.) x 3.5 cm ( $1^{3}/_{8}$ in.)	20.63
airless insert, $61.0 \text{ cm} (24 \text{ in.}) \times 3.2 \text{ cm} (1^{1}/_{4} \text{ in.})$	20.63
airless insert, 61.0 cm (24 in.) x 3.5 cm ( $1^{3}/_{8}$ in.)	20.63
airless insert, 66.0 cm (26 in.) x 3.5 cm ( $1^{3}/_{8}$ in.)	31.93

# TIRES AND INSERTS

# FOR POWERED WHEEL CHAIRS

# SUPPLIER: ORTHOFAB INC.

tire, inner tube, 33.0 cm (13 in.) x 10.2 cm (4 in.) (400-5)	16.70
tire, inner tube, $18.8 \text{ cm} (7 \text{ in.}) \times 4.4 \text{ cm} (1^{3}/_{4} \text{ in.})$	8.15
tire, inner tube, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)	6.60
tire, inner tube, 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4} in.)$	8.95
tire, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)	7.40
tire, inner tube, 21.6 cm $(8^{1}/_{2} \text{ in.}) \times 5.3 \text{ cm } (2^{1}/_{8} \text{ in.})$	37.00
tire, inner tube, 20.3 cm (8 in.) x 7 cm $(2^{3}/_{4}$ in.)	9.14
tire, inner tube, 22.9 cm (9 in.) x 7 cm $(2^{3}/_{4}$ in.)	9.95
tire, inner tube, 25.4 cm (10 in.) x 7.6 cm (3 in.)	11.50
tire, inner tube, 30.5 cm (12 in.) x 7.6 cm (3 in.)	15.95
tire, inner tube, 31.8 cm $(12^{1}/_{2} \text{ in.}) \times 5.7 \text{ cm } (2^{1}/_{4} \text{ in.})$	9.45
tire, inner tube, 35.6 cm (14 in.) x 5.7 cm ( $2^{1}/_{4}$ in.)	12.50
tire, inner tube, 35.6 cm (14 in.) x 7.6 cm (3 in.), (300-8)	17.95
tire, inner tube, 35.6 cm (14 in.) x 10.2 cm (4 in.) (400-6)	15.00
tire, inner tube, $40 \text{ cm} (15^3/_4 \text{ in.}) \times 7 \text{ cm} (2^3/_4 \text{ in.})$	58.00
tire, inner tube, $40.6 \text{ cm} (16 \text{ in.}) \times 5.7 \text{ cm} (2^{1}/_{4} \text{ in.})$	11.90
tire, inner tube, $40.6.\text{cm}$ (16 in.) x 5.3 cm (2 <sup>1</sup> / <sub>8</sub> in.)	11.90
tire, inner tube, 45.7 cm (18 in.) x 5.7 cm ( $2^{1}/_{4}$ in.)	12.45
tire, inner tube, $50.8 \text{ cm} (20 \text{ in.}) \times 5.3 \text{ cm} (2^{1}/_{8} \text{ in.})$	14.10
tire, inner tube, $50.8 \text{ cm} (20 \text{ in.}) \times 5.7 \text{ cm} (2^{1}/_{4} \text{ in.})$	12.45
semi-pneumatic tire, 20.3 cm (8 in.) x 4.4 cm ( $1^{3}/_{4}$ in.) (poly kik)	13.00

semi-pneumatic tire, 22.9 cm (9 in.) x 7 cm $(2^3/4 \text{ in.})$	28.00
puncture-resistant tire, 20.3 cm (8 in.) x 4.4 cm ( $1^{3}$ / <sub>4</sub> in.) (poly kik)	12.50
puncture-resistant tire, 22.9 cm (9 in.) x 7 cm $(2^{3}/_{4}$ in.), $(280/250-4)$	37.40
puncture-resistant tire, 25.4 cm (10 in.) x 7.6 cm (3 in.)	48.90
puncture-resistant tire, 30.5 cm (12 in.) x 7.6 cm (3 in.)	35.50
puncture-resistant tire, 35.6 cm (14 in.) x 10.2 cm (4 in.)	53.00
puncture-resistant tire, 35.6 cm (14 in.) x 7.6 cm (3 in.)	67.70
puncture-resistant tire, 35.6 cm (14 in.) x 10.2 cm (4 in.), (400-6)	53.00
puncture-resistant tire, 50.8 cm (20 in.) x 5.3 cm ( $^{2}$ / $_{8}$ in.)	29.00
puncture-resistant tire, 20.3 cm (8 in.) x 5.1 cm (2 in.)	14.00
puncture-resistant tire, 20.3 cm (8 in.) x 5.1 cm (2 in.) (poly kik)	13.50
airless insert, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)	12.20
airless insert, 20.3 cm (8 in.) x 4.4 cm (1 <sup>3</sup> / <sub>4</sub> in.)	14.80
airless insert, 31.8 cm $(12^{1}/_{2} \text{ in.})$ x 5.7 cm $(2^{1}/_{4} \text{ in.})$	24.00
airless insert, 35.6 cm (14 in.) x 5.7 cm ( $2^{1}/_{4}$ in.)	24.00
airless insert, $40.6 \text{ cm} (16 \text{ in.}) \times 5.3 \text{ cm} (2^{1}/_{8} \text{ in.})$	27.00
airless insert, 45.7 cm (18 in.) x 5.7 cm ( $2^{1}/_{4}$ in.)	23.00
airless insert, 50.8 cm (20 in.) x 5.3 cm ( $2^{1/8}$ in.)	23.00
airless insert, 50.8 cm (20 in.) x 5.7 cm ( $2^{1}/_{4}$ in.)	23.00

# **BATTERIES**

# FOR POWERED WHEEL CHAIRS

# SEALED LEAD BATTERIES (AQUEOUS-TYPE, DEEP CYCLE, NOMINAL VOLTAGE OF 12 VOLTS)

RPrice including delivery of goods and their recovery after use

GROUP 22:

Model: 22NF-DC

56.16

Model: 22F-DC

60.24

GROUP 24:

Model: 24-DC

50.93

GROUP U1:

Model: U1-DC

44.67

#### DIVISION II

POSITIONING BASES

#### DEVICE FROM: INVACARE CANADA INC.

**PRICE** 

# POSITIONING BASE, ADULT, "SOLARA" MODEL

\$1 713.00

#### **Basic Component(s)**

#### **Body support system**

- seating height: from  $42.5 \text{ cm} (16^3/_4 \text{ in.})$  to  $48.9 \text{ cm} (19^1/_4 \text{ in.})$
- seat widths: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.)
- seat depths: 30.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.)
- back heights: 50.8 cm (20 in.), 61.0 cm (24 in.)
- rocker device for seat and back, from  $-10^{\circ}$  to  $+45^{\circ}$
- folding back, angle-adjustable
- push handles
- push handles, angle-adjustable
- safety belt, velcro-type, auto-type
- supple back, nylon, nylon cloth for supple back, reclining

# **Armrests**

- "T"-type armrests, detachable, height-adjustable from 15.2 cm (6 in.), to 25.4 cm (10 in.) or from 20.3 cm (8 in.) to 35.6 cm (14 in.), short, long
- "U"-type armrests, fixed height, from 21.6 cm (8½ in.) to 31.8 cm (12½ in.), short, long
- "U"-type armrests, detachable, height-adjustable from 21.6 cm (8½ in.) to 31.8 cm (12½ in.), short, long
- "I"-type armrests, height-adjustable from 17.8 cm (7 in.) to 30.5 cm (12 in.), short, long
- straight armrest pads, short, long

- 60° footrests, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 44.5 cm (17¹/₂ in.)
- 70° footrests, detachable, swingaway, length-adjustable from 34.3 cm (13½ in.) to 41.9 cm (16½ in.)
- padded calfrests
- heel loops, non-adjustable
- heel loops, length-adjustable
- · folding footplates, standard

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock
- · standard forks
- threaded axles, quick-release
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.)
- · anti-tip rollers
- frame length: 73.7 cm (29 in.), 81.3 cm (32 in.), 86.4 cm (34 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.), 20.3 cm (8 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
modification of seat width to 53.3 cm (21 in.) or 55.9 cm (22 in.)	59.00	N/A
rigid seat, flat	49.00	95.00
rocker device for seat and back, from – 10° to + 45°	N/C	N/A
push handles	N/C	38.00
push handles, angle-adjustable	N/C	N/A
safety belt, velcro-type	N/C	40.00
safety belt, auto-type	N/C	50.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
supple back, nylon	N/C	50.00
nylon cloth for supple back, reclining	N/C	75.00
folding back, angle-adjustable	N/C	N/A
Armrests:		
"I"-type armrests, height-adjustable from 17.8 cm (7 in.)	NIG	00.00
to 30.5 cm (12 in.), short or long	N/C	98.00
"U"-type armrests, detachable, height-adjustable	NIC	00.00
from 21.6 cm ( $8^{1}/_{2}$ in.) to 31.8 cm ( $12^{1}/_{2}$ in.), short or long	N/C	98.00
"U"-type armrests, fixed height, from 21.6 cm (8½ in.)	N/C	66.00
to 31.8 cm (12 <sup>1</sup> / <sub>2</sub> in.), short or long "T"-type armrests, detachable, height-adjustable	N/C	00.00
from 15.2 cm (6 in.), to 25.4 cm (10 in.) or from 20.3 cm (8 in.)		
to 35.6 cm (14 in.), short or long	N/C	125.00
straight armrest pads, long	N/C N/C	26.00
straight armrest pads, long straight armrest pads, short	N/C N/C	26.00
straight armiest paus, short	IV/C	20.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
60° footrests, detachable, swingaway, length-adjustable		
from 34.3 cm $(13\frac{1}{2} \text{ in.})$ to 44.5 cm $(17\frac{1}{2} \text{ in.})$	N/C	81.00
70° footrests, detachable, swingaway, length-adjustable		
from 34.3 cm $(13^{1}/_{2} \text{ in.})$ to 41.9 cm $(16^{1}/_{2} \text{ in.})$	N/C	81.00
90° footrests, detachable, swingaway, length-adjustable		
from 6.4 cm $(2^{1}/_{2} \text{ in.})$ to 23.5 cm $(9^{1}/_{4} \text{ in.})$	107.00	
pair	107.00	125.00
each		135.00
60° footrests, MFX, detachable, swingaway, length-adjustable from 22.9 cm (9 in.) to 31.8 cm (12 <sup>1</sup> / <sub>2</sub> in.)		
pair	144.00	
each	144.00	153.00
70° footrests, MFX, detachable, swingaway, length-adjustable		155.00
from 14.6 cm ( $5^{3}/_{4}$ in.) to 29.8 cm ( $11^{3}/_{4}$ in.)		
pair	144.00	
each		153.00
70° elevating legrests, tapered, detachable, swingaway,		
length-adjustable from 32.4 cm $(12^{3}/_{4} \text{ in.})$ to 41.3 cm $(16^{1}/_{4} \text{ in.})$		
pair	107.00	
each		135.00
elevating legrests, detachable, swingaway, length-adjustable		
from 39.4 cm $(15^{1}/_{2} \text{ in.})$ to 50.8 cm (20 in.)	220.00	
pair	230.00	106.00
each elevating legrests, compensating mechanism		196.00
pair	151.00	
each	131.00	157.00
modification of legrest length by $-2.5$ cm (1 in.) or by $-5.1$ cm (2 in	.) 190.00	190.00
padded calfrests	N/C	20.00
single calf strap	22.00	34.00
double calf strap	35.00	52.00
folding footplates, standard	N/C	40.00
folding footplates, angle-adjustable and depth-adjustable,		
standard size or oversized 18.4 cm (7 <sup>1</sup> / <sub>4</sub> in.)		
pair	72.00	
each		76.00
oversized footplates	20.00	
pair	39.00	(0.00
each	N/C	60.00
heel loops, non-adjustable heel loops, length-adjustable	N/C N/C	5.00 12.00
heel loops and ankle straps	IV/C	12.00
pair	32.00	
each	52.00	16.00
V4011		10.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems:		
anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	34.00
plastic-coated or combined handrims	52.00	
each	32.00	60.00
handrims with vertical or oblique projections		00.00
pair	155.00	
each		112.00
anti-tip rollers	N/C	48.00
frame length, 73.7 cm (29 in.), 81.3 cm (32 in.) or 86.4 cm (34 in.)	N/C	400.00
Wheel locks:		
standard wheel locks, push-to-lock	N/C	44.00
wheel lock extensions		
pair	32.00	16.00
each		16.00
Types of forks:		
standard forks	N/C	50.00
Rear axles:		
threaded axles	N/C	16.00
quick-release axles	N/C	53.00
Types of wheels:		
rear mag wheels, standard pressure, 30.5 cm (12 in.)	N/C	71.00
rear mag wheels, standard pressure, 50.8 cm (20 in.),	NIC	00.00
55.9 cm (22 in.) or 61.0 cm (24 in.) rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)	N/C	90.00
or 61.0 cm (24 in.)	N/C	90.00
Front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)	1470	70.00
or 15.2 cm (6 in.)	N/C	40.00
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)	N/C	52.00
Front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	70.00
front wheels, semi-pneumatic, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
pair	56.00	
each		68.00
Front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)	49.00	
pair each	48.00	64.00
Cacii		04.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
contracture footrests, bilateral-angle adjustable*	176.00	265.00
reclining back*	496.00	776.00
heavy-duty frame*	322.00	N/A
contracture footrests, one-piece*	176.00	265.00
DEVICE FROM: ORTHOFAB INC.		
		PRICE
POSITIONING BASE, ADULT, "TANGO" MODEL		\$1 669.00

# **Basic Component(s)**

### **Body support system**

- seat height: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat widths: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.)
- seat depths: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.)
- folding back, angle-adjustable, height of 40.6 cm (16 in.) to 66.0 cm (26 in.)
- rocker device for seat and back, from  $-5^{\circ}$  to  $+45^{\circ}$
- · push handles
- safety belt, auto-type

#### **Armrests**

- "U"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), short
- straight armrest pads, short, long
- · rigid clothing guards

- 60° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- · padded calfrests
- heel loops, length-adjustable
- folding footplates, standard

- · straight front frame
- · standard wheel locks, push-to-lock
- · high forks
- threaded axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.)
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.), 17.8 cm (7 in.), 15.2 cm (6 in.) x 2.5 cm (1 in.)
- · anti-tip rollers
- smooth handrims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
headrest, hammock-style	75.00	75.00
padded headrest, contoured, nylon	100.00	100.00
rigid seat, flat	81.00	81.00
rocker device for seat and back, from $-5^{\circ}$ to $+45^{\circ}$	N/C	N/A
push handles	N/C	N/A
articulated headrest mounting	102.00	102.00
articulated headrest mounting, uniball	115.00	115.00
back tension bar with headrest mounting bracket	99.00	99.00
back tension bar	69.00	69.00
safety belt, velcro-type	27.00	63.00
safety belt, auto-type	N/C	36.00
safety belt, airplane-type	38.00	74.00
seat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
seat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
supple back, nylon	64.00	64.00
supple back, tension adjustable	133.00	133.00
folding back, angle-adjustable, height of 40.6 cm (16 in.)		
to 66.0 cm (26 in.)	N/C	N/A
Armrests:		
"U"-type armrests, detachable, height-adjustable	NIC	04.00
from 25.4 cm (10 in.) to 35.6 cm (14 in.), short	N/C	94.00
"U"-type armrests, detachable, height-adjustable		
from 25.4 cm (10 in.) to 35.6 cm (14 in.), long	52.00	
pair	52.00	120.00
each	NI/C	120.00
straight armrest pads, long	N/C	15.00
straight armrest pads, short	N/C	12.00
contoured armrest pads, short	44.00	
pair	44.00	24.00
each		34.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
contoured armrest pads, long		
pair	48.00	
each		39.00
modification of armrest height to under 25.4 cm (10 in.)	79.00	N/A
rigid clothing guards	N/C	N/A
Footrests:		
60° footrests, tapered, detachable, swingaway, length-adjustable	27/0	102.00
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	102.00
70° footrests, tapered, detachable, swingaway, length-adjustable	NIG	102.00
from 35.6 cm (14 in.) to 48.3 cm (19 in.)	N/C	102.00
60° or 70° footrests, parallel, detachable, swingaway,	20.00	NT/A
ength-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)	29.00	N/A
90° footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
oair	86.00	
each	80.00	145.00
elevating legrests, detachable, swingaway, length-adjustable		143.00
from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
pair	165.00	
each	100.00	185.00
elevating legrests, compensating mechanism, detachable, swingaway.		
ength-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)		
pair	234.00	
each		219.00
modification of footrest or legrest length to under 35.6 cm (14 in.)		
or to over 48.3 cm (19 in.)	79.00	N/A
padded calfrests	N/C	20.00
contoured calfrests		
pair	60.00	
each		50.00
louble calf strap	55.00	55.00
folding footplates, standard	N/C	16.00
Olding footplates, aluminum	41.00	
pair	41.00	26.00
each		36.00
standard footplates, angle-adjustable and depth-adjustable	72.00	
oair each	72.00	52.00
oversized footplates, angle-adjustable and depth-adjustable		32.00
oair	79.00	
each	13.00	55.00
facii Full-width footplate, angle-adjustable	168.00	200.00
ront impact guard with rollers	100.00	200.00
pair	36.00	
each	30.00	18.00
oe loops		10.00
pair	30.00	
ach		15.00
neel loops, length-adjustable	N/C	11.00
1 / 1 01 111/11111111111111111111111111	<del>-</del>	

ypes of drive systems: nooth handrims		Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
mooth handrims         N/C         46.00           on-slip handrims         84.00         88.00           ach         88.00         88.00           lastic-coated handrims         74.00         88.00           air         56.00         74.00           ombined handrims         74.00         74.00           air         66.00         79.00           ont anti-tip rollers         N/C         46.00           prional flared frame         N/C         N/A           vheel lock reference         N/C         N/A           vheel lock extensions, retractable         N/C         53.00           heel lock extensions, fixed         19.00           air         38.00         1           air         38.00         1           air         38.00         1           air         86.00         1           air         86.00         4           air         86.00         4           air         86.00         4           ser arakes:         86.00         5           tended axles         N/C         5         5           yes of wheels:         87.00         1         1	Wheels and frame		
on-slip handrims air ach	Types of drive systems:		
air ach ach 88.00 lastic-coated handrims air 56.00 ashic-coated handrims air 66.00 abhed 66.00 ambined handrims air 66.00 anti-tip rollers ach 79.00 ont anti-tip rollers yes of lock extensions, retractable air 38.00 ach 19.00 heel lock extensions, retractable air 38.00 ach 19.00 heel lock extensions, fixed air 98.00 ach 19.00 air arm ag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 98.00 arm ag wheels, standard pressure, 30.5 cm (12 in.) ach 123.00 arm ag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00 ach 108.00 booked rear wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00	smooth handrims	N/C	46.00
ach lastic-coated handrims air 56.00 are coated handrims air 66.00 are coated handrims 79.00 are may beels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air are may wheels, solid tires, 30.5 cm (12 in.) are may wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air are may wheels, standard pressure, 50.8 cm (20 in.) are may wheels, standard pressure, 50.8 cm (20 in.) are may wheels, solid tires, 30.5 cm (12 in.) are may wheels, solid tires, 30.5 cm (12 in.) are may wheels, solid tires, 30.5 cm (12 in.) are may wheels, solid tires, 30.5 cm (12 in.) are may wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00 are may wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00 are may wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00 are may wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00 are coated are wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00 are coated are wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00 are coated are wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00 are coated are wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00 are coated are wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00 are coat		84.00	
lastic-coated handrims air		04.00	88.00
air ach 56.00 ach 74.00 ombined handrims air 66.00 ach 79.00 ombined handrims air 66.00 ach 79.00 ach 79.0			00.00
bombined handrims air air 66.00 air air 79.00 ach 79.00 and anti-tip rollers 79.00 N/C 46.00 N/C 46.00 N/C N/C N/A 46.00 N/A N/C N/A N/A N/C 53.00 air 38.00	air	56.00	
air ach ach 79.00 ach 79.00 ach 79.00 ont anti-tip rollers N/C 46.00 ptional flared frame 95.00 N/A raight front frame N/C N/A Wheel locks: andard, push-to-lock N/C 53.00 ach ach 19.00 a	ach		74.00
ach ont anti-tip rollers problems		< 0.0	
ront anti-tip rollers potional flared frame	air	66.00	70.00
ptional flared frame		N/C	
raight front frame N/C N/A  Vheel locks: andard, push-to-lock N/C 53.00 heel lock extensions, retractable air 38.00 aich 19.00 heel lock extensions, fixed air 38.00 air 38.00 air 38.00 air 38.00 air 43.00  Vypes of forks: igh forks N/C 55.00  Vypes of wheels: ara mag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air ach 123.00 ara mag wheels, solid tires, 30.5 cm (12 in.) air ach 123.00 ara mag wheels, solid tires, 30.5 cm (12 in.) air ach 123.00 ara mag wheels, standard pressure, 50.8 cm (20 in.) air ach 123.00 ara mag wheels, solid tires, 30.5 cm (12 in.) air 68.00 air ach 123.00 ara mag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00	ntional flared frame		
Wheel locks:     N/C     53.00       andard, push-to-lock     N/C     53.00       cheel lock extensions, retractable air     38.00     19.00       arch     19.00     19.00       cheel lock extensions, fixed air     38.00     19.00       arch     19.00     19.00       nti-rollback brakes     86.00     43.00       ach     43.00     43.00       ypes of forks:     ypes of forks:     ypes of forks:       igh forks     N/C     55.00       ypes of wheels:     ypes of wheels:       sar mag wheels, standard pressure, 50.8 cm (20 in.),     5.00       5.9 cm (22 in.) or 61.0 cm (24 in.)     98.00       aar mag wheels, standard pressure, 30.5 cm (12 in.)     N/C     74.00       aar mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)     98.00       aar mag wheels, solid tires, 30.5 cm (12 in.)     aar mag wheels, solid tires, 30.5 cm (12 in.)     123.00       aar mag wheels, solid tires, 30.5 cm (12 in.)     68.00     123.00       aar mag wheels, standard pressure, 50.8 cm (20 in.),     68.00     108.00       aar mag wheels, standard pressure, 50.8 cm (20 in.),     68.00     68.00			
andard, push-to-lock heel lock extensions, retractable air ach		- " -	- 11
theel lock extensions, retractable air and above theel lock extensions, fixed air and above theel lock extensions, fixed air as a second air and above theel lock extensions, fixed air as a second air above theel lock extensions, fixed above theel lock extensions, fixed air above theel lock extensions, fixed above theel lock extensions, fixed air above theel lock extensions, fixed above theel lock extensions above the lock extensions above theel lock extensions and fixed extensions above the lock extensions above the lock extensions above the lock extensions and fixed extensions above the lock extensions above the lo	Wheel locks:		
air ach 19.00 cheel lock extensions, fixed air 38.00 ach 19.00 cheel lock extensions, fixed air 38.00 ach 19.00 cheel school brakes air 86.00 ach 43.00 chear axles: meaded axles N/C 55.00 chear axles: mag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air and wheels, standard pressure, 30.5 cm (12 in.) air and wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.) air 98.00 ach 123.00 chear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.) air 98.00 ach 123.00 chear mag wheels, solid tires, 30.5 cm (12 in.) air 68.00 ach 123.00 chear mag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00 ach 123.00 chear mag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00 ach 108.00 chear mag wheels, standard pressure, 50.8 cm (20 in.), 68.00 ach 108.00 chear mag wheels, standard pressure, 50.8 cm (20 in.), 68.00 ach 108.00 chear mag wheels, standard pressure, 50.8 cm (20 in.), 68.00 ach 108.00 chear mag wheels, standard pressure, 50.8 cm (20 in.), 68.00 ach 108.00 chear mag wheels, standard pressure, 50.8 cm (20 in.), 68.00 ach 108.00 chear mag wheels, standard pressure, 50.8 cm (20 in.), 68.00 ach 108.00 ach		N/C	53.00
theel lock extensions, fixed air 38.00 air 38.00 air 38.00 air 19.00 air 38.00 air 38.		29.00	
theel lock extensions, fixed air 38.00 arch 19.00 arch		36.00	19.00
air ach 19.00 nti-rollback brakes air 86.00 ach 43.00 ach 43.00 ach 86.00 ach 43.00 arm ang wheels, standard pressure, 30.5 cm (12 in.) arm ang wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.) air ach ach 86.00 ach 123.00 ach arm ang wheels, standard pressure, 50.8 cm (20 in.) air 68.00 ach 68.00			17.00
ach 19.00  nti-rollback brakes air 86.00  ach 43.00   types of forks: igh forks N/C 55.00  tear axles: are aded axles N/C 55.00  types of wheels: are mag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air and wheels, standard pressure, 30.5 cm (12 in.) air and wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.) air and wheels, solid tires, 30.5 cm (12 in.) air and wheels, solid tires, 30.5 cm (12 in.) air and wheels, solid tires, 30.5 cm (12 in.) air 68.00 air and wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00 and 108.00	air	38.00	
air 86.00  Aypes of forks:  igh forks  N/C 55.00  Agear axles:  are aded axles  N/C 5.00  Aypes of wheels:  are mag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.)  air 98.00  are mag wheels, standard pressure, 30.5 cm (12 in.)  are mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)  air 98.00  are mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)  air 98.00  are mag wheels, solid tires, 30.5 cm (12 in.)  air 68.00  are mag wheels, standard pressure, 50.8 cm (20 in.),  are mag wheels, standard pressure, 50.8 cm (20 in.),  are mag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.)  air 68.00	ach		19.00
Asymptotic   Asy		0.6.00	
ypes of forks:  igh forks  N/C  55.00  Rear axles:  preaded axles  N/C  5.00  ypes of wheels:  par mag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.)  par mag wheels, standard pressure, 30.5 cm (12 in.)  par mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)  par mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)  par mag wheels, solid tires, 30.5 cm (12 in.)  par mag wheels, solid tires, 30.5 cm (12 in.)  par mag wheels, solid tires, 30.5 cm (12 in.)  par mag wheels, solid tires, 30.5 cm (12 in.)  par mag wheels, solid tires, 30.5 cm (12 in.)  par mag wheels, solid tires, 30.5 cm (12 in.)  par mag wheels, solid tires, 30.5 cm (20 in.),  par mag wheels, standard pressure, 50.8 cm (20 in.),  5.9 cm (22 in.) or 61.0 cm (24 in.)  air  68.00	oair	86.00	42.00
tear axles:  Irreaded axles  N/C  5.00  Ixreaded axles  Ixread	acn		43.00
tear axles:  Intereded axles  Intereded	Types of forks:		
readed axles  N/C  Spes of wheels:  Exar mag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.)  Exar mag wheels, standard pressure, 50.8 cm (20 in.),  Exar mag wheels, standard pressure, 30.5 cm (12 in.)  Exar mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)  Exar mag wheels, solid tires, 30.5 cm (12 in.)  Exar mag wheels, solid tires, 30.5 cm (22 in.) or 61.0 cm (24 in.)	nigh forks	N/C	55.00
readed axles  N/C  Spes of wheels:  Exar mag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.)  Exar mag wheels, standard pressure, 50.8 cm (20 in.),  Exar mag wheels, standard pressure, 30.5 cm (12 in.)  Exar mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)  Exar mag wheels, solid tires, 30.5 cm (12 in.)  Exar mag wheels, solid tires, 30.5 cm (22 in.) or 61.0 cm (24 in.)	Rear ayles		
tar mag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air ach ach ar mag wheels, standard pressure, 30.5 cm (12 in.) ar mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.) air ach	hreaded axles	N/C	5.00
5.9 cm (22 in.) or 61.0 cm (24 in.) air 98.00 ach 123.00 ar mag wheels, standard pressure, 30.5 cm (12 in.) N/C 74.00 ar mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.) air 98.00 ach 123.00 ach 123.00 ach 68.00 ach 68.00 ach 68.00 ach 108.00 ach 68.00	Types of wheels: ear mag wheels, standard pressure, 50.8 cm (20 in.).		
123.00 arr mag wheels, standard pressure, 30.5 cm (12 in.) N/C 74.00 arr mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.) arr mag wheels, solid tires, 30.5 cm (12 in.) 98.00 arr mag wheels, solid tires, 30.5 cm (12 in.) arr mag wheels, solid tires, 30.5 cm (12 in.) 68.00 arr mag wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) arr 68.00	55.9 cm (22 in.) or 61.0 cm (24 in.)		
ear mag wheels, standard pressure, 30.5 cm (12 in.)  ear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)  ear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)  ear mag wheels, solid tires, 30.5 cm (12 in.)  ear mag wheels, solid tires, 30.5 cm (12 in.)  ear mag wheels, standard pressure, 50.8 cm (20 in.),  5.9 cm (22 in.) or 61.0 cm (24 in.)  ear mag wheels, standard pressure, 50.8 cm (20 in.),  68.00	pair	98.00	
ear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)  air 98.00  123.00  ach ear mag wheels, solid tires, 30.5 cm (12 in.)  air 68.00  108.00  108.00  5.9 cm (22 in.) or 61.0 cm (24 in.)  air 68.00	ach	NAC	
air 98.00 ach 123.00 ear mag wheels, solid tires, 30.5 cm (12 in.) air 68.00 ach 108.00		N/C	74.00
123.00 tar mag wheels, solid tires, 30.5 cm (12 in.)  air 68.00 tach  ach  booked rear wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.)  air 68.00		98.00	
ear mag wheels, solid tires, 30.5 cm (12 in.)  air 68.00  ach 108.00  boked rear wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.)  air 68.00	ach	70.00	123.00
108.00 boked rear wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00	ear mag wheels, solid tires, 30.5 cm (12 in.)		
boked rear wheels, standard pressure, 50.8 cm (20 in.), 5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00	air	68.00	
5.9 cm (22 in.) or 61.0 cm (24 in.) air 68.00	ach		108.00
air 68.00			
		68.00	
	ach	00.00	108.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.) spoked rear wheels, semi-pneumatic tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	74.00
pair each rear mag wheels, semi-pneumatic tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	68.00	108.00
pair each	128.00	138.00
Front wheels, solid tires, 20.3 cm (8 in.), 17.8 cm (7 in.) or 15.2 cm (6 in.) x 2.5 cm (1 in.) Front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	N/C	30.00
or 15.2 cm (6 in.) x 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) to air teach front wheels, semi-pneumatic tires, 20.3 cm (8 in.),	32.00	46.00
5.2 cm (6 in) or 12.7 cm (5 in.) x 3.8 cm (1 <sup>1</sup> / <sub>2</sub> in.) pair each	32.00	46.00
Component(s) under Special Consideration		
eclining back* poke guards*	699.00	699.00
pair each puick-release axles*	114.00	57.00
pair each	76.00	43.00
DEVICE FROM: SUNRISE MEDICAL CANADA INC.		PRIC
POSITIONING BASE, ADULT, "QUICKIE TS" MODEL		\$1 790.

# Basic Component(s)

# **Body support system**

- seat height: from 40.6 cm (16 in.) to 50.8 cm (20 in.)
- seat width: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- seat depth: from 35.6 cm (14 in.) to 55.9 cm (22 in.)
- rocker mechanism, from 0° to 45°
- safety belt, auto-type, velcro-type
- raised push handles
- angle-adjustable back
- back heights: 54.6 cm (21<sup>1</sup>/<sub>2</sub> in.), 62.2 cm (24<sup>1</sup>/<sub>2</sub> in.), 69.9 cm (27<sup>1</sup>/<sub>2</sub> in.), with push handles

#### Armrests

- "T"-type armrests, detachable, height-adjustable from 26.0 cm (10<sup>1</sup>/<sub>4</sub> in.) to 38.7 cm (15<sup>1</sup>/<sub>4</sub> in.), short, long, with built-in clothing guards
- "L"-type armrests, height adjustable from 16.5 cm (6<sup>1</sup>/<sub>2</sub> in.) to 33.0 cm (13 in.), short, long
- straight armrest pads, short, long
- tubular armrest pads

#### **Footrests**

- 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 37.5 cm (14<sup>3</sup>/<sub>4</sub> in.) to 43.8 cm (17<sup>1</sup>/<sub>4</sub> in.)
- 70 footrests, tapered, detachable, swingaway, length-adjustable from 37.5 cm (14<sup>3</sup>/<sub>4</sub> in.) to 43.8 cm (17<sup>1</sup>/<sub>4</sub> in.)
- 70°, 80°, 90° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- padded calfrests
- padded calfrests for legrests with compensating mechanism
- heel loops, length-adjustable
- · folding footplates, standard

- smooth handrims, 45.7 cm (18 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- fork stems,  $+ 1.9 \text{ cm} (\sqrt[3]{4} \text{ in.}), + 3.8 \text{ cm} (1\sqrt[1]{2} \text{ in.})$
- quick-release axles
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- anti-tip rollers
- standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5<sup>1</sup>/<sub>4</sub> in.); high forks 17.8 cm (7 in.), for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
neadrest, small	90.00	93.00
neadrest, medium	96.00	103.00
neadrest, large	102.00	107.00
rigid seat, flat	47.00	89.00
rocker mechanism, from 0° to 45°	N/C	N/A
afety belt, velcro-type	N/C	28.00
afety belt, auto-type	N/C	41.00
afety belt, airplane-type	49.00	77.00
afety belt, airplane-type, padded	74.00	101.00
crossbar for headrest mounting	194.00	206.00
articulated headrest mounting	154.00	168.00
aised push handles	N/C	N/A
back height: $54.6 \text{ cm} (21^{1}/_{2} \text{ in.}), 62.2 \text{ cm} (24^{1}/_{2} \text{ in.})$		
or 69.9 cm $(27^{1}/_{2} \text{ in.})$ , with push handles	N/C	N/A
olding back, angle-adjustable	N/C	N/A
Armrests:		
'U"-type armrests, detachable, height-adjustable		
From 24.1 cm (9 $\frac{1}{2}$ in.) to 36.8 cm (14 $\frac{1}{2}$ in.), short or long,		
vith built-in clothing guards		
pair	132.00	
each		156.50
'T"-type armrests, detachable, height-adjustable		
From 26.0 cm $(10^{1}/_{4} \text{ in.})$ to 38.7 cm $(15^{1}/_{4} \text{ in.})$ , short or long,		
vith built-in clothing guards	N/C	132.00
'I"-type armrests, height-adjustable from 16.5 cm (6 <sup>1</sup> / <sub>2</sub> in.)		
o 33.0 cm (13 in.), short or long	N/C	90.50
ubular armrest pads	N/C	2.00
straight armrest pads, long	N/C	17.00
straight armrest pads short	N/C	15.00
igid clothing guards, detachable		
pair	90.00	
each		66.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
70°, 80° or 90° footrests, parallel, detachable, swingaway,		
length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)	N/C	55.00
70° or 80° footrests, heavy-duty, detachable, non-flip-back		
pair	63.00	0.4.00
each		84.00
60° or 70° footrests, parallel, detachable, swingaway,	3716	
length-adjustable from 37.5 cm $(14^{3}/_{4} \text{ in.})$ to 43.8 cm $(17^{1}/_{4} \text{ in.})$	N/C	52.50
70° footrests, tapered, detachable, swingaway, length-adjustable	NIG	52.50
from 37.5 cm $(14^3/_4 \text{ in.})$ to 43.8 cm $(17^1/_4 \text{ in.})$	N/C	52.50
elevating legrests	105.00	
pair	105.00	105.00
each		105.00
elevating legrests, compensating mechanism	194.00	
each	194.00	149.50
modification of footrest length from 45.7 cm (18 in.)		149.30
to 52.1 cm ( $20^{1/2}$ in.)		
pair	30.00	
each	30.00	29.00
padded calfrests	N/C	18.00
calfrests for legrests with compensating mechanism	N/C	39.00
contoured calfrests	100	27.00
pair	70.00	
each		53.00
single calf strap	18.00	18.00
Folding footplates, standard	N/C	48.00
Folding footplates, standard size, angle-adjustable and depth-adjustable		
pair	51.00	
each		73.50
90° legrests, from 20.3 cm (8 in.) to 33.0 cm (13 in.)		
pair	69.00	
each		87.00
full-width footplate, angle-adjustable	83.00	179.00
modification of length of detachable footrests by 5.1 cm (2 in.)		
or by 10.2 cm (4 in.)		
pair	30.00	
each		15.00
full-width foot platform, 90°	89.00	185.00
heel loops, length-adjustable	N/C	10.00
footrest mounting, from 17.8 cm (7 in.) to $34.3$ cm ( $13^{1}/_{2}$ in.)		
pair	54.00	
each		33.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems:		
smooth handrims, 45.7 cm (18 in.), 50.8 cm (20 in.),		
55.9 cm (22 in.), 61.0 cm (24 in.)	N/C	58.00
small handrim for one-arm drive	<b>5</b> 4.00	
pair	54.00	27/4
each		N/A
plastic-coated handrims, 45.7 cm (18 in.), 50.8 cm (20 in.),		
55.9 cm (22 in.), 61.0 cm (24 in.)	54.00	
pair	54.00	05.00
each		85.00
handrims with oblique or vertical projections	88.00	
pair each	88.00	102.00
anti-tip rollers	N/C	22.00
tapered frame	128.00	22.00 N/A
frame with growth option	128.00	N/A N/A
heavy-duty frame: robust option (350 lb.)	81.00	N/A
one-arm drive for dual handrim	549.00	692.00
cane holder	44.00	44.00
front anti-tippers		
pair	55.00	
each	22123	27.50
Wheel locks:		
standard, push-to-lock or pull-to-lock	N/C	39.00
anti-rollback brakes		
pair	66.00	
each		33.00
wheel lock extensions	25.00	
pair	26.00	12.00
each		13.00
Types of forks:		
standard forks, 15.2 cm (6 in.); short forks, 13.3 cm ( $5^{1}/_{4}$ in.);		
or high forks 17.8 cm (7 in.) for 12.7 cm (5 in.),		
15.2 cm (6 in.) and 20.3 cm (8 in.) wheels	N/C	31.00
fork stems, $+ 1.9 \text{ cm} (\sqrt[3]{4} \text{ in.}) \text{ or } + 3.8 \text{ cm} (\sqrt{1}/2 \text{ in.})$	N/C	16.00
(,4 m) (1, 2 m)	1., 0	10.00
Rear axles:		
quick-release axles	N/C	32.50
rear-wheel camber	112.00	N/A

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
rear mag wheels, standard pressure, 30.5 cm (12 in.) rear mag wheels, standard pressure, 55.9 cm (22 in.)	N/C	126.00
or 61.0 cm (24 in.)	N/C	110.00
rear mag wheels, standard pressure, 50.8 cm (20 in.) rear mag wheels, standard pressure, 40.6 cm (16 in.)	N/C	132.00
pair	32.00	
each		142.00
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	132.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	132.00
spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	149.00
spoked rear wheels, standard pressure, 45.7 cm (18 in.)	32.00	
oair each	32.00	126.00
Front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)	N/C	61.00
Front wheels, solid tires, 20.3 cm (6 in.) x 2.3 cm (1 in.)	N/C N/C	60.00
Front wheels, solid tires, 13.2 cm (6 in.)	N/C N/C	46.00
Front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm ( $1^{1}/_{4}$ in.) front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	60.00
pair	47.00	
each	17.00	69.50
Front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm ( $1^{1}/_{2}$ i or 15.2 cm (6 in.) x 3.8 cm ( $1^{1}/_{2}$ in.)	n.)	09.50
pair	80.00	
each		86.00
Front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm ( $1^{1}/_{2}$ i	n.)	
pair	100.00	
each		96.00
Front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)	N/C	61.00
Component(s) under Special Consideration		
reclining back, including tension bar* spoke guards*	414.00	N/A
pair	67.00	
each	07.00	33.50
contracture footrests*	295.00	387.00
seat frame for contracture footrests*	128.00	367.00 N/A
eat frame for contracture footiests"	120.00	IN/A

# DEVICE FROM: LES ÉQUIPEMENTS ADAPTÉS PHYSIPRO INC.

**PRICE** 

# POSITIONING BASE, ADULT, "CARDINAL" MODEL

\$1 760.00

#### **Basic Component(s)**

# **Body support system**

- folding back, angle-adjustable, height of 43.2 cm (17 in) to 55.9 cm (22 in.)
- seat structure, width-adjustable from 38.1 cm (15 in.) to 61.1 cm (24 in.), and depth-adjustable from 40.6 cm (16 in.) to 55.9 cm (22 in.)
- rocker device for seat and back, from  $-10^{\circ}$  to  $+35^{\circ}$
- seat height: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- "U"-shaped push handles, straight
- safety belt, velcro-type, auto-type

#### Armrests

- "T"-type armrests, detachable, flip-back, height-adjustable from 21.6 cm (8½ in.) to 34.3 cm (13½ in.), short, or "T"-type armrests, detachable, flip-back, height-adjustable from 29.2 cm (11½ in.) to 39.4 cm (15½ in.), long
- straight armrest pads, short, long
- rigid clothing guards

#### **Footrests**

- 60°, 70°, 75° footrests, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 40.6 cm (16 in.)
- heel loops, length-adjustable
- folding footplates, standard
- padded calfrests
- modification of footrest length

- standard wheel locks, push-to-lock
- · standard forks
- · threaded axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)
- anti-tip rollers
- tie-down points for adapted transport
- smooth handrims for 50.8 cm (20 in.), 55.9 cm (22 in.) and 61.0 cm (24 in.) wheels

Basic and Optional Component(s)  Body support system  Seat and back: "U"-shaped push handles, straight safety belt, velcro-type safety belt, auto-type rocker device for seat and back, from – 10° to + 35° rigid seat, flat, grooved and adjustable back tension bar headrest, small, medium, large headrest bracket crossbar for headrest bracket	N/C N/C N/C N/C 92.00 118.00 95.00 135.00	N/A 18.00 48.00 N/A 92.00 118.00 95.00
Seat and back: "U"-shaped push handles, straight safety belt, velcro-type safety belt, auto-type rocker device for seat and back, from – 10° to + 35° rigid seat, flat, grooved and adjustable back tension bar headrest, small, medium, large headrest bracket crossbar for headrest bracket	N/C N/C N/C 92.00 118.00 95.00 135.00	18.00 48.00 N/A 92.00 118.00
"U"-shaped push handles, straight safety belt, velcro-type safety belt, auto-type rocker device for seat and back, from – 10° to + 35° rigid seat, flat, grooved and adjustable back tension bar headrest, small, medium, large headrest bracket crossbar for headrest bracket	N/C N/C N/C 92.00 118.00 95.00 135.00	18.00 48.00 N/A 92.00 118.00
safety belt, velcro-type safety belt, auto-type rocker device for seat and back, from – 10° to + 35° rigid seat, flat, grooved and adjustable back tension bar headrest, small, medium, large headrest bracket crossbar for headrest bracket	N/C N/C N/C 92.00 118.00 95.00 135.00	18.00 48.00 N/A 92.00 118.00
safety belt, auto-type rocker device for seat and back, from – 10° to + 35° rigid seat, flat, grooved and adjustable back tension bar headrest, small, medium, large headrest bracket crossbar for headrest bracket	N/C N/C 92.00 118.00 95.00 135.00	48.00 N/A 92.00 118.00
rocker device for seat and back, from – 10° to + 35° rigid seat, flat, grooved and adjustable back tension bar headrest, small, medium, large headrest bracket crossbar for headrest bracket	N/C 92.00 118.00 95.00 135.00	N/A 92.00 118.00
rigid seat, flat, grooved and adjustable back tension bar headrest, small, medium, large headrest bracket crossbar for headrest bracket	92.00 118.00 95.00 135.00	92.00 118.00
back tension bar headrest, small, medium, large headrest bracket crossbar for headrest bracket	118.00 95.00 135.00	118.00
headrest, small, medium, large headrest bracket crossbar for headrest bracket	95.00 135.00	
headrest bracket crossbar for headrest bracket	135.00	95 NN
crossbar for headrest bracket		
		135.00
	210.00	210.00
basic growth kit	78.00	78.00
folding back, angle-adjustable, height of 43.2 cm (17 in.)		
to 55.9 cm (22 in.)	N/C	N/A
Armrests:		
"T"-type armrests, detachable, flip-back, height-adjustable		
from 21.6 cm ( $8^{1}/_{2}$ in.) to 34.3 cm ( $13^{1}/_{2}$ in.), short, or		
"T"-type armrests, detachable, flip-back, height-adjustable		
from 29.2 cm (11 $^{1}$ / <sub>2</sub> in.) to 39.4 cm (15 $^{1}$ / <sub>2</sub> in.), long	N/C	186.00
straight armrest pads, short	N/C	26.00
straight armrest pads, long	N/C	28.00
rigid clothing guards	N/C	14.00
Footrests:		
60°, 70° or 75° footrests detachable, swingaway, length-adjustable		
from 27.9 cm (11 in.) to 40.6 cm (16 in.)	N/C	99.00
90° footrests, detachable, swingaway, length-adjustable	14.6	<i>)</i>
from 27.9 cm (11 in.) to 40.6 cm (16 in.)		
pair	60.00	
each	00.00	129.00
elevating legrests, detachable, swingaway, length-adjustable		127.00
pair	376.30	
each	270.20	287.30
"H"-shaped calf strap	45.00	45.00
single calf strap	43.00	43.00
double calf strap	55.00	55.00
single calf strap, cushioned	80.00	80.00
double calf strap, cushioned	95.00	95.00
folding footplates, standard	N/C	40.00
folding footplates, angle-adjustable and depth-adjustable, non-skid		10.00
pair	70.00	
each	, 5.50	75.00
folding footplates, oversized, angle-adjustable and depth-adjustable	<b>1</b>	75.00
non-skid	<b>,</b>	
pair	100.00	
each	100.00	90.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
folding footplate, full-width, angle-adjustable and depth-adjust	able,	
non-skid	140.00	110.00
heel loops, length-adjustable	N/C	12.00
toe loops pair	20.00	
each	20.00	22.00
nodification of footrest length	N/C	40.00
contoured calfrests	26.00	
pair each	36.00	48.00
padded calfrests	N/C	30.00
ront impact guard with roller	14/6	30.00
pair	80.00	
each		40.00
Wheels and frame		
Types of drive systems: neavy-duty frame	180.00	N/A
mooth handrims for 50.8 cm (20 in.), 55.9 cm (22 in.)	100.00	1471
nd 61.0 cm (24 in.) wheels	N/C	45.00
lastic-coated handrims	(0.00	
air ach	60.00	75.00
on-slip handrims		73.00
air	70.00	
ach		80.00
andrims with vertical, oblique or horizontal projections pair	158.00	
ach	130.00	124.00
nti-tip rollers	N/C	43.00
Wheel locks:		
tandard, push-to-lock	N/C	55.00
vheel lock extensions		
air	30.00	4.500
ach nti-rollback brakes		15.00
air	104.00	
ach		52.00
lyman of foulty		
Types of forks: tandard forks	N/C	56.00
	100	50.00
Rear axles:	27/0	
hreaded axles lates with hardware for 50.8 cm (20 in.), 55.9 cm (22 in.)	N/C	6.00
nd 61.0 cm (24 in.) wheels		
air	156.00	
ach		78.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
rear mag wheels, standard pressure, 30.5 cm (12 in.) rear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C	76.00
pair	98.00	
each		125.00
rear mag wheels, standard pressure, 55.9 cm (22 in.) or 61.0 cm (24 in.)		
pair	78.00	
each	70.00	115.00
rear mag wheels, solid tires, 30.5 cm (12 in.)		
pair	40.00	
each		96.00
rear mag wheels, solid tires, 55.9 cm (22 in.) or 61.0 cm (24 in.)	79.00	
pair each	78.00	115.00
rear mag wheels, solid tires, 50.8 cm (20 in.)		113.00
pair	98.00	
each		125.00
spoked rear wheels, standard pressure, 50.8 cm (20 in.)		
pair	98.00	125.00
each		125.00
spoked rear wheels, standard pressure, 55.9 cm (22 in.) pair	78.00	
each	76.00	115.00
spoked rear wheels, standard pressure, 61.0 cm (24 in.)		110.00
pair	78.00	
each		115.00
spoked rear wheels, solid tires, 50.8 cm (20 in.)	00.00	
pair each	98.00	125.00
spoked rear wheels, solid tires, 55.9 cm (22 in.)		123.00
pair	78.00	
each	,	115.00
spoked rear wheels, solid tires, 61.0 cm (24 in.)		
pair	78.00	44-7-05
each		115.00
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)	N/C	25.00
front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)	N/C	35.00
pair	60.00	
each		65.00
front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)		
or 20.3 cm (8 in.) x 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)	40.0-	
pair	40.00	55.00
each front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)		55.00
pair	60.00	
each	00.00	65.00
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 17.8 cm (7 in.	)	
or 15.2 cm (6 in.) x 2.5 cm (1 in.)		
pair	40.00	
each		55.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Component(s) under Special Consideration		
quick-release axles*	98.00	
pair each	98.00	55.00
reclining back with cylinder*	280.00	280.00
spoke guards* pair	90.00	
each	70.00	45.00

#### DEVICE FROM: PRODUCT DESIGN GROUP INC.

**PRICE** 

# POSITIONING BASE, ADULT, "STELLAR" MODEL

\$1 746.14

#### **Basic Component(s)**

### **Body support system**

- seat height: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- seat widths: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.)
- seat depths: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.)
- back height: from 45.7 cm (18 in.) to 58.4 cm (23 in.)
- rocker device for seat and back
- · push handles
- safety belt, auto-type

#### Armrests

- "T"-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 40.6 cm (16 in.), short, long
- "L"-type armrests, short, long
- · contoured armrest pads, short, long

- 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 33.0 cm (13 in.) to 48.3 cm (19 in.)
- · padded calfrests
- heel loops, length-adjustable
- folding footplates, standard
- modification of length of footrests or legrests by + 5.1 cm (2 in.)

- standard wheel locks, push-to-lock, pull-to-lock
- standard forks, short forks
- · threaded axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.),
   40.6 cm (16 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 30.5 cm (12 in.), 40.6 cm (16 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 12.7 cm (5 in.)
- · anti-tip rollers
- anodized aluminum handrims

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
rigid seat, flat	36.00	36.00
rocker device for seat and back	N/C	N/A
push handles	N/C	84.00
headrest bracket, fixed, universal	12.00	12.00
headrest extension, 25.4 cm (10 in.) high	60.00	60.00
attendant and user-controlled tilt	32.64	32.64
modification of seat width to 53.3 cm (21 in.) or to 55.9 cm (22 in.)		N/A
modification of seat depth to 53.3 cm (21 in.) or to 55.9 cm (22 in.)		96.00
safety belt, four-point	53.28	72.48
safety belt, auto-type	N/C	19.20
supple back, nylon	60.00	60.00
Armrests: "L"-type armrests, short, long	N/C	82.56
"T"-type armrests, short, long "T"-type armrests, detachable, height-adjustable,	11/0	02.30
from 25.4 cm (10 in.) to 40.6 cm (16 in.), short, long	N/C	82.56
contoured armrest pads, long	N/C	9.60
contoured armrest pads, short	N/C	8.64
modification of armrest height by + 7.6 cm (3 in.)	23.52	23.52

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
60° or 70 footrests, parallel, detachable, swingaway,		
length-adjustable from 33.0 cm (13 in.) to 48.3 cm (19 in.)	N/C	70.80
70° footrests, inward-pointing, detachable, swingaway,		
length-adjustable from 33.0 cm (13 in.) to 48.3 cm (19 in.)		
pair	14.40	
each		78.00
elevating legrests, detachable, swingaway, length-adjustable		
pair	170.40	
each		156.00
elevating legrests, compensating mechanism, detachable,		
swingaway, length-adjustable		
pair	213.60	
each		177.60
modification of length of footrests or legrests by + 5.1 cm (2 in.)	N/C	30.24
padded calfrests	N/C	19.20
single calf strap	23.52	23.52
folding footplates, standard	N/C	17.28
folding footplates, oversized		
pair	57.60	
each		46.08
oversized footplates, angle-adjustable and depth-adjustable		
pair	74.40	
each		54.48
heel loops, length-adjustable	N/C	11.28
Wheels and frame		
Types of drive systems:		
anodized aluminum handrims	N/C	16.32
plastic-coated handrims		
pair	113.28	
each	2710	41.80
anti-tip rollers	N/C	31.20
Wheel locks:		
standard, push-to-lock or pull-to-lock	N/C	42.24
wheel lock extensions		
pair	28.80	
each		14.40
Types of forks:		
standard forks	N/C	30.24
short forks	N/C	77.76
Rear axles:		
threaded axles	N/C	1.00
inicaucu axics	11/C	1.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
rear mag wheels, standard pressure, 40.6 cm (16 in),		
50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	114.72
rear mag wheels, standard pressure, 30.5 cm (12 in.)	N/C	68.64
rear mag wheels, solid tires, 30.5 cm (12 in.)	N/C	70.56
rear mag wheels, solid tires, 61.0 cm (24 in.)	N/C	104.16
rear mag wheels, solid tires, 40.6 cm (16 in.), 50.8 cm (20 in.),		
55.9 cm (22 in.)	N/C	96.48
front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)	N/C	29.28
front wheels, solid tires, 12.7 cm (5 in.)	N/C	15.84
front wheels, solid tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
pair	60.00	
each		59.28
Component(s) under Special Consideration		
reclining back*	384.00	384.00
quick-release axles*	20.76	
pair	29.76	15.04
each		15.84

# DEVICE FROM: ADVANCED MOBILITY SYSTEMS CORPORATION

**PRICE** 

# POSITIONING BASE, ADULT, "TCR" MODEL

\$1 922.00

# **Basic Component(s)**

# **Body support system**

- seat height: from 38.1 cm (15 in.) to 44.5 cm  $(17^{1}/_{2} in.)$
- seat widths: 35.6 cm (14 in.), 40.6 cm (16 in.), 45.7 cm (18 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- seat depth: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- back height: from 45.7 cm (18 in.) to 61.0 cm (24 in.)
- rocker device for seat and back
- · push handles
- safety belt, auto-type, velcro-type
- · rig seat, flat
- · rigid seat, contoured
- rigid back
- seat cushion, flat, foam, 5.1 cm (2 in.)
- angle-adjustable back
- · headrest with bracket

#### Armrests

- "T"-type armrests, detachable, height-adjustable from 20.3 cm (8 in.) to 35.6 cm (14 in.), long, with straight armrest pads
- rigid clothing guards
- · armrest adjustment collars

#### **Footrests**

- 70° footrests, detachable, swingaway, length-adjustable from 41.9 cm (16<sup>1</sup>/<sub>2</sub> in.) to 57.2 cm (22<sup>1</sup>/<sub>2</sub> in.)
- folding footplates, standard, with adjustable heel loops
- folding footplates, angle-adjustable, with adjustable heel loops

- plastic-coated handrims
- standard wheel locks, push-to-lock
- standard forks, short forks
- · threaded axles
- rear mag wheels, solid tires, 40.6 cm (16 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.), 12.7 cm (5 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)
- · anti-tip rollers
- extended-range caster headtube mountings
- front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$  in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
headrest with bracket	N/C	206.00
rigid seat, flat	N/C	99.25
rigid seat, contoured	N/C	126.00
rocker device for seat and back	N/C	117.00
safety belt, velcro-type	N/C	37.80
safety belt, auto-type	N/C	45.00
seat cushion, flat, foam, 5.1 cm (2 in.)	N/C	99.00
angle-adjustable back	N/C N/C	123.00 165.40
rigid back push handles	N/C N/C	105.40 N/A
Armrests:	TVC	14/1
"T"-type armrests, detachable, height-adjustable from 20.3 cm (8 in.) to 35.6 cm (14 in.), long, with straight armrest pads "T"-type armrests, detachable, height-adjustable from 20.3 cm (8 in.) to 35.6 cm (14 in.), short, with straight armrest pads	N/C	72.00
pair	75.60	
each	75.00	109.80
armrest adjustment collars	N/C	15.00
rigid clothing guards	N/C	22.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
70° footrests, detachable, swingaway, length-adjustable from 41.9 cm (16 <sup>1</sup> / <sub>2</sub> in.) to 57.2 cm (22 <sup>1</sup> / <sub>2</sub> in.)	N/C	83.00
elevating legrests, compensating mechanism, with calfrests	145.00	
each	113.00	155.50
ingle calf strap	45.10	45.10
louble calf strap	51.40	51.40
olding footplates, standard, with adjustable heel loops	N/C	21.00
olding footplates, angle-adjustable with adjustable heel loops	N/C	21.00
Wheels and frame		
Types of drive systems:		
plastic-coated handrims	N/C	N/A
anti-tip rollers	N/C	36.00
Wheel locks:		
tandard wheel locks, push-to-lock wheel lock extensions	N/C	43.00
vneer lock extensions pair	102.00	
ach	102.00	51.00
Types of forks:		
tandard or short forks	N/C	37.00
extended-range caster headtube mountings	N/C	37.00
Atchded-range easter headtube mountings	TVC	37.00
Rear axles: hreaded axles	N/C	N/A
ill caucu axies	N/C	IVA
Types of wheels:		
ear mag wheels, solid tires, 40.6 cm (16 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)	N/C	126.00
	N/C	120.00
ear mag wheels, semi-pneumatic tires, 15.2 cm (6 in.)	N/C	47.00
r 12.7 cm (5 in.) x 3.2 cm ( $1^{1}/_{4}$ in.) ront wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)	N/C N/C	47.00 47.00
ont wheels, solid tires, 20.5 cm (8 in.) x 5.2 cm (174 in.)	N/C	47.00
Component(s) under Special Consideration		
uick-release axles*		
air	100.00	
ach		50.00

#### DEVICE FROM: INVACARE CANADA INC.

#### **PRICE**

# POSITIONING BASE, CHILD, "SOLARA JR" MODEL

\$1 713.00

## **Basic Component(s)**

#### **Body support system**

- seat height: from 42.5 cm  $(16^{3}/_{4} \text{ in.})$  to 48.9 cm  $(19^{1}/_{4} \text{ in.})$
- seat widths: 25.4 cm (10 in.), 27.9 cm (11 in.), 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.)
- seat depth: from 30.5 cm (12 in.) to 40.6 cm (16 in.)
- back heights: 50.8 cm (20 in.), 61.0 cm (24 in.)
- rocker device for seat and back, from  $-10^{\circ}$  to  $+45^{\circ}$
- · push handles
- push handle, angle-adjustable
- safety belt, velcro-type, auto-type
- supple back, nylon
- supple back, nylon, reclining
- basic growth kit (once only during first three years from date of purchase, for first user)
- folding back, angle-adjustable

#### **Armrests**

- "T"-type armrests, detachable, height-adjustable from 15.2 cm (6 in.) to 25.4 cm (10 in.), from 20.3 cm (8 in.) to 35.6 cm (14 in.), short, long
- "U"-type armrests, fixed height, from 21.6 cm (8½ in.) to 31.8 cm (12½ in.), short, long
- "U"-type armrests, detachable, height-adjustable from 21.6 cm (8½ in.) to 31.8 cm (12½ in.), short, long
- "I"-type armrests, height-adjustable from 17.8 cm (7 in.) to 30.5 cm (12 in.), short, long
- straight armrest pads, short, long

#### **Footrests**

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13<sup>1</sup>/<sub>2</sub> in.) to 44.5 cm (17<sup>1</sup>/<sub>2</sub> in.)
- 70° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13<sup>1</sup>/<sub>2</sub> in) to 41.9 cm (16<sup>1</sup>/<sub>2</sub> in.)
- 90° footrests, parallel, detachable, swingaway, length-adjustable from 6.4 cm (2¹/₂ in.) to 23.5 cm (9¹/₄ in.)
- heel loops, non-adjustable
- heel loops, length-adjustable
- folding footplates, standard
- 60° footrests, MFX, detachable, swingaway, length-adjustable from 22.9 cm (9 in.) to 31.8 cm (12<sup>1</sup>/<sub>2</sub> in.)
- 70° footrests, MFX, detachable, swingaway, length-adjustable from 14.6 cm (5<sup>3</sup>/<sub>4</sub> in.) to 29.8 cm (11<sup>3</sup>/<sub>4</sub> in.)

- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock
- standard forks
- quick-release axles
- threaded axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- anti-tip rollers
- frame length: 73.7 cm (29 in.), 81.3 cm (32 in.), 86.4 cm (34 in.)
- front wheels, inner tubes, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$  in.)

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
rigid seat, flat	49.00	95.00
cocker device for seat and back, from $-10^{\circ}$ to $+45^{\circ}$	N/C	N/A
oush handles	N/C	38.00
oush handles, angle-adjustable	N/C	N/A
safety belt, velcro-type	N/C	50.00
afety belt, auto-type	N/C	40.00
eat cushion, flat, foam, 5.1 cm (2 in.)	56.00	56.00
eat cushion, flat, foam, 7.6 cm (3 in.)	56.00	56.00
upple back, nylon	N/C	50.00
upple back, nylon, reclining	N/C	75.00
pasic growth kit (once only during first three years from date		
of purchase, for first user)	N/C	N/A
folding back, angle-adjustable	N/C	N/A
Armrests:	,	
'U"-type armrests, detachable, height-adjustable from 21.6 cm (8½ i		00.00
o 31.8 cm $(12^{1}/_{2} \text{ in.})$ , short or long	N/C	98.00
'U"-type armrests, fixed height, from 21.6 cm ( $8^{1}/_{2}$ in.)	N/C	66.00
o 31.8 cm (12½ in.), short or long		00.00
T"-type armrests, detachable, height-adjustable from 15.2 cm (6 in	1.)	
o 25.4 cm (10 in.), from 20.3 cm (8 in.) to 35.6 cm (14 in.), short or long	N/C	125.00
	N/C	123.00
'I"-type armrests, height-adjustable from 17.8 cm (7 in.)	N/C	98.00
o 30.5 cm (12 in.), short or long	N/C N/C	98.00 26.00
straight armrest pads, long		
straight armrest pads, short	N/C	26.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
60° footrests, parallel, detachable, swingaway, length-adjustable		
from 34.3 cm ( $13^{1}/_{2}$ in.) to 44.5 cm ( $17^{1}/_{2}$ in.)	N/C	81.00
70° footrests, parallel, detachable, swingaway, length-adjustable		
from 34.3 cm $(13^{1}/_{2} \text{ in.})$ to 41.9 cm $(16^{1}/_{2} \text{ in.})$	N/C	81.00
90° footrests, parallel, detachable, swingaway, length-adjustable		
from 6.4 cm $(2^{1}/_{2} \text{ in.})$ to 23.5 cm $(9^{1}/_{4} \text{ in.})$	N/C	135.00
60° footrests, MFX, detachable, swingaway, length-adjustable		
from 22.9 cm (9 in.) to 31.8 cm $(12^{1}/_{2} in.)$	N/C	153.00
70° footrests, MFX, detachable, swingaway, length-adjustable		
from 14.6 cm (5 $^{3}$ / <sub>4</sub> in.) to 29.8 cm (11 $^{3}$ / <sub>4</sub> in.)	N/C	153.00
70° footrests, tapered, detachable, swingaway, length-adjustable		
from 32.4 cm ( $12^{3}/_{4}$ in.) to 41.3 cm ( $16^{1}/_{4}$ in.)	107.00	
pair	107.00	125.00
each	22.00	135.00 34.00
single calf strap double calf strap	35.00	52.00
folding footplates, standard	33.00 N/C	40.00
Folding footplates, standard Solding footplates, angle-adjustable and depth-adjustable	14/6	40.00
oding rootplates, angle adjustable and depth adjustable	72.00	
each	72.00	76.00
neel loops, non-adjustable	N/C	5.00
neel loops, length-adjustable	N/C	12.00
neel loops and ankle straps		
pair	32.00	
each		16.00
Wheels and frame		
Types of drive systems:		
anodized aluminum handrims, 50.8 cm (20 in.),		
55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	34.00
plastic-coated handrims		
pair	52.00	60.00
each		60.00
nandrims with oblique or vertical projections	155.00	
oair each	155.00	112.00
each anti-tip rollers	N/C	48.00
Frame length: 73.7 cm (29 in.), 81.3 cm (32 in.) or 86.4 cm (34 in.)		400.00
	1.,0	100.00
Wheel locks:		
standard wheel locks, push-to-lock	N/C	44.00
wheel lock extensions	22.00	
oair	32.00	16.00
each		16.00
Types of forks:		
standard forks	N/C	50.00

**PRICE** 

\$1 665.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Rear axles:		
threaded axles	N/C	16.00
quick-release axles	N/C	53.00
Types of wheels:		
rear mag wheels, standard pressure, 30.5 cm (12 in.)	N/C	71.00
rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	90.00
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)	TV/C	70.00
or 61.0 cm (24 in.)	N/C	90.00
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.),		
12.7 cm (5 in.), 15.2 cm (6 in.)	N/C	40.00
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.) front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)	N/C	52.00
pair	48.00	
each		64.00
Component(s) under Special Consideration		
contracture footrest, bilateral-angle adjustable*	176.00	265.00
reclining back*	496.00	776.00
DEVICE FROM: SUNRISE MEDICAL CANADA INC.		

# Basic Component(s)

# **Body support system**

- · back tension bar on folding base
- folding back, angle-adjustable
- back heights: 54.6 cm (21<sup>1</sup>/<sub>2</sub> in.), 62.2 cm (24<sup>1</sup>/<sub>2</sub> in.), 69.9 cm (27<sup>1</sup>/<sub>2</sub> in.), with push handles

POSITIONING BASE, CHILD, "ZIPPIE TS" MODEL

- seat width: from 25.4 cm (10 in.) to 40.6 cm (16 in.)
- seat depth: from 33.0 cm (13 in.) to 50.8 cm (20 in.)
- front seat height: from 40.6 cm (16 in.) to 51.4 cm (20<sup>1</sup>/<sub>4</sub> in.)
- safety belt, velcro-type, auto-type
- · raised push handle

#### Armrests

- "T"-type armrests, detachable, height-adjustable from 23.5 cm (9<sup>1</sup>/<sub>4</sub> in.) to 40.0 cm (15<sup>3</sup>/<sub>4</sub> in.), short, long
- "T"-type armrests, detachable, height-adjustable from 14.0 cm (5<sup>1</sup>/<sub>2</sub> in.), 16.5 cm (6<sup>1</sup>/<sub>2</sub> in.), 19.1 cm (7<sup>1</sup>/<sub>2</sub> in.), short
- · straight armrest pads, short, long
- tubular armrest pads

#### **Footrests**

- 60°, 70° footrests, detachable, swingaway, length-adjustable from 31.1 cm (12¹/₄ in.) to 50.2 cm (19³/₄ in.)
- 70°, 80°, 90° footrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- 70°, 80°, 90° footrests, heavy-duty, detachable, non-flip-back
- heel loops, length-adjustable
- folding footplates, standard
- padded calfrests

- anti-tip rollers
- anodized aluminum handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- standard forks 15.2 cm (6 in.); short forks, 13.3 cm (5<sup>1</sup>/<sub>4</sub> in.); high forks 17.8 cm (7 in.), compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- 17.8 cm (7 in.) forks for 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- fork stems, + 1.9 cm ( $^{3}/_{4}$  in.), + 3.8 cm ( $^{1}/_{2}$  in.)
- quick-release axles
- · standard axle plate
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.), 15.2 cm (6 in.) x 3.2 cm (1<sup>1</sup>/<sub>4</sub> in.)
- rocker device, 45°

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back:		
headrest, small	90.00	93.00
headrest, medium	96.00	103.00
headrest, large	102.00	107.00
articulated headrest mounting	154.00	168.00
transversal bar for headrest mounting, fixed frame	194.00	206.00
transversal bar for headrest mounting, folding frame	226.00	242.00
back tension bar on folding base	N/C	185.00
folding back, angle-adjustable	N/C	N/A
rigid seat, flat	121.00	126.00
raised push handle	N/C	N/A
back heights: $54.6 \text{ cm} (21^{1}/_{2} \text{ in.}), 62.2 \text{ cm} (24^{1}/_{2} \text{ in.}),$		
$69.9 \text{ cm } (27^{1}/_{2} \text{ in.}), \text{ with push handles}$	N/C	N/A
safety belt, velcro-type	N/C	28.00
safety belt, auto-type	N/C	41.00
safety belt, airplane-type	49.00	77.00
safety belt, airplane-type, padded	74.00	101.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Armrests:		
"T"-type armrests, detachable, height-adjustable from 23.5 cm (9 <sup>1</sup> / <sub>4</sub> in.) to 40.0 cm (15 <sup>3</sup> / <sub>4</sub> in.), short or long "T"-type armrests, detachable, height-adjustable, 14.0 cm (5 <sup>1</sup> / <sub>2</sub> in.)	N/C	132.00
16.5 cm ( $6^{1}/_{2}$ in.), 19.1 cm ( $7^{1}/_{2}$ in.), short "I"-type armrests, flip-back, height-adjustable from 16.5 cm ( $6^{1}/_{2}$ in.) to 33.0 cm (13 in.), short or long	, N/C	155.00
pair	126.00	
each	120.00	195.00
tubular armrest pads	N/C	2.00
straight armrest pads, long	N/C	17.00
straight armrest pads short	N/C	15.00
rigid clothing guards	11/C	13.00
pair	90.00	
each	70.00	66.00
Footrests:		
60° or 70° footrests, detachable, swingaway, length-adjustable		
from 31.1 cm (12 <sup>1</sup> / <sub>4</sub> in.) to 50.2 cm (19 <sup>3</sup> / <sub>4</sub> in.) 70°, 80° or 90° footrests, detachable, swingaway, length-adjustable	N/C	53.00
from 20.3 cm (8 in.) to 33.0 cm (13 in.)	N/C	55.00
70°, 80° or 90° footrests, heavy-duty, detachable, non-flip-back 90° elevating legrests, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)	N/C	80.00
pair	69.00	
each	09.00	87.00
elevating legrests, detachable, swingaway, length-adjustable		67.00
pair	105.00	
each	105.00	105.50
modification of footrest length from 48.3 cm (19 in.)		103.50
to 52.1 cm $(20^{1}/_{2} \text{ in.})$	30.00	29.00
modification of footrest length by + 5.1 cm (2 in.)	20.00	27.00
or by +10.2 cm (4 in.)	30.00	15.00
single calf strap	18.00	18.00
folding footplates, standard	N/C	48.00
folding footplates, angle-adjustable, standard		
pair	51.00	
each		73.50
full-width footplate, angle-adjustable	83.00	179.00
full-width footplate, 90°, rigid	89.00	185.00
Footrest mountings, from 17.8 cm (7 in.) to 34.3 cm $(13^{1}/_{2} in.)$		
pair	54.00	
each		33.00
neel loops, length-adjustable	N/C	10.00
padded calfrests	N/C	18.00
contoured calfrests	<b>5</b> 0.63	
pair	70.00	<b>50.00</b>
each		53.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheels and frame		
Types of drive systems:		
one-arm dual handrim drive nodized aluminum handrims, 50.8 cm (20 in.),	546.00	688.00
5.9 cm (22 in.) or 61.0 cm (24 in.)	N/C	58.00
andrims with oblique or vertical projections air	88.00	
ach		102.00
lastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.) r 61.0 cm (24 in.)		
air ach	54.00	85.00
on-slip handrims, 55.9 cm (22 in.) or 61.0 cm (24 in.)		83.00
air ach	164.00	140.00
lastic-coated handrims for one-arm drive	54.00	N/A
nti-tip rollers	N/C	22.00
ont anti-tippers air	55.00	
ach		27.50
ane holder	44.00	44.00
ptional folding base ocker device, 45°	105.00 N/C	N/A N/A
Wheel locks:		
tandard, push-to-lock or pull-to-lock /heel lock extensions	N/C	39.00
air	26.00	
ach nti-rollback brakes		13.00
air	66.00	
ach		33.00
Types of forks:		
tandard forks, 15.2 cm (6 in.); short forks, 13.3 cm ( $5^{1/4}$ in.); or high forks 17.8 cm (7 in.), compatible with 12.7 cm (5 in.),		
5.2 cm (6 in.) and 20.3 cm (8 in.) wheels	N/C	31.00
7.8 cm (7 in.) forks for 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels ork-locking mechanisms	N/C	36.00
air	44.00	
ach ork stems, $+ 1.9 \text{ cm} (\frac{3}{4} \text{ in.}) \text{ or } + 3.8 \text{ cm} (\frac{1}{2} \text{ in.})$	N/C	22.00 16.00
	100	10.00
Rear axles: uick-release axles	N/C	32.50
xle extension plates		32.33
air ach	44.00	50.00
tandard axle plate	N/C	28.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Types of wheels:		
rear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C	132.00
rear mag wheels, standard pressure, 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	110.00
rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.)		
or 61.0 cm (24 in.)	N/C	132.00
rear mag wheels, standard pressure, 30.5 cm (12 in.)	N/C	126.00
rear mag wheels, standard pressure, 40.6 cm (16 in.)		
pair	32.00	
each		142.00
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)	N/C	61.00
front wheels, solid tires, 15.2 cm (6 in.)	N/C	60.00
front wheels, solid tires, 12.7 cm (5 in.)	N/C	46.00
front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.)		
pair	47.00	
each		69.50
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm ( $1^{1}/_{4}$ in.)	N/C	61.00
front wheels, inner tube, 15.2 cm (6 in.) x 3.2 cm ( $1\frac{1}{4}$ in.)	N/C	60.00
front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm (1½ i	n.)	
or 15.2 cm (6 in.) $\times$ 3.8 cm (1½ in.)	,	
pair	80.00	
each		86.00
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1 <sup>1</sup> / <sub>2</sub> i	n.)	
pair	100.00	
each		96.00

# DEVICE FROM: LES ÉQUIPEMENTS ADAPTÉS PHYSIPRO INC.

**PRICE** 

# POSITIONING BASE, CHILD, "ROSSIGNOL" MODEL

\$1 585.00

# **Basic Component(s)**

## **Body support system**

- folding back, angle-adjustable, height of 43.2 cm (17 in.) to 55.9 cm (22 in.)
- seat structure, width-adjustable from 30.5 cm (12 in.) to 40.6 cm (16 in.) and depth-adjustable from 26.7 cm (10<sup>1</sup>/<sub>2</sub> in.) to 40.6 cm (16 in.)
- rocker device for seat and back, from  $-10^{\circ}$  to  $+35^{\circ}$
- seat height: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- push handles
- safety belt, velcro-type, auto-type

#### Armrests

- "T"-type armrests, detachable, flip-back, height-adjustable from 19.1 cm (7<sup>1</sup>/<sub>2</sub> in.) to 29.2 cm (11<sup>1</sup>/<sub>2</sub> in.), short, or height-adjustable from 29.2 cm (11<sup>1</sup>/<sub>2</sub> in.) to 39.4 cm (15<sup>1</sup>/<sub>2</sub> in.), long
- straight armrest pads, short, long
- · rigid clothing guards

## **Footrests**

- 60°, 70°, 75°, 90° footrests, detachable, swingaway, length-adjustable from 14.0 cm (5½ in.) to 31.8 cm (12½ in.)
- heel loops, length-adjustable
- folding footplates, standard
- · padded calfrests

- · standard wheel locks, push-to-lock
- · standard forks
- · threaded axles
- rear mag wheels, standard pressure, 30.5 cm (12 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.), 12.7 cm (5 in.)
- · anti-tip rollers
- tie-down points for adapted transport
- smooth handrims for 50.8 cm (20 in.) and 55.9 cm (22 in.) wheels

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Basic and Optional Component(s)		
Body support system		
Seat and back: folding back, angle-adjustable, height of 43.2 cm (17 in.) to 55.9 cm (22 in.) push handles safety belt, velcro-type safety belt, auto-type rocker device for seat and back, from – 10° to + 35° rigid seat, flat rigid back headrest, small, medium, large headrest bracket crossbar for headrest bracket back tension bar basic growth kit	N/C N/C N/C N/C N/C 92.00 92.00 95.00 135.00 210.00 118.00 78.00	N/A N/A 18.00 48.00 N/A 92.00 92.00 95.00 135.00 210.00 118.00 78.00
<b>Armrests:</b> "T"-type armrests, detachable, flip-back, height-adjustable from 19.1 cm $(7^{1}/_{2} \text{ in.})$ to 29.2 cm $(11^{1}/_{2} \text{ in.})$ , short, or height-adjustable from 29.2 cm $(11^{1}/_{2} \text{ in.})$ to 39.4 cm $(15^{1}/_{2} \text{ in.})$ , long straight armrest pads, short straight armrest pads, long rigid clothing guards	N/C N/C N/C N/C	186.00 26.00 28.00 14.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Footrests:		
60°, 70°, 75° or 90° footrests, detachable, swingaway,		
length-adjustable from 14.0 cm ( $5^{1}/_{2}$ in.) to 31.8 cm ( $12^{1}/_{2}$ in.)	N/C	99.00
elevating legrests, detachable, swingaway, length-adjustable		
pair	376.30	
each		287.30
padded calfrests	N/C	30.00
contoured calfrests		
pair	36.00	
each		48.00
single calf strap	43.00	43.00
double calf strap	55.00	55.00
single calf strap, cushioned	80.00	80.00
double calf strap, cushioned	95.00	95.00
'H-" shaped calf strap	45.00	45.00
front impact guard with roller	80.00	40.00
folding footplates, standard	N/C	40.00
folding footplates, angle-adjustable and depth-adjustable, non-skid		
pair	70.00	
each		75.00
folding footplates, oversized, angle-adjustable and		
depth-adjustable, non-skid		
pair	100.00	
each		90.00
folding footplate, full-width, angle-adjustable and		
depth-adjustable, non-skid	140.00	110.00
neel loops, length-adjustable	N/C	12.00
oe loops		
pair	20.00	
each		22.00
Wheels and frame		
Types of drive systems:		
smooth handrims for 50.8 cm (20 in.) and 55.9 cm (22 in.) wheels	N/C	45.30
plastic-coated handrims		
pair	60.00	
each		75.00
non-slip handrims		
pair	70.00	
each		80.00
nandrims with vertical, oblique or horizontal projections		
pair	158.00	
each		124.00
anti-tip rollers	N/C	43.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
Wheel locks:		
standard, push-to-lock wheel lock extensions	N/C	55.00
pair each	30.00	15.00
anti-rollback brakes		13.00
pair each	104.00	52.00
Types of forks:		
standard forks	N/C	56.00
Rear axles: threaded axles	N/C	6.00
plates with hardware for 50.8 cm (20 in.) and 55.9 cm (22 in.) wheels	156.00	78.00
Frame:		
tie-down points for adapted transport	N/C	N/A
heavy-duty frame	180.00	N/A
Types of wheels:	NIC	76.00
rear mag wheels, standard pressure, 30.5 cm (12 in.) rear mag wheels, standard pressure, 50.8 cm (20 in.)	N/C	76.00
pair	68.00	4.5.00
each		125.00
rear mag wheels, standard pressure, 55.9 cm (22 in.)	78.00	
pair each	78.00	115.00
rear mag wheels, solid tires, 50.8 cm (20 in.)		
pair each	98.00	125.00
rear mag wheels, solid tires, 30.5 cm (12 in.)		123.00
pair	40.00	06.00
each rear mag wheels, solid tires, 55.9 cm (22 in.)		96.00
pair	78.00	44.70-
each spoked rear wheels, standard pressure, 50.8 cm (20 in.)		115.00
pair	98.00	
each		125.00
spoked rear wheels, standard pressure, 55.9 cm (22 in.) pair	78.00	
each		115.00
spoked rear wheels, solid tires, 50.8 cm (20 in.) pair	98.00	
each	70.00	125.00
spoked rear wheels, solid tires, 55.9 cm (22 in.)	70.00	
pair each	78.00	115.00
front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.),		
15.2 cm (6 in.) or 12.7 cm (5 in.)	N/C	35.00

	Price upon initial purchase or replacement of wheel chair	Price upon replacement of component (unit price)
front wheels, inner tube, 20.3 cm (8 in.) x 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.)		
or 15.2 cm (6 in.) x 3.2 cm (1 <sup>1</sup> / <sub>4</sub> in.) pair	40.00	
each		55.00
front wheels, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.) pair	60.00	
each		65.00
front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) pair	60.00	
each	00.00	65.00
front wheels, semi-pneumatic tires, 15.2 cm (6 in.), 17.8 cm (7 in.)		
or 20.3 cm (8 in.) x 2.5 cm (1 in.) pair	40.00	
each		55.00
Component(s) under Special Consideration		
quick-release axles*		
pair	98.00	
each reclining back with cylinder*	280.00	55.00 280.00
spoke guards*	200.00	200.00
pair	90.00	45.00
each		45.00
DIVISION III STROLLERS		
DEVICE		PRICE
"Buggy Major"-type stroller, including footrests and harness less than three years of age* three years of age and over		600.00 600.00
Available Component(s)		
padded seat		90.00
other components		S.C.
thoracic support chest pad		96.00 48.00
DURATION OF GUARANTEE: 12 months		40.00
DEVICE		
Other strollers*		S.C.