Notice RAMQ 003-2005

Health Insurance Act (R.S.Q., c. A-29)

Devices which compensate for a physical deficiency — Amendments

MAKING by the Régie de l'assurance maladie du Québec of a Regulation to amend the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act, dated 11 May 2005

THE RÉGIE DE L'ASSURANCE MALADIE DU QUÉBEC,

CONSIDERING the fifth paragraph of section 3 and section 72.1 of the Health Insurance Act (R.S.Q., c. A-29);

CONSIDERING that it is necessary to amend certain lists of locomotor and posture assists contained in the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act;

GIVES NOTICE that, by Resolution CA-420-05-08 of the board of directors dated 11 May 2005, it has made the Regulation to amend the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act, the text of which appears below.

Québec, 11 May 2005

NORMAND JULIEN, Secretary General of the Régie de l'assurance maladie du Québec

Regulation to amend the Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act*

Health Insurance Act (R.S.Q., c. A-29, s. 3, 5th and 10th pars. and s. 72.1)

- **1.** The Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act is amended by replacing Divisions I, II and III of Part I of Chapter V of Title Two by the Divisions appearing in Schedule I to this Regulation.
- **2.** This Regulation comes into force on 1 June 2005.

^{*} The Regulation respecting devices which compensate for a physical deficiency and are insured under the Health Insurance Act, made by Order in Council 612-94 dated 27 April 1994 (1994, G.O. 2, 1589), was last amended by Resolutions CA-409-04-07 dated 14 April 2004 (2004, G.O. 2, 1360) and CA-419-05-06 dated 13 April 2005 (2005, G.O. 2, 1110) of the Régie de l'assurance maladie du Québec. For previous amendments, refer to the *Tableau des modifications et Index sommaire*, Éditeur officiel du Québec, 2005, updated to 1 March 2005.

SCHEDULE I

CHAPTER V

LISTS

LOCOMOTOR AND POSTURE ASSISTS

PART I

LOCOMOTOR ASSISTS

DIVISION I

WHEEL CHAIRS

§1. Manual wheel chairs

SUPPLIER: INVACARE CANADA INC.

PRICE

MANUAL WHEEL CHAIR PATRIOT MODEL

\$759.00

Basic Components

Body support system

- fixed back, height-adjustable from 38.1 cm (15 in.) to 48.3 cm (19 in.)
- seat heights: $39.4 \text{ cm} (15^{1}/_{2} \text{ in.}), 41.9 \text{ cm} (16^{1}/_{2} \text{ in.}), 44.5 \text{ cm} (17^{1}/_{2} \text{ in.}), 49.5 \text{ cm} (19^{1}/_{2} \text{ in.})$
- seat widths: 35.6 cm (14 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 50.8 cm (20 in.)
- seat depths: 40.6 cm (16 in.), 45.7 cm (18 in.)
- · supple seat and back, nylon
- safety belt, velcro-type, auto-type

Armrests

- U-type armrests, detachable, flip-back, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), from 20.3 cm (8 in.) to 25.4 cm (10 in.)
- armrest pads, straight, short, long
- armrest pads, tubular
- · clothing guards, flexible, rigid

Footrests

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.9 cm (13³/₄ in.) to 44.5 cm (17¹/₂ in.); 70° footrests, parallel, detachable, swingaway, length-adjustable from 31.8 cm (12¹/₂ in.) to 44.5 cm (17¹/₂ in.)
- · folding footplates, standard
- heel loops, fixed
- heel loops, adjustable
- · padded calfrests

Frame

- anti-tip rollers
- · push handles, integrated

- plastic-coated handrims, smooth
- standard wheel locks, push-to-lock, pull-to-lock
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)

- front wheels, solid tires, 15.2 cm (6 in.), 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.)
- standard forks
- threaded axles, quick-release

| Seat and back Supple back, tension-adjustable 80.00 133.00 N/A | | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|--|---|
| Seat and back: Supple back, tension-adjustable Supple back, tension-adjustable Supple back, tension-adjustable Supple back, tension-adjustable Supple back, nylon Supple back, nylon Supple back, nylon Supple seat, nylon Seat cushion, flat, foam, 5.1 cm (2 in.) Seat cushion, flat, foam, 7.6 cm (3 in.) Sact cushion, flat, foam, 7.6 cm (10 in.) Sact cushion, flat, float flat flat flat flat flat flat flat fl | Basic and Optional Components | | |
| Supple back, tension-adjustable modification of back height to $50.8 \text{ cm} (20 \text{ in.})$ 32.00 N/A supple back, nylon N/C 53.00 supple back, nylon N/C 63.00 supple seat, nylon N/C 63.00 seat cushion, flat, foam, $5.1 \text{ cm} (2 \text{ in.})$ 59.00 59.00 59.00 seat cushion, flat, foam, $7.6 \text{ cm} (3 \text{ in.})$ 59.00 59.00 safety belt, velcro-type N/C 42.00 safety belt, auto-type N/C 53.00 N/C 53.0 | Body support system | | |
| modification of back height to $50.8 \text{ cm} (20 \text{ in.})$ supple back, nylon supple back, nylon supple back, nylon supple back, nylon supple seat, nylon seat cushion, flat, foam, $5.1 \text{ cm} (2 \text{ in.})$ seat cushion, flat, foam, $5.1 \text{ cm} (2 \text{ in.})$ seat cushion, flat, foam, $7.6 \text{ cm} (3 \text{ in.})$ seat cushion, flat, foam, $7.6 \text{ cm} (3 \text{ in.})$ seat cushion, flat, foam, $7.6 \text{ cm} (3 \text{ in.})$ seat cushion, flat, foam, $7.6 \text{ cm} (3 \text{ in.})$ seat cushion, flat, foam, $7.6 \text{ cm} (3 \text{ in.})$ safety belt, velcro-type N/C safety belt, auto-type N/C Armrests: U-type armrests, detachable, flip-back, height-adjustable from 20.3 cm (8 in.) to $25.4 \text{ cm} (10 \text{ in.})$, from $25.4 \text{ cm} (10 \text{ in.})$ to $35.6 \text{ cm} (14 \text{ in.})$, short, long N/C 35.6 cm (14 in.), short, long N/C 36.0 cm (14 in.), short, long N/C 37.0 cm (14 in.), short, long N/C 38.0 cm (14 in.) N/C 38.0 cm | Seat and back: | | |
| supple back, nylon N/C 53.00 supple seat, nylon N/C 65.00 N/C 67.00 N/C 6 | Supple back, tension-adjustable | 80.00 | 133.00 |
| supple seat, nylon seat cushion, flat, foam, 5.1 cm (2 in.) 59.00 | modification of back height to 50.8 cm (20 in.) | 32.00 | N/A |
| sear cushion, flat, foam, 5.1 cm (2 in.) 59.00 59.00 59.00 seat cushion, flat, foam, 7.6 cm (3 in.) 59.00 5 | supple back, nylon | | 53.00 |
| seat cushion, flat, foam, 7.6 cm (3 in.) 59.00 59.00 safety belt, velcro-type N/C 42.00 safety belt, velcro-type N/C 53.00 N/C 54.00 N/C 54.00 N/C 55.00 N/C 56.00 N/C 56.00 N/C 56.00 N/C 56.00 N/C 56.00 N/C 56.00 N/C 57.00 N/C 57.0 | | | |
| safety belt, velcro-type N/C 42.00 safety belt, auto-type N/C 53.00 Armrests: U-type armrests, detachable, flip-back, height-adjustable from 20.3 cm (8 in.) to 25.4 cm (10 in.), from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long N/C 11.00 armrest pads, tubular N/C 11.00 armrest pads, straight, short N/C 26.00 clothing guards, flexible N/C 48.00 clothing guards, flexible N/C 48.00 Footrests: 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.9 cm $(13^{1/4}, in.)$ to 44.5 cm $(17^{1/2}, in.)$; 70° footrests, parallel, detachable, swingaway, length-adjustable from 31.8 cm $(12^{1/2}, in.)$ to 44.5 cm $(17^{1/2}, in.)$ 70° footrests, tapered, detachable, swingaway, length-adjustable from 37.5 cm $(14^{1/4}, in.)$ to 47.6 cm $(18^{1/4}, in.)$ 113.00 170.00 elevating legrests, length-adjustable from 36.2 cm $(14^{1/4}, in.)$ to 51.4 cm $(20^{1/4}, in.)$ 244.00 236.00 elevating legrests with compensating mechanism 160.00 194.00 modification of elevating legrest height by -2.5 cm $(1$ in.) or by -5.1 cm $(2$ in.) 250.00 250.00 and double calf strap 25.00 37.00 double calf strap 38.00 55.00 folding footplates, angle-adjustable and depth-adjustable, standard footplates, angle-adjustable and depth-adjustable, standard or oversized, 18.4 cm $(7^{1/4}, in.)$ 76.00 80.00 | | | |
| safety belt, auto-type N/C 53.00 Armrests: U-type armrests, detachable, flip-back, height-adjustable from 20.3 cm (8 in.) to 25.4 cm (10 in.), from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long N/C 131.00 armrest pads, tubular N/C 11.00 armrest pads, straight, short N/C 26.00 armrest pads, straight, long N/C 26.00 clothing guards, flexible N/C 48.00 clothing guards, rigid N/C 48.00 N/C 48.00 N/C 48.00 N/C 48.00 N/C 48.00 N/C 48.00 N/C 49.00 N/C 40.00 N/C 40.00 N/C 40.00 50.00 N/C 40.00 50.00 N/C 40.00 50.00 50.00 N/C 40.00 50.00 50.00 50.00 N/C 40.00 50 | | | |
| Armrests: U-type armrests, detachable, flip-back, height-adjustable from 20.3 cm (8 in.) to 25.4 cm (10 in.), from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long N/C 11.00 armrest pads, tubular N/C 11.00 armrest pads, straight, short N/C 26.00 N/C 26.00 clothing guards, flexible N/C 48.00 clothing guards, rigid N/C 48.00 N/C N/C 48.00 N/C N/C N/C 48.00 N/C N/C N/C N/C A8.00 N/C | safety belt, velcro-type | | |
| U-type armrests, detachable, flip-back, height-adjustable from 20.3 cm (8 in.) to 25.4 cm (10 in.), from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long 36.6 cm (14 in.), short, long 37.6 cm (18.6 cm (17.0 cm)) $\frac{11.00}{11.00}$ armrest pads, straight, short $\frac{11.00}{11.00}$ $\frac{11.00}{11.00}$ armrest pads, straight, long $\frac{11.00}{11.00}$ $\frac{11.00}{11.00}$ $\frac{11.00}{11.00}$ armrest pads, straight, long $\frac{11.00}{11.00}$ 1 | safety belt, auto-type | N/C | 53.00 |
| 20.3 cm (8 in.) to 25.4 cm (10 in.), from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long armrest pads, tubular N/C 11.00 armrest pads, straight, short N/C 26.00 armrest pads, straight, long N/C 26.00 clothing guards, flexible N/C 48.00 clothing guards, rigid N/C 48.00 N/C 131.00 N/C 148.00 N/C 148.00 N/C 15.00 | Armrests: | | |
| 35.6 cm (14 in.), short, long armrest pads, tubular N/C 11.00 armrest pads, straight, short N/C 26.00 armrest pads, straight, short N/C 26.00 clothing guards, straight, long N/C 26.00 clothing guards, flexible N/C 48.00 N/C A8.00 N/C N/C A8.00 N/C N/C N/C A8.00 N/C N/C N/C A8.00 N/C | | | |
| armrest pads, tubular armrest pads, straight, short Armrest pads, straight, short Armrest pads, straight, long Clothing guards, flexible Clothing guards, rigid Footrests: $60^{\circ} \text{ footrests, parallel, detachable, swingaway, length-adjustable}} From 34.9 cm (13^{3}/_{4} \text{ in.}) to 44.5 cm (17^{1}/_{2} \text{ in.}); 70^{\circ} footrests, parallel, detachable, swingaway, length-adjustable from 31.8 cm (12^{1}/_{2} \text{ in.}) to 44.5 cm (17^{1}/_{2} \text{ in.}) 70^{\circ} footrests, tapered, detachable, swingaway, length-adjustable from 31.8 cm (12^{1}/_{2} \text{ in.}) 70^{\circ} footrests, tapered, detachable, swingaway, length-adjustable from 37.5 cm (14^{3}/_{4} \text{ in.}) to 47.6 cm (18^{3}/_{4} \text{ in.}) 113.00 170.00 170.00 elevating legrests, length-adjustable from 36.2 cm (14^{3}/_{4} \text{ in.}) 244.00 236.00 194.00 23$ | | N/C | 121.00 |
| armrest pads, straight, short 26.00 armrest pads, straight, long N/C 48.00 armrest pads, straight N/C 48.00 armrest pads, straight, long N/C 48.00 armrest pads, straight, long N/C 48.00 armrest pads, rigid N/C 48.00 armrest pads, rigid N/C 48.00 armrest pads, rigid N/C 48.00 armrest pads, straight, long levels, parallel, detachable, swingaway, length-adjustable from 31.8 cm $(12^{1}/_{2} \text{ in.})$ armrest pads, straight, long levels, swingaway, length-adjustable from 31.8 cm $(12^{1}/_{2} \text{ in.})$ armrest pads, straight, long levels, stangular, long levels, parallel, detachable, swingaway, length-adjustable from 31.8 cm $(12^{1}/_{2} \text{ in.})$ armrest pads, straight, long levels, parallel, detachable, swingaway, length-adjustable from 31.8 cm $(12^{1}/_{2} \text{ in.})$ armrest pads, straight, long levels, long length-adjustable from 31.8 cm $(12^{1}/_{2} \text{ in.})$ armrest pads, long levels, long length-adjustable from 31.8 cm $(12^{1}/_{2} \text{ in.})$ armrest pads, long levels, long length-adjustable from 31.8 cm $(12^{1}/_{2} \text{ in.})$ armrest pads, long levels, long length-adjustable from 31.8 cm $(12^{1}/_{2} \text{ in.})$ armrest pads, long levels, long length-adjustable, standard or long levels, long length-adjustable, standard or long length | | | |
| armrest pads, straight, long clothing guards, flexible N/C 48.00 clothing guards, rigid N/C 48.00 Footrests: $ 60^{\circ} \text{ footrests, parallel, detachable, swingaway, length-adjustable from 34.9 cm (13^{3}l_{4} \text{ in.}) to 44.5 \text{ cm } (17^{1}l_{2} \text{ in.}); 70^{\circ} footrests, parallel, detachable, swingaway, length-adjustable from 31.8 \text{ cm } (12^{1}l_{2} \text{ in.}) N/C 114.00 to 44.5 \text{ cm } (17^{1}l_{2} \text{ in.}) N/C 114.00 170.00 \text{ clevating legrests, length-adjustable from 36.2 cm } 113.00 170.00 \text{ clevating legrests with compensating mechanism 160.00 194.00 modification of elevating legrest height by -2.5 \text{ cm } (1 \text{ in.}) or by -5.1 \text{ cm } (2 \text{ in.}) 250.00 250.00 250.00 padded calfrests N/C 28.00 37.00 double calf strap 38.00 55.00 37.00 folding footplates, standard N/C 42.00 footplates, angle-adjustable and depth-adjustable, standard or oversized, 18.4 \text{ cm } (7^{1}l_{4} \text{ in.}) 76.00 80.00$ | | | |
| clothing guards, flexible clothing guards, rigid N/C 48.00 Footrests: $60^{\circ} \text{ footrests, parallel, detachable, swingaway, length-adjustable from 34.9 cm } (13^{3}/_{4} \text{ in.}) \text{ to } 44.5 \text{ cm } (17^{1}/_{2} \text{ in.}); 70^{\circ} \text{ footrests, parallel, detachable, swingaway, length-adjustable from 31.8 cm } (12^{1}/_{2} \text{ in.}) \text{ to } 44.5 \text{ cm } (17^{1}/_{2} \text{ in.}) \text{ to } 44.5 \text{ cm } (17^{1}/_{2} \text{ in.}) \text{ N/C} 114.00}$ $70^{\circ} \text{ footrests, tapered, detachable, swingaway, length-adjustable from 37.5 cm } (14^{3}/_{4} \text{ in.}) \text{ to } 47.6 \text{ cm } (18^{3}/_{4} \text{ in.}) \text{ to } 47.6 \text{ cm } (18^{3}/_{4} \text{ in.}) \text{ to } 51.4 \text{ cm } (20^{1}/_{4} \text{ in.}) \text{ to } 47.6 \text{ cm } (18^{3}/_{4} \text{ in.}) \text{ to } 51.4 \text{ cm } (20^{1}/_{4} \text{ in.}) \text{ to } 51.4 \text{ cm } (20^{1}/_{4} \text{ in.}) \text{ to } 244.00 \text{ 236.00} \text{ 194.00} \text{ 236.00} \text{ 194.00} \text{ 236.00} \text{ 194.00} \text{ 250.00} 2$ | | | |
| clothing guards, rigid N/C 48.00 Footrests: 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.9 cm $(13^{3}/_{4} \text{ in.})$ to 44.5 cm $(17^{1}/_{2} \text{ in.})$; 70° footrests, parallel, detachable, swingaway, length-adjustable from 31.8 cm $(12^{1}/_{2} \text{ in.})$ to 44.5 cm $(17^{1}/_{2} \text{ in.})$ N/C 114.00 70° footrests, tapered, detachable, swingaway, length-adjustable from 37.5 cm $(14^{3}/_{4} \text{ in.})$ to 47.6 cm $(18^{3}/_{4} \text{ in.})$ 113.00 170.00 elevating legrests, length-adjustable from 36.2 cm $(14^{3}/_{4} \text{ in.})$ 244.00 236.00 elevating legrests with compensating mechanism 160.00 194.00 modification of elevating legrest height by -2.5 cm (1 in.) or by -5.1 cm (2 in.) 250.00 250.00 250.00 250.00 clouble calf strap 38.00 37.00 folding footplates, standard N/C 42.00 footplates, angle-adjustable and depth-adjustable, standard or oversized, 18.4 cm $(7^{1}/_{4} \text{ in.})$ 76.00 80.00 | | | |
| 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.9 cm $(13^3/_4 \text{ in.})$ to 44.5 cm $(17^4/_2 \text{ in.})$; 70° footrests, parallel, detachable, swingaway, length-adjustable from 31.8 cm $(12^4/_2 \text{ in.})$ to 44.5 cm $(17^4/_2 \text{ in.})$ N/C 114.00 70° footrests, tapered, detachable, swingaway, length-adjustable from 37.5 cm $(14^3/_4 \text{ in.})$ to 47.6 cm $(18^3/_4 \text{ in.})$ 113.00 170.00 elevating legrests, length-adjustable from 36.2 cm $(14^3/_4 \text{ in.})$ 244.00 236.00 elevating legrests with compensating mechanism 160.00 194.00 modification of elevating legrest height by -2.5 cm (1 in.) or by -5.1 cm (2 in.) 250.00 250.00 250.00 padded calfrests N/C 28.00 37.00 double calf strap 38.00 55.00 folding footplates, standard N/C 42.00 footplates, angle-adjustable and depth-adjustable, standard or oversized, 18.4 cm $(7^4/_4 \text{ in.})$ 76.00 80.00 | clothing guards, rigid | , - | 48.00 |
| from 34.9 cm $(13^3/_4 \text{ in.})$ to 44.5 cm $(17^1/_2 \text{ in.})$; 70° footrests, parallel, detachable, swingaway, length-adjustable from 31.8 cm $(12^1/_2 \text{ in.})$ | Footrests: | | |
| to $44.5 \text{ cm } (17^{1}/_{2} \text{ in.})$ N/C 114.00 70° footrests, tapered, detachable, swingaway, length-adjustable from 37.5 cm $(14^{3}/_{4} \text{ in.})$ to $47.6 \text{ cm } (18^{3}/_{4} \text{ in.})$ to $51.4 \text{ cm } (20^{1}/_{4} \text{ in.})$ elevating legrests, length-adjustable from $36.2 \text{ cm } (14^{3}/_{4} \text{ in.})$ to $51.4 \text{ cm } (20^{1}/_{4} \text{ in.})$ 244.00 236.00 elevating legrests with compensating mechanism 160.00 194.00 modification of elevating legrest height by $-2.5 \text{ cm } (1 \text{ in.})$ or by $-5.1 \text{ cm } (2 \text{ in.})$ 250.00 250.00 padded calfrests N/C 28.00 37.00 double calf strap 38.00 55.00 folding footplates, standard footplates, angle-adjustable and depth-adjustable, standard or oversized, $18.4 \text{ cm } (7^{1}/_{4} \text{ in.})$ 76.00 80.00 | | el, | |
| from $37.5 \text{ cm} (14^3/_4 \text{ in.})$ to $47.6 \text{ cm} (18^3/_4 \text{ in.})$ 113.00 170.00 elevating legrests, length-adjustable from $36.2 \text{ cm} (14^3/_4 \text{ in.})$ 244.00 236.00 elevating legrests with compensating mechanism 160.00 194.00 modification of elevating legrest height by $-2.5 \text{ cm} (1 \text{ in.})$ or by $-5.1 \text{ cm} (2 \text{ in.})$ 250.00 250.00 padded calfrests N/C 28.00 37.00 double calf strap 25.00 37.00 double calf strap 38.00 55.00 folding footplates, standard N/C 42.00 footplates, angle-adjustable and depth-adjustable, standard or oversized, $18.4 \text{ cm} (7^1/_4 \text{ in.})$ 76.00 80.00 | to $44.5 \text{ cm} (17^{1}/_{2} \text{ in.})$ | N/C | 114.00 |
| to $51.4 \text{ cm} (20)/_4 \text{ in.})$ 244.00 236.00 296.00 194.00 236.00 194.00 modification of elevating legrest height by $-2.5 \text{ cm} (1 \text{ in.})$ or by $-5.1 \text{ cm} (2 \text{ in.})$ 250.00 250.00 padded calfrests N/C 28.00 37.00 double calf strap 25.00 37.00 double calf strap 38.00 55.00 folding footplates, standard N/C 42.00 footplates, angle-adjustable and depth-adjustable, standard or oversized, $18.4 \text{ cm} (7)/_4 \text{ in.})$ 76.00 80.00 | from 37.5 cm $(14^3/_4 \text{ in.})$ to 47.6 cm $(18^3/_4 \text{ in.})$ | 113.00 | 170.00 |
| elevating legrests with compensating mechanism modification of elevating legrest height by $-2.5 \text{ cm } (1 \text{ in.})$ or by $-5.1 \text{ cm } (2 \text{ in.})$ padded calfrests N/C 28.00 37.00 double calf strap 38.00 folding footplates, standard footplates, angle-adjustable and depth-adjustable, standard or oversized, $18.4 \text{ cm } (7^{1}/_4 \text{ in.})$ 160.00 250.00 250.00 37.00 37.00 42.00 80.00 | | 244.00 | 236.00 |
| modification of elevating legrest height by $-2.5 \mathrm{cm} (1 \mathrm{in.})$ or by $-5.1 \mathrm{cm} (2 \mathrm{in.})$ 250.00 250.00 padded calfrests N/C 28.00 37.00 double calf strap 25.00 37.00 double calf strap 38.00 55.00 folding footplates, standard N/C 42.00 footplates, angle-adjustable and depth-adjustable, standard or oversized, $18.4 \mathrm{cm} (7^{1}/_4 \mathrm{in.})$ 76.00 80.00 | | | 194.00 |
| by $-5.1 \text{ cm } (2 \text{ in.})$ 250.00 250.00 250.00 padded calfrests N/C 28.00 37.00 37.00 double calf strap 25.00 37.00 55.00 50.00 55.00 55.00 55.00 50.00 55.00 | | | |
| padded calfrests N/C 28.00 single calf strap 25.00 37.00 double calf strap 38.00 55.00 folding footplates, standard N/C 42.00 footplates, angle-adjustable and depth-adjustable, standard or oversized, $18.4 \text{ cm} (7^{1}/_4 \text{ in.})$ 76.00 80.00 | | 250.00 | 250.00 |
| Single calf strap 25.00 37.00 double calf strap 38.00 55.00 38.00 55.00 folding footplates, standard 80.00 N/C 80.00 footplates, angle-adjustable and depth-adjustable, standard or oversized, 18.4 cm $(7^{1}/_{4}$ in.) 90.00 80.00 | | | 28.00 |
| Houble calf strap 38.00 55.00 folding footplates, standard N/C 42.00 footplates, angle-adjustable and depth-adjustable, standard or oversized, $18.4 \text{ cm} (7^{1}/_{4} \text{ in.})$ 76.00 80.00 | | 25.00 | 37.00 |
| Footplates, angle-adjustable and depth-adjustable, standard or oversized, $18.4 \text{ cm} (7\frac{1}{4} \text{ in.})$ 76.00 80.00 | | 38.00 | 55.00 |
| oversized, $18.4 \text{ cm} (7^{1}/_{4} \text{ in.})$ 76.00 80.00 | | N/C | 42.00 |
| | | 76.00 | 80.00 |
| | | | 65.00 |
| | | | 7.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| heel loops, adjustable heel loops and ankle strap | N/C 25.00 | 15.00 19.00 |
| Frame | | |
| anti-tip rollers | N/C | 50.00 |
| cane holder | 34.00 | 34.00 |
| push handles, integrated | N/C | 38.00 |
| Drive systems: | | |
| handrims with vertical or oblique projections | 155.00 | 125.00 |
| smooth handrims | N/C | 36.00 |
| plastic-coated handrims | N/C | 63.00 |
| Wheel locks: | | |
| standard wheel locks, push-to-lock | N/C | 46.00 |
| tandard wheel locks, pull-to-lock | N/C | 46.00 |
| vheel lock extensions | 34.00 | 17.00 |
| anti-rollback brakes | 94.00 | 93.00 |
| Wheels: | | |
| rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | 37/5 | 40.500 |
| 61.0 cm (24 in.) | N/C | 105.00 |
| ear mag wheels, standard pressure, 50.8 cm (20 in.), | | |
| 55.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 105.00 |
| Front wheels, solid tires, 15.2 cm (6 in.), | | |
| $20.3 \text{ cm } (8 \text{ in.}) \times 3.2 \text{ cm } (1^{1}/_{4} \text{ in.})$ | N/C | 40.00 |
| Front wheels, inner tube tires, 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.) | 30.00 | 55.00 |
| Forks: | NIC | 52.00 |
| standard forks | N/C | 52.00 |
| Rear axles: | | |
| hreaded axles | N/C | 15.00 |
| juick-release axles | N/C | 53.00 |
| plates for amputees | 52.00 | 26.00 |
| Component(s) under Special Consideration | | |
| spoke guards* | 94.00 | 47.00 |
| SUPPLIER: INVACARE CANADA INC. | | nnı |
| | | PRI |
| MANUAL WHEEL CHAIR MVP MODEL | | \$1 344 |

Body support system

- fixed back, height-adjustable from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- seat heights: $37.5 \text{ cm} (14^3/_4 \text{ in.})$, $54.0 \text{ cm} (21^1/_4 \text{ in.})$

- seat width: from 38.1 cm (15 in.) to 45.7 cm (18 in.)
- seat depth: from 33.0 cm (13 in.) to 45.7 cm (18 in.)
- supple seat and back, nylon
- safety belt, velcro-type, auto-type

Armrests

- L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 25.4 cm (10 in.), short
- U-type armrests, detachable, flip-back, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long
- · armrest pads, straight, short, long
- armrest pads, tubular
- · clothing guards, flexible, rigid

Footrests

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 37.5 cm (14³/₄ in.) to 47.6 cm (18³/₄ in.); 70° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 47.0 cm (18¹/₂ in.)
- · padded calfrests
- folding footplates, standard
- full-width footrest, tubular
- heel loops, fixed
- heel loops, adjustable

Frame

- anti-tip rollers
- backposts with push handles

- plastic-coated handrims, smooth
- standard wheel locks, push-to-lock, pull-to-lock
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, solid tires, 61.0 cm (24 in.), 66.0 cm (26 in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 7.6 cm (3 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, solid tires, 12.7 cm (5 in.) x 3.8 cm ($1^{1}/_{2}$ in.)
- front wheels, solid tires, 15.2 cm (6 in.) x 3.8 cm ($1^{1}/_{2}$ in.)
- standard forks, short
- threaded axles, quick-release

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| supple back, tension-adjustable | 80.00 | 133.00 |
| rigid seat, flat, lowered | 128.00 | 191.00 |
| modification of seat depth to 48.3 cm (19 in.), 50.8 cm (20 in.), | | |
| 53.3 cm (21 in.) or 55.9 cm (22 in.) | 186.00 | N/A |
| modification of seat width to 48.3 cm (19 in.), 50.8 cm (20 in.) | 106.00 | 37/4 |
| or 55.9 cm (22 in.) | 186.00 | N/A |
| modification of back height to 50.8 cm (20 in.) | 32.00 | N/A |
| supple back, nylon supple seat, nylon | N/C N/C | 53.00 63.00 |
| seat cushion, flat, foam, 5.1 cm (2 in.) | 59.00 | 59.00 |
| seat cushion, flat, foam, 7.6 cm (3 in.) | 59.00 | 59.00 |
| safety belt, velcro-type | N/C | 42.00 |
| safety belt, velero type | N/C | 53.00 |
| | 1,70 | 22.00 |
| Armrests: | | |
| L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 25.4 cm (10 in.), short | N/C | 55.00 |
| U-type armrests, detachable, flip-back, height-adjustable | N/C | 33.00 |
| from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long | N/C | 131.00 |
| T-type armrests, detachable, height-adjustable from 15.2 cm (6 in.) | 11/C | 131.00 |
| to 25.4 cm (10 in.), from 20.3 cm (8 in.) to 35.6 cm (14 in.), | | |
| short, long | 152.00 | 131.00 |
| armrest pads, tubular | N/C | 11.00 |
| armrest pads, straight, short | N/C | 26.00 |
| armrest pads, straight, long | N/C | 26.00 |
| clothing guards, flexible | N/C | 48.00 |
| clothing guards, rigid | N/C | 48.00 |
| modification of L-type armrest height, shortening by 2.5 cm (1 in.) | | |
| to 10.2 cm (4 in.) | 80.00 | N/A |
| Footrests: | | |
| 60° footrests, parallel, detachable, swingaway, length-adjustable | | |
| from 37.5 cm $(14^{3}/_{4} \text{ in.})$ to 47.6 cm $(18^{3}/_{4} \text{ in.})$; 70° footrests, parallel | l, | |
| detachable, swingaway, length-adjustable from 34.3 cm (13 ¹ / ₂ in.) | NIC | 44400 |
| to $47.0 \text{ cm} (18^{1}/_{2} \text{ in.})$ | N/C | 114.00 |
| 70° footrests, tapered, detachable, swingaway, length-adjustable | 112.00 | 170.00 |
| from $40.0 \text{ cm} (15^3/_4 \text{ in.})$ to $45.1 \text{ cm} (17^3/_4 \text{ in.})$ | 113.00 | 170.00 |
| 60° or 80° fixed footrests, parallel, length-adjustable from | 177.00 | 120.00 |
| $37.5 \text{ cm} (14^3/4 \text{ in.}) \text{ to } 47.0 \text{ cm} (18^1/2 \text{ in.})$ | 177.00 | 130.00 |
| 90° footrests, parallel, detachable, swingaway, length-adjustable | 113.00 | 170.00 |
| from 12.7 cm (5 ¹ / ₄ in.) to 26.7 cm (10 ¹ / ₂ in.) 60° footrests, MFX, parallel, detachable, swingaway, | 113.00 | 1/0.00 |
| length-adjustable from 27.9 cm (11 in.) to 38.1 cm (15 in.); | | |
| 70° footrests, MFX, parallel, detachable, swingaway, | | |
| length-adjustable from 22.2 cm $(8^3/_4 \text{ in.})$ to 37.5 cm $(14^3/_4 \text{ in.})$ | 113.00 | 170.00 |
| 1011501 adjustable 110111 22.2 cm (0 /4 m.) to 3 / .3 cm (1 + /4 m.) | 113.00 | 170.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| elevating legrests, length-adjustable from 38.7 cm (15 ¹ / ₄ in.) | | |
| to 54.0 cm (21 ¹ / ₄ in.) | 244.00 | 236.00 |
| elevating legrests with compensating mechanism, length-adjustable from 40.6 cm (16 in.) to 53.3 cm (21 in.) | 160.00 | 194.00 |
| modification of elevating legrest height, by -2.5 cm (1 in.) or | 250.00 | 250.00 |
| by -5.1 cm (2 in.) | 250.00 | 250.00 |
| padded calfrests | N/C | 28.00 |
| ingle calf strap | 25.00 | 37.00 |
| ouble calf strap | 38.00 | 55.00 |
| olding footplates, standard | N/C | 42.00 |
| ull-width footrest, tubular | N/C | 127.00 |
| ull-width footrest, tubular, plastic-coated | 25.00 | 152.00 |
| ull-width footrest, angle-adjustable ootplates, angle-adjustable, depth-adjustable, standard or | 72.00 | 199.00 |
| oversized, $18.4 \text{ cm} (7^{1}/_{4} \text{ in.})$ | 76.00 | 80.00 |
| versized footplates, folding | 45.00 | 65.00 |
| eel loops, fixed | N/C | 7.00 |
| eel loops, adjustable | N/C | 15.00 |
| eel loops with ankle straps | 25.00 | 19.00 |
| clamps, 1.9 cm (³ / ₄ in.) to 2.5 cm (1 in.), making it possible to install footplates higher up on the legrest bracket | 30.00 | 15.00 |
| Frame: | | |
| neavy-duty frame | 245.00 | N/A |
| ack, angle-adjustable | 70.00 | 133.00 |
| nti-tip rollers | N/C | 50.00 |
| packposts with push handles | N/C | 38.00 |
| ane holder | 34.00 | 34.00 |
| Orive systems: nandrims with vertical or oblique projections | 155.00 | 125.00 |
| emooth handrims | N/C | 36.00 |
| lastic-coated handrims | N/C N/C | 63.00 |
| | N/C | 03.00 |
| Vheel locks: | NIC | 47.00 |
| tandard wheel locks, push-to-lock | N/C | 46.00 |
| tandard wheel locks, pull-to-lock | N/C | 46.00 |
| wheel lock extensions | 34.00 | 17.00 |
| nti-rollback brakes | 94.00 | 93.00 |
| cissor-type wheel locks | 118.00 | 105.00 |
| Wheels: ear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | | |
| 61.0 cm (24 in.) | N/C | 105.00 |
| ear mag wheels, standard pressure, 50.8 cm (20 in.), | 1110 | 103.00 |
| 5.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 105.00 |
| poked rear wheels, standard pressure, 50.8 cm (20 in.), | 11/0 | 105.00 |
| 5.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.) | N/C | 142.00 |
| 3.7 cm (22 m.), 01.0 cm (24 m.), 00.0 cm (20 m.) | 14/ | 142.00 |

\$815.00

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.) rear wheels, heavy-duty, standard pressure, high pressure, solid |) N/C | 142.00 |
| ires, 61.0 cm (24 in.), 66.0 cm (26 in.) | 82.00 | 183.00 |
| poked rear wheels, solid tires, 61.0 cm (24 in.), 66.0 cm (26 in.) | N/C | 142.00 |
| ont wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.) | N/C | 50.00 |
| cont wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in. cont wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.), |) N/C | 63.00 |
| .6 cm (3 in.), 12.7 cm (5 in.), 15.2 cm (6 in.) | N/C | 40.00 |
| ont wheels, solid tires, 12.7 cm (5 in.) x 3.8 cm ($1^{1}/_{2}$ in.) | N/C | 42.00 |
| ront wheels, solid tires, 15.2 cm (6 in.) x 3.8 cm (1½ in.) ront wheels, inner tube tires, 15.2 cm (6 in.), | N/C | 42.00 |
| $0.3 \text{ cm } (8 \text{ in.}) \times 3.2 \text{ cm } (1^{1}/_{4} \text{ in.})$ | 30.00 | 55.00 |
| orks: | NIG | 52 .00 |
| tandard forks, short | N/C | 52.00 |
| ork-locking mechanism | 100.00 | 50.00 |
| ear axles: | NUC | 15.00 |
| nreaded axles | N/C | 15.00 |
| uick-release axles | N/C | 53.00 |
| xtension plates for amputees | 52.00 | 26.00 |
| Component(s) under Special Consideration | | |
| poke guards* | 94.00 | 47.00 |
| uick-release rear axles with lever mechanism* | 76.00 | 53.00 |
| UPPLIER: SUNRISE MEDICAL CANADA INC. | | nn: |
| | | PR |
| | | |

Basic Components

Body support system

- supple back, nylon
- seat height: from 40.6 cm (16 in.) to 48.3 cm (19 in.)

MANUAL WHEEL CHAIR BREEZY 600 MODEL

- supple seat, nylon, padded
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.)
- front seat height: from 40.6 cm (16 in.) to 50.8 cm (20 in.)
- safety belt, velcro-type, auto-type

Armrests

- L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- U-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short, long
- armrest pads, straight, short, long
- armrest pads, tubular
- · clothing guards, flexible, rigid

Footrests

- 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 33.0 cm (13 in.) to 45.7 cm (18 in.)
- · folding footplates, standard
- aluminum footplates for elevating legrests
- heel loops, adjustable
- padded calfrests for elevating legrests with compensating mechanism

Frame

- anti-tip rollers
- · push handles, integrated

Drive, brake, wheel, fork and axle systems

- plastic-coated handrims, smooth
- standard wheel locks, push-to-lock, pull-to-lock
- rear mag wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.)
- rear mag wheels, standard pressure, 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.)
- front wheels, solid tires, 12.7 cm (5 in.)
- front wheels, solid tires, 15.2 cm (6 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)
- front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm (1¹/₂ in.), 15.2 cm (6 in.) x 3.8 cm (1¹/₂ in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm $(1^{1}/_{2}$ in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.)
- · standard forks, short forks
- fork stems, $+3.8 \text{ cm} (1^{1}/_{2} \text{ in.})$
- · threaded axles, quick-release
- · extension plates for amputees
- forkstems, $+3.8 \text{ cm } (1^{1}/_{2} \text{ in.})$
- threaded axles, quick-release
- extension plates for amputees

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
|--|---|---|

Basic and Optional Components

Body support system

Seat and back:

| modification of seat height from 33.0 cm (13 in.) to | | |
|--|-------|--------|
| $39.4 \text{ cm } (15^{1}/_{2} \text{ in.})$, on ultra-hemi frame | 65.00 | N/A |
| modification of seat width to 48.3 cm (19 in.) or 50.8 cm (20 in.) | 75.00 | N/A |
| modification of seat depth to 45.7 cm (18 in.) | 78.00 | N/A |
| supple back, tension-adjustable | 76.00 | 140.00 |
| supple back, nylon | N/C | 64.00 |
| supple seat, nylon | N/C | 55.00 |
| supple seat, padded nylon | N/C | 55.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|--|
| seat cushion, flat, foam, 5.1 cm (2 in.) | 58.00 | 58.00 |
| seat cushion, flat, foam, 7.6 cm (3 in.) | 58.00 | 58.00 |
| seat cushion, flat, foam, 10.2 cm (4 in.) | 58.00 | 58.00 |
| safety belt, velcro-type | N/C | 29.00 |
| safety belt, auto-type | N/C | 42.00 |
| Armrests: | | |
| L-type armrests, detachable, swingaway, height-adjustable | | |
| from 20.3 cm (8 in.) to 30.5 cm (12 in.), short | N/C | 96.00 |
| U-type armrests, detachable, flip-back, height-adjustable | | |
| From 22.9 cm (9 in.) to 33.0 cm (13 in.), short, long | N/C | 131.00 |
| armrest pads, tubular | N/C | 2.00 |
| armrest pads, straight, short | N/C | 15.00 |
| armrest pads, straight, long | N/C | 18.00 |
| clothing guards, flexible | N/C | 22.00 |
| clothing guards, rigid | N/C | 68.00 |
| Footrests: 60° footrests, parallel, detachable, swingaway, length-adjustable from 33.0 cm (13 in.) to 45.7 cm (18 in.) 70° footrests, parallel, detachable, swingaway, length-adjustable from 33.0 cm (13 in.) to 45.7 cm (18 in.) elevating legrests elevating legrests with compensating mechanism padded calfrests for elevating legrests padded calfrests for legrests with compensating mechanism single calf strap double calf strap | N/C N/C 108.00 200.00 N/C N/C 19.00 33.00 | 55.00 55.00 109.00 155.00 19.00 40.00 19.00 33.00 |
| Folding footplates, standard | N/C | 49.00 |
| olding footplates, standard olding footplates, angle-adjustable and depth-adjustable | 54.00 | 76.00 |
| oversized footplates | 74.00 | 86.00 |
| duminum footplates for elevating legrests | N/C | 49.00 |
| neel loops, adjustable | N/C | 10.00 |
| modification of the length of footrests from 45.7 cm (18 in.) o 52.1 cm $(20^{1}/_{2} \text{ in.})$ | 31.00 | 30.00 |
| Frame: | | |
| anti-tip rollers | N/C | 22.00 |
| cane holder | 45.00 | 45.00 |
| bush handles, integrated | N/C | 36.00 |
| Drive systems: | | |
| one-arm dual handrim drive | 399.00 | 522.00 |
| mooth handrims | N/C | 60.00 |
| plastic-coated handrim for one-arm drive | N/C | 97.00 |
| plastic-coated handrims | N/C | 88.00 |
| nandrims with vertical or oblique projections, 61.0 cm (24 in.) | 90.00 | 105.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| Wheel locks: | | |
| standard wheel locks, push-to-lock, pull-to-lock | N/C | 40.00 |
| wheel lock extensions | 26.00 | 13.00 |
| anti-rollback brakes | 68.00 | 34.00 |
| Wheels: | | |
| rear mag wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 136.00 |
| rear mag wheels, solid tires, 50.8 cm (20 in.) | N/C | 136.00 |
| rear mag wheels, standard pressure, 55.9 cm (22 in.), | | |
| 61.0 cm (24 in.) | N/C | 113.00 |
| rear mag wheels, standard pressure, 50.8 cm (20 in.) | N/C | 136.00 |
| front wheels, solid tires, 12.7 cm (5 in.) | N/C | 47.00 |
| front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) | N/C | 63.00 |
| Front wheels, solid tires, 15.2 cm (6 in.) | N/C | 62.00 |
| front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm ($1^{1}/_{2}$ ir | 1.), | |
| 15.2 cm (6 in.) x 3.8 cm ($1\frac{1}{2}$ in.) | N/C | 89.00 |
| front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm ($1^{1}/_{2}$ ir | n.) N/C | 99.00 |
| front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.) | N/C | 63.00 |
| Forks: | | |
| standard forks, 15.2 cm (6 in.), compatible with 12.7 cm (5 in.), | | |
| 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels | N/C | 32.00 |
| short forks, 12.1 cm (4 ³ / ₄ in.), compatible with 12.7 cm (5 in.) when | els N/C | 32.00 |
| fork stems, $+3.8 \text{ cm} (1^{1}/_{2} \text{ in.})$ | N/C | 16.00 |
| Rear axles: | | |
| threaded axles | N/C | 18.00 |
| quick-release axles | N/C | 33.00 |
| extension plates for amputees | N/C | N/A |
| Component(s) under Special Consideration | | |
| spoke guards* | 70.00 | 35.00 |
| SUPPLIER: SUNRISE MEDICAL CANADA INC. | | |
| | | PRI |
| MANUAL WHEEL CHAIR QUICKIE LXI MODEL | | \$1 195 |

- Body support systemsupple back, nylon
- back height: from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- front seat height: from $40.0 \text{ cm} (15^3/_4 \text{ in.})$ to $54.6 \text{ cm} (21^1/_2 \text{ in.})$
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: 40.6 cm (16 in.)
- supple seat, nylon
- safety belt, velcro-type, auto-type

Armrests

- L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- U-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short, long
- · armrest pads, straight, short, long
- armrest pads, tubular
- clothing guards, supple, rigid

Footrests

- 60° parallel footrests, 70° parallel footrests, or 70° tapered footrests, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 90° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- padded calfrests
- · folding footplates, standard
- folding footplates, tubular
- heel loops, adjustable

Frame

- · anti-tip rollers
- push handles, integrated
- backposts, at an 8° angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.)

- plastic-coated handrims, smooth
- standard wheel locks, push-to-lock, pull-to-lock
- rear mag wheels, solid tires, 50.8 cm (20 in.)
- rear mag wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.)
- rear mag wheels, standard pressure, 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.)
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 15.2 cm (6 in.)
- front wheels, solid tires, 12.7 cm (5 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.)
- front wheels, inner tube tires, 15.2 cm (6 in.) x 3.2 cm ($1^{1}/_{4}$ in.)
- front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm (1¹/₂ in.), 15.2 cm (6 in.) x 3.8 cm (1¹/₂ in.)
- standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5¹/₄ in.); high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- high forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- fork stems, $+1.9 \text{ cm} (\frac{3}{4} \text{ in.})$, $+3.8 \text{ cm} (\frac{1}{2} \text{ in.})$
- threaded axles, quick-release

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: modification of seat depth to 35.6 cm (14 in.) or 38.1 cm (15 in.) modification of seat width to 48.3 cm (19 in.) or 50.8 cm (20 in.) modification of seat depth to 43.2 cm (17 in.) or 45.7 cm (18 in.) supple back, nylon supple back, tension-adjustable | 41.00 98.00 69.00 N/C 76.00 | N/A N/A N/A 64.00 140.00 |
| supple seat, tension adjustable supple seat, tension adjustable supple seat, nylon seat cushion, flat, foam, 5.1 cm (2 in.) seat cushion, flat, foam, 7.6 cm (3 in.) seat cushion, flat, foam, 10.2 cm (4 in.) safety belt, velcro-type safety belt, auto-type | 58.00 58.00 58.00 58.00 N/C N/C | 55.00 58.00 58.00 58.00 29.00 42.00 |
| Armrests: L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short U-type armrests, detachable, flip-back, height-adjustable | N/C | 96.00 |
| from 22.9 cm (9 in.) to 33.0 cm (13 in.), short, long armrest pads, tubular armrest pads, straight, short armrest pads, straight, long clothing guards, rigid clothing guards, flexible | N/C N/C N/C N/C N/C N/C | 131.00 2.00 15.00 18.00 68.00 22.00 |
| Footrests: 60° footrests, parallel; 70° footrests, parallel, detachable, swingav length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 70° footrests, tapered, detachable, swingaway, length-adjustable | N/C | 55.00 |
| from 35.6 cm (14 in.) to 48.3 cm (19 in.) 90° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) elevating legrests elevating legrests with compensating mechanism | N/C N/C 108.00 | 55.00 57.00 109.00 |
| padded calfrests single calf strap double calf strap folding footplates, standard | 200.00 N/C 19.00 33.00 N/C | 155.00 19.00 19.00 33.00 49.00 |
| folding footplates, standard folding footplates, angle-adjustable and depth-adjustable folding footplates, tubular full-width footrest oversized footplates | 54.00 N/C 85.00 74.00 | 76.00 49.00 183.00 86.00 |
| heel loops, adjustable modification of footrest length from 48.3 cm (19 in.) to 52.1 cm (20 ¹ / ₂ in.) | N/C 31.00 | 10.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| modification of the footrest mounting from 17.8 cm (7 in.) | 56.00 | 24.00 |
| to 34.3 cm $(13^{1}/_{2} \text{ in.})$ modification of 90° footrest length by +5.1 cm (2 in.) or by +10.2 cm (4 in.) | 56.00 32.00 | 34.00 16.00 |
| | | |
| Frame: anti-tip rollers | N/C | 22.00 |
| cane holder | 45.00 | 45.00 |
| bush handles, integrated | N/C | 23.00 |
| backposts, at an 8° angle, from 35.6 cm (14 in.) to 48.3 cm (19 in.) | N/C | 28.00 |
| Jackposts, at an 8 angle, from 33.0 cm (14 m.) to 46.3 cm (19 m.) | IV/C | 28.00 |
| Drive systems: | 402.00 | 577.00 |
| one-arm dual handrim drive | 482.00 | 577.00 |
| smooth handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), | .) N/C | 60.00 |
| 61.0 cm (24 in.) | N/C | 88.00 |
| nandrims with vertical or oblique projections, 61.0 cm (24 in.) | 90.00 | 105.00 |
| small plastic-coated handrim for one-arm drive | N/C | 97.00 |
| Wheel locks: | | |
| standard wheel locks, push-to-lock, pull-to-lock | N/C | 40.00 |
| wheel lock extensions | 26.00 | 13.00 |
| anti-rollback brakes | 68.00 | 34.00 |
| Wheels: | | |
| rear mag wheels, solid tires, 50.8 cm (20 in.) | N/C | 136.00 |
| rear mag wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 136.00 |
| ear mag wheels, standard pressure, 50.8 cm (20 in.) | N/C | 136.00 |
| rear mag wheels, standard pressure, 55.9 cm (22 in.), 61.0 cm (24 in.) poked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm | i.) N/C | 113.00 |
| 22 in.), 61.0 cm (24 in.) | N/C | 136.00 |
| spoked rear wheels, high pressure, 61.0 cm (24 in.) | N/C | 136.00 |
| poked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | 14/6 | 130.00 |
| 51.0 cm (24 in.) | N/C | 153.00 |
| Front wheels, solid tires, 15.2 cm (6 in.) | N/C | 62.00 |
| Front wheels, solid tires, 12.7 cm (5 in.) | N/C | 47.00 |
| Front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) | N/C | 63.00 |
| Front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm ($1\frac{1}{4}$ in.) | N/C | 63.00 |
| Front wheels, inner tube tires, 15.2 cm (6 in.) x 3.2 cm ($1^{1}/_{4} \text{ in.}$) | N/C | 62.00 |
| ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 48.00 | 72.00 |
| Front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm ($1^{1}/_{2}$ in. 15.2 cm (6 in.) x 3.8 cm ($1^{1}/_{2}$ in.) |), N/C | 89.00 |
| Forks: tandard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); | | |
| high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), | NIC | 22.00 |
| 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels | N/C | 32.00 |
| high forks, 17.8 cm (7 in.), compatible with | N/C | 27.00 |
| 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels | N/C | 37.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| fork-locking mechanism | 46.00 | 23.00 |
| fork stems, $+1.9 \text{ cm} ({}^{3}/_{4} \text{ in.})$, $+3.8 \text{ cm} (1{}^{1}/_{2} \text{ in.})$ | N/C | 16.00 |
| Rear axles: | | |
| threaded axles | N/C | 11.00 |
| quick-release axles | N/C | 33.00 |
| extension plates for amputees | 66.00 | N/A |
| Component(s) under Special Consideration | | |
| spoke guards* | 70.00 | 35.00 |
| quick-release axles with lever mechanism* | 66.00 | 66.00 |
| SUPPLIER: SUNRISE MEDICAL CANADA INC. | | |
| 2 | | PRIC |

MANUAL WHEEL CHAIR QUICKIE 2 ADULT MODEL

\$1 540.00

Basic Components

Body support system

- supple back, nylon
- seat height: from 21.6 cm $(8^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$
- supple seat, nylon
- seat width: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- seat depth: 40.6 cm (16 in.)
- front seat height: from 36.8 cm $(14^{1}/_{2} \text{ in.})$ to 54.6 cm $(21^{1}/_{2} \text{ in.})$
- safety belt, velcro-type, auto-type

Armrests

- L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- U-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short, long
- · armrest pads, straight, short, long
- armrest pads, tubular
- · clothing guards, flexible, rigid

Footrests

- 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70°, 80° or 90° footrests, parallel, detachable, swingaway, length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.)
- · padded calfrests
- padded calfrests for elevating legrests with compensating mechanism
- folding footplates, standard
- · folding footplates, tubular

- · aluminum footplates for elevating legrests
- heel loops, adjustable

Frame

- growth kit, including seat, back, footrests, front frame and crossbars (once only during first three years from date of purchase, for first user)
- anti-tip rollers
- · push handles, integrated

Drive, brake, wheel, fork and axle systems

- plastic-coated handrims, smooth
- standard wheel locks, push-to-lock, pull-to-lock
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 15.2 cm (6 in.) x 3.2 cm (1¹/₄ in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1¹/₂ in.), 15.2 cm (6 in.) x 3.8 cm (1¹/₂ in.), 12.7 cm (5 in.) x 3.8 cm (1¹/₂ in.)

modification of back height from 48.3 cm (19 in.) to 55.9 cm (22 in.)

- standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 //4 in.); high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- high forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.), 20.3 cm (8 in.) wheels
- fork stems, $+1.9 \text{ cm} (\frac{3}{4} \text{ in.})$, $+3.8 \text{ cm} (\frac{1}{2} \text{ in.})$
- threaded axles, quick-release

43.2 cm (17 in.) or 45.7 cm (18 in.)

seat cushion, flat, foam, 5.1 cm (2 in.)

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: supple back, tension-adjustable supple back, nylon supple seat, nylon modification of seat depth to 35.6 cm (14 in.), 38.1 cm (15 in.), | 76.00 N/C N/C | 140.00 64.00 55.00 |

40.00

103.00

58.00

N/A

N/A

58.00

| 58.00 58.00 29.00 42.00 106.00 173.00 |
|--|
| 29.00 42.00 106.00 |
| 42.00 106.00 |
| 106.00 |
| |
| 173.00 |
| |
| |
| |
| 96.00 |
| |
| 135.00 |
| |
| 131.00 |
| 2.00 |
| 18.00 |
| 15.00 |
| 22.00 |
| 68.00 |
| 55.00 |
| 55.00 |
| 87.00 |
| |
| 57.00 |
| 155.00 |
| 109.00 |
| 19.00 |
| 55.00 |
| 40.00 |
| 19.00 |
| 33.00 |
| 49.00 |
| 76.00 |
| 178.00 |
| 102.00 |
| 49.00 |
| 86.00 |
| 183.00 |
| 49.00 |
| 10.00 |
| |
| 30.00 |
| |
| 16.00 |
| |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| raised footplate mountings, 7.8 cm (7 in.) to 34.3 cm ($13^{1}/_{2}$ in.) | | |
| n length | 56.00 | 34.00 |
| Front impact guard with rollers | 38.00 | 19.00 |
| Frame: | | |
| optional heavy-duty frame, 45.7 cm (18 in.) to 55.9 cm (22 in.) wid | de 371.00 | N/A |
| extra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in. |) 52.00 | N/A |
| olding back, angle-adjustable | 107.00 | N/A |
| packposts, at an 8° angle, from 31.8 cm ($12^{1}/_{2}$ in.) | | |
| o $47.0 \text{ cm} (18^{1}/_{2} \text{ in.})$ | 14.00 | 27.00 |
| packposts, angle adjustable from -3° to +15°, 3 positions | 122.00 | N/A |
| pack spreader bar | 130.00 | N/A |
| back spreader bar, folding | 226.00 | 226.00 |
| oush handles, integrated | N/C | 20.00 |
| growth kit, including seat, back, footrests, front frame and crossbar once only during first three years from date of purchase, | rs · | |
| For first user) | N/C | N/A |
| anti-tip rollers | N/C | 22.00 |
| cane holder | 45.00 | 45.00 |
| | 13.00 | 13.00 |
| Drive systems : one-arm dual handrim drive | 562.00 | 709.00 |
| smooth handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), | 302.00 | 707.00 |
| 61.0 cm (24 in.), 66.0 cm (26 in.) | N/C | 60.00 |
| nandrims with vertical or oblique projections, 61.0 cm (24 in.) | 90.00 | 105.00 |
| plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), | 20.00 | 103.00 |
| 61.0 cm (24 in.), 66.0 cm (26 in.) | N/C | 88.00 |
| non-slip handrims, 55.9 cm (22 in.), 61.0 cm (24 in.) | 168.00 | 144.00 |
| small plastic-coated handrim for one-arm drive | N/C | 97.00 |
| • | 140 | 77.00 |
| Wheel locks: standard wheel locks, push-to-lock, pull-to-lock | N/C | 40.00 |
| wheel lock extensions | 26.00 | 13.00 |
| unti-rollback brakes | 68.00 | 34.00 |
| wheel locks, push-to-lock, unilateral control | 128.00 | 54.00 N/A |
| wheel locks, push-to-lock, unhateral control wheel locks, push-to-lock, flip-back | 50.00 | 65.00 |
| viicei iocks, pusii-to-iock, iiip-vack | 30.00 | 03.00 |
| Wheels: | | |
| spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | N/C | 152.00 |
| 51.0 cm (24 in.) | N/C | 153.00 |
| poked rear wheels, standard pressure, 50.8 cm (20 in.), | NIC | 126.00 |
| (5.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.) | N/C | 136.00 |
| poked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in ear wheels, heavy-duty, standard pressure, high pressure, | | 136.00 |
| 61.0 cm (24 in.) | 126.00 | 199.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | | |
| 61.0 cm (24 in.) | N/C | 136.00 |
| rear mag wheels, standard pressure, 50.8 cm (20 in.) | N/C | 136.00 |
| rear mag wheels, standard pressure, 55.9 cm (22 in.), | | |
| 61.0 cm (24 in.) | N/C | 113.00 |
| Front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) | N/C | 63.00 |
| Front wheels, solid tires, 15.2 cm (6 in.) | N/C | 62.00 |
| Front wheels, solid tires, 12.7 cm (5 in.) | N/C | 47.00 |
| ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 48.00 | 72.00 |
| Front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.) | N/C | 63.00 |
| Front wheels, inner tube tires, $15.2 \text{ cm} (6 \text{ in.}) \times 3.2 \text{ cm} (1^{1}/_{4} \text{ in.})$ | N/C | 62.00 |
| Front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm ($1^{1}/_{2}$ i | | |
| 15.2 cm (6 in.) x $3.\hat{8}$ cm ($1^{1}/_{2}$ in.) | N/C | 89.00 |
| Front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 in. | | 81.00 |
| Front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm ($1^{1}/_{2}$ i | n.) N/C | 99.00 |
| Forks: standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels high forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels fork-locking mechanism fork stems, +1.9 cm (³ / ₄ in.), +3.8 cm (1 ¹ / ₂ in.) multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels | N/C N/C 46.00 N/C N/C | 32.00 37.00 23.00 16.00 56.00 |
| Rear axles: | | |
| quick-release axles | N/C | 33.00 |
| hreaded axles | N/C | 33.00 |
| extension plates for amputees | 42.00 | 73.00 |
| curved multi-position plates | 28.00 | 66.00 |
| Component(s) under Special Consideration | | |
| spoke guards* | 70.00 | 35.00 |
| quick-release axles with lever mechanism* | 66.00 | 66.00 |
| SUPPLIER: SUNRISE MEDICAL CANADA INC. | | ppr |
| | | PRI |
| MANUAL WHEEL CHAIR QUICKIE 2 HP - ADULT MODE | L | \$1 540 |

Body support system

- supple back, nylon
- seat height: from 21.6 cm $(8^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$
- supple seat, nylon

- seat width: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- seat depth: 40.6 cm (16 in.)
- front seat height: from 41.9 cm $(16^{1}/_{2} \text{ in.})$ to 54.6 cm $(21^{1}/_{2} \text{ in.})$
- safety belt, velcro-type, auto-type

Armrests

- L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- U-type armrests, detachable, flip-back, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short, long
- · armrest pads, straight, short, long
- armrest pads, tubular
- · clothing guards, flexible, rigid

Footrests

- 60° or 70° footrests, fixed, parallel, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- folding footplates, standard
- folding footplates, tubular
- heel loops, adjustable

Frame

- anti-tip rollers
- · push handles, integrated

- plastic-coated handrims, smooth
- standard wheel locks, push-to-lock, pull-to-lock
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 15.2 cm (6 in.) x 3.2 cm (1¹/₄ in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1¹/₂ in.), 15.2 cm (6 in.) x 3.8 cm (1¹/₂ in.), 12.7 cm (5 in.) x 3.8 cm (1¹/₂ in.)
- standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5¹/₄ in.); high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- high forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- fork stems, $+1.9 \text{ cm} (\frac{3}{4} \text{ in.})$, $+3.8 \text{ cm} (\frac{11}{2} \text{ in.})$
- threaded axles, quick-release

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| supple back, tension-adjustable | 76.00 | 140.00 |
| supple back, nylon | N/C | 64.00 |
| supple seat, nylon | N/C | 55.00 |
| modification of seat depth to 35.6 cm (14 in.), 38.1 cm (15 in.), | | |
| 43.2 cm (17 in.) or 45.7 cm (18 in.) | 48.00 | N/A |
| modification of back height from 48.3 cm (19 in.) to 55.9 cm (22 in | | N/A |
| seat cushion, flat, foam, 5.1 cm (2 in.) | 58.00 | 58.00 |
| seat cushion, flat, foam, 7.6 cm (3 in.) | 58.00 | 58.00 |
| seat cushion, flat, foam, 10.2 cm (4 in.) | 58.00 | 58.00 |
| safety belt, velcro-type | N/C | 29.00 |
| safety belt, auto-type | N/C | 42.00 |
| Armrests: | | |
| L-type armrests, detachable, swingaway, height-adjustable | | |
| from 20.3 cm (8 in.) to 30.5 cm (12 in.), short | N/C | 96.00 |
| T-type armrests, detachable, height-adjustable from 22.9 cm (9 in.) | | |
| to 35.6 cm (14 in.), short, long | 78.00 | 135.00 |
| U-type armrests, detachable, flip-back, height-adjustable | | |
| from 22.9 cm (9 in.) to 33.0 cm (13 in.), short, long | N/C | 131.00 |
| armrest pads, tubular | N/C | 2.00 |
| armrest pads, straight, long | N/C | 18.00 |
| armrest pads, straight, short | N/C | 15.00 |
| clothing guards, flexible | N/C | 22.00 |
| clothing guards, rigid | N/C | 68.00 |
| Footrests: | | |
| 60° to 70° footrests, fixed, parallel, length-adjustable | | |
| from 35.6 cm (14 in.) to 48.3 cm (19 in.) | N/C | 44.00 |
| single calf strap | 19.00 | 19.00 |
| double calf strap | 33.00 | 33.00 |
| folding footplates, standard | N/C | 49.00 |
| folding footplates, angle-adjustable and depth-adjustable | 54.00 | 76.00 |
| folding footplates, tubular | N/C | 49.00 |
| oversized footplates | 74.00 | 86.00 |
| full-width footrest | 85.00 | 183.00 |
| heel loops, adjustable | N/C | 10.00 |
| modification of footrest length from 48.3 cm (19 in.) | | |
| to 52.1 cm $(20^{1}/_{2} in.)$ | 31.00 | 30.00 |
| raised footplate mountings, 17.8 cm (7 in.) to 34.3 cm $(13^{1}/_{2} in.)$ | | |
| in length | 56.00 | 34.00 |
| Frame: | | |
| optional heavy-duty frame, 45.7 cm (18 in.) to 55.9 cm (22 in.) wid | e 371.00 | N/A |
| extra-long frame for depths of 48.3 cm (19 in.) and 50.8 cm (20 in.) | | N/A |
| 6 | | - 17.2 |

| backposts, at an 8° angle, from 31.8 cm (12 ¹ / ₂ in.) to 47.0 cm (18 ¹ / ₂ in.), with handles backposts, angle-adjustable from -3° to +15°, 3 positions push handles, integrated back spreader bar | 14.00 122.00 N/C 130.00 | 27.00 N/A |
|---|----------------------------------|----------------|
| to 47.0 cm (18 ¹ / ₂ in.), with handles backposts, angle-adjustable from -3° to +15°, 3 positions push handles, integrated | 122.00 N/C | |
| backposts, angle-adjustable from -3° to +15°, 3 positions push handles, integrated | N/C | N/A |
| | | 11/11 |
| hack spreader har | 130.00 | 20.00 |
| suck spreader our | 130.00 | N/A |
| anti-tip rollers | N/C | 22.00 |
| cane holder | 45.00 | 45.00 |
| Drive systems: | 5.00 | 5 00.00 |
| one-arm dual handrim drive | 562.00 | 709.00 |
| smooth handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), | NIG | 60.00 |
| 51.0 cm (24 in.), 66.0 cm (26 in.) | N/C | 60.00 |
| nandrims with vertical or oblique projections, 61.0 cm (24 in.) plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), | 90.00 | 105.00 |
| 61.0 cm (24 in.), 66.0 cm (26 in.) | N/C | 88.00 |
| non-slip handrims, 55.9 cm (22 in.), 61.0 cm (24 in.) | 168.00 | 144.00 |
| mall plastic-coated handrim for one-arm drive | N/C | 97.00 |
| Wheel locks: | 3716 | 40.00 |
| tandard wheel locks, push-to-lock, pull-to-lock | N/C | 40.00 |
| cissor-type wheel locks | 26.00 | 53.00 |
| wheel lock extensions | 26.00 | 13.00 |
| wheel locks, push-to-lock, unilateral control | 128.00 | N/A |
| nti-rollback brakes | 68.00 | 34.00 |
| wheel locks, push-to-lock, flip-back | 50.00 | 65.00 |
| Wheels: spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | | |
| 61.0 cm (24 in.) | N/C | 153.00 |
| poked rear wheels, standard pressure, 50.8 cm (20 in.), | 1,, 0 | 100.00 |
| 5.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.) | N/C | 136.00 |
| poked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in eavy-duty rear wheels, standard pressure, high pressure, | | 136.00 |
| 1.0 cm (24 in.) ear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | 126.00 | 199.00 |
| 1.0 cm (24 in.) | N/C | 136.00 |
| ear mag wheels, standard pressure, 50.8 cm (20 in.) | N/C | 136.00 |
| ear mag wheels, standard pressure, 55.9 cm (22 in.), 61.0 cm (24 i | | 113.00 |
| cont wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) | N/C | 63.00 |
| ront wheels, solid tires, 15.2 cm (6 in.) | N/C | 62.00 |
| ront wheels, solid tires, 12.7 cm (5 in.) | N/C | 47.00 |
| ront wheels, solid tires, 10.2 cm (4 in.) | 26.00 | 60.00 |
| ront wheels, solid tires, 7.6 cm (3 in.) | 40.00 | 67.00 |
| ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 48.00 | 72.00 |
| ront wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.) | N/C | 63.00 |
| cont wheels, inner tube tires, 15.2 cm (6 in.) \times 3.2 cm (1 ¹ / ₄ in.) cont wheels, semi-pneumatic tires, 12.7 cm (5 in.) \times 3.8 cm (1 ¹ / ₂ ir.) | N/C | 62.00 |
| 5.2 cm (6 in.) x 3.8 cm ($1^{1}/_{2}$ in.) | N/C | 89.00 |

\$1 748.00

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm ($1\frac{1}{2}$ in. front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 in.) |) N/C 68.00 | 99.00 81.00 |
| Forks: standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels | N/C | 32.00 |
| high forks, 17.8 cm (7 in.), compatible with | MG | 27.00 |
| 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels | N/C | 37.00 |
| fork-locking mechanism | 46.00 N/C | 23.00 16.00 |
| fork stems, $+1.9 \text{ cm} (\frac{3}{4} \text{ in.})$, $+3.8 \text{ cm} (\frac{1}{2} \text{ in.})$ multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.) | N/C | 10.00 |
| and 20.3 cm (8 in.) wheels | N/C | 56.00 |
| Rear axles: | | |
| quick-release axles | N/C | 33.00 |
| neavy-duty axles | 102.00 | 84.00 |
| threaded axles | N/C | 33.00 |
| extension plates for amputees | 42.00 | 73.00 |
| curved plates | 28.00 | 66.00 |
| Component(s) under Special Consideration | | |
| spoke guards* | 70.00 | 35.00 |
| quick-release axles with lever mechanism* | 66.00 | 66.00 |
| SUPPLIER: ORTHOFAB INC. | | |
| | | PR |

Basic Components

Body support system

- supple back, nylon
- back, height-adjustable from 38.1 cm (15 in.) to 45.7 cm (18 in.)
- seat-back angle: 90°, 96°
- telescopic backposts, 8° at 20.3 cm (8 in.), 0°

MANUAL WHEEL CHAIR PRIMA MODEL

- seat width: from 35.6 cm (14 in.) to 55.9 cm (22 in.)
- seat depth: 40.6 cm (16 in.)
- supple seat, nylon
- front seat height: from 34.0 cm $(13^3/_8 \text{ in.})$ to 52.1 cm $(20^1/_2 \text{ in.})$
- safety belt, auto-type

Armrests

- L-type armrests, detachable, swingaway, height-adjustable from 22.9 cm (9 in.) to 30.5 cm (12 in.), long
- U-type armrests, detachable, flip-back, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.) or from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long

- · armrest pads, straight, short, long
- · clothing guards, rigid, detachable

Footrests

- 60° or 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests
- folding footplates, tubular
- · heel loops, adjustable

Frame

- anti-tip rollers
- push handles, integrated

- plastic-coated handrims, smooth
- standard wheel locks, push-to-lock
- spoked rear wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, semi-pneumatic tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.), 17.8 cm (7 in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1¹/₂ in.), 15.2 cm (6 in.) x 3.8 cm (1¹/₂ in.), 12.7 cm (5 in.) x 3.8 cm (1¹/₂ in.)
- standard forks, high forks
- threaded axles, quick-release
- · plates for amputees

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| supple back, tension-adjustable | 74.00 | 133.00 |
| rigid seat, flat | 116.00 | 173.00 |
| modification of back height from 33.0 cm (13 in.) to | | |
| 35.6 cm (14 in.) or from 48.3 cm (19 in.) to 55.9 cm (22 in.) | 99.00 | N/A |
| contoured headrest, nylon | 100.00 | 100.00 |
| headrest mounting, articulated, uniball | 115.00 | 115.00 |
| modification of seat depth to 35.6 cm (14 in.), 38.1 cm (15 in.), | | |
| 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.) or 50.8 cm (20 i | 5 | N/A |
| supple back, nylon | N/C | 59.00 |
| supple seat, nylon | N/C | 57.00 |
| seat cushion, flat, foam, 5.1 cm (2 in.) | 56.00 | 56.00 |
| seat cushion, flat, foam, 7.6 cm (3 in.) | 56.00 | 56.00 |
| safety belt, velcro-type | 27.00 | 63.00 |
| safety belt, auto-type | N/C | 36.00 |
| safety belt, airplane-type | 38.00 | 74.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| Armrests: | | |
| L-type armrests, detachable, swingaway, height-adjustable | | |
| from 22.9 cm (9 in.) to 30.5 cm (12 in.), long | N/C | 48.00 |
| U-type armrests, detachable, flip-back, height-adjustable | | |
| from 20.3 cm (8 in.) to 30.5 cm (12 in.) or from 25.4 cm (10 in. | | |
| to 35.6 cm (14 in.), short | N/C | 94.00 |
| U-type armrests, detachable, flip-back, height-adjustable | | |
| from 20.3 cm (8 in.) to 27.9 cm (11 in.) or from 22.9 cm (9 in.) | | 120.00 |
| to 30.5 cm (12 in.), long | N/C | 120.00 |
| armrest pads, straight, long | N/C | 15.00 |
| armrest pads, straight, short | N/C N/C | 12.00 65.00 |
| clothing guards, rigid, detachable modification of U-type armrest height to under 20.3 cm (8 in.) | N/C | 03.00 |
| or to over 30.5 cm (12 in.) | 79.00 | N/A |
| or to over 50.5 cm (12 m.) | 79.00 | IVA |
| Footrests: | | |
| 60° footrests, parallel, detachable, swingaway, length-adjustable | e | |
| from 35.6 cm (14 in.) to 48.3 cm (19 in.) | 29.00 | N/A |
| 70° footrests, parallel, detachable, swingaway, length-adjustable | | |
| From 35.6 cm (14 in.) to 48.3 cm (19 in.) | 29.00 | N/A |
| 90° footrests, parallel, detachable, swingaway, length-adjustable | | |
| from 35.6 cm (14 in.) to 48.3 cm (19 in.) | 86.00 | 121.00 |
| 60° footrests, tapered, detachable, swingaway, length-adjustable | | 7 0.00 |
| from 35.6 cm (14 in.) to 48.3 cm (19 in.) | N/C | 78.00 |
| 70° footrests, tapered, detachable, swingaway, length-adjustable | | 70.00 |
| from 35.6 cm (14 in.) to 48.3 cm (19 in.) | N/C | 78.00 |
| elevating legrests with compensating mechanism from 35.6 cm (14 in.) to 48.3 cm (19 in.) | 234.00 | 195.00 |
| elevating legrests, from 35.6 cm (14 in.) to 48.3 cm (19 in.) | 214.00 | 185.00 |
| contoured calfrests | 60.00 | 50.00 |
| padded calfrests | N/C | 20.00 |
| nodification of footrest or legrest length to under 35.6 cm (14 i | | 20.00 |
| or to over 48.3 cm (19 in.) | 79.00 | N/A |
| oversized footplates, aluminum | 44.00 | 38.00 |
| folding footplates, tubular | N/C | 16.00 |
| oversized footplates, angle-adjustable and depth-adjustable, | | |
| aluminum or composite | 82.00 | 57.00 |
| standard footplates, angle-adjustable and depth-adjustable, | | |
| aluminum or composite | 76.00 | 54.00 |
| full-width footrest, angle-adjustable and depth-adjustable, | | |
| aluminum or composite | 168.00 | 200.00 |
| louble calf strap | 55.00 | 55.00 |
| neel loops, adjustable | N/C | 11.00 |
| oe loops front impact guard with rollers | 30.00 | 15.00 |
| cront impact guard with rollers | 36.00 | 18.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| Frame: | | |
| folding mechanism with double crossbars | 269.00 | N/A |
| back, angle-adjustable | 102.00 | N/A |
| back spreader bar | 69.00 | 69.00 |
| back spreader bar with headrest support | 99.00 | 99.00 |
| push handles, integrated | N/C | N/A |
| anti-tip rollers | N/C | 46.00 |
| cane holder | 40.00 | 40.00 |
| Drive systems: | | |
| non-slip handrims | 88.00 | 92.00 |
| plastic-coated handrims | N/C | 77.00 |
| smooth handrims | N/C | 48.00 |
| Wheel locks: | | |
| standard wheel locks, push-to-lock | N/C | 53.00 |
| retractable wheel lock extensions | 40.00 | 20.00 |
| wheel lock extensions, fixed | 40.00 | 20.00 |
| anti-rollback brakes | 86.00 | 43.00 |
| Wheels: | | |
| spoked rear wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 77.00 |
| rear mag wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.) spoked rear wheels, standard pressure, 50.8 cm (20 in.), | 104.00 | 129.00 |
| 55.9 cm (22 in.), 61.0 cm (24 in.) | 72.00 | 113.00 |
| rear mag wheels, standard pressure, 50.8 cm (20 in.), | | |
| 55.9 cm (22 in.), 61.0 cm (24 in.) | 104.00 | 129.00 |
| neavy-duty rear wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in rear wheels, heavy-duty, standard pressure, 50.8 cm (20 in.), | 162.00 | 158.00 |
| 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.) rear wheels, heavy-duty, high pressure, 55.9 cm (22 in.), | 162.00 | 158.00 |
| 61.0 cm (24 in.), 66.0 cm (26 in.) rear mag wheels, semi-pneumatic tires, 50.8 cm (20 in.), | 162.00 | 158.00 |
| 55.9 cm (22 in.), 61.0 cm (24 in.) spoked rear wheels, semi-pneumatic tires, 50.8 cm (20 in.), | 104.00 | 129.00 |
| 55.9 cm (22 in.), 61.0 cm (24 in.) rear wheels, heavy-duty spokes, semi-pneumatic tires, | N/C | 77.00 |
| 55.9 cm (22 in.), 61.0 cm (24 in.) front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), | 162.00 | 158.00 |
| 12.7 cm (5 in.), 15.2 cm (6 in.), 17.8 cm (7 in.) front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm (1 ¹ / ₄ in.), | N/C | 31.00 |
| 15.2 cm (6 in.) x 3.2 cm ($^{1}/_{4}$ in.) | 34.00 | 48.00 |
| Front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 34.00 | 48.00 |
| front wheels, inner tube tires, 17.8 cm (7 in.) x 4.4 cm ($1^{3}/_{4}$ in.) | 34.00 | 48.00 |
| front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm ($1^{1}/_{2}$ in. |), | |
| $15.2 \text{ cm } (6 \text{ in.}) \times 3.8 \text{ cm } (1\frac{1}{2} \text{ in.}), 12.7 \text{ cm } (5 \text{ in.}) \times 3.8 \text{ cm } (1\frac{1}{2} \text{ in.})$ | N/C | 48.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| Forks: | | |
| standard forks | N/C | 38.00 |
| high forks | N/C | 55.00 |
| fork stems, $+1.6 \text{ cm} (\frac{5}{8} \text{ in.}), +3.2 \text{ cm} (\frac{11}{4} \text{ in.})$ | 89.00 | N/A |
| Rear axles: | | |
| threaded axles | N/C | 5.00 |
| quick-release axles | N/C | 44.00 |
| plates for amputees | N/C | N/A |
| Component(s) under Special Consideration | | |
| spoke guards* | 114.00 | 57.00 |
| SUPPLIER: INVACARE CANADA INC. | | |
| | | PRICE |
| MANUAL WHEEL CHAIR MVP JR MODEL | | \$1 344.00 |

Body support system

- fixed back, height-adjustable from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- front seat height: from 37.5 cm $(14^{3}/_{4} \text{ in.})$ to 54.0 cm $(21^{1}/_{4} \text{ in.})$
- seat widths: 30.5 cm (12 in.), 32.5 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.)
- seat depth: from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- supple seat and back, nylon
- backposts, straight or with 10° angle, with push handles
- safety belt, velcro-type, auto-type

Armrests

- L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 25.4 cm (10 in.), short
- U-type armrests, detachable, flip-back, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long
- armrest pads, straight, short, long
- · armrest pads, tubular
- clothing guards, flexible, rigid, detachable

Footrests

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 37.5 cm (14³/4 in.) to 47.6 cm (18³/4 in.)
- 70° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 47.0 cm (18¹/₂ in.)
- 90° footrests, parallel, length-adjustable from 13.3 cm (5¹/₄ in.) to 26.0 cm (10¹/₄ in.)
- 60° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 38.1 cm (15 in.)

- 70° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 22.2 cm (8³/₄ in.) to 37.5 cm (14³/₄ in.)
- padded calfrests
- · folding footplates, standard
- full-width footrest, tubular
- heel loops, fixed
- heel loops, adjustable

Frame

- growth kit (once only during first three years from date of purchase, for first user)
- anti-tip rollers
- · push handles, integrated

Drive, brake, wheel, fork and axle systems

- plastic-coated handrims, smooth
- standard wheel locks, push-to-lock, pull-to-lock
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, solid tires, 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 7.6 cm (3 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, solid tires, 12.7 cm (5 in.) x 3.8 cm (1¹/₂ in.), 1 5.2 cm (6 in.) x 3.8 cm (1¹/₂ in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 4.4 cm (1³/₄ in.)
- standard forks, short
- threaded axles, quick-release

| | initial purchase or replacement of wheel chair (price per pair, as applicable) | replacement of component (unit price) |
|---|--|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| supple back, tension-adjustable | 80.00 | 133.00 |
| modification of back height to 50.8 cm (20 in.) | 32.00 | N/A |
| supple back, nylon | N/C | 53.00 |
| rigid seat, flat, lowered | 128.00 | 191.00 |
| supple seat, nylon | N/C | 63.00 |
| seat cushion, flat, foam, 5.1 cm (2 in.) | 59.00 | 59.00 |
| seat cushion, flat, foam, 7.6 cm (3 in.) | 59.00 | 59.00 |
| safety belt, velcro-type | N/C | 42.00 |
| safety belt, auto-type | N/C | 53.00 |

Price upon

Price upon

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| Armrests: | | |
| L-type armrests, detachable, swingaway, height-adjustable | | |
| from 20.3 cm (8 in.) to 25.4 cm (10 in.), short | N/C | 55.00 |
| U-type armrests, detachable, flip-back, height-adjustable | 2716 | 4.4.00 |
| from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long | N/C | 131.00 |
| T-type armrests, detachable, height-adjustable from 15.2 cm (6 in.) | | |
| to 25.4 cm (10 in.) or from 20.3 cm (8 in.) to 35.6 cm (14 in.), short, long | 152.00 | 131.00 |
| I-type armrests, height-adjustable from 12.7 cm (5 in.) | 132.00 | 131.00 |
| to 25.4 cm (10 in.), short, long | 92.00 | 101.00 |
| clothing guards, flexible | N/C | 48.00 |
| clothing guards, rigid, detachable | N/C | 48.00 |
| armrest pads, straight, short, long | N/C | 26.00 |
| armrest pads, tubular | N/C | 11.00 |
| modification of L-type armrest height, shortening by 2.5 cm (1 in.) | | |
| to 10.2 cm (4 in.) | 80.00 | N/A |
| Footrests: | | |
| 60° or 80° footrests, fixed, parallel, length-adjustable | 4== 00 | 4.00.00 |
| from 37.5 cm $(14^3/_4 \text{ in.})$ to 47.0 cm $(18^1/_2 \text{ in.})$ | 177.00 | 130.00 |
| 60° footrests, parallel, detachable, swingaway, length-adjustable | | |
| from 37.5 cm $(14^3/_4 \text{ in.})$ to 47.6 cm $(18^3/_4 \text{ in.})$; 70° footrests, parallel detachable, equipopoly langth adjustable from 34.3 cm $(13^3/_4 \text{ in.})$ | | |
| detachable, swingaway, length-adjustable from 34.3 cm $(13^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$ | N/C | 114.00 |
| 60° footrests, MFX, parallel, detachable, swingaway, | N/C | 114.00 |
| length-adjustable from 27.9 cm (11 in.) to 38.1 cm (15 in.) | N/C | 170.00 |
| 90° footrests, parallel, length-adjustable from 13.3 cm (5 ¹ / ₄ in.) | 140 | 170.00 |
| to 26.0 cm $(10^{1}/_{4} \text{ in.})$ | N/C | 170.00 |
| 70° footrests, MFX, parallel, detachable, swingaway, | | |
| length-adjustable from 22.2 cm ($8^3/_4$ in.) to 37.5 cm ($14^3/_4$ in.) | N/C | 170.00 |
| 70° footrests, tapered, detachable, length-adjustable | | |
| from 40.0 cm $(15^3/_4 \text{ in.})$ to 45.1 cm $(17^3/_4 \text{ in.})$ | 113.00 | 170.00 |
| elevating legrests, from 38.7 cm ($15^{1}/_{4}$ in.) to 54.0 cm ($21^{1}/_{4}$ in.) | 244.00 | 236.00 |
| elevating legrests with compensating mechanism, | 160.00 | 104.00 |
| from 40.6 cm (16 in.) to 53.3 cm (21 in.) padded calfrests | 160.00 | 194.00 |
| | N/C 25.00 | 28.00 37.00 |
| single calf strap louble calf strap | 38.00 | 55.00 |
| nodification of elevating legrest length by -2.5 cm (1 in.) or | 30.00 | 55.00 |
| by -5.1 cm (2 in.) | 250.00 | 250.00 |
| folding footplates, standard | N/C | 42.00 |
| neel loops, adjustable | N/C | 15.00 |
| neel loops, fixed | N/C | 7.00 |
| neel loops with ankle strap | 25.00 | 19.00 |
| full-width footrest, tubular, plastic-coated | 25.00 | 152.00 |
| full-width footrest, angle-adjustable | 72.00 | 199.00 |
| full-width footrest, tubular | N/C | 127.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| footplates, angle-adjustable, depth-adjustable, standard clamps, 1.9 cm (3/4 in.) to 2.5 cm (1 in.), making it possible to | 76.00 | 80.00 |
| install footplates higher up on footrest bracket | 30.00 | 15.00 |
| Frame: | | |
| back, angle-adjustable | 70.00 | 133.00 |
| growth kit (once only during first three years from date of purchase, | | |
| for first user) | N/C | N/A |
| oush handles, integrated | N/C | 38.00 |
| anti-tip rollers | N/C | 50.00 |
| cane holder | 34.00 | 34.00 |
| Drive systems: | | |
| nandrims with vertical or oblique projections | 155.00 | 125.00 |
| plastic-coated handrims | N/C | 63.00 |
| smooth handrims | N/C | 36.00 |
| Wheel locks: | | |
| standard wheel locks, push-to-lock, pull-to-lock | N/C | 46.00 |
| scissor-type wheel locks | 118.00 | 105.00 |
| wheel lock extensions | 34.00 | 17.00 |
| anti-rollback brakes | 94.00 | 93.00 |
| Wheels: | | |
| rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | | |
| 61.0 cm (24 in.) | N/C | 105.00 |
| rear mag wheels, standard pressure, 50.8 cm (20 in.), | | |
| 55.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 105.00 |
| poked rear wheels, high pressure, 61.0 cm (24 in.) | N/C | 142.00 |
| poked rear wheels, standard pressure, 50.8 cm (20 in.), | | |
| 55.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 142.00 |
| spoked rear wheels, solid tires, 61.0 cm (24 in.) | N/C | 142.00 |
| ear wheels, heavy-duty, standard pressure, high pressure, | | |
| solid tires, 61.0 cm (24 in.) | 82.00 | 183.00 |
| Front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.), | | |
| 7.6 cm (3 in.), 12.7 cm (5 in.), 15.2 cm (6 in.) | N/C | 40.00 |
| Front wheels, solid tires, 12.7 cm (5 in.) x 3.8 cm ($1^{1}/_{2}$ in.), | 3716 | 40.00 |
| $15.2 \text{ cm } (6 \text{ in.}) \times 3.8 \text{ cm } (1^{1}/_{2} \text{ in.})$ | N/C | 42.00 |
| Front wheels, inner tube tires, 15.2 cm (6 in.) x 3.2 cm ($1^{1}/_{4}$ in.), | 20.00 | o- |
| $20.3 \text{ cm } (8 \text{ in.}) \times 3.2 \text{ cm } (1^{1}/_{4} \text{ in.})$ | 30.00 | 55.00 |
| front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.) | N/C | 50.00 |
| Front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in. |) N/C | 63.00 |
| Forks: | | |
| standard forks, short | N/C | 52.00 |
| ork-locking mechanism | 100.00 | 50.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Rear axles: | | |
| threaded axles | N/C | 15.00 |
| quick-release axles | N/C | 53.00 |
| extension plates for amputees | 52.00 | 26.00 |
| Component(s) under Special Consideration | | |
| spoke guards* | 94.00 | 47.00 |
| quick-release axles with lever mechanism* | 76.00 | 53.00 |
| SUPPLIER: SUNRISE MEDICAL CANADA INC. | | |
| | | PRIC |
| MANUAL WHEEL CHAIR, CHILD, QUICKIE 2 MODEL | | \$1 540.0 |

Body support system

- supple back, nylon
- seat height: from 21.6 cm $(8^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$
- supple seat, nylon
- seat width: from 27.9 cm (11 in.) to 38.1 cm (15 in.)
- seat depths: 30.5 cm (12 in.), 35.6 cm (14 in.)
- front seat height: from 41.9 cm $(16^{1}/_{2} \text{ in.})$ to 54.6 cm $(21^{1}/_{2} \text{ in.})$
- safety belt, velcro-type, auto-type

Armrests

- L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- · armrest pads, straight, short, long
- armrest pads, tubular
- clothing guards, flexible

Footrests

- 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 90° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- 70° or 80° footrests, parallel, detachable, swingaway, length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.)
- padded calfrests
- padded calfrests for legrests with compensating mechanism
- heel loops, adjustable
- folding footplates, standard
- · folding footplates, tubular

Frame

- anti-tip rollers
- growth kit, including seat, back, footrests, front frame and crossbars (once only during first three years from date of purchase, for first user)
- push handles, integrated

Price unon

Drive, brake, wheel, fork and axle systems

- · plastic-coated handrims, smooth
- standard wheel locks, push-to-lock, pull-to-lock
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 15.2 cm (6 in.) x 3.2 cm (1¹/₄ in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1¹/₂ in.), 15.2 cm (6 in.) x 3.8 cm (1¹/₂ in.), 12.7 cm (5 in.) x 3.8 cm (1¹/₂ in.)
- standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5¹/₄ in.); high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- standard forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- fork stems, $+1.9 \text{ cm} (\frac{3}{4} \text{ in.})$, $+3.8 \text{ cm} (\frac{11}{2} \text{ in.})$
- multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- threaded axles, quick-release

| | initial purchase or replacement of wheel chair (price per pair, as applicable) | replacement of component (unit price) |
|--|--|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| supple back, tension-adjustable | 76.00 | 140.00 |
| supple back, nylon | N/C | 64.00 |
| supple seat, nylon | N/C | 55.00 |
| modification of seat depth to 25.4 cm (10 in.), 27.9 cm (11 in.) | | |
| or 33.0 cm (13 in.) | 40.00 | N/A |
| modification of seat width to 40.6 cm (16 in.) | 108.00 | N/A |
| modification of back height from 48.3 cm (19 in.) to 55.9 cm (22 | | N/A |
| seat cushion, flat, foam, 5.1 cm (2 in.) | 58.00 | 58.00 |
| seat cushion, flat, foam, 7.6 cm (3 in.) | 58.00 | 58.00 |
| seat cushion, flat, foam, 10.2 cm (4 in.) | 58.00 | 58.00 |
| safety belt, velcro-type | N/C | 29.00 |
| safety belt, auto-type | N/C | 42.00 |
| headrest mounting, articulated | 159.00 | 173.00 |
| headrest | 99.00 | 106.00 |

Price unon

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Armrests: | | |
| L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short T-type armrests, detachable, height-adjustable from | N/C | 96.00 |
| 19.1 cm ($7^{1}/_{2}$ in.) to 30.5 cm (12 in.), short, long I-type armrests, height-adjustable from 22.2 cm ($8^{3}/_{4}$ in.) | 78.00 | 135.00 |
| to 34.9 cm (13 ³ / ₄ in.), short | 300.00 | 246.00 |
| armrest pads, tubular | N/C | 2.00 |
| armrest pads, straight, long | N/C | 18.00 |
| armrest pads, straight, short | N/C | 15.00 |
| clothing guards, flexible | N/C | 22.00 |
| clothing guards, rigid | 92.00 | 68.00 |
| Footrests: | (4.00 | 07.00 |
| 70° or 80° footrests, heavy-duty | 64.00 | 87.00 |
| 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 90° footrests, parallel, detachable, swingaway, length-adjustable | N/C | 55.00 |
| from 20.3 cm (8 in.) to 33.0 cm (13 in.) 70° or 80° footrests, parallel, detachable, swingaway, | N/C | 55.00 |
| length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.) | N/C | 57.00 |
| 90° elevating legrests with compensating mechanism 90° elevating legrests, detachable, swingaway, length-adjustable | 200.00 | 155.00 |
| from 20.3 cm (8 in.) to 30.5 cm (12 in.) | 72.00 | 91.00 |
| elevating legrests nodification of footrest length from 17.8 cm (7 in.) | 108.00 | 109.00 |
| to 34.3 cm (13 ¹ / ₂ in.) modification of 90° footrest length by +5.1 cm (2 in.) or by | 56.00 | 34.00 |
| +10.2 cm (4 in.) | 32.00 | 16.00 |
| padded calfrests | N/C | 19.00 |
| contoured calfrests | 72.00 | 55.00 |
| padded calfrests for legrests with compensating mechanism | N/C | 40.00 |
| single calf strap | 19.00 | 19.00 |
| double calf strap | 33.00 | 33.00 |
| folding footplates, standard | N/C | 49.00 |
| folding footplates, tubular | N/C | 49.00 |
| folding footplates, angle-adjustable and depth-adjustable folding footplates, angle-adjustable, locking, width | 54.00 | 76.00 |
| of 35.6 cm (14 in.) and more | 80.00 | 178.00 |
| oversized footplates | 74.00 | 86.00 |
| full-width footrest, angle-adjustable | 85.00 | 183.00 |
| 90° full-width platform footrest | 92.00 | 190.00 |
| neel loops, adjustable | N/C | 10.00 |
| front floor rollers | 58.00 | 29.00 |
| front impact guard with rollers | 38.00 | 19.00 |
| Frame: | 107.00 | NT/A |
| folding back, angle-adjustable | 107.00 130.00 | N/A N/A |
| back spreader bar | 130.00 | IN/A |

| o () | Price upon nitial purchase or replacement of wheel chair price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| packposts, angle-adjustable from -3° to +15°, 3 positions packposts, at an 8° angle, from 31.8 cm (12¹/₂ in.) | 122.00 | N/A |
| o $47.0 \text{ cm} (18^{1}/_{2} \text{ in.})$ | 14.00 | 27.00 |
| bush handles, integrated | N/C | 20.00 |
| nti-tip rollers | N/C | 22.00 |
| ane holder | 45.00 | 45.00 |
| growth kit, including seat, back, footrests, front frame and crossbars (once only during first three years from date of | | |
| ourchase, for first user) | N/C | N/A |
| Orive systems: | T (0 0 0 0 | = 00.00 |
| one-arm dual handrim drive mooth handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), | 562.00 | 709.00 |
| 51.0 cm (24 in.) | N/C | 60.00 |
| andrims with vertical or oblique projections plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), | 90.00 | 105.00 |
| 51.0 cm (24 in.) | N/C | 88.00 |
| non-slip handrims, 55.9 cm (22 in.), 61.0 cm (24 in.) | 168.00 | 144.00 |
| mall plastic-coated handrim for one-arm drive | N/C | 97.00 |
| Wheel locks: | | |
| tandard wheel locks, push-to-lock, pull-to-lock | N/C | 40.00 |
| vheel lock extensions | 26.00 | 13.00 |
| nti-rollback brakes | 68.00 | 34.00 |
| wheel locks, push-to-lock, pull-to-lock, unilateral control | 128.00 | N/A |
| Wheels: | | |
| poked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | NUC | 1.50.00 |
| 51.0 cm (24 in.) | N/C | 153.00 |
| poked rear wheels, standard pressure, 50.8 cm (20 in.), | NIC | 126.00 |
| (5.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 136.00 |
| poked rear wheels, high pressure, 61.0 cm (24 in.) | N/C | 136.00 |
| ear mag wheels, standard pressure, 50.8 cm (20 in.) | N/C | 136.00 |
| ear mag wheels, standard pressure, 55.9 cm (22 in.), | N/C | 112.00 |
| 51.0 cm (24 in.) | N/C | 113.00 |
| ear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | N/C | 136.00 |
| 51.0 cm (24 in.) | | |
| ront wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) | N/C | 63.00 |
| ront wheels, solid tires, 15.2 cm (6 in.) ront wheels, solid tires, 12.7 cm (5 in.) | N/C N/C | 62.00 47.00 |
| ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 48.00 | 72.00 |
| ront wheels, inner tube tires, 20.3 cm (8 in.) x 3.1 cm (2 iii.) ront wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.) | 46.00 N/C | 63.00 |
| OHE WINGER THIELDING THES 70 FCM LATHERS 3 / CHILL 1/10 F | | 62.00 |
| | | |
| ront wheels, inner tube tires, 15.2 cm (6 in.) x 3.2 cm ($1^{1}/_{4}$ in.) | N/C | 02.00 |
| ront wheels, inner tube tires, 15.2 cm (6 in.) x 3.2 cm ($1^{1}/_{4}$ in.) ront wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm ($1^{1}/_{2}$ in.), | | |
| ront wheels, inner tube tires, 15.2 cm (6 in.) x 3.2 cm ($1^{1}/_{4}$ in.) | | 89.00 81.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Forks: | | |
| standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); | | |
| high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), | NIC | 22.00 |
| 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels | N/C | 32.00 |
| standard forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels | N/C | 37.00 |
| fork-locking mechanism | 46.00 | 23.00 |
| fork stems, $+1.9 \text{ cm } (\frac{3}{4} \text{ in.}), +3.8 \text{ cm } (\frac{1}{2} \text{ in.})$ | N/C | 16.00 |
| multi-position forks for 12.7 cm (5 in.), 15.2 cm (6 in.) | | |
| and 20.3 cm (8 in.) wheels | N/C | 56.00 |
| Rear axles: | | |
| quick-release axles | N/C | 33.00 |
| threaded axles | N/C | 33.00 |
| extension plates for amputees | 42.00 | 73.00 |
| curved plates | 28.00 | 66.00 |
| Component(s) under Special Consideration | | |
| spoke guards* | 70.00 | 35.00 |
| quick-release axles with lever mechanism* | 66.00 | 66.00 |
| SUPPLIER: SUNRISE MEDICAL CANADA INC. | | |
| | | PRI |

PRICE

MANUAL WHEEL CHAIR, CHILD, ZIPPIE GS MODEL

\$1 475.00

Basic Components

Body support system

- supple back, nylon
- seat height: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- · rigid seat, flat
- seat width: from 25.4 cm (10 in.) to 40.6 cm (16 in.)
- seat depth: from 25.4 cm (10 in.) to 45.7 cm (18 in.)
- front seat height: from 35.6 cm (14 in.) to 47.6 cm (18³/₄ in.)
- safety belt, velcro-type, auto-type

Armrests

- T-type armrests, detachable, height-adjustable from 19.1 cm (7½ in.) to 30.5 cm (12 in.), short, long
- T-type armrests, height-adjustable to 14.0 cm ($5^{1}/_{2}$ in.), 16.5 cm ($6^{1}/_{2}$ in.) or 19.1 cm (7¹/₂ in.), short
- · armrest pads, straight, short, long
- armrest pads, tubular
- clothing guards, flexible

Footrests

- 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 90° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- 70° or 80° footrests, parallel, detachable, swingaway, length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.)
- 70°, 80°, or 90° footrests, heavy-duty, detachable, non-flip-back
- heel loops, adjustable
- folding footplates, standard
- padded calfrests for elevating legrests with compensating mechanism
- padded calfrests for elevating legrests

Frame

- · optional heavy-duty frame
- anti-tip rollers
- · folding back, angle-adjustable
- push handles, integrated
- backposts, with push handles at $55.2 \text{ cm} (21^3/_4 \text{ in.})$, $62.9 \text{ cm} (24^3/_4 \text{ in.})$, $70.5 \text{ cm} (27^3/_4 \text{ in.})$

- plastic-coated handrims, smooth
- standard wheel locks, push-to-lock, pull-to-lock
- spoked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.)
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1¹/₂ in.), 15.2 cm (6 in.) x 3.8 cm (1¹/₂ in.), 12.7 cm (5 in.) x 3.8 cm (1¹/₂ in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 15.2 cm (6 in.) x 3.2 cm (1¹/₄ in.)
- rear wheel camber, from 0° to 6°
- standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5¹/₄ in.); high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- fork stems, $+1.9 \text{ cm} (\frac{3}{4} \text{ in.})$, $+3.8 \text{ cm} (\frac{1}{2} \text{ in.})$
- threaded axles, quick-release

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|--|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: headrest, small, medium, large transversal bar for headrest mounting (folding) headrest mounting, articulated transversal bar for headrest mounting (rigid) supple back, tension-adjustable supple back, nylon rigid seat, flat seat cushion, flat, foam, 5.1 cm (2 in.) seat cushion, flat, foam, 7.6 cm (3 in.) safety belt, velcro-type safety belt, auto-type safety belt, airplane-type safety belt, airplane-type, padded | 99.00 233.00 159.00 200.00 76.00 N/C N/C 58.00 58.00 N/C N/C 50.00 76.00 | 106.00 249.00 173.00 212.00 140.00 64.00 130.00 58.00 58.00 29.00 42.00 79.00 105.00 |
| Armrests: T-type armrests, detachable, height-adjustable from 19.1 cm (7 ¹ / ₂ in.) to 30.5 cm (12 in.), short, long I-type armrests, with latch, depth-adjustable, height-adjustable from 16.5 cm (6 ¹ / ₂ in.) to 33.0 cm (13 in.), short, long T-type armrests, height-adjustable to 14.0 cm (5 ¹ / ₂ in.), 16.5 cm (6 ¹ / ₂ in.) or 19.1 cm (7 ¹ / ₂ in.), short armrest pads, tubular armrest pads, straight, long armrest pads, straight, short clothing guards, rigid clothing guards, flexible | N/C 130.00 N/C N/C N/C N/C N/C 92.00 N/C | 135.00 200.00 160.00 2.00 18.00 15.00 68.00 22.00 |
| Footrests: 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 90° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) 70° or 80° footrests, parallel, detachable, swingaway, length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.) 70°, 80° or 90° footrests, heavy-duty, detachable, non-flip-back elevating legrests with compensating mechanism 90° elevating legrests, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) elevating legrests padded calfrests for elevating legrests contoured calfrests padded calfrests for elevating legrests with compensating mechanism | N/C N/C N/C N/C 200.00 70.00 108.00 N/C 72.00 | 55.00 57.00 57.00 87.00 155.00 90.00 109.00 19.00 55.00 40.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| modification of footrest length from 48.3 cm (19 in.) | | |
| to 52.1 cm $(20^{1}/_{2} in.)$ | 31.00 | 30.00 |
| modification of footrest length by +5.1 cm (2 in.) or by | | |
| +10.2 cm (4 in.) | 32.00 | 16.00 |
| single calf strap | 19.00 | 19.00 |
| double calf strap | 33.00 | 33.00 |
| folding footplates, standard | N/C | 49.00 |
| olding footplates, standard, angle-adjustable and depth-adjustable | 54.00 | 76.00 |
| full-width footrest | 85.00 | 183.00 |
| neel loops, adjustable | N/C | 10.00 |
| 90° foot platform, rigid | 92.00 | 190.00 |
| Cootrest brackets, from 17.8 cm (7 in.) to 34.3 cm $(13^{1}/_{2} \text{ in.})$ | 56.00 | 34.00 |
| Frame: anti-tip rollers | N/C | 22.00 |
| Front anti-tip devices | 58.00 | 29.00 |
| cane holder | 45.00 | 45.00 |
| olding back, angle-adjustable | N/C | N/A |
| bush handles, integrated | N/C | N/A |
| packposts, with push handles at 55.2 cm (21 ³ / ₄ in.), | 1,70 | 1,712 |
| $52.9 \text{ cm } (24^3/_4 \text{ in.}), 70.5 \text{ cm } (27^3/_4 \text{ in.})$ | N/C | N/A |
| optional heavy-duty frame | N/C | N/A |
| pack spreader bar | 130.00 | N/A |
| Orive systems: | | |
| one-arm dual handrim drive | 562.00 | 709.00 |
| mooth handrims | N/C | 60.00 |
| andrims with vertical or oblique projections, 61.0 cm (24 in.) | 90.00 | 105.00 |
| lastic-coated handrims | N/C | 88.00 |
| on-slip handrims, 55.9 cm (22 in.), 61.0 cm (24 in.) | 168.00 | 144.00 |
| mall plastic-coated handrim for one-arm drive | N/C | 97.00 |
| Vheel locks: tandard wheel locks, push-to-lock, pull-to-lock | N/C | 40.00 |
| wheel lock extensions | 26.00 | 13.00 |
| nti-rollback brakes | 68.00 | 34.00 |
| Vheels: | | |
| poked rear wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | NIC | 1.50.00 |
| 1.0 cm (24 in.) | N/C | 153.00 |
| poked rear wheels, standard pressure, 50.8 cm (20 in.), | NIC | 106.00 |
| 5.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 136.00 |
| poked rear wheels, high pressure, 61.0 cm (24 in.) | N/C | 136.00 |
| ear mag wheels, standard pressure, 50.8 cm (20 in.) | N/C | 136.00 |
| ear mag wheels, standard pressure, 55.9 cm (22 in.), | N/C | 112.00 |
| 1.0 cm (24 in.) | N/C | 113.00 |
| ear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | N/C | 126.00 |
| 1.0 cm (24 in.) | N/C | 136.00 |
| ear mag wheels, standard pressure, 30.5 cm (12 in.) | N/C | 130.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| rear mag wheels, standard pressure, 40.6 cm (16 in.) | 32.00 | 146.00 |
| front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) | N/C | 63.00 |
| front wheels, solid tires, 15.2 cm (6 in.) | N/C | 62.00 |
| front wheels, solid tires, 12.7 cm (5 in.) | N/C | 47.00 |
| front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 48.00 | 72.00 |
| front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.) | N/C | 63.00 |
| front wheels, inner tube tires, 15.2 cm (6 in.) x 3.2 cm ($1^{1}/_{4}$ in.) front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm ($1^{1}/_{2}$ in. | N/C), | 62.00 |
| 15.2 cm (6 in.) x $3.\hat{8}$ cm ($1^{1}/_{2}$ in.) | N/C | 89.00 |
| front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1 ¹ / ₂ in. |) N/C | 99.00 |
| rear wheel camber, from 0° to 6° | N/C | N/A |
| Forks: standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5 ¹ / ₄ in.); high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels fork-locking mechanism fork stems, +1.9 cm (³ / ₄ in.), +3.8 cm (1 ¹ / ₂ in.), long | N/C 46.00 N/C | 32.00 23.00 16.00 |
| Rear axles: threaded axles, quick-release | N/C | 33.00 |
| Component(s) under Special Consideration spoke guards* | 70.00 | 35.00 |
| | | |

§2. Lightweight manual wheel chairs

SUPPLIER: INVACARE CANADA INC.

PRICE

LIGHTWEIGHT MANUAL WHEEL CHAIR A-4 MODEL

\$1 575.00

Basic Components

Body support system

- supple seat and back, nylon
- front seat height: from 43.2 cm (17 in.) to 53.3 cm (21 in.)
- seat width: from 30.5 cm (12 in.) to 50.8 cm (20 in.)
- seat depth: from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- safety belt, velcro-type, auto-type

Armrests

- L-type armrests, detachable, swingaway, height-adjustable from 22.9 cm (9 in.) to 27.9 cm (11 in.), short
- armrest pads, tubular
- armrest pads, straight, short, long
- clothing guards, flexible, rigid

Footrests

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 37.5 cm (14³/₄ in.) to 47.0 cm (18¹/₂ in.); 70° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 47.0 cm (18¹/₂ in.)
- 60° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 38.1 cm (15 in.); 70° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 22.2 cm (8³/₄ in.) to 37.5 cm (14³/₄ in.)
- 80° footrests, fixed, pointing inwards, tapered, length-adjustable from 28.6 cm (11¹/₄ in.) to 51.4 cm (20¹/₄ in.)
- · folding footplates, standard
- · full-width footrest
- · full-width footrest, angle-adjustable and depth-adjustable
- single calf strap
- · heel loops, fixed, adjustable on swingaway footrests only

Frame

- · anti-tip rollers
- folding back, height-adjustable from 20.3 cm (8 in.) to 50.8 cm (20 in.)
- push handles, bolt-on, integrated

Drive, brake, wheel, fork and axle systems

- smooth handrims
- scissor-type wheel locks, standard, push-to-lock, pull-to-lock
- spoked rear wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear wheels, heavy-duty, standard pressure, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- rear mag wheels, standard pressure, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, solid tires, high pressure, 61.0 cm (24 in.)
- front wheels, solid tires, 7.6 cm (3 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 2.5 cm (1 in.), 10.2 cm (4 in.) x 2.5 cm (1 in.)
- front wheels, solid tires, 12.7 cm (5 in.) x 3.8 cm (1¹/₂ in.), 15.2 cm (6 in.) x 3.8 cm (1¹/₂ in.)
- · standard forks, short
- quick-release axles
- double camber tubes for the following angles: 0°, 3°, 6°, 9°, 12°

| Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|
|--|---|

Basic and Optional Components

Body support system

Seat and back:

modification of seat width to 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.) or 55.9 cm (22 in.)

62.00

| -type armrests, detachable, swingaway, height-adjustable rom $22.9 \text{ cm } (9 \text{ in.}) \text{ to } 27.9 \text{ cm } (11 \text{ in.}), \text{ short}$ -type armrests, height-adjustable from $15.2 \text{ cm } (6 \text{ in.})$ -5 25.4 cm (10 in.) or from $20.3 \text{ cm } (8 \text{ in.})$ to $35.6 \text{ cm } (14 \text{ in.})$, hort, long -6 15.4 cm (10 in.) or from $20.3 \text{ cm } (8 \text{ in.})$ to $35.6 \text{ cm } (14 \text{ in.})$, hort, long -7 15.2 cm (10 in.) or from $20.3 \text{ cm } (8 \text{ in.})$ to $35.6 \text{ cm } (14 \text{ in.})$, hort, long -7 15.2 cm (14 in.) to $35.6 \text{ cm } (14 \text{ in.})$, hort, long -7 16 26.0 lothing guards, flexible -7 17 26.0 lothing guards, rigid -7 27 26.0 lothing guards, straight, short, long -7 28 28 28 28 28 28 28 28 28 28 28 28 28 | | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|--|---|
| r 55.9 cm (22 in.) | modification of seat depth to 48.3 cm (19 in.), 50.8 cm (20 in.) | | |
| upple back, tension-adjustable 80.00 133.00 upple back, nylon N/C 53.00 upple seat, nylon N/C 63.00 eat cushion, flat, foam, 5.1 cm (2 in.) 59.00 59.00 eat cushion, flat, foam, 7.6 cm (3 in.) 59.00 59.00 act cushion, flat, foam, 7.6 cm (3 in.) 59.00 59.00 afety belt, velcro-type N/C 42.00 afety belt, auto-type N/C 42.00 afety belt, auto-type N/C 53.00 ***Type armrests, detachable, swingaway, height-adjustable ***Type armrests, height-adjustable from 15.2 cm (6 in.) ****Type armrests, height-adjustable from 15.2 cm (6 in.) ****Type armrest, height-adjustable from 15.2 cm (6 in.) ****Type armrest, height-adjustable from 15.2 cm (6 in.) ****Type armrest, ads.***Type armset, height-adjustable from 8.0 cm (14 in.), hor 15.0 cm (18 in.) ****Type armset, ads.***Type armset, ads.***Type armset, ads.***Type armset, ads.***Type armset, ads.***Type armset, ads.**Type armset, ads.***Type armset, ads.**Type armset, ads.***Type armset, ads.***Type armset, ads.***Type armset, ads.***Type | | 62.00 | N/A |
| upple back, nylon N/C 53.00 upple seat, nylon N/C 63.00 eat cushion, flat, foam, $7.6 \text{cm} (3 \text{in.})$ 59.00 59.00 afety belt, clero-type N/C 42.00 afety belt, clero-type N/C 45.00 afety belt, auto-type N/C 53.00 Armrests: -type armrests, detachable, swingaway, height-adjustable rom 22.9 cm (9 in.) to 27.9 cm (11 in.), short N/C 55.00 type armrests, height-adjustable from 15.2 cm (6 in.) N/C 55.00 25.4 cm (10 in.) or from 20.3 cm (8 in.) to 35.6 cm (14 in.), 152.00 131.00 lothing guards, flexible N/C 48.00 lothing guards, rigid N/C 48.00 mrest pads, tubular N/C 48.00 rom 28.6 cm (11½, in.) to 51.4 cm (20½, in.) N/C N/C colorests: 0° footrests, fixed, tapered, pointing inwards, length-adjustable N/C N/C rom 28.6 cm (11½, in.) to 51.4 cm (20½, in.) N/C N/C N/A 0° footrests, parallel, detachable, swingaway, length-adjustable N/C N/C rom 37.5 cm (14½, in.) to 51.4 cm | | | |
| uipple seat, nylon N/C 63.00 eat cushion, flat, foam, 5.1 cm (2 in.) 59.00 59.00 eat cushion, flat, foam, 5.1 cm (2 in.) 59.00 59.00 afety belt, velcro-type N/C 42.00 afety belt, auto-type N/C 53.00 **Type armrests, detachable, swingaway, height-adjustable from 22.9 cm (9 in.) to 27.9 cm (11 in.), short N/C 55.00 -type armrests, height-adjustable from 15.2 cm (6 in.) 52.5.4 cm (10 in.) or from 20.3 cm (8 in.) to 35.6 cm (14 in.), 55.00 -type armrests, height-adjustable from 15.2 cm (6 in.) 52.5.4 cm (10 in.) or from 20.3 cm (8 in.) to 35.6 cm (14 in.), 55.00 bothing guards, flexible N/C 48.00 lothing guards, rigid N/C 48.00 mrest pads, tubular N/C 11.00 coutrests 0° footrests, fixed, tapered, pointing inwards, length-adjustable rom 28.6 cm (11½, in.) to 51.4 cm (20½, in.) N/C N/C cotrests, parallel, detachable, swingaway, length-adjustable rom 37.5 cm (14½, in.) to 47.0 cm (18½); 70° footrests, parallel, detachable, swingaway, length-adjustable rom 13.3 cm (5½, in.) to 26.7 cm (10½, in.) N/C 114.00 0° footrests, tapered, detachable, swingaway, length-adjustable rom 40 | | | |
| $\begin{array}{c} {\rm cal\ cushion,\ flat,\ foam,\ 5.1\ cm\ (2\ in)} \\ {\rm cal\ cushion,\ flat,\ foam,\ 7.6\ cm\ (3\ in.)} \\ {\rm 59.00} \\ {\rm 42.00} \\ {\rm affety\ belt,\ auto-type} \\ {\rm N/C} \\ {\rm 53.00} \\ {\rm cmrests:} \\ \\ {\rm ctype\ armrests,\ detachable,\ swingaway,\ height-adjustable\ rom\ 22.9\ cm\ (9\ in.)\ to\ 27.9\ cm\ (11\ in.),\ short \\ {\rm 100\ in.} \\ {\rm 50.00\ in.} \\ {\rm 152.00\ in.} \\ {\rm 50.00\ $ | | | |
| eat cushion, flat, foam, 7.6 cm (3 in.) afety belt, velcro-type AVC 42.00 afety belt, auto-type N/C 53.00 AVC 42.00 afety belt, auto-type N/C 53.00 AVC 53.00 AVC 53.00 AVC 53.00 AVC 53.00 AVC 55.00 AVC 60.01 AVC 60.01 AVC 60.01 AVC 60.01 AVC 60.01 AVC 60.00 A | | | |
| afety belt, velcro-type afety belt, auto-type | | | |
| Armrests | | | |
| **Timprests:**type armrests, detachable, swingaway, height-adjustable rom 22.9 cm (9 in.) to 27.9 cm (11 in.), short | | | |
| rom 22.9 cm (9 in.) to 27.9 cm (1 in.), short | Armrests: | 100 | 23.00 |
| Type armrests, height-adjustable from 15.2 cm (6 in.) by 25.4 cm (10 in.) or from 20.3 cm (8 in.) to 35.6 cm (14 in.), hort, long | | | |
| $\begin{array}{c} 25.4 \text{ cm} & (10 \text{ in.}) \text{ or from } 20.3 \text{ cm} & (8 \text{ in.}) \text{ to } 35.6 \text{ cm} & (14 \text{ in.}), \\ \text{hort, long} & 131.00 \\ \text{lothing guards, flexible} & N/C & 48.00 \\ \text{lothing guards, rigid} & N/C & 11.00 \\ \text{rmrest pads, tubular} & N/C & 11.00 \\ \text{rmrest pads, tubular} & N/C & 11.00 \\ \text{rmrest pads, tubular} & N/C & 26.00 \\ \hline \\ \textbf{Footrests} & \textbf{fixed}, \text{ tapered, pointing inwards, length-adjustable} \\ \text{rom } 28.6 \text{ cm} & (11^{1}/_4 \text{ in.}) \text{ to } 51.4 \text{ cm} & (20^{1}/_4 \text{ in.}) \\ \textbf{o}^{\circ} \text{ footrests, parallel, detachable, swingaway, length-adjustable} \\ \text{rom } 37.5 \text{ cm} & (14^{1}/_4 \text{ in.}) \text{ to } 47.0 \text{ cm} & (18^{1}/_2) \text{ in.} \\ \textbf{o} \text{ of footrests, parallel, detachable, swingaway, length-adjustable} \\ \text{rom } 13.3 \text{ cm} & (5^{1}/_4 \text{ in.}) \text{ to } 26.7 \text{ cm} & (10^{1}/_2 \text{ in.}) \\ \textbf{o}^{\circ} \text{ footrests, parallel, detachable, swingaway, length-adjustable} \\ \text{rom } 13.3 \text{ cm} & (5^{1}/_4 \text{ in.}) \text{ to } 50.2 \text{ cm} & (19^{1}/_4 \text{ in.}) \\ \textbf{o}^{\circ} \text{ footrests, parallel, detachable, swingaway, length-adjustable} \\ \text{rom } 13.3 \text{ cm} & (5^{1}/_4 \text{ in.}) \text{ to } 50.2 \text{ cm} & (19^{1}/_4 \text{ in.}) \\ \textbf{o}^{\circ} \text{ footrests, parallel, detachable, swingaway, length-adjustable} \\ \text{rom } 40.0 \text{ cm} & (15^{1}/_4 \text{ in.}) \text{ to } 50.2 \text{ cm} & (19^{1}/_4 \text{ in.}) \\ \textbf{o}^{\circ} \text{ footrests, MFX, parallel, detachable, swing-away,} \\ \text{ength-adjustable from } 27.9 \text{ cm} & (11 \text{ in.}) \text{ to } 38.1 \text{ cm} & (15 \text{ in.}); \\ \textbf{o}^{\circ} \text{ footrests, MFX, parallel, detachable, swing-away,} \\ \text{ength-adjustable from } 27.9 \text{ cm} & (11 \text{ in.}) \text{ to } 37.5 \text{ cm} & (14^{1}/_4 \text{ in.}) \\ \text{ingle calf strap} & 38.00 & 55.00 \\ \text{oblding footplates, standard} & N/C & 37.00 \\ \text{ouble calf strap} & 38.00 & 55.00 \\ \text{olding footplates, and and depth-adjustable} & 76.00 & 80.00 \\ \text{all-width footrest} & 45.00 & 65.00 \\ \text{tandard footplates, angle-adjustable and depth-adjustable} & 76.00 & 80.00 \\ \text{all-width footrest, angle-adjustable and depth-adjustable} & 76.00 & 80.00 \\ all-width footrest, a$ | | N/C | 55.00 |
| hort, long hort, long lothing guards, flexible hothing guards, flexible hothing guards, rigid N/C 48.00 mrest pads, tubular N/C 11.00 mrest pads, tubular N/C 11.00 mrest pads, straight, short, long N/C 26.00 Notrests: 0° footrests; 0° footrests, fixed, tapered, pointing inwards, length-adjustable rom 28.6 cm (11 1 /4 in.) to 51.4 cm (20 1 /4 in.) 0° footrests, parallel, detachable, swingaway, length-adjustable rom 37.5 cm (14 1 /4 in.) to 47.0 cm (18 1 /5); 70° footrests, parallel, etachable, swingaway, length-adjustable rom 34.3 cm (13 1 /2 in.) 0° footrests, parallel, detachable, swingaway, length-adjustable rom 13.3 cm (5 1 /4 in.) to 26.7 cm (10 1 /2 in.) 0° footrests, parallel, detachable, swingaway, length-adjustable rom 40.0 cm (15 1 /4 in.) to 50.2 cm (19 3 /4 in.) 113.00 170.00 0° footrests, MFX, parallel, detachable, swing-away, ength-adjustable from 27.9 cm (11 in.) to 38.1 cm (15 in.); 0° footrests, MFX, parallel, detachable, swing-away, ength-adjustable from 22.2 cm (8 3 /4 in.) to 37.5 cm (14 3 /4 in.) 0° footrests, MFX, parallel, detachable, swingaway, ength-adjustable from 22.2 cm (8 3 /4 in.) to 37.5 cm (14 3 /4 in.) N/C 37.00 ouble calf strap 38.00 55.00 olding footplates, standard N/C 42.00 ull-width footrest with N/C 63.00 tandard footplates, angle-adjustable and depth-adjustable N/C 98.00 versized footplates, 18.4 cm (7 1 /4 in.), angle-adjustable and epth-adjustable not epth-adjustable not phase, 1.87 cm (7 /4 in.), angle-adjustable and epth-adjustable not epth-adjustable, no swingaway footrests only N/C 15.00 | | | |
| lothing guards, flexible N/C 48.00 lothing guards, rigid N/C 48.00 mrest pads, tubular N/C 11.00 mrest pads, straight, short, long N/C 26.00 lothests; 0° footrests; 0° footrests, fixed, tapered, pointing inwards, length-adjustable rom 28.6 cm (11½ in.) to 51.4 cm (20¼ in.) N/C N/A 0° footrests, parallel, detachable, swingaway, length-adjustable rom 37.5 cm (14½ in.) to 47.0 cm (18½); 70° footrests, parallel, etachable, swingaway, length-adjustable rom 34.3 cm (13½ in.) 0° footrests, parallel, detachable, swingaway, length-adjustable rom 13.3 cm (5½ in.) to 26.7 cm (10½ in.) N/C 114.00 0° footrests, parallel, detachable, swingaway, length-adjustable rom 13.3 cm (5½ in.) to 50.2 cm (10½ in.) 113.00 170.00 0° footrests, tapered, detachable, swingaway, length-adjustable rom 40.0 cm (15½ in.) to 50.2 cm (19¼ in.) 113.00 170.00 0° footrests, MFX, parallel, detachable, swingaway, ength-adjustable from 27.9 cm (11 in.) to 38.1 cm (15 in.); 0° footrests, MFX, parallel, detachable, swingaway, ength-adjustable from 22.2 cm (8¼ in.) to 37.5 cm (14¼ in.) N/C 114.00 ingle calf strap 38.00 55.00 olding footplates, standard N/C 42.00 wresized footplates, standard N/C 42.00 ingle calf strap N/C 63.00 versized footplates, angle-adjustable and depth-adjustable N/C 98.00 versized footplates, 18.4 cm (7% in.), angle-adjustable and epth-adjustable oversized footplates, 18.4 cm (7% in.), angle-adjustable and epth-adjustable oversized footplates, 18.4 cm (7% in.), angle-adjustable and epth-adjustable oversized footplates, higher up on the footrest bracket 30.00 15.00 eel loops, adjustable, on swingaway footrests only N/C 15.00 | | | |
| lothing guards, rigid N/C 11.00 rmrest pads, tubular N/C 11.00 rmrest pads, tubular N/C 11.00 rmrest pads, straight, short, long N/C 11.00 N/C 11.00 rmrest pads, straight, short, long N/C 26.00 N/C N/A 26.00 N/C 114.00 N/C N/A 114.00 N/A 114.0 | short, long | | |
| lothing guards, rigid N/C 11.00 rmrest pads, tubular N/C 11.00 rmrest pads, tubular N/C 11.00 rmrest pads, straight, short, long N/C 11.00 N/C 11.00 rmrest pads, straight, short, long N/C 26.00 N/C N/A 26.00 N/C 114.00 N/C N/A 114.00 N/A 114.0 | clothing guards, flexible | N/C | 48.00 |
| ### Process of Cootrests of Cootrests of Cootrests of Cootrests of Cootrests of Cootrests of Cootrests, fixed, tapered, pointing inwards, length-adjustable of Cootrests, parallel, detachable, swingaway, length-adjustable of Cootrests, tapered, detachable, swingaway, length-adjustable of Cootrests, MFX, parallel, detachable, swingaway, length-adjustable of Cootrests, MFX, parallel, detachable, swing-away, ength-adjustable from 27.9 cm (11 in.) to 38.1 cm (15 in.); of Cootrests, MFX, parallel, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 38.1 cm (15 in.); of Cootrests, MFX, parallel, detachable, swingaway, ength-adjustable from 22.2 cm (8³/₄ in.) to 37.5 cm (14³/₄ in.) ### N/C ### 114.00 ### 114.00 ### 114.00 ### 115.00 ### 116.00 ## | clothing guards, rigid | | 48.00 |
| Footrests: 0° footrests, fixed, tapered, pointing inwards, length-adjustable rom $28.6 \text{ cm} (11^{1}/_4 \text{ in.})$ to $51.4 \text{ cm} (20^{1}/_4 \text{ in.})$ m/C 0° footrests, parallel, detachable, swingaway, length-adjustable rom $37.5 \text{ cm} (14^{1}/_4 \text{ in.})$ to $47.0 \text{ cm} (18^{1}/_2)$; 70° footrests, parallel, etachable, swingaway, length-adjustable from $34.3 \text{ cm} (13^{1}/_2 \text{ in.})$ m/C $114.00 \text{ cm} (18^{1}/_2)$ m/C $114.00 \text{ cm} (15^{1}/_4 \text{ in.})$ to $26.7 \text{ cm} (10^{1}/_2 \text{ in.})$ m/C $113.00 \text{ cm} (15.00 \text{ cm} (10.1) \text{ cm} (10.1) \text{ cm} (10.1)$ m/C $113.00 \text{ cm} (10.1) \text{ cm} (1$ | rmrest pads, tubular | N/C | 11.00 |
| $\begin{array}{cccccccccccccccccccccccccccccccccccc$ | rmrest pads, straight, short, long | N/C | 26.00 |
| $\begin{array}{c} 0.47.0\ \text{cm}\ (18^{1}/_{2}) \\ 0^{\circ}\ \text{footrests, parallel, detachable, swingaway, length-adjustable} \\ \text{rom}\ 13.3\ \text{cm}\ (5^{1}/_{4}\ \text{in.})\ \text{to}\ 26.7\ \text{cm}\ (10^{1}/_{2}\ \text{in.}) \\ 0^{\circ}\ \text{footrests, tapered, detachable, swingaway, length-adjustable} \\ \text{rom}\ 40.0\ \text{cm}\ (15^{3}/_{4}\ \text{in.})\ \text{to}\ 50.2\ \text{cm}\ (19^{3}/_{4}\ \text{in.}) \\ \text{o}^{\circ}\ \text{footrests, MFX, parallel, detachable, swing-away,} \\ \text{ength-adjustable from}\ 27.9\ \text{cm}\ (11\ \text{in.})\ \text{to}\ 38.1\ \text{cm}\ (15\ \text{in.}); \\ 0^{\circ}\ \text{footrests, MFX, parallel, detachable, swingaway,} \\ \text{ength-adjustable from}\ 22.2\ \text{cm}\ (8^{3}/_{4}\ \text{in.})\ \text{to}\ 37.5\ \text{cm}\ (14^{3}/_{4}\ \text{in.}) \\ \text{ingle calf strap} \\ \text{ouble calf strap} \\ \text{olding footplates, standard} \\ \text{olding footplates, standard} \\ \text{olding footplates, standard} \\ \text{olding footplates, standard} \\ \text{olding footplates, angle-adjustable and depth-adjustable} \\ \text{versized footplates, angle-adjustable and depth-adjustable} \\ \text{value, the footrest, angle-adjustable and depth-adjustable} \\ \text{versized footplates, } 18.4\ \text{cm}\ (7^{1}/_{4}\ \text{in.}), \text{ angle-adjustable and} \\ \text{epth-adjustable} \\ \text{lamps, } 1.87\ \text{cm}\ (3^{1}/_{4}\ \text{in.}), \text{ to}\ 2.5\ \text{cm}\ (1\ \text{in.}), \text{ making it possible to} \\ \text{stall footplates higher up on the footrest bracket} \\ \text{soloo} \\ \text{eel loops, adjustable, on swingaway footrests only} \\ \text{N/C} \\ \text{15.00} \\ 15$ | 80° footrests, fixed, tapered, pointing inwards, length-adjustable from 28.6 cm (11¹/₄ in.) to 51.4 cm (20¹/₄ in.) 60° footrests, parallel, detachable, swingaway, length-adjustable from 37.5 cm (14³/₄ in.) to 47.0 cm (18¹/₂); 70° footrests, parallel, | N/C | N/A |
| rom 13.3 cm $(5^{1}/_{4} \text{ in.})$ to 26.7 cm $(10^{1}/_{2} \text{ in.})$ 113.00 170.00 0° footrests, tapered, detachable, swingaway, length-adjustable rom 40.0 cm $(15^{3}/_{4} \text{ in.})$ to 50.2 cm $(19^{3}/_{4} \text{ in.})$ 113.00 170.00 0° footrests, MFX, parallel, detachable, swing-away, ength-adjustable from 27.9 cm (11 in.) to 38.1 cm (15 in.) ; 0° footrests, MFX, parallel, detachable, swingaway, ength-adjustable from 22.2 cm $(8^{3}/_{4} \text{ in.})$ to 37.5 cm $(14^{3}/_{4} \text{ in.})$ N/C 114.00 ingle calf strap N/C 37.00 ouble calf strap 38.00 55.00 all-width footrest N/C 42.00 ull-width footrest N/C 42.00 ull-width footrest N/C 42.00 all-width footrest N/C 63.00 versized footplates, angle-adjustable and depth-adjustable N/C 98.00 versized footplates, 18.4 cm $(7^{1}/_{4} \text{ in.})$, angle-adjustable and epth-adjustable and epth-adjustable and epth-adjustable not stall footplates higher up on the footrest bracket 30.00 15.00 eel loops, adjustable, on swingaway footrests only N/C 15.00 | o $47.0 \text{ cm} (18^{1}/_{2})$ | N/C | 114.00 |
| rom $40.0 \text{ cm } (15^3/_4 \text{ in.}) \text{ to } 50.2 \text{ cm } (19^3/_4 \text{ in.})$ $0^\circ \text{ footrests, MFX, parallel, detachable, swing-away, ength-adjustable from } 27.9 \text{ cm } (11 \text{ in.}) \text{ to } 38.1 \text{ cm } (15 \text{ in.});$ $0^\circ \text{ footrests, MFX, parallel, detachable, swingaway, ength-adjustable from } 22.2 \text{ cm } (8^3/_4 \text{ in.}) \text{ to } 37.5 \text{ cm } (14^3/_4 \text{ in.})$ single calf strap ouble calf strap ouble calf strap $\text{olding footplates, standard}$ $\text{olding footplates, standard}$ olding footplates $\text{versized footplates}$ $\text{to } 0$ $\text{tandard footplates, angle-adjustable and depth-adjustable}$ $\text{to } 0$ $\text{tandard footplates, angle-adjustable and depth-adjustable}$ $\text{to } 0$ $\text{to } 0$ $\text{tandard footplates, } 18.4 \text{ cm } (7^1/_4 \text{ in.}), \text{ angle-adjustable}$ $\text{to } 0$ $\text{tandard footplates, } 18.4 \text{ cm } (7^1/_4 \text{ in.}), \text{ angle-adjustable}$ $\text{to } 0$ $\text{tandard footplates, } 18.4 \text{ cm } (7^1/_4 \text{ in.}), \text{ angle-adjustable}$ $\text{to } 0$ $\text{tandard footplates, } 18.4 \text{ cm } (7^1/_4 \text{ in.}), \text{ angle-adjustable}$ $\text{to } 0$ $\text{tandard footplates, } 18.4 \text{ cm } (7^1/_4 \text{ in.}), \text{ angle-adjustable}$ $\text{to } 0$ $\text{tandard footplates, } 18.4 \text{ cm } (7^1/_4 \text{ in.}), \text{ angle-adjustable}$ $\text{to } 0$ $\text{tandard footplates, } 18.4 \text{ cm } (7^1/_4 \text{ in.}), \text{ angle-adjustable}$ $\text{to } 0$ $\text{tandard footplates, } 18.4 \text{ cm } (7^1/_4 \text{ in.}), \text{ angle-adjustable}$ $\text{to } 0$ $\text{tandard footplates, } 18.4 \text{ cm } (7^1/_4 \text{ in.}), \text{ angle-adjustable}$ $\text{to } 0$ $\text{tandard footplates, } 18.4 \text{ cm } (7^1/_4 \text{ in.}), \text{ angle-adjustable}$ $\text{to } 0$ $\text{tandard footplates, } 18.4 \text{ cm } (7^1/_4 \text{ in.}), \text{ angle-adjustable}$ $\text{to } 0$ $\text{tandard footplates, } 18.4 \text{ cm } (7^1/_4 \text{ in.}), \text{ angle-adjustable}$ $\text{to } 0$ | From 13.3 cm $(5^{1}/_{4} in.)$ to 26.7 cm $(10^{1}/_{2} in.)$ | 113.00 | 170.00 |
| 0° footrests, MFX, parallel, detachable, swingaway, ength-adjustable from 22.2 cm ($8^3/_4$ in.) to 37.5 cm ($14^3/_4$ in.)N/C114.00ingle calf strapN/C37.00ouble calf strap38.0055.00olding footplates, standardN/C42.00ull-width footrestN/C63.00versized footplates45.0065.00tandard footplates, angle-adjustable and depth-adjustable76.0080.00ull-width footrest, angle-adjustable and depth-adjustableN/C98.00versized footplates, 18.4 cm ($7^1/_4$ in.), angle-adjustable and76.0080.00lamps, 1.87 cm ($3^1/_4$ in.) to 2.5 cm (1 in.), making it possible to install footplates higher up on the footrest bracket30.0015.00eel loops, adjustable, on swingaway footrests onlyN/C15.00 | from 40.0 cm (15 ³ / ₄ in.) to 50.2 cm (19 ³ / ₄ in.) 60° footrests, MFX, parallel, detachable, swing-away, | 113.00 | 170.00 |
| ength-adjustable from 22.2 cm $(8^3/_4 \text{ in.})$ to 37.5 cm $(14^3/_4 \text{ in.})$ N/C 37.00 ingle calf strap 38.00 55.00 ouble calf strap 38.00 55.00 olding footplates, standard N/C 42.00 all-width footrest N/C 63.00 versized footplates 45.00 65.00 tandard footplates, angle-adjustable and depth-adjustable 76.00 80.00 all-width footrest, angle-adjustable and depth-adjustable N/C 98.00 versized footplates, 18.4 cm $(7^1/_4 \text{ in.})$, angle-adjustable and epth-adjustable and epth-adjustable and epth-adjustable (76.00 so) $(76$ | | | |
| ingle calf strap ouble calf strap ouble calf strap olding footplates, standard olding footplates, standard oull-width footrest versized footplates tandard footplates, angle-adjustable and depth-adjustable outl-width footrest, angle-adjustable outl-width footrest outl- | | N/C | 114.00 |
| ouble calf strap olding footplates, standard olding footplates versized footplates tandard footplates, angle-adjustable and depth-adjustable tandard footplates, angle-adjustable and depth-adjustable olding footplates, angle-adjustable and depth-adjustable olding footplates, angle-adjustable and depth-adjustable olding footplates, angle-adjustable and depth-adjustable N/C 98.00 versized footplates, 18.4 cm (7¹/₄ in.), angle-adjustable and epth-adjustable olding footplates, 18.4 cm (7¹/₄ in.), angle-adjustable olding footplates, 18.4 cm (7¹/₄ in.), angle-adjustable olding footplates, standard N/C 98.00 80.00 lamps, 1.87 cm (³/₄ in.) to 2.5 cm (1 in.), making it possible to olding footplates higher up on the footrest bracket 30.00 15.00 eel loops, adjustable, on swingaway footrests only N/C 15.00 | | | |
| olding footplates, standard N/C 42.00 ull-width footrest N/C 63.00 versized footplates 45.00 65.00 tandard footplates, angle-adjustable and depth-adjustable 76.00 80.00 ull-width footrest, angle-adjustable and depth-adjustable N/C 98.00 versized footplates, $18.4 \text{ cm} (7^1/_4 \text{ in.})$, angle-adjustable and epth-adjustable and epth-adjustable $1.87 \text{ cm} (3^1/_4 \text{ in.})$ to $2.5 \text{ cm} (1 \text{ in.})$, making it possible to install footplates higher up on the footrest bracket 30.00 15.00 eel loops, adjustable, on swingaway footrests only N/C 15.00 | | | |
| ull-width footrest N/C 63.00 versized footplates 45.00 65.00 tandard footplates, angle-adjustable and depth-adjustable 76.00 80.00 ull-width footrest, angle-adjustable and depth-adjustable N/C 98.00 versized footplates, $18.4 \text{ cm} (7^1/_4 \text{ in.})$, angle-adjustable and epth-adjustable and epth-adjustable 76.00 80.00 lamps, $1.87 \text{ cm} (3^1/_4 \text{ in.})$ to $2.5 \text{ cm} (1 \text{ in.})$, making it possible to estall footplates higher up on the footrest bracket 90.00 install footplates higher up on swingaway footrests only 90.00 install $90.$ | | | |
| versized footplates tandard footplates, angle-adjustable and depth-adjustable versized footplates, angle-adjustable and depth-adjustable versized footplates, 18.4 cm (7 ¹ / ₄ in.), angle-adjustable and epth-adjustable tepth-adjustable lamps, 1.87 cm (³ / ₄ in.) to 2.5 cm (1 in.), making it possible to estall footplates higher up on the footrest bracket telloops, adjustable, on swingaway footrests only 45.00 80.00 80.00 15.00 15.00 15.00 | | | |
| tandard footplates, angle-adjustable and depth-adjustable N/C 98.00 wersized footplates, 18.4 cm (7 ¹ / ₄ in.), angle-adjustable and epth-adjustable and epth-adjustable and epth-adjustable and epth-adjustable 76.00 80.00 lamps, 1.87 cm (3 ¹ / ₄ in.) to 2.5 cm (1 in.), making it possible to estall footplates higher up on the footrest bracket 30.00 15.00 eel loops, adjustable, on swingaway footrests only N/C 15.00 | | | |
| ull-width footrest, angle-adjustable and depth-adjustable N/C 98.00 versized footplates, 18.4 cm (7 ¹ / ₄ in.), angle-adjustable and epth-adjustable and epth-adjustable 76.00 80.00 lamps, 1.87 cm (³ / ₄ in.) to 2.5 cm (1 in.), making it possible to estall footplates higher up on the footrest bracket 30.00 15.00 eel loops, adjustable, on swingaway footrests only N/C 15.00 | | | |
| versized footplates, 18.4 cm (7 ¹ / ₄ in.), angle-adjustable and epth-adjustable 76.00 80.00 lamps, 1.87 cm (³ / ₄ in.) to 2.5 cm (1 in.), making it possible to install footplates higher up on the footrest bracket 30.00 15.00 eel loops, adjustable, on swingaway footrests only N/C 15.00 | | | |
| lamps, $1.87 \text{ cm} (\frac{3}{4} \text{ in.})$ to $2.5 \text{ cm} (1 \text{ in.})$, making it possible to install footplates higher up on the footrest bracket 30.00 15.00 eel loops, adjustable, on swingaway footrests only N/C 15.00 | oversized footplates, 18.4 cm (7 ¹ / ₄ in.), angle-adjustable and | | |
| nstall footplates higher up on the footrest bracket 30.00 15.00 eel loops, adjustable, on swingaway footrests only N/C 15.00 | | 76.00 | 80.00 |
| eel loops, adjustable, on swingaway footrests only N/C 15.00 | | 20.00 | 15.00 |
| | | | |
| | neel loops, adjustable, on swingaway footrests only neel loops, fixed, on swingaway footrests only | N/C N/C | 15.00 7.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Frame: | | |
| anti-tip rollers | N/C | 50.00 |
| front floor roller | 35.00 | 35.00 |
| cane holder | 34.00 | 34.00 |
| push handles, integrated | N/C | 38.00 |
| modification of frame permitting the installation of swingaway | | |
| footrests | 505.00 | N/A |
| folding back, height-adjustable from 20.3 cm (8 in.) | | |
| to 50.8 cm (20 in.) | N/C | N/A |
| push handles, bolt-on | N/C | 40.00 |
| Duivo evetema | | |
| Drive systems: handrims with vertical or oblique projections | 155.00 | 125.00 |
| smooth handrims | N/C | 36.00 |
| plastic-coated handrims | 54.00 | 63.00 |
| plastic-coated handrins | 34.00 | 05.00 |
| Wheel locks: | | |
| standard, push-to-lock, pull-to-lock | N/C | 46.00 |
| scissor-type wheel locks | N/C | 105.00 |
| anti-rollback brakes | 94.00 | 93.00 |
| modification of frame permitting the installation of swingaway | | |
| footrests | 505.00 | N/A |
| wheel lock extensions | 34.00 | 17.00 |
| Wheels: | | |
| rear mag wheels, standard pressure, 50.8 cm (20 in.), | | |
| 55.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 105.00 |
| rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | | |
| 61.0 cm (24 in.) | N/C | 105.00 |
| spoked rear wheels, standard pressure, 50.8 cm (20 in.), | | |
| 55.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 142.00 |
| spoked rear wheels, high pressure, 61.0 cm (24 in.) | N/C | 142.00 |
| spoked rear wheels, high pressure, 66.0 cm (26 in.) | 74.00 | 142.00 |
| spoked rear wheels, standard pressure, 66.0 cm (26 in.) | 74.00 | 142.00 |
| spoked rear wheels, solid tires, 61.0 cm (24 in.) | N/C | 142.00 |
| spoked rear wheels, solid tires, 66.0 cm (26 in.) | 74.00 | 142.00 |
| heavy-duty rear wheels, standard pressure, high pressure, | N/G | 102.00 |
| 61.0 cm (24 in.), 66.0 cm (26 in.) | N/C | 183.00 |
| neavy-duty rear wheels, solid tires, 61.0 cm (24 in.) | 82.00 | 183.00 |
| Front wheels, inner tube tires, 15.2 cm (6 in.) x 3.2 cm ($\frac{1}{4}$ in.) | 30.00 | 55.00 |
| Front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 2.5 cm (1 in.) | | 42.00 |
| 10.2 cm (4 in.) x 2.5 cm (1 in.) | N/C | 42.00 |
| front wheels, solid tires, 7.6 cm (3 in.), 12.7 cm (5 in.), | N/C | 40.00 |
| 15.2 cm (6 in.) Front wheels, solid tires, 12.7 cm (5 in.) x 3.8 cm (1 ¹ / ₂ in.), | N/C | 40.00 |
| from wheels, solid tires, 12.7 cm (3 iii.) x 3.8 cm (1 $\frac{7}{2}$ iii.), 15.2 cm (6 iii.) x 3.8 cm ($\frac{11}{2}$ iii.) | N/C | 42.00 |
| 13.2 cm (0 m.) x 3.0 cm (1 /2 m.) | 14/6 | 42.00 |
| Forks: | | |
| standard forks, short | N/C | 52.00 |
| | | |

\$1 680.00

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| Rear axles: | NIC | 52.00 |
| quick-release axles | N/C | 53.00 |
| quick-release axles with lever mechanism | 76.00 | 53.00 |
| double camber tubes for the following angles: 0°, 3°, 6°, 9°, 12° Commonant(s) under Special Consideration | N/C | N/A |
| Component(s) under Special Consideration spoke guards* | 94.00 | 47.00 |
| modification permitting the installation of fork-locking mechanisms | , | 17.00 N/A |
| quick-release axles with lever mechanism* | 76.00 | 53.00 |
| SUPPLIER: SUNRISE MEDICAL CANADA INC. | 70.00 | PRIC |

Basic Components

Body support system

• folding back, angle-adjustable, height-adjustable from 25.4 cm (10 in.) to 45.7 cm (18 in.)

LIGHTWEIGHT MANUAL WHEEL CHAIR, ADULT QUICKIE GT

- supple seat and back, nylon
- front seat height: from 40.6 cm (16 in.) to 53.3 cm (21 in.)
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- safety belt, velcro-type, auto-type
- push handles, bolt-on, integrated

Armrests

- L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- armrest pads, straight, short, long
- armrest pads, tubular
- clothing guards, flexible, rigid
- clothing guards, aluminum, folding, with mudguard

Footrests

- 75° or 85° footrests, parallel, shortened by 2.5 cm (1 in.) or by 5.1 cm (2 in.), fixed, length-adjustable from 33.0 cm (13 in.) to 50.8 cm (20 in.)
- full-width footrest, tubular, with cover
- single calf strap

Drive, brake, wheel, fork and axle systems

- smooth handrims, 55.9 cm (22 in.), 61.0 cm (24 in.), 63.5 cm (25 in.), 66.0 cm (26 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- scissor-type wheel locks
- rear mag wheels, standard pressure, 55.9 cm (22 in.), 61.2 cm (24 in.)
- rear mag wheels, solid tires, 55.9 cm (22 in.), 61.2 cm (24 in.)

- spoked rear wheels, standard pressure, 55.9 cm (22 in.), 61.2 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, solid tires, 55.9 cm (22 in.), 61.2 cm (24 in.)
- rear wheels, heavy-duty, standard pressure, high pressure, 61.0 cm (24 in.)
- front wheels, solid tires, 15.2 cm (6 in.), 12.7 cm (5 in.), 10.2 cm (4 in.), 7.6 cm (3 in.)
- standard forks, wide, compatible with 7.6 cm (3 in.), 10.2 cm (4 in.), 12.7 cm (5 in.) and 15.2 cm (6 in.) wheels
- quick-release axles
- rear wheel camber, 0°, 3°, 6°, 9°

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| modification of seat width to 48.3 cm (19 in.) or 50.8 cm (20 in. |) 55.00 | N/A |
| modification of seat depth to 48.3 cm (19 in.) or 50.8 cm (20 in.) folding back, angle-adjustable, height-adjustable | | N/A |
| from 25.4 cm (10 in.) to 45.7 cm (18 in.) | N/C | N/A |
| supple back, tension-adjustable | 76.00 | 143.00 |
| push handles, bolt-on | N/C | 28.00 |
| push handles, integrated | N/C | 25.00 |
| push handles, fold-down | 52.00 | 51.00 |
| supple back, nylon | N/C | 67.00 |
| supple seat, nylon | N/C | 55.00 |
| seat cushion, flat, foam, 5.1 cm (2 in.) | 58.00 | 58.00 |
| seat cushion, flat, foam, 7.6 cm (3 in.) | 58.00 | 58.00 |
| seat cushion, flat, foam, 10.2 cm (4 in.) | 58.00 | 58.00 |
| safety belt, velcro-type | N/C | 29.00 |
| safety belt, auto-type | N/C | 42.00 |
| Armrests: | | |
| L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short | N/C | 96.00 |
| T-type armrests, height-adjustable from 22.9 cm (9 in.) | 14/6 | 70.00 |
| to 35.6 cm (14 in.), short, long | 78.00 | 135.00 |
| clothing guards, flexible | N/C | 22.00 |
| clothing guards, rigid | N/C | 68.00 |
| clothing guards, aluminum, folding, with mudguard | N/C | 145.00 |
| armrest pads, tubular | N/C | 2.00 |
| armrest pads, straight, short | N/C | 15.00 |
| armrest pads, straight, long | N/C | 18.00 |
| Footrests: 75° or 85° footrests, parallel, shortened by 2.5 cm (1 in.) or by 5.1 cm (2 in.), fixed, length-adjustable from 33.0 cm (13 in.) | | |
| to 50.8 cm (20 in.) | N/C | N/A |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| ingle calf strap | N/C | 19.00 |
| louble calf strap | 14.00 | 33.00 |
| ull-width footrest, tubular, with cover | N/C | N/A |
| full-width platform footrest, angle-adjustable and depth-adjustable | 40.00 | 111.00 |
| ootplate spacers, 5.1 cm (2 in.), 10.2 cm (4 in.), 15.2 cm (6 in.) | 20.00 | 10.00 |
| eet-positioning plates | 40.00 | 20.00 |
| Orive systems: | | |
| nandrims with vertical or oblique projections mooth handrims, 55.9 cm (22 in.), 61.2 cm (24 in.), | 90.00 | 105.00 |
| 3.5 cm (25 in.), 66.0 cm (26 in.) | N/C | 60.00 |
| lastic-coated handrims, 55.9 cm (22 in.), 61.2 cm (24 in.), | 1110 | 00.00 |
| 3.5 cm (25 in.), 66.0 cm (26 in.) | 56.00 | 88.00 |
| ion-slip handrims, 61.0 cm (24 in.) | 168.00 | 144.00 |
| nti-tip rollers | 44.00 | 39.00 |
| djustment of backrest depth by -2.5 cm (1 in.) or by -5.1 cm (2 in.) | 76.00 | N/A |
| ane holder | 45.00 | 45.00 |
| Wheel locks: | | |
| tandard, push-to-lock, pull-to-lock | N/C | 40.00 |
| cissor-type wheel locks | N/C | 27.00 |
| heel lock extensions | 26.00 | 13.00 |
| nti-rollback brakes | 68.00 | 34.00 |
| rgo scissor-type wheel locks | 24.00 | 52.00 |
| Wheels: | | |
| ear mag wheels, standard pressure, 55.9 cm (22 in.), | NIC | 112.00 |
| 1.2 cm (24 in.) | N/C | 113.00 |
| ear mag wheels, solid tires, 55.9 cm (22 in.), 61.2 cm (24 in.) poked rear wheels, standard pressure, 55.9 cm (22 in.), | N/C | 136.00 |
| 1.2 cm (24 in.), 66.0 cm (26 in.) | N/C | 136.00 |
| poked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.) | N/C | 136.00 |
| booked rear wheels, solid tires, 55.9 cm (22 in.), 61.2 cm (24 in.) ear wheels, heavy-duty, standard pressure, high pressure, | N/C | 153.00 |
| 1.0 cm (24 in.) | N/C | 199.00 |
| ear wheels, heavy-duty, standard pressure, high pressure, | 56.00 | 227.00 |
| 6.0 cm (26 in.) | 56.00 | 227.00 |
| ear wheels, heavy-duty, high pressure, 63.5 cm (25 in.) | 56.00 | 227.00 |
| ront wheels, solid tires, 15.2 cm (6 in.) | N/C | 62.00 |
| ont wheels, solid tires, 12.7 cm (5 in.) | N/C | 47.00 |
| ont wheels, solid tires, 10.2 cm (4 in.) | N/C | 60.00 |
| ont wheels, solid tires, 7.6 cm (3 in.) ont wheels, semi-pneumatic tires, 10.2 cm (4 in.) x 3.8 cm ($1^{1}/_{2}$ in.) | | 67.00 |
| 2.7 cm (5 in.) x 3.8 cm ($1^{1}/_{2}$ in.), 15.2 cm (6 in.) x 3.8 cm ($1^{1}/_{2}$ in.) | 84.00 | 89.00 |
| ront wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 in.) | 68.00 | 81.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Forks: | | |
| standard forks, wide, compatible with 7.6 cm (3 in.), 10 | | |
| 12.7 cm (5 in.) and 15.2 cm (6 in.) wheels | N/C | 69.00 |
| fork-locking mechanism | 99.00 | 83.00 |
| Rear axles: | | |
| quick-release axles | N/C | 33.00 |
| plates for amputees | 56.00 | 84.00 |
| rear wheel camber, 0°, 3°, 6°, 9° | N/C | 38.00 |
| Component(s) under Special Consideration | | |
| spoke guards* | 70.00 | 35.00 |
| quick-release axles with lever mechanism* | 66.00 | 66.00 |
| heavy-duty axles* | 102.00 | 84.00 |
| SUPPLIER: SUNRISE MEDICAL CANADA INC. | | |
| | | PRIC |
| LIGHTWEIGHT MANUAL WHEEL CHAIR, CHIL | LD OUICKIE GT MODEL | \$1 680.0 |

Basic Components

Body support system

- supple seat, nylon
- supple back, nylon
- seat width: from 30.5 cm (12 in.) to 40.6 cm (16 in.)
- seat depth: from 30.5 cm (12 in.) to 38.1 cm (15 in.)
- seat height: from 40.6 cm (16 in.) to 53.3 cm (21 in.)
- back height: from 25.4 cm (10 in.) to 45.7 cm (18 in.)
- safety belt, velcro-type, auto-type

Armrests

- L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short
- armrest pads, tubular
- armrest pads, straight, short, long
- clothing guards, flexible, rigid
- · clothing guards, aluminum, folding, with mudguard

Footrests

- 75° or 85° footrests, fixed, parallel, length-adjustable from 33.0 cm (13 in.) to 50.8 cm (20 in.)
- 75° or 85° footrests, fixed, shortened by 2.5 cm (1 in.) or by 5.1 cm (2 in.)
- · single calf strap
- full-width footrest, tubular aluminum
- full-width footrest, tubular aluminum, with cover
- footplate spacers, 5.1 cm (2 in.), 10.2 cm (4 in.), 15.2 cm (6 in.)

Frame

- folding back, angle-adjustable, 28° of adjustment
- push handles, bolt-on, integrated
- · anti-tip rollers

Drive, brake, wheel, fork and axle systems

- smooth handrims, 55.9 cm (22 in.), 61.0 cm (24 in.), 63.5 cm (25 in.), 66.0 cm (26 in.)
- standard wheel locks, push-to-lock, pull-to-lock
- · scissor-type wheel locks
- rear mag wheels, standard pressure, 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 55.9 cm (22 in.), 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in.)
- spoked rear wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear wheels, heavy-duty, standard pressure, high pressure, 61.0 cm (24 in.)
- front wheels, solid tires, 15.2 cm (6 in.), 12.7 cm (5 in.), 10.2 cm (4 in.), 7.6 cm (3 in.)
- standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) and 12.7 cm (5 in.) wheels
- wide forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.), 12.7 cm (5 in.) and 15.2 cm (6 in.) wheels with solid or semi-pneumatic tires
- · adjustment plates
- quick-release axles
- rear wheel camber, 0° , 3° , 6° , 9°
- axle position along the backrest axis, 2.5 cm (1 in.) to +11.4 cm ($4^{1}/_{2}$ in.)

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: supple back, tension-adjustable supple back, nylon supple seat, nylon seat cushion, flat, foam, 5.1 cm (2 in.) seat cushion, flat, foam, 7.6 cm (3 in.) seat cushion, flat, foam, 10.2 cm (4 in.) safety belt, velcro-type safety belt, auto-type | 76.00 N/C N/C 58.00 58.00 58.00 N/C N/C | 143.00 67.00 55.00 58.00 58.00 58.00 29.00 42.00 |
| Armrests: L-type armrests, detachable, swingaway, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short T-type armrests, height-adjustable from 22.9 cm (9 in.) to 30.5 cm (14 in.), short, long clothing guards, flexible clothing guards, rigid clothing guards, aluminum, folding, with mudguard armrest pads, tubular | N/C 78.00 N/C N/C N/C N/C | 96.00 135.00 22.00 68.00 145.00 2.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| armrest pads, straight, short armrest pads, straight, long | N/C N/C | 15.00 18.00 |
| Footrests: 75° or 85° footrests, parallel, shortened by 2.5 cm (1 in.) or by 5.1 cm (2 in.), fixed, length-adjustable from 33.0 cm (13 in.) to 50.8 cm (20 in.) single calf strap double calf strap | N/C N/C 14.00 N/C | N/A 19.00 33.00 N/A |
| full-width footrest, tubular aluminum, with cover full-width footrest, angle-adjustable and depth-adjustable footplate spacers, 5.1 cm (2 in.), 10.2 cm (4 in.), 15.2 cm (6 in.) feet-positioning plate | 40.00 N/C 40.00 | 111.00 10.00 20.00 |
| Frame: folding back, angle-adjustable, 28° of adjustment push handles, bolt-on push handles, integrated push handles, folding anti-tip rollers adjustment of backrest depth by -2.5 cm (1 in.) or by -5.1 cm (2 in.) cane holder | N/C N/C N/C 52.00 N/C 76.00 45.00 | N/A 28.00 25.00 51.00 39.00 N/A 45.00 |
| Drive systems: handrims with vertical or oblique projections smooth handrims, 55.9 cm (22 in.), 61.0 cm (24 in.), 63.5 cm (25 in.), 66.0 cm (26 in.) plastic-coated handrims, 55.9 cm (22 in.), 61.0 cm (24 in.), 63.5 cm (25 in.), 66.0 cm (26 in.) non-slip handrims, 61.0 cm (24 in.) | 90.00 N/C 56.00 168.00 | 105.00 60.00 88.00 144.00 |
| Wheel locks: standard wheel locks, push-to-lock, pull-to-lock scissor-type wheel locks ergo scissor-type wheel locks wheel lock extensions anti-rollback brakes | N/C N/C 24.00 26.00 68.00 | 40.00 27.00 52.00 13.00 34.00 |
| Wheels: rear mag wheels, standard pressure, 55.9 cm (22 in.), 61.0 cm (24 in.) rear mag wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.) spoked rear wheels, standard pressure, 55.9 cm (22 in.), | N/C N/C | 113.00 136.00 |
| 61.0 cm (24 in.), 66.0 cm (26 in.) spoked rear wheels, high pressure, 61.0 cm (24 in.), 66.0 cm (26 in. spoked rear wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.) rear wheels, heavy-duty, standard pressure, high pressure, | N/C | 136.00 136.00 153.00 |
| 61.0 cm (24 in.) | N/C | 199.00 |

| rear wheels, heavy-duty, high pressure, 63.5 cm (25 in.) front wheels, solid tires, 15.2 cm (6 in.) front wheels, solid tires, 12.7 cm (5 in.) front wheels, solid tires, 10.2 cm (4 in.) front wheels, solid tires, 10.2 cm (4 in.) front wheels, solid tires, 7.6 cm (3 in.) front wheels, semi-pneumatic tires, 10.2 cm (4 in.) x 3.8 cm (1½ in.) 12.7 cm (5 in.) x 3.8 cm (1½ in.), 15.2 cm (6 in.) x 3.8 cm (1½ in.) Forks: standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) and 12.7 cm (5 in.) wheels wide forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) 12.7 cm (5 in.) and 15.2 cm (6 in.) wheels with solid or semi-pneumatic tires semi-pneumatic tires N/C 69.00 Rear axles: quick-release axles axle position along the backrest axis, -2.5 cm (1 in.) to +11.4 cm (4½ in.) plates for amputees 56.00 84.00 Component(s) under Special Consideration spoke guards* 70.00 35.00 227.00 62.00 7/C 62.00 7/C 60.00 7/C 7/C 7/C 7/C 7/C 7/C 7/C 7 | | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|---|
| 66.0 cm (26 in.) 76.00 cm (26 in.) 77.00 cm (27 in.) 78.00 cm (3 in.) 78.00 cm (1½ in.) 78.00 cm (1½ in.) 78.00 cm (1½ in.) 78.00 cm (1½ i | rear wheels, heavy-duty, standard pressure, high pressure. | | |
| rear wheels, heavy-duty, high pressure, 63.5 cm (25 in.) front wheels, solid tires, 15.2 cm (6 in.) front wheels, solid tires, 12.7 cm (5 in.) front wheels, solid tires, 10.2 cm (4 in.) front wheels, solid tires, 7.6 cm (3 in.) front wheels, solid tires, 7.6 cm (3 in.) front wheels, semi-pneumatic tires, 10.2 cm (4 in.) x 3.8 cm (1½ in.) 12.7 cm (5 in.) x 3.8 cm (1½ in.), 15.2 cm (6 in.) x 3.8 cm (1½ in.) 12.7 cm (5 in.) x 3.8 cm (1½ in.), 15.2 cm (6 in.) x 5.1 cm (2 in.) Forks: standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) 21.7 cm (5 in.) and 15.2 cm (6 in.) wheels with solid or semi-pneumatic tires fork-locking mechanism Fork-locking mechanism Rear axles: quick-release axles axle position along the backrest axis, -2.5 cm (1 in.) to +11.4 cm (4½ in.) plates for amputees adjustment plates rear wheel camber tubes, 0°, 3°, 6°, 9° Component(s) under Special Consideration spoke guards* 70.00 35.00 60.00 227.00 A7.00 62.01 N/C 47.00 60.00 N/C 70.00 35.00 60.00 70.00 35.00 60.00 60.00 | | 56.00 | 227.00 |
| For the wheels, solid tires, 15.2 cm (6 in.) Front wheels, solid tires, 12.7 cm (5 in.) Front wheels, solid tires, 10.2 cm (4 in.) Front wheels, semi-pneumatic tires, 10.2 cm (4 in.) x 3.8 cm (1½ in.), 12.7 cm (5 in.) x 3.8 cm (1½ in.), 15.2 cm (6 in.) x 3.8 cm (1½ in.) 12.7 cm (5 in.) x 3.8 cm (1½ in.), 15.2 cm (6 in.) x 5.1 cm (2 in.) Forks: Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) and 12.7 cm (5 in.) wheels wide forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.), 12.7 cm (5 in.) and 15.2 cm (6 in.) wheels with solid or semi-pneumatic tires Fork-locking mechanism Rear axles: quick-release axles axle position along the backrest axis, -2.5 cm (1 in.) to +11.4 cm (4½ in.) Polates for amputees digustment plates Formal methods of the component of the compone | | | 227.00 |
| Forks: Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: Standard forks, adjustable for 7.6 cm (3 in.) to wheels Wide forks, adjustable for 7.6 cm (3 in.) to wheels Fork-locking mechanism Forks: Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Fork-locking mechanism Forks: Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Fork-locking mechanism Forks: Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Fork-locking mechanism Forks: Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Standard forks, adjustable for 7.6 cm (3 in.) to wheels with solid or Standard forks, adjustable for 7.6 cm (1 in.) to wheels with solid or Standard forks, adjustable for 7.6 cm (1 in.) to wheels with solid or Standard forks, | | | 62.00 |
| Fort wheels, solid tires, 10.2 cm (4 in.) Front wheels, solid tires, 7.6 cm (3 in.) Front wheels, semi-pneumatic tires, 10.2 cm (4 in.) x 3.8 cm (1 ¹ / ₂ in.), Fort wheels, semi-pneumatic tires, 10.2 cm (6 in.) x 3.8 cm (1 ¹ / ₂ in.), Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Forks: International forks, adjustable for 7.6 cm (3 in.) x 3.8 cm (1 ¹ / ₂ in.) Forks: International forks, adjustable for 7.6 cm (3 in.) x 3.8 cm (1 ¹ / ₂ in.) Forks: International forks, adjustable for 7.6 cm (3 in.) x 3.8 cm (1 ¹ / ₂ in.) Forks: International forks and fo | | | 47.00 |
| Front wheels, solid tires, 7.6 cm (3 in.) Front wheels, semi-pneumatic tires, 10.2 cm (4 in.) x 3.8 cm (1½ in.), 12.7 cm (5 in.) x 3.8 cm (1½ in.), 15.2 cm (6 in.) x 3.8 cm (1½ in.) Front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 in.) Forks: Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) and 12.7 cm (5 in.) wheels Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) and 12.7 cm (5 in.) and 15.2 cm (6 in.) wheels with solid or semi-pneumatic tires Fork-locking mechanism Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.), 12.7 cm (5 in.) and 15.2 cm (6 in.) wheels with solid or semi-pneumatic tires Fork-locking mechanism Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.), 10.2 cm (4 in.), 10.2 cm (4 in.), 10.2 cm (5 in.) and 15.2 cm (6 in.) wheels with solid or semi-pneumatic tires Fork-locking mechanism Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.) at 0.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) Standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in. | | N/C | 60.00 |
| ront wheels, semi-pneumatic tires, 10.2 cm (4 in.) x 3.8 cm (1½ in.), 2.7 cm (5 in.) x 3.8 cm (1½ in.), 15.2 cm (6 in.) x 3.8 cm (1½ in.) 84.00 89.00 ront wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 in.) 84.00 81.00 Forks: tandard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) and 12.7 cm (5 in.) wheels vide forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.), 2.7 cm (5 in.) and 15.2 cm (6 in.) wheels with solid or emi-pneumatic tires ork-locking mechanism Rear axles: puick-release axles xy/C solates for amputees djustment plates xy/C solates for amputees x | | | 67.00 |
| 2.7 cm (5 in.) x 3.8 cm (1½ in.), 15.2 cm (6 in.) x 3.8 cm (1½ in.) 84.00 89.00 81.0 | | 1.), | |
| Forks: standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) and 12.7 cm (5 in.) wheels wide forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.), 12.7 cm (5 in.) and 15.2 cm (6 in.) wheels with solid or semi-pneumatic tires N/C ork-locking mechanism Rear axles: quick-release axles xxle position along the backrest axis, -2.5 cm (1 in.) to 11.4 cm (4½ in.) xxle position along the backrest axis, -2.5 cm (1 in.) to xxle position | | | 89.00 |
| standard forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.) and 12.7 cm (5 in.) wheels wide forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.), 12.7 cm (5 in.) and 15.2 cm (6 in.) wheels with solid or semi-pneumatic tires N/C fork-locking mechanism Rear axles: quick-release axles axle position along the backrest axis, -2.5 cm (1 in.) to +11.4 cm (4 ¹ / ₂ in.) balates for amputees adjustment plates rear wheel camber tubes, 0°, 3°, 6°, 9° Component(s) under Special Consideration spoke guards* quick-release axles with lever mechanism* 70.00 35.00 66.00 | front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 5.1 cm (2 in.) | 68.00 | 81.00 |
| quick-release axles axle position along the backrest axis, -2.5 cm (1 in.) to $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ plates for amputees $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ plates for amputees $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ plates for amputees $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ plates for amputees $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/C \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/A$ $+11.4 \text{ cm } (4^{1}/_{2} \text{ in.}) \qquad N/A$ $+11.4 cm$ | wide forks, adjustable for 7.6 cm (3 in.), 10.2 cm (4 in.), 12.7 cm (5 in.) and 15.2 cm (6 in.) wheels with solid or semi-pneumatic tires | N/C | 69.00 69.00 83.00 |
| Taxle position along the backrest axis, -2.5 cm (1 in.) to $+11.4$ cm $(4^{1}/_{2}$ in.) N/C N/A plates for amputees Sequence N/C S6.00 N/C S6.00 N/C S6.00 N/C S6.00 N/C S6.00 N/C S6.00 N/C N/C S6.00 N/C S6.00 N/C S6.00 N/C | Rear axles: | | |
| +11.4 cm $(4^{1}/_{2} \text{ in.})$ N/C N/A plates for amputees 56.00 84.00 adjustment plates N/C 56.00 rear wheel camber tubes, 0° , 3° , 6° , 9° N/C 38.00 Component(s) under Special Consideration spoke guards* 70.00 35.00 quick-release axles with lever mechanism* 66.00 66.00 | quick-release axles | N/C | 33.00 |
| polates for amputees 56.00 84.00 dijustment plates N/C 56.00 84.00 ear wheel camber tubes, 0°, 3°, 6°, 9° N/C 38.00 Component(s) under Special Consideration epoke guards* 70.00 35.00 quick-release axles with lever mechanism* 66.00 66.00 | | | |
| adjustment plates ear wheel camber tubes, 0°, 3°, 6°, 9° Component(s) under Special Consideration poke guards* 70.00 puick-release axles with lever mechanism* 70.00 66.00 | | N/C | N/A |
| ear wheel camber tubes, 0°, 3°, 6°, 9° Component(s) under Special Consideration poke guards* 70.00 135.00 puick-release axles with lever mechanism* 66.00 66.00 | | | 84.00 |
| Component(s) under Special Consideration spoke guards* quick-release axles with lever mechanism* 70.00 35.00 66.00 | adjustment plates | | 56.00 |
| poke guards* 70.00 35.00 quick-release axles with lever mechanism* 66.00 66.00 | ear wheel camber tubes, 0° , 3° , 6° , 9° | N/C | 38.00 |
| poke guards* 70.00 35.00 uick-release axles with lever mechanism* 66.00 66.00 | Component(s) under Special Consideration | | |
| puick-release axles with lever mechanism* 66.00 66.00 | poke guards* | 70.00 | 35.00 |
| | quick-release axles with lever mechanism* | 66.00 | 66.00 |
| | | 102.00 | 84.00 |

§3. Powered wheel chairs

SUPPLIER: INVACARE CANADA INC.

PRICE

POWERED WHEEL CHAIR STORM ARROW 3G MODEL

\$5 070.00

Basic Components

Body support system

- rigid seat, flat
- · supple back, fabric, leatherette
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: from 40.6 cm (16 in.) to 45.7 cm (18 in.)
- seat heights: $44.5 \text{ cm} (17^{1}/_{2} \text{ in.}), 50.2 \text{ cm} (19^{3}/_{4} \text{ in.})$
- back height: from 30.5 cm (12 in.) to 48.3 cm (19 in.)
- back, angle-adjustable

- back tension bar, on reclining back
- · push handles
- push bar
- · centre of gravity adjustment from seat
- · headrest mounting, articulated
- · safety belt, auto-type

Armrests

- U-type armrests, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), short, long
- U-type armrests, fixed height, short, long
- · armrest pads, straight, short, long
- · armrest pads, contoured, short, long
- rigid clothing guards, built into armrests

Footrests

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 44.5 cm (17¹/₂ in.); 70° footrests, parallel, detachable, swingaway, length-adjustable from 29.8 cm (11³/₄ in.) to 43.2 cm (17 in.)
- padded calfrests
- folding footplates, standard
- heel loops, adjustable
- · heel loops, fixed

Frame

- · heavy-duty frame or robust base
- · rear suspension
- · rear reflectors
- running lights
- · tie-down points for adapted transport
- · anti-tip rollers

Drive systems

- · programmable joystick control
- battery charge display
- toggle switch
- direction joystick
- battery charger
- battery box, group 22, group 24
- · side bracket for joystick control
- swivel side bracket for joystick control
- controller
- heavy-duty motors

- reflector strips
- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.), 20.3 cm (8 in.) x 5.7 cm (2¹/₄ in.)
- rear wheel rims
- · front wheel rims
- · standard forks

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| seat/back structure, with angle-adjustable back (ASBA) | 566.00 | 566.00 |
| back, angle-adjustable | N/C | N/A |
| back tension bar, on reclining back | N/C | N/A |
| headrest, small | 125.00 | 125.00 |
| headrest, large | 125.00 | 125.00 |
| combined headrest/neckrest | 125.00 | 125.00 |
| headrest mounting, articulated | N/C | N/A |
| headrest mounting | 233.00 | 233.00 |
| supple back, fabric | N/C | 70.00 |
| supple back, leatherette | N/C | 90.00 |
| padded back, contoured, leatherette | 423.00 | 423.00 |
| padded back, contoured, fabric | 317.00 | 317.00 |
| padded back, contoured, fabric, non-standard sizes | 402.00 | 402.00 |
| padded back, contoured, leatherette, non-standard sizes | 508.00 | 508.00 |
| padded seat, contoured, fabric | 255.00 | 255.00 |
| padded seat, contoured, fabric, non-standard sizes | 337.00 | 337.00 |
| padded seat, contoured, leatherette | 361.00 | 361.00 |
| padded seat, contoured, leatherette, non-standard sizes | 447.00 | 447.00 |
| rigid seat, flat | N/C | 79.00 |
| modification of back height to 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.), 58.4 cm (23 in.) or 61.0 cm (24 in.) | 92.00 | N/A |
| modification of seat depth to 48.3 cm (19 in.) or 50.8 cm (20 in.) | 128.00 | N/A N/A |
| modification of seat depth to 46.3 cm (19 iii.) of 30.8 cm (20 iii.) modification of seat depth ASBA to 53.3 cm (21 iii.) | 128.00 | IV/A |
| or 55.9 cm (22 in.) | 235.00 | N/A |
| modification of seat width to 48.3 cm (19 in.), 50.8 cm (20 in.), | 233.00 | IV/A |
| 53.3 cm (21 in.) or 55.9 cm (22 in.) | 230.00 | N/A |
| modification of seat width ASBA to 58.4 cm (23 in.) | 230.00 | 11/11 |
| or 61.0 cm (24 in.) | 288.00 | N/A |
| modification of seat height, to 54.6 cm (21 ¹ / ₂ in.) | 134.00 | N/A |
| centre of gravity adjustment from seat | N/C | N/A |
| push handles | N/C | 42.00 |
| push bar | N/C | 61.00 |
| seat cushion, flat, foam, 5.1 cm (2 in.) | 59.00 | 59.00 |
| seat cushion, flat, foam, 7.6 cm (3 in.) | 59.00 | 59.00 |
| safety belt, auto-type | N/C | 53.00 |
| Armrests: | | |
| U-type armrests, height-adjustable from 20.3 cm (8 in.) | | |
| to 30.5 cm (12 in.), short, long | N/C | 120.00 |
| U-type armrests, fixed-height, short, long | N/C | 100.00 |
| padded armrests, straight, contoured, short, long | N/C | 26.00 |
| ministration of the second of the site of the second of th | N/C | N/A |
| rigid clothing guards built into armrests modification of armrests by -2.5 cm (1 in.) | 188.00 | N/A |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| Footrests: | | |
| 60° footrests, parallel, detachable, swingaway, length-adjustable | | |
| from 34.3 cm $(13^{1}/_{2} \text{ in.})$ to 44.5 cm $(17^{1}/_{2} \text{ in.})$; 70° footrests, paral | lel, | |
| detachable, swingaway, length-adjustable from 29.8 cm $(11^3\hat{l}_4 \text{ in.})$ | | 114.00 |
| to 43.2 cm (17 in.) | N/C | 114.00 |
| footrests, tapered, detachable, swingaway, length-adjustable from 34.3 cm (13 ¹ / ₂ in.) to 44.5 cm (17 ¹ / ₂ in.) | 113.00 | 170.00 |
| 60° footrests, MFX, parallel, detachable, swingaway, | 113.00 | 170.00 |
| length-adjustable from 24.1 cm (9 $^{1}/_{2}$ in.) to 36.8 cm (14 $^{1}/_{2}$ in.); | | |
| 70° footrests, MFX, parallel, detachable, swingaway, | | |
| length-adjustable from 11.4 cm ($4^{1}/_{2}$ in.) to 25.4 cm (10 in.) | 113.00 | 170.00 |
| 90° footrests, parallel, detachable, swingaway, length-adjustable | | |
| from 12.7 cm (5 in.) to 20.3 cm (8 in.) | 113.00 | 170.00 |
| elevating legrests, length-adjustable from 40.6 cm (16 in.) | | |
| to 50.8 cm (20 in.) | 244.00 | 236.00 |
| elevating legrests, with compensating mechanism, length-adjustal | ble | |
| from 43.8 cm $(17^{1}/_{4} \text{ in.})$ to 54.6 cm $(21^{1}/_{2} \text{ in.})$ | 160.00 | 190.00 |
| modification of elevating legrest length, by -2.5 cm (1 in.) | | |
| or -5.1 cm (2 in.), not available on legrests with compensating | | |
| mechanisms | 250.00 | 250.00 |
| padded calfrests | N/C | 28.00 |
| single calf strap | 25.00 | 37.00 |
| double calf strap | 38.00 N/C | 55.00 42.00 |
| folding footplates, standard oversized footplates | 45.00 | 65.00 |
| full-width footplate, wooden | 83.00 | 101.00 |
| footplates, angle-adjustable and depth-adjustable, standard | 76.00 | 80.00 |
| footplates, angle-adjustable and depth-adjustable, oversized | 76.00 | 80.00 |
| neel loops, fixed | N/C | 15.00 |
| neel loops, adjustable | N/C | 7.00 |
| clamps, 1.8 cm ($^{3}/_{4}$ in.) to 2.5 cm (1 in.), making it possible | | |
| to install footplates higher up on the legrest bracket | 30.00 | 15.00 |
| | | |
| Frame: | | |
| neavy-duty frame or robust base | N/C | N/A |
| rear suspension | N/C | N/A |
| rear reflectors | N/C | N/A |
| ie-down points for adapted transport | N/C | 100.00 |
| running lights | N/C | N/A |
| anti-tip rollers | N/C | N/A |
| Drive systems: | | |
| programmable joystick control | N/C | 503.00 |
| compact joystick control, including display module | 1 257.00 | 1 760.00 |
| heavy-duty joystick control, including display and interface | 1 891.00 | 2 394.00 |
| ouch pad control | 967.00 | 1 470.00 |
| nodification of joystick control, each | 75.00 | 75.00 |
| nounication of joystick control, each | | |
| battery charge display | N/C | N/A |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| pattery boxes, group 22 | N/C | 195.00 |
| pattery boxes, group 24 | N/C | 211.00 |
| control with separate switches, including display and interface | 1 790.00 | 1 980.00 |
| proportional chin control, including display | 1 257.00 | 1 760.00 |
| non-proportional chin control, including display and interface | 1 790.00 | 2 293.00 |
| preath control, including display and interface | 1 790.00 | 2 293.00 |
| nead control, including display | 1 235.00 | 1 738.00 |
| aptray touch switch control, including display | 1 384.00 | 1 887.00 |
| oot control, including display | 1 384.00 | 1 887.00 |
| oggle switch | N/C | 19.00 |
| emergency stop ribbon switch | 55.00 | 79.00 |
| FASH micro light switch | 167.00 | 167.00 |
| ASL egg switch | 140.00 | 140.00 |
| dapted controls interface | 727.00 | 727.00 |
| non-proportional controls interface | 727.00 | 727.00 |
| eparate display module | 1 063.00 | 1 063.00 |
| lirection joystick | N/C | 133.00 |
| tick extension | 21.00 | 21.00 |
| all extension | 7.00 | 7.00 |
| E-type extension | 21.00 | 21.00 |
| wivel side bracket for joystick control | N/C | 250.00 |
| ide bracket for joystick control | N/C | 15.00 |
| wivel midline bracket for joystick control | 118.00 | 197.00 |
| breath control bracket | 357.00 | 357.00 |
| hin control bracket | 357.00 | 357.00 |
| nead control bracket | 150.00 | 150.00 |
| oracket for separate display module | 115.00 | 115.00 |
| hin bib control | 333.00 | 333.00 |
| ontroller | N/C | 1 358.00 |
| eavy-duty motors | N/C | 1 139.00 |
| Vheel locks: | 1,, C | 1 137.00 |
| nanual auxiliary brakes | 72.00 | 45.00 |
| Wheels and forks: | | |
| eflector strips | N/C | N/A |
| ear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) | N/C | 55.00 |
| ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) ront wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.), | N/C | 82.00 |
| $0.3 \text{ cm } (8 \text{ in.}) \times 5.7 \text{ cm } (2^{1}/_{4} \text{ in.})$ | N/C | 42.00 |
| ront wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm ($2^{3}/_{4}$ in.) | 84.00 | 82.00 |
| ront wheel rims | N/C | N/A |
| ear wheel rims | N/C | 62.00 |
| irless inserts for rear wheels | 95.00 | N/A |
| irless inserts for front wheels | 94.00 | N/A |
| tandard forks | N/C | 57.00 |
| uspension forks | 130.00 | 125.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| Component(s) under Special Consideration | | |
| seat/back structure, with reclining back and cylinder (ASBA)* | 776.00 | 776.00 |
| control system for one power accessory only (required only to | | |
| activate the tipping mechanism with the joystick)* | 478.00 | 938.00 |
| control system for several power accessories | | |
| (COM12 for two accessories)* | 341.00 | 839.00 |
| control system for several power accessories | | |
| (COM34 for two additional accessories)* | 341.00 | 839.00 |
| power rocker device (INVACARE PTO)* | 1 400.00 | 1 400.00 |
| power elevating legrests (INVACARE)* | 1 479.00 | 1 409.00 |
| TAC control module for power elevating legrests (INVACARE)* | 515.00 | 515.00 |
| TRCM module to activate power legrests and rocker device | | |
| using the joystick* | 960.00 | 960.00 |

SUPPLIER: SUNRISE MEDICAL CANADA INC.

PRICE

POWERED WHEEL CHAIR, ADULT QUICKIE S 525 MODEL

\$4 390.00

Basic Components

Body support system

- · supple seat, nylon
- supple back, nylon
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat heights: 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.)
- back height: from 38.1 cm (15 in.) to 50.8 cm (20 in.)
- back, angle-adjustable from 86° to 102°
- safety belt, auto-type, velcro-type

Armrests

- T-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 30.5 cm (12 in.), short, long
- I-type armrests, flip-back, inclinable, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long, straight, contoured, for SP101
- · armrest pads, straight, short, long
- · armrest pads, contoured, short, long

Footrests

- 70° footrests, parallel, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 54.6 cm (21¹/₂ in.)
- 90° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- padded calfrests
- · folding footplates, standard
- heel loops, adjustable

Frame

- · rear reflectors
- · tie-down points for adapted transport
- anti-tip rollers
- back tension bar
- · push handles

Drive systems

- control system for one power accessory only (Solo 40)*
- programmable joystick control
- battery charge display
- toggle switch
- · battery charger
- battery boxes, group 22
- side bracket for joystick control
- swivel side bracket for joystick control
- controller
- · motors

- driving wheels, inner tube tires, 30.5 cm (12 in.) x 7.6 cm (3 in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- · rear wheel rims
- front wheel rims
- · standard forks

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| seat/back structure, with angle-adjustable back | 645.00 | 645.00 |
| folding back | 121.00 | N/A |
| headrest, small | 99.00 | 106.00 |
| headrest, medium | 99.00 | 106.00 |
| headrest, large | 99.00 | 106.00 |
| headrest mounting, articulated | 159.00 | 173.00 |
| crossbar for headrest mounting | 201.00 | 213.00 |
| supple back, nylon | N/C | 71.00 |
| back, angle-adjustable from 86° to 102° | N/C | N/A |
| padded back, contoured, fabric | 314.00 | 385.00 |
| padded back, contoured, fabric, with rigid structure | 405.00 | 476.00 |
| padded back, contoured, velour | 350.00 | 421.00 |
| padded back, contoured, velour, with rigid structure | 433.00 | 504.00 |
| supple back, tension-adjustable | 76.00 | 147.00 |
| rigid seat, flat | 88.00 | 142.00 |
| padded seat, contoured, velour | 332.00 | 355.00 |
| padded seat, contoured, fabric | 254.00 | 308.00 |
| modification of seat width to 48.3 cm (19 in.) or 50.8 cm (20 in.) | 297.00 | N/A |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| modification of seat depth to 48.3 cm (19 in.) or 50.8 cm (20 in.) | 200.00 | N/A |
| supple seat, nylon | N/C | 54.00 |
| seat cushion, flat, foam, 5.1 cm (2 in.) | 58.00 | 58.00 |
| seat cushion, flat, foam, 7.6 cm (3 in.) | 58.00 | 58.00 |
| safety belt, auto-type | N/C | 42.00 |
| safety belt, velcro-type | N/C | 29.00 |
| Armrests: | | |
| T-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) |) N/C | 136.00 |
| to 30.5 cm (12 in.), short, long U-type armrests, detachable, height-adjustable from 24.1 cm ($9^{1}/_{2}$ in | | 130.00 |
| to 35.6 cm (14 in.), short, long | 90.00 | 181.00 |
| I-type armrests, flip-back, inclinable, height-adjustable from | 90.00 | 101.00 |
| 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long, straight, | | |
| contoured, for SP101 | N/C | 136.00 |
| I-type armrests, flip-back, inclinable, height-adjustable, with | IV/C | 130.00 |
| transfer assists and clothing guards, for SP101, short, long | 160.00 | 216.00 |
| armrest pads, straight, short | N/C | 15.00 |
| armrest pads, straight, short | N/C | 18.00 |
| armrest pads, straight, long | N/C | 26.00 |
| modification of T-type armrest height from 15.2 cm (6 in.) | TV/C | 20.00 |
| to 24.8 cm ($9^3/_4$ in.) | 82.00 | N/A |
| Footrests: | | |
| 70° footrests, parallel, detachable, swingaway, length-adjustable | | |
| from 27.9 cm (11 in.) to 54.6 cm (21 ¹ / ₂ in.) | N/C | 140.00 |
| 90° footrests, parallel, detachable, swingaway, length-adjustable | | |
| from 20.3 cm (8 in.) to 33.0 cm (13 in.) | N/C | 140.00 |
| 70° footrests, heavy-duty, parallel, detachable, swingaway, | | |
| length-adjustable from 27.9 cm (11 in.) to 54.6 cm $(21^{1}/_{2} in.)$ | 41.00 | N/A |
| angled footrests, from 55° to 70°, on SP101 | 160.00 | 220.00 |
| modification of 90° footrest length by 5.1 cm (2 in.) | | |
| or 10.2 cm (4 in.) | 32.00 | 16.00 |
| elevating legrests | 178.00 | 229.00 |
| padded calfrests | N/C | 19.00 |
| contoured calfrests | 72.00 | 55.00 |
| single calf strap | 19.00 | 19.00 |
| double calf strap | 33.00 | 33.00 |
| folding footplates, standard | N/C | 49.00 |
| oversized footplates | 74.00 | 86.00 |
| folding footplates, multi-position | 106.00 | 102.00 |
| folding footplates, angle-adjustable and depth-adjustable, | 54.00 | 77.00 |
| standard size | 54.00 | 76.00 |
| heel loops, adjustable | N/C | 10.00 |
| Frame: heavy-duty frame or robust base | 128.00 | N/A |
| motorization for over 250 lb. | 78.00 | 942.00 |
| rear reflectors | N/C | 942.00 N/A |
| tie-down points for adapted transport | N/C N/C | 120.00 |
| ne-down points for adapted transport | IN/C | 120.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, | Price upon replacement of component (unit price) |
|--|--|---|
| | as applicable) | |
| anti-tip rollers | N/C | N/A |
| centre of gravity adjustment | 67.00 | N/A |
| push handles | N/C | N/A |
| push handles, with 8° angle | 23.00 | N/A |
| back tension bar | N/C | N/A |
| front impact guard with rollers | 38.00 | 19.00 |
| Drive systems: | | |
| programmable joystick control | N/C | 630.00 |
| battery charge display | N/C | N/A |
| battery charger | N/C | 384.00 |
| battery boxes, group 22 | N/C | 121.00 |
| proportional chin control (requires interface) | 555.00 | 555.00 |
| non-proportional chin control | 555.00 | 555.00 |
| breath control (requires interface) | 426.00 | 426.00 |
| head control (requires interface) | 555.00 | 555.00 |
| laptray touch switch control (requires interface) | 314.00 | 314.00 |
| foot control, including bracket | 1 740.00 | 1 740.00 |
| control with separate switches (requires interface) | 1 770.00 | 1 770.00 |
| proportional mini-joystick control (requires interface) | 790.00 | 1 090.00 |
| adapted controls interface with built-in display module | 1 445.00 | 1 445.00 |
| auxiliary switch | 91.00 | 96.00 |
| modification of joystick control | 121.00 | 751.00 |
| toggle switch | N/C | N/A |
| push-button switch | 88.00 | N/A |
| ball extension | 52.00 | 52.00 |
| T-type extension | 52.00 | 52.00 |
| stick extension | 21.00 | 21.00 |
| adjustable bracket for joystick control bracket | 66.00 | 66.00 |
| modification, repositioning of joystick bracket inward | 120.00 | N/A |
| swivel side bracket for joystick control | N/C | 188.00 |
| swivel midline bracket for joystick control | 163.00 | 351.00 |
| side bracket for joystick control | N/C | 74.00 |
| breath control bracket | 352.00 | 352.00 |
| chin control bracket | 352.00 | 352.00 |
| head control bracket | 352.00 | 352.00 |
| bracket for separate display module | 352.00 | 352.00 |
| chin bib control | 352.00 | 352.00 |
| controller motors | N/C N/C | 1 453.00 979.00 |
| Wheel locks: | | |
| manual auxiliary brakes | 53.00 | 43.00 |
| wheel lock extensions | 38.00 | 19.00 |
| wheel lock extensions | 36.00 | 19.00 |
| Wheels and forks: | 20.00 | 53 00 |
| front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 28.00 | 72.00 |
| front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | | 58.00 |
| driving wheels, inner tube tires, 30.5 cm (12 in.) x 7.6 cm (3 in.) | N/C | 145.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| front wheel rims | N/C | 40.00 |
| rear wheel rims | N/C | 131.00 |
| airless inserts for rear wheels | 136.00 | N/A |
| airless inserts for front wheels | 114.00 | N/A |
| standard forks | N/C | 62.00 |
| Component(s) under Special Consideration | | |
| seat/back structure, SP101, for power mechanism* seat/back structure, SP101, with manual compensating | 850.00 | 850.00 |
| reclining back and cylinder* | 1 185.00 | 1 185.00 |
| control system for one power accessory only (Solo 40)* | N/C | 275.00 |
| control system for four power accessories (Quattro)* | 575.00 | 575.00 |
| power reclining back, compensating mechanism, SP101* | 1 100.00 | 1 950.00 |
| power rocker device, from 0° to 55°* | 1 695.00 | 1 695.00 |
| power elevating legrests, per pair, including legrests, footplates, on SP101, requires Solo controller* | 1 295.00 | 1 072.00 |
| power elevating legrests, per unit, including legrests, footplates, on SP101, requires Quattro controller* interface for activation via joystick* | 1 295.00 450.00 | 1 072.00 525.00 |

SUPPLIER: SUNRISE MEDICAL CANADA INC.

PRICE

POWERED WHEEL CHAIR, ADULT QUICKIE S 646 SE MODEL

\$4 841.00

Basic Components

Body support system

- supple back, nylon
- rigid seat, flat
- seat rails, parallel
- · centre of gravity adjustment from seat
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat height: from 43.8 cm $(17^{1}/_{4} \text{ in.})$ to 59.7 cm $(23^{1}/_{2} \text{ in.})$
- back height: from 38.1 cm (15 in.) to 50.8 cm (20 in.)
- safety belt, auto-type, velcro-type

Armrests

- T-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 30.5 cm (12 in.), short, long
- I-type armrests, flip-back, inclinable, height-adjustable, for SP101
- armrest pads, straight, short, long
- · armrest pads, contoured, short, long

Footrests

 70° footrests, parallel, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 54.6 cm (21¹/₂ in.)

- 90° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- padded calfrests for elevating legrests
- · folding footplates, standard
- · heel loops, adjustable

Frame

- · rear suspension
- · rear reflectors
- running lights
- tie-down points for adapted transport
- · adjustable seat bracket
- · push handles
- back tension bar

Drive systems

- control system for one power accessory only (Solo 40)*
- programmable joystick control
- battery charge display
- · toggle switch
- · battery charger
- battery boxes, group 22, group 24
- side bracket for joystick control
- · swivel side bracket for joystick control
- · controller
- motors

- driving wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- · rear wheel rims
- · front wheel rims
- · standard forks

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| seat/back structure, with angle-adjustable back, Trax system | 684.00 | 684.00 |
| headrest, small | 99.00 | 106.00 |
| headrest, medium | 99.00 | 106.00 |
| headrest, large | 99.00 | 106.00 |
| headrest mounting, articulated | 159.00 | 173.00 |
| supple back, nylon | N/C | 71.00 |
| supple back, tension-adjustable | 76.00 | 147.00 |
| padded back, contoured, fabric | 314.00 | 385.00 |
| padded back, contoured, velour | 350.00 | 421.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| padded back, contoured, velour, with rigid base | 433.00 | 504.00 |
| padded back, contoured, fabric, with rigid base | 405.00 | 476.00 |
| modification of back height from 53.3 cm (21 in.) to 61.0 cm (24 | | N/A |
| padded back, contoured, velour, from 53.3 cm (21 in.) o 61.0 cm (24 in.) | 391.00 | 462.00 |
| padded back, contoured, fabric, from 53.3 cm (21 in.) | | |
| o 61.0 cm (24 in.) | 359.00 | 431.00 |
| padded back, contoured, velour, with rigid structure, | | |
| from 53.3 cm (21 in.) to 61.0 cm (24 in.) | 490.00 | 561.00 |
| padded back, contoured, fabric, with rigid structure, | | |
| rom 53.3 cm (21 in.) to 61.0 cm (24 in.) | 466.00 | 537.00 |
| igid seat, flat | N/C | 141.00 |
| padded seat, contoured, fabric | 254.00 | 308.00 |
| added seat, contoured, velour | 332.00 | 355.00 |
| eat rails, parallel | N/C | 31.00 |
| eat rails, tapered | 72.00 | 67.00 |
| nodification of seat width to 48.3 cm (19 in.), 50.8 cm (20 in.), | | |
| 75.9 cm (22 in.) or 61.0 cm (24 in.) | 401.00 | N/A |
| nodification of seat depth to 48.3 cm (19 in.), 50.8 cm (20 in.), | | |
| 53.3 cm (21 in.) or 55.9 cm (22 in.) | 265.00 | N/A |
| eat cushion, flat, foam, 5.1 cm (2 in.) | 58.00 | 58.00 |
| eat cushion, flat, foam, 7.6 cm (3 in.) | 58.00 | 58.00 |
| afety belt, auto-type | N/C | 42.00 |
| afety belt, velcro-type | N/C | 29.00 |
| centre of gravity adjustment from seat | N/C | N/A |
| Armrests: | | |
| Γ-type armrests, detachable, height-adjustable from 25.4 cm (10) | in.) | |
| o 30.5 cm (12 in.), short, long | N/C | 136.00 |
| J-type armrests, height-adjustable, short, long | 90.00 | 181.00 |
| -type armrests, flip-back, inclinable, height-adjustable, for SP10-type armrests, flip-back, inclinable, height-adjustable, with | 01 N/C | 136.00 |
| ransfer assists and clothing guards, short, long, for SP101 nodification of T-type armrest height from 15.2 cm (6 in.) | 160.00 | 216.00 |
| o 24.8 cm $(9^3/_4 \text{ in.})$ | 82.00 | N/A |
| urmrest pads, straight, short | N/C | 15.00 |
| | N/C N/C | 18.00 |
| urmrest pads, straight, long urmrest pads, contoured, short, long | N/C N/C | 26.00 |
| • | N/C | 20.00 |
| Footrests: 70° footrests, parallel, detachable, swingaway, length-adjustable | | |
| from 27.9 cm (11 in.) to 54.6 cm ($21^{1}/_{2}$ in.) | N/C | 140.00 |
| 00° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) | N/C | 140.00 |
| 70° footrests, heavy-duty, parallel, detachable, swingaway, | | |
| ength-adjustable from 29.2 cm $(11^{1}/_{2} \text{ in.})$ to 54.6 cm $(21^{1}/_{2} \text{ in.})$ | 41.00 | N/A |
| ingled footrests, adjustable from 55° to 70°, on SP101 | 160.00 | 220.00 |
| elevating legrests | 178.00 | 229.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| padded calfrests for elevating legrests | N/C | 19.00 |
| contoured calfrests | 72.00 | 55.00 |
| single calf strap | 19.00 | 19.00 |
| double calf strap | 33.00 | 33.00 |
| folding footplates, standard | N/C | 49.00 |
| oversized footplates | 74.00 | 86.00 |
| folding footplates, angle-adjustable, locking | 80.00 | 178.00 |
| folding footplates, angle-adjustable and depth-adjustable, oversize | | 76.00 |
| folding footplates, multi-position | 106.00 | 102.00 |
| heel loops, adjustable | N/C | 10.00 |
| front impact guard with rollers | 38.00 | 19.00 |
| mont impact guard with foners | 36.00 | 19.00 |
| Frame: running lights | N/C | N/A |
| rear suspension | N/C N/C | N/A N/A |
| rear reflectors | N/C N/C | N/A N/A |
| | | |
| tie-down points for adapted transport | N/C | 131.00 |
| push handles | N/C | N/A |
| back tension bar | N/C | N/A |
| adjustable seat bracket | N/C | N/A |
| Drive systems: | 3316 | 600.00 |
| programmable joystick control | N/C | 630.00 |
| battery charge display | N/C | N/A |
| battery charger | N/C | 384.00 |
| battery boxes, group 22, group 24 | N/C | N/A |
| proportional chin control (requires interface) | 555.00 | 555.00 |
| non-proportional chin control (requires interface) | 555.00 | 555.00 |
| nead control (requires interface) | 555.00 | 555.00 |
| aptray touch switch control (requires interface) | 314.00 | 314.00 |
| control with separate Zero Touch switches (requires interface) | 1 770.00 | 1 770.00 |
| oreath control (requires interface) | 426.00 | 426.00 |
| proportional mini-joystick control (requires interface) | 790.00 | 1 090.00 |
| Foot control, including bracket (requires interface) | 1 740.00 | 1 740.00 |
| adapted controls interface with built-in display module | 1 445.00 | 1 445.00 |
| nterface pour activation via joystick | 450.00 | 525.00 |
| auxiliary switch | 91.00 | 96.00 |
| toggle switch | N/C | N/A |
| bush-button switch | 88.00 | N/A |
| nodification of joystick control for auxiliary switch | 121.00 | 751.00 |
| pall extension | 52.00 | 52.00 |
| Γ-type extension | 52.00 | 52.00 |
| stick extension | 21.00 | 21.00 |
| swivel side bracket for joystick control | N/C | 188.00 |
| | 163.00 | 351.00 |
| swivel midline bracket for joystick control | N/C | |
| side bracket for joystick control | | 74.00 |
| breath control bracket chin control bracket | 352.00 352.00 | 352.00 352.00 |
| | | |

| head control bracket bracket for separate display module adjustable bracket for joystick control modification, repositioning of joystick bracket inward chin bib control controller motors high-torque transmission, heavy-duty Wheel locks: manual auxiliary brakes wheel lock extensions Wheels and forks: | 352.00 352.00 66.00 120.00 352.00 N/C N/C 281.00 | 352.00 352.00 66.00 N/A 352.00 1 586.00 1 123.00 N/A |
|--|---|---|
| adjustable bracket for joystick control modification, repositioning of joystick bracket inward chin bib control controller motors high-torque transmission, heavy-duty Wheel locks: manual auxiliary brakes wheel lock extensions Wheels and forks: | 66.00 120.00 352.00 N/C N/C | 66.00 N/A 352.00 1 586.00 1 123.00 |
| modification, repositioning of joystick bracket inward chin bib control controller motors high-torque transmission, heavy-duty Wheel locks: manual auxiliary brakes wheel lock extensions Wheels and forks: | 120.00 352.00 N/C N/C | N/A 352.00 1 586.00 1 123.00 |
| modification, repositioning of joystick bracket inward chin bib control controller motors nigh-torque transmission, heavy-duty Wheel locks: manual auxiliary brakes wheel lock extensions Wheels and forks: | 352.00 N/C N/C | 352.00 1 586.00 1 123.00 |
| chin bib control controller notors nigh-torque transmission, heavy-duty Wheel locks: nanual auxiliary brakes wheel lock extensions Wheels and forks: | N/C N/C | 1 586.00 1 123.00 |
| motors nigh-torque transmission, heavy-duty Wheel locks: manual auxiliary brakes wheel lock extensions Wheels and forks: | N/C | 1 123.00 |
| notors high-torque transmission, heavy-duty Wheel locks: hanual auxiliary brakes wheel lock extensions Wheels and forks: | N/C | 1 123.00 |
| Wheel locks: nanual auxiliary brakes wheel lock extensions Wheels and forks: | | |
| Wheel locks: nanual auxiliary brakes wheel lock extensions Wheels and forks: | 201.00 | |
| nanual auxiliary brakes wheel lock extensions Wheels and forks: | | 11/11 |
| wheel lock extensions Wheels and forks: | 53.00 | 43.00 |
| Wheels and forks: | 38.00 | 19.00 |
| | | |
| ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | N/C | 72.00 |
| ront wheels, solid tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | N/C | 84.00 |
| front wheels, solid tires, 22.9 cm (9 in.) x 7.6 cm (3 in.) | 69.00 | 97.00 |
| ront wheels, inner tube tires, 22.9 cm (9 in.) x 7.6 cm (3 in.) | 69.00 | 97.00 |
| driving wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) | N/C | 215.00 |
| ront wheel rims | N/C | 40.00 |
| ear wheel rims | N/C | 47.00 |
| irless inserts for rear wheels | 136.00 | N/A |
| tandard forks | N/C | 87.00 |
| uspension forks, up to 68 kg (150 lb.) | 135.00 | N/A |
| uspension forks, up to 114 kg (250 lb.) | 135.00 | N/A |
| uspension forks, up to 182 kg (400 lb.) | 135.00 | N/A |
| | 133.00 | 1771 |
| Component(s) under Special Consideration eat/back structure, for power mechanism, SP101* | 850.00 | 850.00 |
| eclining back with cylinder, compensating mechanism, SP101* | 1 185.00 | 1 185.00 |
| ower reclining back, compensating mechanism, SP101* | 1 100.00 | 1 950.00 |
| ower rocker device, 0° to 55°* | 1 695.00 | 1 695.00 |
| ower elevating legrests, per pair, including legrests and footplates | 1 0/3.00 | 1 075.00 |
| on SP101, requires Solo controller* | 1 295.00 | 1 072.00 |
| ower elevating legrests, per unit, including legrests and footplates | 1 2/3.00 | 1 072.00 |
| in SP101, requires Quattro controller* | 1 295.00 | 1 072.00 |
| ontrol system for one power accessory only (Solo 40)* | N/C | 275.00 |
| ontrol system for four power accessories (Quattro)* | 575.00 | 273.00 |

SUPPLIER: SUNRISE MEDICAL CANADA INC.

PRICE

POWERED WHEEL CHAIR, ADULT FREESTYLE F11 MODEL

\$4 340

Basic Components

Body support system

- rigid seat, flat
- seat rails, parallel

- supple back, nylon
- seat width: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat depth: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat height: from 43.8 cm $(17^{1}/_{4} \text{ in.})$ to 54.6 cm $(21^{1}/_{2} \text{ in.})$
- back height: from 38.1 cm (15 in.) to 50.8 cm (20 in.)
- · adjustable seat bracket
- back, angle-adjustable from 84° to 124°
- safety belt, auto-type, velcro-type

Armrests

- T-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 30.5 cm (12 in.), short, long
- I-type armrests, flip-back, inclinable, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long, straight, contoured, for SP101
- armrest pads, straight, short, long
- · armrest pads, contoured, short, long

Footrests

- 70° footrests, parallel, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 54.6 cm (21½ in.)
- 90° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- · padded calfrests for elevating legrests
- · folding footplates, standard
- heel loops, adjustable

Frame

- · rear reflectors
- · running lights
- · tie-down points for adapted transport
- rear suspension
- · back tension bar
- push handles

Drive systems

- control system for one power accessory only (Solo 40)*
- programmable joystick control
- battery charge display
- · toggle switch
- battery charger
- battery boxes, group 22, group 24
- side bracket for joystick control
- swivel side bracket for joystick control
- · controller
- · motors

- driving wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)
- · rear wheel rims
- · front wheel rims
- · standard forks

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| seat/back structure, with angle-adjustable back, Trax system | 684.00 | 684.00 |
| headrest, small | 99.00 | 106.00 |
| headrest, medium | 99.00 | 106.00 |
| headrest, large | 99.00 | 106.00 |
| headrest mounting, articulated | 159.00 | 173.00 |
| supple back, nylon | N/C | 71.00 |
| supple back, tension-adjustable | 76.00 | 147.00 |
| back, angle-adjustable from 84° to 124° | N/C | N/A |
| padded back, contoured, fabric | 314.00 | 385.00 |
| padded back, contoured, velour | 350.00 | 421.00 |
| padded back, contoured, velour, with rigid base | 433.00 | 504.00 |
| padded back, contoured, fabric, with rigid base | 405.00 | 476.00 |
| padded back, contoured, velour, from 53.3 cm (21 in.) | | |
| to 61.0 cm (24 in.) | 391.00 | 462.00 |
| padded back, contoured, fabric, from 53.3 cm (21 in.) | | |
| to 61.0 cm (24 in.) | 359.00 | 431.00 |
| padded back, contoured, fabric, with rigid base, | | |
| from 53.3 cm (21 in.) to 61.0 cm (24 in.) | 466.00 | 537.00 |
| padded back, contoured, velour, with rigid base, | | |
| from 53.3 cm (21 in.) to 61.0 cm (24 in.) | 490.00 | 561.00 |
| supple seat, nylon (in-factory only) | 293.00 | N/A |
| rigid seat, flat | N/C | 141.00 |
| padded seat, contoured, fabric | 254.00 | 308.00 |
| padded seat, contoured, velour | 332.00 | 355.00 |
| seat rails, parallel | N/C | 31.00 |
| seat rails, tapered | 72.00 | 67.00 |
| adjustable seat bracket | N/C | N/A |
| seat cushion, flat, foam, 5.1 cm (2 in.) | 58.00 | 58.00 |
| seat cushion, flat, foam, 7.6 cm (3 in.) | 58.00 | 58.00 |
| modification of seat width to 48.3 cm (19 in.) or 50.8 cm (20 in.) | 295.00 | N/A |
| modification of seat width to 53.3 cm (21 in.), 55.9 cm (22 in.), | 2,0.00 | 1,111 |
| 58.4 cm (23 in.) or 61.0 cm (24 in.) | 330.00 | N/A |
| modification of seat depth to 48.3 cm (19 in.), 50.8 cm (20 in.), | 330.00 | 1771 |
| 53.3 cm (21 in.) or 55.9 cm (22 in.) | 265.00 | N/A |
| modification of back height to 53.3 cm (21 in.), 55.9 cm (22 in.), | 203.00 | 14/11 |
| 58.4 cm (23 in.) or 61.0 cm (24 in.) | 83.00 | N/A |
| safety belt, auto-type | N/C | 42.00 |
| safety belt, talko type safety belt, velcro-type | N/C | 29.00 |
| Armrests: | | |
| T-type armrests, detachable, height-adjustable from 25.4 cm (10 in | .) | |
| to 30.5 cm (12 in.), short, long | N/C | 136.00 |
| modification of T-type armrests from 15.2 cm (6 in.) | | |
| to 24.8 cm (9 ³ / ₄ in.) | 82.00 | N/A |
| | | |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| U-type armrests, height-adjustable, short, long I-type armrests, flip-back, inclinable, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long, straight, | 90.00 | 181.00 |
| contoured, for SP101 | N/C | 136.00 |
| I-type armrests, flip-back, inclinable, height-adjustable, with transfer assists and clothing guards, short, long, for SP101 | 160.00 | 216.00 |
| armrest pads, straight, short | N/C | 15.00 |
| armrest pads, straight, long | N/C | 18.00 |
| armrest pads, straight, long | N/C | 26.00 |
| Footrests: | | |
| contracture footrests | 316.00 | 316.00 |
| 70° footrests, parallel, detachable, swingaway, length-adjustable | | |
| from 27.9 cm (11 in.) to 54.6 cm (21 ¹ / ₂ in.) | N/C | 140.00 |
| 70° footrests, heavy-duty, parallel, detachable, swingaway, | | |
| length-adjustable from 27.9 cm (11 in.) to 54.6 cm (21½ in.) | 41.00 | N/A |
| 90° footrests, parallel, detachable, swingaway, length-adjustable | N/C | 140.00 |
| from 20.3 cm (8 in.) to 33.0 cm (13 in.) angled footrests, adjustable from 55° to 70°, on SP101 | 160.00 | 220.00 |
| modification of footrest length by 5.1 cm (2 in.) or | 100.00 | 220.00 |
| by 10.2 cm (4 in.) | 32.00 | 16.00 |
| elevating legrests | 178.00 | 229.00 |
| padded calfrests for elevating legrests | N/C | 19.00 |
| contoured calfrests for elevating legrests | 72.00 | 55.00 |
| single calf strap | 19.00 | 19.00 |
| double calf strap | 33.00 | 33.00 |
| folding footplates, standard size | N/C | 49.00 |
| oversized footplates | 74.00 | 86.00 |
| folding footplates, oversized, angle-adjustable and depth-adjustable | 54.00 | 76.00 |
| folding footplates, multi-position | 106.00 | 102.00 |
| folding footplates, angle-adjustable, locking | 80.00 | 178.00 |
| heel loops, adjustable | N/C | 10.00 |
| Frame: | | |
| rear suspension | N/C | N/A |
| rear reflectors | N/C | N/A |
| running lights | N/C | N/A |
| tie-down points for adapted transport | N/C | 140.00 |
| front impact guard with rollers | 38.00 | 19.00 |
| back tension bar | N/C | N/A |
| push handles cane holder | N/C 45.00 | N/A 45.00 |
| | - | |
| Drive systems: | N/C | 620.00 |
| programmable joystick control | N/C N/C | 630.00 N/A |
| battery charger | N/C N/C | N/A 384.00 |
| battery charger battery boxes, group 22, group 24 | N/C N/C | 384.00 N/A |
| proportional chin control (requires interface) | 555.00 | 555.00 |
| proportional citili control (requires interface) | 333.00 | 333.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| non-proportional chin control (requires interface) | 555.00 | 555.00 |
| preath control (requires interface) | 426.00 | 426.00 |
| nead control (requires interface) | 555.00 | 555.00 |
| aptray touch switch control (Penta, T-shape, Wafer) | | |
| requires interface) | 314.00 | 314.00 |
| foot control, including bracket (requires interface) | 1 740.00 | 1 740.00 |
| control with separate switches (Zero Touch) (requires interface) | 1 770.00 | 1 770.00 |
| proportional mini-joystick control (requires interface) | 790.00 | 1 090.00 |
| dapted controls interface with built-in display module | 1 445.00 | 1 445.00 |
| nterface for activation via joystick | 450.00 | 525.00 |
| uxiliary switch | 91.00 | 96.00 |
| oggle switch | N/C | N/A |
| bush-button switch | 88.00 | N/A |
| nodification of joystick control for auxiliary switch | 121.00 | 751.00 |
| pall extension | 52.00 | 52.00 |
| Γ-type extension | 52.00 | 52.00 |
| tick extension | 21.00 | 21.00 |
| ide bracket for joystick control | N/C | 74.00 |
| wivel side bracket for joystick control | N/C | 188.00 |
| wivel midline bracket for joystick control | 163.00 | 351.00 |
| preath control bracket | 352.00 | 352.00 |
| chin control bracket | 352.00 | 352.00 |
| nead control bracket | 352.00 | 352.00 |
| pracket for separate display module | 352.00 | 352.00 |
| adjustable bracket for joystick control | 66.00 | 66.00 |
| chin bib control | 352.00 | 352.00 |
| nodification, repositioning of joystick bracket inward | 120.00 | N/A |
| controller | N/C | 1 425.00 |
| motors | N/C | 662.00 |
| high-torque transmission, for 400 lb. user | 315.00 | N/A |
| Wheels and forks: driving wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) | N/C | 202.00 |
| Front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.) | | 62.00 |
| Front wheel rims | N/C | N/A |
| ear wheel rims | N/C | N/A |
| irless inserts for rear wheels | 136.00 | N/A |
| tandard forks | N/C | 70.00 |
| Component(s) under Special Consideration | | |
| seat/back structure, for power mechanism, SP101* | 850.00 | 850.00 |
| control system for one power accessory only (Solo 40)* | N/C | 275.00 |
| control system for four power accessories (Quattro)* leat/back structure, SP101, for power mechanism with reclining | 575.00 | 575.00 |
| pack and cylinder, compensating mechanism* | 1 185.00 | 1 185.00 |
| power reclining back, compensating mechanism, SP101* | 1 100.00 | 1 950.00 |
| power rocker device, 0° to 55°* | 1 695.00 | 1 695.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| power elevating legrests, per pair, including legrests and footplates, on SP101, requires Solo controller* | 1 295.00 | 1 072.00 |
| power elevating legrests, per unit, including legrests and footplates on SP101, requires Quatro controller* | 1 295.00 | 1 072.00 |
| SUPPLIER: ORTHOFAB INC. | | PRICE |

POWERED WHEEL CHAIR OASIS 2 MODEL

\$5 122.00

Basic Components

Body support system

- · rigid seat, flat
- supple back, nylon
- rigid back, flat
- seat widths: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat depths: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.)
- seat height: from 39.4 cm $(15^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$
- back height: from 38.1 cm (15 in.) to 48.3 cm (19 in.)
- modification of seat height by +2.5 cm (1 in.) or by +5.1 cm (2 in.)
- push handles, integrated
- power rocker device, including installation and one control for one accessory*
- · safety belt, auto-type

Armrests

- U-type armrests, detachable, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.) or from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long
- T-type armrests, detachable, height-adjustable from 20.3 cm (8 in.) to 27.9 cm (11 in.) or from 27.9 cm (11 in.) to 35.6 cm (14 in.), short, long
- · armrest pads, straight, short, long
- rigid clothing guards

Footrests

- 60° footrests, parallel, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70° footrests, parallel, detachable, swingaway, length-adjustable, from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests
- · folding footplates, standard
- heel loops, adjustable

Frame

- rear suspension
- rear reflectors
- running lights, front, back
- tie-down points for adapted transport
- anti-tip rollers
- modification of frame length

Price upon

replacement

Drive systems

- connecting cables for power reclining devices*
- programmable joystick control
- battery charge display
- push-button switch
- · direction joystick
- · battery charger
- battery boxes, group 22, group 24
- conical-spherical extension
- swivel side bracket for joystick control
- controller
- motors
- · breath control included with interface

Wheels and forks:

- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- · rear wheel rims
- · front wheel rims
- standard forks for 20.3 cm (8 in.) and 22.9 cm (9 in.) wheels
- forks for 20.3 cm (8 in.) wheels

| | or replacement of wheel chair (price per pair, as applicable) | of component (unit price) |
|--|--|------------------------------|
| Basic and Optional Components: | | |
| Body support system | | |
| Seat and back: | | |
| headrest, small, medium, large | 100.00 | 100.00 |
| headrest, padded, contoured | 100.00 | 100.00 |
| headrest, hammock-type | 75.00 | 75.00 |
| headrest mounting, articulated, uniball | 115.00 | 115.00 |
| headrest mounting, articulated | 102.00 | 102.00 |
| seat/back structure, with angle-adjustable back | 838.00 | 838.00 |
| rigid back, flat | N/C | 59.00 |
| rigid back, contoured | 191.00 | 250.00 |
| supple back, tension-adjustable | 74.00 | 133.00 |
| supple back, nylon | N/C | 59.00 |
| back cushion, contoured, nylon | 118.00 | 118.00 |
| back cushion, contoured, leatherette | 118.00 | 118.00 |
| rigid seat, flat | N/C | 55.00 |
| rigid seat, elastic webbing | 48.00 | 103.00 |
| seat cushion, flat, 5.1 cm (2 in.) | 56.00 | 56.00 |
| seat cushion, flat, 7.6 cm (3 in.) | 56.00 | 56.00 |
| seat cushion, contoured, nylon | 210.00 | 210.00 |
| seat cushion, contoured, leatherette | 210.00 | 210.00 |
| modification of back height to 50.8 cm (20 in.), 53.3 cm (21 in.), | | |
| 55.9 cm (22 in.), 58.4 cm (23 in.), 61.0 cm (24 in.) or 63.5 cm (25 in.) | n.) 96.00 | N/A |
| modification of seat depth to 38.1 cm (15 in.) or 48.3 cm (19 in.) | 264.00 | N/A |

Price upon

initial purchase

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| nodification of seat depth to 50.8 cm (20 in.) or 53.3 cm (21 in.) | 500.00 | N/A |
| nodification of seat width from 48.3 cm (19 in.) to 58.4 cm (23 in.) | 290.00 | N/A |
| nodification of seat height by +2.5 cm (1 in.) or by +5.1 cm (2 in.) | N/C | N/A |
| afety belt, velcro-type | 27.00 | 63.00 |
| afety belt, auto-type | N/C | 36.00 |
| afety belt, airplane-type | 38.00 | 74.00 |
| bush handles, integrated | N/C | N/A |
| rmrests: | | |
| E-type armrests, detachable, height-adjustable from 20.3 cm (8 in.) to 27.9 cm (11 in.) or from 27.9 cm (11 in.) to 35.6 cm (14 in.), shor | t N/C | 94.00 |
| | ı N/C | 94.00 |
| E-type armrests, detachable, height-adjustable from 20.3 cm (8 in.) to 27.9 cm (11 in.) or from 27.9 cm (11 in.) to 35.6 cm (14 in.), long | N/C | 120.00 |
| 1-type armrests, detachable, height-adjustable from 20.3 cm (8 in.) | IV/C | 120.00 |
| o 30.5 cm (12 in.) or from 25.4 cm (10 in.) to 35.6 cm (14 in.), shor | t N/C | 94.00 |
| J-type armrests, detachable, height-adjustable from 20.3 cm (8 in.) | ı N/C | 94.00 |
| 27.9 cm (11 in.) or from 22.9 cm (9 in.) to 30.5 cm (12 in.), long | N/C | 120.00 |
| rmrest pads, straight, short | N/C | 12.00 |
| mrest pads, straight, long | N/C | 15.00 |
| rmrest pads, straight, long | 44.00 | 34.00 |
| rmrest pads, contoured, snort | 48.00 | 39.00 |
| nodification of armrest height to under 20.3 cm (8 in.) | 79.00 | N/A |
| gid clothing guards | N/C | N/A |
| Cootrests: 0° footrests, parallel, detachable, swingaway, length-adjustable | | |
| rom 35.6 cm (14 in.) to 48.3 cm (19 in.) 0° footrests, parallel, detachable, swingaway, length-adjustable | N/C | 78.00 |
| rom 35.6 cm (14 in.) to 48.3 cm (19 in.) 0° footrests, inward-pointing, detachable, swingaway, | N/C | 78.00 |
| ength-adjustable from 38.1 cm (15 in.) to 48.3 cm (19 in.) | 86.00 | 121.00 |
| 0° footrests, inward-pointing, detachable, swingaway, ength-adjustable from 38.1 cm (15 in.) to 48.3 cm (19 in.) nodification of footrest length to under 35.6 cm (14 in.) or | 86.00 | 121.00 |
| o over 48.3 cm (19 in.) levating legrests with compensating mechanism, length-adjustable | 79.00 | N/A |
| rom 35.6 cm (14 in.) to 48.3 cm (19 in.) | 234.00 | 195.00 |
| added calfrests | N/C | 20.00 |
| ontoured calfrests | 60.00 | 50.00 |
| puble calf strap | 55.00 | 55.00 |
| olding footplates, standard size | N/C | 16.00 |
| ootplate, angle-adjustable and depth-adjustable, standard size | 76.00 | 54.00 |
| potplates, angle-adjustable and depth-adjustable, oversized | 82.00 | 57.00 |
| ıll-width footplate, angle-adjustable and depth-adjustable | 168.00 | 200.00 |
| versized footplates | 50.00 | 41.00 |
| all-width footplate | 221.00 | 252.00 |
| olding footplates, aluminum | 44.00 | 38.00 |
| eel loops, adjustable | N/C | 11.00 |
| pe loops | 30.00 | 15.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| Frame: | | |
| modification of frame length | N/C | N/A |
| rear suspension | N/C | N/A |
| rear reflectors | N/C | N/A |
| running lights, front, back | N/C | N/A |
| tie-down points for adapted transport | N/C | N/A |
| back tension bar | 69.00 | 69.00 |
| cane holder | 40.00 | 40.00 |
| front impact guard with rollers | 36.00 | 18.00 |
| anti-tip rollers | N/C | 48.00 |
| • | | |
| Drive systems: programmable joystick control | N/C | 511.00 |
| compact joystick control | 58.00 | 569.00 |
| | N/C | N/A |
| battery charge display | N/C N/C | 359.00 |
| battery charger battery boxes, group 22, group 24 | N/C N/C | 208.00 |
| adapted controls interface | 1 400.00 | 1 911.00 |
| | 540.00 | 540.00 |
| proportional chin control | 421.00 | 421.00 |
| non-proportional chin control head control | 540.00 | 540.00 |
| breath control, included with the interface | N/C | N/A |
| laptray touch switch control | 301.00 | 301.00 |
| control with separate switches | 530.00 | 530.00 |
| chin bib control | 219.00 | 219.00 |
| breath control bracket | 340.00 | 340.00 |
| chin control bracket | 340.00 | 340.00 |
| head control bracket | 340.00 | 340.00 |
| bracket for separate display module | 37.00 | 37.00 |
| flexible bracket for interface display module | 90.00 | 90.00 |
| push-button switch | N/C | N/A |
| direction joystick | N/C | N/A |
| stick extension | 19.00 | 27.00 |
| ball extension | 27.00 | 35.00 |
| T-type extension | 27.00 | 35.00 |
| mushroom-shaped extension | 27.00 | 35.00 |
| conical-spherical extension | N/C | 8.00 |
| swivel side bracket for joystick control | N/C | 202.00 |
| swivel midline bracket for joystick control | 85.00 | 287.00 |
| modification of joystick control, potentiometer and switches | 78.00 | 589.00 |
| controller | N/C | 1 437.00 |
| motors | N/C | 1 082.00 |
| XXI 1 10 1 | | |
| Wheels and forks: | NIC | 102.00 |
| rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) | N/C | 102.00 |
| front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | N/C | 85.00 |
| front wheels, inner tube tires, 22.9 cm (9 in.) x 7 cm ($2^{3}/_{4}$ in.) airless inserts for front wheels | 88.00 133.00 | 129.00 |
| | | N/A |
| airless inserts for rear wheels | 151.00 | N/A |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| rear wheel rims | N/C | N/A |
| front wheel rims | N/C | N/A |
| standard forks for 20.3 cm (8 in.) and 22.9 cm (9 in.) wheels | N/C | 87.00 |
| forks for 20.3 cm (8 in.) wheels | N/C | 87.00 |
| Component(s) under Special Consideration | | |
| power reclining back* | 639.00 | 639.00 |
| power rocker device, including installation and one control for | | |
| one accessory* | N/C | 2 375.00 |
| power elevating legrests, individual controls, length-adjustable | | |
| from 35.6 cm (14 in.) to 48.3 cm (19 in.)* | 1 273.00 | 717.00 |
| power elevating legrests, dual control, length-adjustable | | |
| from 35.6 cm (14 in.) to 48.3 cm (19 in.)* | 1 273.00 | 717.00 |
| control system for one power accessory only* | 230.00 | 230.00 |
| control system for four power accessories* | 740.00 | 740.00 |
| reclining back with cylinder (manual mechanism)* | 269.00 | 269.00 |
| connecting cables for power reclining devices* | N/C | N/A |

SUPPLIER: PRIDE MOBILITY PRODUCTS

PRICE

POWERED WHEEL CHAIR QUANTUM 1121 HDRQ MODEL

\$4 850.00

Basic Components

Body support system

- · rigid seat, flat
- supple back, nylon
- seat width: from 25.4 cm (10 in.) to 55.8 cm (22 in.)
- seat depth: from 25.4 cm (10 in.) to 50.8 cm (20 in.)
- seat height: from 43.2 cm (17 in.) to 48.3 cm (19 in.)
- back height: from 35.6 cm (14 in.) to 63.5 cm (25 in.)
- · adjustable seat bracket
- · back, angle-adjustable
- · push handles
- push bar
- installation of power reclining back, 100% compensating, 300 lb.*
- installation of power rocker device*
- · centre of gravity adjustment from seat
- safety belt, auto-type, velcro-type
- control system for one power accessory only*
- · control system for four power accessories*

Armrests

- T-type armrests, height-adjustable from 27.9 cm (11 in.) to 43.2 cm (17 in.), short, long
- I-type armrests, height-adjustable from 22.9 cm (9 in.) to 50.8 cm (20 in.), short, long

- · armrest pads, straight, short, long
- · armrest pads, contoured, short, long

Footrests

- 70° or 80° footrests, parallel, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.), footplates, angle-adjustable and depth-adjustable
- padded calfrests
- footplates, angle-adjustable and depth-adjustable,
 10.2 cm (4 in.) x 15.2 cm (6 in.), 12.7 cm (5 in.) x 15.2 cm (6 in.),
 12.7 cm (5 in.) x 20.3 cm (8 in.), 15.2 cm (6 in.) x 20.3 cm (8 in.),
 standard size
- oversized footplates, angle-adjustable and depth-adjustable,
 15.2 cm (6 in.) x 27.9 cm (11 in.), 20.3 cm (8 in.) x 27.9 cm (11 in.)
- heel loops, adjustable
- heel loops, fixed
- modification of legrest length from 35.6 cm (14 in.) to 43.2 cm (17 in.) or from 43.2 cm (17 in.) to 50.8 cm (20 in.)

Frame

- rear suspension
- · rear reflectors
- · tie-down points for adapted transport
- anti-tip rollers

Drive systems

- · programmable joystick control
- battery charge display
- · push-button switch
- toggle switch
- battery charger, external, Lester 8A
- built-in charger, Guest 5A
- battery boxes, group 24
- conical-spherical extension
- side bracket for joystick control
- swivel side bracket for joystick control
- side bracket for joystick control, lateral, multi-directional
- · head control bracket
- P&G controller, 100A 5 profiles
- HAMMER motors, 4-brush, 6.25 mph, 400 lb. capacity

- driving wheels, inner tube tires 300-8, 35.6 cm (14 in.)
- pivoting wheels, solid tires 200-50, 20.3 cm (8 in.)
- front wheels, solid tires 200-50, 15.2 cm (6 in.) x 5.1 cm (2 in.)
- front wheels, inner tube tires 200-50, 20.3 cm (8 in.)
- · rear wheel rims
- · front wheel rims
- · suspension forks

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| seat/back structure, with angle-adjustable back | 550.00 | 600.00 |
| headrest, padded, contoured, small | 60.00 | 170.00 |
| headrest, padded, contoured, large | 60.00 | 170.00 |
| headrest and mounting for power reclining back | 160.00 | 234.00 |
| headrest mounting, articulated, uniball | 100.00 | 290.00 |
| supple back, nylon | N/C | 80.00 |
| padded back, flat, fabric | 280.00 | 340.00 |
| padded back, contoured, fabric, leatherette, PRAMQ | 280.00 | 340.00 |
| padded back, contoured, Basic Back Future Mobility, 300 lb. | 390.00 | 470.00 |
| supple back on rigid base, on power reclining back | 270.00 | 170.00 |
| (rigid base not included) | 250.00 | 340.00 |
| back, angle-adjustable | N/C | 160.00 |
| padded seat, contoured, fabric | 200.00 | 200.00 |
| rigid seat, flat | N/C | 40.00 |
| adjustable seat bracket | N/C | N/A |
| push handles | N/C N/C | 40.00 |
| push bar | N/C N/C | 85.00 |
| safety belt, auto-type | N/C N/C | 25.00 |
| safety belt, auto-type safety belt, velcro-type | N/C N/C | 25.00 |
| | 35.00 | 75.00 |
| safety belt, airplane-type | | |
| centre of gravity adjustment from seat | N/C | N/A |
| Armrests: | | |
| I-type armrests, height-adjustable from 22.9 cm (9 in.) to 50.8 cm (20 in.), short, long | N/C | 80.00 |
| I-type armrests, on power reclining back, from 25.4 cm (10 in.) | N/C | 80.00 |
| | 200.00 | 306.00 |
| to 33.0 cm (13 in.), short, long | 200.00 | 300.00 |
| T-type armrests, height-adjustable from 27.9 cm (11 in.) to 43.2 cm (17 in.), short, long | N/C | 190.00 |
| | N/C | 190.00 |
| T-type armrests, height-adjustable from 19.7 cm (7 ³ / ₄ in.) | 200.00 | 100.00 |
| to 27.3 cm (10 ³ / ₄ in.), short, long | 200.00 | 190.00 |
| T-type armrests, heavy-duty, adjustable, fixed, wide armrest pads, | 200.00 | 200.00 |
| height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), long | 200.00 | 290.00 |
| U-type armrests, height-adjustable from 22.9 cm (9 in.) | 200.00 | 200.00 |
| to 33.0 cm (13 in.), short, long | 200.00 | 290.00 |
| armrest pads, straight, short, long | N/C | 10.00 |
| armrest pads, contoured, short, long | N/C | 10.00 |
| armrest pads, wide gutter-style, one-piece, left, right | 55.00 | 65.00 |
| flexible clothing guards for U-type armrests | 60.00 | 60.00 |
| rigid clothing guards for U-type armrests | 15.00 | 36.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| Footrests: | | |
| 70° or 80° footrests, parallel, detachable, swingaway, | | |
| ength-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.), cootplates, angle-adjustable and depth-adjustable | N/C | 70.00 |
| 70° or 80° footrests, heavy-duty, parallel, detachable, swingaway, | N/C | 70.00 |
| ength-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.), | | |
| Sootplates, angle-adjustable and depth-adjustable | 200.00 | 170.00 |
| elevating legrests | 200.00 | 170.00 |
| elevating legrests, heavy-duty | 290.00 | 200.00 |
| modification of legrest length from 35.6 cm (14 in.) | | |
| o 43.2 cm (17 in.), from 43.2 cm (17 in.) to 50.8 cm (20 in.) | N/C | N/A |
| padded calfrests | N/C | 15.00 |
| contoured calfrests | 40.00 | 60.00 |
| single calf strap | 35.00 | 35.00 |
| louble calf strap | 60.00 | 60.00 |
| cootplates, angle-adjustable and depth-adjustable, | | |
| 10.2 cm (4 in.) x 15.2 cm (6 in.), 12.7 cm (5 in.) x 15.2 cm (6 in.), | | |
| 2.7 cm (5 in.) x 20.3 cm (8 in.), 15.2 cm (6 in.) x 20.3 cm (8 in.), | | 25.00 |
| standard size | N/C | 35.00 |
| oversized footplates, angle-adjustable and depth-adjustable, 15.2 cm (6 in.) x 27.9 cm (11 in.), 20.3 cm (8 in.) x 27.9 cm (11 ir.) | n.) N/C | 70.00 |
| full-width footplate | 100.00 | 150.00 |
| custom-made footplates (on approval of R&D) | 100.00 | 150.00 |
| neel loops, adjustable | N/C | 10.00 |
| neel loops, fixed | N/C | 10.00 |
| oe loops | 20.00 | 15.00 |
| - | | |
| Frame: | 20.00 | 15.00 |
| ront impact guard with rollers | 20.00 | 15.00 |
| ear suspension unti-tip rollers | N/C N/C | N/A 12.00 |
| ear reflectors | N/C N/C | 20.00 |
| ie-down points for adapted transport | N/C | 25.00 |
| cane holder | 40.00 | 40.00 |
| une norder | 10.00 | 10.00 |
| Orive systems: | | |
| programmable joystick control | N/C | 725.00 |
| compact joystick control, MicroDrive Mini P&G | 475.00 | 1 152.00 |
| controller heavy-duty, Stealth Mushroom | | |
| requires OmniPlus interface) | 1 500.00 | 2 200.00 |
| oystick control with built-in controller | 50.00 | 775.00 |
| pattery charge display | N/C | N/A |
| oggle switch | N/C | N/A |
| bush-button switch | N/C | N/A |
| nuxiliary switch, Buddy Button (requires OmniPlus interface) | 44.00 N/C | 44.00 210.00 |
| pattery charger, external, Lester 8A puilt-in charger, Guest 5A | N/C N/C | 151.00 |
| | IN/L | 131.00 |
| pattery boxes, group 24 | N/C | 66.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| on-proportional chin control, Mini Joystick | | |
| requires OmniPlus interface) | 420.00 | 420.00 |
| ead control, ASL RIM (requires OmniPlus interface) CTLDC1380 aptray touch switch control, TASH (requires OmniPlus interface) | 1 077.00 | 1 077.00 |
| WTMCRO1003 | 292.00 | 292.00 |
| ontrol with separate switches (requires interface) | 105.00 | 105.00 |
| oot control, RIM (requires OmniPlus interface) | 1 250.00 | 1 250.00 |
| ccessory interface/Synergy seat | 24.00 | 24.00 |
| on-proportional joystick control interface, OmniPlus | 860.00 | 860.00 |
| dapted controls interface, OmniPlus (breath control included) | 860.00 | 860.00 |
| tick extension | 40.00 | 50.00 |
| all extension, hard | 30.00 | 40.00 |
| E-type extension | 60.00 | 70.00 |
| nushroom-shaped extension | 40.00 | 50.00 |
| onical-spherical extension | N/C | 50.00 |
| ide bracket for joystick control | N/C | 12.00 |
| wivel side bracket for joystick control | N/C | 160.00 |
| wivel midline bracket for joystick control, GATLIN FRASMB4088 | | 432.00 |
| racket for joystick control, lateral, multi-directional | N/C | 160.00 |
| reath control bracket (requires OmniPlus interface) INDPART2151 | | 264.00 |
| hin control bracket, FRMASMB8041 | 328.00 | 488.00 |
| ead control bracket | N/C | 125.00 |
| racket for separate display module, OmniPlus | 48.00 | 63.00 |
| hin bib control, SBM750 GATLIN | 395.00 | 556.00 |
| &G controller, 100A 5 profiles | N/C | 750.00 |
| IAMMER motors, 4-brush, 6.25 mph, 400 lb. capacity | N/C | 850.00 |
| Vheels and forks: | N/C | 90.00 |
| riving wheels, inner tube tires 300-8, 35.6 cm (14 in.) | N/C | 80.00 |
| ivoting wheels, solid tires 200-50, 20.3 cm (8 in.) | N/C N/C | 34.00 |
| ront wheels, solid tires 200-50, 15.2 cm (6 in.) x 5.1 cm (2 in.) ront wheels, inner tube tires 200-50, 20.3 cm (8 in.) | N/C N/C | 20.00 15.00 |
| ront wheel rims | N/C N/C | 7.00 |
| ear wheel rims | N/C N/C | 24.00 |
| irless inserts for front wheels | 90.00 | 48.00 |
| uspension forks | 90.00 N/C | 45.00 |
| Component(s) under Special Consideration | | |
| eat/back structure, with reclining back and cylinder, | 950.00 | 950.00 |
| 5.9 cm (22 in.) backposts, including a Synergy seat* eat/back structure, with manual rocker device, max. 0.6 cm (16 in.) x 40.6 cm (16 in.), 160 lb., structure from | 930.00 | 930.00 |
| 5.4 cm (10 in.) to 35.6 cm (14 in.) or from 35.6 cm (14 in.) to | 1 145 00 | 1 200 00 |
| 0.6 cm (16 in.), including a Synergy seat* | 1 145.00 | 1 300.00 |
| ontrol system for one power accessory only* | N/C | 133.00 |
| ontrol system for four power accessories* | N/C | 133.00 |
| | 100.00 | |
| onnecting cables for power reclining devices* eclining back with cylinder* | 100.00 400.00 | 100.00 400.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| nstallation of power reclining back, 100% compensating, 300 lb.* | N/C | 50.00 |
| power reclining back, joystick-controlled* | 250.00 | 450.00 |
| oower rocker device* | 1 895.00 | 2 095.00 |
| nstallation of power rocker device* | N/C | 150.00 |
| power rocker device, joystick-controlled* | 375.00 | 450.00 |
| troller handles for manual tipping* | 75.00 | 93.00 |
| ower elevating legrests, high-pivot, per pair* | 600.00 | 400.00 |
| ower elevating legrests, high-pivot, each* | 350.00 | 400.00 |
| power elevating legrests, with compensating mechanism, per pair* | 1 500.00 | 850.00 |

SUPPLIER: PRIDE MOBILITY PRODUCTS

PRICE

POWERED WHEEL CHAIR QUANTUM 600 MODEL

\$4 500.00

Basic Components

Body support system

- · rigid seat, flat
- supple back, nylon
- seat width: from 25.4 cm (10 in.) to 50.8 cm (20 in.)
- seat depth: from 25.4 cm (10 in.) to 50.8 cm (20 in.)
- seat height: from 43.2 cm (17 in.) to 53.3 cm (21 in.)
- back height: from 35.6 cm (14 in.) to 63.5 cm (25 in.)
- · adjustable seat bracket
- back, angle-adjustable
- · push handles
- push bar
- installation of power reclining back, 100% compensating*
- · installation of power rocker device*
- · centre of gravity adjustment from seat
- safety belt, auto-type, velcro-type
- control system for one power accessory only*
- control system for four power accessories*

Armrests

- T-type armrests, height-adjustable from 27.9 cm (11 in.) to 43.2 cm (17 in.), short, long
- I-type armrests, height-adjustable from 22.9 cm (9 in.) to 50.8 cm (20 in.), short, long
- armrest pads, straight, short, long
- · armrest pads, contoured, short, long

Footrests

- 70° footrests, parallel, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.), footplates angle-adjustable and depth-adjustable
- 70° footrests, parallel, detachable, swingaway, length-adjustable from 21.6 cm (8½ in.) to 28.6 cm (11¼ in.), footplates, angle-adjustable and depth-adjustable
- foot platform, 25.4 cm (10 in.) x 25.4 cm (10 in.)
- modification of legrest length from 35.6 cm (14 in.) to 43.2 cm (17 in.) or from 43.2 cm (17 in.) to 50.8 cm (20 in.)

- padded calfrests
- footplates, angle-adjustable and depth-adjustable, 10.2 cm (4 in.) x 15.2 cm (6 in.), 12.7 cm (5 in.) x 15.2 cm (6 in.), 12.7 cm (5 in.) x 20.3 cm (8 in.), 15.2 cm (6 in.) x 20.3 cm (8 in.), standard size
- oversized footplates, angle-adjustable and depth-adjustable,
 15.2 cm (6 in.) x 27.9 cm (11 in.), 20.3 cm (8 in.) x 27.9 cm (11 in.)
- heel loops, adjustable
- heel loops, fixed

Frame

- · rear suspension
- rear reflectors
- tie-down points for adapted transport
- anti-tip rollers

Drive systems

- programmable joystick control
- battery charge display
- push-button switch
- · toggle switch
- battery charger, external, Lester 8A
- built-in charger, Quest 4A
- battery boxes, group 22
- · conical-spherical extension
- side bracket for joystick control
- · swivel side bracket for joystick control
- · bracket for joystick control, lateral, multi-directional
- · head control bracket
- P&G controller, 80A 5 profiles
- GLIDE motors, 5 mph, 300 lb. capacity

Wheels and forks

- rear wheels, inner tube tires 300-8, 35.6 cm (14 in.)
- front wheels, solid tires, spherical, 15.2 cm (6 in.), 12.7 cm (5 in.)
- rear wheel rims
- front wheel rims
- · standard forks

| | initial purchase or replacement of wheel chair (price per pair, as applicable) | replacement of component (unit price) |
|---|--|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| seat/back structure, with angle-adjustable back | 550.00 | 600.00 |
| headrest, padded, contoured, small | 60.00 | 170.00 |
| headrest, padded, contoured, large | 60.00 | 170.00 |
| headrest and mounting for power reclining back | 160.00 | 234.00 |
| headrest mounting, articulated, uniball | 100.00 | 290.00 |
| supple back, nylon | N/C | 80.00 |

Price upon

Price upon

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| padded back, flat, fabric | 280.00 | 340.00 |
| badded back, contoured, fabric, leatherette, PRAMQ | 280.00 | 340.00 |
| padded back, contoured, Basic Back Future Mobility, 300 lb. supple back on rigid base, on power reclining back | 390.00 | 470.00 |
| rigid base not included) | 250.00 | 340.00 |
| back, angle-adjustable | N/C | 160.00 |
| padded seat, contoured, fabric | 200.00 | 200.00 |
| igid seat, flat | N/C | 40.00 |
| djustable seat bracket | N/C | N/A |
| oush handles | N/C | 40.00 |
| oush bar | N/C | 85.00 |
| afety belt, auto-type | N/C | 25.00 |
| afety belt, velcro-type | N/C | 25.00 |
| afety belt, airplane-type | 35.00 | 75.00 |
| centre of gravity adjustment from seat | N/C | N/A |
| Armrests: | | |
| -type armrests, height-adjustable from 22.9 cm (9 in.) | | |
| o 50.8 cm (20 in.), short, long | N/C | 80.00 |
| -type armrests, on power reclining back, from 25.4 cm (10 in.) | | |
| 33.0 cm (13 in.), short, long | 200.00 | 306.00 |
| type armrests, height-adjustable from 27.9 cm (11 in.) | | |
| o 43.2 cm (17 in.), short, long | N/C | 190.00 |
| E-type armrests, height-adjustable from 19.7 cm (7 ³ / ₄ in.) | | |
| o 27.3 cm (10 ³ / ₄ in.), short, long | 200.00 | 190.00 |
| E-type armrests, heavy-duty, adjustable, fixed, wide armrest pad, | | |
| eight-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.), long J-type armrests, height-adjustable from 22.9 cm (9 in.) | 200.00 | 290.00 |
| o 33.0 cm (13 in.), short, long | 200.00 | 290.00 |
| rmrest pads, straight, short, long | N/C | 10.00 |
| rmrest pads, contoured, short, long | N/C | 10.00 |
| rmrest pads, wide gutter-type, one-piece, left, right | 55.00 | 65.00 |
| lexible clothing guards for U-type armrests | 60.00 | 60.00 |
| igid clothing guards for U-type armrests | 15.00 | 36.00 |
| Cootrests: | | |
| 0° footrests, parallel, detachable, swingaway, length-adjustable | | |
| from 27.9 cm (11 in.) to 50.8 cm (20 in.), footplates, | NIC | 70.00 |
| ngle-adjustable and depth-adjustable | N/C | 70.00 |
| 0° footrests, heavy-duty, parallel, detachable, swingaway, | | |
| ength-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.), | 200.00 | 170.00 |
| potplates, angle-adjustable and depth-adjustable | 200.00 | 170.00 |
| 0° footrests, parallel, detachable, swingaway, length-adjustable | | |
| rom 21.6 cm ($8^{1}/_{2}$ in.) to 28.6 cm ($11^{1}/_{4}$ in.), footplates, | NIC | 70.00 |
| ngle-adjustable and depth-adjustable | N/C | 70.00 |
| oot platform, 25.4 cm (10 in.) x 25.4 cm (10 in.) | N/C | 133.00 |
| levating legrests | 200.00 | 170.00 |
| levating legrests, heavy-duty | 290.00 | 200.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| modification of legrest length from 35.6 cm (14 in.) | | |
| to 43.2 cm (17 in.) or from 43.2 cm (17 in.) to 50.8 cm (20 in.) | N/C | N/A |
| padded calfrests | N/C | 15.00 |
| contoured calfrests | 40.00 | 60.00 |
| single calf strap | 35.00 | 35.00 |
| double calf strap | 60.00 | 60.00 |
| footplates, angle-adjustable and depth-adjustable, 10.2 cm (4 in.) x 15.2 cm (6 in.), 12.7 cm (5 in.) x 15.2 cm (6 in.), 12.7 cm (5 in.) x 20.3 cm (8 in.), 15.2 cm (6 in.) x 20.3 cm (8 in.), | | |
| standard size oversized footplates, angle-adjustable and depth-adjustable, | N/C | 35.00 |
| 15.2 cm (6 in.) x 27.9 cm (11 in.), 20.3 cm (8 in.) x 27.9 cm (11 in.) | N/C | 70.00 |
| full-width footplate | 100.00 | 150.00 |
| custom-made footplates (on approval from R&D) | 100.00 | 150.00 |
| neel loops, adjustable | N/C | 10.00 |
| neel loops, fixed | N/C | 10.00 |
| oe loops | 20.00 | 15.00 |
| Frame: rear suspension | N/C | N/A |
| ear reflectors | N/C N/C | 20.00 |
| ie-down points for adapted transport | N/C N/C | 25.00 |
| ront impact guard with rollers | 20.00 | 15.00 |
| inti-tip rollers | N/C | 12.00 |
| ane holder | 40.00 | 40.00 |
| Drive systems: | | |
| programmable joystick control | N/C | 725.00 |
| compact joystick control, MicroDrive Mini P&G | 475.00 | 1 152.00 |
| ontroller heavy-duty, Stealth Mushroom | 1 500 00 | 2 200 00 |
| requires OmniPlus interface) | 1 500.00 | 2 200.00 |
| bystick control with built-in controller | 50.00 | 775.00 |
| attery charge display | N/C N/C | N/A N/A |
| oggle switch oush-button switch | N/C N/C | N/A N/A |
| uxiliary switch, Buddy Button (requires OmniPlus interface) | 44.00 | 1N/A 44.00 |
| nattery charger, external, Lester 8A | 44.00 N/C | 210.00 |
| ouilt-in charger, Quest 4A | N/C N/C | 95.00 |
| pattery boxes, group 22 | N/C N/C | 66.00 |
| proportional chin control, P&G CTLDC1117 | 452.00 | 597.00 |
| on-proportional chin control, Mini Joystick | | |
| requires OmniPlus interface) | 420.00 | 420.00 |
| ead control, ASL RIM (requires OmniPlus interface), CTLDC1380 aptray touch switch control, TASH (requires OmniPlus interface), | | 1 077.00 |
| SWTMCRO1003 | 292.00 | 292.00 |
| ontrol with separate switches (requires interface) | 105.00 | 105.00 |
| oot control, RIM (requires OmniPlus interface) | 1 250.00 | 1 250.00 |
| ccessory interface/Synergy seat | 24.00 | 24.00 |
| non-proportional joystick control interface, OmniPlus | 860.00 | 860.00 |
| dapted controls interface, OmniPlus (breath control included) | 860.00 | 860.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| stick extension | 40.00 | 50.00 |
| ball extension, hard | 30.00 | 40.00 |
| T-type extension | 60.00 | 70.00 |
| mushroom-shaped extension | 40.00 | 50.00 |
| conical-spherical extension | N/C | 50.00 |
| pracket for joystick control, lateral, multi-directional | N/C | 12.00 |
| swivel side bracket for joystick control | N/C | 160.00 |
| wivel midline bracket for joystick control, GATLIN FRASMB4088 | | 432.00 |
| oracket for joystick control, lateral, multi-directional oreath control bracket, (requires OmniPlus interface), | N/C | 160.00 |
| NDPART2151 | 264.00 | 264.00 |
| chin control bracket, FRMASMB8041 | 328.00 | 488.00 |
| nead control bracket | N/C | 125.00 |
| bracket for separate display module, OmniPlus | 48.00 | 63.00 |
| hin bib control, SBM750 GATLIN | 395.00 | 556.00 |
| P&G controller, 80A 5 profiles | N/C | 750.00 |
| GLIDE motors, 5 mph, 300 lb. capacity | N/C | 468.00 |
| Wheels and forks: | NG | 17.00 |
| front wheels, solid tires, spherical, 15.2 cm (6 in.), 12.7 cm (5 in.) | N/C | 17.00 |
| ear wheels, inner tube tires 300-8, 35.6 cm (14 in.) | N/C | 71.00 |
| ront wheel rims | N/C | N/A |
| ear wheel rims | N/C | 30.00 |
| irless inserts for rear wheels tandard forks | 90.00 N/C | 48.00 12.00 |
| Component(s) under Special Consideration seat/back structure, with reclining back and cylinder, 55.9 cm (22 in.) backposts, including a Synergy seat* | 950.00 | 950.00 |
| teat/back structure, with manual rocker device, max. 40.6 cm (16 in.) x 40.6 cm (16 in.), 160 lb., structure from 25.4 cm (10 in.) to 35.6 cm (14 in.), from 35.6 cm (14 in.) | 1 145 00 | 1 200 00 |
| o 40.6 cm (16 in.), including a Synergy seat* | 1 145.00 | 1 300.00 |
| troller handles for manual tipping* | 75.00 | 93.00 133.00 |
| ontrol system for one power accessory only* | N/C N/C | |
| ontrol system for four power accessories* | | 133.00 |
| onnecting cables for power reclining devices* | 100.00 | 100.00 |
| eclining back with cylinder* | 400.00 | 400.00 |
| ower reclining back, 100% compensating* | 2 250.00 | 2 250.00 |
| nstallation of power reclining back, 100% compensating* | N/C | 50.00 |
| ower reclining back, joystick-controlled* | 250.00 | 450.00 |
| ower rocker device* | 1 895.00 | 2 095.00 150.00 |
| nstallation of power rocker device* | N/C | |
| ower rocker device, joystick-controlled* | 250.00 | 450.00 |
| ower elevating legrests, high-pivot, per pair* | 600.00 | 400.00 |
| ower elevating legrests, high-pivot, per unit* | 350.00 | 400.00 |
| ower elevating legrests, with compensating mechanism, per pair* | 1 500.00 | 850.00 |

SUPPLIER: PRIDE MOBILITY PRODUCTS

PRICE

POWERED WHEEL CHAIR QUANTUM VIBE

\$4 450.00

Basic Components

Body support system

- rigid seat, flat
- · supple back, nylon
- seat width: from 25.4 cm (10 in.) to 50.8 cm (20 in.)
- seat depth: from 25.4 cm (10 in.) to 50.8 cm (20 in.)
- seat height: from 41.9 cm $(16^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$
- back height: from 35.6 cm (14 in.) to 61.0 cm (24 in.)
- adjustable seat bracket
- · back, angle-adjustable
- installation of power reclining back, 100% compensating*
- · installation of power rocker device*
- centre of gravity adjustment from seat
- safety belt, auto-type, velcro-type
- control system for one power accessory only*
- control system for four power accessories*

Armrests

- T-type armrests, height-adjustable from 27.9 cm (11 in.) to 43.2 cm (17 in.), short, long
- I-type armrests, height-adjustable from 22.9 cm (9 in.) to 50.8 cm (20 in.), short, long
- · armrest pads, straight, short, long
- · armrest pads, contoured, short, long

Footrests

- 70° or 80° footrests, parallel, detachable, swingaway, length-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.), footplates, angle-adjustable and depth-adjustable
- modification of legrest length from 35.6 cm (14 in.) to 43.2 cm (17 in.) or from 43.2 cm (17 in.) to 50.8 cm (20 in.)
- · padded calfrests
- footplates, angle-adjustable and depth-adjustable,
 10.2 cm (4 in.) x 15.2 cm (6 in.), 12.7 cm (5 in.) x 15.2 cm (6 in.),
 12.7 cm (5 in.) x 20.3 cm (8 in.), 15.2 cm (6 in.) x 20.3 cm (8 in.), standard size
- oversized footplates, angle-adjustable and depth-adjustable,
 15.2 cm (6 in.) x 27.9 cm (11 in.), 20.3 cm (8 in.) x 27.9 cm (11 in.)
- heel loops, adjustable
- · heel loops, fixed

Frame

- · rear suspension
- · rear reflectors
- tie-down points for adapted transport
- anti-tip rollers
- push handles
- push bar

Price upon

Drive systems

- programmable joystick control
- · battery charge display
- · toggle switch
- push-button switch
- battery charger, external, Lester 8A
- conical-spherical extension
- battery boxes, group 24
- side bracket for joystick control
- swivel side bracket for joystick control
- bracket for joystick control, lateral, multi-directional
- · head control bracket
- P&G controller, 80A 5 profiles
- GLIDE motors, 6 mph, 300 lb. capacity

Wheels and forks

- rear wheels, inner tube tires 300-8, 35.6 cm (14 in.)
- front wheels, inner tube tires 2.80/2.50-4, 22.9 cm (9 in.)
- rear wheel rims
- · front wheel rims
- · standard forks

| | initial purchase or replacement of wheel chair (price per pair, as applicable) | replacement of component (unit price) |
|---|--|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: seat/back structure, with angle-adjustable back headrest, padded, contoured, small headrest, padded, contoured, large | 550.00 60.00 60.00 | 600.00 170.00 170.00 |
| headrest mounting, articulated, uniball headrest and mounting for power reclining back supple back, nylon | 100.00 160.00 N/C | 290.00 234.00 80.00 |
| supple back on rigid base, on power reclining back back, angle-adjustable padded back, contoured, PRAMQ, fabric, leatherette padded back, flat, fabric | 250.00 N/C 280.00 280.00 | 340.00 160.00 340.00 340.00 |
| padded back, flat, fabric padded back, contoured, Basic Back Future Mobility, 300 lb. padded seat, contoured, fabric rigid seat, flat | 390.00 200.00 N/C | 470.00 200.00 40.00 |
| adjustable seat bracket safety belt, auto-type safety belt, velcro-type | N/C N/C N/C | N/A 25.00 25.00 |
| safety belt, airplane-type centre of gravity adjustment from seat | 35.00 N/C | 75.00 N/A |
| Armrests: I-type armrests, on power reclining back, from 25.4 cm (10 in.) to 33.0 cm (13 in.), short, long | 200.00 | 306.00 |

Price upon

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| -type armrests, height-adjustable from 22.9 cm (9 in.) o 50.8 cm (20 in.), short, long | N/C | 80.00 |
| Γ-type armrests, height-adjustable from 27.9 cm (11 in.) o 43.2 cm (17 in.), short, long | N/C | 190.00 |
| Γ-type armrests, heavy-duty, adjustable, fixed, wide armrest pads, from 20.3 cm (8 in.) to 30.5 cm (12 in.), long Γ-type armrests, height-adjustable from 19.7 cm (7 ³ / ₄ in.) | 200.00 | 290.00 |
| o 27.3 cm (10 ³ / ₄ in.), short, long J-type armrests, height-adjustable from 22.9 cm (9 in.) | 200.00 | 190.00 |
| o 33.0 cm (13 in.), short, long | 200.00 | 290.00 |
| urmrest pads, straight, short, long | N/C | 10.00 |
| urmrest pads, straight, short, long | N/C N/C | 10.00 |
| lexible clothing guards for U-type armrests | 60.00 | 60.00 |
| | | |
| igid clothing guards for U-type armrests armrest pads, wide gutter-type, one-piece, left, right | 15.00 55.00 | 36.00 65.00 |
| Footrests: | 33.00 | 03.00 |
| 70° or 80° footrests, parallel, detachable, swingaway, | | |
| ength-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.), | NIC | 70.00 |
| ootplates, angle-adjustable and depth-adjustable 70° or 80° footrests, heavy-duty, parallel, detachable, swingaway, ength-adjustable from 27.9 cm (11 in.) to 50.8 cm (20 in.), | N/C | 70.00 |
| ootplates, angle-adjustable and depth-adjustable | 200.00 | 170.00 |
| levating legrests | 200.00 | 170.00 |
| levating legrests, heavy-duty | 290.00 | 200.00 |
| nodification of legrest length from 35.6 cm (14 in.) | 290.00 | 200.00 |
| o 43.2 cm (17 in.) or from 43.2 cm (17 in.) to 50.8 cm (20 in.) | N/C | N/A |
| padded calfrests | N/C | 15.00 |
| contoured calfrests | 40.00 | |
| | | 60.00 |
| ingle calf strap | 35.00 | 35.00 |
| louble calf strap ootplates, angle-adjustable and depth-adjustable, 0.2 cm (4 in.) x 15.2 cm (6 in.), 12.7 cm (5 in.) x 15.2 cm (6 in.), 2.7 cm (5 in.) x 20.3 cm (8 in.), 15.2 cm (6 in.) x 20.3 cm (8 in.), | 60.00 | 60.00 |
| standard size oversized footplates, angle-adjustable and depth-adjustable, | N/C | 35.00 |
| 5.2 cm (6 in.) x 27.9 cm (11 in.), 20.3 cm (8 in.) x 27.9 cm (11 in.) | | 70.00 |
| ull-width footplate | 100.00 | 150.00 |
| ustom-made footplates (on approval of R&D) | 100.00 | 150.00 |
| eel loops, adjustable | N/C | 10.00 |
| eel loops, fixed | N/C | 10.00 |
| Frame: nti-tip rollers | N/C | 12.00 |
| oush handles | N/C N/C | 40.00 |
| | | |
| troller handles for manual tipping | 75.00 | 93.00 |
| oush bar | N/C | 85.00 |
| ear reflectors | N/C | 20.00 |
| ie-down points for adapted transport | N/C | 25.00 |
| ear suspension | N/C | N/A |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| front impact guard with rollers | 20.00 | 15.00 |
| toe loops | 20.00 | 15.00 |
| cane holder | 40.00 | 40.00 |
| Drive systems: | | |
| programmable joystick control | N/C | 725.00 |
| compact joystick control, MicroDrive Mini P&G | 475.00 | 1 152.00 |
| joystick control, heavy-duty, Stealth Mushroom | 1 500.00 | 2 200.00 |
| joystick control with built-in controller | 50.00 | 775.00 |
| battery charge display | N/C | N/A |
| toggle switch | N/C | N/A |
| push-button switch | N/C | N/A |
| auxiliary switch, Buddy Button, with OmniPlus interface | 44.00 | 44.00 |
| battery charger, external, Lester 8A | N/C | 210.00 |
| battery boxes, group 24 | N/C | 66.00 |
| proportional chin control, P& G CTLDC1117 | 452.00 | 597.00 |
| non-proportional chin control, Mini Joystick | 420.00 | 420.00 |
| head control, ASL RIM CTLDC1380 | 1 077.00 | 1 077.00 |
| laptray touch switch control, TASH SWTMCRO1003 | 292.00 | 292.00 |
| foot control, RIM | 1 250.00 | 1 250.00 |
| control with separate switches (requires interface) | 105.00 | 105.00 |
| non-proportional joystick control interface, OmniPlus | 860.00 | 860.00 |
| adapted controls interface, OmniPlus (includes breath control) | 860.00 | 860.00 |
| accessory interface/Synergy seat | 24.00 | 24.00 |
| stick extension | 40.00 | 50.00 |
| ball extension, hard | 30.00 | 40.00 |
| T-type extension | 60.00 | 70.00 |
| mushroom-shaped extension | 40.00 | 50.00 |
| conical-spherical extension | N/C | 50.00 |
| side bracket for joystick control | N/C | 12.00 |
| swivel side bracket for joystick control | N/C | 160.00 |
| swivel midline bracket for joystick control, GATLIN FRASMB4088 | | 432.00 |
| bracket for joystick control, lateral, multi-directional | N/C | 160.00 264.00 |
| breath control bracket, INDPART2151 | 264.00 | |
| chin control bracket, FRMASMB8041 | 328.00 | 488.00 |
| head control bracket | N/C 48.00 | 125.00 63.00 |
| bracket for separate display module, OmniPlus | | |
| chin bib control, SBM750 GATLIN (requires OmniPlus interface) | 395.00 N/C | 556.00 750.00 |
| P&G controller, 80A 5 profiles GLIDE motors, 6 mph, 300 lb. capacity | N/C N/C | 417.00 |
| | | |
| Wheels and forks: | N/C | 20.00 |
| front wheels, inner tube tires 2.80/2.50-4, 22.9 cm (9 in.) | N/C | 30.00 |
| front wheels, solid tires 200-50, 20.3 cm (8 in.) | 68.00 | 34.00 |
| front wheels, solid tires, 15.2 cm (6 in.) x 5.1 cm (2 in.) | 38.00 N/C | 20.00 |
| rear wheels, inner tube tires 300-8, 35.6 cm (14 in.) | N/C | 80.00 |
| front wheel rims | N/C | 33.00 |
| rear wheel rims | N/C | 30.00 |
| airless inserts for rear wheels | 90.00 | 48.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| nirless inserts for front wheels | 50.00 N/C | 28.00 12.00 |
| Component(c) under Energial Consideration | | |
| Component(s) under Special Consideration seat/back structure, with reclining back and cylinder, 55.9 cm (22 in.) backposts, including a Synergy seat* seat/back structure, with manual rocker device, maximum 10.6 cm (16 in.) x 40.6 cm (16 in.), 160 lb., structure from | 950.00 | 950.00 |
| 5.4 cm (10 in.) to 35.6 cm (14 in.) or from 35.6 cm (14 in.) or 40.6 cm (16 in.), including a Synergy seat* | 1 145.00 | 1 300.00 |
| ontrol system for one power accessory only* | N/C | 133.00 |
| ontrol system for four power accessories* | N/C | 133.00 |
| onnecting cables for power reclining devices* | 100.00 | 100.00 |
| clining back with cylinder* | 400.00 | 400.00 |
| ower reclining back, 100% compensating, max 160 lb.* | 2 250.00 | 2 250.00 |
| stallation of power reclining back, 100% compensating* | N/C | 50.00 |
| ower reclining back, joystick-controlled* | 250.00 | 450.00 |
| ower rocker device* | 1 895.00 | 2 095.00 |
| stallation of power rocker device* | N/C | 150.00 |
| ower rocker device, joystick-controlled* | 375.00 | 450.00 |
| ower elevating legrests, high-pivot, per pair* | 600.00 | 400.00 |
| ower elevating legrests, high-pivot, per unit* | 350.00 | 400.00 |
| ower elevating legrests, compensating mechanism, per pair* | 1 500.00 | 850.00 |

SUPPLIER: SUNRISE MEDICAL CANADA INC.

PRICE

POWERED WHEEL CHAIR, CHILD FREESTYLE M11 MODEL

\$4 256.00

Basic Components

Body support system

- · rigid seat, flat
- seat rails, parallel
- · supple back, nylon
- seat width: from 30.5 cm (12 in.) to 40.6 cm (16 in.)
- seat depth: from 30.5 cm (12 in.) to 40.6 cm (16 in.)
- seat height: from 40.6 cm (16 in.) to $49.5 \text{ cm} (19^{1}/_{2} \text{ in.})$
- back height: from 38.1 cm (15 in.) to 50.8 cm (20 in.)
- adjustable seat bracket
- back, angle-adjustable from 84° to 124°
- safety belt, auto-type, velcro-type

Armrests

- T-type armrests, detachable, height-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.), short, long
- I-type armrests, flip-back, inclinable, height-adjustable from 15.2 cm (6 in.) to 25.4 cm (10 in.), short, long, straight, contoured, for SP101

- · armrest pads, straight, short, long
- · armrest pads, contoured, short, long

Footrests

- 70°, 80° or 90° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- padded calfrests for elevating legrests
- · folding footplates, standard
- heel loops, length-adjustable

Frame

- rear reflectors
- · running lights
- tie-down points for adapted transport
- · rear suspension
- · back tension bar
- · push handles

Drive systems

- control system for one power accessory only (Solo 40)*
- programmable joystick control
- battery charge display
- · toggle switch
- · battery charger
- battery boxes, group 22, group 24
- side bracket for joystick control
- · swivel side bracket for joystick control
- controller
- · motors

Wheels and forks

- driving wheels, inner tube tires, 25.4 cm (10 in.) x 7.6 cm (3 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)
- · rear wheel rims
- · front wheel rims
- · standard forks

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| seat/back structure, with angle-adjustable back, Trax system | 684.00 | 684.00 |
| headrest, small | 99.00 | 106.00 |
| headrest, medium | 99.00 | 106.00 |
| headrest, large | 99.00 | 106.00 |
| headrest mounting, articulated | 159.00 | 173.00 |
| supple back, nylon | N/C | 71.00 |
| supple back, tension-adjustable | 76.00 | 147.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| pack, angle-adjustable from 84° to 124° | N/C | N/A |
| padded back, contoured, fabric | 314.00 | 385.00 |
| padded back, contoured, velour | 350.00 | 421.00 |
| badded back, contoured, velour, with rigid base | 433.00 | 504.00 |
| badded back, contoured, fabric, with rigid base | 405.00 | 476.00 |
| supple seat, nylon (factory-installed only) | 293.00 | N/A |
| igid seat, flat | N/C | 141.00 |
| padded seat, contoured, fabric | 254.00 | 308.00 |
| padded seat, contoured, velour | 332.00 | 355.00 |
| eat rails, parallel | N/C | 31.00 |
| eat rails, tapered | 72.00 | 67.00 |
| djustable seat bracket | N/C | N/A |
| eat cushion, flat, foam, 5.1 cm (2 in.) | 58.00 | 58.00 |
| eat cushion, flat, foam, 7.6 cm (3 in.) | 58.00 | 58.00 |
| afety belt, auto-type | N/C | 42.00 |
| afety belt, velcro-type | N/C | 29.00 |
| Armrests: Γ-type armrests, detachable, height-adjustable from 15.2 cm (6 in.) | | |
| o 30.5 cm (12 in.), short, long | N/C | 136.00 |
| -type armrests, flip-back, inclinable, height-adjustable | 14/6 | 150.00 |
| from 15.2 cm (6 in.) to 25.4 cm (10 in.), short, long, straight, | | |
| contoured, for SP101 | N/C | 136.00 |
| -type armrests, flip-back, inclinable, height-adjustable | 100 | 150.00 |
| from 15.2 cm (6 in.) to 25.4 cm (10 in.), with transfer assists and | | |
| clothing guards, short, long, for SP101 | 160.00 | 216.00 |
| rmrest pads, straight, short | N/C | 15.00 |
| rmrest pads, straight, long | N/C | 18.00 |
| rmrest pads, contoured, short, long | N/C | 26.00 |
| | - ", " | |
| Footrests: | 316.00 | 316.00 |
| 0°, 80° or 90° footrests, parallel, detachable, swingaway, | | |
| ength-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) 0°, 80° or 90° footrests, heavy-duty, parallel, detachable, | N/C | 57.00 |
| wingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 i | (n.) 41.00 | N/A |
| ngled footrests, adjustable from 55° to 70°, on SP101 | 160.00 | 220.00 |
| nodification of footrest length by 5.1 cm (2 in.) or by 10.2 cm (4 i | | 16.00 |
| 0° elevating legrests, from 20.3 cm (8 in.) to 33.0 cm (13 in.) | 66.00 | 90.00 |
| added calfrests for elevating legrests | N/C | 19.00 |
| ontoured calfrests for elevating legrests | 72.00 | 55.00 |
| ingle calf strap | 19.00 | 19.00 |
| ouble calf strap | 33.00 | 33.00 |
| olding footplates, standard size | N/C | 49.00 |
| versized footplates | 74.00 | 86.00 |
| olding footplates, oversized, angle-adjustable and depth-adjustable | | 76.00 |
| olding footplates, multi-position | 106.00 | 102.00 |
| olding footplates, angle-adjustable, locking | 80.00 | 178.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| 90° full-width foot platform heel loops, length-adjustable | 92.00 N/C | 190.00 10.00 |
| Frame: | | |
| rear suspension | N/C | N/A |
| rear reflectors | N/C | N/A |
| running lights | N/C | N/A |
| tie-down points for adapted transport | N/C | 140.00 |
| front impact guard with rollers | 38.00 | 19.00 |
| back tension bar | N/C | N/A |
| push handles | N/C | N/A |
| cane holder | 45.00 | 45.00 |
| Drive systems: | | |
| programmable joystick control | N/C | 630.00 |
| battery charge display | N/C | N/A |
| battery charger | N/C | 384.00 |
| pattery boxes, group 22, group 24 | N/C | N/A |
| proportional chin control (requires interface) | 555.00 | 555.00 |
| non-proportional chin control (requires interface) | 555.00 | 555.00 |
| preath control (requires interface) | 426.00 | 426.00 |
| head control (requires interface) | 555.00 | 555.00 |
| aptray touch switch control (Penta, T-shaped, Wafer) | | |
| (requires interface) | 314.00 | 314.00 |
| foot control, including bracket (requires interface) | 1 740.00 | 1 740.00 |
| control with separate switches (Zero Touch) (requires interface) | 1 770.00 | 1 770.00 |
| proportional mini-joystick control (requires interface) | 790.00 | 1 090.00 |
| adapted controls interface with built-in display module | 1 445.00 | 1 445.00 |
| nterface for activation via joystick | 450.00 | 525.00 |
| nuxiliary switch | 91.00 | 96.00 |
| oggle switch | N/C | N/A |
| bush-button switch | 88.00 | N/A |
| modification of joystick control for auxiliary switch | 121.00 | 751.00 |
| pall extension | 52.00 | 52.00 |
| Γ-type extension | 52.00 | 52.00 |
| stick extension | 21.00 | 21.00 |
| side bracket for joystick control | N/C | 74.00 |
| swivel side bracket for joystick control | N/C | 188.00 |
| swivel midline bracket for joystick control | 163.00 | 351.00 |
| preath control bracket | 352.00 | 352.00 |
| chin control bracket | 352.00 | 352.00 |
| nead control bracket | 352.00 | 352.00 |
| pracket for separate display module | 352.00 | 352.00 |
| adjustable bracket for joystick control | 66.00 | 66.00 |
| chin bib control | 352.00 | 352.00 |
| modification, repositioning of joystick bracket inward | 120.00 | N/A |
| controller | N/C | 1 425.00 |
| motors | N/C | 662.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| Wheels and forks: | | |
| front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.) | N/C | 62.00 |
| driving wheels, inner tube tires, 25.4 cm (10 in.) x 7.6 cm (3 in.) | N/C | 202.00 |
| front wheel rims | N/C | N/A |
| rear wheel rims | N/C | N/A |
| airless inserts for rear wheels | 136.00 | N/A |
| standard forks | N/C | 70.00 |
| Component(s) under Special Consideration | | |
| seat/back structure, for power mechanism, SP101* | 850.00 | 850.00 |
| seat/back structure, SP101, for power mechanism with reclining | | |
| back with cylinder, compensating mechanism* | 1 185.00 | 1 185.00 |
| control system for one power accessory only (Solo 40)* | N/C | 275.00 |
| control system for four power accessories (Quattro)* | 575.00 | 575.00 |
| power reclining back, compensating mechanism, SP101* | 1 100.00 | 1 950.00 |
| power rocker device, 0° to 55°* | 1 695.00 | 1 695.00 |
| power elevating legrests, per pair, including legrests and footplates, | | |
| on SP101, requires Solo controller* | 1 295.00 | 1 072.00 |
| power elevating legrests, per unit, including legrests and footplates, | | |
| on SP101, requires Quattro controller* | 1 295.00 | 1 072.00 |

SUPPLIER: ORTHOFAB INC.

PRICE

POWERED WHEEL CHAIR OASIS 2 JR MODEL

\$5 122.00

Basic Components

Body support system

- rigid seat, flat
- supple back, nylon
- · rigid back, flat
- seat widths: 30.5 cm (12 in.), 33.0 cm (13 in.), 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.)
- seat depths: 35.6 cm (14 in.), 40.6 cm (16 in.)
- seat height: from 39.4 cm $(15^{1}/_{2} \text{ in.})$ to 47.0 cm $(18^{1}/_{2} \text{ in.})$
- back height: from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- modification of seat height by +2.5 cm (1 in.) or by +5.1 cm (2 in.)
- push handles
- power rocker device, including installation and one control for one accessory*
- safety belt, auto-type

Armrests

- U-type armrests, height-adjustable from 15.2 cm (6 in.) to 25.4 cm (10 in.), short, long
- T-type armrests, height-adjustable from 15.2 cm (6 in.) to 25.4 cm (10 in.), short
- armrest pads, straight, short, long
- rigid clothing guards, for T-type armrest, for U-type armrest

Footrests

- 70° footrests, parallel, detachable, swingaway, length-adjustable from 17.8 cm (7 in.) to 35.6 cm (14 in.)
- · contoured calfrests
- · folding footplates, standard
- heel loops, adjustable

Frame

- · rear suspension
- rear reflectors
- running lights, front, back
- tie-down points for adapted transport
- · anti-tip rollers

Drive systems

- · connecting cables for power reclining devices*
- programmable joystick control
- battery charge display
- push-button switch
- direction joystick
- battery charger
- battery boxes, group 22, group 24 breath control (requires interface)
- conical-spherical extension
- · swivel side bracket for joystick control
- controller
- motors

Wheels and forks

- rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- · rear wheel rims
- · front wheel rims
- standard forks for 20.3 cm (8 in.) and 22.9 cm (9 in.) wheels
- wheel forks, 20.3 cm (8 in.)

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| headrest, padded, contoured | 100.00 | 100.00 |
| headrest, ĥammock-type | 75.00 | 75.00 |
| headrest, small, medium, large | 100.00 | 100.00 |
| headrest mounting, articulated, uniball | 115.00 | 115.00 |
| headrest mounting, articulated | 102.00 | 102.00 |
| seat/back structure, with angle-adjustable back | 838.00 | 838.00 |
| back tension bar | 69.00 | 69.00 |
| rigid back, flat | N/C | 59.00 |
| rigid back, contoured | 191.00 | 250.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| supple back, nylon | N/C | 59.00 |
| supple back, tension-adjustable | 74.00 | 133.00 |
| back cushion, contoured, nylon | 118.00 | 118.00 |
| back cushion, contoured, leatherette | 118.00 | 118.00 |
| rigid seat, flat | N/C | 55.00 |
| rigid seat, elastic webbing | 48.00 | 103.00 |
| seat cushion, contoured, nylon | 210.00 | 210.00 |
| seat cushion, contoured, leatherette | 210.00 | 210.00 |
| seat cushion, flat, foam, 5.1 cm (2 in.) | 56.00 | 56.00 |
| seat cushion, flat, foam, 7.6 cm (3 in.) | 56.00 | 56.00 |
| modification of back height to + 48.3 cm (19 in.) modification of seat depth to 30.5 cm (12 in.), 33.0 cm (13 in.) | 96.00 | N/A |
| or 38.1 cm (15 in.) | 264.00 | N/A |
| modification of seat height by +2.5 cm (1 in.) or by +5.1 cm (2 in.) | | N/A |
| safety belt, velcro-type | 27.00 | 63.00 |
| safety belt, auto-type | N/C | 36.00 |
| safety belt, airplane-type | 38.00 | 74.00 |
| push handles | N/C | N/A |
| Armrests: U-type armrests, height-adjustable from 15.2 cm (6 in.) to 25.4 cm (10 in.), short U-type armrests, height-adjustable from 15.2 cm (6 in.) | N/C | 94.00 |
| to 25.4 cm (10 in.), long Γ-type armrests, height-adjustable from 15.2 cm (6 in.) | N/C | 120.00 |
| to 25.4 cm (10 in.), short | N/C | 148.00 |
| modification of armrests to +25.4 cm (10 in.) | 79.00 | N/A |
| armrest pads, straight, short | N/C | 12.00 |
| armrest pads, straight, long | N/C | 15.00 |
| armrest pads, contoured, short | 44.00 | 34.00 |
| armrest pads, contoured, long | 48.00 | 39.00 |
| rigid clothing guards, for T-type armrests or U-type armrests | N/C | N/A |
| Footrests: | | |
| 70° footrests, parallel, detachable, swingaway, length-adjustable from 17.8 cm (7 in.) to 35.6 cm (14 in.) modification of legrest length from 35.6 cm (14 in.) | N/C | 78.00 |
| to 48.3 cm (19 in.) 90° footrests, parallel, detachable, swingaway, length-adjustable | 79.00 | N/A |
| from 17.8 cm (7 in.) to 35.6 cm (14 in.) elevating legrests with compensating mechanism, length-adjustable | 140.00 | 148.00 |
| from 17.8 cm (7 in.) to 33.0 cm (13 in.) | 234.00 | 195.00 |
| contoured calfrests | N/C | N/A |
| louble calf strap | 55.00 | 55.00 |
| Folding footplates, standard | N/C | 16.00 |
| Full-width footplate | 221.00 | 252.00 |
| Folding footplates, aluminum | 44.00 | 38.00 |
| Cootplates, angle-adjustable and depth-adjustable, standard size | 76.00 | 54.00 |
| | , 0.00 | 27.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| full-width footplate, angle-adjustable and depth-adjustable | 168.00 N/C | 200.00 11.00 |
| heel loops, adjustable toe loops front impact guard with rollers | 30.00 36.00 | 15.00 15.00 18.00 |
| Frame: | | |
| anti-tip rollers | N/C | 48.00 |
| tie-down points for adapted transport | N/C | N/A |
| running lights, front, back | N/C | N/A |
| rear suspension | N/C | N/A |
| rear reflectors | N/C | N/A |
| Drive systems: | | |
| programmable joystick control | N/C | 511.00 |
| compact joystick control | 58.00 | 569.00 |
| battery charge display | N/C | N/A |
| push-button switch | N/C | N/A |
| direction joystick | N/C | N/A |
| modification of joystick control, switches and potentiometer | 78.00 | 589.00 |
| battery charger | N/C | 359.00 |
| battery boxes, group 22, group 24 | N/C | 208.00 |
| adapted controls interface | 1 400.00 | 1 911.00 |
| proportional chin control | 540.00 | 540.00 |
| non-proportional chin control | 421.00 | 421.00 |
| breath control (requires interface) | N/C | N/A |
| head control | 540.00 | 540.00 |
| laptray touch switch control | 301.00 | 301.00 |
| control with separate switches | 530.00 | 530.00 |
| chin bib control | 219.00 | 219.00 |
| breath control bracket | 340.00 | 340.00 |
| chin control bracket | 340.00 | 340.00 |
| head control bracket | 340.00 | 340.00 |
| bracket for separate display module | 37.00 | 37.00 |
| flexible bracket for interface display module | 90.00 | 90.00 |
| stick extension | 19.00 | 27.00 |
| ball extension | 27.00 | 35.00 |
| T-type extension | 27.00 | 35.00 |
| mushroom-shaped extension | 27.00 | 35.00 |
| conical-spherical extension | N/C | 8.00 |
| swivel side bracket for joystick control | N/C | 202.00 |
| swivel midline bracket for joystick control | 85.00 | 287.00 |
| controller motors | N/C N/C | 1 437.00 1 082.00 |
| Wheeler and Control | | |
| Wheels and forks: rear wheels, inner tube tires, 35.6 cm (14 in.) x 7.6 cm (3 in.) | N/C | 102.00 |
| | | |
| front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | N/C | 85.00 |
| front wheels, inner tube tires, 22.9 cm (9 in.) x 7.0 cm ($2^{3}/_{4}$ cm) | 88.00 | 129.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| rear wheel rims | N/C | N/A |
| front wheel rims | N/C | N/A |
| airless inserts for front wheels | 133.00 | N/A |
| airless inserts for rear wheels | 151.00 | N/A |
| wheel forks, 20.3 cm (8 in.) | N/C | 87.00 |
| standard forks for 20.3 cm (8 in.) or 22.9 cm (9 in.) wheels | N/C | 87.00 |
| Component(s) under Special Consideration | | |
| power rocker device, including installation and one control for one accessory* | N/C | 2 375.00 |
| power elevating legrests, from 17.8 cm (7 in.) to 33.0 cm (13 in.), | | |
| each* | 1 273.00 | 717.00 |
| power elevating legrests, from 17.8 cm (7 in.) to 33.0 cm (13 in.), | | |
| per pair* | 1 273.00 | 717.00 |
| control system for one power accessory only* | 230.00 | 230.00 |
| control system for four power accessories* | 740.00 | 740.00 |
| reclining back with cylinder (manual mechanism)* | 269.00 | N/A |
| connecting cables for power reclining devices* | N/C | N/A |

SUPPLIER: PRIDE MOBILITY PRODUCTS

PRICE

POWERED WHEEL CHAIR QUANTUM 1107 MODEL

\$4 250.00

Basic Components

Body support system

- rigid seat, flat
- · supple back, nylon
- seat width: from 25.4 cm (10 in.) to 50.8 cm (20 in.)
- seat depth: from 25.4 cm (10 in.) to 45.7 cm (18 in.)
- seat height: from 39.4 cm $(15^{1}/_{2} \text{ in.})$ to 44.5 cm $(17^{1}/_{2} \text{ in.})$
- back height: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- · adjustable seat bracket
- back, angle-adjustable
- push handles
- push bar
- installation of power reclining back, 100% compensating*
- · installation of power rocker device*
- · centre of gravity adjustment from seat
- safety belt, auto-type, velcro-type
- control system for one power accessory only*
- control system for four power accessories*

Armrests

- T-type armrests, height-adjustable from 27.9 cm (11 in.) to 43.2 cm (17 in.), short, long
- T-type armrests, pediatric, height-adjustable from 19.7 cm (7³/₄ in.) to 27.3 cm (10³/₄ in.), short, long
- I-type armrests, height-adjustable from 22.9 cm (9 in.) to 50.8 cm (20 in.), short, long

- · armrest pads, straight, short, long
- · armrest pads, contoured, short, long

Footrests

- 70° footrests, parallel, detachable, swingaway, length-adjustable from 25.4 cm (10 in.) to 43.2 cm (17 in.), footplates, angle-adjustable and depth-adjustable
- 70° footrests, pediatric, parallel, detachable, swingaway, length-adjustable, from 21.6 cm (8¹/₂ in.) to 28.6 cm (11¹/₄ in.), footplates, angle-adjustable and depth-adjustable
- 85° footplates, pediatric, parallel, detachable, swingaway, footplates length-adjustable from 19.1 cm (7¹/₂ in.) to 26.7 cm (10¹/₂ in.)
- modification of legrest length from 35.6 cm (14 in.) to 43.2 cm (17 in.) or from 43.2 cm (17 in.) to 50.8 cm (20 in.)
- padded calfrests
- footplates, angle-adjustable and depth-adjustable, 10.2 cm (4 in.) x 15.2 cm (6 in.), 12.7 cm (5 in.) x 15.2 cm (6 in.), 12.7 cm (5 in.) x 20.3 cm (8 in.), 15.2 cm (6 in.) x 20.3 cm (8 in.), standard size
- oversized footplates, angle-adjustable and depth-adjustable, 15.2 cm (6 in.) x 27.9 cm (11 in.), 20.3 cm (8 in.) x 27.9 cm (11 in.)
- heel loops, adjustable
- · heel loops, fixed

Frame

- · rear suspension
- · rear reflectors
- · tie-down points for adapted transport
- · anti-tip rollers

Drive systems

- programmable joystick control
- push-button switch
- battery charge display
- toggle switch
- battery charger, external 5A
- battery boxes, group U1 front, group U1 back
- conical-spherical extension
- side bracket for joystick control
- swivel side bracket for joystick control
- bracket for joystick control, lateral, multi-directional
- head control bracket
- P&G controller 80A 5 profiles
- GLIDE motors, 4.5 mph, 300 lb. capacity

Wheels and forks

- rear wheels, inner tube tires 300-4, 25.4 cm (10 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)
- · rear wheel rims
- · front wheel rims
- · airless inserts for front wheels
- standard forks

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| seat/back structure, with angle-adjustable back headrest, padded, contoured, small headrest, padded, contoured, large headrest and mounting for reclining back headrest mounting, articulated, uniball supple back, nylon padded back, flat, fabric padded back, contoured, fabric, leatherette, PRAMQ padded back, contoured, Basic Back Future Mobility, 300 lb. supple back on rigid base, on power reclining back back, angle-adjustable padded seat, contoured, fabric rigid seat, flat adjustable seat bracket push handles push bar safety belt, auto-type safety belt, velcro-type | 550.00 60.00 60.00 160.00 100.00 N/C 280.00 280.00 390.00 250.00 N/C 200.00 N/C | 600.00 170.00 170.00 234.00 290.00 80.00 340.00 470.00 340.00 160.00 200.00 40.00 N/A 40.00 85.00 25.00 25.00 |
| safety belt, airplane-type centre of gravity adjustment from seat | 35.00 N/C | 75.00 N/A |
| Armrests: | | |
| I-type armrests, height-adjustable from 22.9 cm (9 in.) to 50.8 cm (20 in.), short, long I-type armrests, on power reclining back, from 25.4 cm (10 in.) | N/C | 80.00 |
| to 33.0 cm (13 in.), short, long T-type armrests, height-adjustable from 27.9 cm (11 in.) | 200.00 | 306.00 |
| to 43.2 cm (17 in.), short, long T-type armrests, pediatric, height-adjustable from 19.7 cm (7 ³ / ₄ in.) to 27.3 cm (10 ³ / ₄ in.), short, long | N/C) N/C | 190.00 190.00 |
| U-type armrests, height-adjustable from 22.9 cm (9 in.) to 33.0 cm (13 in.), short, long | 200.00 | 290.00 |
| armrest pads, straight, short, long | N/C | 10.00 |
| armrest pads, contoured, short, long | N/C | 10.00 |
| armrest pads, wide gutter-type, one-piece, left, right | 55.00 | 65.00 |
| flexible clothing guards for U-type armrests rigid clothing guards for U-type armrests | 60.00 15.00 | 60.00 36.00 |
| Footrests: 70° footrests, parallel, detachable, swingaway, length-adjustable from 25.4 cm (10 in.) to 43.2 cm (17 in.), footplates, | N/G | 70.00 |
| angle-adjustable and depth-adjustable | N/C | 70.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| 5° footrests, drop-in, parallel, detachable, swingaway, | | |
| ength-adjustable from 14.0 cm (5½ in.) to 22.9 cm (9 in.), ootplates, angle-adjustable and depth-adjustable 10° footrests, pediatric, parallel, detachable, swingaway, | 200.00 | 170.00 |
| ength-adjustable from 21.6 cm (8 ¹ / ₂ in.) to 28.6 cm (11 ¹ / ₄ in.), ootplates, angle-adjustable and depth-adjustable (5° footrests, pediatric, parallel, detachable, swingaway, | N/C | 70.00 |
| ootplates length-adjustable from 19.1 cm ($7^{1}/_{2}$ in.) to 26.7 cm ($10^{1}/_{2}$ in.) | N/C | 170.00 |
| oot platform, 24.21 cm ($9^{1}/_{2}$ in.), length-adjustable | 11/C | 170.00 |
| rom 25.4 cm (10 in.) to 33.0 cm (13 in.) | 75.00 | 84.00 |
| levating legrests, adult, from 25.4 cm (10 in.) to 43.2 cm (17 in.) nodification of legrest length from 35.6 cm (14 in.) | 200.00 | 170.00 |
| o 43.2 cm (17 in.) or from 43.2 cm (17 in.) to 50.8 cm (20 in.) | N/C | N/A |
| added calfrests | N/C | 15.00 |
| ontoured calfrests | 40.00 | 60.00 |
| ingle calf strap | 35.00 | 35.00 |
| ouble calf strap | 60.00 | 60.00 |
| ootplates, angle-adjustable and depth-adjustable, 0.2 cm (4 in.) x 15.2 cm (6 in.), 12.7 cm (5 in.) x 15.2 cm (6 in.), 2.7 cm (5 in.) x 20.3 cm (8 in.), 15.2 cm (6 in.) x 20.3 cm (8 in.), tandard size | N/C | 35.00 |
| versized footplates, angle-adjustable and depth-adjustable, | | |
| 5.2 cm (6 in.) x 27.9 cm (11 in.), 20.3 cm (8 in.) x 27.9 cm (11 in.) | N/C | 70.00 |
| ull-width footplate | 100.00 | 150.00 |
| ustom-made footplates (on approval of R&D) | 100.00 | 150.00 |
| eel loops, adjustable | N/C | 10.00 |
| eel loops, fixed | N/C | 10.00 |
| pe loops | 20.00 | 15.00 |
| Frame: ear suspension | N/C | N/A |
| ear reflectors | N/C | 20.00 |
| le-down points for adapted transport | N/C | 25.00 |
| cont impact guard with rollers | 20.00 | 15.00 |
| nti-tip rollers | N/C | 12.00 |
| ane holder | 40.00 | 40.00 |
| Orive systems: | 2716 | |
| rogrammable joystick control | N/C | 725.00 |
| ompact joystick control, MicroDrive Mini P&G | 475.00 | 1 152.00 |
| ontroller heavy-duty, Stealth Mushroom | 1 500.00 | 2 200.00 |
| pystick control with built-in controller | 50.00 | 775.00 |
| attery charge display | N/C | N/A |
| oggle switch | N/C | N/A |
| | N/C | N/A |
| | | |
| oush-button switch uxiliary switch, Buddy Button, with OmniPlus interface sattery charger, external 5A | 44.00 N/C | 44.00 110.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| pattery boxes, group U1 rear | N/C | 17.00 |
| proportional chin control, P& G CTLDC1117 | 452.00 | 597.00 |
| non-proportional chin control, Mini Joystick | 420.00 | 420.00 |
| nead control, ASL RIM CTLDC1380 | 1 077.00 | 1 077.00 |
| aptray touch switch control, TASH SWTMCRO1003 | 292.00 | 292.00 |
| foot control, RIM | 1 250.00 | 1 250.00 |
| control with separate switches (requires interface) | 105.00 | 105.00 |
| accessory interface/Synergy seat | 24.00 | 24.00 |
| non-proportional controls interfaces, OmniPlus | 860.00 | 860.00 |
| adapted controls interface, OmniPlus (breath control included) | 860.00 | 860.00 |
| tick extension | 40.00 | 50.00 |
| pall extension, hard | 30.00 | 40.00 |
| Γ-type extension | 60.00 | 70.00 |
| nushroom-shaped extension | 40.00 | 50.00 |
| conical-spherical extension | N/C | 50.00 |
| wivel side bracket for joystick control | N/C | 160.00 |
| ide bracket for joystick control | N/C | 12.00 |
| wivel midline bracket for joystick control, GATLIN FRASMB4088 | 272.00 | 432.00 |
| pracket for joystick control, lateral, multi-directional | N/C | 160.00 |
| oreath control bracket, INDPART2151 | 264.00 | 264.00 |
| chin control bracket, FRMASMB8041 | 328.00 | 488.00 |
| nead control bracket | N/C | 125.00 |
| oracket for separate display module, OmniPlus | 48.00 | 63.00 |
| chin bib control, SBM750 GATLIN (requires OmniPlus interface) | 395.00 | 556.00 |
| P&G controller, 80A 5 profiles | N/C | 561.00 |
| GLIDE motors, 4.5 mph, 300 lb. capacity | N/C | 520.00 |
| Wheels and forks: | | |
| rear wheels, inner tube tires 300-4, 25.4 cm (10 in.) | N/C | 80.00 |
| front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.) | N/C | 30.00 |
| ront wheel rims | N/C | 10.00 |
| ear wheel rims | N/C | 40.00 |
| irless inserts for rear wheels | 80.00 | 42.00 |
| irless inserts for front wheels | N/C | 19.00 |
| standard forks | N/C | 36.00 |
| Component(s) under Special Consideration seat/back structure, with reclining back and cylinder, 55.0 cm (22 in) backposts, including a Syngray seat* | 950.00 | 950.00 |
| 65.9 cm (22 in.) backposts, including a Synergy seat* eat/back structure, with manual tipping device, maximum 0.6 cm (16 in.) x 40.6 cm (16 in.), 160 lb., structure from 25.4 cm (10 in.) to 35.6 cm (14 in.) or from 35.6 cm (14 in.) | 930.00 | 930.00 |
| o 40.6 cm (16 in.), including a Synergy seat* | 1 145.00 | 1 300.00 |
| stroller handles for manual tipping* | 75.00 | 93.00 |
| control system for one power accessory only* | N/C | 133.00 |
| control system for four power accessories* | N/C | 133.00 |
| connecting cables for power reclining devices* | 100.00 | 100.00 |
| eclining back with cylinder* | 400.00 | 400.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| power reclining back, 100% compensating, max. 160 lb.* installation of power reclining back, 100% compensating* | 2 250.00 N/C | 2 250.00 50.00 |
| bower reclining back, joystick-controlled* bower rocker device, max. 160 lb., from 35.6 cm (14 in.) x 35.6 cm (14 in.) to | 250.00 | 450.00 |
| 40.6 cm (16 in.) x 45.7 cm (18 in.)* | 1 895.00 | 2 095.00 |
| nstallation of power rocker device* | N/C | 150.00 |
| ower rocker device, joystick-controlled* | 375.00 | 450.00 |
| power elevating legrests, high-pivot, per pair* | 600.00 | 400.00 |
| power elevating legrests, high-pivot, each* | 350.00 | 400.00 |
| power elevating legrests with compensating mechanism, per pair* | 1 500.00 | 850.00 |

§4. Supplements for wheel chairs

CUSHIONS

FOR WHEEL CHAIRS

| | PRICE |
|--|--------|
| contoured seat cushion, waterproof, with stretch fabric cover | 205.00 |
| contoured seat cushion with gel, waterproof, with stretch fabric cover | 270.00 |
| COMBI-type cushion or equivalent* | S.C. |
| JAY-type cushion or equivalent* | S.C. |
| gel cushion or equivalent* | S.C. |
| ROHO cushion or equivalent* | S.C. |
| special cushion* | S.C. |

§5. Components for wheel chairs

TIRES AND INSERTS

FOR MANUAL WHEEL CHAIRS

| SUPPLIER: ORTHOFAB INC. | PRICE |
|--|-------|
| tire, inner tube, standard pressure, 31.8 cm $(12^{1}/_{2} \text{ in.}) \times 5.7 \text{ cm } (2^{1}/_{4} \text{ in.})$ | 8.32 |
| tire, inner tube, standard pressure, 50.8 cm (20 in.) x 3.5 cm (1^{3} / ₈ in.) | 7.48 |
| tire, inner tube, standard pressure, 55.9 cm (22 in.) x 3.5 cm (1^{3} / ₈ in.) | 7.00 |
| tire, inner tube, standard pressure, 61.0 cm (24 in.) x 3.2 cm ($1^{1}/_{4}$ in.) | 6.38 |
| tire, inner tube, standard pressure, 61.0 cm (24 in.) x 3.5 cm (1^{3} / ₈ in.) | 7.00 |
| tire, inner tube, standard pressure, 61.0 cm (24 in.) x 4.4 cm (1 ³ / ₄ in.) | 8.76 |
| tire, inner tube, standard pressure, $40.6 \text{ cm} (16 \text{ in.}) \times 4.4 \text{ cm} (1^3/_4 \text{ in.})$ | 8.76 |
| tire, inner tube, standard pressure, 66.0 cm (26 in.) x 3.5 cm (1^{3} / ₈ in.) | 7.88 |
| tire, inner tube, high pressure, 50.8 cm (20 in.) x 2.5 cm (1 in.) | 11.09 |
| tire, inner tube, high pressure, 55.9 cm (22 in.) x 2.5 cm (1 in.) | 11.09 |
| tire, inner tube, high pressure, 61.0 cm (24 in.) x 2.5 cm (1 in.) | 11.09 |
| tire, inner tube, high pressure, 66.0 cm (26 in.) x 2.5 cm (1 in.) | 11.09 |
| tire, inner tube, 61.0 cm (24 in.) x 3.5 cm (1 ³ / ₈ in.), all-terrain, rounded surface | 11.22 |

| tire, inner tube, 61.0 cm (24 in.) x 3.5 cm (1 ³ / ₈ in.), all-terrain, rounded surface | 8.36 |
|---|-------|
| solid tire, 20.3 cm (8 in.) x 2.5 cm (1 in.) | 3.96 |
| solid tire, 55.9 cm (22 in.) x 2.5 cm (1 in.) | 9.57 |
| solid tire, 61.0 cm (24 in.) x 2.5 cm (1 in.) | 9.19 |
| tire, inner tube, $15.2 \text{ cm } (6 \text{ in.}) \text{ x } 3.2 \text{ cm } (1\frac{1}{4} \text{ in.})$ | 6.25 |
| tire, inner tube, 20.3 cm (8 in.) x 3.2 cm ($1\frac{1}{4}$ in.) (C-63) | 5.81 |
| tire, inner tube, 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.) | 7.88 |
| tire, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 6.51 |
| tire, inner tube, $18.8 \text{ cm} (7 \text{ in.}) \text{ x } 4.4 \text{ cm} (1^{3}/_{4} \text{ in.})$ | 7.17 |
| tire, inner tube, 20.3 cm (8 in.) x 3.2 cm ($1\frac{1}{4}$ in.) (C-737) | 5.81 |
| semi-pneumatic tire, 12.7 cm (5 in.) x 2.5 cm (1 in.) | 8.01 |
| semi-pneumatic tire, 15.2 cm (6 in.) x 2.5 cm (1 in.) | 8.01 |
| semi-pneumatic tire, 20.3 cm (8 in.) x 2.5 cm (1 in.) (poly kik) | 9.14 |
| semi-pneumatic tire, 20.3 cm (8 in.) x 2.5 cm (1 in.) (poly pyramide) | 8.82 |
| semi-pneumatic tire, 55.9 cm (22 in.) x 2.5 cm (1 in.) | 13.33 |
| semi-pneumatic tire, 61.0 cm (24 in.) x 2.5 cm (1 in.) | 14.04 |
| semi-pneumatic tire, 66.0 cm (26 in.) x 2.5 cm (1 in.) | 14.04 |
| puncture-resistant tire, 15.2 cm (6 in.) x 3.2 cm ($1\frac{1}{4}$ in.) | 9.34 |
| puncture-resistant tire, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.) | 9.68 |
| puncture-resistant tire, 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.) | 11.00 |
| puncture-resistant tire, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 12.32 |
| puncture-resistant tire, 50.8 cm (20 in.) x 3.5 cm ($\frac{1}{6}$ in.) | 21.25 |
| puncture-resistant tire, 55.9 cm (22 in.) x 3.5 cm ($\frac{1}{8}$ in.) | 21.25 |
| puncture-resistant tire, 61.0 cm (24 in.) x 2.5 cm (1 in.) | 17.51 |
| puncture-resistant tire, 61.0 cm (24 in.) x 3.5 cm ($1^3/_8$ in.) | 21.47 |

TIRES AND INSERTS

FOR POWERED WHEEL CHAIRS

| SUPPLIER: ORTHOFAB INC. | PRICE |
|--|-------|
| tire, inner tube, 33.0 cm (13 in.) x 10.2 cm (4 in.) (400-5) | 14.70 |
| tire, inner tube, $18.8 \text{ cm} (7 \text{ in.}) \times 4.4 \text{ cm} (1^{3}/_{4} \text{ in.})$ | 7.17 |
| tire, inner tube, 20.3 cm (8 in.) x 3.2 cm ($1\frac{1}{4}$ in.) | 5.81 |
| tire, inner tube, 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.) | 7.88 |
| tire, inner tube, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 6.51 |
| tire, inner tube, 21.6 cm $(8^{1}/_{2} \text{ in.}) \times 5.3 \text{ cm } (2^{1}/_{8} \text{ in.})$ | 37.00 |
| tire, inner tube, 20.3 cm (8 in.) x 7 cm $(2^{3}/_{4}$ in.) | 8.04 |
| tire, inner tube, 22.9 cm (9 in.) x 7 cm $(2^{3}/_{4} in.)$ | 8.76 |
| tire, inner tube, 25.4 cm (10 in.) x 7.6 cm (3 in.) | 10.12 |
| tire, inner tube, 30.5 cm (12 in.) x 7.6 cm (3 in.) | 14.04 |
| tire, inner tube, $31.8 \text{ cm } (12^{1}/_{2} \text{ in.}) \times 5.7 \text{ cm } (2^{1}/_{4} \text{ in.})$ | 8.32 |
| tire, inner tube, 35.6 cm (14 in.) x 5.7 cm ($2^{1}/_{4}$ in.) | 11.00 |
| tire, inner tube, 35.6 cm (14 in.) x 7.6 cm (3 in.), (300-8) | 15.80 |
| tire, inner tube, 35.6 cm (14 in.) x 10.2 cm (4 in.) (400-6) | 13.20 |
| tire, inner tube, $40 \text{ cm } (15^3/_4 \text{ in.}) \times 7 \text{ cm } (2^3/_4 \text{ in.})$ | 58.00 |
| tire, inner tube, $40.6 \text{ cm} (16 \text{ in.}) \times 5.7 \text{ cm} (2^{1}/_{4} \text{ in.})$ | 10.47 |
| tire, inner tube, $40.6 \text{ cm } (16 \text{ in.}) \times 5.3 \text{ cm } (2^{1}/_{8} \text{ in.})$ | 10.47 |
| tire, inner tube, 45.7 cm (18 in.) x 5.7 cm ($2^{1}/_{4}$ in.) | 10.96 |
| tire, inner tube, 50.8 cm (20 in.) x 5.3 cm ($2^{1/8}$ in.) | 12.41 |
| tire, inner tube, $50.8 \text{ cm} (20 \text{ in.}) \times 5.7 \text{ cm} (2^{1}/_{4} \text{ in.})$ | 10.96 |
| semi-pneumatic tire, 20.3 cm (8 in.) x 4.4 cm ($1^{3}/_{4}$ in.) | 11.44 |
| semi-pneumatic tire, $22.9 \text{ cm } (9 \text{ in.}) \text{ x } 7 \text{ cm } (2^3/_4 \text{ in.})$ | 24.64 |

| puncture-resistant tire, 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4} in.)$ (poly kik) | 11.00 |
|---|-------|
| puncture-resistant tire, 22.9 cm (9 in.) x 7 cm ($\frac{27}{4}$ in.) | 32.91 |
| | 32.91 |
| puncture-resistant tire, (280/250-4) | |
| puncture-resistant tire, 25.4 cm (10 in.) x 7.6 cm (3 in.) | 43.03 |
| puncture-resistant tire, 30.5 cm (12 in.) x 7.6 cm (3 in.) | 31.24 |
| puncture-resistant tire, 35.6 cm (14 in.) x 10.2 cm (4 in.) | 46.64 |
| puncture-resistant tire, 35.6 cm (14 in.) x 7.6 cm (3 in.) | 59.58 |
| puncture-resistant tire, (300-8) | 59.58 |
| puncture-resistant tire, 35.6 cm (14 in.) x 10.2 cm (4 in.), (400-6) | 46.64 |
| puncture-resistant tire, 50.8 cm (20 in.) x 5.3 cm ($2^{1}/_{8}$ in.) | 25.52 |
| puncture-resistant tire, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 12.32 |
| puncture-resistant tire, 20.3 cm (8 in.) x 5.1 cm (2 in.) (poly kik) | 11.88 |
| airless insert, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.) | 10.74 |
| airless insert, 20.3 cm (8 in.) x 4.4 cm $(1^{3}/_{4}$ in.) | 13.02 |
| airless insert, 31.8 cm ($12^{1}/_{2}$ in.) x 5.7 cm ($2^{1}/_{4}$ in.) | 21.12 |
| airless insert, 35.6 cm (14 in.) x 5.7 cm ($2^{1}/_{4}$ in.) | 21.12 |
| airless insert, 40.6 cm (16 in.) x 5.3 cm ($2^{1}/_{8}$ in.) | 23.76 |
| airless insert, 45.7 cm (18 in.) x 5.7 cm (2 / ₄ in.) | 20.24 |
| airless insert, 50.8 cm (20 in.) x 5.3 cm (2 / $_{8}$ in.) | 20.24 |
| airless insert, 50.8 cm (20 in.) x 5.7 cm ($2^{1}/_{4}$ in.) | 20.24 |

BATTERIES

FOR POWERED WHEEL CHAIRS

SEALED LEAD BATTERIES (AGM OR AGM/GEL, DEEP CYCLE, NOMINAL VOLTAGE OF 12 VOLTS)

Price including delivery, guarantee, and recovery of non-compliant or defective batteries after use (price per pair)

SUPPLIER: PORTAMAX 2003 INC.

GROUP 22 BATTERIES (AGM):

Model: PM12V50 179.00

SUPPLIER: BATTERIES POWER (IBERVILLE) LTÉE

GROUP 24 BATTERIES (AGM/GEL):

Model: WCG-24 225.00

SUPPLIER: EAST PENN/POWER BATTERY

GROUP U1 BATTERIES (AGM):

Model: 8AU1 114.00

DIVISION II

POSITIONING BASES

SUPPLIER: INVACARE CANADA INC.

PRICE

POSITIONING BASE, ADULT SOLARA 2G MODEL

\$1 836.00

Basic Components

Body support system

- seat height: from 36.8 cm $(14^{1}/_{2} \text{ in.})$ to 48.3 cm (19 in.)
- seat widths: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.)
- seat depths: 30.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.)
- back heights: 50.8 cm (20 in.), 61.0 cm (24 in.)
- safety belt, velcro-type, auto-type

Armrests

- T-type armrests, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.) or from 25.4 cm (10 in.) to 40.6 cm (16 in.), short, long
- U-type armrests, height-adjustable from 21.6 cm (8¹/₂ in.) to 31.8 cm (12¹/₂ in.), short, long
- armrest pads, straight, short, long
- · clothing guards, rigid, integrated into armrests offered

Footrests

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 44.5 cm (17¹/₂ in.)
- 70° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 41.9 cm (16¹/₂ in.)
- 70° footrests, lift-off, parallel, length-adjustable from 34.3 cm (13¹/₂ in.) to 41.9 cm (16¹/₂ in.)
- padded calfrests
- heel loops, fixed
- heel loops, adjustable
- · folding footplates, standard

Frame

- frame length, from 38.1 cm (15 in.) to 48.3 cm (19 in.) or from 45.7 cm (18 in.) to 55.9 cm (22 in.)
- · rocker device
- tie-down points for transport
- · folding back, angle-adjustable
- push handles, integrated
- · anti-tip rollers

Drive, brake, wheel, fork, and axle systems

- · smooth handrims
- standard, push-to-lock
- rear mag wheels, standard pressure, 30.5 cm (12 in.)
- rear mag wheels, standard pressure, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)

- rear mag wheels, solid tires, 30.5 cm (12 in.), with airless inserts
- front wheels, solid tires, 15.2 cm (6 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.)
- front wheels, solid tires, 12.7 cm (5 in.), aluminium rims
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 in.)
- standard forks
- · threaded axles
- quick-release axles*

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: Stealth headrest, 25.4 cm (10 in.), 35.6 cm (14 in.), adjustable mounting large headrest, fixed mounting modification of seat width to 53.3 cm (21 in.) or to 55.9 cm (22 in.) rigid seat, flat safety belt, velcro-type safety belt, auto-type | 205.00 189.00 62.00 54.00 N/C N/C | 325.00 257.00 N/A 119.00 42.00 53.00 |
| Armrests: U-type armrests, height-adjustable from 21.6 cm (8 ¹ / ₂ in.) to 31.8 cm (12 ¹ / ₂ in.), short, long T-type armrests, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.) from 25.4 cm (10 in.) to 40.6 cm (16 in.), short, long armrest pads, straight, long armrest pads, straight, short clothing guards, rigid, integrated into armrests offered | N/C N/C N/C N/C N/C | 131.00 131.00 26.00 26.00 N/A |
| Footrests: 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13 ¹ / ₂ in.) to 44.5 cm (17 ¹ / ₂ in.) 70° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13 ¹ / ₂ in.) to 41.9 cm (16 ¹ / ₂ in.) 90° footrests, parallel, detachable, swingaway, length-adjustable | N/C N/C | 114.00 114.00 |
| from 11.4 cm (4 ¹ / ₂ in.) to 19.1 cm (7 ¹ / ₂ in.) 60° footrests, MFX, parallel, detachable, swingaway, length-adjustable from 22.9 cm (9 in.) to 31.8 cm (12 ¹ / ₂ in.) 70° footrests, MFX, parallel, detachable, swingaway, | 113.00 113.00 | 170.00 170.00 |
| length-adjustable from 14.6 cm $(5^3/_4$ in.) to 29.8 cm $(11^3/_4$ in.) 70° footrests, tapered, detachable, swingaway, length-adjustable from 32.4 cm $(12^3/_4$ in.) to 41.3 cm $(16^1/_4$ in.) | 113.00 113.00 | 170.00 170.00 |
| 70° footrests, lift-off, parallel, length-adjustable from 34.3 cm ($13^{1}/_{2}$ in.) to 41.9 cm ($16^{1}/_{2}$ in.) | N/C | 114.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| 70° footrests, lift-off, MFX, length-adjustable from 14.6 cm (5 ³ / ₄ in.) to 29.8 cm (11 ³ / ₄ in.) | 113.00 | 170.00 |
| 70° footrests, lift-off, tapered, length-adjustable from 32.4 cm (12³/₄ in.) to 41.3 cm (16¹/₄ in.) 90° footrests, lift-off, parallel, length-adjustable from | 113.00 | 170.00 |
| 11.4 cm ($4^{1}/_{2}$ in.) to 19.1 cm ($7^{1}/_{2}$ in.) elevating legrests, length-adjustable from 35.6 cm (14 in.) to | 113.00 | 170.00 |
| 50.8 cm (20 in.) elevating legrests with compensating mechanism, from | 244.00 | 236.00 |
| 40.6 cm (16 in.) to 53.3 cm (21 in.) modification of elevating legrest length, by -2.5 cm (1 in.) or | 160.00 | 194.00 |
| by -5.1 cm (2 in.) | 250.00 | 250.00 |
| padded calfrests | N/C | 28.00 |
| ingle calf strap | 25.00 | 37.00 |
| louble calf strap | 38.00 | 55.00 |
| folding footplates, standard cotplates, angle-adjustable and depth-adjustable, standard size | N/C | 42.00 |
| or oversized, $18.4 \text{ cm} (7^{1}/_{4} \text{ in.})$ | 76.00 | 80.00 |
| oversized footplates | 45.00 | 65.00 |
| neel loops, fixed | N/C | 7.00 |
| neel loops, adjustable | N/C | 15.00 |
| Frame: push handles, integrated | N/C | 52.00 |
| anti-tip rollers frame length, from 38.1 cm (15 in.) to 48.3 cm (19 in.) or from | N/C | 50.00 |
| 45.7 cm (18 in.) to 55.9 cm (22 in.) | N/C | N/A |
| pack tension bar | 20.00 | 60.00 |
| ie-down points for transport | N/C | N/A |
| olding back, angle-adjustable | N/C | N/A |
| ocker device | N/C | N/A N/A |
| Drive systems: | 2716 | 24.00 |
| smooth handrims | N/C | 36.00 |
| plastic-coated handrims | 54.00 | 63.00 |
| nandrims with vertical or oblique projections | 155.00 | 125.00 |
| Wheel locks: standard wheel locks, push-to-lock | N/C | 46.00 |
| wheel lock extensions | 34.00 | 34.00 |
| Wheels: rear mag wheels, standard pressure, 30.5 cm (12 in.) rear mag wheels, standard pressure, 50.8 cm (20 in.), | N/C | 75.00 |
| 25.9 cm (22 in.), 61.0 cm (24 in.) rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | N/C | 105.00 |
| 61.0 cm (24 in.) | N/C | 105.00 |
| rear mag wheels, solid tires, 30.5 cm (12 in.), with airless inserts | N/C | 95.00 |
| Front wheels, solid tires, 15.2 cm (6 in.) | N/C | 40.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm (1 ¹ / ₄ in.) | N/C | 40.00 |
| front wheels, solid tires, 12.7 cm (5 in.), aluminum rims | N/C | 60.00 |
| front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | N/C | 63.00 |
| front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.) | N/C | 50.00 |
| Forks: standard forks | N/C | 52.00 |
| Rear axles: threaded axles | N/C | 15.00 |
| Component(s) under Special Consideration | | |
| reclining back* | 504.00 | N/A |
| heavy-duty frame* | 322.00 | N/A |
| contracture footrests, bilateral* | 187.00 | N/A |
| contracture footrests, one-piece* | 187.00 | N/A |
| quick-release axles* | N/C | 53.00 |

SUPPLIER: SUNRISE MEDICAL CANADA INC.

PRICE

POSITIONING BASE, ADULT QUICKIE IRIS MODEL

\$1 798.00

Basic Components

Body support system

- seat height: from 36.8 cm (14¹/₂ in.) to 52.1 cm (20¹/₂ in.), from 31.8 cm (12¹/₂ in.) to 47.0 cm (18¹/₂ in.) in the case of optional drop seat
- seat width: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- seat depth: from 38.1 cm (15 in.) to 55.9 cm (22 in.)
- back heights: 54.6 cm $(21^{1}/_{2} \text{ in.})$, 62.2 cm $(24^{1}/_{2} \text{ in.})$, 69.9 cm $(27^{1}/_{2} \text{ in.})$
- safety belt, auto-type, velcro-type
- tension bar available on optional reclining back

Armrests

- T-type armrests, height-adjustable from 26.7 cm (10¹/₂ in.) to 40.0 cm (15³/₄ in.), short, long
- armrest pads, straight, short, long
- armrest pads, tubular

Footrests

- 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70°, 80° or 90° footrests, parallel, detachable, swingaway, length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.)
- padded calfrests for elevating legrests
- · folding footplates, standard
- heel loops, adjustable

Price upon

Frame

- anti-tip rollers
- seat frame for contracture footrests
- rocker device, from -5° to $+60^{\circ}$
- folding back, angle-adjustable from 80° to 120°
- push handles, integrated

Drive, brake, wheel, fork, and axle systems

- smooth handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard, push-to-lock
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, standard pressure, 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.)
- front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm (1¹/₂ in.), 15.2 cm (6 in.) x 3.8 cm (1¹/₂ in.), 20.3 cm (8 in.) x 3.8 cm (1¹/₂ in.)
- forks, 17.8 cm (7 in.) compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5¹/₄ in.); high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- long fork stems, $+1.9 \text{ cm} (\frac{3}{4} \text{ in.})$, $+3.8 \text{ cm} (\frac{1}{2} \text{ in.})$
- threaded rear axles
- quick-release axles*

| | initial purchase or replacement of wheel chair (price per pair, as applicable) | replacement of component (unit price) |
|---|--|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| headrest | 99.00 | 106.00 |
| rigid seat, flat, adjustable for growth | 64.00 | 158.00 |
| rigid seat, flat, dropped, adjustable for growth | 64.00 | 158.00 |
| modification of seat width to 53.3 cm (21 in.) or to 55.9 cm (22 in.) | | N/A |
| safety belt, auto-type | N/C | 42.00 |
| safety belt, velcro-type | N/C | 29.00 |
| safety belt, airplane-type | 50.00 | 79.00 |
| safety belt, airplane-type, padded | 76.00 | 105.00 |
| headrest mounting, articulated | 159.00 | 173.00 |
| crossbar for headrest mounting | 200.00 | 212.00 |
| back tension bar available on optional reclining back | N/C | N/A |
| Armrests: | | |
| U-type armrests, detachable, flip-back, height-adjustable, | | |
| short, long | 82.00 | 176.00 |
| T-type armrests, height-adjustable from 26.7 cm $(10^{1}/_{2} \text{ in.})$ | | |
| to 40.0 cm (15 ³ / ₄ in.), short, long | N/C | 135.00 |

Price upon

| | (price per pair, as applicable) | of component (unit price) |
|---|------------------------------------|------------------------------|
| I-type armrests, height-adjustable and depth-adjustable, | | |
| lockable, short | 220.00 | 245.00 |
| armrest pads, tubular | N/C | 2.00 |
| armrest pads, straight, short | N/C | 15.00 |
| armrest pads, straight, long | N/C | 18.00 |
| clothing guards, rigid | 93.00 | 68.00 |
| Footrests: | | |
| 60° or 70° footrests, parallel, detachable, swingaway, | NIG | 55.00 |
| length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) | N/C | 55.00 |
| 70° footrests, tapered, detachable, swingaway, length-adjustable | NIG | 55.00 |
| from 35.6 cm (14 in.) to 48.3 cm (19 in.) | N/C | 55.00 |
| 70°, 80° or 90° footrests, parallel, detachable, swingaway, | NIC | 57.00 |
| length-adjustable from 15.2 cm (6 in.) to 30.5 cm (12 in.) | N/C | 57.00 |
| 70°, 80° or 90° footrests, heavy-duty, non flip-back | 64.00 | 87.00 |
| modification of footrest length from 48.3 cm (19 in.) | 21.00 | 20.00 |
| to 52.1 cm $(20^{1}/_{2} \text{ in.})$ | 31.00 | 30.00 |
| modification of 70°, 80° or 90° footrest length by 5.1 cm (2 in.) | 22.00 | 16.00 |
| or by 10.2 cm (4 in.) | 32.00 108.00 | 16.00 109.00 |
| elevating legrests elevating legrests with compensating mechanism | 200.00 | 155.00 |
| 90° elevating legrests, length-adjustable from 20.3 cm (8 in.) | 200.00 | 133.00 |
| to 33.0 cm (13 in.) | 72.00 | 91.00 |
| padded calfrests for elevating legrests | N/C | 19.00 |
| contoured calfrests | 72.00 | 55.00 |
| single calf strap | 19.00 | 19.00 |
| double calf strap | 33.00 | 33.00 |
| heel loops, adjustable | N/C | 10.00 |
| folding footplates, standard | N/C | 49.00 |
| folding footplates, oversized | 54.00 | 76.00 |
| full-width footplate | 85.00 | 183.00 |
| folding footplates, angle-adjustable, locking | 80.00 | 178.00 |
| 90° full-width foot platform | 92.00 | 190.00 |
| modification of footrest mounting from 17.8 cm (7 in.) | > 2. 00 | 1,0.00 |
| to 34.3 cm (13 ¹ / ₂ in.) | 56.00 | 34.00 |
| Frame: | | |
| heavy-duty frame | 270.00 | N/A |
| seat frame for contracture footrests | N/C | N/A |
| front anti-tippers | 70.00 | 40.00 |
| anti-tip rollers | N/C | 25.00 |
| rocker device, from -5° to +60° | N/C | N/A |
| folding back, angle-adjustable from 80° to 120° | N/C | N/A |
| push handles, integrated | N/C | N/A |
| Drive systems: | | 60.00 |
| smooth handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), | | 60.00 |
| 61.0 cm (24 in.) | 56.00 | 88.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| handrims with vertical or oblique projections, 61.0 cm (24 in.) | 90.00 | 105.00 |
| small handrim for one-arm drive | 56.00 | 97.00 |
| one-arm drive for dual handrim | 536.00 | 669.00 |
| Wheel locks: | | |
| standard wheel locks, push-to-lock | N/C | 40.00 |
| wheel lock extensions | 40.00 | 20.00 |
| Wheels: | | |
| rear mag wheels, standard pressure, 30.5 cm (12 in.) | N/C | 130.00 |
| rear mag wheels, standard pressure, 40.6 cm (16 in.) | 32.00 | 146.00 |
| rear mag wheels, standard pressure, 50.8 cm (20 in.) | N/C | 136.00 |
| rear mag wheels, standard pressure, 55.9 cm (22 in.), 61.0 cm (24 in | | 113.00 |
| rear mag wheels, solid tires, 30.5 cm (12 in.) rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | N/C | 145.00 |
| 61.0 cm (24 in.) | N/C | 136.00 |
| spoked rear wheels, standard pressure, 61.0 cm (24 in.) | N/C | 136.00 |
| front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 48.00 | 72.00 |
| front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) | N/C | 63.00 |
| Front wheels, solid tires, 15.2 cm (6 in.) Front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm ($1^{1}/_{2}$ in. | N/C | 62.00 |
| 15.2 cm (6 in.) x 3.8 cm ($1\frac{1}{2}$ in.) | , N/C | 89.00 |
| front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm ($1\frac{1}{2}$ in. | | 99.00 |
| Forks: forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels | N/C | 37.00 |
| standard forks, 15.2 cm (6 in.); short forks, 13.3 cm ($5\frac{1}{4}$ in.); | | |
| high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels | N/C | 32.00 |
| long fork stems, $+1.9 \text{ cm} ({}^{3}/_{4} \text{ in.})$, $+3.8 \text{ cm} ({}^{1}/_{2} \text{ in.})$ | N/C N/C | 16.00 |
| Rear axles: | | |
| threaded rear axles | N/C | 33.00 |
| Component(s) under Special Consideration | | |
| contracture footrests, angle-adjustable and multi-directional* | 218.00 | 316.00 |
| spoke guards* | 70.00 | 35.00 |
| reclining back* | 574.00 | N/A |
| quick-release axles* | N/C | 33.00 |

SUPPLIER: ORTHOFAB INC.

PRICE

POSITIONING BASE, ADULT TANGO MODEL

\$1 847.00

Basic Components

Body support system

- seat height: from 35.6 cm (14 in.) to 45.7 cm (18 in.)
- seat widths: 35.6 cm (14 in.), 38.1 cm (15 in.), 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.)
- seat depths: 40.6 cm (16 in.), 43.2 cm (17 in.), 45.7 cm (18 in.), 48.3 cm (19 in.), 50.8 cm (20 in.), 53.3 cm (21 in.), 55.9 cm (22 in.)
- back height: from 40.6 cm (16 in.) to 63.5 cm (25 in.)
- safety belt, auto-type

Armrests

- U-type armrests, detachable, flip-back, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), short, long
- T-type armrests, detachable, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), long
- · armrest pads, straight, short, long
- clothing guards, rigid

Footrests

- 60° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- padded calfrests
- heel loops, adjustable
- · folding footplates, standard

Frame

- · straight front frame
- central propulsion configuration*
- anti-tip rollers
- push handles, integrated, bolt-on, directional
- folding back, angle-adjustable
- · rocker device

Drive, brake, wheel, fork, and axle systems

- · smooth handrims
- standard, push-to-lock
- · foot-activated wheel locks
- spoked rear wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.)
- spoked rear wheels, semi-pneumatic tires, 50.8 cm (20 in.),
 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.), 17.8 cm (7 in.), 15.2 cm (6 in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1¹/₂ in.), 15.2 cm (6 in.) x 3.8 cm (1¹/₂ in.), 12.7 cm (5 in.) x 3.8 cm (1¹/₂ in.)
- · high forks
- threaded axles
- quick-release axles*

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: headrest, hammock-style contoured headrest, nylon rigid seat, flat rigid seat, on elastic webbing headrest mounting, articulated headrest mounting, uniball safety belt, velcro-type safety belt, auto-type safety belt, airplane-type | 75.00 100.00 81.00 103.00 102.00 115.00 27.00 N/C 38.00 | 75.00 100.00 81.00 103.00 102.00 115.00 63.00 36.00 74.00 |
| Armrests: U-type armrests, detachable, flip-back, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), short U-type armrests, detachable, flip-back, height-adjustable from 25.4 cm (10 in.) to 35.6 cm (14 in.), long T-type armrests, detachable, height-adjustable from 25.4 cm (10 to 35.6 cm (14 in.), long armrest pads, straight, long armrest pads, straight, short modification of U-type armrest height to under 25.4 cm (10 in.) clothing guards, rigid | N/C N/C in.) N/C N/C N/C 79.00 N/C | 94.00 120.00 120.00 15.00 12.00 N/A N/A |
| Footrests: 60° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 70° footrests, tapered, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) | N/C N/C 29.00 | 78.00 78.00 N/A |
| 90° footrests, parallel, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) elevating legrests, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) elevating legrests with compensating mechanism modification of footrest or legrest length to +35.6 cm (14 in.) | 86.00 214.00 234.00 | 121.00 185.00 195.00 |
| or to +48.3 cm (19 in.) padded calfrests contoured calfrests double calf strap folding footplates, standard folding footplates, aluminum standard footplates, angle-adjustable and depth-adjustable oversized footplates, angle-adjustable and depth-adjustable full-width footplate, angle-adjustable and depth-adjustable | 79.00 N/C 60.00 55.00 N/C 44.00 76.00 82.00 168.00 | N/A 20.00 50.00 55.00 16.00 38.00 54.00 57.00 200.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| front impact guard with rollers toe loops heel loops, adjustable | 36.00 30.00 N/C | 18.00 15.00 11.00 |
| Frame: | | |
| folding back, angle-adjustable | N/C | N/A |
| anti-tip rollers | N/C | 46.00 |
| straight front frame | N/C | N/A |
| flared frame | 95.00 | N/A |
| cane holder | 40.00 | 40.00 |
| ocker device | N/C | N/A |
| bush handles, integrated | N/C | N/A |
| bush handles, bolt-on, directional | N/C | 99.00 |
| back tension bar with headrest mounting bracket | 99.00 | 99.00 |
| back tension bar | 69.00 | 69.00 |
| Orive systems: | | |
| smooth handrims | N/C | 48.00 |
| non-slip handrims | 88.00 | 92.00 |
| plastic-coated handrims | 58.00 | 77.00 |
| Wheel locks: | | |
| standard wheel locks, push-to-lock | N/C | 53.00 |
| wheel lock extensions, retractable | 40.00 | 20.00 |
| wheel lock extensions, fixed | 40.00 | 20.00 |
| anti-rollback brakes | 86.00 | 43.00 |
| Coot-activated wheel locks | N/C | N/A |
| Wheels: | 72.00 | 112.00 |
| rear mag wheels, solid tires, 30.5 cm (12 in.) | 72.00 N/C | 113.00 77.00 |
| spoked rear wheels, solid tires, 55.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 77.00 |
| spoked rear wheels, semi-pneumatic tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 77.00 |
| Front wheels, solid tires, 20.3 cm (8 in.), 15.2 cm (6 in.), | | |
| 17.8 cm (7 in.) | N/C | 31.00 |
| Front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.), | | |
| $5.2 \text{ cm } (6 \text{ in.}) \text{ x } 3.2 \text{ cm } (1^{1}/_{4} \text{ in.})$ | 34.00 | 48.00 |
| Front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm ($1^{1}/_{2}$ in.) 15.2 cm (6 in.) x 3.8 cm ($1^{1}/_{2}$ in.), 12.7 cm (5 in.) x 3.8 cm ($1^{1}/_{2}$ in.) |), N/C | 48.00 |
| | 14/C | 40.00 |
| F orks: nigh forks | N/C | 55.00 |
| | IV/C | 33.00 |
| Rear axles: | N/C | 5.00 |
| hreaded axles | N/C | 5.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Component(s) under Special Consideration | | |
| central propulsion configuration* | N/C | N/A |
| elevating legrests, assisted, including contoured calfrests* | 234.00 | 195.00 |
| reclining back* | 269.00 | N/A |
| spoke guards* | 114.00 | 57.00 |
| quick-release axles* | N/C | 44.00 |

SUPPLIER: LES ÉQUIPEMENTS ADAPTÉS PHYSIPRO INC.

PRICE

POSITIONING BASE, ADULT X = ACT MODEL

\$1 855.00

Basic Components

Body support system

- seat width: from 38.1 cm (15 in.) to 50.8 cm (20 in.)
- seat depth: from 40.6 cm (16 in.) to 55.9 cm (22 in.)
- seat height: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- back height: from 50.8 cm (20 in.) to 61.0 cm (24 in.)
- safety belt, auto-type

Armrests

- T-type armrests, height-adjustable from 20.3 cm (8 in.) to 35.6 cm (14 in.), short, long
- armrest pads, straight, short, long
- · clothing guards, rigid

Footrests

- 60°, 70° or 75° footrests, parallel, detachable, swingaway, length-adjustable from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- padded calfrests for elevating legrests
- folding footplates, standard
- · heel loops, adjustable

Frame

- rocker device, from -5° to + 35°
- folding back, angle-adjustable
- push handles, integrated
- anti-tip rollers
- tie-down points for transport
- push handle extension

- · standard, push-to-lock
- foot-activated wheel locks
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 40.6 cm (16 in.)
- rear mag wheels, solid tires, 30.5 cm (12 in.), 40.6 cm (16 in.)
- rear mag wheels, semi-pneumatic tires, 30.5 cm (12 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.)

- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.) x 2.5 cm (1 in.)
- standard forks
- threaded rear axles

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: safety belt, auto-type | N/C | 51.00 |
| Armrests: T-type armrests, height-adjustable from 20.3 cm (8 in.) to 35.6 cm (14 in.), short, long armrest pads, straight, short armrest pads, straight, long clothing guards, rigid | N/C N/C N/C N/C | 196.00 28.00 30.00 16.00 |
| Footrests: 60°, 70° or 75° footrests, parallel, detachable, swingaway, length-adjustable from 30.5 cm (12 in.) to 45.7 cm (18 in.) 90° footrests, parallel, detachable, swingaway, length-adjustable from 30.5 cm (12 in.) to 45.7 cm (18 in.) elevating legrests padded calfrests for elevating legrests contoured calfrests single calf strap double calf strap H-shaped calf strap heel loops, adjustable folding footplates, standard toe loops full-width footplate footplates, angle-adjustable and depth-adjustable, standard size footplates, angle-adjustable and depth-adjustable, oversized front impact guard with rollers | N/C 62.00 394.00 N/C 36.00 45.00 58.00 47.00 N/C N/C 20.00 148.00 74.00 106.00 84.00 | 105.00 136.00 302.00 32.00 50.00 45.00 58.00 47.00 14.00 42.00 24.00 116.00 79.00 95.00 42.00 |
| Frame: tension bar with headrest mounting bracket push handles, integrated push handle extension tie-down points for transport growth kit, side rails for depth anti-tip rollers folding back, angle-adjustable rocker device, from – 5° to + 35° | 124.00 N/C N/C N/C N/A N/C N/C N/C | 124.00 N/A 228.00 35.00 156.00 45.00 N/A N/A |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| Wheel locks: | | |
| standard wheel locks, push-to-lock | N/C | 58.00 |
| wheel lock extension | 36.00 | 18.00 |
| Coot-activated wheel locks | N/C | 158.00 |
| Wheels: | | |
| rear mag wheels, standard pressure, 30.5 cm (12 in.), 40.6 cm (16 in.) | n.) N/C | 102.00 |
| ear mag wheels, solid tires, 30.5 cm (12 in.), 40.6 cm (16 in.) | N/C | 102.00 |
| ear mag wheels, semi-pneumatic tires, 30.5 cm (12 in.) | N/C | 102.00 |
| ront wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 56.00 | 68.00 |
| Front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.), 15.2 cm (6 in.) x 3.2 cm ($1^{1}/_{4}$ in.) | 36.00 | 58.00 |
| Front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), | 30.00 | 36.00 |
| 5.2 cm (6 in.) | N/C | 40.00 |
| front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 2.5 cm (1 in.), | | 40.00 |
| 20.3 cm (8 in.) x 2.5 cm (1 in.) | N/C | 40.00 |
| Front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 56.00 | 68.00 |
| • | 20.00 | 00.00 |
| Forks: orks compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) front wheels | 22.00 | 70.00 |
| standard forks | N/C | 59.00 |
| | | |
| Rear axles: | NIC | 7.00 |
| hreaded rear axles | N/C | 7.00 |
| Component(s) under Special Consideration | | |
| uick-release rear axles* | 78.00 | 46.00 |
| eavy-duty frame* | 280.00 | N/A |
| eclining back* | 295.00 | 295.00 |
| SUPPLIER: PRODUCT DESIGN GROUP INC. | | |
| | | PR |

PRICE

POSITIONING BASE, ADULT STELLAR MODEL

\$1 760.00

Basic Components

Body support system

- seat widths: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- seat depth: from 40.6 cm (16 in.) to 50.8 cm (20 in.)
- seat height: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- back height: from 50.8 cm (20 in.) to 78.7 cm (31 in.)
- safety belt, auto-type
- · rocker device

Armrests

- U-type armrests, height-adjustable, short, long
- I-type armrests, short, long

- · armrest pads, straight, short, long
- clothing guards, rigid

Footrests

- 70° footrests, fixed, parallel, plug-in, detachable,
- 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.)
- 60° footrests, inward-pointing, detachable, swingaway
- · padded calfrests
- folding footplates, standard
- · heel loops, adjustable

Frame

- heavy-duty frame, 350 lb. maximum*
- back angle-adjustable from 90° to 120°
- back tension bar
- double gas strut, chair width from 58.4 cm (23 in.) to 81.3 cm (32 in.)
- · anti-tip rollers

- smooth handrims
- standard, push-to-lock, pull-to-lock
- rear mag wheels, solid tires, 30.5 cm (12 in.), 40.6 cm (16 in.), 50.8 cm (20 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.), 15.2 cm (6 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 2.5 cm (1 in.)
- · standard forks
- · threaded axles
- quick-release axles*

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| rigid seat, flat | 47.00 | 47.00 |
| headrest and mounting, 25.4 cm (10 in.) pad, 35.6 cm (14 in.) pad, | | |
| double articulated (depth and height) | 181.00 | 181.00 |
| headrest mounting plate | 16.00 | 16.00 |
| back extension, 25.4 cm (10 in.) | 93.00 | 93.00 |
| modification of seat width from 68.6 cm (27 in.) to 81.3 cm (32 in.) | | N/A |
| modification of seat width from 58.4 cm (23 in.) to 66.0 cm (26 in.) | | N/A |
| modification of seat width to 53.3 cm (21 in.) or to 55.9 cm (22 in.) | 78.00 | N/A |
| modification of seat depth to 53.3 cm (21 in.) or to 55.9 cm (22 in.) | 78.00 | 78.00 |
| safety belt, auto-type | N/C | 20.00 |
| Armrests: | | |
| U-type armrests, height-adjustable, short, long | N/C | 85.00 |
| I-type armrests, short, long | N/C | 85.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| armrest tube extension, 7.6 cm (3 in.) | 40.00 | 20.00 |
| modification of armrest height from 20.3 cm (8 in.) to | 45.00 | 00.00 |
| 25.4 cm (10 in.) or from 30.5 cm (12 in.) to 40.6 cm (16 in.) | 15.00 | 90.00 |
| armrest pads, straight, short, long | N/C N/C | 12.00 |
| clothing guards, rigid | N/C | 31.00 |
| Footrests: | | |
| 60° or 70° footrests, parallel, detachable, swingaway, | | |
| ength-adjustable from 35.6 cm (14 in.) to 48.3 cm (19 in.) | N/C | 95.00 |
| 50° footrests, inward-pointing, detachable, swingaway | N/C | 105.00 |
| '0° footrests, inward-pointing, detachable, swingaway | 30.00 | 110.00 |
| '0° footrests, fixed, plug-in, detachable, parallel | N/C | 93.00 |
| ixed footrests, plug-in, detachable, parallel, angle-adjustable | | |
| t knees | 128.00 | 157.00 |
| elevating legrests | 260.00 | 223.00 |
| levating legrests with compensating mechanism | 350.00 | 268.00 |
| added calfrests | N/C | 33.00 |
| ingle calf strap | 30.00 | 30.00 |
| olding footplates, standard | N/C | 19.00 |
| ull-width footplate | 216.00 | 254.00 |
| oversized footplates | 68.00 | 53.00 |
| ootplates, angle-adjustable and depth-adjustable, oversized | 72.00 | 55.00 |
| neel loops, adjustable | N/C | 34.00 |
| Frame: | | |
| anti-tip rollers | N/C | 47.00 |
| ocker device | N/C | 97.00 |
| ocker device activated by the user and the attendant | 62.00 | 62.00 |
| extension to allow user to control tilt/uplift | 30.00 | 30.00 |
| eack, angle-adjustable from 90° to 120° | N/C | N/A |
| ack tension bar, standard | N/C | N/A |
| growth kit, 5.1 cm (2 in.) increase in width | N/A | 47.00 |
| louble gas strut for user-activated tilt | 186.00 | 186.00 |
| louble gas strut for seat widths of 58.4 cm (23 in.) to 81.3 cm (32 i | n.) N/C | 186.00 |
| Orive systems: | | |
| smooth handrims | N/C | 23.00 |
| plastic-coated handrims | 80.00 | 63.00 |
| andrims with vertical projections | 355.00 | 202.00 |
| Wheel locks: | | |
| standard wheel locks, push-to-lock, pull-to-lock | N/C | 33.00 |
| wheel lock extensions | 38.00 | 19.00 |
| Wheels: ear mag wheels, standard pressure, 30.5 cm (12 in.), 40.6 cm (16 in.) | n.) 68.00 | 135.00 |
| ear mag wheels, solid tires, 30.5 cm (12 in.), 40.6 cm (16 in.), | 371- | |
| 0.8 cm (20 in.), 61.0 cm (24 in.) | N/C | 101.00 |
| Front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.) | N/C | 97.00 |

| or replacement of wheel chair (price per pair, as applicable) | of component (unit price) |
|--|--|
| N/C | 97.00 |
| 48.00 | 105.00 |
| N/C | 97.00 |
| 62.00 | 112.00 |
| N/C | 35.00 |
| N/C | 37.00 |
| | |
| 713.00 | 713.00 |
| N/C | N/A |
| N/C | 45.00 |
| | (price per pair, as applicable) N/C 48.00 N/C 62.00 N/C N/C 713.00 N/C |

SUPPLIER: INVACARE CANADA INC.

PRICE

POSITIONING BASE, CHILD SPREE XT MODEL

\$1 694.00

Basic Components

Body support system

- seat height: from 39.4 cm $(15^{1}/_{2} \text{ in.})$ to 48.3 cm (19 in.)
- seat width: from 25.4 cm (10 in.) to 40.6 cm (16 in.)
- seat depth: from 30.5 cm (12 in.) to 45.7 cm (18 in.)
- back heights: 50.8 cm (20 in.), 61.0 cm (24 in.)
- safety belt, auto-type, velcro-type

Armrests

- T-type armrests, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.) or from 25.4 cm (10 in.) to 40.6 cm (16 in.), short, long
- I-type armrests, height-adjustable from 15.2 cm (6 in.) to 22.9 cm (9 in.) or from 22.9 cm (9 in.) to 30.5 cm (12 in.), short, long
- · armrest pads, straight, short, long
- · clothing guards, rigid

Footrests

- 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 44.5 cm (17¹/₂ in.)
- 70° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13¹/₂ in.) to 41.9 cm (16¹/₂ in.)
- 90° footrests, parallel, detachable, swingaway, length-adjustable from 11.4 cm (4¹/₂ in.) to 19.1 cm (7¹/₂ in.)
- 60° footrests, MFX, detachable, swingaway, length-adjustable from 22.9 cm (9 in.) to 31.8 cm (12¹/₂ in.)
- 70° footrests, MFX, detachable, swingaway, length-adjustable from 14.6 cm (5³/₄ in.) to 29.8 cm (11³/₄ in.)

- padded calfrests
- heel loops, non-adjustable
- heel loops, adjustable
- · folding footplates, standard

Frame

- anti-tip rollers
- tie-down points for transport
- · rocker device
- push handles, integrated
- folding back, angle-adjustable

- smooth handrims
- standard, push-to-lock
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, with airless inserts, 30.5 cm (12 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 15.2 cm (6 in.), 12.7 cm (5 in.)
- front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.), 10.2 cm (4 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.) x 2.5 cm (1 in.)
- · standard forks
- quick-release axles*
- · threaded axles

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: safety belt, auto-type safety belt, velcro-type | N/C N/C | 53.00 42.00 |
| Armrests: T-type armrests, height-adjustable from 20.3 cm (8 in.) to 30.5 cm (12 in.) or from 25.4 cm (10 in.) to 40.6 cm (16 in.), short, long I-type armrests, height-adjustable from 15.2 cm (6 in.) to 22.9 cm (9 in.) or from 22.9 cm (9 in.) to 30.5 cm (12 in.), short, long armrest pads, straight, long | N/C N/C N/C | 131.00 101.00 26.00 |
| armrest pads, straight, long armrest pads, straight, short clothing guards, rigid | N/C N/C N/C | 26.00 26.00 46.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| Footrests: | | |
| 60° footrests, parallel, detachable, swingaway, length-adjustable from 34.3 cm (13 ¹ / ₂ in.) to 44.5 cm (17 ¹ / ₂ in.) 70° footrests, parallel, detachable, swingaway, length-adjustable | N/C | 114.00 |
| from 34.3 cm (13 ¹ / ₂ in.) to 41.9 cm (16 ¹ / ₂ in.) 90° footrests, parallel, detachable, swingaway, length-adjustable | N/C | 114.00 |
| from 11.4 cm ($4^{1}/_{2}$ in.) to 19.1 cm ($7^{1}/_{2}$ in.) 60° footrests, MFX, detachable, swingaway, length-adjustable | N/C | 170.00 |
| from 22.9 cm (9 in.) to 31.8 cm (12 ¹ / ₂ in.) 70° footrests, MFX, detachable, swingaway, length-adjustable | N/C | 170.00 |
| from 14.6 cm ($5^3/_4$ in.) to 29.8 cm ($11^3/_4$ in.) 70° footrests, tapered, detachable, swingaway, length-adjustable | N/C | 170.00 |
| from 32.4 cm (12^{3} / ₄ in.) to 41.3 cm (16^{1} / ₄ in.) | 113.00 | 170.00 |
| elevating legrests from 35.6 cm (14 in.) to 50.8 cm (20 in.) modification of elevating legrest length by -2.5 cm (1 in.) or | 244.00 | 236.00 |
| by -5.1 cm (2 in.) | 250.00 | 250.00 |
| padded calfrests | N/C | 28.00 |
| single calf strap | 25.00 | 37.00 |
| double calf strap | 38.00 | 55.00 |
| | N/C | 7.00 |
| heel loops, non-adjustable | | |
| heel loops, adjustable | N/C | 15.00 |
| folding footplates, standard folding footplates, angle-adjustable and depth-adjustable | N/C 76.00 | 42.00 80.00 |
| Frame: | N/G | 50.00 |
| anti-tip rollers | N/C | 50.00 |
| back tension bar | 60.00 | 60.00 |
| push handles, integrated | N/C | 52.00 |
| folding back, angle-adjustable | N/C | N/A |
| tie-down points for transport | N/C | N/A |
| rocker device | N/C | N/A |
| Drive systems: smooth handrims | N/C | 36.00 |
| plastic-coated handrims | 54.00 | 63.00 |
| handrims with vertical or oblique projections | 155.00 | 125.00 |
| Wheel locks: | NG | 46.00 |
| standard wheel locks, push-to-lock | N/C | 46.00 |
| wheel lock extensions | 34.00 | 34.00 |
| anti-rollback brakes | 94.00 | 93.00 |
| Wheels: rear mag wheels, standard pressure, 30.5 cm (12 in.) rear mag wheels, standard pressure, 50.8 cm (20 in.), | N/C | 75.00 |
| 55.9 cm (22 in.), 61.0 cm (24 in.) | N/C | 105.00 |
| rear mag wheels, solid tires, with airless inserts, 30.5 cm (12 in.) rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), | N/C | 95.00 |
| 61.0 cm (24 in.) | N/C | 105.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| front wheels, solid tires, 20.3 cm (8 in.) x 3.2 cm (1 ¹ / ₄ in.), | | |
| 15.2 cm (6 in.), 12.7 cm (5 in.) | N/C | 40.00 |
| front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm ($1^{1}/_{4}$ in.) | 31.00 | 55.00 |
| front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 3.2 cm (1 ¹ / ₄ in. | | 55.00 |
| front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 5.1 cm (2 in.) front wheels, semi-pneumatic tires, 10.2 cm (4 in.) x 2.5 cm (1 in.), | N/C | 50.00 |
| 12.7 cm (5 in.) x 2.5 cm (1 in.) | N/C | 42.00 |
| Forks: standard forks | N/C | 52.00 |
| Rear axles: threaded axles | N/C | 15.00 |
| Component(s) under Special Consideration quick-release axles* | N/C | 53.00 |
| SUPPLIER: SUNRISE MEDICAL CANADA INC. | | PRIC |
| POSITIONING BASE, CHILD ZIPPIE TS MODEL | | \$1 715. |

Basic Components

Body support system

- back heights: 54.6 cm (21¹/₂ in.), 62.2 cm (24¹/₂ in.), 69.9 cm (27¹/₂ in.), with push handles
- seat width: from 25.4 cm (10 in.) to 40.6 cm (16 in.)
- seat depth: from 33.0 cm (13 in.) to 50.8 cm (20 in.)
- front seat height: from 40.6 cm (16 in.) to $51.4 \text{ cm} (20^{1}/_{4} \text{ in.})$
- safety belt, velcro-type, auto-type

Armrests

- T-type armrests, detachable, height-adjustable from 17.1 cm (6³/₄ in.) to 37.5 cm (14 in.), short, long
- T-type armrests, detachable, height-adjustable, 14.0 cm (5¹/₂ in.), 16.5 cm (6¹/₂ in.), 19.1 cm (7¹/₂ in.), short
- I-type armrests, locking, depth-adjustable, height-adjustable from 16.5 cm (6½ in.) to 33.0 cm (13 in.), short,
- · armrest pads, straight, short, long
- · armrest pads, tubular
- clothing guards, flexible

Footrests

- 60° or 70° footrests, parallel, detachable, swingaway, length-adjustable from 31.1 cm (12¹/₄ in.) to 48.9 cm (19¹/₄ in.)
- 70°, 80° or 90° footrests, parallel, detachable, swingaway, length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.)
- 70°, 80° or 90° footrests, heavy-duty, detachable, non-flip-back

- heel loops, adjustable
- · folding footplates, standard
- padded calfrests for elevating legrests

Frame

- · anti-tip rollers
- rocker device
- · folding back, angle-adjustable
- back tension bar
- push handle extension

- smooth handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- standard, push-to-lock, pull-to-lock
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- rear mag wheels, solid tires, 30.5 cm (12 in.), 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 12.7 cm (5 in.), 15.2 cm (6 in.)
- front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm (1¹/₄ in.), 15.2 cm (6 in.) x 3.2 cm (1¹/₄ in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1¹/₂ in.), 15.2 cm (6 in.) x 3.8 cm (1¹/₂ in.), 12.7 cm (5 in.) x 3.8 cm (1¹/₂ in.)
- standard forks, 15.2 cm (6 in.); short forks, 13.3 cm (5¹/₄ in.), high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels
- forks, 17.8 cm (7 in.) compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels
- long fork stems, $+ 1.9 \text{ cm} (\frac{3}{4} \text{ in.}), + 3.8 \text{ cm} (\frac{1}{2} \text{ in.})$
- quick-release axles*
- standard axle plates

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | | |
| headrest, small, medium, large | 99.00 | 106.00 |
| headrest mounting, articulated | 159.00 | 173.00 |
| rigid seat, flat | 125.00 | 130.00 |
| safety belt, velcro-type | N/C | 29.00 |
| safety belt, auto-type | N/C | 42.00 |
| safety belt, airplane-type | 50.00 | 79.00 |
| safety belt, airplane-type, padded | 76.00 | 105.00 |
| Armrests: | | |
| T-type armrests, detachable, height-adjustable from 17.1 cm (6 ³ / ₄ in to 37.5 cm (14 in.), short, long | n.) N/C | 135.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|---|---|
| T-type armrests, detachable, height-adjustable, 14.0 cm (5 ¹ / ₂ in.), | | |
| 16.5 cm ($6^{1}/_{2}$ in.), 19.1 cm ($7^{1}/_{2}$ in.), short I-type armrests, locking, depth-adjustable, height-adjustable | N/C | 160.00 |
| from 16.5 cm ($6^{1}/_{2}$ in.) to 33.0 cm (13 in.), short | N/C | 200.00 |
| armrest pads, tubular | N/C | 2.00 |
| armrest pads, straight, long | N/C | 18.00 |
| armrest pads, straight, short | N/C | 15.00 |
| clothing guards, rigid | 92.00 | 68.00 |
| clothing guards, flexible | N/C | 22.00 |
| Footrests: | | |
| 60° or 70° footrests, parallel, detachable, swingaway, | | |
| length-adjustable from 31.1 cm (12 ¹ / ₄ in.) to 48.9 cm (19 ¹ / ₄ in.) 70°, 80° or 90° footrests, parallel, detachable, swingaway, | N/C | 55.00 |
| length-adjustable from 20.3 cm (8 in.) to 33.0 cm (13 in.) | N/C | 57.00 |
| 70°, 80° or 90° footrests, heavy-duty, detachable, non-flip-back 90° elevating legrests, length-adjustable from 20.3 cm (8 in.) | N/C | 87.00 |
| to 33.0 cm (13 in.) | 70.00 | 90.00 |
| elevating legrests | 108.00 | 109.00 |
| elevating legrests with compensating mechanism | 200.00 | 155.00 |
| | 200.00 N/C | 19.00 |
| padded calfrests for elevating legrests | 72.00 | 55.00 |
| contoured calfrests for elevating legrests modification of footrest length by 5.1 cm (2 in.) or by 10.2 cm (4 in. | | 16.00 |
| folding footplates, standard | N/C | 49.00 |
| | 54.00 | 76.00 |
| folding, footplates, angle-adjustable and depth-adjustable | 85.00 | 183.00 |
| full-width footplate, angle-adjustable | 92.00 | 190.00 |
| 90° full-width foot platform bracket, footrest mounting, from 17.8 cm (7 in.) to 34.3 cm (13½ in. | | |
| | | 34.00 |
| single calf strap heel loops, adjustable | 19.00 N/C | 19.00 10.00 |
| Frame: | | |
| back tension bar | N/C | 191.00 |
| rocker device | N/C | N/A |
| anti-tip rollers | N/C | 22.00 |
| Front anti-tippers | 58.00 | 29.00 |
| cane holder | 45.00 | 45.00 |
| optional folding base | 108.00 | N/A |
| olding back, angle-adjustable | N/C | N/A |
| bush handle extension | N/C | 69.00 |
| crossbar for headrest mounting, fixed frame | 200.00 | 212.00 |
| crossbar for headrest mounting, folding frame | 233.00 | 249.00 |
| Drive systems: | | |
| one-arm dual handrim drive | 562.00 | 709.00 |
| smooth handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) | | 60.00 |
| nandrims with oblique or vertical projections, 61.0 cm (24 in.) plastic-coated handrims, 50.8 cm (20 in.), 55.9 cm (22 in.), | 90.00 | 105.00 |
| product control management, 2000 cm (20 mi.), 22.7 cm (22 mi.), | 56.00 | 88.00 |

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|---|--|--|
| non-slip handrims, 55.9 cm (22 in.), 61.0 cm (24 in.) small plastic-coated handrim for one-arm drive | 168.00 56.00 | 144.00 97.00 |
| Wheel locks: standard wheel locks, push-to-lock, pull-to-lock wheel lock extensions anti-rollback brakes | N/C 26.00 68.00 | 40.00 13.00 34.00 |
| Wheels: rear mag wheels, standard pressure, 30.5 cm (12 in.) rear mag wheels, standard pressure, 40.6 cm (16 in.) rear mag wheels, standard pressure, 50.8 cm (20 in.) rear mag wheels, standard pressure, 55.9 cm (22 in.), 61.0 cm (24 i rear mag wheels, solid tires, 30.5 cm (12 in.) rear mag wheels, solid tires, 50.8 cm (20 in.), 55.9 cm (22 in.), 61.0 cm (24 in.) front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.) front wheels, solid tires, 15.2 cm (6 in.) front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm (1 $\frac{1}{4}$ in.) front wheels, semi-pneumatic tires, 12.7 cm (5 in.) x 3.8 cm (1 $\frac{1}{2}$ in.) front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1 $\frac{1}{2}$ in.) front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 3.8 cm (1 $\frac{1}{2}$ in.) | N/C N/C N/C N/C N/C N/C 48.00 N/C N/C N/C N/C N/C N/C | 130.00 146.00 136.00 113.00 145.00 136.00 63.00 62.00 47.00 72.00 63.00 62.00 |
| Forks: standard forks, 15.2 cm (6 in.); short forks, 13.3 cm ($5^{1}/_{4}$ in.); high forks, 17.8 cm (7 in.); compatible with 12.7 cm (5 in.), 15.2 cm (6 in.) and 20.3 cm (8 in.) wheels forks, 17.8 cm (7 in.), compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) wheels fork-locking mechanism long fork stems, + 1.9 cm ($3^{1}/_{4}$ in.), + 3.8 cm ($1^{1}/_{2}$ in.) | N/C N/C 46.00 N/C | 32.00 37.00 23.00 16.00 |
| Rear axles: axle extension plates standard axle plates | 46.00 N/C | 52.00 29.00 |
| Component(s) under Special Consideration quick-release axles* | N/C | 33.00 |

SUPPLIER: LES ÉQUIPEMENTS ADAPTÉS PHYSIPRO INC.

PRICE

POSITIONING BASE, CHILD TWIGY MODEL

\$1 668.00

Basic Components

Body support system

- seat width: from 25.4 cm (10 in.) to 40.6 cm (16 in.)
- seat depth: from 30.5 cm (12 in.) to 40.6 cm (16 in.)
- seat height: from 35.6 cm (14 in.) to 50.8 cm (20 in.)
- back height: from 43.2 cm (17 in.) to 55.9 cm (22 in.)
- · safety belt, auto-type

Armrests

- T-type armrests, height-adjustable from 17.8 cm (7 in.) to 35.6 cm (14 in.), short, long
- · armrest pads, straight, short, long
- · clothing guards, rigid

Footrests

- 60°, 70°, 75° or 90° footrests, parallel, detachable, swingaway, length-adjustable from 17.8 cm (7 in.) to 33.0 cm (13 in.)
- · folding footplates, standard
- heel loops, adjustable
- · padded calfrests for elevating legrests

Frame

- rocker device, from -5° to + 35°
- folding back, angle-adjustable
- push handles, integrated
- tie-down points for transport
- anti-tip rollers
- push handle extension

- standard, push-to-lock
- · foot-activated wheel locks
- rear mag wheels, standard pressure, 30.5 cm (12 in.), 40.6 cm (16 in.)
- rear mag wheels, solid tires, 30.5 cm (12 in.), 40.6 cm (16 in.)
- rear mag wheels, semi-pneumatic tires, 30.5 cm (12 in.)
- front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.)
- front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), 15.2 cm (6 in.) x 2.5 cm (1 in.)
- standard forks
- · threaded rear axles

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|---|---|
| | | |
| Basic and Optional Components | | |
| Body support system | | |
| Seat and back: | NIC | 51.00 |
| safety belt, auto-type | N/C | 51.00 |
| Armrests: | | |
| T-type armrests, height-adjustable from 17.8 cm (7 in.) to | | |
| 35.6 cm (14 in.), short, long | N/C | 196.00 |
| armrest pads, straight, short | N/C | 28.00 |
| armrest pads, straight, long | N/C N/C | 30.00 |
| clothing guards, rigid | N/C | 16.00 |
| Footrests: | | |
| 60°, 70°, 75° or 90° footrests, parallel, detachable, swingaway, | | |
| length-adjustable from 17.8 cm (7 in.) to 33.0 cm (13 in.) | N/C | 105.00 |
| elevating legrests | 394.00 | 302.00 |
| padded calfrests for elevating legrests | N/C | 32.00 |
| contoured calfrests | 36.00 | 50.00 |
| single calf strap | 45.00 | 45.00 |
| double calf strap | 58.00 | 58.00 |
| H-shaped calf strap | 47.00 | 47.00 |
| heel loops, adjustable | N/C | 14.00 |
| folding footplates, standard size | N/C | 42.00 |
| toe loops full-width footplate | 20.00 148.00 | 24.00 116.00 |
| footplates, angle-adjustable and depth-adjustable, standard size | 74.00 | 79.00 |
| footplates, angle-adjustable and depth-adjustable, standard size | 106.00 | 95.00 |
| front impact guard with rollers | 84.00 | 42.00 |
| Holt impact guard with foliors | 01.00 | 12.00 |
| Frame: | | |
| growth kit, side rails for frame depth and inside crossbars | | |
| for frame width | N/A | 156.00 |
| tension bar with headrest mounting bracket | 124.00 | 124.00 |
| anti-tip rollers | N/C | 45.00 |
| push handles, integrated | N/C | 145.00 |
| push handle extension | N/C | 228.00 |
| tie-down points for transport rocker device, from-5° to + 35° | N/C N/C | 35.00 N/A |
| folding back, angle-adjustable | N/C N/C | N/A |
| | 140 | 11/11 |
| Wheel locks: | | |
| standard wheel locks, push-to-lock | N/C | 58.00 |
| wheel lock extension | 36.00 | 18.00 |
| foot-activated wheel locks | N/C | 158.00 |
| | | |

6823

| | Price upon initial purchase or replacement of wheel chair (price per pair, as applicable) | Price upon replacement of component (unit price) |
|--|--|---|
| Wheels: | | |
| rear mag wheels, standard pressure, 30.5 cm (12 in.), | | |
| 40.6 cm (16 in.) | N/C | 102.00 |
| rear mag wheels, solid tires, 30.5 cm (12 in.), 40.6 cm (16 in.) | N/C | 102.00 |
| rear mag wheels, semi-pneumatic tires, 30.5 cm (12 in.) | N/C | 102.00 |
| front wheels, inner tube tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) front wheels, inner tube tires, 20.3 cm (8 in.) x 3.2 cm ($1\frac{1}{4}$ in.), | 56.00 | 68.00 |
| 15.2 cm (6 in.) x 3.2 cm ($1^{1}/_{4}$ in.) front wheels, solid tires, 20.3 cm (8 in.) x 2.5 cm (1 in.), | 36.00 | 58.00 |
| 15.2 cm (6 in.) front wheels, semi-pneumatic tires, 15.2 cm (6 in.) x 2.5 cm (1 in.). | N/C | 40.00 |
| 20.3 cm (8 in.) x 2.5 cm (1 in.) | N/C | 40.00 |
| front wheels, semi-pneumatic tires, 20.3 cm (8 in.) x 5.1 cm (2 in.) | 56.00 | 68.00 |
| Forks: | 22.00 | 70.00 |
| forks compatible with 20.3 cm (8 in.) x 5.1 cm (2 in.) front wheels standard forks | 22.00 N/C | 70.00 59.00 |
| Rear axles: | | |
| threaded rear axles | N/C | 7.00 |
| Component(s) under Special Consideration | | |
| quick-release rear axles* | 78.00 | 46.00 |
| reclining back* | 295.00 | 295.00 |
| heavy-duty frame* | 280.00 | N/A |
| DIVISION III STROLLERS | | |
| DEVICE | | PRICE |
| Buggy Major-type stroller, including footrests and harness | | |
| less than three years of age* three years of age and over | | 600.00 600.00 |
| Available Component(s) | | |
| modded coet | | 00.00 |
| padded seat other components | | 90.00 S.C. |
| thoracic support | | 96.00 |
| chest pad | | 48.00 |
| DURATION OF GUARANTEE: 12 months | | |
| DEVICE | | |
| Other strollers* | | S.C. |
| | | |