

## Draft Regulations

---

### Draft Regulation

Environment Quality Act  
(c. Q-2)

#### Mandatory reporting of certain emissions of contaminants into the atmosphere

##### — Amendment

Notice is hereby given, in accordance with sections 10 and 12 of the Regulations Act (R.S.Q., c. R-18.1) and sections 2.2 and 46.2 of the Environment Quality Act (R.S.Q., c. Q-2), that the “Regulation to amend the Regulation respecting mandatory reporting of certain emissions of contaminants into the atmosphere” the text of which appears below, may be made by the Minister of Sustainable Development, Environment, Wildlife and Parks on the expiry of 45 days from this publication.

The draft regulation includes a number of amendments to specify the information that must be provided in connection with emissions of contaminants, including greenhouse gases.

With regard to the verification of greenhouse gas emissions reports, the draft regulation sets requirements concerning conflicts of interest between emitters, their directors and the members of the verification team.

Based on new provisions in the Environment Quality Act, the draft regulation sets monetary administrative penalties and adjusts the applicable penal penalties.

Last, the draft regulation introduces amendments to the existing protocols governing the calculation of greenhouse gas emissions, and adds new protocols concerning titanium dioxide production, titanium slag and iron production from ilmenite reduction, oil and natural gas exploration and production and natural gas processing, and metal powder production.

Under section 13 of the Regulations Act, the draft regulation may be made at the expiry of a shorter period than the 60-day period prescribed by sections 2.2 and 46.2 of the Environment Quality Act because of the urgency of the situation, specifically that

— the amendments made by the draft regulation, in particular concerning methods for the calculation of greenhouse gas emissions, must be applicable from 1 January 2013 to ensure that the emissions of contaminants for the year 2013 are reported in compliance with the new requirements.

Further information may be obtained from Vicky Leblond, Direction des politiques de la qualité de l’atmosphère, Ministère du Développement durable, de l’Environnement, de la Faune et des Parcs; telephone: 418 521-3813, extension 4386; E-mail: vicky.leblond@mddep.gouv.qc.ca; fax: 418 646-0001.

Any person wishing to comment on the draft regulation may submit written comments to Daniel Champagne, interim director, Direction des politiques de la qualité de l’atmosphère, Ministère du Développement durable, de l’Environnement, de la Faune et des Parcs, Édifice Marie-Guyart, 675, Boulevard René-Lévesque Est, 5<sup>e</sup> étage, Boîte 30, Québec (Québec) G1R 5V7; E-mail: daniel.champagne@mddep.gouv.qc.ca, before the end of the 45-day period.

DANIEL BRETON,  
*Minister of Sustainable Development, Environment,  
Wildlife and Parks*

---

## REGULATION TO AMEND THE REGULATION RESPECTING MANDATORY REPORTING OF CERTAIN EMISSIONS OF CONTAMINANTS INTO THE ATMOSPHERE

Environment Quality Act

(R.S.Q., c. Q-2, ss. 2.2, 46.2, 115.27 and 115.34)

1. The Regulation respecting mandatory reporting of certain emissions of contaminants into the atmosphere (R.R.Q., c. Q-2, r. 15) is amended by adding the following paragraph at the end of section 3:

“Last, for the application of this Regulation to a closed landfill site, a person or municipality is considered to operate the site until such time as it is released from its environmental monitoring and maintenance obligations under section 85 of the Regulation respecting the landfilling and incineration of residual materials (c. Q-2, r. 19).”.

2. Section 4 is amended

(1) by inserting “reaches or” after “quantity that”;

(2) by inserting “, using the form available on-line on the website of the Ministère du Développement durable, de l'Environnement, de la Faune et des Parcs,” after “electronic means” in the first paragraph;

(3) by adding “along with their source and, if they originate in published documents, the applicable reference” at the end of the second paragraph;

(4) by striking out the third paragraph;

(5) by inserting “the emissions attributable to them,” after “for each of them,” in the fifth paragraph.

3. Section 5 is amended

(1) by replacing the first paragraph by the following paragraph:

“5. If the operator of the facility or establishment is required, under a public notice given pursuant to section 46 of the Canadian Environmental Protection Act (1999) (S.C. 1999, c. 33), to report to the Minister of the Environment of Canada, the operator must, not later than 1 June each year, transmit to the Minister by electronic means, using the form available on-line on the website of the Ministère du Développement durable, de l'Environnement, de la Faune et des Parcs, the quantity of each contaminant listed in Part II of Schedule A that the facility or establishment emitted into the atmosphere in the preceding calendar year.”;

- (2) in the second paragraph,
  - (a) by inserting “, their source and, if they originate in published documents, the applicable reference” after “used for the calculation” in the second paragraph;
  - (b) by striking out “That information must be provided in the form in Parts I and III of Schedule B.”;
- (3) by striking out the third paragraph.

**4.** The following sections are inserted after section 5:

**“5.1.** The operator referred to in section 4 or 5 must include the following information with the information referred to in those sections:

(1) the name of and contact information for the enterprise, facility or establishment as well as the name of and contact information for its representative;

(2) the business number assigned to the operator when registered under the Act respecting the legal publicity of enterprises (R.S.Q., c. P-44.1) as well as the ID number assigned under the National Pollutant Release Inventory of the Government of Canada;

(3) the type of enterprise, facility or establishment operated, the activities pursued and processes and equipment used as well as, where applicable, the 6-digit code under the North American Industry Classification System (NAICS Canada);

(4) the name of and contact information for the person responsible for the contaminants emissions report for the enterprise, facility or establishment.

**5.2.** When the emissions of contaminants from an establishment reported in accordance with section 4 or 5 fall below the reporting threshold the following year, the operator of the establishment must, not later than 1 June following the first year in which the emissions are below the threshold, send a notice to the Minister including the following information and documents:

- (1) the information referred to in section 5.1;
- (2) an attestation that the emissions of contaminants referred to in Schedule A are below the reporting threshold;

(3) the reason for the reduction in emissions of contaminants;

(4) the signature of the person responsible for the declaration at the establishment.”.

**5.** Section 6 is amended

(1) by replacing “emission factor” in subparagraph 4 of the first paragraph by “emission rate“;

(2) by replacing the third paragraph by the following paragraphs:

“In addition, unless otherwise indicated, the data required under this Regulation must be in metric units.

An emissions report made under section 4 or 5 must be signed by the person responsible for the report at the enterprise, facility or establishment, who must also attest to the veracity of the information communicated.”.

**6.** Section 6.2 is amended

(1) by replacing “electronically to the Minister” in the part of the first paragraph preceding subparagraph 1 by “to the Minister by electronic means, using the form available on-line on the website of the Ministère du Développement durable, de l’Environnement, de la Faune et des Parcs,”;

(2) by replacing the part of subparagraph 1 of the first paragraph preceding the equation by the following:

“(1) the total quantity of the emitter’s greenhouse gas emissions in metric tons CO<sub>2</sub> equivalent, excluding greenhouse gas emissions captured, stored, re-used, eliminated or transferred out of the establishment and emissions reported in accordance with protocols QC.17 and QC.30, calculated using the following equation:”;

(3) by inserting “Total” before “Annual” in the definitions of the factors “CO<sub>2e</sub>” and “GHG<sub>i</sub>” in the equation of subparagraph 1 of the first paragraph;

(4) by replacing subparagraph 2 of the first paragraph by the following subparagraph:

“(2) the total quantity of emissions of each type of greenhouse gas referred to in Schedule A.1, in metric tons, excluding greenhouse gas emissions captured, stored, re-used, eliminated or transferred out of the establishment, and emissions reported in accordance with protocols QC.17 and QC.30; »;

(5) by inserting the following after subparagraph 2.1 of the first paragraph:

“(2.2) the total quantity of the emitter’s greenhouse gas emissions, in metric tons CO<sub>2</sub> equivalent, excluding greenhouse gas emissions captured, stored, re-used, eliminated or transferred out of the establishment, and emissions referred to in the second paragraph of section 6.6”;

(6) by replacing subparagraph 4.2 of the first paragraph by the following:

“(4.2) the quantity and description of biomass used, for each of the following categories:

(a) forest biomass, specifying the quantity and description of each of the following types of waste:

(i) primary forest waste, namely waste from forest management activities such as parts of trees, residual trees, commercial and non-commercial tree sections, branches and foliage;

(ii) secondary forest waste, namely waste from industrial processes and related products such as woodchips, sawdust, shavings and bark;

(iii) tertiary forest waste, namely waste from construction, demolition and packing processes;

(b) agricultural biomass, specifying the quantity and description of each of the following types of waste:

(i) animal waste;

(ii) plant waste;

(iii) municipal biomass;

(iv) any other type of biomass not referred to in subparagraphs a to c;

(7) by replacing “CO<sub>2</sub> emissions that is” in subparagraph 5 of the first paragraph by “emissions of each greenhouse gas”;

(8) by replacing subparagraphs 6 to 8 of the first paragraph by the following:

“(6) the calculation methods used in accordance with section 6.3;

(7) in the case of types of enterprise, facility or establishment or types of activity, process or equipment not covered by a specific protocol in Schedule A.2 or for which greenhouse gas emissions have been calculated in accordance with the second paragraph of section 6.3:

(a) the quantity of emissions of each type of greenhouse gas referred to in Schedule A.1 attributable to each type of activity or the use of each type of process or equipment in metric tons, excluding greenhouse gas emissions captured, stored, re-used, eliminated or transferred out of the establishment;

(b) the CO<sub>2</sub> emissions attributable to the combustion or fermentation of biomass or biomass fuels, in metric tons;

(c) the emission factors or rates used and their origin or method of determination;

(8) in the case of an emitter referred to in section 6.6:

(a) the total annual quantity of benchmark units relating to the emitter’s activities;

(b) for each benchmark unit, the total greenhouse gas emissions for each type of emission, excluding emissions referred to in the second paragraph of section 6.6, namely:

(i) the fixed process CO<sub>2</sub> emissions, in metric tons;

(ii) the annual greenhouse gas combustion emissions, in metric tons CO<sub>2</sub> equivalent;

(iii) the annual other category greenhouse gas emissions, in metric tons CO<sub>2</sub> equivalent;”;

(9) by striking out subparagraph 9 of the first paragraph;

(10) by inserting the following paragraph after the first paragraph:

“When the facility or establishment is equipped with a continuous CO<sub>2</sub> monitoring system and when the emitter must, in accordance with this Regulation, indicate emissions by type, whether combustion, fixed process or “other”, the emitter must, for each type of emission,

(1) estimate the greenhouse gas combustion emissions and the “other” category emissions using the emission factors in tables 1-1 to 1-8 in QC.1.7. If no factor is indicated in the tables, the emitter may use a factor determined by Environment Canada, the U.S. Environmental Protection Agency (USEPA), the Intergovernmental Panel on Climate Change (IPCC), the National Council for Air and Stream Improvement (NCASI) or the World Business Council for Sustainable Development (WBCSD);

(2) determine the annual fixed process greenhouse gas emissions by subtracting from the data measured by the continuous CO<sub>2</sub> monitoring system the greenhouse gas combustion emissions and the “other” category emissions estimated in accordance with subparagraph 1.”.

7. Section 6.3 is amended by replacing “the emitter’s total emissions” in subparagraph 1 of the first paragraph by “total emissions from the establishment”.

8. Section 6.4 is amended:

(1) by replacing paragraph 1 by the following:

“(1) the name of and contact information for the enterprise, facility or establishment as well as the name of and contact information for its representative;”;

(2) by striking out paragraph 2;

(3) by replacing paragraph 3 by the following:

“(3) the business number assigned to the emitter when registered under the Act respecting the legal publicity of enterprises (R.S.Q., c. P-44.1) as well as the ID number assigned under the National Pollutant Release Inventory of the Government of Canada;”.

9. Section 6.5 is replaced by the following:

“**6.5.** An emitter whose annual greenhouse gas emissions report includes one or more errors or omissions must, as soon as possible, communicate a notice of correction to the Minister containing the following information:

- (1) a description of the corrections to be made to the initial report;
- (2) the circumstances that led to the errors or omissions and, where applicable, the corrections made;
- (3) where applicable, an estimate of the quantity of greenhouse gas emissions represented by the errors or omissions.”.

**10.** Section 6.6 is amended

(1) by adding the following after subparagraph 6 of the second paragraph:

“(7) until 31 December 2014, CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to oil and gas exploration and production and natural gas processing, as referred to in QC.33.3.1, QC.33.3.2, QC.33.3.8, QC.33.3.16, QC.33.3.17 and QC.33.3.20 in Schedule A.2.”;

(2) by inserting “and a verifier designated by that organization” after “organization” in the part of the third paragraph preceding subparagraph 1;

(3) by inserting “or provided a service referred to in subparagraph 3 of the first paragraph of section 6.10” after “report” in subparagraph 1 of the third paragraph;

(4) by replacing subparagraph 3 of the third paragraph by the following:

“(3) where the emitter wishes to have the verification of the annual report done by a verifying organization or verifier other than the organization or verifier that verified the report the preceding year, the verifying organization or verifier must not have verified the emissions report for that establishment during the 3 previous years.”.

**11.** Section 6.7 is replaced by the following:

**6.7.** An emitter referred to in section 6.6 who communicates a notice of correction for the emitter’s emissions report in accordance with section 6.5 must include a verification report setting out, in addition to the information referred to in section 6.9,

(1) an assessment of the errors and omissions calculated using the following equation:



$$PE = \left( \frac{SEO}{TER} \times 100 \right)$$

Where:

PE = Percentage of error;

SEO = Sum of CO<sub>2</sub> equivalent greenhouse gas emissions erroneously calculated or omitted, in metric tons;

TER = Total CO<sub>2</sub> equivalent greenhouse gas emissions initially reported;

(2) an attestation that the errors or omissions calculated using the equation in paragraph 1 represent less than 5% of total emissions from the establishment, up to a total of 25,000 metric tons CO<sub>2</sub> equivalent.”.

**12.** Section 6.8 is amended by replacing “initial or revised greenhouse gas emissions report” in the part of the first paragraph preceding subparagraph 1 by “initial greenhouse gas emissions report or notice of correction”.

**13.** Section 6.9 is amended

(1) by replacing paragraph 1 by the following:

“(1) the name of and contact information for the verification organization and its representative, as well as the name of and contact information for the chief verifier, the person assigned to the internal review of the verification process and the other members of the verification team designated by the organization to carry out the verification;”;

(2) by striking out paragraph 5;

(3) by replacing paragraph 8 by the following:

“(8) the conclusions of the verification and an attestation that the emissions report is exact and reliable;

(9) a conflict of interest declaration, including

(a) the name of and contact information for the verification organization, as well as the name of, contact information for, accredited sector and sub-sector of activity of the chief verifier, the person assigned to the internal review of the verification process and the other members of the verification team designated by the organization to carry out the verification;

(b) a copy of the organization chart for the verification organization, as well as the names of and contact information for any subcontractors who took part in the verification;

(c) an attestation signed by the chief verifier of the verification team and the representative of the verification organization that the requirements of section 6.10 have been met and that the risk of conflict of interest is acceptable.”.

**14.** The following is inserted after section 6.9:

**“6.10.** In addition to the requirements of the standards ISO 14064-3 and ISO 14065 concerning conflicts of interest, the emitter must ensure that none of the following situations exists between the emitter, its officers, the verification organization and the members of the verification team:

(1) during the 3 years preceding the year of the declaration, one of the officers of the emitter was employed by the verification organization or, inversely, one of the officers of the verification organization was employed by the emitter;

(2) a member of the verification team or a close relative of that member has personal ties with the emitter or one of its officers;

(3) during the 3 years preceding the year of the declaration, one of the members of the verification team or one of the subcontractors who took part in the verification provided the emitter with one of the following services:

(a) the design, development, commissioning or maintenance of a data inventory or data management system for emissions into the atmosphere from the establishment or facility of the emitter or, where applicable, for data on electricity or fuel transactions;

(b) the development of greenhouse gas emission factors or other data required under this Regulation;

(c) consultation concerning greenhouse gas emissions reductions, and in particular the design of an energy efficiency or renewable energy project and the assessment of assets relating to greenhouse gas sources;

(d) the preparation of manuals, guides or procedures connected with the emitter’s greenhouse gas emissions reports;

(e) consultation in connection with a greenhouse gas emission allowances market, including

(i) brokerage, with or without registration, while acting as a promoter or subscriber on behalf of the emitter;

(ii) advice concerning the suitability of a greenhouse gas emissions transaction;

(iii) the holding, purchase, sale, negotiation or withdrawal of emission allowances referred to in the second paragraph of section 46.6 of the Environment Quality Act (R.S.Q., c. Q-2);

(f) a consultation in the field of health and safety and environmental management, including the consultation leading to ISO 14001 certification;

(g) actuarial, bookkeeping or other services relating to accounting documents or financial statements;

(h) a service connected with the process data management systems covered by the greenhouse gas emissions verification process;

(i) an internal audit of greenhouse gas emissions;

(j) a service provided in connection with litigation or an inquiry into greenhouse gas emissions;

(k) a consultation for a greenhouse gas emissions reduction project or an offset credit project in accordance with the Regulation respecting a cap-and-trade system for greenhouse gas emission allowances (c. Q-2, r. 46.1);

(4) the person at the verification organization responsible for carrying out an internal review of the verification process, in accordance with the standards ISO 14065 and ISO 14064-3, has previously provided a verification or other service referred to in subparagraph 3 to the emitter during the report year or the preceding year.

The existence of one of the situations described in the first paragraph is considered to be a conflict of interest that invalidates the verification report.

For the purposes of this section, a close relative of a member of the verification team is that person's spouse, child, spouse's child, mother or father, mother's or father's spouse, child's spouse or spouse's child's spouse.”.

**15.** Section 7 is amended by adding “and submit them to the Minister on request” at the end of the first paragraph.

**16.** Division III is replaced by the following divisions:

**“DIVISION III  
MONETARY ADMINISTRATIVE PENALTIES**

**8.** A monetary administrative penalty of \$250 in the case of a natural person or \$1,000 in all other cases may be imposed on any person who

(1) contravenes the third paragraph of section 6.2;

(2) fails to keep any information, calculation, assessment, measurement or data for the time prescribed in section 7;

(3) in contravention of this Regulation, refuses or neglects to provide any other notice or other information, any study, research or expert report, or any information, report, calculation, plan or other document, or fails to comply with the time limit for providing them, if no monetary administrative penalty is otherwise provided for.

**9.** A monetary administrative penalty of \$350 in the case of a natural person or \$1,500 in all other cases may be imposed on any person who fails to communicate, in the prescribed conditions, any information, notice, attestation or report, as prescribed in one of sections 4, 5, 5.1 or 5.2, the fourth paragraph of section 6, section 6.1, the first or second paragraph of section 6.2 or section 6.4 or 6.5.

**9.1.** A monetary administrative penalty of \$500 in the case of a natural person or \$2,500 in all other cases may be imposed on any person who fails

(1) to base any information communicated on the best data and best information, in accordance with the first or second paragraph of section 6;

(2) to calculate the quantities of greenhouse gas emissions reported using once of the methods in section 6.3;

(3) to carry out a verification referred to in section 6.8 in accordance with the standard prescribed by that section or to include in the verification report the information prescribed by section 6.9.

**9.2.** A monetary administrative penalty of \$750 in the case of a natural person or \$3,500 in all other cases may be imposed on any person who fails

(1) to send to the Minister, within the prescribed time, the verification report referred to in section 6.6 or 6.7, in accordance with those sections;

(2) to ensure that none of the situations described in section 6.10 exist, in accordance with that section;

(3) to maintain any device, system or equipment referred to in section 7.1 in good working order, or to ensure that it operates optimally during operating hours.

### **DIVISION III.1**

#### **PENAL PENALTIES**

**9.3.** Any person who contravenes the third paragraph of section 6 or 6.2 or section 7 is guilty of an offence and liable to a fine of

(1) \$1,000 to \$100,000, in the case of a natural person;

(2) \$3,000 to \$600,000, in all other cases.

Any person who, in contravention of this Regulation, refuses or neglects to provide any other notice or other information, any study, research or expert report, or any information, report, calculation, plan or other document, or fails to comply with the time limit for providing them, is guilty of an offence and liable to the same fines, if no monetary administrative penalty is otherwise provided for.

**9.4.** Any person who contravenes section 4, 5, 5.1 or 5.2, the fourth paragraph of section 6, section 6.1, the first or second paragraph of section 6.2, or section 6.4 or 6.5 is guilty of an offence and liable to a fine of

(1) \$2,000 to \$100,000, in the case of a natural person;

(2) \$5,000 to \$600,000, in all other cases.



(b) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.1.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(c) by inserting the following after paragraph 1 of QC.1.2:

“(1.1) in the case of emitters referred to in section 6.6, for each benchmark unit, the annual greenhouse gas combustion emissions, excluding CO<sub>2</sub> emissions attributable to the combustion of biomass, in metric tons CO<sub>2</sub> equivalent;”;

(d) by replacing subparagraphs *a* to *d* of paragraph 2 of QC.1.2 by the following:

“(a) in bone dry metric tons, when the quantity is expressed as a mass;

(b) in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;

(c) in kilolitres, when the quantity is expressed as a volume of liquid;

(d) in metric tons collected, in the case of municipal solid waste;”;

(e) by replacing paragraphs 3 and 4 of QC.1.2 by the following:

“(3) where carbon content is used to calculate CO<sub>2</sub> emissions, the average annual carbon content of each type of fuel;

(4) where high heat value is used to calculate CO<sub>2</sub> emissions, the average annual high heat value of each type of fuel, expressed

(a) in gigajoules per bone dry metric ton, when the quantity is expressed as a mass;

(b) in gigajoules per thousand cubic metres, when the quantity is expressed as a volume of gas;

(c) in gigajoules per kilolitre, when the quantity is expressed as a volume of liquid;

(d) in gigajoules per metric ton collected, in the case of municipal solid waste;”;

(f) by replacing “kilograms” in paragraph 5 of QC.1.2 by “metric tons”;

(g) by inserting “for fluidized bed boilers” after “equipment” in the first paragraph of QC.1.3;

(h) by replacing QC.1.3.1 and QC.1.3.2 by the following:

“QC.1.3.1. Calculation method using the fuel-specific default CO<sub>2</sub> emission factor, the default high heat value and the annual fuel consumption

The annual CO<sub>2</sub> emissions attributable to the combustion of fuels in stationary units may be calculated using equation 1-1 or 1-1.1

(1) in the case of an emitter not referred to in section 6.6 who uses any type of fuel for which an emission factor is specified in Table 1-2, 1-3, 1-4, 1-5 or 1-6 in QC.1.7 and a high heat value is specified in Table 1-1 or 1-2;

(2) in the case of an emitter referred to in section 6.6 who uses

(a) natural gas with a high heat value that is equal to or greater than 36.3 GJ per thousand cubic metres but less than or equal to 40.98 GJ per thousand cubic metres, with the exception of an emitter using a stationary unit with a design rated heat input capacity that is greater than 264 GJ/h and that has operated for more than 1,000 hours during at least one of the 3 preceding years;

(b) a fuel in Table 1-2;

(c) municipal solid waste when no steam is generated;

(d) a biomass fuel specified in Table 1-3 except if it is targeted by another protocol specified in this Schedule.

However, this method cannot be used by an emitter who determines the high heat value of the fuels used using measurements carried out by the emitter in accordance with QC.1.5.4 or using data indicated by the fuel supplier, obtained at the frequency prescribed by QC.1.5.1.

### Equation 1-1

$$CO_2 = Fuel \times HHV \times EF \times 0.001$$



Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to the combustion of each type of fuel, in metric tons;

Fuel = Mass or volume of the fuel combusted during the year, expressed

- in bone dry metric tons, when the quantity is expressed as a mass;
- in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;
- in kilolitres, when the quantity is expressed as a volume of liquid;
- in metric tons collected, in the case of municipal solid waste;

HHV = High heat value of the fuel specified in Tables 1-1 and 1-2, expressed

- in gigajoules per bone dry metric ton, in the case of a fuel whose quantity is expressed as a mass;
- in gigajoules per thousand cubic metres, in the case of a fuel whose quantity is expressed as a volume of gas;
- in gigajoules per kilolitre, in the case of a fuel whose quantity is expressed as a volume of liquid;
- in gigajoules per metric ton collected, in the case of municipal solid waste;

EF = CO<sub>2</sub> emission factor for the fuel specified in Table 1-2, 1-3, 1-4, 1-5 or 1-6, in kilograms of CO<sub>2</sub> per gigajoule;

0.001 = Conversion factor, kilograms to metric tons;

#### Equation 1-1.1

$$CO_2 \times Fuel \times OEF$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to the combustion of each type of fuel, in metric tons;

Fuel = Mass or volume of the fuel combusted during the year, expressed

- in bone dry metric tons, when the quantity is expressed as a mass;
- in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;
- in kilolitres, when the quantity is expressed as a volume of liquid;
- in metric tons collected, in the case of municipal solid waste;

OEF = Overall CO<sub>2</sub> emission factor for the fuel, as specified in Table 1-3, 1-4 or 1-5, expressed

- in kilograms of CO<sub>2</sub> per bone dry kilogram, in the case of a fuel whose quantity is expressed as a mass;
- in kilograms of CO<sub>2</sub> per cubic metres at standard conditions, in the case of a fuel whose quantity is expressed as a volume of gas;
- in kilograms of CO<sub>2</sub> per litre, in the case of a fuel whose quantity is expressed as a volume of liquid;
- in kilograms of CO<sub>2</sub> per kilogram collected, in the case of municipal solid waste.

QC.1.3.2. Calculation method using the fuel-specific default CO<sub>2</sub> emission factor and the high heat value indicated by the fuel supplier or determined by the emitter

The annual CO<sub>2</sub> emissions attributable to the combustion of fuels in stationary units may be calculated

(1) in the case of an emitter not referred to in section 6.6 who uses

(a) any type of fuel other than municipal solid waste, for which an emission factor is specified in Table 1-2, 1-3, 1-4, 1-5 or 1-6 in QC.1.7, using equation 1-2;

(b) municipal solid waste and any biomass solid fuel specified in Table 1-3 in QC.1.7, when the combustion of the fuel produces steam, using equation 1-3;

(2) in the case of an emitter referred to in section 6.6 who uses natural gas with a high heat value that is equal to or greater than 36.3 GJ per thousand cubic metres but less than or equal to 40.98 GJ per thousand cubic metres or who uses a fuel in Table 1-2 or a biomass fuel, using equation 1-2.

### Equation 1-2

$$CO_2 = \sum_{i=1}^n Fuel_i \times HHV_i \times EF \times 0.001$$

Where:

$CO_2$  = Annual  $CO_2$  emissions attributable to the combustion of each type of fuel, in metric tons;

$n$  = Number of measurements of high heat value required annually, as specified in QC.1.5.1;

$i$  = Measurement period;

$Fuel_i$  = Mass or volume of fuel combusted during measurement period  $i$ , expressed

- in bone dry metric tons, when the quantity is expressed as a mass;
- in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;
- in kilolitres, when the quantity is expressed as a volume of liquid;

HHV<sub>i</sub> = High heat value of the fuel for measurement period *i*, expressed

- in gigajoules per bone dry metric ton, in the case of a fuel whose quantity is expressed as a mass;
- in gigajoules per thousand cubic metres, in the case of a fuel whose quantity is expressed as a volume of gas;
- in gigajoules per kilolitre, in the case of a fuel whose quantity is expressed as a volume of liquid;

EF = CO<sub>2</sub> emission factor for the fuel as specified in Table 1-2, 1-3, 1-4, 1-5 or 1-6, in kilograms of CO<sub>2</sub> per gigajoule;

0.001 = Conversion factor, kilograms to metric tons;

### Equation 1-3

$$CO_2 = Steam \times B \times EF \times 0.001$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to the combustion of each type of biomass solid fuel or municipal solid waste, in metric tons;

Steam = Total quantity of steam produced during the year by the combustion of biomass solid fuel or municipal solid waste, in metric tons;

B = Ratio of the boiler's design rated heat input capacity to its design rated steam output capacity, in gigajoules per metric ton of steam;

EF = CO<sub>2</sub> emission factor for biomass solid fuel or municipal solid waste specified in Table 1-3 or 1-6, or an establishment-specific factor determined in accordance with QC.1.5.3, in kilograms of CO<sub>2</sub> per gigajoule;

0.001 = Conversion factor, kilograms to metric tons.”;

(i) by replacing the part of QC.1.3.3 preceding paragraph 1 by “The annual CO<sub>2</sub> emissions may be calculated using the following methods:”;

(j) by replacing “solid fuels” in the part of paragraph 1 of QC.1.3.3 preceding equation 1-4 by “fuels whose quantity is expressed as a mass”;

(k) by replacing “Mass” in the definition of the factor “Fuel<sub>i</sub>” in equation 1-4 of QC.1.3.3 by “Bone dry mass”;

(l) by replacing the definition of “CC<sub>i</sub>” in equation 1-4 of paragraph 1 of QC.1.3.3 by the following:

“CC<sub>i</sub> = Average carbon content of the fuel whose quantity is expressed as a mass, from the fuel analysis results for the measurement period *i* indicated by the fuel supplier or measured by the emitter in accordance with QC.1.5.5, in kilograms of carbon per kilogram of fuel.”;

(m) by replacing “liquid fuels” in the part of paragraph 3 of QC.1.3.3 preceding equation 1-6 by “fuels whose quantity is expressed as a volume of liquid”;

(n) by replacing “liquid fuel” in equation 1-6 in paragraph 3 of QC.1.3.3 by “fuel whose quantity is expressed as a volume of liquid”;

(o) by striking out “liquid” in the definition of the factor “Fuel<sub>i</sub>” in equation 1-6 of paragraph 3 of QC.1.3.3;

(p) by replacing paragraph 4 of QC.1.3.3 by the following:

“(4) for fuels whose quantity is expressed as a volume of gas, the emitter must use equation 1-7:

#### Equation 1-7

$$CO_2 = \sum_{i=1}^n Fuel_i \times CC_i \times \frac{MW}{MVC} \times 3.664 \times 1$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to the combustion of each type of fuel whose quantity is expressed as a volume of gas, in metric tons;

*n* = Number of measurements of carbon content and molecular weight required annually, as specified in QC.1.5.1;

*i* = Measurement period;

Fuel<sub>*i*</sub> = Volume of gaseous fuel combusted during measurement period *i*, in thousands of cubic metres at standard conditions;

CC<sub>i</sub> = Average carbon content of the gaseous fuel, from the fuel analysis results for the measurement period *i* indicated by the fuel supplier or measured by the emitter in accordance with QC.1.5.5, in kilograms of carbon per kilogram of fuel;

MW = Molecular weight of the gaseous fuel, established in accordance with QC.1.5.5 from the fuel analysis results, in kilograms per kilomole or, when a mass flowmeter is used to measure the flow in kilograms per unit of time, replace

$\frac{MW}{MVC}$  by 1;

MVC = Molar volume conversion factor (24.06 m<sup>3</sup> per kilomole at standard conditions);

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon;

1 = Conversion factor, kilograms to metric tons and thousands of cubic metres to cubic metres.”;

(q) by adding “, or, in the case of an emitter not referred to in section 6.6, in accordance with the manufacturer’s specifications” at the end of the first paragraph of QC.1.3.4;

(r) by adding the following after subparagraph 2 of the fourth paragraph of QC.1.3.4:

“(3) when the facility or establishment is equipped with a continuous CO<sub>2</sub> monitoring system and when the emitter must, in accordance with this Regulation, report emissions by type, namely combustion, fixed process or “other” category, the emitter must, for each type of emission,

(a) estimate the greenhouse gas emissions attributable to combustion and the “other” category emissions using the emission factors in tables 1-1 to 1-8 in QC.1.7. If no factor is indicated in the tables, the emitter may use a factor published by Environment Canada, the U.S. Environmental Protection Agency (USEPA), the Intergovernmental Panel on Climate Change (IPCC), the National Council for Air and Stream Improvement (NCASI) or the World Business Council for Sustainable Development (WBCSD);

(b) determine the annual greenhouse gas emissions attributable to the fixed process by subtracting from the data measured by the continuous CO<sub>2</sub> monitoring system the greenhouse gas emissions attributable to combustion and the “other” category emissions estimated in accordance with subparagraph a.”;

(s) by replacing subparagraphs b and c of paragraph 2 of QC.1.3.5 by the following:

“(b) if the fuels contain over 5% of biomass by weight or if waste-derived fuels make up over 30% by weight of the fuels combusted during the year, calculate the emissions in accordance with the most recent version of ASTM D6866 “Standard Test Methods for Determining the Biobased Content of Solid, Liquid, and Gaseous Samples Using Radiocarbon Analysis”, or using any other analysis method published by an organization listed in QC.1.5;

(c) conduct, at least every 3 months, an analysis on a representative fuel or exhaust gas sample in accordance with the most recent version of ASTM D6866 or using any other analysis method published by an organization listed in QC.1.5, the analysis being conducted on the exhaust gas stream when waste-derived fuels are combusted;

(c.1) when the exhaust gas stream is sampled, collect samples over a period of at least 24 consecutive hours in accordance with the most recent version of ASTM D7459 “Standard Practice for Collection of Integrated Samples for the Speciation of Biomass (Biogenic) and Fossil-Derived Carbon Dioxide Emitted from Stationary Emissions Sources”, or using any other analysis method published by an organization listed in QC.1.5.”;

(t) by replacing subparagraph e of paragraph 2 of QC.1.3.5 by the following:

“(e) make the measurements in accordance with the most recent version of ASTM D6866 on the stationary combustion unit of the emitter’s choice if there is a common fuel source for multiple units or using any other analysis method published by an organization listed in QC.1.5.”;

(u) by adding “for fluidized bed boilers” at the end of the heading of QC.1.3.6;

(v) by inserting “for fluidized bed boilers” after “equipment” in the part of QC.1.3.6 preceding equation 1-9, and after “equipment” in the definition of the factor “CO<sub>2</sub>” in that equation;

(w) by replacing “QC.1.4.4” in the first paragraph of QC.1.4 by “QC.1.4.5”;

(x) by replacing QC.1.4.1 by the following:

“QC.1.4.1. Calculation method using a default CH<sub>4</sub> and N<sub>2</sub>O emission factor and the default high heat value for the fuel

The annual CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to the combustion of a fuel whose high heat value is not determined by the measurements made by the emitter or the data provided by the fuel supplier for the purpose of calculating CO<sub>2</sub> emissions may be calculated using equation 1-10 or 1-10.1

(1) in the case of an emitter not referred to in section 6.6 who uses any type of fuel for which an emission factor is specified in Table 1-3, 1-6 or 1-7 in QC.1.7 and a high heat value is specified in Table 1-1 or 1-2;

(2) in the case of an emitter referred to in section 6.6 who uses either

(a) natural gas with a high heat value that is equal to or greater than 36.3 GJ per thousand cubic metres but less than or equal to 40.98 GJ per thousand cubic metres; or

(b) a fuel in Table 1-2 or a biomass fuel.

In the case of any emitter, the emissions attributable to the combustion of coal must be calculated using equation 1-11.

### Equation 1-10

$$CH_4 \text{ or } N_2O = Fuel \times HHV \times EF \times 0.000001$$

Where:

CH<sub>4</sub> or N<sub>2</sub>O = Annual CH<sub>4</sub> or N<sub>2</sub>O emissions attributable to the combustion of each type of fuel, in metric tons;

Fuel = Mass or volume of the fuel combusted during the year, expressed

- in bone dry metric tons, when the quantity is expressed as a mass;
- in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;



- in kilolitres, when the quantity is expressed as a volume of liquid;

- in metric tons collected, in the case of municipal solid waste;

HHV = High heat value of the fuel specified in Tables 1-1 and 1-2, expressed

- in gigajoules per bone dry metric ton, in the case of a fuel whose quantity is expressed as a mass;

- in gigajoules per thousand cubic metres, in the case of a fuel whose quantity is expressed as a volume of gas;

- in gigajoules per kilolitre, in the case of a fuel whose quantity is expressed as a volume of liquid;

- in gigajoules per metric ton collected, in the case of municipal solid waste;

EF = CH<sub>4</sub> or N<sub>2</sub>O emission factor for the fuel established by the emitter in accordance with QC.1.5.3, emission factor for the fuel as specified in Table 1-3, 1-6 or 1-7, or emission factor from the document "AP-42, Compilation of Air Pollutant Emission Factors" published by the U.S. Environmental Protection Agency (USEPA), in grams of CH<sub>4</sub> or N<sub>2</sub>O per gigajoule;

0.000001 = Conversion factor, grams to metric tons;

### Equation 1-10.1

$$CH_4 \text{ or } N_2O = Fuel \times OEF \times 0.001$$

Where:

CH<sub>4</sub> or N<sub>2</sub>O = Annual CH<sub>4</sub> or N<sub>2</sub>O emissions attributable to the combustion of each type of fuel, in metric tons;

Fuel = Mass or volume of the fuel combusted during the year, expressed

- in bone dry metric tons, when the quantity is expressed as a mass;

- in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;

- in kilolitres, when the quantity is expressed as a volume of liquid;

- in metric tons collected, in the case of municipal solid waste;

OEF = Overall CH<sub>4</sub> or N<sub>2</sub>O emission factor for the fuel, as specified in Table 1-3, 1-7 or 1-8, expressed

- in grams of CH<sub>4</sub> or N<sub>2</sub>O per kilogram, in the case of a fuel whose quantity is expressed as a mass;

- in grams of CH<sub>4</sub> or N<sub>2</sub>O per cubic metre at standard conditions, in the case of a fuel whose quantity is expressed as a volume of gas;

- in grams of CH<sub>4</sub> or N<sub>2</sub>O per litre in the case of a fuel whose quantity is expressed as a volume of liquid;

0.001 = Conversion factor, kilograms to metric tons;

#### Equation 1-11

$$CH_4 \text{ or } N_2O = Fuel \times EF_c \times 0.001$$

Where:

CH<sub>4</sub> or N<sub>2</sub>O = Annual CH<sub>4</sub> or N<sub>2</sub>O emissions attributable to the combustion of coal, in metric tons;

Fuel = Mass of coal combusted during the year, in metric tons;

EF<sub>c</sub> = CH<sub>4</sub> or N<sub>2</sub>O emission factor for the coal established by the emitter in accordance with QC.1.5.3 or emission factor for the coal specified in Table 1-8, in grams of CH<sub>4</sub> or N<sub>2</sub>O per kilogram of coal;

0.001 = Conversion factor, kilograms to metric tons.”;

(y) by replacing equations 1-12 and 1-13 of QC.1.4.2 by the following:

#### “Equation 1-12

$$CH_4 \text{ or } N_2O = \sum_{i=1}^n Fuel_i \times HHV_i \times EF \times 0.000001$$

Where:

$\text{CH}_4$  or  $\text{N}_2\text{O}$  = Annual  $\text{CH}_4$  or  $\text{N}_2\text{O}$  emissions attributable to each type of fuel, in metric tons;

$n$  = Number of measurements of high heat value required annually, as specified in QC.1.5.1;

$i$  = Measurement period;

$\text{Fuel}_i$  = Mass or volume of fuel combusted during measurement period  $i$ , expressed

- in bone dry metric tons, when the quantity is expressed as a mass;
- in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;
- in kilolitres, when the quantity is expressed as a volume of liquid;
- in metric tons collected, in the case of municipal solid waste;

$\text{HHV}_i$  = High heat value determined from data provided by the fuel supplier or measurements made by the emitter for the measurement period  $i$  in accordance with QC.1.5.4, for each type of fuel, expressed

- in gigajoules per bone dry metric ton, in the case of a fuel whose quantity is expressed as a mass;
- in gigajoules per kilolitre, in the case of a fuel whose quantity is expressed as a volume of liquid;
- in gigajoules per thousand cubic metres, in the case of a fuel whose quantity is expressed as a volume of gas;
- in gigajoules per metric ton collected, in the case of municipal solid waste;

EF = CH<sub>4</sub> or N<sub>2</sub>O emission factor for the fuel established by the emitter in accordance with QC.1.5.3, emission factor for the fuel as specified in Table 1-3 or 1-7 in QC.1.7, or emission factor from the document “AP-42, Compilation of Air Pollutant Emission Factors” published by the U.S. Environmental Protection Agency (USEPA), in grams of CH<sub>4</sub> or N<sub>2</sub>O per gigajoule;

0.000001 = Conversion factor, grams to metric tons;

### Equation 1-13

$$CH_4 \text{ or } N_2O = \sum_{i=1}^n Fuel_i \times EF_c \times 0.001$$

Where:

CH<sub>4</sub> or N<sub>2</sub>O = Annual CH<sub>4</sub> or N<sub>2</sub>O emissions attributable to the combustion of coal, in metric tons;

n = Number of measurements required annually, as specified in QC.1.5.1;

i = Measurement period;

Fuel<sub>i</sub> = Mass of coal combusted during measurement period *i*, in metric tons;

EF<sub>c</sub> = CH<sub>4</sub> or N<sub>2</sub>O emission factor for the coal, indicated by the fuel supplier or established by the emitter in accordance with QC.1.5.3, in grams of CH<sub>4</sub> or N<sub>2</sub>O per kilogram of coal;

0.001 = Conversion factor, kilograms to metric tons.”;

(z) by adding the following after QC.1.4.4:

“QC.1.4.5. Calculation method using data from a continuous emission monitoring and recording system

The annual CH<sub>4</sub> or N<sub>2</sub>O emissions attributable to the combustion of any type of fuel used in stationary combustion units may be calculated using data from a continuous emission monitoring and recording system including a gas volumetric flow rate monitor and a CH<sub>4</sub> or N<sub>2</sub>O concentration monitor, in accordance with the EPS 1/PG/7 protocol entitled “Protocols and performance specifications for continuous monitoring of gaseous emissions from thermal power generation” published in November 2005 by Environment Canada or, in the case of an emitter not referred to in section 6.6, in accordance with the manufacturer’s specifications.”;

(aa) by inserting the following after the heading of QC.1.5:

“In the cases provided for in this protocol, the emitter may use the analysis methods published by the following organizations:

- (1) American Society for Testing and Materials (ASTM);
- (2) Centre d'Expertise en Analyse Environnementale du Québec (CEAEQ);
- (3) Environment Canada;
- (4) U.S. Environmental Protection Agency (USEPA);
- (5) International Organization for Standardization (ISO);
- (6) Technical Association of the Pulp and Paper Industry: Industry Standards & Regulations (TAPPI);
- (7) Canadian Standards Association;
- (8) Measurement Canada.”;

(bb) by replacing the second paragraph of QC.1.5.2 by the following:

“Fuel flow meters that measure mass flow rates may be used for liquid fuels, provided that the fuel density is used to convert the readings to volumetric flow rates. The density must in such cases be measured at the same frequency as the carbon content using the most recent version of method ASTM D1298, “Standard Test Method for Density, Relative Density (Specific Gravity), or API Gravity of Crude Petroleum and Liquid Petroleum Products by Hydrometer Method”, or any other analysis method published by an organization listed in QC.1.5. An emitter using one of the methods specified in QC.1.3.1 or QC.1.3.2 may, however, use the mass flow specified in Table 1-10 in QC.1.7.”;

(cc) by replacing equation 1-16 in the first paragraph of QC.1.5.4 by the following:

“**Equation 1-16**

$$HHV_a = \frac{\sum_{i=1}^n [HHV_i \times Fuel_i]}{\sum_{i=1}^n Fuel_i}$$

Where:

$HHV_a$  = Average annual high heat value, expressed

- in gigajoules per bone dry metric ton, in the case of a fuel whose quantity is expressed as a mass;
- in gigajoules per thousand cubic metres, in the case of a fuel whose quantity is expressed as a volume of gas;
- in gigajoules per kilolitre, in the case of a fuel whose quantity is expressed as a volume of liquid;
- in gigajoules per metric ton collected, in the case of municipal solid waste;

$n$  = Number of measurements of high heat value;

$i$  = Measurement period;

$HHV_i$  = High heat value for the measurement period  $i$ , expressed

- in gigajoules per bone dry metric ton, in the case of a fuel whose quantity is expressed as a mass;
- in gigajoules per thousand cubic metres, in the case of a fuel whose quantity is expressed as a volume of gas;
- in gigajoules per kilolitre, in the case of a fuel whose quantity is expressed as a volume of liquid;
- in gigajoules per metric ton collected, in the case of municipal solid waste;

$Fuel_i$  = Mass or volume of fuel combusted during measurement period  $i$ , expressed

- in bone dry metric tons, when the quantity is expressed as a mass;
- in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;

- in kilolitres, when the quantity is expressed as a volume of liquid;
- in metric tons collected, in the case of municipal solid waste.”;

(dd) by replacing subparagraph a of subparagraph 1 of the second paragraph of QC.1.5.4 by the following:

“(a) in accordance with the most recent version of ASTM D1826 “Standard Test Method for Calorific (Heating) Value of Gases in Natural Gas Range by Continuous Recording Calorimeter”, ASTM D3588 “Standard Practice for Calculating Heat Value, Compressibility Factor, and Relative Density of Gaseous Fuels”, and ASTM D4891 “Standard Test Method for Heating Value of Gases in Natural Gas Range by Stoichiometric Combustion”, and GPA 2261 “Analysis for natural gas and similar gaseous mixtures by gas chromatography” published by the Gas Processors Association (GPA), or using any other analysis method published by an organization listed in QC.1.5.”;

(ee) by replacing “megajoules per cubic metre” in the definitions of the factors “HHV” and “LHV” in equation 1-17 in the second paragraph of QC.1.5.4 by “gigajoules per thousand cubic metres”;

(ff) by replacing subparagraphs 2 to 4 of the second paragraph of QC.1.5.4 by the following:

“(2) for middle distillates, fuel oil and liquid waste-derived fuels, in accordance with the most recent version of ASTM D240 “Standard Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter”, or ASTM D4809 “Standard Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter (Precision Method)”, or using any other analysis method published by an organization listed in QC.1.5;

(3) for biomass solid fuel, in accordance with the most recent version of ASTM D5865 “Standard Test Method for Gross Calorific Value of Coal and Coke”, or using any other analysis method published by an organization listed in QC.1.5;

(4) for waste-derived fuels, in accordance with the most recent version of ASTM D5865 or ASTM D5468 “Standard Test Method for Gross Calorific and Ash Value of Waste Materials”, or using any other analysis method published by an organization listed in QC.1.5 and, when the waste-derived fuels are not pure biomass fuels, by calculating the biomass fuel portion of CO<sub>2</sub> emissions in accordance with subparagraph 2 of the fifth paragraph of QC.1.3.4.”;

(gg) by replacing QC.1.5.5 by the following:

“QC.1.5.5. Carbon content, molecular weight and molar fraction of fuel

The emitter must determine the average annual carbon content using equation 1-18:

**Equation 1-18**

$$CC_a = \frac{\sum_{i=1}^n [CC_i \times Fuel_i]}{\sum_{i=1}^n Fuel_i}$$

Where:

CC<sub>a</sub> = Average annual carbon content, expressed

- in kilograms of carbon per bone dry kilogram, in the case of a fuel whose quantity is expressed as a mass;
- in kilograms of carbon per kilogram, in the case of a fuel whose quantity is expressed as a volume of gas;
- in kilograms of carbon par kilolitre, in the case of a fuel whose quantity is expressed as a volume of liquid;

n = Number of measurements of carbon content;

i = Measurement period;

CC<sub>i</sub> = Carbon content of the fuel for the measurement period *i*, expressed

- in kilograms of carbon per bone dry kilogram, in the case of a fuel whose quantity is expressed as a mass;
- in kilograms of carbon per kilogram, in the case of a fuel whose quantity is expressed as a volume of gas;



- in kilograms of carbon par kilolitre, in the case of a fuel whose quantity is expressed as a volume of liquid;

Fuel<sub>i</sub> = Mass or volume of fuel combusted during measurement period *i*, expressed

- in bone dry metric tons, when the quantity is expressed as a mass;
- in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;
- in kilolitres, when the quantity is expressed as a volume of liquid.

The carbon content and molecular weight or molar fraction of gaseous fuels must be determined using the sampling and analysis results indicated by the fuel supplier or the results of the sampling conducted by the emitter using one of the following methods:

(1) for solid fuels, namely coal, coke, biomass solid fuels and waste-derived fuels, in accordance with the most recent version of ASTM D5373 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal”, or using any other analysis method published by an organization listed in QC.1.5;

(2) for petroleum-based liquid fuels and liquid waste-derived fuels, using one of the following methods:

(a) in accordance with the most recent version of ASTM D5291 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants”;

(b) by applying the elementary analysis method;

(c) in accordance with the most recent version of ASTM D3238 “Standard Test Method for Calculation of Carbon Distribution and Structural Group Analysis of Petroleum Oils by n-d-M Method” and the most recent version of either ASTM D2502 “Standard Test Method for Estimation of Molecular Weight (Relative Molecular Mas(s) of Petroleum Oils From Viscosity Measurements” or ASTM D2503 “Standard Test Method for Relative Molecular Mass (Molecular Weight) of Hydrocarbons by Thermoelectric Measurements of Vapor Pressure”;

(d) using any other analysis method published by an organization listed in QC.1.5;

(3) for gaseous fuels, in accordance with the most recent version of ASTM D1945 “Standard Test Method for Analysis of Natural Gas by Gas Chromatography”, ASTM D1946 “Standard Practice for Analysis of Reformed Gas by Gas Chromatography”, or ASTM D2163 “Standard Test Method for Determination of Hydrocarbons in Liquefied Petroleum (L(P) Gases and Propane/Propene Mixtures by Gas Chromatography”, in accordance with any other analysis method published by an organization listed in QC.1.5, or by measuring the carbon content of the fuel to within  $\pm 5\%$  using data from a continuous emission monitoring and recording system, at the following frequency:

- (a) weekly, for natural gas and biogas;
- (b) daily, for all other types of gaseous fuel.”;

(hh) by replacing “and QC.1.4.4 must determine the replacement data for the CO<sub>2</sub> concentration” in the part of QC.1.6 preceding subparagraph a of paragraph 2, as amended by the Regulation to amend the Regulation respecting mandatory reporting of certain emissions of contaminants into the atmosphere (M.O., 2012, G.O.2, 2759), by “, QC.1.4.4 and QC.1.4.5 must determine the replacement data for the CO<sub>2</sub>, CH<sub>4</sub>, and N<sub>2</sub>O concentration”;

(ii) by replacing Table 1-1 in QC.1.7 by the following:

**“Table 1-1. High heat value by fuel type**

(QC.1.3.1, (1), QC.1.4.1, (1), QC.1.5.2, (2), QC.17.3.1, (2))

Liquid fuels	High heat value (GJ/kl)
Asphalt & Road Oil	44.46
Aviation Gasoline	33.52
Diesel	38.30
Aviation Turbo Fuel	37.40
Kerosene	37.68
Propane	25.31
Ethane	17.22
Butane	28.44
Lubricants	39.16
Motor Gasoline 34.87	
Light Fuel Oil No.1	38.78
Light Fuel Oil No. 2	38.50
Residual Fuel Oil (#5 & 6)	42.50
Crude Oil 39.16	
Naphtha	35.17

Petrochemical Feedstocks	35.17
Petroleum Coke - Refinery Use	46.35
Petroleum Coke - Upgrader Use	40.57
Ethanol (100%)	23.41
Biodiesel (100%)	35.67
Rendered animal fat	34.84
Vegetable oil	33.44
<b>Solid fuels</b>	<b>High heat value (GJ/t)</b>
Anthracite Coal	27.70
Bituminous Coal	26.33
Foreign Bituminous Coal	29.82
Sub-Bituminous Coal	19.15
Lignite	15.00
Coal coke	28.83
Wood Waste (dry basis)	19.2
Spent Puling Liquor (dry basis)	14.2
Municipal solid waste	11.57
Peat	9.30
Tires	31.18
Agricultural By-products <sup>1</sup>	9.59
Biomass By-products <sup>2</sup>	30.03
<b>Gaseous fuels</b>	<b>High heat value (GJ/10<sup>3</sup> m<sup>3</sup>)</b>
Natural Gas	38.32
Coke Oven Gas	19.14
Still Gas – Refineries	36.08
Still Gas – Upgraders	43.24
Landfill Gas (methane portion)	39.82
Biogas (methane portion)	31.50

1. By-products not destined for consumption.

2. Animal and vegetable waste, excluding wood waste and spent liquor.“;

(jj) by replacing Table 1-3 in QC.1.7 by the following:

**“Table 1-3. Emission factors by fuel type**

(QC.1.3.1, (1), QC.1.3.2, QC.1.4.1, (1), QC.1.4.4, QC.17.3.1, (2))

<b>Liquid fuels and biofuels</b>	<b>CO<sub>2</sub> (kg/l)</b>	<b>CO<sub>2</sub> (kg/ GJ)</b>	<b>CH<sub>4</sub> (g/l)</b>	<b>CH<sub>4</sub> (g/GJ)</b>	<b>N<sub>2</sub>O (g/l)</b>	<b>N<sub>2</sub>O (g/GJ)</b>
Aviation Gasoline	2.342	69.87	2.200	65.630	0.230	6.862
Diesel	2.663	69.53	0.133	3.473	0.400	10.44
Aviation Turbo Fuel	2.534	67.75	0.080	2.139	0.230	6.150
<b>Kerosene</b>						
- Electric Utilities	2.534	67.25	0.006	0.159	0.031	0.823
- Industrial	2.534	67.25	0.006	0.159	0.031	0.823
- Producer Consumption	2.534	67.25	0.006	0.159	0.031	0.823
- Forestry, Construction, and Commercial/Institutional	2.534	67.25	0.026	0.690	0.031	0.823
<b>Propane</b>						
- Residential	1.510	59.66	0.027	1.067	0.108	4.267
- All other uses	1.510	59.66	0.024	0.948	0.108	4.267
Ethane	0.976	56.68	S. O.	S. O.	S. O.	S. O.
Butane	1.730	60.83	0.024	0.844	0.108	3.797
Lubricants	1.410	36.01	S. O.	S. O.	S. O.	S. O.
Motor Gasoline	2.289	65.40	2.700	77.140	0.050	1.429
<b>Light Fuel Oil</b>						
- Electric Utilities	2.725	70.23	0.180	4.639	0.031	0.799
- Industrial	2.725	70.23	0.006	0.155	0.031	0.799
- Producer Consumption	2.643	68.12	0.006	0.155	0.031	0.799
- Forestry, Construction, and Commercial/Institutional	2.725	70.23	0.026	0.670	0.031	0.799
<b>Residual Fuel Oil (#5 &amp; 6)</b>						
- Electric Utilities	3.124	73.51	0.034	0.800	0.064	1.506
- Industrial	3.124	73.51	0.12	2.824	0.064	1.506
- Producer Consumption	3.158	74.31	0.12	2.824	0.064	1.506

- Forestry, Construction, and Commercial/Institutional	3.124	73.51	0.057	1.341	0.064	1.820
Naphtha	0.625	17.77	S. O.	S. O.	S. O.	S. O.
Petrochemical Feedstocks	0.556	14.22	S. O.	S. O.	S. O.	S. O.
Petroleum Coke - Refinery Use	3.826	82.55	0.12	2.589	0.0265	0.572
Petroleum Coke - Upgrader Use	3.494	86.12	0.12	2.958	0.0231	0.569
Ethanol (100%)	1.519	64.9	N/A	N/A	N/A	N/A
Biodiesel (100%)	2.497	70	N/A	N/A	N/A	N/A
Rendered Animal Fat	2.348	67.4	N/A	N/A	N/A	N/A
Vegetable Oil	2.585	77.3	N/A	N/A	N/A	N/A
<b>Biomass and other solid fuels</b>	<b>CO<sub>2</sub> (kg/kg)</b>	<b>CO<sub>2</sub> (kg/GJ)</b>	<b>CH<sub>4</sub> (g/kg)</b>	<b>CH<sub>4</sub> (g/GJ)</b>	<b>N<sub>2</sub>O (g/kg)</b>	<b>N<sub>2</sub>O (g/GJ)</b>
Wood Waste (dry basis)	1.799	93.7	0.576	30	0.077	4
Spent Puling Liquor (dry basis)	1.304	91.8	0.041	2.9	0.027	1.9
Agricultural By-products <sup>1</sup>	1.074	112	N/A	N/A	N/A	N/A
Biomass By-products <sup>2</sup>	3.000	100	N/A	N/A	N/A	N/A
Coal Coke	2.480	86.02	0.03	1.041	0.02	0.694
Tires	2.650	85.0	S. O.	S. O.	S. O.	S. O.
<b>Gaseous fuels and biofuels</b>	<b>CO<sub>2</sub> (kg/m<sup>3</sup>)</b>	<b>CO<sub>2</sub> (kg/GJ)</b>	<b>CH<sub>4</sub> (g/m<sup>3</sup>)</b>	<b>CH<sub>4</sub> (g/GJ)</b>	<b>N<sub>2</sub>O (g/m<sup>3</sup>)</b>	<b>N<sub>2</sub>O (g/GJ)</b>
Coke Oven Gas	0.879	45.92	0.037	1.933	0.0350	1.829
Still Gas – Refineries	1.75	48.50	S. O.	S. O.	0.0222	0.615
Still Gas – Upgraders	2.14	49.49	S. O.	S. O.	0.0222	0.513
Landfill Gas	2.175	54.63	0.040	1.0	0.004	0.1
Biogas (methane portion)	1.556	49.4	N/A	N/A	N/A	N/A

1. By-products not destined for consumption.

2. Animal and vegetable waste, excluding wood waste and spent liquor.“;

(kk) by replacing the line beginning by “Peat” in Table 1-6 in QC.1.7 by the following line:

“

Peat	103.0	1.0	1.5
------	-------	-----	-----

»;

(2) in QC.2:

(a) by replacing QC.2.1 by the following:

**“QC.2.1. Covered sources**

The covered sources are stationary combustion units that combust gaseous fuels such as refinery fuel gas, flexigas or associated gas.

Notwithstanding the first paragraph, emissions attributable to the combustion of gas fuels at a flare must be calculated in accordance with QC.9.3.5.”;

(b) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of the first paragraph of QC.2.2 preceding subparagraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(c) by inserting the following after subparagraph 1 of the first paragraph of QC.2.2:

“(1.1) the emissions attributable to the combustion of gas fuels at a flare, calculated in accordance with QC.9.3.5, in metric tons CO<sub>2</sub> equivalent;”;

(d) by replacing “millions” in subparagraph 2 of the first paragraph of QC.2.2 by “thousands”;

(e) by replacing “average carbon content” in subparagraph 3 of the first paragraph of QC.2.2 by “average annual carbon content”;

(f) by inserting “annual” after “average” in subparagraph 5 of the first paragraph of QC.2.2;

(g) by replacing “3 and 4” in the second paragraph of QC.2.2 by “3 and 5”;

(h) by replacing “stationary combustion units located at a petroleum refinery” in the first paragraph of QC.2.3 by “stationary units that combust gaseous fuels” and by replacing “stationary combustion units located at a petroleum refinery that uses refinery fuel gas, flexigas and associated gas” in the second paragraph of QC.2.3 by “stationary units that combust gaseous fuels”;

(i) by replacing equation 2-1 in QC.2.3.2 by the following:

**“Equation 2-1**

$$CO_2 = \sum_{i=1}^n \sum_{j=1}^m \left( RFG_{ij} \times CC_{ij} \times \frac{MW_{ij}}{MVC} \right) \times 3.664 \times 1$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to the combustion of refinery gas or flexigas, in metric tons;

n = Number of days of operation in the year;

m = Number of supply systems;

i = Day;

j = Supply system;

RFG<sub>ij</sub> = Consumption of refinery gas or flexigas in supply system *j* for day *i*, in thousands of cubic metres at standard conditions;

CC<sub>ij</sub> = Carbon content of the sample of refinery gas or flexigas in supply system *j* for day *i*, measured in accordance with QC.2.4.2, in kilograms of carbon per kilogram of fuel;

MW<sub>ij</sub> = Molecular weight of the sample of refinery gas or flexigas in supply system *j* for day *i*, in kilograms per kilomole;

MVC = Molar volume conversion factor (24.06 m<sup>3</sup> per kilomole at standard conditions);

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon;

1 = Conversion factor, kilograms to metric tons and thousands of cubic metres to cubic metres.”;

(j) by replacing “pouvoir” in the French text of subparagraph *b* of paragraph 3 of QC.2.3.4 by “pouvoir”;

(k) by replacing the part of QC.2.4.2 preceding paragraph 1 by the following:

“When the calculation method in QC.2.3.2 is used, the emitter must measure the carbon content and molecular weight of the gaseous fuels daily, using one of the following methods:”;

(3) in QC.3:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of the first paragraph of QC.3.2 preceding subparagraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by inserting “and reported” after “calculated” in subparagraph 6 of the first paragraph of QC.3.2;

(c) by replacing “monthly and annual” in subparagraph 7 of the first paragraph of QC.3.2 by “annual”;

(d) by replacing subparagraphs 8 to 11 of the first paragraph of QC.3.2 by the following:

“(8) for the use of the prebaked anodes process, the annual net prebaked anode consumption for liquid aluminum production, in metric tons of anodes per metric ton of liquid aluminum;

(9) for the use of the Sørderberg anodes process, the annual anode paste consumption, in metric tons of paste per metric ton of liquid aluminum;

(10) for the use of the baking process for prebaked anodes or cathodes, the annual production of baked anodes or cathodes, in metric tons;

(11) for the use of the coke calcination process:

(a) the annual consumption of green coke, in metric tons;

(b) the annual quantity of calcinated coke produced, in metric tons;

(c) the annual quantity of under-calcinated coke produced, in tons;”;

(e) by striking out subparagraphs *b*, *c*, *d*, *e*, *g* and *h* of subparagraph 12 of the first paragraph of QC.3.2;



(f) by striking out subparagraph 13 of the first paragraph of QC.3.2;

(g) by replacing subparagraph 16 of the first paragraph of QC.3.2 by the following:

“(16) the annual quantity of aluminum hydrate produced, measured as precipitation stage output, in metric tons of aluminum hydrate (Al<sub>2</sub>O<sub>3</sub>) equivalent.”;

(h) by inserting “*f* of subparagraph” after “Subparagraph” in the second paragraph of QC.3.2;

(i) by replacing equation 3-1 in QC.3.3.1 by the following:

**“Equation 3-1**

$$CO_2 = \sum_{i=1}^{12} [NAC \times MP \times (1 - S_a - Ash_a) \times 3.664]_i$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to the consumption of prebaked anodes, in metric tons;

*i* = Month;

NAC = Net anode consumption for liquid aluminum production for month *i*, in metric tons of anodes per metric ton of liquid aluminum;

MP = Production of liquid aluminum for month *i*, in metric tons;

S<sub>a</sub> = Sulphur content in the prebaked anodes for month *i*, in kilograms of sulphur per kilogram of prebaked anodes;

Ash<sub>a</sub> = Ash content in the prebaked anodes for month *i*, in kilograms of ash per kilogram of prebaked anodes;

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon.

(j) by replacing equation 3-2 in QC.3.3.2 by the following:

**“Equation 3-2**

$$CO_2 = \sum_{i=1}^{12} \left[ (PC \times MP) - \left( BSM \times \frac{MP}{1000} \right) - (BC \times PC \times MP \times (S_b + Ash_b + H_b)) \right] - \left[ ((1 - BC) \times PC \times MP \times (S_c + Ash_c)) - (MP \times CP) \right] \times 3.664$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to anode consumption from Söderberg electrolysis cells, in metric tons;

i = Month;

PC = Anode paste consumption for month *i*, in metric tons of paste per metric ton of liquid aluminum;

MP = Production of liquid aluminum for month *i*, in metric tons;

BSM = Emissions of benzene-soluble matter (BSM) or the International Aluminium Institute factor used, in kilograms of BSM per metric ton of liquid aluminum;

BC = Average content of pitch or other binding agent in paste for month *i*, in kilograms of pitch or other binding agent per kilogram of paste;

S<sub>b</sub> = Sulphur content in pitch or other binding agent for month *i*, in kilograms of sulphur per kilogram of pitch or other binding agent;

Ash<sub>p</sub> = Ash content in pitch or other binding agent, in kilograms of ash per kilogram of pitch or other binding agent;

H<sub>b</sub> = Hydrogen content in pitch or other binding agent, in kilograms of hydrogen per kilogram of pitch or other binding agent or the International Aluminium Institute factor used;

S<sub>c</sub> = Sulphur content in calcinated coke, in kilograms of sulphur per kilogram of calcinated coke;

Ash<sub>c</sub> = Ash content in calcinated coke, in kilograms of ash per kilogram of calcinated coke;

CP = Monthly reported carbon present in the dust from Söderberg electrolysis cells, in kilograms of carbon per kilogram of liquid aluminum produced, or a value of 0;

3.664 =Ratio of molecular weights, CO<sub>2</sub> to carbon.”;

(k) by replacing paragraphs 1 to 3 of QC.3.3.3 by the following:

“(1) for annual CO<sub>2</sub> emissions, using equation 3-3:

**Equation 3-3**

$$CO_2 = CO_{2PM} + CO_{2P}$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to anode and cathode baking, in metric tons;

CO<sub>2PM</sub> = Annual CO<sub>2</sub> emissions attributable to packing material calculated in accordance with equation 3-4, in metric tons;

CO<sub>2P</sub> = Annual CO<sub>2</sub> emissions attributable to the coking of pitch or another binding agent, calculated in accordance with equation 3-5, in metric tons;

(2) for emissions of CO<sub>2</sub> attributable to packing material, using equation 3-4:

**Equation 3-4**

$$CO_{2PM} = \sum_{i=1}^{12} (CPM \times BAC \times (1 - Ash_{pm} - S_{pm}))_i \times 3.664$$

Where:

CO<sub>2PM</sub> = Annual CO<sub>2</sub> emissions attributable to packing material, in metric tons;

i = Month;

CPM = Consumption of packing material for month *i*, in metric tons of packing material per metric ton of baked anodes or cathodes;

BAC = Production of baked anodes or cathodes for month *i*, in metric tons;

Ash<sub>pm</sub> = Ash content of packing material for month *i*, in kilograms of ash per kilogram of packing material;

S<sub>pm</sub> = Sulphur content of packing material for month *i*, in kilograms of sulphur per kilogram of packing material;

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon;

(3) for emissions of CO<sub>2</sub> attributable to the coking of pitch or another binding agent, using equation 3-5:

**“Equation 3-5**

$$CO_{2,P} = \sum_{i=1}^{12} (GAC - BAC - (H_b \times PC \times GAC) - RT)_i \times 3.664$$

Where:

CO<sub>2,P</sub> = Annual CO<sub>2</sub> emissions attributable to the coking of pitch or another binding agent, in metric tons;

*i* = Month;

GAC = Consumption of green anodes or cathodes for month *i*, in metric tons;

BAC = Production of baked anodes or cathodes for month *i*, in metric tons;

H<sub>p</sub> = Hydrogen content in pitch or other binding agent for month *i* or the International Aluminium Institute factor used, in kilograms of hydrogen per kilogram of pitch or other binding agent;

PC = Pitch or other binding agent content of green anodes or cathodes for month *i*, in kilograms of pitch or other binding agent per kilogram of green anodes or cathodes;

RT = Recovered tar for month *i*, in metric tons;

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon.”;

(1) by replacing equation 3-6 of QC.3.3.4 by the following:

**“Equation 3-6**

$$CO_2 = \sum_{i=1}^{12} [(GC \times (1 - H_2O - V_{gc} - S_{gc}) - (CC + UCC + ED) \times (1 - S_{cc})) \times 3.664 + (GC \times 0.035 \times 2.75)]_i$$

Where:

$CO_2$  = Annual  $CO_2$  emissions attributable to green coke calcination, in metric tons;

$i$  = Month;

$GC$  = Consumption of green coke for month  $i$ , in metric tons;

$H_2O_{gc}$  = Humidity content of green coke for month  $i$ , in kilograms of water per kilogram of green coke;

$V_{gc}$  = Volatiles content of green coke for month  $i$ , in kilograms of volatiles per kilogram of green coke;

$S_{gc}$  = Sulphur content of green coke for month  $i$ , in kilograms of sulphur per kilogram of green coke;

$CC$  = Calcinated coke produced for month  $i$ , in metric tons;

$UCC$  = Under-calcinated coke produced for month  $i$ , in metric tons;

$ED$  = Emissions of coke dust for month  $i$ , in metric tons;

$S_{cc}$  = Sulphur in calcinated coke, in kilograms of sulphur per kilogram of calcinated coke;

3.664 = Ratio of molecular weights,  $CO_2$  to carbon;

0.035 =  $CH_4$  and tar content in coke volatiles contributing to  $CO_2$  emissions;

2.75 = Conversion factor,  $CH_4$  to  $CO_2$ .”;

(m) by replacing equation 3-7 of QC.3.4.2 by the following:

**“Equation 3-7**

$$E_{CF4} = \sum_{i=1}^{12} [slope_{CF4} \times AED \times MP]_i$$

Where:

$E_{CF_4}$  = Annual  $CF_4$  emissions, in metric tons;

$i$  = Month;

$slope_{CF_4}$  = Slope for series of pots  $j$ , determined in accordance with the method in QC.3.6.1, in metric tons of  $CF_4$  per metric ton of liquid aluminum, per anode effect minute, per pot-day, for month  $i$ ;

AED = Anode effect duration, in anode effect minutes per pot-day, calculated for month  $i$ ;

MP = Monthly production of liquid aluminum, in metric tons;”;

(n) by inserting “**Equation 3-8.1**” before the equation in paragraph 2 of QC.3.4.2;

(o) by inserting “technology used in a” after “each” in the second paragraph of QC.3.6.1;

(4) in QC.4:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.4.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by striking out paragraph 1 of QC.4.2;

(c) by replacing “the monthly quantity” in subparagraph *b* of paragraph 3 of QC.4.2 by “the annual quantity”;

(d) by striking out subparagraphs *c* to *g* of paragraph 3 of QC.4.2;

(e) by replacing “discarded” in subparagraph *h* of paragraph 3 of QC.4.2 by “collected”;

(f) by striking out subparagraphs *h.1* and *h.2* of paragraph 3 of QC.4.2;

(g) by replacing “quarterly quantity of the dust discarded” in subparagraph *i* of paragraph 3 of QC.4.2 by “annual quantity of dust collected”;

(h) by replacing “raw material” in paragraph 6 of QC.4.2 by “carbon-containing raw material that contributes 0.5% or more of the total carbon in the process”;

(i) by replacing “matières premières utilisées” in the French text of subparagraph *a* of paragraph 6 of QC.4.2 by “matière première utilisée”;

(j) by replacing subparagraph *b* of paragraph 6 of QC.4.2 by the following:

“(b) the total organic carbon content of the raw material, in metric tons of organic carbon per metric ton of raw material;”;

(k) by replacing paragraph 7 of QC.4.2 by the following:

“(7) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to fuel combustion in all cement kilns, in metric tons;”;

(l) by inserting “and reported” after “calculated” in paragraph 8 of QC.4.2;

(m) by replacing “2 and 4” in subparagraph *a* of paragraph 10 of QC.4.2 by “2 and 5”;

(n) by replacing “6 and 7” in subparagraph *b* of paragraph 10 of QC.4.2 by “7 and 8”;

(o) by adding the following paragraph at the end of QC.4.2:

“Subparagraphs *a* and *h* of subparagraph 3 and subparagraph *b* of subparagraph 6 of the first paragraph do not apply to the emissions of an emitter who calculates emissions using data from a continuous emission monitoring and recording system.”;

(p) by inserting “, **CH<sub>4</sub> and N<sub>2</sub>O**” after “CO<sub>2</sub>” in the heading of QC.4.3;

(q) by replacing the paragraph of QC.4.3 preceding QC.4.3.1 by the following paragraphs:

“The annual CO<sub>2</sub> emissions attributable to the use of cement kilns, other than combustion emissions, must be calculated in accordance with one of the 2 calculation methods in QC.4.3.1 and QC.4.3.2.

The annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to the combustion of fuels in all cement kilns must be calculated in accordance with QC.4.3.3.”;

(r) by replacing “in accordance with paragraph 2 of QC.4.3.2” in the second paragraph of QC.4.3.1 by “in accordance with QC.4.3.3”;

(s) by replacing the part of QC.4.3.2 preceding equation 4-1 by the following:

“The CO<sub>2</sub> emissions attributable to the use of each cement kiln must be calculated by adding together the CO<sub>2</sub> emissions attributable to calcination and the CO<sub>2</sub> emissions attributable to the oxidation of the organic carbon present in the raw materials, calculated in accordance with the following methods:

(1) the CO<sub>2</sub> emissions attributable to calcination must be calculated, for each cement kiln, using equations 4-1 to 4-3:”;

(t) by replacing “discarded” in the definitions of the factors “Q<sub>CKD</sub>” and “EF<sub>CKD</sub>” in equation 4-1 of QC.4.3.2 by “collected”;

(u) by inserting “, determined in accordance with paragraph 1 of QC.4.4” after “in the clinker” in the definition of the factor “CaO<sub>cli</sub>” in equation 4-2 of QC.4.3.2;

(v) by replacing the second paragraph of the definition of the factor “CaO<sub>NCC</sub>” in equation 4-2 of QC.4.3.2 by the following paragraph:

“The non-calcined calcium oxide content in the clinker is the sum of the CaO content present as a non-carbonate species in the raw materials entering the kiln and the non-transformed CaCO<sub>3</sub> content remaining in the clinker after oxidation, expressed as CaO; these values must be determined, respectively, in accordance with paragraphs 4 and 5 of QC.4.4, or a value of 0 must be used;”;

(w) by inserting “, determined in accordance with paragraph 1 of QC.4.4” after “in the clinker” in the definition of the factor “MgO<sub>cli</sub>” in equation 4-2 of QC.4.3.2;

(x) by replacing the second paragraph of the definition of the factor “MgO<sub>NCC</sub>” in equation 4-2 of QC.4.3.2 by the following paragraph:

“The non-calcined magnesium oxide content in the clinker is the sum of the MgO content present as a non-carbonate species in the raw materials entering the kiln and the non-transformed MgCO<sub>3</sub> content remaining in the clinker after oxidation, expressed as MgO; these values must be determined, respectively, in accordance with paragraphs 4 and 5 of QC.4.4, or a value of 0 must be used;”;



(y) by replacing “discarded” in the definition of the factor “ $EF_{CKD}$ ” in equation 4-3 of QC.4.3.2 by “collected”;

(z) by replacing the definition of the factor “ $CaO_{CKD}$ ” in equation 4-3 of QC.4.3.2 by the following definition:

“ $CaO_{CKD}$  = Quarterly content of calcium oxide in the dust collected that is not recycled to the cement kiln, determined in accordance with paragraph 6 of QC.4.4, in metric tons of calcium oxide per metric ton of dust;”;

(aa) by replacing “discarded” in the first paragraph of the definition of the factor “ $CaO_{NCD}$ ” in equation 4-3 of QC.4.3.2 by “collected”;

(bb) by replacing the second paragraph of the definition of the factor “ $CaO_{NCD}$ ” in equation 4-3 of QC.4.3.2 by the following paragraph:

“The non-calcined calcium oxide content in the dust is the sum of the CaO content present as a non-carbonate species in the raw materials entering the kiln and the non-transformed  $CaCO_3$  content remaining in the kiln dust collected that is not recycled after oxidation, expressed as CaO; these values must be determined, respectively, in accordance with paragraphs 7 and 8 of QC.4.4, or a value of 0 must be used;”;

(cc) by replacing the definition of the factor “ $MgO_{CKD}$ ” in equation 4-3 of QC.4.3.2 by the following:

“ $MgO_{CKD}$  = Quarterly content of magnesium oxide in the kiln dust collected that is not recycled in the cement kiln, determined in accordance with paragraph 6 of QC.4.4, in metric tons of magnesium oxide per metric ton of dust;”;

(dd) by replacing “discarded” in the first paragraph of the definition of the factor “ $MgO_{NCD}$ ” in equation 4-3 of QC.4.3.2 by “collected”;

(ee) by replacing the second paragraph of the definition of the factor “ $MgO_{NCD}$ ” in equation 4-3 of QC.4.3.2 by the following paragraph:

“The non-calcined magnesium oxide content in the dust is the sum of the magnesium oxide that enters the kiln as a non-carbonate species and the non-transformed  $MgCO_3$  content remaining in the kiln dust collected that is not recycled after oxidation, expressed as MgO; these values must be determined, respectively, in accordance with paragraphs 7 and 8 of QC.4.4, or a value of 0 must be used;”;

(ff) by replacing subparagraph *b* of paragraph 1 and equation 4-4 in QC.4.3.2 by the following:

“(2) the CO<sub>2</sub> emissions attributable to the oxidation of the organic carbon present in the raw material must be calculated using equation 4-4:

**Equation 4-4**

$$CO_{2, RMm} = \sum_{m=1}^n TOC_{RMm} \times RM_m \times 3.664$$

Where:

CO<sub>2, RMm</sub> = CO<sub>2</sub> emissions resulting from the oxidation of the raw material, in metric tons;

n = Number of raw materials;

m = Raw material;

TOC<sub>RMm</sub> = Total organic carbon content in raw material, determined in accordance with paragraph 10 of QC.4.4 or using a default value of 0.2% metric tons of total organic carbon content per metric ton of raw material;

RM<sub>m</sub> = Quantity of raw material, in metric tons;

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon.”;

(gg) by replacing paragraph 2 of QC.4.3.2 by the following:

“4.3.3. Calculation of the emissions attributable to the combustion of the fuels used in cement kilns

The CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to fuel combustion in each cement kiln must be calculated and reported using the calculation methods in QC.1. When pure biomass fuels, in other words fuels constituted of the same substance for at least 97% of their total weight, are combusted only during start-up, shut-down, or malfunction operating periods for the apparatus or units, the emitter may calculate CO<sub>2</sub> emissions using the calculation method in QC.1.3.1.”;

(hh) by replacing “An emitter” in the part of QC.4.4 preceding paragraph 1 by “When using the calculation method in QC.4.3.2, an emitter”;

(ii) by replacing paragraph 1 of QC.4.4 by the following:

- “(1) determine monthly the calcium oxide and magnesium oxide content of the clinker, in accordance with the most recent version of ASTM C114 “Standard Test Methods for Chemical Analysis of Hydraulic Cement”, or using any other analysis method published by an organization listed in QC.1.5; the measurements being made daily from clinker drawn from the clinker cooler or monthly from clinker drawn from bulk storage;”;
- (jj) by adding “, or using a material balance” at the end of paragraph 3 of QC.4.4;
- (kk) by replacing paragraphs 4 to 10 of QC.4.4 by the following:
- “(4) determine monthly the calcium oxide and magnesium oxide content of the raw material entering the kiln as a non-carbonate species, in accordance with the most recent version of ASTM C114 or in accordance with any other analysis method published by an organization listed in QC.1.5, or use the value of 0;
- (5) determine monthly the non-transformed  $\text{CaCO}_3$  content and the non-transformed  $\text{MgCO}_3$ , expressed as  $\text{MgO}$ , remaining in the clinker after oxidation in accordance with the most recent version of ASTM C114, or in accordance with any other analysis method published by an organization listed in QC.1.5, or use the value of 0;
- (6) determine quarterly the calcium oxide and magnesium oxide content in the kiln dust collected that is not recycled to the cement kiln in accordance with the most recent version of ASTM C114, or using any other analysis method published by an organization listed in QC.1.5; the measurements being made daily at the exit of the kiln or quarterly if the dust is in bulk storage;
- (7) determine quarterly the calcium oxide and magnesium oxide content in the kiln dust collected that is not recycled that enters the kiln as a non-carbonate species in accordance with the most recent version of ASTM C114 or in accordance with any other analysis method published by an organization listed in QC.1.5, or use the value of 0;
- (8) determine quarterly the calcium oxide and magnesium oxide content remaining in the kiln dust collected that is not recycled after oxidation in accordance with the most recent version of ASTM C114 or in accordance with any other analysis method published by an organization listed in QC.1.5, or use the value of 0;

(9) determine quarterly the quantity of kiln dust collected that is not recycled to the cement kiln by direct weight measurement using the same plant instruments used for inventory purposes, such as weigh hoppers or belt weigh feeders, or using a material balance;

(10) take samples annually of each category of raw materials in bulk storage and determine the total organic carbon content of the raw materials in accordance with the most recent version of ASTM C114 or in accordance with any other analysis method published by an organization listed in QC.1.5, or use the value of 0.2%.”;

(5) in QC.5, by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.5.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(6) in QC.6:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of the first paragraph of QC.6.2 preceding subparagraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by replacing subparagraphs a to c of subparagraph 2 of the first paragraph of QC.6.2 by the following:

“(a) in bone dry metric tons, when the quantity is expressed as a mass;

(b) in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;

(c) in kilolitres, when the quantity is expressed as a volume of liquid;”;

(c) by replacing “millions” in subparagraph 3 of the first paragraph of QC.6.2 by “thousands”;

(d) by inserting “annual” after “average” in subparagraph 4 of the first paragraph of QC.6.2;

(e) by inserting “and reported” after “calculated” in subparagraph 5 of the first paragraph of QC.6.2;

(f) by replacing QC.6.3.2 by the following:

“QC.6.3.2. Calculation by feedstock material balance

The annual CO<sub>2</sub> emissions attributable to the production of hydrogen may be calculated by feedstock material balance using equations 6-1 to 6-3, depending on the type of feedstock:

(1) in the case of feedstocks for which the quantity is expressed as a volume of gas, the emitter must use equation 6-1:

**Equation 6-1**

$$CO_2 = \sum_{j=1}^{12} Q_j \times CC_j \times \frac{MW}{MVC} \times 3.664 \times 1$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to the production of hydrogen, in metric tons;

j = Month;

Q<sub>j</sub> = Quantity of gaseous feedstock consumed in month *j*, in thousands of cubic metres at standard conditions, or in metric tons when a mass flowmeter is used;

CC<sub>j</sub> = Average carbon content of the feedstock based on the analysis results for month *j* and measured by an emitter in accordance with QC.6.4, in kilograms of carbon per kilogram of feedstock;

MW = Molecular weight of the feedstock, in kilograms per kilomole or, when a mass flowmeter is used to measure the flow, in metric tons per unit of time, replace

$\frac{MW}{\text{_____}}$  by 1;

MVC

MVC = Molar volume conversion factor (24.06 m<sup>3</sup> per kilomole at standard conditions);

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon;

1 = Conversion factor, kilograms to metric tons and thousands of cubic metres to cubic metres;

(2) in the case of feedstocks for which the quantity is expressed as a volume of liquid, the emitter must use equation 6-2:

### Equation 6-2

$$CO_2 = \sum_{j=1}^{12} Q_j \times CF_j \times 3.664$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to the production of hydrogen, in metric tons;

j = Month;

Q<sub>j</sub> = Quantity of raw material consumed in month *j*, in kilolitres;

CF<sub>j</sub> = Average carbon content of feedstock based on the analysis results for month *j* and measured by an emitter in accordance with QC.6.4, in metric tons of carbon per kilolitre of feedstock;

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon;

(3) in the case of feedstocks for which the quantity is expressed as a mass, the emitter must use equation 6-3:

### Equation 6-3

$$CO_2 = \sum_{j=1}^{12} Q_j \times CC_j \times 3.664$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to the production of hydrogen, in metric tons;

j = Month;

Q<sub>j</sub> = Quantity of raw material consumed in month *j*, in metric tons;

$CC_j$  = Average carbon content of the feedstock based on the analysis results for month  $j$  and measured by an emitter in accordance with QC.6.4, in kilograms of carbon per kilogram of feedstock;

3.664 = Ratio of molecular weights,  $CO_2$  to carbon.”;

(g) by replacing paragraph 5 of QC.6.4 by the following:

“(5) to measure the average carbon content of each type of feedstock, use an analysis method published by an organization listed in QC.1.5 or one of the following analysis methods:

(a) for solid feedstocks, the most recent version of ASTM D2013/D2013M “Standard Practice for Preparing Coal Samples for Analysis”, ASTM D2234/D2234M “Standard Practice for Collection of a Gross Sample of Coal”, ASTM D3176 “Standard Practice for Ultimate Analysis of Coal and Coke”, ASTM D6609 “Standard Guide for Part-Stream Sampling of Coal”, ASTM D6883 “Standard Practice for Manual Sampling of Stationary Coal from Railroad Cars, Barges, Trucks, or Stockpiles” or ASTM D7430 “Standard Practice for Mechanical Sampling of Coal”;

(b) for liquid feedstocks, the most recent version of ASTM D2597 “Standard Test Method for Analysis of Demethanized Hydrocarbon Liquid Mixtures Containing Nitrogen and Carbon Dioxide by Gas Chromatography”, ASTM D4057 “Standard Practice for Manual Sampling of Petroleum and Petroleum Products”, ASTM D4177 “Standard Practice for Automatic Sampling of Petroleum and Petroleum Products”, ISO 3170 “Petroleum Liquids—Manual sampling” or ISO 3171 “Petroleum liquids—Automatic pipeline sampling”;

(c) for gaseous feedstocks, the most recent version of UOP539 “Refinery Gas Analysis by Gas Chromatography” or GPA 2261 “Analysis for Natural Gas and Similar Gaseous Mixtures by Gas Chromatography.”;

(7) in QC.7:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of the first paragraph of QC.7.2 preceding subparagraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by striking out subparagraph *a* of subparagraph 1 of the first paragraph of QC.7.2;

(c) by inserting “and reported” after “calculated” in subparagraph *b* of subparagraph 1 of the first paragraph of QC.7.2;

(d) by replacing subparagraph *h* of subparagraph 2 of the first paragraph of QC.7.2 by the following:

“(h) the average annual carbon content of the materials input for the production of metallurgical coke and of derivatives of those materials referred to in subparagraphs *b* to *g.1*, in metric tons of carbon per metric ton of material;”;

(e) by replacing subparagraph *h* of subparagraph 3 of the first paragraph of QC.7.2 by the following:

“(h) the average annual carbon content of the materials and products referred to in subparagraphs *b* to *g* that contribute 0.5% or more of the total carbon in the process, in metric tons of carbon per metric ton of material and products;”;

(f) by replacing subparagraph *f* of paragraph 4 of the first paragraph of QC.7.2 by the following:

“(f) the average annual carbon content of the materials and products referred to in subparagraphs *b* to *e* that contribute 0.5% or more of the total carbon in the process, in metric tons of carbon per metric ton of material and products;”;

(g) by replacing subparagraph *j* of paragraph 5 of the first paragraph of QC.7.2 by the following:

“(j) the average annual carbon content of the materials and products referred to in subparagraphs *b* to *j* that contribute 0.5% or more of the total carbon in the process, in metric tons of carbon per metric ton of material or product;”;

(h) by replacing “carbon content” in subparagraphs *c*, *d* and *f* of subparagraph 6 of the first paragraph of QC.7.2 by “average annual carbon content”;

(i) by replacing subparagraph *g* of subparagraph 7 of the first paragraph of QC.7.2 by the following:

“(g) the average annual carbon content of the materials and products referred to in subparagraphs *b* to *f* that contribute 0.5% or more of the total carbon in the process, in metric tons of carbon per metric ton of material or product;”;



(j) by replacing subparagraph *h* of subparagraph 8 of the first paragraph of QC.7.2 by the following:

“(h) the average annual carbon content of the materials and products referred to in subparagraphs *b* to *g* that contribute 0.5% or more of the total carbon in the process, in metric tons of carbon per metric ton of material and product;”;

(k) by inserting “, for each type of pellets” after “pellets” in subparagraph *a* of subparagraph 9 of the first paragraph of QC.7.2;

(l) by replacing subparagraph *e* of subparagraph 9 of the first paragraph of QC.7.2 by the following:

“(e) the average annual carbon content of the materials and products referred to in subparagraphs *b* to *d* that contribute 0.5% or more of the total carbon in the process, in metric tons of carbon per metric ton of material and product;”;

(m) by adding the following paragraph after the second paragraph of QC.7.2:

“Subparagraph *h.1* of subparagraph 2, subparagraph *i* of subparagraph 3, subparagraph *g* of subparagraph 4, subparagraph *k* of subparagraph 5, subparagraph *g* of subparagraph 6, subparagraph *h* of subparagraph 7 and subparagraph *i* of subparagraph 8 of the first paragraph do not apply to the CH<sub>4</sub> emissions of an emitter who calculates emissions using data from a continuous emission monitoring and recording system.”;

(n) by replacing equation 7-2 in paragraph 2 of QC.7.3.2, in by the following:

**“Equation 7-2**

$$CO_{2,COKE} = \left[ (CC \times C_{CC}) - (GOC \times C_{GOC}) - (MC \times C_{MC}) - (R \times C_R) - \sum_{i=1}^n (COB_i \times C_{COB,i}) \right] \times 3.664$$

Where:

CO<sub>2,COKE</sub> = Annual CO<sub>2</sub> emissions attributable to the production of metallurgical coke, in metric tons;

CC = Annual consumption of coking coal, in metric tons;

$C_{CC}$  = Average annual carbon content of coking coal, in metric tons of carbon per metric ton of coking coal;

$GOC$  = Quantity of coke oven gas transferred offsite during the year, in metric tons;

$C_{GOC}$  = Average annual carbon content of the coke oven gas transferred offsite during the year, in metric tons of carbon per metric ton of coke oven gas;

$MC$  = Annual production of metallurgical coke, in metric tons;

$C_{MC}$  = Average annual carbon content of the metallurgical coke produced, in metric tons of carbon per metric ton of metallurgical coke;

$R$  = Annual quantity of air pollution control residue collected, in metric tons;

$C_R$  = Average annual carbon content of air pollution control residue collected, in metric tons of carbon per metric ton of residue;

$COB_i$  = Quantity of coke oven by-product  $i$  transferred offsite during the year, in metric tons;

$C_{COB, i}$  = Average annual carbon content of coke oven by-product  $i$  transferred offsite during the year, in metric tons of carbon per metric ton of by-product  $i$ ;

$n$  = Number of coke oven by-products transferred offsite during the year;

$i$  = Type of by-product;

3.664 = Ratio of molecular weights,  $CO_2$  to carbon;"

(o) by replacing the words "carbon content", wherever they occur in the definitions of the factors for equations 7-3 to 7-9 in QC.7.3.2, by "average annual carbon content";

(p) in equation 7-4 in paragraph 4 of QC.7.3.2:

(i) by inserting ", and that contributes 0.5% or more of the total carbon in the process," after "oil" in the definition of the factor " $RM_j$ ";

(ii) by replacing the definition of the factor " $C_{RMj}$ " by the following:

“ $C_{RMj}$  = Average annual carbon content of raw material  $j$ , other than carbonaceous materials, required for sinter production, and that contributes 0.5% or more of the total carbon in the process, in metric tons of carbon per metric ton of raw material  $j$ ”;

(q) by inserting “and that contributes 0.5% or more of the total carbon in the process,” after “oil” in the definition of the factor “ $RM_j$ ” in equation 7-7 in paragraph 7 of QC.7.3.2;

(r) by inserting “and that contributes 0.5% or more of the total carbon in the process,” after “ore” in the definition of the factor “ $RM_j$ ” in equation 7-8 in paragraph 8 of QC.7.3.2;

(s) by replacing “in accordance with QC.1.3.4” in QC.7.4.1 by “in accordance with QC.1.4.5”;

(t) by replacing the part of QC.7.5.1 preceding paragraph 1 by the following:

“When the calculation method in QC.7.3.2 is used, an emitter who operates a facility or establishment that produces iron or steel or who operates the indurating of iron ore pellets must use the data provided by the supplier or determine the carbon content by analyzing a minimum of 3 representative samples per year, using an analysis method published by an organization listed in QC.1.5 or the following methods.”;

(u) by replacing paragraphs 3 to 7 of QC.7.5.1 by the following:

(3) for flux materials such as limestone or dolomite, using the most recent version of ASTM C25 “Standard Test Methods for Chemical Analysis of Limestone, Quicklime, and Hydrated Lime”;

(4) for coal, coke and the carbon electrodes used in electric arc furnaces, using the most recent version of ASTM D5373 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal” or, for fuels, raw materials or liquid products, the most recent version of ASTM D7582 “Standard Test Methods for Proximate Analysis of Coal and Coke by Macro Thermogravimetric Analysis”;

(5) for iron and ferrous scrap, using the most recent version of ASTM E1019 “Standard Test Methods for Determination of Carbon, Sulfur, Nitrogen, and Oxygen in Steel, Iron, Nickel, and Cobalt Alloys by Various Combustion and Fusion Techniques”;

(6) for the steel produced, using one of the following methods:

(a) the most recent version of ASM CS-104 UNS G10460 “Carbon Steel of Medium Carbon Content” published by ASM International;

(b) the most recent version of ISO/TR 15349-1 “Unalloyed steel – Determination of low carbon content, Part 1: Infrared absorption method after combustion in an electric resistance furnace (by peak separation)”;

(c) the most recent version of ISO/TR 15349-3 “Unalloyed steel – Determination of low carbon content, Part 3: Infrared absorption method after combustion in an electric resistance furnace (with preheating)”;

(d) the most recent version of ASTM E415 “Standard Test Method for Atomic Emission Vacuum Spectrometric Analysis of Carbon and Low-Alloy Steel”;

(7) for baked or greenball iron ore pellets, using the most recent version of ASTM E1915 “Standard Test Methods for Analysis of Metal Bearing Ores and Related Materials for Carbon, Sulfur, and Acid-Base Characteristics”;

(8) in QC.8:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.8.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by striking out paragraph 1 of QC.8.2;

(c) by replacing “lime production process” in paragraph 2 of QC.8.2 by “production process for each type of lime”;

(d) by replacing subparagraph *b* of paragraph 3 of QC.8.2 by the following:

“(b) the annual production of each type of lime, in metric tons;”;

(e) by striking out subparagraphs *c* and *d* of paragraph 3 of QC.8.2;

(f) by replacing “quarterly” in subparagraph *b* of paragraph 4 of QC.8.2 by “annual”;

(g) by striking out subparagraphs *c* and *d* of paragraph 4 of QC.8.2;

(h) by striking out “calculated in accordance with paragraph 2 of QC.8.3.2, (2),” in paragraph 5 of QC.8.2;

(i) by inserting “and reported” after “calculated” in paragraph 6 of QC.8.2;

(j) by adding the following paragraph at the end of QC.8.2:

“Subparagraphs *a* of paragraphs 3 and 4 of the first paragraph do not apply to the emissions of an emitter who calculates emissions using data from a continuous emission monitoring and recording system.”;

(k) by replacing “**emissions from kilns**” in the heading of QC.8.3 by inserting “, **CH<sub>4</sub> and N<sub>2</sub>O emissions**”;

(l) by replacing the paragraph of QC.8.3 preceding QC.8.3.1 by the following paragraphs:

“The annual CO<sub>2</sub> emissions, other than combustion emissions, attributable to the use of kilns must be calculated in accordance with one of the 2 calculation methods in QC.8.3.1 and QC.8.3.2.

The annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O attributable to the combustion of fuels in kilns must be calculated in accordance with QC.8.3.3.”;

(m) by replacing the part of QC.8.3.2 preceding paragraph 1, and paragraph 1 preceding equation 8-1, by the following:

“The annual CO<sub>2</sub> emissions attributable to the use of kilns must be calculated, pour each type of lime, using equations 8-1 to 8-3:”;

(n) by striking out the part of subparagraph *a* preceding equation 8-2 of QC.8.3.2;

(o) by striking out the part of subparagraph *b* preceding equation 8-3 of QC.8.3.2;

(p) by replacing paragraph 2 of QC.8.3.2 by the following:

“QC.8.3.3. Calculation of the emissions attributable to the combustion of fuels in kilns

The CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to the combustion of fuels in kilns must be calculated and reported in accordance with the calculation methods in QC.1. When pure biomass fuels, in other words fuels constituted of the same substance for at least 97% of their total weight, are consumed only during start-up, shut-down, or malfunction operating periods for the apparatus or units, the emitter may calculate CO<sub>2</sub> emissions using the calculation method in QC.1.3.1.”;

(q) by inserting “and who uses the method in QC.8.3.2” after “lime” in the part of QC.8.4 preceding paragraph 1;

(r) by replacing paragraph 1 of QC.8.4 by the following:

“(1) collect at least one sample each month for each type of lime produced during the month and determine the monthly content of calcium oxide and of magnesium oxide in each type of lime using the most recent version of ASTM C25 “Standard Test Methods for Chemical Analysis of Limestone, Quicklime, and Hydrated Lime” or the most recent revision of the National Lime Association’s “CO<sub>2</sub> Emissions Calculation Protocol for the Lime Industry”, or using any other analysis method published by an organization listed in QC.1.5.”;

(s) by replacing paragraph 6 of QC.8.4 by the following:

“(6) follow the quality assurance/quality control procedures in the most recent revision of the National Lime Association’s “CO<sub>2</sub> Emissions Calculation Protocol for the Lime Industry” published by la National Lime Association.”;

(9) in QC.9:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.9.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by inserting “and reported” after “calculated” in paragraph 1 of QC.9.2;

(c) by striking out “, CH<sub>4</sub> and N<sub>2</sub>O” in paragraph 2 of QC.9.2;

(d) by inserting the following after paragraph 2 of QC.9.2:

“(2.1) the annual CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to catalyst regeneration, calculated in accordance with QC.9.3.1, in metric tons;”;

(e) by replacing paragraph 6 of QC.9.2 by the following:

“(6) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to the use of stationary combustion units that are not referred to in paragraphs 1 and 7, calculated and reported in accordance with QC.1, in metric tons;”;

(f) by inserting “and reported” after “calculated” in paragraph 6.1 of QC.9.2;

(g) by replacing subparagraphs *a* to *d* of paragraph 12 of QC.9.2 by the following:

“(a) in bone dry metric tons, when the quantity is expressed as a mass;

(b) in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;

(c) in kilolitres, when the quantity is expressed as a volume of liquid;”;

(h) by replacing subparagraphs *a* to *d* of paragraph 13 of QC.9.2 by the following:

“(a) in bone dry metric tons, when the quantity is expressed as a mass;

(b) in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;

(c) in kilolitres, when the quantity is expressed as a volume of liquid;”;

(i) by replacing paragraph 14 of QC.9.2 by the following:

“(14) the annual CO<sub>2</sub> emissions from coke calcining, calculated in accordance with QC.9.3.10, in metric tons;

(14.1) the annual CH<sub>4</sub> and N<sub>2</sub>O emissions from coke calcining, calculated in accordance with QC.9.3.10, in metric tons;”;

(j) by inserting “calculated in accordance with QC.9.3.11,” after “systems,” in paragraph 15 of QC.9.2;

(k) by inserting “calculated in accordance with QC.9.3.12,” after “operations,” in paragraph 16 of QC.9.2;

(l) by inserting “calculated in accordance with QC.9.3.13,” after “coking,” in paragraph 17 of QC.9.2;

(m) by replacing “, 14 and 17” by “and 14” in subparagraph a of paragraph 19 of QC.9.2;

(n) by replacing “3 to 5, 7 to 11, 15 and 16” in subparagraph c of paragraph 19 of QC.9.2 by “2.1, 3 to 5, 7 to 11, 14.1 and 15 to 17”;

(o) by replacing “the total” in paragraph 21 of QC.9.2 by “the annual total”;

(p) by replacing “ to QC.9.3.9” in QC.9.3 by “to QC.9.3.13”;

(q) by replacing equations 9-1 and 9-2 in subparagraph a of paragraph 1 of QC.9.3.1 by the following:

**“Equation 9-1**

$$CO_2 = \sum_{j=1}^n (CB_j)_n \times CC \times 3.664$$

Where:

$CO_2$  = Annual  $CO_2$  emissions attributable to the continuous regeneration of catalyst material in fluid catalytic cracking units and fluid cokers, in metric tons;

$n$  = Number of hours of operation during the year;

$j$  = Hour;

$CB_j$  = Hourly coke burn for hour  $j$ , calculated in accordance with equation 9-2 or determined by the emitter, in metric tons;

$CC$  = Carbon content of coke burned, in kilograms of carbon per kilogram of coke burned;

3.664 = Ratio of molecular weights,  $CO_2$  to carbon;

**Equation 9-2**

$$CB_j = \left( K_1 Q_r \times (\%CO_2 + \%CO) + K_2 Q_a - K_3 Q_r \times \left( \frac{\%CO}{2} + \%CO_2 + \%O_2 \right) + K_3 Q_{oxy} \times \%O_{2,oxy} \right) \times 0.001$$



Where:

$CB_j$  = Hourly coke burn, in metric tons;

$K_1, K_2, K_3$  = Material balance and conversion factors ( $K_1, K_2$  and  $K_3$ ) from Table 9-1 in QC.9.6;

$Q_r$  = Volumetric flow of regeneration gas before entering the antipollution system, calculated in accordance with equation 9-3 or measured continuously, in cubic metres per minute, at standard conditions and on a dry basis;

$\%CO_2$  =  $CO_2$  concentration in regenerator exhaust, in cubic metres of  $CO_2$  per cubic metre of regeneration gas on a dry basis, expressed as a percentage;

$\%CO$  = Concentration of carbon monoxide in regenerator exhaust, in cubic metres of carbon monoxide per cubic metre of regeneration gas on a dry basis, expressed as a percentage;

$Q_a$  = Volumetric flow of air to regenerator, in cubic metres per minute, at standard conditions and on a dry basis;

$\%O_2$  = Concentration of oxygen in regenerator exhaust, in cubic metres of oxygen per cubic metre of regeneration gas on a dry basis, expressed as a percentage;

$Q_{oxy}$  = Volumetric flow of oxygen to regenerator, in cubic metres per minute, at standard conditions and on a dry basis;

$\%O_{2,oxy}$  = Concentration of oxygen in enriched air stream inlet to regenerator, expressed as a percentage par volume on a dry basis;

0.001 = Conversion factor, kilograms to metric tons;"

(r) by replacing equation 9-4 of paragraph 2 of QC.9.3.1 by the following:

**"Equation 9-3.1**

$$CO_2 = \sum_{i=1}^n \left[ Q_r \times \left( \frac{\%CO_2 + \%CO}{100\%} \right) \right] \times \frac{44}{MVC} \times 0.001 \times 60$$

Where:

$CO_2$  = Annual  $CO_2$  emissions attributable to the continuous regeneration of catalyst material in fluid catalytic cracking units and fluid cokers, in metric tons;

$n$  = Number of hours of operation during the year;

$j$  = Hour;

$Q_r$  = Volumetric flow of regeneration gas from regenerator before entering the antipollution system, in cubic metres per minute, at standard conditions and on a dry basis;

$\%CO_2$  =  $CO_2$  concentration in regenerator exhaust, in cubic metres of  $CO_2$  per cubic metre of regeneration gas on a dry basis, expressed as a percentage;

$\%CO$  = Concentration of carbon monoxide in regenerator exhaust, in cubic metres of carbon monoxide per cubic metre of regeneration gas on a dry basis, expressed as a percentage or, if there is no post-combustion device, a percentage of 0;

44 = Molecular weight of  $CO_2$  in kilograms per kilomole;

MVC = Molar volume conversion factor (24.06  $m^3$  per kilomole at standard conditions);

0.001 = Conversion factor, kilograms to metric tons;

60 = Conversion factor, minutes to hours;";

(s) by replacing equation 9-4 of paragraph 2 of QC.9.3.1 by the following:

**“Equation 9-4**

$$CO_2 = \sum_{i=1}^n (CB_i)_n \times CC \times 3.664$$

Where:

$CO_2$  = Annual  $CO_2$  emissions attributable to periodic catalyst regeneration processes, in metric tons;

$n$  = Number of regeneration cycles during the year;

$i$  = Regeneration cycle;

$CB_i$  = Quantity of coke burned, in metric tons per regeneration cycle  $i$ ;

$C$  = Carbon content of coke burned, measured or estimated by the emitter, or using a default value of 0.94 kg of carbon per kilogram of coke burned;

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon;”;

(*t*) by replacing equation 9-5.1 in paragraph 4 of QC.9.3.1 by the following:

**“Equation 9-5.1**

$$CH_4 = CO_2 \times \frac{EF_{CH_4}}{EF_{CO_2}}$$

Where:

$CH_4$  = Annual CH<sub>4</sub> emissions from catalyst regeneration, in metric tons;

$CO_2$  = Annual CO<sub>2</sub> emissions from catalyst regeneration, calculated using equation 9-1, in metric tons;

$EF_{CH_4}$  = CH<sub>4</sub> emission factor, 2.8 x 10<sup>-3</sup> kg per gigajoule;

$EF_{CO_2}$  = CO<sub>2</sub> emission factor, namely 97 kg per gigajoule;”;

(*u*) by replacing equation 9-10 in paragraph 1 of QC.9.3.5 by the following:

**“Equation 9-10**

$$CO_2 = \left[ \sum_{p=1}^n \left( Flare_p \times \frac{MW_p}{MVC} \times CC_p \times 3.664 \right) \right] \times 0.98 \times 1$$

Where:

$CO_2$  = Annual CO<sub>2</sub> emissions attributable to the combustion of hydrocarbons in flares, in metric tons;

$n$  = Number of measurement periods; minimum of 52 for weekly measurements and maximum of 366 for daily measurements;

$p$  = Measurement period;

$\text{Flare}_p$  = Volume of gas directed to flares during measurement period  $p$ , in thousands of cubic metres at standard conditions;

$MW_p$  = Average molecular weight of flare gas combusted during measurement period  $p$ , in kilograms per kilomole or, when a mass flowmeter is used to measure flare gas flow in kilograms per measurement period, replace

$$\frac{MW_p}{MVC} \text{ by } 1.$$

If measurements are taken more frequently than daily, the arithmetic average of measurement values must be used;

$MVC$  = Molar volume conversion factor ( $24.06 \text{ m}^3$  per kilomole at standard conditions);

$CC_p$  = Average carbon content of flare gas combusted during measurement period  $p$ , in kilograms of carbon per kilogram of flare gas.

If measurements are taken more frequently than daily, the arithmetic average of measurement values must be used;

3.664 = Ratio of molecular weights,  $\text{CO}_2$  to carbon;

0.98 = Flare combustion efficiency;

1 = Conversion factor, kilograms to metric tons and thousands of cubic metres to cubic metres;"

(v) by replacing the definition of the factor " $\text{Flare}_p$ " in equation 9-11 of paragraph 2 of QC.9.3.5 by the following:

" $\text{Flare}_p$  = Volume of gas directed to flares during measurement period  $p$ , in thousands of cubic metres at standard conditions;"

(w) by replacing "cubic metres" in the definition of the factor " $\text{HHV}_p$ " in equation 9-11 of paragraph 2 of QC.9.3.5 by "thousand cubic metres";

(x) by replacing equation 9-12 of paragraph 2 of QC.9.3.5 by the following:

**“Equation 9-12**

$$Flare_p = Flare_p (kg) \times \frac{MVC}{MW_p} \times 0.001$$

Where:

Flare<sub>p</sub> = Volume of gas directed to flares during measurement period *p*, in thousands of cubic metres;

Flare<sub>p</sub> (kg) = Masse of flare gas combusted during measurement period *p*, in kilograms;

MVC = Molar volume conversion factor (24.06 m<sup>3</sup> per kilomole at standard conditions);

MW<sub>p</sub> = Average molecular weight of flare gas combusted during measurement period *p*, in kilograms per kilomole;

0.001 = Conversion factor, cubic metres to thousands of cubic metres;”;

(y) by replacing equation 9-13 in paragraph 3 of QC.9.3.5 by the following:

**“Equation 9-13**

$$CO_2 = \left[ \sum_{p=1}^n (Flare_{SSM})_p \times \frac{MW_p}{MVC} \times CC_p \times 3.664 \right] \times 0.98 \times 1$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to the combustion of hydrocarbons in flare during startup, shutdown or malfunctions, in metric tons;

*n* = Annual number of startups, shutdowns or malfunctions;

*p* = Startup, shutdown or malfunction period;

(Flare<sub>SSM</sub>)<sub>p</sub> = Volume of gas directed to flare during startup, shutdown or malfunction period *p*, in thousands of cubic metres at standard conditions;

$MW_p$  = Average molecular weight of flare gas combusted during measurement period  $p$ , in kilograms per kilomole;

$MVC$  = Molar volume conversion factor (24.06 m<sup>3</sup> per kilomole at standard conditions);

$CC_p$  = Average carbon content of flare gas combusted during measurement period  $p$ , in kilograms of carbon per kilogram of flare gas;

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon;

0.98 = Flare combustion efficiency;

1 = Conversion factor, kilograms to metric tons and thousands of cubic metres to cubic metres;";

(z) by replacing equation 9-16 in paragraph 6 of QC.9.3.5 by the following:

**“Equation 9-16**

$$CO_2 = \sum_{p=1}^n \left( GV_p \times CC_p \times \frac{MW_p}{MVC} \right) \times 3.664 \times 1$$

Where:

$CO_2$  = Annual CO<sub>2</sub> emissions attributable to the combustion of low Btu gases, in metric tons;

$n$  = Total number of low Btu gases;

$p$  = Low Btu gas;

$GV_p$  = Annual volume of gas  $p$ , in thousands of cubic metres at standard conditions or in kilograms for a mass balance;

$CC_p$  = Carbon content of gas  $p$ , in kilograms of carbon per kilogram of gas;

$MW_p$  = Molecular weight of gas  $p$  in kilograms per kilomole or, when a mass flowmeter is used to measure the flow of gas  $p$  in kilograms, replace

$$\frac{MW_p}{MVC} \text{ by } 1;$$

MVC = Molar volume conversion factor (24.06 m<sup>3</sup> per kilomole at standard conditions);

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon;

1 = Conversion factor, kilograms to metric tons and thousands of cubic metres to cubic metres.”;

(aa) by replacing equation 9-17 in subparagraph *b* of paragraph 1 of QC.9.3.6 by the following:

**“Equation 9-17**

$$CH_4 = Q_{pb} \times 6.29 \times 10^{-7}$$

Where:

CH<sub>4</sub> = Annual CH<sub>4</sub> emissions from storage tanks, in metric tons;

Q<sub>pb</sub> = Annual quantity of crude oil and intermediate products received from off-site that are processed at the establishment, in kilolitres;

6.29 x 10<sup>-7</sup> = Default emission factor for storage tanks, in metric tons of CH<sub>4</sub> per kilolitre;”;

(bb) by replacing equation 9-18 in subparagraph *b* of paragraph 2 of QC.9.3.6 by the following:

**“Equation 9-18**

$$CH_4 = (2.57 \times 10^{-5}) \times Q_{un} \times \Delta P \times MF_{CH_4} \times \frac{16}{MVC} \times 1$$

Where:

CH<sub>4</sub> = Annual CH<sub>4</sub> emissions from storage tanks, in metric tons;

2.57 x 10<sup>-5</sup> = Equation correlation factor, in thousands of cubic metres at standard conditions, per kilolitre per kilopascal;

Q<sub>un</sub> = Annual quantity of unstabilized crude oil, in kilolitres;

ΔP = Pressure differential from storage pressure to atmospheric pressure, in kilopascals;

$MF_{CH_4}$  = Mole fraction of  $CH_4$  in vent gas from the unstabilized crude oil storage tank, measured by the emitter, in kilomoles of  $CH_4$  per kilomole of gas, or a value of 0.27;

16 = Molecular weight of  $CH_4$ , in kilograms per kilomole;

MVC = Molar volume conversion factor (24.06 m<sup>3</sup> per kilomole at standard conditions);

1 = Conversion factor, kilograms to metric tons and thousands of cubic metres to cubic metres.”;

(cc) by inserting the following heading in the French text before the heading of QC.9.4.1:

**“QC.9.4. Exigences d'échantillonnage, d'analyse et de mesure »;**

(dd) by replacing “utilisée” in the French text of the part of paragraph 3 of QC.9.4.1 preceding subparagraph a by “utilisés”;

(ee) by replacing subparagraphs 2 and 3 of the first paragraph of QC.9.4.5 by the following:

“(2) if using equation 9-10 or 9-13, measure the parameters used to determine the carbon content of the flare gas daily;

(3) if using equation 9-11, measure the parameters used to determine the high heat value of the flare gas daily.”;

(ff) by replacing paragraphs 1 to 3 of QC.9.4.9 by the following:

“(1) the most recent version of ASTM D3176 “Standard Practice for Ultimate Analysis of Coal and Coke”;

(2) the most recent version of ASTM D5291 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants”;

(3) the most recent version of ASTM D5373 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal”;

(4) any other analysis method published by an organization listed in QC.1.5.”;

(10) in QC.10:



(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.10.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by inserting “and reported” after “calculated” in paragraphs 1, 2, 3, 3.1, 4 and 7 of QC.10.2;

(c) by replacing “the annual” in paragraph 9 of QC.10.2 by “the total annual”;

(d) by replacing “paragraph 2” in subparagraph c of paragraph 9 of QC.10.2 by “paragraphs 2 and 7”;

(e) by replacing QC.10.3 by the following:

**“QC.10.3. Calculation methods for CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions**

To calculate the CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions from biomass, the high heat value or carbon content of the biomass must be determined by the emitter in accordance with QC.10.4.”;

(f) by inserting “the most recent version of” after “with” in subparagraph a of paragraph 1 of QC.10.4;

(g) by replacing subparagraph b of paragraph 1 of QC.10.4 by the following:

“(b) by measuring it using monthly data from a monitoring device installed on the process line;

(c) by determining it using equation 1-8;

(d) by using any other analysis method published by an organization listed in QC.1.5.”;

(h) by replacing paragraphs 1.1 and 2 of QC.10.4 by the following:

“(1.1) determine the high heat value of the black liquor using the most recent version of TAPPI T 684 om-11 “Gross heating value of black liquor”, or using any other analysis method published by an organization listed in QC.1.5;

(2) measure the monthly carbon content of the black liquor using the most recent version of ASTM D5373 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal” or ASTM 5291 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricant”, or using any other analysis method published by an organization listed in QC.1.5;”;

(i) by striking out paragraphs 3 and 4 of QC.10.4;

(11) in QC.11:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.11.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by inserting “and reported” after “calculated” in paragraph 2 of QC.11.2;

(c) by replacing “monthly” in paragraph 3 of QC.11.2 by “annual”;

(d) by replacing paragraph 1 of QC.11.4 by the following:

“(1) determine the monthly inorganic carbon content of the trona or sodium carbonate from a weekly composite sample for each production unit using the most recent version of ASTM E359 e1 “Standard Test Methods for Analysis of Soda Ash (Sodium Carbonate(e))”, or using any other analysis method published by an organization listed in QC.1.5;”;

(12) in QC.12:

(a) by inserting “and reported” after “calculated” wherever it occurs in the second paragraph of QC.12.1;

(b) by replacing “chloruration” in the French text of the third paragraph of QC.12.1 by “chloration”;

(c) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.12.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(d) by inserting “and reported” after “calculated” in paragraphs 1, 2 and 2.1 of QC.12.2;

(e) by replacing paragraph 3 of QC.12.2 by the following:

“(3) the annual CO<sub>2</sub> emissions attributable to each petrochemical process, in metric tons ;”;

(f) by striking out “, calculated in accordance with QC.12.3.2” in paragraph 4 of QC.12.2;

(g) by inserting the following after paragraph 4 of QC.12.2:

“(4.1) the annual CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to catalyst regeneration, in metric tons;”;

(h) by striking out “, calculated in accordance with QC.12.3.3” in paragraph 5 of QC.12.2;

(i) by striking out “, calculated in accordance with QC.12.3.4” in paragraph 6 of QC.12.2;

(j) by striking out “, calculated in accordance with QC.12.3.5” in paragraph 7 of QC.12.2;

(k) by striking out “calculated in accordance with QC.12.3.6” in paragraph 8 of QC.12.2;

(l) by replacing paragraphs 9 to 11 of QC.12.2 by the following:

“(9) the annual CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to wastewater treatment, calculated and reported in accordance with QC.9.3.7, in metric tons;

(10) the annual CH<sub>4</sub> emissions attributable to oil-water separators, calculated and reported in accordance with QC.9.3.8, in metric tons;

(11) the annual consumption of each type of raw material that emits CO<sub>2</sub>, CH<sub>4</sub> or N<sub>2</sub>O, expressed

(a) in metric tons, when the quantity is expressed as a mass;

(b) in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;

(c) in kilolitres, when the quantity is expressed as a volume of liquid;

(d) in bone dry metric tons, for biomass-derived solid fuels, when the quantity is expressed as a mass;”;

(m) by replacing “monthly” in paragraphs 12 and 13 of QC.12.2 by “annual”;

(n) by inserting “4.1 and” after “paragraphs” in subparagraph c of paragraph 15 of QC.12.2;

(o) by replacing “QC.12.3.8” in QC.12.3 by “QC.12.3.6”;

(p) by replacing QC.12.3.1 by the following:

“QC.12.3.1. Calculation of CO<sub>2</sub> emissions attributable to each petrochemical process

The annual CO<sub>2</sub> emissions attributable to each petrochemical process must be calculated in accordance with the following methods:

(1) where the quantity of feedstock and the quantity of product are expressed as volumes of gas, using equation 12-1:

**Equation 12-1**

$$CO_2 = \sum_{n=1}^{12} \left[ \sum_{i=1}^k \left[ (V_{GI})_{i,n} \times (C_{GI})_{i,n} \times \frac{(MM_{GI})_i}{MVC} \right] - \sum_{j=1}^m \left[ (V_{GP})_{j,n} \times (C_{GP})_{j,n} \times \frac{(MM_{GP})_j}{MVC} \right] \right] \times 3.664 \times 1$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to each petrochemical process, in metric tons;

n = Month;

k = Number of feedstock materials;

m = Number of products;

i = Type of feedstock the quantity of which is expressed as a volume of gas;

j = Type of product the quantity of which is expressed as a volume of gas;

(V<sub>GI</sub>)<sub>i,n</sub> = Quantity of feedstock *i* consumed in month *n*, in thousands of cubic metres at standard conditions;

$(C_{GI})_{i,n}$  = Average carbon content of feedstock  $i$  in for month  $n$ , in kilograms of carbon per kilogram of feedstock;

$(MM_{GI})_i$  = Monthly average molecular mass of feedstock  $i$ , in kilograms per kilomole or, when a mass flowmeter is used to measure the flow of gas input in metric tons for month  $n$ , replace

$MM_{GI}$   
\_\_\_\_\_ by 1;

$MVC$

$MVC$  = Molar volume conversion factor (24.06 m<sup>3</sup> per kilomole at standard conditions);

$(V_{GP})_{j,n}$  = Volume of product  $j$  produced in month  $n$ , in thousands of cubic metres at standard conditions;

$(C_{GP})_{j,n}$  = Average carbon content of product  $j$  produced in month  $n$ , in kilograms of carbon per kilogram of product;

$(MM_{GP})_j$  = Monthly average molecular mass of gas  $j$ , in kilograms per kilomole;

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon;

1 = Conversion factor, kilograms to metric tons and thousands of cubic metres to cubic metres;

(2) where the quantity of feedstock and the quantity of product are expressed as a mass, using equation 12-2:

### Equation 12-2

$$CO_2 = \sum_{n=1}^{12} \left[ \sum_{i=1}^k [(Q_F)_{i,n} \times (C_F)_{i,n}] - \sum_{j=1}^m [(Q_P)_{j,n} \times (C_P)_{j,n}] \right] \times 3.664$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to each petrochemical process, in metric tons;

$n$  = Month;

$k$  = Number of feedstock materials;

$m$  = Number of products;

$i$  = Type of feedstock material the quantity of which is expressed as a mass;

$j$  = Type of product the quantity of which is expressed as a mass;

$(Q_F)_{i,n}$  = Quantity of feedstock  $i$  consumed in month  $n$ , in metric tons;

$(C_F)_{i,n}$  = Average carbon content of feedstock  $i$  for month  $n$ , in kilograms of carbon per kilogram of feedstock;

$(Q_P)_{j,n}$  = Quantity of product  $j$  for month  $n$ , in metric tons;

$(C_P)_{j,n}$  = Average carbon content of product  $j$  for month  $n$ , in kilograms of carbon per kilogram of product;

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon.”;

(*q*) by inserting “, CH<sub>4</sub> and N<sub>2</sub>O” after “CO<sub>2</sub>” in the heading of QC.12.3.2 and in the paragraph following;

(*r*) by striking out QC.12.3.7, QC.12.3.8 and QC.12.4.4;

(13) in QC.13:

(*a*) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.13.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(*b*) by inserting “and reported” after “calculated” in paragraph 1.1 of QC.13.2;

(*c*) by inserting “carried out in accordance with QC.13.4” after “performance test *l*” in the definition of the factor “C<sub>N2O</sub>” in equation 13-2 of QC.13.3.1;

(*d*) by replacing “ASTM D6348-03 (2010)” in subparagraph *b* of paragraph 1 of the third paragraph of QC.13.4 by “the most recent version of ASTM D6348”;

(*e*) by inserting the following after subparagraph *b* of paragraph 1 of the third paragraph of QC.13.4:

“(b.1) any other analysis method published by an organization listed in QC.1.5.”;

(14) in QC.14:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.14.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by striking out paragraph 1 of QC.14.2;

(c) by replacing paragraph 2 of QC.14.2 by the following:

“(2) the annual CO<sub>2</sub> emissions attributable to the use in the furnace of each material that contributes 0.5% or more of the total carbon in the process, in metric tons.”;

(d) by inserting “and reported” after “calculated” in paragraph 2.1 of QC.14.2;

(e) by replacing paragraphs 3 and 4 of QC.14.2 by the following:

“(3) the annual quantity of each material that contributes 0.5% or more of the total carbon in the process, in metric tons;

(4) the average annual carbon content of each material that contributes 0.5% or more of the total carbon in the process, in metric tons of carbon per metric ton of material.”;

(f) by adding the following at the end of QC.14.2:

“Subparagraph 4 of the first paragraph does not apply to the CO<sub>2</sub> emissions of an emitter who calculates emissions using data from a continuous emission monitoring and recording system.”;

(g) by replacing the definition of the factor “M<sub>i</sub>” in equation 14-1 of QC.14.3.2 by the following:

“M<sub>i</sub> = Annual quantity of each material *i* used that contributes 0.5% or more of the total carbon in the process, in metric tons.”;

(h) by replacing “Carbon content” in the definition of the factor “CC<sub>i</sub>” in equation 14-1 of QC.14.3.2 by “Average annual carbon content”;

(i) by replacing “An emitter” in the part of QC.14.4 preceding paragraph 1 by “When the calculation method in QC.14.3.2 is used, an emitter”;

(j) by replacing paragraph 1 of QC.14.4 by the following:

“(1) determine annually the carbon content of each material that contributes 0.5% or more of the total carbon in the process used in the furnace, either by using the data provided by the material supplier or by using the following methods, based on a minimum of 3 representative samples per year:

(a) for solid carbonaceous reducing agents and carbon electrodes, using the most recent version of ASTM D5373 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal”, or using any other analysis method published by an organization listed in QC.1.5;

(b) for liquid reducing agents, using the most recent version of ASTM D2502 “Standard Test Method for Estimation of Molecular Weight (Relative Molecular Mass) of Petroleum Oils From Viscosity Measurements”, ASTM D2503 “Standard Test Method for Relative Molecular Mass (Molecular Weight) of Hydrocarbons by Thermoelectric Measurement of Vapor Pressure”, ASTM D3238 “Standard Test Method for Calculation of Carbon Distribution and Structural Group Analysis of Petroleum Oils by the n-d-M Method” or ASTM D5291 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants”, or using any other analysis method published by an organization listed in QC.1.5;

(c) for gaseous reducing agents, using the most recent version of ASTM D1945 “Standard Test Method for Analysis of Natural Gas by Gas Chromatograph” or ASTM D1946 “Standard Practice for Analysis of Reformed Gas by Gas Chromatography”, or using any other analysis method published by an organization listed in QC.1.5;

(d) for waste-based materials and ores, by sampling and chemical analysis using an analysis method published by an organization listed in QC.1.5.”;

(15) in QC.15:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.15.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular.”;



- (b) by striking out paragraph 1 of QC.15.2;
- (c) by replacing paragraph 2 of QC.15.2 by the following:  
“(2) the annual CO<sub>2</sub> emissions attributable to the use in the furnace of materials that contribute 0.5% or more of the total carbon in the process, in metric tons;”;
- (d) by inserting “and reported” after “calculated” in paragraph 2.1 of QC.15.2;
- (e) by replacing paragraphs 3 and 4 of QC.15.2 by the following:  
“(3) the annual quantity of each material that contributes 0.5% or more of the total carbon in the process, in metric tons;  
  
(4) the average annual carbon content of each material that contributes 0.5% or more of the total carbon in the process, in metric tons of carbon per metric ton of material;”;
- (f) by adding the following paragraph at the end of QC.15.2:  
“Subparagraph 4 of the first paragraph does not apply to the CO<sub>2</sub> emissions of an emitter who calculates emissions using data from a continuous emission monitoring and recording system.”;
- (g) by replacing the definition of the factor “M<sub>i</sub>” in equation 15-1 of QC.15.3.2 by the following:  
“M<sub>i</sub> = Annual quantity of each material *i* used that contributes 0.5% or more of the total carbon in the process, in metric tons;”;
- (h) by replacing “Carbon content” in the definition of the factor “CC<sub>i</sub>” in equation 15-1 of QC.15.3.2 by “Average monthly carbon content”;
- (i) by replacing “An emitter” in the part of QC.15.4 preceding paragraph 1 by “When the calculation method in QC.15.3.2 is used, an emitter”;
- (j) by replacing paragraph 1 of QC.15.4 by the following:  
“(1) determine annually the carbon content of each material that contributes 0.5% or more of the total carbon in the process, either by using the data provided by the supplier, or by using the following methods:

(a) for ores containing zinc, using the most recent version of ASTM E1941 “Standard Test Method for Determination of Carbon in Refractory and Reactive Metals and Their Alloys”, or using any other analysis method published by an organization listed in QC.1.5;

(b) for carbonaceous reducing agents and carbon electrodes, using the most recent version of ASTM D5373 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal”, or using any other analysis method published by an organization listed in QC.1.5;

(c) for flux materials, using the most recent version of ASTM C25 “Standard Test Methods for Chemical Analysis of Limestone, Quicklime, and Hydrated Lime”, or using any other analysis method published by an organization listed in QC.1.5;

(d) for waste-based materials and ores, by sampling and chemical analysis using an analysis method published by an organization listed in QC.1.5;”;

(16) in QC.16:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.16.2 preceding subparagraph 1 the first paragraph by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by replacing subparagraphs *a* to *d* of subparagraph 2 of the first paragraph of QC.16.2 by the following:

“(a) in bone dry metric tons, when the quantity is expressed as a mass;

(b) in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;

(c) in kilolitres, when the quantity is expressed as a volume of liquid;

(d) in bone dry metric tons, in the case of biomass fuels, when the quantity is expressed as a mass;

(e) in metric tons collected, in the case of municipal solid waste;”;

(c) by inserting “annual” after “average” in subparagraph 3 of the first paragraph of QC.16.2;

(d) by inserting “annual” after “average” in subparagraph 4 of the first paragraph of QC.16.2;

(e) by replacing subparagraphs *a* to *c* of subparagraph 4 of the first paragraph of QC.16.2 by the following:

“(a) in gigajoules per bone dry metric ton, in the case of a fuel whose quantity is expressed as a mass;

(b) in gigajoules per thousand cubic metres, in the case of a fuel whose quantity is expressed as a volume of gas;

(c) in gigajoules per kilolitre, in the case of a fuel whose quantity is expressed as a volume of liquid;

(d) in gigajoules per metric ton collected, in the case of municipal solid waste;”;

(f) by replacing “and acid gas reagent” in subparagraph 8 of the first paragraph of QC.16.2 by “for fluidized bed boilers”, and by inserting “for fluidized bed boilers” after “equipment” in subparagraph 12 of the first paragraph of QC.16.2;

(g) by replacing subparagraph 11 of the first paragraph of QC.16.2 by the following:

“(11) the annual fugitive emissions of CH<sub>4</sub> from coal storage calculated and reported in accordance with QC.5, in metric tons;”;

(h) by inserting “CO<sub>2</sub>” after “except” in subparagraph *b* of subparagraph 18 of the first paragraph of QC.16.2;

(i) by replacing “and 10” in subparagraph *c* of subparagraph 18 of the first paragraph of QC.16.2 by “, 10 and 11”;

(j) by striking out “, CH<sub>4</sub> and N<sub>2</sub>O” in the second paragraph of QC.16.3;

(k) by replacing “and QC.1.3.3” in subparagraph *a* of paragraph 7 of QC.16.3.2 by “or QC.1.3.3”;

(l) by inserting “for fluidized bed boilers” after “scrubbing” in QC.16.3.3;

(m) by adding the following paragraphs at the end of QC.16.4:

“For a facility or establishment with natural gas, diesel or heavy oil-powered units that are not individually equipped with a flowmeter or a dedicated tank and for which data cannot be obtained using a continuous emission monitoring and recording system, an emitter may calculate CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions using data from a measurement device common to all the units.

To calculate the emissions attributable to each stationary combustion unit, the estimate must be based on total emissions, the hours of operation and the combustion efficiency of each unit. For diesel-powered units, the estimate may be based on the total quantity of energy produced, the energy produced by each unit, and the total quantity of diesel fuel consumed.”;

(n) by adding “when the calculation method in QC.16.3.2 is used” at the end of QC.16.6.1 and QC.16.6.2;

(o) by inserting “who operates a fluid bed boiler equipped with a gas scrubber” after “emitter” in QC.16.6.3;

(17) in QC.17:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of the first paragraph of QC.17.2 preceding subparagraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by replacing subparagraph *b* of subparagraph 1 of the first paragraph of QC.17.2 by the following:

“(b) the annual total greenhouse gas emissions attributable to the production of electricity referred to in subparagraph *a*, calculated in accordance with QC.17.3.1, in metric tons CO<sub>2</sub> equivalent;”;

(c) by replacing “CO<sub>2</sub> emissions” in subparagraph *c* of subparagraph 1 of the first paragraph of QC.17.2 by “greenhouse gas emissions”;

(d) by replacing subparagraphs *v* and *vi* of subparagraph *c* of subparagraph 1 of the first paragraph of QC.17.2 by the following:

“(v) the annual greenhouse gas emissions attributable to the production of the electricity acquired from the facility, in metric tons CO<sub>2</sub> equivalent;

(vi) the annual greenhouse gas emissions of the facility, in metric tons CO<sub>2</sub> equivalent;”;

(e) by replacing “CO<sub>2</sub>” in subparagraphs *d* and *e* of subparagraph 1 of the first paragraph of QC.17.2 by “greenhouse gas”;

(f) by replacing subparagraph iii of subparagraph *e* of subparagraph 1 of the first paragraph of QC.17.2 by the following:

“(iii) the annual greenhouse gas emissions attributable to the electricity acquired, in metric tons CO<sub>2</sub> equivalent, by province or state;”;

(g) by replacing subparagraph *b* of subparagraph 2 of the first paragraph of QC.17.2 by the following:

“(b) the annual total greenhouse gas emissions caused or avoided by the exportation of the electricity, calculated in accordance with QC.17.3.2, in metric tons CO<sub>2</sub> equivalent;”;

(h) by replacing “CO<sub>2</sub>” in subparagraph *c* of subparagraph 2 of the first paragraph of QC.17.2 by “greenhouse gas”;

(i) by replacing subparagraph i of subparagraph *c* of subparagraph 2 of the first paragraph of QC.17.2 by the following:

“(i) the annual greenhouse gas emissions caused or avoided by the exportation of the electricity produced by the facility, in metric tons CO<sub>2</sub> equivalent;”;

(j) by replacing “CO<sub>2</sub>” in subparagraph *d* of subparagraph 2 of the first paragraph of QC.17.2 by “greenhouse gas”;

(k) by replacing subparagraph ii of subparagraph *d* of subparagraph 2 of the first paragraph of QC.17.2 by the following:

“(i) the annual greenhouse gas emissions caused or avoided by the exportation of the electricity produced by the facility, in metric tons CO<sub>2</sub> equivalent;”;

(l) by striking out the second paragraph of QC.17.2;

(m) by replacing “CO<sub>2</sub>” and “CO<sub>2</sub>” in QC.17.3 and in the heading to QC.17.3 by “greenhouse gas” and “**greenhouse gas**”, respectively;

(n) by replacing QC.17.3.1 and QC.17.3.2 by the following:

“QC.17.3.1. Calculation of greenhouse gas emissions attributable to the production of electricity acquired outside Québec and sold or consumed within Québec

The annual greenhouse gas emissions attributable to electricity produced outside Québec and sold or consumed within Québec must be calculated by adding the greenhouse gas emissions attributable to electricity acquired outside Québec and produced by identifiable and unidentifiable facilities which emissions are calculated in accordance with the following methods:

(1) for an identifiable facility covered by a greenhouse gas emissions report made to Environment Canada under section 71 of the Canadian Environmental Protection Act (1999) (1999, c. 33), the U.S. Environmental Protection Agency (USEPA) under Part 75 of Title 40 of the Code of Federal Regulations, or the organization The Climate Registry, using equation 17-1:

#### Equation 17-1

$$GHG = GHG_i \times \frac{MWh_{imp}}{MWh_n}$$

Where:

GHG = Annual greenhouse gas emissions attributable to the production of electricity acquired outside Québec and produced by the identifiable facility, in metric tons CO<sub>2</sub> equivalent;

GHG<sub>i</sub> = Annual greenhouse gas emissions attributable to the identifiable facility, in metric tons CO<sub>2</sub> equivalent;

MWh<sub>imp</sub> = Total quantity of electricity acquired from the identifiable facility and consumed or sold annually in Québec, including an estimate of transmission losses, from the facility's busbar, in megawatt-hours;

MWh<sub>n</sub> = Net annual production of electricity at the identifiable facility, in megawatt-hours;

(2) for an identifiable facility not covered by a greenhouse gas emissions report made to one of the organizations referred to in paragraph 1, using equation 17-2:

#### Equation 17-2

$$GHG = \sum_{j=1}^n (Q_j \times HHV_j \times EF_j) \times \frac{MWh_{imp}}{MWh_n}$$

Where:

GHG = Annual greenhouse gas emissions attributable to the production of electricity acquired outside Québec and produced by the identifiable facility, in metric tons CO<sub>2</sub> equivalent;

n = Number of fuels used annually by the facility;

j = Type of fuel;

Q<sub>j</sub> = Quantity of fuel *j*, expressed

- in bone dry metric tons, when the quantity is expressed as a mass;
- in kilolitres, when the quantity is expressed as a volume of liquid;
- in thousands of cubic metres, when the quantity is expressed as a volume of gas;

HHV<sub>j</sub> = High heat value of fuel *j* consumed for electricity production, as specified in Table 1-1 or 1-2 in QC.1.7, expressed

- in gigajoules per bone dry metric ton, when the quantity is expressed as a mass;
- in gigajoules per kilolitre, when the quantity is expressed as a volume of liquid;
- in gigajoules per thousand cubic metres, when the quantity is expressed as a volume of gas;

EF<sub>j</sub> = Greenhouse gas emission factor for fuel *j*, calculated using equation 17-2.1, in metric tons CO<sub>2</sub> equivalent per gigajoule;

MWh<sub>imp</sub> = Quantity of electricity acquired from the identifiable facility and consumed or sold annually in Québec, including an estimate of transmission losses, from the facility's busbar, in megawatt-hours;

MWh<sub>n</sub> = Net annual production of electricity at the identifiable facility, in megawatt-hours;

**Equation 17-2.1**

$$EF_j = [(EF_{CO_2} \times 1000) + (EF_{CH_4} \times 21) + (EF_{N_2O} \times 310)] \times 0.000001$$

Where:

$EF_j$  = Greenhouse gas emission factor for fuel  $j$ , in metric tons CO<sub>2</sub> equivalent per gigajoule;

$EF_{CO_2}$  = CO<sub>2</sub> emission factor for fuel  $j$  as specified in Table 1-2, 1-3, 1-4, 1-5 or 1-6 in QC.1.7, in kilograms of CO<sub>2</sub> per gigajoule;

1000 = Conversion factor, kilograms to grams;

$EF_{CH_4}$  = CH<sub>4</sub> emission factor for fuel  $j$  as specified in Table 1-2, 1-3, 1-4, 1-5 or 1-6 in QC.1.7, in grams of CH<sub>4</sub> per gigajoule;

21 = Global warming potential of CH<sub>4</sub>;

$EF_{N_2O}$  = N<sub>2</sub>O emission factor for fuel  $j$  as specified in Table 1-2, 1-3, 1-4, 1-5 or 1-6 in QC.1.7, in grams of N<sub>2</sub>O per gigajoule;

310 = Global warming potential of N<sub>2</sub>O;

0.000001 = Conversion factor, grams to metric tons;

(3) for an identifiable facility for which the information needed to calculate greenhouse gas emissions using equation 17-1 or 17-2 is not available, and for an unidentifiable facility, using equation 17-3:

**Equation 17-3**

$$GHG = MWh_{imp} \times EF_D$$

Where:

GHG = Annual greenhouse gas emissions attributable to the production of electricity acquired outside Québec and produced by the identifiable or unidentifiable facility, in metric tons CO<sub>2</sub> equivalent;

$MWh_{imp}$  = Quantity of electricity acquired from the identifiable or unidentifiable facility and consumed or sold annually in Québec, in megawatt-hours;



$EF_D$  = Greenhouse gas emission factor for the province or North American market from which the electricity comes, in metric tons of CO<sub>2</sub> per megawatt-hour, which is either

- indicated in Table 17-1 in QC.17.4;
- when the electricity comes from an identifiable nuclear, hydroelectric, sea current, wind, solar or tidal power facility, a factor of 0;
- when the electricity comes from a non-identifiable facility, a factor of 0.999.

QC.17.3.2. Calculation of greenhouse gas emissions caused or avoided by the exportation of the electricity

The annual greenhouse gas emissions caused or avoided by the exportation of the electricity must be calculated by adding the greenhouse gas emissions attributable to the exportation of electricity produced by identifiable facilities to the greenhouse gas emissions attributable to the exportation of electricity produced by unidentifiable facilities, using one of the following methods:

(1) for an identifiable facility covered by a greenhouse gas emissions report in accordance with QC.16, using equation 17-4:

**Equation 17-4**

$$GHG = GHG_t \times \frac{MWh_{exp}}{MWh_n} - (MWh_{exp} \times EF_D)$$

Where:

GHG = Annual greenhouse gas emissions caused or avoided by the exportation of the electricity produced by the identifiable facility, in metric tons CO<sub>2</sub> equivalent;

GHG<sub>t</sub> = Total annual greenhouse gas emissions attributable to the identifiable facility, in metric tons CO<sub>2</sub> equivalent;

MWh<sub>exp</sub> = Total quantity of electricity produced by the identifiable facility and exported annually, including an estimate of transmission losses, from the facility's busbar, in megawatt-hours;

MWh<sub>n</sub> = Net annual production of electricity at the identifiable facility, in megawatt-hours;

$EF_D$  = Greenhouse gas emission factor for the province or North American market where the electricity is delivered, as specified in Table 17-1 in QC.17.4, in metric tons CO<sub>2</sub> equivalent per megawatt-hour;

(2) for an identifiable facility not covered by a greenhouse gas emissions report in accordance with QC.16 and for an unidentifiable facility, using equation 17-5:

#### Equation 17-5

$$GHG = MWh_{\text{exp}} \times (EF_{QC} - EF_D)$$

Where:

GHG = Annual greenhouse gas emissions caused or avoided by the exportation of the electricity produced by the identifiable or unidentifiable facility, in metric tons CO<sub>2</sub> equivalent;

$MWh_{\text{exp}}$  = Quantity of electricity produced by the identifiable or unidentifiable facility and exported annually, in megawatt-hours;

$EF_{QC}$  = Greenhouse gas emission factor for Québec, as specified in Table 17-1 in QC.17.4, in metric tons CO<sub>2</sub> equivalent per megawatt-hour;

$EF_D$  = Greenhouse gas emission factor for the province or North American market where the electricity is delivered, in metric tons CO<sub>2</sub> equivalent per megawatt-hour, which is either

- indicated in Table 17-1 in QC.17.4;
- when the electricity comes from an identifiable nuclear, hydroelectric, sea current, wind, solar or tidal power facility, a factor of 0;
- when the electricity comes from a non-identifiable facility, a factor of 0.”;

(o) by replacing the heading of Table 17-1 in QC.17.4 by the following:

**“Table 17-1. Default greenhouse gas emission factors for Canadian provinces and certain North American markets, in metric tons CO<sub>2</sub> equivalent per megawatt-hour”;**

(p) by replacing the heading of Table 17-1 in QC.17.4 and the first 5 lines of the Table by the following:

“

Canadian province or North American market	Default emission factor (metric ton GHG /MWh)
Newfoundland and Labrador	0.021
Nova Scotia	0.850
New Brunswick	0.550
Québec	0.002
Ontario	0.100

“,

(18) in QC.18:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of the first paragraph of QC.18.2 preceding subparagraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by striking out subparagraph 1 of the first paragraph of QC.18.2;

(c) by inserting “and reported” after “calculated” in subparagraph 2 of the first paragraph of QC.18.2;

(d) by replacing “carbon content” in subparagraphs 9, 11, 13 and 15 of the first paragraph of QC.18.2 by “average annual carbon content”;

(e) by replacing subparagraphs 16 and 17 of the first paragraph of QC.18.2 by the following:

“(16) the annual consumption of each other raw material that contributes 0.5% or more of the total carbon in the process, in metric tons;

(17) the average annual carbon content of the other raw materials that contribute 0.5% or more of the total carbon in the process, in metric tons of carbon per metric ton of feedstock;”;

(f) by adding “When the emissions referred to in subparagraphs 3 to 7 of the first paragraph are measured by the same continuous emission monitoring and recording system, the emissions may be declared as a whole.” at the end of the second paragraph of QC.18.2;

(g) by replacing “carbon-containing raw materials” in the definition of the factor “ $CO_{2, RM}$ ” in equation 18-1 of paragraph 1 of QC.18.3.2 by “raw materials that contribute 0.5% or more of the total carbon in the process”;

(h) by replacing “Calcium carbonate content” in the definition of the factor “ $C_{LS}$ ” in equation 18-2 of paragraph 2 of QC.18.3.2 by “Average annual calcium carbonate content”;

(i) by replacing the definition of the factor “ $C_D$ ” in equation 18-2 of paragraph 2 of QC.18.3.2 by the following:

“ $C_D$  = Average annual calcium carbonate and magnesium carbonate content, in metric tons of carbonates per metric ton of dolomite;”;

(j) by replacing “Carbon content” in the definition of the factor “ $C_{RA}$ ” in equation 18-3 in paragraph 3, the definition of the factor “ $C_{ORE}$ ” in equation 18-4 in paragraph 4 and the definition of the factor “ $C_{CE}$ ” in equation 18-5 in paragraph 5 of QC.18.3.2 by “Average annual carbon content”;

(k) by replacing definition of the factor “ $CO_{2, RM}$ ” in equation 18-6 of paragraph 6 of QC.18.3.2 by the following:

“ $CO_{2, RM}$  = Annual  $CO_2$  emissions attributable to raw materials that contribute 0.5% or more of the total carbon in the process, in metric tons;”;

(l) by adding “that contribute 0.5% or more of the total carbon in the process” at the end of the definition of the factor “n” in equation 18-6 in paragraph 6 of QC.18.3.2;

(m) by replacing “, that contributes to 0.5%” in the definition of the factor “ $RM_i$ ” in equation 18-6 in paragraph 6 of QC.18.3.2 by “that contributes 0.5%”;

(n) by replacing “Carbon content” in the definition of the factor “ $C_{RM, i}$ ” in equation 18-6 in paragraph 6 of QC.18.3.2 by “Average annual carbon content”;

(o) by replacing “An emitter” in the part of QC.18.4 preceding paragraph 1 by “When the calculation method in QC.18.3.2 is used, an emitter”;

(p) by replacing paragraph 1 of QC.18.4 by the following:

“(1) when a calculation method in QC.18.3 is used, determine annually the carbon or carbonate content of each material used, either by using data from the material supplier or by using the following methods:

(a) for coal and coke, the most recent version of ASTM D5373 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal and Coke”, or any other analysis method published by an organization listed in QC.1.5;

(b) for petroleum-based liquid fuels and liquid waste-derived fuels, the most recent version of ASTM D5291 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants”, the elementary analysis method or calculations specified in the most recent version of ASTM D3238 “Standard Test Method for Calculation of Carbon Distribution and Structural Group Analysis of Petroleum Oils by the n-d-M Method”, and the most recent version of either ASTM D2502 “Standard Test Method for Estimation of Molecular Weight (Relative Molecular Mass) of Petroleum Oils From Viscosity Measurements” or ASTM D2503 “Standard Test Method for Relative Molecular Mass (Molecular Weight) of Hydrocarbons by Thermoelectric Measurement of Vapor Pressure”, or any other analysis method published by an organization listed in QC.1.5;

(c) for gaseous fuels, the most recent version of ASTM D1945 “Standard Test Method for Analysis of Natural Gas by Gas Chromatography” or ASTM D1946 “Standard Practice for Analysis of Reformed Gas by Gas Chromatography”, or any other analysis method published by an organization listed in QC.1.5;

(d) for limestone and dolomite, the most recent version of ASTM C25 “Standard Test Methods for Chemical Analysis of Limestone, Quicklime, and Hydrated Lime”, or any other analysis method published by an organization listed in QC.1.5;

(e) for other raw materials, any other analysis method published by an organization listed in QC.1.5;”;

(19) in QC.19:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of the first paragraph of QC.19.2 preceding subparagraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by striking out subparagraph 1 of the first paragraph of QC.19.2;

(c) by replacing “carbon-containing material” in subparagraph *d* of subparagraph 2 of the first paragraph of QC.19.2 by “material that contributes 0.5% or more of the total carbon in the process”;

(d) by replacing subparagraph e of subparagraph 2 of the first paragraph of QC.19.2 by the following:

“(e) the average annual carbon content of each material that contributes 1% or more of the total carbon in the process, in metric tons of carbon per metric ton of material;”;

(e) by inserting “and reported” after “calculated” in subparagraphs 3 and 4 of the first paragraph of QC.19.2;

(f) by replacing “Carbon content” in the definitions of the factors “ $C_{RA}$ ”, “ $C_{CE}$ ”, “ $C_{ORE}$ ”, “ $C_{MF}$ ”, “ $C_{FEA}$ ” and “ $C_{NAM}$ ” in equation 19-1 of QC.19.3.2 by “Average annual carbon content”;

(g) by replacing “An emitter” in the part of QC.19.5 preceding paragraph 1 by “When the calculation method in QC.19.3.2 is used, an emitter”;

(h) by replacing paragraph 1 of QC.19.5 by the following:

“(1) determine annually the carbon content of each material that contributes at least 1% of the total carbon in the process, based on either the data indicated by the supplier or the analysis of a minimum of 3 representative samples per year using any analysis method published by an organization listed in QC.1.5, or the following methods:

(a) for metal ores and ferroalloy products, the most recent version of ASTM E1941 “Standard Test Method for Determination of Carbon in Refractory and Reactive Metals and Their Alloys by Combustion Analysis”;

(b) for carbonaceous reducing agents and carbon electrodes, the most recent version of ASTM D5373 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal”;

(c) for flux materials, the most recent version of ASTM C25 “Standard Test Methods for Chemical Analysis of Limestone, Quicklime, and Hydrated Lime”;;

(i) by adding “, in metric tons of  $CH_4$  per metric ton of ferroalloy product” at the end of the heading of Table 19-1 in QC.19.7;

(20) in QC.20:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.20.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by inserting “and reported” after “calculated” in paragraph 2 of QC.20.2;

(c) by replacing “combustion” in subparagraph a of paragraph 7 of QC.20.2 by “greenhouse gas”;

(21) in QC.21:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.21.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by inserting “and reported” after “calculated” in paragraph 2 of QC.21.2;

(c) by adding the following paragraph at the end of QC.21.2:

“Subparagraph c of subparagraph 3 of the first paragraph does not apply to the N<sub>2</sub>O emissions of an emitter who calculates emissions using data from a continuous emission monitoring and recording system.”;

(d) by replacing “An emitter” in the part of QC.21.4 preceding paragraph 1 by “When the method in QC.21.3.2 is used, an emitter”;

(e) by replacing subparagraph ii of subparagraph b of paragraph 1 of QC.21.4 by the following:

“(ii) the most recent version of ASTM D6348 “Standard Test Method for Determination of Gaseous Compounds by Extractive Direct Interface Fourier Transform Infrared (FTIR) Spectroscopy”, or any other analysis method published by an organization listed in QC.1.5.”;

(f) by replacing “subparagraph b” in paragraph 2 of QC.21.4 by “subparagraph c”;

(22) in QC.22:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of the first paragraph of QC.22.2 preceding subparagraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by inserting “and reported” after “calculated” in subparagraph 2 of the first paragraph of QC.22.2;

(c) by replacing “monthly inorganic carbon” in subparagraph 4 of the first paragraph of QC.22.2 by “annual average inorganic carbon content”;

(d) by striking out “monthly and” in subparagraph 5 of the first paragraph of QC.22.2;

(e) by replacing “Carbon content” in the definition of the factor “ $C_i$ ” in equation 22-1 in QC.22.3.2 by “Monthly carbon content”;

(f) by replacing “An emitter” in the part of QC.22.4 preceding paragraph 1 by “When the calculation method in QC.22.3.2 is used, an emitter”;

(g) by adding “or any other analysis method published by an organization listed in QC.1.5” at the end of paragraph 2 of QC.22.4;

(23) in QC.23:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.23.2 preceding subparagraph 1 the first paragraph by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by inserting “and reported” after “calculated” in subparagraph 2 of the first paragraph of QC.23.2;

(c) by replacing subparagraph 3 of the first paragraph of QC.23.2 by the following:

“(3) the annual consumption of each raw material used in ammonia production, expressed

(a) in bone dry metric tons, when the quantity is expressed as a mass;

(b) in thousands of cubic metres at standard conditions, when the quantity is expressed as a volume of gas;

(c) in kilolitres, when the quantity is expressed as a volume of liquid;”;



(d) by replacing “monthly” in subparagraphs 4 and 7 of the first paragraph of QC.23.2 by “average annual”;

(e) by replacing “4 to 7” in the second paragraph of QC.23.2 by “4 and 7”;

(f) by replacing the definitions of “CO<sub>2, G</sub>”, “CO<sub>2, L</sub>” and “CO<sub>2, S</sub>” in equation 23-1 of QC.23.3.2 by the following:

“CO<sub>2, G</sub> = Annual CO<sub>2</sub> emissions attributable to ammonia production for production unit *k* from feedstock the quantity of which is expressed as a volume of gas, calculated in accordance with equation 23-2, in metric tons;

CO<sub>2, L</sub> = Annual CO<sub>2</sub> emissions attributable to ammonia production for production unit *k* from feedstock the quantity of which is expressed as a volume of liquid, calculated in accordance with equation 23-3, in metric tons;

CO<sub>2, S</sub> = Annual CO<sub>2</sub> emissions attributable to ammonia production for production unit *k* from feedstock the volume of which is expressed as a mass, calculated in accordance with equation 23-4, in metric tons;”;

(g) by replacing equations 23-2, 23-3 and 23-4 of QC.23.3.2 by the following:

**“Equation 23-2**

$$CO_{2,G} = \sum_{i=1}^{12} [Fdstk_i \times C_i] \times \frac{MW}{MVC} \times 3.664 \times 1$$

Where:

CO<sub>2, G</sub> = Annual CO<sub>2</sub> emissions attributable to ammonia production for production unit *k* from feedstock the quantity of which is expressed as a volume of gas, in metric tons;

*i* = Month;

Fdstk<sub>*i*</sub> = Consumption of feedstock the quantity of which is expressed as a volume of gas for month *i*, in thousands of cubic metres at standard conditions, or, when a mass flowmeter is used, in metric tons;

$C_i$  = Carbon content of feedstock the quantity of which is expressed as a volume of gas consumed in month  $i$ , in kilograms of carbon per kilogram of feedstock;

MW = Molecular weight of feedstock the quantity of which is expressed as a volume of gas, in kilograms per kilomole or, when a mass flowmeter is used, replace

$MW$   
\_\_\_\_\_ by 1;

MVC

MVC = Molar volume conversion factor (24.06 m<sup>3</sup> per kilomole at standard conditions);

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon;

1 = Conversion factor, kilograms to metric tons and thousands of cubic metres to cubic metres;

### Equation 23-3

$$CO_{2,L} = \sum_{i=1}^{12} [Fdstk_i \times C_i] \times 3.664$$

Where:

CO<sub>2,L</sub> = Annual CO<sub>2</sub> emissions attributable to ammonia production for production unit  $k$  from feedstock the quantity of which is expressed as a volume of liquid, in metric tons;

$i$  = Month;

Fdstk <sub>$i$</sub>  = Consumption of feedstock the quantity of which is expressed as a volume of liquid for month  $i$ , in kilolitres;

$C_i$  = Carbon content of the feedstock the quantity of which is expressed as a volume of liquid consumed in month  $i$ , in metric tons of carbon par kilolitre of feedstock;

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon;”;

### Equation 23-4

$$CO_{2,S} = \sum_{i=1}^{12} [Fdstk_i \times C_i] \times 3.664$$

Where:

$CO_{2,S}$  = Annual  $CO_2$  emissions attributable to ammonia production at production unit  $k$  from feedstock the quantity of which is expressed as a mass, in metric tons;

$i$  = Month;

$Fdstk_i$  = Consumption of feedstock the quantity of which is expressed as a mass for month  $i$ , in metric tons;

$C_i$  = Carbon content of the feedstock the quantity of which is expressed as a mass consumed in month  $i$ , in kilograms of carbon per kilogram of feedstock;

3.664 = Ratio of molecular weights,  $CO_2$  to carbon.”;

(h) by replacing equation 23-5 in QC.23.3.3 by the following:

“Equation 23-5

$$CO_{2,WR} = \sum_{i=1}^{12} [WRG_i \times C_i] \times \frac{MW}{MVC} \times 3.664 \times 1$$

Where:

$CO_{2,WR}$  = Annual  $CO_2$  emissions attributable to the combustion of gas from the waste recycle stream of each production unit, in metric tons;

$i$  = Month;

$WRG_i$  = Quantity of gas from the waste recycle stream for month  $i$ , in thousands of cubic metres at standard conditions or, when a mass flowmeter is used, in metric tons;

$C_i$  = Carbon content of gas from the waste recycle stream for month  $i$ , in kilograms of carbon per kilogram of gas;

$MW$  = Molecular weight of gas from the waste recycle stream, in kilograms per kilomole or, when a mass flowmeter is used, replace

$MW$   
\_\_\_\_\_ by 1;

$MVC$

$MVC$  = Molar volume conversion factor (24.06 m<sup>3</sup> per kilomole at standard conditions);

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon;

1 = Conversion factor, kilograms to metric tons and thousands of cubic metres to cubic metres.”;

(i) by replacing paragraph 2 of QC.23.4 by the following:

“(2) when the calculation method in QC.23.3.2 is used, determine monthly the carbon content and the average molecular weight of each feedstock consumed and of gas from the waste recycle stream, either by using data from the material supplier or by using one of the following methods:

(a) the most recent version of ASTM D1945 “Standard Test Method for Analysis of Natural Gas by Gas Chromatography”;

(b) the most recent version of ASTM D1946 “Standard Practice for Analysis of Reformed Gas by Gas Chromatography”;

(c) the most recent version of ASTM D2502 “Standard Test Method for Estimation of Molecular Weight (Relative Molecular Mass) of Petroleum Oils From Viscosity Measurements”;

(d) the most recent version of ASTM D2503 “Standard Test Method for Relative Molecular Mass (Molecular Weight) of Hydrocarbons by Thermoelectric Measurement of Vapor Pressure”;

(e) the most recent version of ASTM D3238 “Standard Test Method for Calculation of Carbon Distribution and Structural Group Analysis of Petroleum Oils by the n-d-M Method”;

(f) the most recent version of ASTM D5291 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants”;

(g) the most recent version of ASTM D3176 “Standard Practice for Ultimate Analysis of Coal and Coke”;

(h) the most recent version of ASTM D5373 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal”;

(i) any other analysis method published by an organization listed in QC.1.5.”;

(24) in QC.24:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.24.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by replacing “QC.24.3.1 and QC.24.3.2” in QC.24.3 by “QC.24.3.1 to QC.24.3.3”;

(c) by replacing equations 24-3 and 24-4 in QC.24.3.1 by the following:

**“Equation 24-3**

$$S_{ACQ} = S_{Cvl} + S_{Equip} + S_{Returned}$$

Where:

$S_{ACQ}$  = Quantity of gas  $j$  acquired during the year, contained in electrical equipment or storage containers, in kilograms;

$S_{Cvl}$  = Quantity of gas  $j$  acquired, contained in containers, in kilograms;

$S_{Equip}$  = Quantity of gas  $j$  acquired, contained in electrical equipment, in kilograms;

$S_{Returned}$  = Quantity of gas  $j$  returned to the enterprise after off-site recycling, in kilograms;

$j$  = Type of gas;

**Equation 24-4**

$$S_{SOLD} = S_{Sales} + S_{Returns} + S_{Destruct} + S_{Recyc}$$

Where:

$S_{\text{SOLD}}$  = Quantity of gas  $j$  sold or transferred to other facilities or establishments during the year, in storage containers or electrical equipment, in kilograms;

$S_{\text{Sales}}$  = Quantity of gas  $j$  sold to other facilities or establishments, including gas left in electrical equipment that is sold, in kilograms;

$S_{\text{Returns}}$  = Quantity of gas  $j$  returned to suppliers, in kilograms;

$S_{\text{Destruct}}$  = Quantity of gas  $j$  sent to destruction facilities, in kilograms;

$S_{\text{Recyc}}$  = Quantity of gas  $j$  sent off-site for recycling, in kilograms;

$j$  = Type of gas.”;

(d) by replacing equation 24-8 of QC.24.3.2 by the following:

“Equation 24-8

$$S_D = \sum_{i=1}^n (NC - S_C)_i$$

Where:

$S_D$  = Annual emissions of gas  $j$  during decommissioning phase of electrical equipment, in kilograms;

$n$  = Number of units of electrical equipment decommissioned during the year;

$i$  = Electrical equipment decommissioned;

$NC$  = Nameplate capacity of decommissioned electrical equipment  $i$ , in kilograms;

$S_C$  = Quantity of gas  $j$  collected from decommissioned electrical equipment  $i$ , in kilograms;

$j$  = Type of gas.”;

(e) by adding the following after QC.24.3.2:

“QC.24.3.3. Calculation of fugitive emissions by mass balance and by direct measurement

Fugitive SF<sub>6</sub> and PFC emissions may be calculated using a mixed method by applying the mass balance method to operations and the direct measurement method to decommissioned equipment.

For the purposes of the calculation, all quantities of SF<sub>6</sub> and PFC that cannot be accounted for are assumed to have been emitted.

The fugitive emissions must be calculated using equations 24-9 to 24-13:

#### Equation 24-9

$$GHG_i = (S_O - S_{REC} + S_{DC}) \times 0.001$$

Where:

GHG<sub>j</sub> = Annual emissions of gas *j* attributable to operations and to the decommissioning of electrical equipment, in metric tons;

S<sub>O</sub> = Annual emissions of gas *j* from electrical equipment during the operating phase, calculated using equation 24-10, in kilograms;

S<sub>REC</sub> = Annual quantity of gas *j* recovered from electrical equipment during the operating phase, calculated using equation 24-13, in kilograms;

S<sub>DC</sub> = Annual emissions of gas *j* from decommissioned electrical equipment, calculated using equation 24-8, in kilograms;

0.001 = Conversion factor, kilograms to metric tons;

*j* = Type of gas;

#### Equation 24-10

$$S_O = (S_{Empty}) \times (1 - f_{j,i})$$

Where:

S<sub>O</sub> = Annual emissions of gas *j* during operating phase of electrical equipment, in kilograms;

$S_{\text{Empty}}$  = Annual quantity of gas  $j$  contained in containers used for operations, expressed as the quantity initially contained in containers returned empty to the supplier, in kilograms;

$f_{j,i}$  = Fraction of gas  $j$  remaining in containers of type  $i$  returned empty to the supplier, calculated using equation 24-11 when the gas from the container is transferred to electrical equipment without a recovery system or using equation 24-12 when a recovery system is used transfer the gas from the container to the electrical equipment;

$i$  = Type of container;

$j$  = Type of gas;

#### Equation 24-11

$$f_{j,i} = \left( \frac{M_{\text{res},j}}{M_{\text{initial},j}} \right)$$

Where:

$f_{j,i}$  = Average fraction of gas  $j$  remaining in containers of type  $i$  returned empty to the supplier;

$M_{\text{res},j}$  = Average residual mass of gas  $j$  in empty containers, in kilograms;

$M_{\text{initial},j}$  = Initial mass of gas  $j$ , based on the average weight of gas indicated by the supplier, in kilograms;

$i$  = Type of container;

$j$  = Type of gas;

#### Equation 24-12

$$f_{j,i} = \left( \frac{P_{\text{discharge},j}}{P_{\text{charge},j}} \right)$$



Where:

$f_{j,i}$  = Average fraction of gas  $j$  remaining in containers of type  $i$  returned empty to the supplier;

$P_{\text{discharge},j}$  = Average discharge pressure of gas  $j$  in empty containers  $i$ , in kilopascals;

$P_{\text{charge},j}$  = Average charging pressure of gas  $j$  in container  $i$ , in kilopascals;

$i$  = Type of container;

$j$  = Type of gas;

### Equation 24-13

$$S_{REC} = S_{Destruct} + S_{Recyc}$$

Where:

$S_{REC}$  = Annual quantity of gas  $j$  recovered from electrical equipment during the operating phase, in kilograms;

$S_{Destruct}$  = Quantity of gas  $j$  sent to destruction facilities, in kilograms;

$S_{Recyc}$  = Quantity of gas  $j$  sent to off-site recycling facilities, in kilograms;

$j$  = Type of gas.”;

(f) by replacing “An emitter” in the part of QC.24.4 preceding paragraph 1 by “When using the calculation methods in QC.24.3.2 and QC.24.3.3, an emitter”;

(25) in QC.25:

(a) by inserting “for fluidized bed boilers” after “equipment” in the third paragraph of QC.25.1;

(b) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.25.2 preceding subparagraph 1 of the first paragraph by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(c) by replacing “the calcination” in subparagraph a of subparagraph 3 of the first paragraph of QC.25.2 by “the average annual calcination”;

(d) by replacing subparagraph 4 of the first paragraph of QC.25.2 by the following:

“(4) when the calculation method in QC.25.3.3 is used:

(a) the annual quantity of carbonate-based material output, in metric tons;

(b) the average annual carbonate content of each material input and output, in metric tons of carbonate per metric ton of material;”;

(e) by replacing “of the first paragraph does not apply” in the second paragraph of QC.25.2 by “and subparagraph *b* of subparagraph 4 of the first paragraph do not apply”;

(f) by replacing “Average annual content” in the definitions of the factors “ $CC_{j,i}$ ” in equations 25-1 and 25-2 of QC.25.3.2 by “Average annual content”;

(g) by replacing paragraphs 1 and 2 of QC.25.4 by the following:

“(1) when the calculation method in QC.25.3.2 is used, determine annually the calcination fraction for each carbonate used by sampling and chemical analysis, using an analysis method published by an organization listed in QC.1.5, or the value of 1.0;

(2) when the calculation method in QC.25.3.2 or QC.25.3.3 is used, determine the average annual carbonate content by calculating the arithmetic average of the monthly data obtained from raw material suppliers by sampling and chemical analysis using one of the following methods:

(a) the most recent version of ASTM C25 “Standard Test Methods for Chemical Analysis of Limestone, Quicklime, and Hydrated Lime”;

(b) the most recent version of ASTM C1301 “Standard Test Method for Major and Trace Elements in Limestone and Lime by Inductively Coupled Plasma-Atomic Emission Spectroscopy (ICP) and Atomic Absorption (AA)”;

(c) the most recent version of ASTM C1271 “Standard Test Method for X-ray Spectrometric Analysis of Lime and Limestone”;

(d) any other analysis method published by an organization listed in QC.1.5;

(e) the value of 1.0;”;

(26) in QC.26:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of the first paragraph of QC.26.2 preceding subparagraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by striking out subparagraph 1 of the first paragraph of QC.26.2;

(c) by striking out “, calculated in accordance with QC.25” in subparagraph 2 of the first paragraph of QC.26.2;

(d) by inserting “and reported” after “calculated” in subparagraph 4 of the first paragraph of QC.26.2;

(e) by replacing “moyenne annuelle en carbonates” in the French text of subparagraph 6 of the first paragraph of QC.26.2 by “en carbonates moyenne annuelle”;

(f) by striking out “2, 3,” in the second paragraph of QC.26.2;

(g) by replacing “An emitter” in the part of preceding paragraph 1 QC.26.4 by “When the calculation method in QC.26.3.2 is used, an emitter”;

(27) in QC.27:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.27.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by replacing paragraph 2 of QC.27.2 by the following:

“(2) the annual consumption of each fuel type, in kilolitres.”;

(c) by replacing “methods in QC.27.3.1 to QC.27.3.3” in the first paragraph of QC.27.3 by “method in QC.27.3.1”;

(d) by replacing QC.27.3.1 by the following:

“QC.27.3.1. Calculation of CO<sub>2</sub> emissions based on the quantity of fuel used

The annual CO<sub>2</sub> emissions attributable to mobile equipment used on-site at a facility or establishment must be calculated, for each type of fuel used, using equation 27-1:

**Equation 27-1**

$$CO_2 = Fuel \times EF \times 1000 \times 0.001$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to each type of fuel used by the mobile equipment, in metric tons;

Fuel = Annual volume of fuel used by the mobile equipment, in kilolitres;

EF = CO<sub>2</sub> emission factor for the fuel, as specified in Table 27-1 in QC.27.7, in kilograms per litre;

1000 = Conversion factor, litres to kilolitres;

0.001 = Conversion factor, kilograms to metric tons.”;

(e) by striking out QC.27.3.2 and QC.27.3.3;

(f) by replacing “methods in QC.27.4.1 to QC.27.4.3” in the first paragraph of QC.27.4 by “method in QC.27.4.1”;

(g) by replacing QC.27.4.1 by the following:

“QC.27.4.1. Calculation of CH<sub>4</sub> and N<sub>2</sub>O emissions based on the quantity of fuel consumed

The annual CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to mobile equipment used on-site at a facility or establishment must be calculated, for each type of fuel used, using equation 27-2:

**Equation 27-2**

$$CH_4 \text{ or } N_2O = Fuel \times EF \times 1000 \times 0.000001$$

Where:

CH<sub>4</sub> or N<sub>2</sub>O = Annual CH<sub>4</sub> or N<sub>2</sub>O emissions attributable to each fuel type used by the mobile equipment, in metric tons;

Fuel = Annual volume of fuel used by the mobile equipment, in kilolitres;

EF = CH<sub>4</sub> or N<sub>2</sub>O emission factor for the fuel, as specified in Table 27-1 in QC.27.7, in grams per litre;

1000 = Conversion factor, litres to kilolitres;

0.000001 = Conversion factor, grams to metric tons.”;

(h) by striking out QC.27.4.2 and QC.27.4.3;

(i) by replacing “quarterly” in paragraph 2 of QC.27.5 by “annually”;

(j) by replacing Table 27-1 by the following:

**“Table 27-1. Emission factors by fuel type**

(QC.27.3.1, QC.27.4.1)

Mobile equipment	CO <sub>2</sub> (kg/l)	CH <sub>4</sub> (g/l)	N <sub>2</sub> O (g/l)
Natural gas vehicle	1.89	0.009	0.00006
Propane vehicle	1.510	0.64	0.028
Gasoline vehicle	2.289	2.7	0.050
Diesel vehicle	2.663	0.15	1.1
Diesel train	2.663	0.15	1.1
Biodiesel vehicle	2.449	0.15	1.1
Ethanol vehicle	1.494	2.7	0.050

”;

(28) in QC.28:

(a) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.28.2 preceding paragraph 1 by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(b) by inserting “and reported” after “calculated” in paragraph 2 of QC.28.2;

(c) by replacing paragraph 2 of QC.28.4.1 by the following:

“(2) by measuring the residual weight or pressure of a container when replacing it and, when the pressure is measured, by determining the residual weight using equation 28-9:

**Equation 28-9**

$$W_{r,i} = \frac{M_i \times p_i \times V_i}{Z_i \times R \times T_i}$$

Where:

$W_{r,i}$  = Residual weight of gas  $i$ , in grams;

$M_i$  = Molar weight of gas  $i$ , in grams par mole;

$p_i$  = Absolute pressure of gas  $i$ , in pascals;

$V_i$  = Volume of gas  $i$ , in cubic metres;

$Z_i$  = Compressibility factor of gas  $i$ ;

$R$  = Perfect gas constant of 8.314 joules par kelvin-mole;

$T_i$  = Absolute temperature of gas  $i$ , in kelvin;”;

(29) in QC.29:

(a) by adding “but including the pipelines and equipment necessary for deliveries to a customer located close to a transmission pipeline” at the end of paragraph 5 of QC.29.1;

(b) by replacing “The greenhouse gas emissions report referred to in section 6.2 must” in the part of QC.29.2 preceding subparagraph 1 of the first paragraph by “In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular,”;

(c) by striking out subparagraph 1 of the first paragraph of QC.29.2;

(d) by inserting “and reported” after “calculated” in subparagraph 2 of the first paragraph of QC.29.2;

(e) by inserting “pneumatic” after “gas” in subparagraph ii of subparagraph a of subparagraph 3 of the first paragraph of QC.29.2;

(f) by replacing “QC.29.3.9” in subparagraph vi of subparagraph a and in subparagraphs d, i and j of subparagraph 3, in subparagraph v of subparagraph a and in subparagraph d of subparagraph 4, in subparagraph iii of subparagraph a and in subparagraph d of subparagraph 5, in subparagraph v of subparagraph a and in subparagraph d of subparagraph 6 and in subparagraph g of subparagraph 7 of the first paragraph of QC.29.2 by “QC.29.3.11”;

(g) by adding “or QC.29.3.8” at the end of subparagraph b of subparagraph 3 of the first paragraph of QC.29.2;

(h) by replacing subparagraph k of subparagraph 3 of the first paragraph of QC.29.2 by the following:

“(k) annual CO<sub>2</sub> and CH<sub>4</sub> emissions from natural gas transmission storage tanks, calculated in accordance with QC.29.3.10;

(l) annual CH<sub>4</sub> emissions attributable to third party pipeline hits, calculated in accordance with QC.29.3.9;”;

(i) by adding the following after subparagraph iv of subparagraph a of subparagraph 6 of the first paragraph of QC.29.2:

“(v) annual CH<sub>4</sub> emissions attributable to third party pipeline hits, calculated in accordance with QC.29.3.9;”;

(j) by inserting the following after subparagraph b of subparagraph 7 of the first paragraph of QC.29.2:

“(b.1) annual CO<sub>2</sub> and CH<sub>4</sub> fugitive emissions from above ground meters and regulators at regulation and measurement stations, including fugitive emissions from the station equipment components, calculated in accordance with QC.29.3.8;”;

(k) by replacing subparagraph f of subparagraph 7 of the first paragraph of QC.29.2 by the following:

“(f) annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions from transmission and distribution system flares and equipment flares connected to transmission and distribution system, calculated in accordance with QC.29.3.4;”;

(l) by striking out “to third party hits” in subparagraph h of subparagraph 7 of the first paragraph of QC.29.2;

(m) by adding the following after subparagraph h of subparagraph 7 of the first paragraph of QC.29.2:

“(i) annual fugitive CO<sub>2</sub> and CH<sub>4</sub> emissions from service line equipment, calculated in accordance with QC.29.3.8;

(j) annual CH<sub>4</sub> emissions attributable to third party pipeline hits, calculated in accordance with QC.29.3.9;

(k) annual venting emissions, namely:

(i) emissions from high bleed pneumatic devices and natural gas driven pumps, calculated in accordance with QC.29.3.1;

(ii) emissions from low bleed or intermittent bleed pneumatic devices, calculated in accordance with QC.29.3.2;

(iii) fugitive emissions from other sources, calculated in accordance with QC.29.3.11;”;

(n) by “and reported” after “calculated” in subparagraph 8 of the first paragraph of QC.29.2;

(o) by inserting the following after subparagraph *d* of subparagraph 9 of the first paragraph of QC.29.2:

“(d.1) the emission factors used in replacement of those specified in Tables 29-1 to 29-5 in QC.29.6;”;

(p) by replacing subparagraph ii of subparagraph *f* of subparagraph 9 of the first paragraph of QC.29.2 by the following:

“(ii) compressor nameplate capacity, in kilowatts;”;

(q) by replacing “le mode” in the French text of subparagraph iv of subparagraph *f* of subparagraph 9 of the first paragraph of QC.29.2 by “les modes”;

(r) by adding the following after subparagraph iv of subparagraph *f* of subparagraph 9 of the first paragraph of QC.29.2:

“(v) number of compressor starts during the year;”

(s) by adding the following after subparagraph ii of subparagraph *h* of subparagraph 9 of the first paragraph of QC.29.2:

“(iii) the number of third party pipeline hits, including a breakdown of hits by volume of gas emitted to the atmosphere;”;



(t) by replacing “QC.29.3.9” in the first paragraph of QC.29.3 by “QC.29.3.11”;

(u) by replacing “high bleed pneumatic device venting and natural gas driven pneumatic pump venting” in the part of QC.29.3.1 preceding equation 29-1 by “the venting of high bleed pneumatic devices, in other words devices with a venting flow rate above 0.17 m<sup>3</sup> per hour, and the venting of natural gas driven pneumatic pumps”;

(v) by replacing equations 29-1 to 29-4 of QC.29.3.1 by the following:

**“Equation 29-1**

$$GHG_i = GHG_{m,i} + GHG_{n-m,i}$$

Where:

GHG<sub>i</sub> = Annual emissions of greenhouse gas *i* attributable to high bleed pneumatic device venting and natural gas driven pneumatic pump venting, in metric tons;

GHG<sub>m,i</sub> = Annual emissions of greenhouse gas *i* attributable to high bleed pneumatic device venting and natural gas driven pneumatic pump venting, calculated using equation 29-2 when the annual volume of natural gas consumed by the devices or pumps is measured, in metric tons;

GHG<sub>n-m,i</sub> = Annual emissions of greenhouse gas *i* attributable to high bleed pneumatic device venting and natural gas driven pneumatic pump venting, when the annual volume of natural gas consumed by the devices or pumps is not measured, calculated using equation 29-3 for high bleed pneumatic devices and using equation 29-4 for natural gas driven pneumatic pumps, in metric tons;

*i* = CO<sub>2</sub> or CH<sub>4</sub>;

**Equation 29-2**

$$GHG_{m,i} = V_{NG} \times MF_i \times \frac{MW_i}{MVC} \times 0.001$$

Where:

$GHG_{m,i}$  = Annual emissions of greenhouse gas  $i$  attributable to high bleed pneumatic device venting or natural gas driven pneumatic pump venting, in metric tons;

$V_{NG}$  = Measured annual volume of natural gas consumed by the high bleed pneumatic devices or natural gas driven pneumatic pumps, in cubic metres at standard conditions;

$MF_i$  = Molar fraction of gas  $i$  in natural gas, determined in accordance with paragraph 3 of QC.29.4;

$MW_i$  = Molecular weight of gas  $i$ , in kilograms per kilomole or, when a mass flowmeter is used, replace

$MW$   
\_\_\_\_\_ by 1;

$MVC$

$MVC$  = Molar volume conversion factor (24.06 m<sup>3</sup> per kilomole at standard conditions);

0.001 = Conversion factor, kilograms to metric tons;

$i$  = CO<sub>2</sub> or CH<sub>4</sub>;

### Equation 29-3

$$GHG_{n-m,i} = \sum_{j=1}^n [D_j \times t_j] \times MF_i \times \rho_i \times 0.001$$

Where:

$GHG_{n-m,i}$  = Annual emissions of greenhouse gas  $i$  attributable to high bleed pneumatic device venting, in metric tons;

$n$  = Total number of high bleed pneumatic devices;

$j$  = High bleed pneumatic device;

$D_j$  = Natural gas flow for pneumatic device  $j$ , determined in accordance with paragraph 2 of QC.29.4.1 or using Table 29-6 in QC.29.6, in cubic metres per hour at standard conditions;

$t_j$  = Annual operating time for pneumatic device  $j$ , in hours;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in natural gas, determined in accordance with paragraph 3 of QC.29.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for CO<sub>2</sub> and 0.690 kg per cubic metre for CH<sub>4</sub> at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  = CO<sub>2</sub> or CH<sub>4</sub>;

#### Equation 29-4

$$GHG_{n-m,i} = \sum_{k=1}^m [Q_{NG,k} \times V_k] \times MF_i \times \rho_i \times 0.001$$

Where:

$GHG_{n-m,i}$  = Annual emissions of greenhouse gas  $i$  attributable to natural gas driven pneumatic pump venting, in metric tons;

$m$  = Total number of natural gas driven pneumatic pumps;

$k$  = Natural gas driven pneumatic pump;

$Q_{NG,k}$  = Quantity of natural gas consumed by the natural gas driven pneumatic pump  $k$ , determined in accordance with paragraph 3 of QC.29.4.1, in cubic metres per litre of liquid pumped at standard conditions;

$V_k$  = Annual volume of liquid pumped, in litres;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in natural gas, determined in accordance with paragraph 3 of QC.29.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for CO<sub>2</sub> and 0.690 kg per cubic metre for CH<sub>4</sub> at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  = CO<sub>2</sub> or CH<sub>4</sub>.”;

**Equation 29-5**

$$GHG_i = \sum_j [N_j \times EF_j \times t_j] \times MF_i \times \rho_i \times 0.001$$

Where:

GHG<sub>i</sub> = Annual emissions of greenhouse gas *i* attributable to low bleed or intermittent bleed natural gas pneumatic device venting, in metric tons;

*j* = Type of low bleed or intermittent bleed natural gas pneumatic device;

N<sub>*j*</sub> = Number of pneumatic devices *j* determined in accordance with QC.29.4.2;

EF<sub>*j*</sub> = Emission factor for pneumatic device *j* as specified in Tables 29-1 and 29-2 in QC.29.6, in cubic metres per hour at standard conditions, either

- indicated in Table 29-1, 29-2 or 29-6 in QC.29.6, for low bleed or intermittent bleed pneumatic devices that maintain operating conditions such as liquid level, pressure, pressure differential or temperature, or

- provided by the manufacturer for intermittent bleed pneumatic devices used for compressor startup;

t<sub>*j*</sub> = Annual operating time for pneumatic device *j*, in hours;

MF<sub>*i*</sub> = Molar fraction of greenhouse gas *i* in natural gas, determined in accordance with paragraph 3 of QC.19.4;

ρ<sub>*i*</sub> = Density of greenhouse gas *i*, of 1.893 kg per cubic metre for CO<sub>2</sub> and 0.690 kg per cubic metre for CH<sub>4</sub> at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

*i* = CO<sub>2</sub> or CH<sub>4</sub>;

(w) by replacing equation 29-6 of QC.29.3.3 by the following:

**“Equation 29-6**

$$GHG_i = \sum_{j=1}^n \left[ N_j \times V_j \times \left( \frac{T_{SC}}{T_B \times P_{SC}} \right) \times (P_{b1} - P_{b2}) \right] \times MF_i \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to natural gas emissions to the atmosphere from equipment blowdown vent stacks, in metric tons;

$n$  = Total number of types of equipment;

$j$  = Type of equipment with the same gas volume in the blowdown equipment chambers between isolation valves;

$N_j$  = Annual number of blowdowns for each equipment type  $j$ , determined in accordance with QC.29.4.3;

$V_j$  = Total volume of gas in blowdown equipment chambers, between isolation valves, for equipment type  $j$ , determined in accordance with QC.29.4.3, in cubic metres;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_B$  = Temperature at blowdown conditions, in kelvin;

$P_{b1}$  = Absolute pressure before blowdown, in kilopascals;

$P_{b2}$  = Absolute pressure after blowdown or a value of 0 if the purge gas used is not  $CO_2$  or  $CH_4$ , in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in natural gas, determined in accordance with paragraph 3 of QC.29.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for  $CO_2$  and 0.690 kg per cubic metre for  $CH_4$  at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $CO_2$  or  $CH_4$ .”;

(x) by replacing “pentanes plus” in the definition of the factor “CA<sub>k</sub>” in equation 29-7 of paragraph 1 of QC.29.3.4 by “pentane, 6 for hexane, and 7 for hexanes plus”;

(y) by inserting “at standard conditions” after “cubic metres” in the definition of “V<sub>G</sub>” and after “per cubic metre” in the definition of “HHV” in equation 29-9 in paragraph 3 of QC.29.3.4;

(z) by replacing equation 29-10 in paragraph 2 of QC.29.3.5 by the following:

**“Equation 29-10**

$$GHG_i = \sum_{j=1}^n \left[ \sum_{m=1}^z (F_{G,j} \times t_j)_m \times (1 - FG_j) \right] \times MF_i \times \left[ \frac{T_{SC} \times P_{cc}}{T_{cc} \times P_{SC}} \right]_j \times \rho_i \times 0.001$$

Where:

GHG<sub>i</sub> = Annual emissions of greenhouse gas *i* attributable to atmospheric centrifugal compressor vents, in metric tons;

*n* = Total number of centrifugal compressors;

*j* = Centrifugal compressor;

*m* = Operating mode of centrifugal compressor *j*;

*z* = Number of operating modes of centrifugal compressor *j*;

F<sub>G,j</sub> = Gas flow from the atmospheric vent of centrifugal compressor *j*, in operating mode *m*, determined in accordance with QC.29.4.5, in cubic metres per hour;

t<sub>j</sub> = Annual operating time of centrifugal compressor *j* equipped with a wet seal oil degassing tank, in operating mode *m*, in hours;

FG<sub>j</sub> = Portion of gas from the atmospheric vent of centrifugal compressor *j* that is recovered using a vapour recovery system or destined for another use, determined in accordance with QC.29.4.5, expressed as a percentage;

MF<sub>i</sub> = Molar fraction of greenhouse gas *i* in the gas from atmospheric vents, determined in accordance with paragraph 3 of QC.29.4;

T<sub>SC</sub> = Temperature at standard conditions of 293.15 kelvin;

$T_{cc}$  = Temperature at the atmospheric vent of centrifugal compressor, in kelvin;

$P_{cc}$  = Pressure at the atmospheric vent of centrifugal compressor, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for CO<sub>2</sub> and 0.690 kg per cubic metre for CH<sub>4</sub> at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  = CO<sub>2</sub> or CH<sub>4</sub>;

(aa) by replacing equation 29-11 of QC.29.3.6 by the following:

**“Equation 29-11**

$$GHG_i = \sum_{j=1}^n \left[ \sum_{m=1}^z (F_{G,j} \times t_j) \times (1 - FG_j) \right] \times MF_i \times \left[ \frac{T_{SC} \times P_{ca}}{T_{ca} \times P_{SC}} \right]_j \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to reciprocating compressor vents, in metric tons;

$n$  = Total number of reciprocating compressors;

$j$  = Reciprocating compressor;

$z$  = Number of operating modes of reciprocating compressor  $j$ ;

$m$  = Operating mode of reciprocating compressor  $j$ ;

$F_{G,j}$  = Gas flow from the venting of reciprocating compressor  $j$ , in operating mode  $m$ , determined in accordance with QC.29.4.6, in cubic metres per hour;

$t_j$  = Annual operating time of reciprocating compressor  $j$ , in operating mode  $m$ , in hours;

$FG_j$  = Quantity of gas from the vent of reciprocating compressor  $j$  that is recovered using a vapour recovery system, determined in accordance with paragraph 4 of QC.29.4.5, expressed as a percentage;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in gas from reciprocating compressor vents, determined in accordance with paragraph 3 of QC.29.4;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_{ca}$  = Temperature at the reciprocating compressor vent, in kelvin;

$P_{ca}$  = Pressure at the reciprocating compressor vent, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for  $CO_2$  and 0.690 kg per cubic metre for  $CH_4$  at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $CO_2$  or  $CH_4$ .”;

(bb) by replacing the part of QC.29.3.7 preceding paragraph 1 by the following:

“Except for emissions from emission sources for which the total weight of  $CO_2$  and  $CH_4$  in the natural gas is below 10%, which must be calculated in accordance with QC.29.3.11, the annual fugitive  $CO_2$  and  $CH_4$  emissions attributable to leaks identified following a leak detection survey must be calculated in accordance with the following methods:”;

(cc) by adding “, in the case of stations with emissions equal to or greater than 10,000 metric tons  $CO_2$  equivalent” at the end of subparagraph i of subparagraph c of paragraph 1 of QC.29.3.7;

(dd) in equation 29-12 in paragraph 2 of QC.29.3.7,

(i) by replacing the definition of the factor “ $N_j$ ” by the following

“ $N_j$  = Total number of components of type  $j$ .”;

(ii) by inserting “at standard conditions” after “cubic metres per hour” in the definition of the factor “ $EF_j$ ”;



(ee) in equation 29-13 in paragraph 2 of QC.29.3.7,

(i) by replacing the definition of the factor “ $N_j$ ” by the following

“ $N_j$  = Total number of components of type  $j$ ”;

(ii) by inserting “at standard conditions” after “metric tons per hour” in the definition of the factor “ $EF_j$ ”;

(ff) by replacing the heading of QC.29.3.8 and the part preceding paragraph 1 of QC.29.3.8 by the following:

“QC.29.3.8. Calculation of fugitive CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to all components not subject to a detection survey

Except for emissions from emission sources for which the total weight of CO<sub>2</sub> and CH<sub>4</sub> in the natural gas is below 10%, which do not need to be calculated, the annual fugitive CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to all components not subject to a detection survey must be calculated in accordance with the following methods:”;

(gg) by adding “in the case of stations with emissions below 10,000 metric tons CO<sub>2</sub> equivalent” at the end of subparagraph i of subparagraph b of paragraph 1 of QC.29.3.8;

(hh) in equation 29-14 in paragraphe 2 of QC.29.3.8,

(i) by replacing the definition of the factor “ $N_j$ ” by the following

“ $N_j$  = Total number of components of type  $j$  determined in accordance with QC.29.4.8;”;

(ii) by inserting “at standard conditions” after “cubic metres per hour” in the definition of the factor “ $EF_j$ ”;

(ii) by replacing the definition of the factor “ $N_j$ ” in equation 29-15 in paragraph 2 of QC.29.3.8 by the following:

“ $N_j$  = Total number of components of type  $j$ ”;

(jj) by replacing QC.29.3.9 by the following:

“QC.29.3.9. Calculation of CH<sub>4</sub> emissions attributable to third party pipeline hits

The annual CH<sub>4</sub> emissions attributable to third party pipeline hits that are equal to or greater than 1.416 m<sup>3</sup> of CH<sub>4</sub> at standard conditions, must be calculated using equations 29-16 and 29-17 for catastrophic pipeline ruptures and pipeline puncture incidents when, as determined under paragraph 1 of QC.29.4.9, the flow is choked and using equation 29-18 for pipeline puncture incidents when the flow is not choked.

### Equation 29-16

$$GHG_{CH_4} = \frac{3,6 \times 10^6 \times A}{\rho_{ref}} \times \sqrt{\frac{K \times MW}{1000 \times R \times T}} \times \frac{P_a \times M}{\left(1 + \frac{K-1}{2} M^2\right)^{\frac{K+1}{2(K-1)}}} \times t \times \left[ \frac{T_{SC} \times P_{ge}}{T_{ge} \times P_{SC}} \right] \times \rho_{ref} \times 0.001$$

Where:

GHG<sub>CH<sub>4</sub></sub> = Annual CH<sub>4</sub> emissions attributable to a third party pipeline hit or to a pipeline puncture incident when the flow is choked, in metric tons;

A = Cross-sectional flow area of the pipe, in square metres;

K = Specific heat ratio of CH<sub>4</sub>, namely 1.299;

MW = Molecular weight of CH<sub>4</sub>, namely 16.043 kg per mole;

M = Mach number of the flow, calculated using equation 29-17 when M is equal to or greater than 1 or a value of 1 in other cases, in metres per second;

ρ<sub>ref</sub> = Density of CH<sub>4</sub>, namely 0.690 kg per cubic metre at standard conditions;

T = Temperature inside pipe, in kelvin;

P<sub>a</sub> = Pressure inside the pipe, determined in accordance with paragraph 2 of QC.29.4.9, in kilopascals;

R = Universal gas constant, namely 8.3145 kPa m<sup>3</sup> per kilomole per kelvin;

t<sub>j</sub> = Duration of venting following hit, in hours;

T<sub>SC</sub> = Temperature at standard conditions of 293.15 kelvin;

$T_{ge}$  = Temperature of gas emitted, in kelvin;

$P_{ge}$  = Pressure of gas emitted, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

0.001 = Conversion factor, kilograms to metric tons;

### Equation 29-17

$$M = \sqrt{\frac{2 \left[ \left( \frac{P_a}{P_e} \right)^{\frac{K-1}{K}} - 1 \right]}{K-1}}$$

Where:

$M$  = Mach number of the flow, in metres per second;

$K$  = Specific heat ratio of  $CH_4$ , namely 1.299;

$P_a$  = Pressure inside the pipe, determined in accordance with paragraph 2 of QC.29.4.9, in kilopascals;

$P_e$  = Atmospheric pressure at the damage point, in kilopascals;

### Equation 29-18

$$CH_4 = \frac{A_e}{\rho_{ref}} \sqrt{\frac{2000 \times K}{K-1}} \times P_a \times \rho_a \times \left[ \left( \frac{P_{atm}}{P_a} \right)^{2/K} - \left( \frac{P_{atm}}{P_a} \right)^{(K+1)/K} \right] \times t_j \times \left[ \frac{T_{SC} \times P_{ge}}{T_{ge} \times P_{SC}} \right] \times \rho_{ref} \times 0.001$$

Where:

$CH_4$  = Annual  $CH_4$  emissions attributable to third party pipeline puncture incident when the flow is not choked, in metric tons;

$A_e$  = Size of the hole in the pipe, in square metres;

$K$  = Specific heat ratio of  $CH_4$ , namely 1.299;

$\rho_{ref}$  = Density of  $CH_4$ , namely 0.690 kg per cubic metre at standard conditions;

$\rho_a$  = Density of CH<sub>4</sub> inside the pipe at the puncture location, in kilograms per cubic metre;

$P_a$  = Pressure inside the pipe, determined in accordance with paragraph 3 of QC.29.4.9, in kilopascals;

$P_{atm}$  = Atmospheric pressure at the damage point, in kilopascals;

$R$  = Universal gas constant, namely 8.3145 kPa m<sup>3</sup> per kilomole per Kelvin;

$t_j$  = Duration of venting following puncture incident, in hours;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_{ge}$  = Temperature of gas emitted, in kelvin;

$P_{ge}$  = Pressure of gas emitted, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

0.001 = Conversion factor, kilograms to metric tons.

QC.29.3.10. Calculation of CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to transmission storage tanks

Except for emissions sent to flares, which must be calculated in accordance with QC.29.3.4 using the quantities measured in accordance with paragraph 1 of QC.29.4.10, the annual CH<sub>4</sub> and CO<sub>2</sub> emissions attributable to compressor scrubber dump valve leakage from condensate storage tanks for either water or hydrocarbon connected to transmission storage tanks, must be calculated using equation 29-19:

#### Equation 29-19

$$GHG_i = \sum_{j=1}^n [EF \times t]_j \times MF_i \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to compressor scrubber dump valve leakage from condensate storage tanks connected to transmission storage tanks, in metric tons;

$n$  = Number of equipments;

$j$  = Device;

$EF$  = Emission factor for leakage from device  $j$ , determined in accordance with QC.29.4.10, in metric tons per hour;

$t$  = Duration of leakage from device  $j$ , determined in accordance with QC.29.4.10, in hours;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in gas from reciprocating compressor vents, determined in accordance with paragraph 3 of QC.29.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for  $CO_2$  and 0.690 kg per cubic metre for  $CH_4$  at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $CO_2$  or  $CH_4$ .

#### QC.29.3.11. Calculation of fugitive emissions from other sources

Fugitive emissions from other sources that are not calculated using the methods in QC.29.3.1 to QC.29.3.10 must be calculated in accordance with the following methods:

(1) the methods in the most recent version of “Methodology Manuel: Estimation of Air Emissions from the Canadian Natural Gas Transmission, Storage and Distribution System” published by Clearstone Engineering Ltd.;

(2) a sector specific method published by the Canadian Gas Association.”;

(kk) by adding the following paragraph after paragraph 3 of QC.29.4:

“Beginning on 1 January 2015, all high bleed pneumatic devices and natural gas driven pneumatic pumps must be equipped with meters.”;

(ll) by replacing paragraph 1 of QC.29.4.1 by the following:

“(1) when using equation 29-2, determine the annual volume of natural gas consumed by high bleed pneumatic devices or natural gas driven pneumatic pumps using the measuring equipment installed on the device.”;

(mm) by adding “If there is no similar device, the emitter must perform the calculation using the data in Table 29-1 in QC.29.6;” at the end of paragraphs 2 and 3 of QC.29.4.1

(nn) by inserting “natural gas driven” after “each” in subparagraph *b* of paragraph 3 of QC.29.4.1;

(oo) by striking out paragraph 3 of QC.29.4.3;

(pp) by replacing “and pentane-plus” in subparagraph ii of subparagraph *b* of paragraph 2 of QC.29.4.4 by “, pentane, hexane and hexane-plus”;

(qq) by replacing paragraph 1 of QC.29.4.5 by the following:

“(1) determine the volume of gas from a wet seal oil degassing tank sent to an atmospheric vent or the volume of gas sent to a flare, using a temporary or permanent flow meter, for each operating mode, namely:

(a) the centrifugal compressor is in operating, standby pressurized mode and the gas emitted is from leaks in the blowdown vent stack;

(b) the centrifugal compressor is in operating mode;

(c) the centrifugal compressor is in not operating, depressurized mode; the gas emitted is from isolation valve leakage through the blowdown vent stack. In that case,

(i) a centrifugal compressor that is not equipped with blind flanges must be sampled at least once in every 3 consecutive years;

(ii) sampling is not required if a centrifugal compressor has been equipped with blind flanges for at least 3 consecutive years;

(rr) by inserting “for less than 200 hours per year” in paragraph 2 of QC.29.4.5 after “purpose”;

(ss) by replacing “is equipped with blind flanges for the entire 3 consecutive year period” in subparagraph ii of subparagraph *c* of paragraph 2 of QC.29.4.6 by “has been equipped with blind flanges for at least 3 consecutive years”;

(tt) by striking out subparagraph iii of subparagraph *c* of paragraph 2 of QC.29.4.6;

(uu) by adding the following after subparagraph *c* of paragraph 2 of QC.29.4.6:

“(d) the reciprocating compressor is used for peaking purposes for no more than 200 hours per year and is not equipped with a meter; the volume of gas must be determined using data from meters installed on similar equipment;”;

(vv) by replacing “the CO<sub>2</sub> and CH<sub>4</sub> concentrations in natural gas using one of” in the part of QC.29.4.7 preceding subparagraph a of paragraph 2 by “emission factor for leakage from each type of device using”;

(ww) by replacing subparagraph ii of subparagraph d of paragraph 2 of QC.29.4.8 by the following:

“(ii) emission factor calculated using equation 29-20 for above ground meters and regulators at non-custody transfer gate stations:

#### Equation 29-20

$$EF_i = \frac{GHG_i \times 1000}{N \times \rho_i \times 8760}$$

Where:

EF<sub>i</sub> = Enterprise-specific emission factor for above grade meters and regulators at non-custody transfer gate stations, in cubic metres per hour per component at standard conditions;

GHG<sub>i</sub> = Annual emissions of greenhouse gas *i* from leaks from above ground meters and regulators at custody transfer gate stations, calculated in accordance with equation 29-12, in metric tons;

N = Total number of components, namely above grade meters and regulators, at custody transfer gate stations;

ρ<sub>i</sub> = Density of greenhouse gas *i* that is 1.893 kg per cubic metre for CO<sub>2</sub> and 0.690 kg per cubic metre for CH<sub>4</sub> at standard conditions;

1000 = Conversion factor, metric tons to kilograms;

8760 = Conversion factor, years to hours;

*i* = CH<sub>4</sub> or CO<sub>2</sub>;”;

(xx) by adding the following after QC.29.4.8:

“29.4.9. Fugitive emissions from third party pipeline hits

For fugitive emissions attributable to third party pipeline hits, the emitter must

(1) for a pipeline puncture incident, determine whether or not the flow is choked using the following method:

If  $P_{atm} / P_a \geq 0.546$  flow is not choked;

If  $P_{atm} / P_a < 0.546$  flow is choked;

Where:

$P_a$  = Pressure inside the pipe, determined in accordance with paragraph 3 of QC.29.4.9, in kilopascals;

$P_{atm}$  = Atmospheric pressure at the damage point, in kilopascals;

(2) determine the pressure inside the pipe:

(a) for a catastrophic pipeline rupture, at the place where the ruptured pipeline joins a larger pipeline;

(b) for a pipeline puncture incident, at the damage point.

#### 29.4.10. Fugitive emissions from transmission storage tanks

For transmission storage tanks, the emitter must

(1) to measure compressor scrubber dump valve leakage from condensate storage tanks connected to transmission storage tanks, determine the emission factor for leaks from each type of component using the following methods:

(a) using equipment specific factors for the operation of the enterprise's equipment;

(b) using the method in the most recent version of "Methodology Manuel: Estimation of Air Emissions from the Canadian Natural Gas Transmission, Storage and Distribution System" published by Clearstone Engineering Ltd.;

(2) determine the duration of the equipment leakage, using the following methods:



(a) when only one leak detection survey is conducted each year, the emitter must assume that the component was leaking from the start of the year until the leak was repaired. If the leak was not repaired, the emitter must assume that the component was leaking for the entire year;

(b) when more than one leak detection survey is conducted each year, the emitter must assume that the component has been leaking since the last survey. If a leak was detected at the last survey, the emitter must assume that the component, unless the leak has been repaired, was leaking for the entire year.”;

(yy) by replacing Tables 29-1 to 29-5 in QC.29.6 by the following:

**“Table 29-1. Emission factors for natural gas leaks by component during compression for onshore transmission**

(QC.29.3.2, QC.29.3.4, (2), QC.29.4.7, (1))

<b>Leaker emission factor by component type</b>	
<b>Component type</b>	<b>Natural gas (metric tons/hour)</b>
Connector	$4.484 \times 10^{-5}$
Block valve	$1.275 \times 10^{-4}$
Control valve	$8.205 \times 10^{-5}$
Compressor blowdown valve	$5.691 \times 10^{-3}$
Pressure relief valve	$5.177 \times 10^{-4}$
Orifice meter	$2.076 \times 10^{-4}$
Other meter	$3.493 \times 10^{-7}$
Regulator	$1.125 \times 10^{-4}$
Open ended line	$1.580 \times 10^{-4}$
<b>Fugitive emission factors by component type</b>	
<b>Component type</b>	<b>Total organic carbon (m<sup>3</sup>/hour)</b>
Low bleed pneumatic device	$5.07 \times 10^{-2}$
High bleed pneumatic device	$5.69 \times 10^{-1}$
Intermittent bleed pneumatic device	$5.69 \times 10^{-1}$
Pneumatic pump	$3.766 \times 10^{-1}$

**Table 29-2. Emission factors for natural gas leaks by component type during underground storage**

(QC.29.3.2, QC.29.3.4, (2), QC.29.4.7, (1), QC.29.4.8, (2))

Component type	Natural gas m <sup>3</sup> /hour
<b>Leaker emission factor by component type following a leak detection survey</b>	
Valve	0.4268
Connector	0.1600
Open ended line	0.4967
Pressure relief valve	1.140
Meter	0.5560
<b>Fugitive emission factor by component type</b>	
Connector	$2.8 \times 10^{-4}$
Valve	$2.8 \times 10^{-3}$
Pressure relief valve	$4.8 \times 10^{-3}$
Open ended line	$8.5 \times 10^{-4}$
Low bleed pneumatic device	$5.07 \times 10^{-2}$
High bleed pneumatic device	$5.69 \times 10^{-1}$
Intermittent bleed pneumatic device	$5.69 \times 10^{-1}$

**Table 29-3. Emission factors for natural gas leaks by component type during liquefied natural gas storage**

(QC.29.4.7, (1), QC.29.4.8, (2))

Component type	Natural gas m <sup>3</sup> /hour
<b>Leaker emission factor by component type following leak detection survey</b>	
Valve	$3.43 \times 10^{-2}$
Pump seal	$1.15 \times 10^{-1}$
Connector	$9.9 \times 10^{-3}$
Other	$5.10 \times 10^{-2}$
<b>Fugitive emission factor by component type</b>	
Vapor recovery compressor	$1.20 \times 10^{-1}$

**Table 29-4. Emission factors for natural gas leaks by component type during imports and exports of liquid natural gas**

(QC.29.4.7, (1), QC.29.4.8, (2))

<b>Component type</b>	<b>Natural gas m<sup>3</sup>/hour</b>
<b>Leaker emission factor by component type following leak detection survey</b>	
Valve	$3.43 \times 10^{-2}$
Pump seal	$1.15 \times 10^{-1}$
Connector	$9.90 \times 10^{-3}$
Other	$5.10 \times 10^{-2}$
<b>Fugitive emission factor by component type</b>	
Vapor recovery compressor	$1.20 \times 10^{-1}$

**Table 29-5. Emission factors for natural gas leaks by component type during natural gas during distribution**

(QC.29.4.7, (1), QC.29.4.8, (2))

<b>Component type</b>	<b>Natural gas metric tons/hour</b>
Connector	$6.875 \times 10^{-6}$
Block valve	$1.410 \times 10^{-5}$
Control valve	$7.881 \times 10^{-5}$
Pressure relief valve	$3.524 \times 10^{-5}$
Orifice meter	$8.091 \times 10^{-6}$
Regulator	$2.849 \times 10^{-5}$
Open ended line	$1.216 \times 10^{-4}$
<b>Component type</b>	<b>Natural gas m<sup>3</sup>/hour</b>
Below ground meter and regulator, inlet pressure greater than 300 psig	$3.74 \times 10^{-2}$
Below ground meter and regulator, inlet pressure between 100 and 300 psig	$5.7 \times 10^{-3}$
Below ground meter and regulator, inlet pressure below 100 psig	$2.8 \times 10^{-3}$

<b>Fugitive emission factor by type of distribution pipeline</b>	
<b>Pipeline type</b>	<b>Natural gas m<sup>3</sup>/hour</b>
Unprotected steel	$1.83 \times 10^{-1}$
Protected steel	$7.22 \times 10^{-2}$
Plastic	$7.75 \times 10^{-2}$
Cast iron	$7.83 \times 10^{-1}$
<b>Fugitive emission factor by type of distribution pipeline</b>	
<b>Pipeline type</b>	<b>Natural gas m<sup>3</sup>/hour</b>
Unprotected steel	$7.08 \times 10^{-2}$
Protected steel	$3.23 \times 10^{-2}$
Plastic	$1.04 \times 10^{-2}$
Copper	$2.7 \times 10^{-2}$

**Table 29-6. Average manufacturer bleed rates for certain liquid level controllers, positioners, pressure controllers, transducers and transmitters**

(QC.29.3.1, QC.29.3.2)

<b>Equipment type</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Operating condition</b>	<b>Manufacturer rate (m<sup>3</sup>/hour)</b>
Liquid level controller	Bristol Babcock	Series 5453-Model 624-II	Continuous	0.0850
Liquid level controller	Fisher	2100	Continuous	0.0283
Liquid level controller	Fisher	2500	Continuous	1.1893
Liquid level controller	Fisher	2660	Continuous	0.0283
Liquid level controller	Fisher	2680	Continuous	0.0283
Liquid level controller	Fisher	2900	Continuous	0.6513
Liquid level controller	Fisher	L2	Continuous	0.0425
Liquid level controller	Invalco	AE-155	Continuous	1.5008
Liquid level controller	Invalco	CT Series	Continuous	1.1327

Liquid level controller	Norriseal	1001 (A) 'Envirosave'	Intermittent	0.0000
Liquid level controller	Norriseal	1001 (A) snap	Intermittent	0.0057
Liquid level controller	Norriseal	1001 (A) throttle	Intermittent	0.0002
Liquid level controller	Wellmark	2001 (snap)	Intermittent	0.0057
Liquid level controller	Wellmark	2001 (throttling)	Intermittent	0.0002
Positioner	Becker	EFP-2.0	Intermittent	0.0000
Positioner	Becker	HPP-5	Continuous	0.1416
Positioner	Fisher	3582	Continuous	0.4531
Positioner	Fisher	3590	Continuous	0.8495
Positioner	Fisher	3660	Continuous	0.1982
Positioner	Fisher	3661	Continuous	0.2959
Positioner	Fisher	3582i	Continuous	0.5833
Positioner	Fisher	3610J	Continuous	0.4531
Positioner	Fisher	3620J	Continuous	0.7532
Positioner	Fisher	DVC 5000	Continuous	0.2832
Positioner	Fisher	DVC 6000	Continuous	0.3964
Positioner	Fisher	Fieldview Digital	Continuous	0.8920
Positioner	Masoneilan	7400	Continuous	1.0477
Positioner	Masoneilan	4600B Series	Continuous	0.6796
Positioner	Masoneilan	4700B Series	Continuous	0.6796
Positioner	Masoneilan	4700E	Continuous	0.6796
Positioner	Masoneilan	SV	Continuous	0.1133
Positioner	Moore Products	73N-B	Continuous	1.0194
Positioner	Moore Products	750P	Continuous	1.1893
Positioner	PMV	D5 Digital	Continuous	0.0283
Positioner	Sampson	3780 Digital	Continuous	0.0283
Positioner	VCR	VP700 PtoP	Continuous	0.0283
Pressure controller	Ametek	Series 40	Continuous	0.1699
Pressure controller	Becker	HPP-SB	Continuous	0.0000
Pressure controller	Becker	VRP-B-CH	Continuous	0.1416
Pressure controller	Becker	VRP-SB	Continuous	0.0000

Pressure controller	Becker	VRP-SB Gap Controller	Continuous	0.0000
Pressure controller	Becker	VRP-SB-CH	Continuous	0.0000
Pressure controller	Becker	VRP-SB-PID Controller	Continuous	0.0000
Pressure controller	Bristol Babcock	Series 5453-Model 10F	Continuous	0.0850
Pressure controller	Bristol Babcock	Series 5455-Model 624-III	Continuous	0.0708
Pressure controller	CSV	4150	Continuous	0.6853
Pressure controller	CSV	4160	Continuous	0.6853
Pressure controller	Dyna-Flow	4000	Continuous	0.6853
Pressure controller	Fisher	2506	Continuous	0.6853
Pressure controller	Fisher	2516	Continuous	0.6853
Pressure controller	Fisher	4150	Continuous	0.7362
Pressure controller	Fisher	4160	Continuous	0.7362
Pressure controller	Fisher	4194	Continuous	0.1203
Pressure controller	Fisher	4195	Continuous	0.1203
Pressure controller	Fisher	4660	Continuous	0.1416
Pressure controller	Fisher	4100 (large orifice)	Continuous	1.4158
Pressure controller	Fisher	4100 (small orifice)	Continuous	0.4248
Pressure controller	Fisher	C1	Continuous	0.1472
Pressure controller	Fisher	DVC 6010	Continuous	0.0878
Pressure controller	Foxboro	43AP	Continuous	0.5097
Pressure controller	ITT Barton	338	Continuous	0.1699
Pressure controller	ITT Barton	358	Continuous	0.0510
Pressure controller	ITT Barton	359	Continuous	0.0510

Pressure controller	ITT Barton	335P	Continuous	0.1699
Pressure controller	ITT Barton	335P	Continuous	0.1699
Transducer	Bristol Babcock	9110-00A	Continuous	0.0119
Transducer	Bristol Babcock	Series 502 A/D	Continuous	0.1671
Transducer	Fairchild	TXI 7800	Continuous	0.2407
Transducer	Fisher	546	Continuous	0.8495
Transducer	Fisher	646	Continuous	0.2209
Transducer	Fisher	846	Continuous	0.3398
Transducer	Fisher	i2P-100	Continuous	0.2832
Transmitter	Bristol Babcock	Series 5457-70F	Continuous	0.0850
Transmitter	ITT Barton	273A	Continuous	0.0850
Transmitter	ITT Barton	274A	Continuous	0.0850
Transmitter	ITT Barton	284B	Continuous	0.0850
Transmitter	ITT Barton	285B	Continuous	0.0850

“;

(30) by adding the following after QC.30:

**“QC.31. TITANIUM DIOXIDE PRODUCTION**

**QC.31.1. Covered sources**

The covered sources are all the chloride processes used for the production of titanium dioxide.

**QC.31.2. Greenhouse gas reporting requirements**

In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular, include the following information:

(1) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to the use of stationary combustion units, calculated and reported in accordance with QC.1, in metric tons;

(2) the annual CO<sub>2</sub> emissions attributable to the coke used in the chloride process as a reducing agent, in metric tons;

(3) the annual quantity of coke used in the chloride process as a reducing agent, in metric tons;

- (4) the average annual carbon content of the coke used in the chloride process as a reducing agent, in metric tons of carbon per metric ton of carbonaceous material.
- (5) the annual quantity of waste, in metric tons;
- (6) the average annual carbon content of the waste, in metric tons of carbon per metric ton of waste;
- (7) the number of times that the methods for estimating missing data provided for in QC.31.5 were used;
- (8) the total greenhouse gas emissions for each type of emission, namely:
  - (a) the annual fixed process emissions corresponding to the total of the emissions referred to in paragraph 3, in metric tons;
  - (b) the annual combustion emissions corresponding to the emissions referred to, in subparagraph 2, in metric tons CO<sub>2</sub> equivalent;
- (9) the annual quantity of each product used to calculate the quantity of titanium oxide pigment equivalent, in metric tons;
- (10) the annual quantity of titanium oxide pigment equivalent, in metric tons.

Subparagraphs 5 and 7 of the first paragraph do not apply to the CO<sub>2</sub> emissions of an emitter who calculates emissions using data from a continuous emission monitoring and recording system.

### **QC.31.3. Calculation methods for CO<sub>2</sub> emissions attributable to titanium dioxide processes**

The annual CO<sub>2</sub> emissions attributable to titanium dioxide production processes must be calculated in accordance with one of the methods in QC.31.3.1 and QC.31.3.2.

QC.31.3.1. Use of a continuous emission monitoring and recording system

The annual CO<sub>2</sub> emissions may be calculated using data from a continuous emission monitoring and recording system in accordance with QC.1.3.4.



### QC.31.3.2. Calculation by mass balance

The annual CO<sub>2</sub> emissions attributable to the carbonaceous materials used in the chloride process as reducing agents may be calculated using equation 31-1:

#### Equation 31-1

$$CO_2 = \left[ \sum_{i=1}^{12} [RA_i \times CC_{RAi}] - [M_{waste} \times CC_{waste}] \right] \times 3.664$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to the coke used in the chloride process as a reducing agent, in metric tons;

i = Month;

RA<sub>i</sub> = Consumption of coke used in the chloride process as a reducing agent in month *i*, in metric tons;

CC<sub>RA i</sub> = Carbon content of the coke used in the chloride process as a reducing agent in month *i*, in metric tons of carbon per metric ton of coke;

M<sub>waste</sub> = Annual quantity of waste, in metric tons;

CC<sub>waste</sub> = Average annual carbon content of waste, in metric tons of carbon per metric ton of waste;

3.664 = Ratio of molecular weights, CO<sub>2</sub> to carbon.

### QC.31.4. Sampling, analysis and measurement requirements

When the calculation method in QC.31.3.2 is used, an emitter who operates a facility or establishment that produces titanium dioxide must

(1) determine, monthly, the carbon content of the coke, either by using data from the material supplier or by using one of the following methods:

(a) the most recent version of ASTM D5373 "Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal";

(b) the most recent version of ASTM D3176 “Standard Practice for Ultimate Analysis of Coal and Coke”;

(c) any other analysis method published by an organization listed in QC.1.5;

(2) calculate the annual quantity of coke used, using the same plant instruments used for inventory purposes, such as weigh hoppers or belt weigh feeders or using the supply documentation;

(3) based on the data determined in accordance with paragraph 1, calculate annually the average annual carbon content of the coke using equation 1-18 in QC.1.5.5;

(4) determine annually the average carbon content of the waste using a annual composite sample based on monthly composite samples in accordance with the most recent version of method MA. 310-CS 1 of the Centre d'expertise en analyse environnementale du Québec;

(5) calculate the annual quantity of waste used by weighing the waste using the same plant instruments as those used for inventory purposes, such as mass balances, weigh hoppers or belt weight feeders;

(6) calculate the annual quantity of each product used to determine the annual quantity of titanium oxide pigment equivalent by weighing the products using the same plant instruments as those used for inventory purposes, such as weigh hoppers or belt weight feeders.

#### **QC.31.5. Methods for estimating missing data**

When, in conducting sampling activities, an emitter is unable to obtain analytical data, the original sample, back-up sample or replacement sample must be analyzed again, using the methods prescribed in this protocol, for the same measurement and sampling periods.

When sampling or measurement data required by this protocol for the calculation of emissions is missing, the emitter must demonstrate that everything possible has been done to ensure that 100% of the data is sampled. The emitter must then use replacement data determined as follows:

(1) for an emitter who uses one of the calculation methods in this protocol:

(a) when the missing value concerns carbon content or other sampled data, the emitter must

(i) determine the sampling or measurement rate using the following equation:

**Equation 31-2**

$$S = \frac{Q_{E\text{Real}}}{Q_{E\text{Req}}}$$

Where:

S = Actual sampling rate or measurement rate, expressed as a percentage;

$Q_{E\text{Real}}$  = Actual number of samples or measurements carried out by the emitter;

$Q_{E\text{Req}}$  = Number of samples or measurements required under QC.31.4;

(ii) for data requiring sampling or analysis, the emitter must

- when  $T \geq 0.9$ : replace the missing value by the arithmetic average of the data sampled or measured immediately preceding and following the missing data period. If no data are available prior to the missing data period, the emitter must use the first data obtained after the missing data period;

- when  $0.75 \leq T < 0.9$ : replace the missing value by the highest value sample or analyzed during the report year for which the calculation is made;

- when  $T < 0.75$ : replace the missing value by the highest value sample or analyzed during the 3 preceding years ;

(b) when the missing value concerns coke consumption, the annual quantity of each product used to determine the annual quantity of titanium oxide pigment equivalent, or the quantity of waste, the replacement value must be estimated on the basis of all the data relating to the processes used;

(2) for an emitter who uses a continuous emission monitoring system, apply the procedure in the EPS 1/PG/7 protocol entitled "Protocols and performance specifications for continuous monitoring of gaseous emissions from thermal power generation" published in November 2005 by Environment Canada or apply the method in subparagraph a of paragraph 2 of QC.1.6 to the missing parameters.

**QC.32. TITANIUM SLAG AND IRON PRODUCTION FROM ILMENITE REDUCTION****QC.32.1. Covered sources**

The covered sources are ilmenite reduction processes.

**QC.32.2. Greenhouse gas reporting requirements**

In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular, include the following information:

(1) the total annual CO<sub>2</sub> emissions attributable to ilmenite reduction, in metric tons;

(2) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to the use of stationary combustion units, calculated and reported in accordance with QC.1, in metric tons;

(3) the annual consumption of each type of ilmenite, in metric tons;

(4) the annual consumption of each material used, other than ilmenite, that contributes 0.5% or more of the total carbon in the process, in metric tons;

(5) the annual consumption of carbon electrodes, in metric tons;

(6) the annual production of iron, in metric tons;

(7) the annual production of titanium slag, in metric tons;

(8) the annual quantity of air pollution control residue collected, in metric tons;

(9) the carbon content of the materials and products in the ilmenite reduction process referred to in subparagraphs 3 to 8 that contribute 0.5% or more of the total carbon in the process, in metric tons of carbon per metric ton of material and products;

(10) the total greenhouse gas emissions for each type of emission, namely:

(a) the annual fixed process emissions corresponding to the total of the emissions referred to in subparagraph 1, in metric tons;

(b) the annual combustion emissions corresponding to the emissions referred to in subparagraph 2, in metric tons CO<sub>2</sub> equivalent;

(11) the number of times that the methods for estimating missing data provided for in QC.32.5 were used.

Subparagraph 9 of the first paragraph does not apply to the CO<sub>2</sub> emissions of an emitter who calculates emissions using data from a continuous emission monitoring and recording system.

### QC.32.3. Calculation methods for CO<sub>2</sub> emissions

The emitter must calculate the annual CO<sub>2</sub> emissions attributable to ilmenite reduction processes in accordance with one of the methods in QC.32.3.1 and QC.32.3.2.

QC.32.3.1. Use of a continuous emission monitoring and recording system

The annual CO<sub>2</sub> emissions attributable to ilmenite reduction processes may be calculated using data from a continuous emission monitoring and recording system in accordance with QC.1.3.4.

QC.32.3.2. Calculation by mass balance

The annual CO<sub>2</sub> emissions attributable to ilmenite reduction processes may be calculated using equation 32-1. Materials or products whose carbon content contributes less than 0.5% of the carbon in the process do not need to be considered in the calculation.

#### Equation 32-1

$$CO_2 = \left[ \sum_{i=1}^n (IL_i \times CC_{IL,i}) + \sum_{k=1}^p (M_k \times CC_{M,k}) + (CE \times CC_{CE}) - (I \times CC_I) - (SL \times CC_{SL}) - (R \times CC_R) \right] \times 3.664$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to ilmenite reduction, in metric tons;

n = Number of types of ilmenite;

i = Type of ilmenite;

$IL_i$  = Annual consumption of ilmenite  $i$ , in metric tons;

$CC_{IL,i}$  = Average annual carbon content of ilmenite  $i$ , in metric tons of carbon per metric ton of ilmenite  $i$ ;

$p$  = Number of materials other than ilmenite used;

$k$  = Material other than ilmenite used;

$M_k$  = Annual quantity of each material  $k$  other than ilmenite used, in metric tons;

$CC_{M,k}$  = Average annual carbon content of each material  $k$  other than ilmenite used, in metric tons of carbon per metric ton of material  $k$ ;

$CE$  = Annual consumption of carbon electrodes, in metric tons;

$CC_{CE}$  = Average annual carbon content of the carbon electrodes, in metric tons of carbon per metric ton of carbon electrodes;

$I$  = Annual production of iron, in metric tons;

$CC_I$  = Average annual carbon content of the iron produced, in metric tons of carbon per metric ton of iron produced;

$SL$  = Annual production of titanium slag, in metric tons;

$CC_{SL}$  = Average annual carbon content of the titanium slag, in metric tons of carbon per metric ton of titanium slag;

$R$  = Annual quantity of air pollution control residue collected, in metric tons;

$CC_R$  = Average annual carbon content of the air pollution control residue collected, in metric tons of carbon per metric ton of residue;

3.664 = Ratio of molecular weights,  $CO_2$  to carbon.

#### **QC.32.4. Sampling, analysis and measurement requirements**

##### **QC.32.4.1. Carbon content**

When the calculation method in QC.32.3.2 is used, the emitter who operates a facility or establishment that uses an ilmenite reduction process must, for materials or products whose carbon content contributes 0.5% or more of the carbon in the process, use the data provided by the supplier or determine the carbon content by analyzing a minimum of 3 representative samples per year using the following methods:

- (1) for fossil fuels, in accordance with QC.1.5.5;
- (2) for the materials used in the ilmenite reduction process, the titanium slag produced and the air pollution control residue collected, in accordance with an analysis method published by an organization referred to in QC.1.5;
- (3) for flux materials such as limestone or dolomite, using the most recent version of ASTM C25 “Standard Test Methods for Chemical Analysis of Limestone, Quicklime, and Hydrated Lime”, or using any other analysis method published by an organization listed in QC.1.5;
- (4) for coal, coke and the carbon electrodes used in electric arc furnaces, using the most recent version of ASTM D5373 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal”, or using any other analysis method published by an organization listed in QC.1.5;
- (5) for fuels, feedstock or liquid products, using the most recent version of ASTM D7582 “Standard Test Methods for Proximate Analysis of Coal and Coke by Macro Thermogravimetric Analysis”, or using any other analysis method published by an organization listed in QC.1.5;
- (6) for iron, using the most recent version of ASTM E1019 “Standard Test Methods for Determination of Carbon, Sulfur, Nitrogen, and Oxygen in Steel, Iron, Nickel, and Cobalt Alloys by Various Combustion and Fusion Techniques”, or using any other analysis method published by an organization listed in QC.1.5.

##### **QC.32.4.2. Consumption of process materials**

The emitter must determine the quantity of solid, liquid and gaseous materials and the quantities required for the calculation in equation 32-1 using the same plant instruments as those used for inventory purposes, such as weigh hoppers or belt weigh feeders.

**QC.32.5. Methods for estimating missing data**

When, in conducting sampling activities, an emitter is unable to obtain analytical data, the original sample, back-up sample or replacement sample must be analyzed again, using the methods prescribed in this protocol, for the same measurement and sampling periods.

When sampling or measurement data required by this protocol for the calculation of emissions is missing, the emitter must demonstrate that everything possible has been done to ensure that 100% of the data is sampled. The emitter must then use replacement data determined as follows:

(1) for an emitter who uses one of the calculation methods in this protocol:

(a) when the missing value concerns carbon content or another sampled value, the emitter must

(i) determine the sampling or measurement rate using the following equation:

**Equation 32-2**

$$S = \frac{Q_{E\text{Real}}}{Q_{E\text{Req}}}$$

Where:

S = Actual sampling rate or measurement rate, expressed as a percentage;

$Q_{E\text{Real}}$  = Actual number of samples or measurements carried out by the emitter;

$Q_{E\text{Req}}$  = Number of samples or measurements required under QC.32.4;

(ii) for data requiring sampling or analysis, the emitter must

- when  $T \geq 0.9$ : replace the missing value by the arithmetic average of the data sampled or measured immediately preceding and following the missing data period. If no data are available prior to the missing data period, the emitter must use the first data obtained after the missing data period;



- when  $0.75 \leq T < 0.9$ : replace the missing value by the highest value sample or analyzed during the report year for which the calculation is made;

- when  $T < 0.75$ : replace the missing value by the highest value sample or analyzed during the 3 preceding years ;

(b) when the missing value concerns the consumption of ilmenite, the consumption of raw materials, the consumption of carbon electrodes, the production of slag, the production of iron or the production of other by-products, the replacement value must be estimated on the basis of all the data relating to the processes used;

(2) for an emitter who uses a continuous emission monitoring system, apply the procedure in the EPS 1/PG/7 protocol entitled "Protocols and performance specifications for continuous monitoring of gaseous emissions from thermal power generation" published in November 2005 by Environment Canada or apply the method in subparagraph a of paragraph 2 of QC.1.6.

### **QC.33. OIL AND NATURAL GAS EXPLORATION AND PRODUCTION AND NATURAL GAS PROCESSING**

#### **QC.33.1. Covered sources**

The covered sources are the following processes and equipment used for

(1) offshore petroleum and natural gas exploration and production from any temporary or permanent platform, which includes

(a) the use of equipment to extract hydrocarbons from submerged land;

(b) the use of equipment to transfer oil or natural gas to storage, transport vessels, or onshore, including secondary platform structures and storage tanks associated with the platform structure;

(2) onshore oil and natural gas exploration and production, which includes

(a) the use of equipment associated with wells, such as compressors, generators, storage facilities and piping, such as flowlines or intra-facility gathering lines;

- (b) the use of portable non-self-propelled equipment, such as well drilling, completion and workover equipment;
  - (c) the use of gravity separation equipment;
  - (d) the use of auxiliary non-transportation-related equipment, including leased, rented or contracted equipment used in exploration and production, extraction, recovery, lifting, stabilization, separation or treating of petroleum and natural gas, including condensate;
  - (e) storage facilities and all systems engaged in gathering produced gas from multiple wells;
  - (f) all enhanced oil recovery (EOR) operations using CO<sub>2</sub>;
  - (g) all exploration and production facilities located on islands, artificial islands or structures connected by a causeway to land or to an island or artificial island;
- (3) onshore natural gas processing, which includes
- (a) oil and condensate removal;
  - (b) water extraction;
  - (c) the separation of natural gas liquids;
  - (d) hydrogen sulphide (H<sub>2</sub>S) and CO<sub>2</sub> removal;
  - (e) fractionation of natural gas liquids;
  - (f) the capture of CO<sub>2</sub> separated from natural gas streams for delivery outside the facility;
  - (g) field gathering or boosting stations that gather and process natural gas from multiple wellheads, and compress and transport natural gas (including but not limited to flowlines or intra-facility gathering lines or compressors) as feed to the natural gas processing plants;
  - (h) any other treatment process.

### **QC.33.2. Greenhouse gas reporting requirements**

In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular, include the following information:

(1) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to the use of stationary combustion units calculated and reported in accordance with QC.1 or, when process vent gas, field gas or any other type of gas is used, in accordance with QC.33.3.19, in metric tons;

(2) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to the use of portable equipment, calculated and reported in accordance with QC.1 or, when process vent gas, field gas or any other type of gas is used, in accordance with QC.33.3.19, in metric tons;

(3) the annual fugitive emissions of CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O from offshore oil and gas exploration and production facilities originating from equipment leaks, venting and flares, calculated in accordance with QC.33.3.21, in metric tons;

(4) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions from onshore oil and gas exploration and production facilities, in metric tons, specifying

(a) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to high bleed pneumatic device venting and natural gas driven pneumatic pump venting, calculated in accordance with QC.33.3.1;

(b) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to natural gas driven low bleed and intermittent bleed pneumatic device venting, calculated in accordance with QC.33.3.2;

(c) the annual CO<sub>2</sub> emissions attributable to acid gas scrubbing equipment, calculated in accordance with QC.33.3.3;

(d) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to dehydrator venting, calculated in accordance with QC.33.3.4;

(e) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to well venting for liquids unloading, calculated in accordance with QC.33.3.5;

(f) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to natural gas well venting during completions or workovers, calculated in accordance with QC.33.3.6;

(g) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to blowdown vent stacks, calculated in accordance with QC.33.3.7;

(h) the annual CH<sub>4</sub> emissions attributable to third party line hits, calculated in accordance with QC.33.3.8;

- (i) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to venting from storage tanks associated with onshore oil and natural gas exploration, production, processing and storage facilities, calculated in accordance with QC.33.3.9;
- (j) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to transmission storage tanks, calculated in accordance with QC.33.3.10;
- (k) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to well testing venting and flaring, calculated in accordance with QC.33.3.11;
- (l) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to associated gas venting and flaring, calculated in accordance with QC.33.3.12;
- (m) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to flare stacks, calculated in accordance with QC.33.3.13;
- (n) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to centrifugal compressor venting, calculated in accordance with QC.33.3.14;
- (o) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to reciprocating compressor venting, calculated in accordance with QC.33.3.15;
- (p) the annual fugitive CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to gathering pipeline equipment leaks, calculated in accordance with QC.33.3.17;
- (q) the annual fugitive CO<sub>2</sub> and CH<sub>4</sub> emissions from equipment components such as valves, connectors, open ended lines, pressure relief valves, pumps, flanges, metrological instruments, loading arms, safety valves, stuffing boxes, compressor seals, dump lever arms, and breather caps for crude oil processing, calculated in accordance with QC.33.3.17;
- (r) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to Enhanced Oil Recovery (EOR) injection pump blowdown, calculated in accordance with QC.33.3.18;
- (s) the annual fugitive emissions from other sources of fugitive emissions, calculated in accordance with QC.33.3.20;
- (5) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions from onshore natural gas processing facilities, in metric tons, specifying

(a) the annual CO<sub>2</sub> emissions attributable to acid gas scrubbing equipment, calculated in accordance with QC.33.3.3;

(b) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to dehydrator venting, calculated in accordance with QC.33.3.4;

(c) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to blowdown vent stacks, calculated in accordance with QC.33.3.7;

(d) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to natural gas storage, calculated in accordance with QC.33.3.9;

(e) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to flare stacks, calculated in accordance with QC.33.3.13;

(f) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to centrifugal compressor venting, calculated in accordance with QC.33.3.14;

(g) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to reciprocating compressor venting, calculated in accordance with QC.33.3.15;

(h) the annual fugitive CO<sub>2</sub> and CH<sub>4</sub> emissions from equipment components such as valves, connectors, open ended lines, pressure relief valves and meters, calculated in accordance with QC.33.3.16;

(i) the annual fugitive CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to gathering pipeline component leaks, calculated in accordance with QC.33.3.17;

(j) the annual fugitive emissions from other fugitive emission sources, such as reciprocating compressor rod-packing vents and centrifugal compressor wet and dry seal vents, calculated in accordance with QC.33.3.20;

(6) the following data for each emission source referred to in paragraphs 2 to 4:

(a) the specific emission factors used in place of the values indicated in Tables 33-1 and 33-2 in QC.33.6;

(b) the number of natural gas driven pneumatic devices used, by type, namely high bleed, low bleed or intermittent bleed;

(c) the number of natural gas driven pneumatic pumps;

- (d) the total throughput of acid gas scrubbing equipment;
- (e) if glycol dehydrators are used, the number of dehydrators operated, specifying
  - (i) the number of dehydrators with throughput less than 11 328 m<sup>3</sup> per day at standard conditions;
  - (ii) the number of dehydrators with throughput equal to or greater than 11 328 m<sup>3</sup> per day at standard conditions;
- (f) the number of wells vented to the atmosphere for liquids unloading;
- (g) the number of third party line hits, including volumes of natural gas emitted to the atmosphere by hit;
- (h) the number of gas wells venting during well completions, specifying
  - (i) the number of conventional well completions;
  - (ii) the number of well completions employing hydraulic fracturing;
    - (i) the number of wells vented during workovers;
    - (j) for each compressor used:
      - (i) the type of compressor;
      - (ii) where the aggregate rated power for the sum of compressors at the establishment is equal to or greater than 186.4 kW:
        - the compressor driver capacity in kilowatts;
        - the annual number of blowdowns;
      - (iii) the number of compressor starts during the year;
    - (k) the number of EOR injection pump blowdowns;
    - (l) the number of wells tested;
    - (m) the number of wells venting or flaring associated gas;

- (n) the number of wells being unloaded for liquids;
- (o) the number of wells worked over;
- (p) when the calculation methods in QC.33.3.16 and QC.33.3.17 are used:
  - (i) the components of each emission source for which an emission factor is specified in Table 33-1, 33-2 or 33-3 in QC.33.6;
  - (ii) the total number of leaks detected during annual leak detection surveys, for each source having an emission factor determined in accordance with QC.33.4.16;
- (q) the quantity of oil produced, in barrels;
- (r) the quantity of natural gas produced;
- (7) the number of times that the methods for estimating missing data provided for in QC.33.5 were used;
- (8) the total greenhouse gas emissions for each type of emission, namely:
  - (a) the annual greenhouse gas combustion emissions corresponding to the emissions referred to in paragraphs 1 and 2, in metric tons CO<sub>2</sub> equivalent;
  - (b) the annual other category greenhouse gas emissions corresponding to the total of the emissions referred to in paragraphs 3 to 5, in metric tons CO<sub>2</sub> equivalent.

The emissions attributable to well venting or to other fugitive emission sources or to the venting referred to in subparagraphs *q* and *s* of subparagraph 4 and in subparagraph *j* of subparagraph 5 of the first paragraph do not need to be reported when the emissions from a given source are less than 0.5% of the emitter's total emissions and when the total of the unreported emissions under this paragraph does not exceed 1% of the emitter's total emissions.

### **QC.33.3. Calculation methods for CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions**

The annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to oil and natural gas exploration and production and to natural gas processing must be calculated in accordance with one of the methods in QC.33.3.1 to QC.33.3.20.

When no calculation method is specified for an emissions source, the emitter must use sector-specific inventory practices.

QC.33.3.1. Calculation of CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to high bleed pneumatic device venting and natural gas driven pneumatic pump venting

The annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to venting from high bleed pneumatic devices, in other devices that bleed to the atmosphere at a rate in excess of 0.17 m<sup>3</sup> per hour, and to natural gas driven pneumatic pumps, must be calculated using equations 33-1 to 33-4:

### Equation 33-1

$$GHG_i = GHG_{m,i} + GHG_{n-m,i}$$

Where:

GHG<sub>i</sub> = Annual emissions of greenhouse gas *i* attributable to high bleed pneumatic device and natural gas driven pneumatic pump venting, in metric tons;

GHG<sub>m,i</sub> = Annual emissions of greenhouse gas *i* attributable to high bleed pneumatic device and natural gas driven pneumatic pump venting, calculated using equation 33-2 when the annual volume of natural gas consumed is metered, in metric tons;

GHG<sub>n-m,i</sub> = Annual emissions of greenhouse gas *i* attributable to high bleed pneumatic device and natural gas driven pneumatic pump venting, calculated, when the annual volume of natural gas consumed by the devices is not metered, using equation 33-3 for high bleed pneumatic devices and equation 33-4 for natural gas driven pneumatic pumps, in metric tons;

*i* = CO<sub>2</sub> or CH<sub>4</sub>;

### Equation 33-2

$$GHG_{m,i} = V_{NG} \times MF_i \times \frac{MW_i}{MVC} \times 0.001$$



Where:

$GHG_{m,i}$  = Annual emissions of greenhouse gas  $i$  attributable to high bleed pneumatic device and natural gas driven pneumatic pump venting, in metric tons;

$V_{NG}$  = Annual volume of natural gas consumed by the high bleed pneumatic devices or natural gas driven pneumatic pumps, measured in accordance with paragraph 1 of QC.33.4.1, in cubic metres at standard conditions;

$MF_i$  = Molar fraction of gas  $i$  in natural gas, determined in accordance with paragraph 3 of QC.33.4;

$MW_i$  = Molecular weight of gas  $i$ , in kilograms per kilomole;

MVC = Molar volume conversion factor (24.06 m<sup>3</sup> per kilomole at standard conditions);

0.001 = Conversion factor, kilograms to metric tons;

$i$  = CO<sub>2</sub> or CH<sub>4</sub>;

### Equation 33-3

$$GHG_{n-m,i} = \sum_{j=1}^n [B_j \times t_j] \times MF_i \times \rho_i \times 0.001$$

Where:

$GHG_{n-m,i}$  = Annual emissions of greenhouse gas  $i$  attributable to high bleed pneumatic device venting, in metric tons;

$n$  = Total number of high bleed pneumatic devices;

$j$  = High bleed pneumatic device;

$B_j$  = Natural gas bleed rate for pneumatic device  $j$ , determined in accordance with paragraph 2 of QC.33.4.1, in cubic metres per hour at standard conditions;

$t_j$  = Annual operating time of pneumatic device  $j$ , in hours;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in natural gas, determined in accordance with paragraph 3 of QC.33.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for CO<sub>2</sub> and 0.690 kg per cubic metre for CH<sub>4</sub> at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  = CO<sub>2</sub> or CH<sub>4</sub>;

#### Equation 33-4

$$GHG_{n-m,i} = \sum_{k=1}^m [Q_{NG,k} \times V_k] \times MF_i \times \rho_i \times 0.001$$

Where:

GHG<sub>n-m,i</sub> = Annual emissions of greenhouse gas  $i$  attributable to natural gas driven pneumatic pump venting, in metric tons;

$m$  = Total number of natural gas driven pneumatic pumps;

$k$  = Natural gas driven pneumatic pump;

Q<sub>NG,k</sub> = Quantity of natural gas consumed by the natural gas driven pneumatic pump  $k$ , determined in accordance with paragraph 3 of QC.33.4.1, in cubic metres per litre of liquid pumped at standard conditions;

V<sub>k</sub> = Annual volume of liquid pumped, in litres;

MF<sub>i</sub> = Molar fraction of greenhouse gas  $i$  in natural gas, determined in accordance with paragraph 3 of QC.33.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for CO<sub>2</sub> and 0.690 kg per cubic metre for CH<sub>4</sub> at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  = CO<sub>2</sub> or CH<sub>4</sub>.

QC.33.3.2. Calculation of CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to natural gas driven low or intermittent bleed pneumatic device venting

The annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to natural gas driven low or intermittent bleed pneumatic device venting must be calculated separately using equation 33-5:

**Equation 33-5**

$$GHG_i = \sum_j [N_j \times EF_j \times t_j] \times MF_i \times \rho_i \times 0.001$$

Where:

GHG<sub>i</sub> = Annual emissions of greenhouse gas *i* attributable to natural gas driven low or intermittent bleed pneumatic device venting, in metric tons;

*j* = Type of natural gas driven low or intermittent bleed pneumatic device;

N<sub>*j*</sub> = Number of pneumatic devices of type *j*, determined in accordance with QC.33.4.2;

EF<sub>*j*</sub> = Emission factor for pneumatic device of type *j*, determined in accordance with paragraph 2 of 33.4.2, in cubic metres per hour at standard conditions;

t<sub>*j*</sub> = Annual operating time for pneumatic device of type *j*, in hours;

MF<sub>*i*</sub> = Molar fraction of greenhouse gas *i* in natural gas, determined in accordance with paragraph 3 of QC.33.4;

ρ<sub>*i*</sub> = Density of greenhouse gas *i* that is 1.893 kg per cubic metre for CO<sub>2</sub> and 0.690 kg per cubic metre for CH<sub>4</sub> at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

*i* = CO<sub>2</sub> or CH<sub>4</sub>.

QC.33.3.3. Calculation of CO<sub>2</sub> emissions attributable to acid gas scrubbing equipment

Except where acid gases emissions are re-injected into an oil/gas field or manifolded to a common flare stack or other equipment, which must be calculated in accordance with QC.33.3.13, the CO<sub>2</sub> emissions attributable to acid gas scrubbing equipment must be calculated in accordance with one of the following methods:

(1) using data obtained from a continuous emission monitoring and recording system in accordance with QC.1.3.4;

(2) when there is no continuous emission monitoring and recording system but an equipment to measure the quantity of gas emitted is available, using equation 33-6:

**Equation 33-6**

$$CO_2 = V_G \times MF_{CO_2} \times \rho_{CO_2} \times 0.001$$

Where:

$CO_2$  = Annual  $CO_2$  emissions attributable to acid gas scrubbing equipment, in metric tons;

$V_G$  = Annual volume of unprocessed natural gas output from the acid gas scrubbing equipment, measured in accordance with paragraph 1 of QC.33.4.3, in cubic metres at standard conditions;

$MF_{CO_2}$  = Mole fraction of  $CO_2$  in the unprocessed natural gas flow from the acid gas scrubbing equipment, determined in accordance with paragraph 2 of QC.33.4.3;

$\rho_{CO_2}$  = Density of  $CO_2$ , namely 1.893 kg per cubic metre, at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

(3) when there is no continuous emission monitoring and recording system and no equipment to measure the quantity of gas emitted, using equation 33-7:

**Equation 33-7**

$$CO_2 = V_G \times \frac{[MF_{CO_2-in} \times (1 - MF_{H_2S-out}) - MF_{CO_2-out} \times (1 - MF_{H_2S-in})]}{(1 - MF_{H_2S-out} - MF_{CO_2-out})} \times \rho_{CO_2} \times 0.001$$

Where:

$CO_2$  = Annual  $CO_2$  emissions attributable to acid gas scrubbing equipment, in metric tons;

$V_G$  = Annual volume of unprocessed natural gas flow into the acid gas scrubbing equipment, measured in accordance with paragraph 1 of QC.33.4.3, in cubic metres at standard conditions;

$MF_{CO_2-in}$  = Mole fraction of  $CO_2$  in unprocessed natural gas flow into the acid gas scrubbing equipment, determined in accordance with paragraph 2 of QC.33.4.3;

$MF_{CO_2-out}$  = Mole fraction of  $CO_2$  in unprocessed natural gas out of the acid gas scrubbing equipment, determined in accordance with paragraph 2 of QC.33.4.3;

$MF_{H_2S-in}$  = Mole fraction of  $H_2S$  in unprocessed natural gas into the acid gas scrubbing equipment, determined in accordance with paragraph 3 of QC.33.4.3;

$MF_{H_2S-out}$  = Mole fraction of  $H_2S$  in processed natural gas out of the acid gas scrubbing equipment, determined in accordance with paragraph 3 of QC.33.4.3;

$\rho_{CO_2}$  = Density of  $CO_2$ , namely 1.893 kg per cubic metre, at standard conditions;

0.001 = Conversion factor, kilograms to metric tons.

QC.33.3.4. Calculation of  $CO_2$ ,  $CH_4$  and  $N_2O$  emissions attributable to dehydrator vents

The annual  $CO_2$ ,  $CH_4$  and  $N_2O$  emissions attributable to dehydrator vents must be calculated using one of the following methods:

(1) determine the  $CO_2$  and  $CH_4$  emissions using a simulation software package such as GRI-GLYCalc, version 4, or AspenTech HYSYS<sup>MD</sup>, or a similar software tool. The software or tool must use the Peng-Robinson equation of state to calculate the equilibrium coefficient, speciate  $CH_4$  and  $CO_2$  emissions from dehydrators and have provisions to include regenerator control devices, a separator flash tank, stripping gas and a gas injection pump or gas assist pump, specifying the following parameters:

- (a) feed natural gas flow rate;
- (b) feed natural gas water content;
- (c) outlet natural gas water content;
- (d) the type of absorbent circulation pump, namely natural gas pneumatic or air pneumatic or electric;
- (e) absorbent circulation rate;

- (f) absorbent type, such as triethylene glycol, diethylene glycol or ethylene glycol;
- (g) use of stripping gas;
- (h) use of flash tank separator and disposition of recovered gas ;
- (i) hours operated;
- (j) wet natural gas temperature and pressure;
- (k) wet natural gas composition, determined in accordance with QC.33.4.4;

(2) for dehydrators that use desiccant, the emissions must be calculated from the amount of natural gas vented from the vessel every time it is depressurized for the desiccant refilling process, using equation 33-8:

**Equation 33-8**

$$GHG_i = \left( \frac{H \times D^2 \times \pi \times P_{atm} \times G \times 365}{4 \times P \times t} \right) \times \left[ \frac{T_{sc} \times P_d}{T_d \times P_{sc}} \right] \times MF_i \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to dehydrator vents, in metric tons;

$H$  = Height of the dehydrator vessel, in metres;

$D$  = Inside diameter of the dehydrator vessel, in metres;

$\pi$  = Pi, namely 3.1416;

$P$  = Natural gas pressure, in kilopascals;

$P_{atm}$  = Atmospheric pressure, in kilopascals;

$G$  = Fraction of packed vessel volume that is natural gas;

$t$  = Time between refilling, in days;

365 = Number of days in the year;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_d$  = Temperature at dehydrator vent, in kelvin;

$P_d$  = Pressure at dehydrator vent, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in natural gas, determined in accordance with paragraph 3 of QC.33.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for  $CO_2$  and 0.690 kg per cubic metre for  $CH_4$  at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $CO_2$  or  $CH_4$ ;

(3) when the emissions attributable to dehydrator vents are directed to flares, the  $CO_2$ ,  $CH_4$  and  $N_2O$  emissions must be calculated in accordance with the method in QC.33.3.13, using the gas volume and composition determined in accordance with paragraph 1.

For the purposes of the emissions calculation under the first paragraph, where the dehydrator has a vapour recovery system, the emissions must be adjusted downward based on the emissions recovered.

QC.33.3.5. Calculation of  $CO_2$  and  $CH_4$  emissions attributable to well venting for liquids unloading

The annual  $CO_2$  and  $CH_4$  emissions attributable to well venting for liquids unloading must be calculated using one of the following methods:

(1) the annual  $CO_2$  and  $CH_4$  emissions attributable to well venting for liquids unloading may be calculated using equation 33-9:

**Equation 33-9**

$$GHG_i = \sum_{j=1}^n [N \times V \times t]_j \times MF_i \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to well venting for liquids unloading, in metric tons;

$n$  = Number of groups of wells;

$j$  = Groups of wells where liquids are unloaded;

$N$  = Number of wells in the group;

$V$  = Average flow of natural gas in the vent line used to vent gas from the representative well for group  $j$ , measured in accordance with paragraph 2 of QC.33.4.5, in cubic metres per hour at standard conditions;

$t$  = Annual venting time for the representative well for group  $j$ , in hours;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in natural gas, determined in accordance with paragraph 3 of QC.33.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for  $CO_2$  and 0.690 kg per cubic metre for  $CH_4$  at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $CO_2$  or  $CH_4$ ;

(2) for wells venting for liquid unloading with plunger assist, the emissions may be calculated using equation 33-10:

### Equation 33-10

$$GHG_i = \sum_j \left[ \left( \frac{H \times D^2 \times \pi \times P \times N}{4 \times 101.325} \right) (V \times (t - 0.5) \times Z) \right]_j \times \left[ \frac{T_{SC} \times P_{wv}}{T_{wv} \times P_{SC}} \right] \times MF_i \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to well venting for liquid unloading with plunger assist, in metric tons;

$j$  = Well venting for liquid unloading with plunger assist;

$H$  = Tubing depth to plunger bumper, in metres;



- D = Inside diameter of well, in metres;
- $\pi$  = Pi, namely 3.1416;
- P = Natural gas pressure, in kilopascals;
- 101.325 = Standard pressure, in kilopascals;
- N = Number of vents per year;
- V = Average flow rate of gas vented, in cubic metres per hour;
- t = Time during which the well was left open to the atmosphere, in hours;
- 0.5 = Average venting time;
- Z = Equal to 0 if  $t < 0.5$ , or equal to 1 if  $t \geq 0.5$ ;
- $T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;
- $T_{wv}$  = Temperature at well vent, in kelvin;
- $P_{wv}$  = Pressure at well vent, in kilopascals;
- $P_{SC}$  = Pressure at standard conditions of 101.325 kPa;
- $MF_i$  = Molar fraction of greenhouse gas  $i$  in natural gas, determined in accordance with paragraph 3 of QC.33.4;
- $\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for  $CO_2$  and 0.690 kg per cubic metre for  $CH_4$  at standard conditions;
- 0.001 = Conversion factor, kilograms to metric tons;
- $i$  =  $CO_2$  or  $CH_4$ .

QC.33.3.6. Calculation of  $CO_2$ ,  $CH_4$  and  $N_2O$  emissions attributable to natural gas well venting during completions or workovers

The annual  $CO_2$ ,  $CH_4$  and  $N_2O$  emissions attributable to natural gas well venting during completions or workovers must be calculated using one of the following methods:

(1) where the vented gas is directed to flares, according to the method in QC.33.3.13, using the volumes determined in accordance with paragraph 1 of QC.33.4.6;

(2) using equation 33-11:

### Equation 33-11

$$GHG_i = \sum_j (V_{ve} - V_{CO_2-N_2} - V_{res})_j \times MF_i \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to gas well venting during completions or workovers, in metric tons;

$j$  = Gas well;

$V_{ve}$  = Quantity of natural gas vented from well  $j$ , determined in accordance with paragraph 1 of QC.33.4.6, in cubic metres at standard conditions;

$V_{CO_2-N_2}$  = Quantity of  $CO_2$  or nitrogen ( $N_2$ ) injected into well  $j$  during completion or workover, in cubic metres at standard conditions;

$V_{res}$  = Quantity of natural gas from well  $j$  sent to the transmission or distribution system during completion or workover, in cubic metres at standard conditions;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in the gas vented from reciprocating compressor, determined in accordance with paragraph 3 of QC.33.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for  $CO_2$  and 0.690 kg per cubic metre for  $CH_4$  at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $CO_2$  or  $CH_4$ ;

(3) where the flow regime is sonic or subsonic, using equation 33-12:

**Equation 33-12**

$$GHG_i = \sum_j (V_{ve-s} + V_{ve-ss} - V_{CO_2-N_2} - V_{res})_j \times MF_i \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to gas well venting during completions or workovers, in metric tons;

$j$  = Gas well;

$V_{ve-s}$  = Quantity of natural gas emitted during sonic flow conditions from venting of well  $j$ , calculated in accordance with subparagraph *a*, in cubic metres at standard conditions;

$V_{ve-ss}$  = Quantity of gas emitted during subsonic flow conditions from venting of well  $j$ , calculated in accordance with subparagraph *b*, in cubic metres at standard conditions;

$V_{CO_2-N_2}$  = Quantity of  $CO_2$  or  $N_2$  injected into well  $j$  during completion or workover, in cubic metres at standard conditions;

$V_{res}$  = Quantity of natural gas from well  $j$  sent to the transmission or distribution system during completion or workover, in cubic metres at standard conditions;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in the vented gas from reciprocating compressor, determined in accordance with paragraph 3 of QC.33.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for  $CO_2$  and 0.690 kg per cubic metre for  $CH_4$  at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $CO_2$  or  $CH_4$ ;

(a) by determining the quantity of natural gas emitted during sonic flow conditions using the following method:

**Equation 33-13**

$$V_{ve-s} = \left( A \times \sqrt{187.08 \times T_{up}} \times t_s \right)_j \times 3600 \times \left[ \frac{T_{SC} \times P_{wv}}{T_{wv} \times P_{SC}} \right]$$

Where:

$V_{ve-s}$  = Quantity of natural gas emitted during sonic flow conditions from venting of well  $j$ , in cubic metres at standard conditions;

$A$  = Cross sectional area of the orifice, in square metres;

187.08 = Constant, in square metres per second squared per degree kelvin;

$T_{up}$  = Temperature of gas upstream from the choke point, in kelvin;

$t_s$  = Annual duration of venting from well  $j$  in during sonic flow conditions, in hours;

3600 = Conversion factor, seconds to hours;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_{wv}$  = Temperature at well vent, in kelvin;

$P_{wv}$  = Pressure at well vent, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

$j$  = Gas well;

(b) by determining the quantity of gas emitted during subsonic flow conditions from the venting of a well by calculating the total volume under the curve of a plot having the instantaneous flow rate of natural gas to the vent, determined using equation 33-14, as the Y-axis, and time as the X-axis, for the time period during which the well was flowing during subsonic conditions.

**Equation 33-14**

$$D_{ss} = \left( A \times \sqrt{3430 \times T_{up} \times \left[ \left( \frac{P_{do}}{P_{up}} \right)^{1.515} - \left( \frac{P_{do}}{P_{up}} \right)^{1.758} \right]} \right)_j \times 3600 \times \left[ \frac{T_{SC} \times P_{wv}}{T_{wv} \times P_{SC}} \right]$$

Where:

$D_{ss}$  = Instantaneous flow rate of gas emitted during subsonic flow conditions from venting of well  $j$ , in cubic metres per hour at standard conditions;

$A$  = Cross sectional area of the choke point, in square metres;

3430 = Constant, in square metres per second squared per degree kelvin;

$T_{up}$  = Temperature of gas upstream from the choke point, in kelvin;

$P_{do}$  = Pressure downstream from the choke point, in kilopascals;

$P_{up}$  = Pressure upstream from the choke point, in kilopascals;

$j$  = Gas well;

3600 = Conversion factor, seconds to hours;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_{ww}$  = Temperature at well vent, in kelvin;

$P_{ww}$  = Pressure at well vent, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

QC.33.3.7. Calculation of CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to blowdown vent stacks

The CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to natural gas emissions to the atmosphere from equipment blowdown vent stacks, except equipment depressurizing to a flare, which must be calculated using QC.33.3.13, a dehydrator, which must be calculated using QC.33.3.4, over-pressure relief valve, which must be calculated using QC.33.3.16, or operating pressure control valve, which must be calculated using QC.33.3.1 and QC.33.3.3, must be calculated using equation 33-15:

#### Equation 33-15

$$GHG_i = \sum_{j=1}^n \left[ N_j \times V_j \times \left( \frac{T_{SC}}{T_B \times P_{SC}} \right) \times (P_{d1} - P_{d2}) \right] \times MF_i \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to natural gas emissions to the atmosphere from equipment blowdown vent stacks, in metric tons;

$n$  = Total number of types of equipment;

$j$  = Type of equipment with the same natural gas volume in the blowdown equipment chambers between isolation valves;

$N_j$  = Annual number of blowdowns for each equipment type  $j$ , determined in accordance with paragraph 2 of QC.33.4.7;

$V_j$  = Total volume of natural gas in blowdown equipment chambers, between isolation valves, for equipment type  $j$ , determined in accordance with paragraph 1 of QC.33.4.7, in cubic metres;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_B$  = Temperature at blowdown conditions, in kelvin;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

$P_{d1}$  = Absolute pressure before depressurization, in kilopascals;

$P_{d2}$  = Absolute pressure after depressurization or a value of 0 if the equipment is purged using a gas other than  $CO_2$  or  $CH_4$ , in kilopascals;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in natural gas, determined in accordance with paragraph 3 of QC.33.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for  $CO_2$  and 0.690 kg per cubic metre for  $CH_4$  at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $CO_2$  or  $CH_4$ .

QC.33.3.8. Calculation of CH<sub>4</sub> emissions attributable to third party line hits

The annual CH<sub>4</sub> emissions attributable to third party line hits that result in emissions equal to or greater than 1.416 m<sup>3</sup> of CH<sub>4</sub> at standard conditions must be calculated using equations 33-16 and 33-17 for catastrophic pipeline ruptures and pipeline puncture incidents when the flow is choked and using equation 33-18 for pipeline puncture incidents when the flow is not choked:

**Equation 33-16**

$$CH_4 = \frac{3.6 \times 10^6 \times A}{\rho_s} \times \sqrt{\frac{K \times MW}{1000 \times R \times T}} \times \frac{P_a \times M}{\left(1 + \frac{K-1}{2} M^2\right)^{\frac{K+1}{2(K-1)}}} \times t \times \left[\frac{T_{SC} \times P_{ge}}{T_{ge} \times P_{SC}}\right] \times \rho_s \times 0.001$$

Where:

CH<sub>4</sub> = Annual CH<sub>4</sub> emissions attributable to a third party catastrophic pipeline rupture or a pipeline puncture incident when the flow is choked, in metric tons;

A = Cross-sectional flow area of the pipe, in square metres;

ρ<sub>s</sub> = Density of CH<sub>4</sub>, namely 0.690 kg per cubic metre at standard conditions;

K = Specific heat ratio of CH<sub>4</sub>, namely 1.299;

MW = Molecular weight of CH<sub>4</sub>, namely 16.043 kg per kilomole;

R = Universal gas constant, namely 8.3145 kPa m<sup>3</sup> per kilomole per degree kelvin;

T = Temperature inside pipe, in kelvin;

P<sub>a</sub> = Pressure inside pipe, determined in accordance with paragraph 2 of QC.33.4.8, in kilopascals;

M = Mach number of the flow, calculated using equation 33-17 when M is equal to or smaller than 1 or a value of 1 in other cases, in metres per second;

t<sub>j</sub> = Duration of the leak caused by a third party hit, in hours;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_{ge}$  = Temperature of gas emitted, in kelvin;

$P_{ge}$  = Pressure of gas emitted, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

0.001 = Conversion factor, kilograms to metric tons;

### Equation 33-17

$$M = \sqrt{\frac{2 \left[ \left( \frac{P_a}{P_e} \right)^{\frac{K-1}{K}} - 1 \right]}{K-1}}$$

Where:

$M$  = Mach number of the flow, in metres per second;

$P_a$  = Pressure inside pipe, determined in accordance with paragraph 2 of QC.33.4.8, in kilopascals;

$P_e$  = Ambient air pressure at the damage point, in kilopascals;

$K$  = Specific heat ratio of  $CH_4$ , namely 1.299;

### Equation 33-18

$$CH_4 = \frac{A_e}{\rho_{ref}} \times \sqrt{\frac{2000 \times K}{K-1}} \times P_a \times \rho_a \times \left[ \left( \frac{P_{atm}}{P_a} \right)^{2/K} - \left( \frac{P_{atm}}{P_a} \right)^{(K+1)/K} \right] \times t \times \left[ \frac{T_{SC} \times P_{ge}}{T_{ge} \times P_{SC}} \right] \times \rho_{ref} \times 0.001$$

Where:

$CH_4$  = Annual  $CH_4$  emissions attributable to third party pipeline puncture incident when the flow is not choked, in metric tons;

$A_e$  = Size of the hole in the pipe, in square metres;

$K$  = Specific heat ratio of  $CH_4$ , namely 1.299;

$\rho_{ref}$  = Density of  $CH_4$ , namely 0.690 kg per cubic metre at standard conditions;



$\rho_a$  = Density of CH<sub>4</sub> inside pipe at the damage point, in kilograms per cubic metre;

$P_a$  = Pressure inside pipe, determined in accordance with paragraph 3 of QC.33.4.8, in kilopascals;

$P_{atm}$  = Atmospheric pressure at the damage point, in kilopascals;

$R$  = Universal gas constant, namely 8.3145 kPa m<sup>3</sup> per kilomole per degree kelvin;

$t_j$  = Duration of the leak caused by the puncture incident, in hours;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_{ge}$  = Temperature of gas emitted, in kelvin;

$P_{ge}$  = Pressure of gas emitted, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

0.001 = Conversion factor, kilograms to metric tons.

QC.33.3.9. Calculation of CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to venting from storage tanks associated with onshore oil and natural gas exploration, production, processing and storage facilities

The CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to atmospheric pressure fixed roof storage tanks receiving hydrocarbon produced liquids from onshore oil and natural gas exploration and production facilities and onshore natural gas processing facilities must be calculated using one of the following methods:

(1) when the gas is directed to flares, using the method in QC.33.3.13 and the volumes determined in accordance with paragraph 6 of QC.33.4.9;

(2) in other cases, using equation 33-19:

#### Equation 33-19

$$GHG_i = \sum_j (GLR \times V \times MF_i)_j \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Emissions of greenhouse gas  $i$  attributable to atmospheric pressure fixed roof storage tanks receiving hydrocarbon produced liquids from onshore oil and natural gas exploration and production facilities and onshore natural gas processing facilities, in metric tons;

$GLR_j$  = Gas oil ratio in storage tank  $j$ , determined in accordance with QC.33.4.9, in cubic metres of gas per cubic metre of liquid at standard conditions;

$j$  = Atmospheric pressure fixed roof storage tank receiving hydrocarbon produced liquids from onshore oil and natural gas exploration and production facilities and onshore natural gas processing facilities;

$V$  = Annual volume of liquid produced, determined in accordance with paragraph 6 of QC.33.4.9, in cubic metres;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in the gas, determined in accordance with paragraph 3 of QC.33.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for  $CO_2$  and 0.690 kg per cubic metre for  $CH_4$  at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $CO_2$  or  $CH_4$ ;

(3) using the latest software package for E&P Tank (exploration and production tank) of the American Petroleum Institute and the following parameters to characterize emissions:

- (a) separator oil composition;
- (b) separator temperature;
- (c) separator pressure;
- (d) sales oil API gravity;
- (e) sales oil production rate;

- (f) sales oil Reid vapour pressure;
- (g) ambient air temperature;
- (h) ambient air pressure.

QC.33.3.10. Calculation of CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to transmission storage tanks

Except for emissions sent to flares, which must be calculated in accordance with QC.33.3.13, the annual CH<sub>4</sub>, CO<sub>2</sub> and N<sub>2</sub>O emissions attributable to compressor scrubber dump valve leakage from condensate storage tanks, connected to transmission storage tanks for water or hydrocarbon, must be calculated using equations 33-20:

**Equation 33-20**

$$GHG_i = \sum_{j=1}^n [EF \times t]_j \times MF_i$$

Where:

GHG<sub>i</sub> = Annual emissions of greenhouse gas *i* attributable to compressor scrubber dump valve leakage from condensate storage tanks connected to transmission storage tanks, in metric tons;

n = Number of equipments;

j = Device;

EF = Emission factor for leakage from device *j*, determined in accordance with QC.33.4.10, in metric tons per hour;

t = Duration of leak from device *j*, determined in accordance with QC.33.4.10, in hours;

MF<sub>i</sub> = Molar fraction of greenhouse gas *i* in gas from reciprocating compressor venting, determined in accordance with paragraph 3 of QC.33.4;

i = CO<sub>2</sub> or CH<sub>4</sub>.

QC.33.3.11. Calculation of CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to venting and flaring during well testing

The CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions vented and flared during well testing must be calculated using one of the following methods:

(1) if the gas is directed to flares, using the method in QC.33.3.13 and the volumes determined in accordance with paragraph 2 of QC.33.4.11;

(2) in other cases, when the quantity of liquid is sufficient to calculate a natural gas to liquid ratio (GLR), using equation 33-21:

**Equation 33-21**

$$GHG_i = \sum_j (GLR \times F_L \times MF_i \times t)_j \times \rho_i \times 0.001$$

Where:

GHG<sub>i</sub> = Annual emissions of greenhouse gas *i* vented during well testing, in metric tons;

*j* = Well tested;

GLR = Gas to liquid ratio for well *j*, determined in accordance with paragraph 1 of QC.33.4.11, in cubic metres of natural gas per cubic metre of liquid at standard conditions;

F<sub>L</sub> = Liquid flow rate in well *j*, in cubic metres per hour;

MF<sub>i</sub> = Molar fraction of greenhouse gas *i* in gas in well *j*, determined in accordance with paragraph 3 of QC.33.4;

*t* = Duration of testing of well *j*, in hours;

ρ<sub>i</sub> = Density of greenhouse gas *i* that is 1.893 kg per cubic metre for CO<sub>2</sub> and 0.690 kg per cubic metre for CH<sub>4</sub> at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

*i* = CO<sub>2</sub> or CH<sub>4</sub>;

(3) in other cases, where insufficient liquids are produced and the gas to liquid ratio (GLR) approaches infinity, using equation 33-22:

**Equation 33-22**

$$GHG_i = \sum_j (D_g \times MF_i \times t)_j \times \rho_i \times 0.001$$

Where:

GHG<sub>i</sub> = Annual emissions of greenhouse gas *i* vented during well testing, in metric tons;

*j* = Well tested;

D<sub>g</sub> = Average gas flow rate from venting of well *j* during testing, measured in accordance with paragraph 2 of QC.33.4.11, in cubic metres per hour at standard conditions;

MF<sub>i</sub> = Molar fraction of greenhouse gas *i* in the gas du well *j*, determined in accordance with paragraph 3 of QC.33.4;

*t* = Duration of testing of well *j*, in hours;

ρ<sub>i</sub> = Density of greenhouse gas *i* that is 1.893 kg per cubic metre for CO<sub>2</sub> and 0.690 kg per cubic metre for CH<sub>4</sub> at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

*i* = CO<sub>2</sub> or CH<sub>4</sub>.

QC.33.3.12. Calculation of CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to associated gas from wells

The annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to associated gas from wells, except emissions attributable to production tests, which must be calculated in accordance with QC.33.3.11, must be calculated using one of the following methods:

(1) using the method in QC.33.3.13 where the gas is directed to flares, using the volumes determined by multiplying the volume of liquid produced by the gas to liquid ration determined in accordance with QC.33.4.12;

(2) in other cases, using equation 33-23:

**Equation 33-23**

$$GHG_i = \sum_j (GLR \times V \times MF_i)_j \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to associated gas, in metric tons;

$j$  = Well;

$GLR$  = Associated gas to liquid ratio for well  $j$ , determined in accordance with QC.33.4.12, in cubic metres of associated gas per cubic metre of liquid at standard conditions;

$V$  = Annual volume of liquid produced, in cubic metres;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in gas in well  $j$ , determined in accordance with paragraph 3 of QC.33.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for  $CO_2$  and 0.690 kg per cubic metre for  $CH_4$  at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $CO_2$  or  $CH_4$ .

QC.33.3.13. Calculation of  $CO_2$ ,  $CH_4$  and  $N_2O$  emissions attributable to flaring

The annual  $CO_2$ ,  $CH_4$  and  $N_2O$  emissions attributable to flaring must be calculated using the following methods:

(1) the annual  $CO_2$  emissions attributable to flaring must be calculated using equation 33-24:

**Equation 33-24**

$$CO_2 = \left[ (V_G \times MF_{CO_2}) + \left( \sum_{k=1}^m (MF_k \times AC_k) \times V_G \times eff_f \right) \right] \times \left[ \frac{T_{SC} \times P_f}{T_f \times P_{SC}} \right] \times \rho_{CO_2} \times 0.001$$

Where:

$CO_2$  = Annual  $CO_2$  emissions attributable to flaring, in metric tons;

$V_G$  = Annual volume of gas flared, determined in accordance with QC.33.4.13, in cubic metres;

$MF_{CO_2}$  = Mole fraction of  $CO_2$  in the gas flared, determined in accordance with paragraph 3 of QC.33.4;

$m$  = Total number of hydrocarbons in the gas stream;

$k$  = Hydrocarbon in the gas stream;

$MF_k$  = Mole fraction of hydrocarbon  $k$  in the gas stream, determined in accordance with QC.33.4.13;

$AC_k$  = Number of carbon atoms in hydrocarbon  $k$  in the gas stream, namely 1 for methane, 2 for ethane, 3 for propane, 4 for butane, 5 for pentanes, 6 for hexanes and 7 for hexanes plus;

$eff_f$  = Flare combustion efficiency determined by the manufacturer, or a default value of 0.98;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_f$  = Flare combustion temperature, in kelvin;

$P_f$  = Flare combustion pressure, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

$\rho_{CO_2}$  = Density of  $CO_2$ , namely 1.893 kg per cubic metre, at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

(2) the annual  $CH_4$  emissions attributable to flaring must be calculated using equation 33-25:

### Equation 33-25

$$CH_4 = \left[ V_G \times MF_{CH_4} \times (1 - eff_f) \right] \times \left[ \frac{T_{SC} \times P_f}{T_f \times P_{SC}} \right] \times \rho_{CH_4} \times 0.001$$

Where:

$CH_4$  = Annual  $CH_4$  emissions attributable to flaring, in metric tons;

$V_G$  = Annual volume of gas flared, determined in accordance with QC.33.4.13, in cubic metres;

$MF_{CH_4}$  = Mole fraction of  $CH_4$  in the gas flared, determined in accordance with paragraph 3 of QC.33.4;

$eff_f$  = Flare combustion efficiency determined by the manufacturer, or a default value of 0.98;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_f$  = Flare combustion temperature, in kelvin;

$P_f$  = Flare combustion pressure, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

$\rho_{CH_4}$  = Density of  $CH_4$ , namely 0.690 kg per cubic metre, at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

(3) the annual  $N_2O$  emissions attributable to flaring must be calculated using equation 33-26:

**Equation 33-26**

$$N_2O = V_G \times HHV \times EF_{N_2O} \times 0.001$$

Where:

$N_2O$  = Annual  $N_2O$  emissions attributable to flaring, in metric tons;

$V_G$  = Annual volume of gas flared, determined in accordance with QC.33.4.13, in cubic metres at standard conditions;

HHV = High heat value of gas as specified in Tables 1-1 and 1-2 in QC.1.7 or high heat value of  $4.579 \times 10^{-2}$  GJ per cubic metre for gas from equipment venting or determined in accordance with QC.1.5.4, in gigajoules per cubic metre at standard conditions;



$EF_{N_2O}$  =  $N_2O$  emission factor, namely  $9.52 \times 10^{-5}$  kg per gigajoule;

0.001 = Conversion factor, kilograms to metric tons.

#### QC.33.3.14. Calculation of $CO_2$ and $CH_4$ emissions attributable to centrifugal compressor venting

The annual  $CO_2$  and  $CH_4$  emissions attributable to centrifugal compressor venting must be calculated using the following methods:

(1) for each centrifugal compressor, the emitter must determine, in accordance with QC.33.4.14, the volume of gas from the wet seal oil degassing tank that is vented to the atmosphere and the volume of gas directed to flares;

(2) the annual  $CO_2$  and  $CH_4$  emissions attributable to gas vented to the atmosphere from centrifugal compressors must be calculated using equation 33-27 where the aggregate rated power for the sum of centrifugal compressors at the establishment is equal to or greater than 186.4 kW and using equation 33-28 where the aggregate rated power of the centrifugal compressors at the establishment is less than 186.4 kW:

#### Equation 33-27

$$GHG_i = \sum_{j=1}^n \left[ \sum_{m=1}^z (F_{G,i} \times t_j)_m \times (1 - FG_j) \right] \times MF_i \times \left[ \frac{T_{SC} \times P_{cc}}{T_{cc} \times P_{SC}} \right] \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to atmospheric centrifugal compressor vents, in metric tons;

$n$  = Total number of centrifugal compressors;

$j$  = Centrifugal compressor;

$z$  = Number of operating modes of centrifugal compressor;

$m$  = Operating mode of centrifugal compressor;

$F_{G,j}$  = Gas flow from the atmospheric vent of centrifugal compressor  $j$  in operating mode  $m$ , determined in accordance with QC.33.4.14, in cubic metres per hour;

$t_j$  = Annual operating time of centrifugal compressor  $j$  equipped with a wet seal oil degassing tank in operating mode  $m$ , in hours;

$FG_j$  = Portion of gas from the atmospheric vent of centrifugal compressor  $j$  that is recovered using a vapour recovery system or destined for another use, determined in accordance with QC.33.4.14, expressed as a percentage;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in the gas from atmospheric vents, determined in accordance with paragraph 3 of QC.33.4;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_{cc}$  = Temperature at the atmospheric vent of centrifugal compressor, in kelvin;

$P_{cc}$  = Pressure at the atmospheric vent of centrifugal compressor, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for  $CO_2$  and 0.690 kg per cubic metre for  $CH_4$  at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $CO_2$  or  $CH_4$ ;

### Equation 33-28

$$GHG_i = N \times EF_i \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to atmospheric centrifugal compressor vents, in metric tons;

$N$  = Total number of centrifugal compressors;

$EF_j$  = Emission factor, namely 15,234.5  $m^3$  for  $CO_2$  and 345,465.5  $m^3$  for  $CH_4$ , at standard conditions;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for  $CO_2$  and 0.690 kg per cubic metre for  $CH_4$  at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $CO_2$  or  $CH_4$ ;

(3) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to the gas directed to flares must be calculated in accordance with the calculation methods in QC.33.3.13 using the volumes of gas determined in accordance with QC.33.4.14.

QC.33.3.15. Calculation of CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to reciprocating compressor venting

The annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to reciprocating compressor venting must be calculated using the following methods:

(1) for each reciprocating compressor, the emitter must determine the gas flow from the venting in accordance with paragraph 1 of QC.33.4.15;

(2) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to gas vented to the atmosphere from centrifugal compressors must be calculated using equation 33-29 where the aggregate rated power of the centrifugal compressors at the establishment is equal to or greater than 186.4 kW or using equation 33-30 where the aggregate rated power of the reciprocating compressors at the establishment is less than 186.4 kW:

#### Equation 33-29

$$GHG_i = \sum_{j=1}^n \left[ \sum_{m=1}^z (F_{G,j} \times t_j)_m \times (1 - FG_j) \right] \times MF_i \times \left[ \frac{T_{SC} \times P_{rc}}{T_{rc} \times P_{SC}} \right] \times \rho_i \times 0.001$$

Where:

GHG<sub>i</sub> = Annual emissions of greenhouse gas *i* attributable to reciprocating compressor venting, in metric tons;

*n* = Total number of reciprocating compressors;

*j* = Reciprocating compressor;

*z* = Number of operating modes of reciprocating compressor;

*m* = Operating mode of reciprocating compressor;

F<sub>G,j</sub> = Gas flow from the venting of reciprocating compressor *j* in operating mode *m*, determined in accordance with paragraph 1 of QC.33.4.15, in cubic metres per hour;

$t_j$  = Annual operating time of reciprocating compressor  $j$  in operating mode  $m$ , determined in accordance with QC.33.4.15, in hours;

$FG_j$  = Portion of gas from the vent of reciprocating compressor  $j$  that is recovered using a vapour recovery system, determined in accordance with paragraph 5 of QC.33.4.15, expressed as a percentage;

$MF_i$  = Molar fraction of greenhouse gas  $i$  in the gas from the reciprocating compressor venting, determined in accordance with paragraph 3 of QC.33.4;

$T_{SC}$  = Temperature at standard conditions of 293.15 kelvin;

$T_{rc}$  = Temperature at the reciprocating compressor vent, in kelvin;

$P_{rc}$  = Pressure at the reciprocating compressor vent, in kilopascals;

$P_{SC}$  = Pressure at standard conditions of 101.325 kPa;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for CO<sub>2</sub> and 0.690 kg per cubic metre for CH<sub>4</sub> at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  = CO<sub>2</sub> or CH<sub>4</sub>;

### Equation 33-30

$$GHG_i = N \times EF_i \times \rho_i \times 0.001$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to reciprocating compressor venting to the atmosphere, in metric tons;

$N$  = Total number of reciprocating compressors;

$EF_j$  = Emission factor, namely 15.2 m<sup>3</sup> for CO<sub>2</sub> and 272.7 m<sup>3</sup> for CH<sub>4</sub>, at standard conditions;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for CO<sub>2</sub> and 0.690 kg per cubic metre for CH<sub>4</sub> at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  = CO<sub>2</sub> or CH<sub>4</sub>;

(3) the annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to gas directed to flares must be calculated in accordance with the calculation methods in QC.33.3.13 using the gas flow rates determined in accordance with QC.33.4.15.

QC.33.3.16. Calculation of CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to leaks identified following a leak detection survey

Except for emissions from emission sources for which the total weight of CO<sub>2</sub> and CH<sub>4</sub> in the natural gas is below 10%, which must be calculated in accordance with QC.33.3.20, the annual fugitive CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to leaks identified following a leak detection survey must be calculated for each source for which leaks are detected using equation 33-31:

**Equation 33-31**

$$GHG_i = \sum_{j=1}^n [N_j \times EF_j \times t_j] \times MF_i \times \rho_i \times 0.001$$

Where:

GHG<sub>*i*</sub> = Annual emissions of greenhouse gas *i*, for each source of fugitive emissions, in metric tons;

$n$  = Total number of types of components, by fugitive emission source;

$j$  = Type of component;

$N_j$  = Total number of components of type *j*;

EF<sub>*j*</sub> = Emission factor for leaks from each type of component *j*, determined in accordance with paragraph 1 of QC.33.4.16, in cubic metres per hour at standard conditions;

$t_j$  = Duration of leakage from component *j*, determined in accordance with paragraph 2 of QC.33.4.16, in hours;

MF<sub>*i*</sub> = Molar fraction of greenhouse gas *i* in the gas from reciprocating compressor venting, determined in accordance with paragraph 3 of QC.33.4;

$\rho_i$  = Density of greenhouse gas  $i$  that is 1.893 kg per cubic metre for CO<sub>2</sub> and 0.690 kg per cubic metre for CH<sub>4</sub> at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  = CO<sub>2</sub> or CH<sub>4</sub>.

QC.33.3.17. Calculation of fugitive CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to all components

Except for emissions from emission sources with gas containing less than 10% CO<sub>2</sub> plus CH<sub>4</sub> by weight, which do not need to be calculated, annual fugitive CO<sub>2</sub> and CH<sub>4</sub> emissions must be calculated equation 33-32 for all centrifugal or reciprocating compressor components used in natural gas and oil exploration and production, or using equation 33-33 for gathering pipeline components:

**Equation 33-32**

$$GHG_i = \sum_k \left[ \sum_j \left( N_{j,k} \times \frac{EF_{j,k}}{THC_k} \times Fr_{i,k} \right) \right] \times t$$

Where:

GHG<sub>*i*</sub> = Annual emissions of greenhouse gas  $i$  for each source of fugitive emissions, in metric tons;

$k$  = Type of service listed in Tables 33-1 and 33-2 in QC.33.6, namely Gas/Vapour or Fuel Gas or Light Liquid or Heavy Liquid;

$j$  = Type of component;

$N_{j,k}$  = Total number of components of type  $j$ , determined in accordance with QC.33.4.17;

$EF_{j,k}$  = Emission factor for each type of component  $j$ , determined in accordance with QC.33.4.17, in metric tons of total hydrocarbon per component per hour;

$THC_k$  = Mass fraction of total hydrocarbons in service  $k$ ;

$Fr_{i,k}$  = Mass fraction of greenhouse gas  $i$  in service  $k$ ;

$t$  = Total time the component type at the origin of the fugitive emissions was operational, in hours;

$i$  = CO<sub>2</sub> or CH<sub>4</sub>;

### Equation 33-33

$$GHG_i = EF_i \times L \times t$$

Where:

$GHG_i$  = Annual emissions of greenhouse gas  $i$  attributable to gathering pipeline components, in metric tons;

$EF_i$  = Emission factor associated with gathering pipeline components, namely  $2.66 \times 10^{-5}$  for CH<sub>4</sub> and  $6.35 \times 10^{-6}$  for CO<sub>2</sub>, in metric tons par kilometre per hour;

$L$  = Length of the gathering pipeline, in kilometres;

$t$  = Total time the gathering pipeline was operational in the year, in hours;

$i$  = CO<sub>2</sub> or CH<sub>4</sub>.

QC.33.3.18. Calculation of CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to EOR injection pump blowdown

The annual CO<sub>2</sub> and CH<sub>4</sub> emissions attributable to EOR injection pump blowdown must be calculated using equation 33-34:

### Equation 33-34

$$GHG_i = \sum_j (N \times V \times F_i) \times \rho_i \times 0.001$$

Where:

$\text{GHG}_i$  = Annual emissions of greenhouse gas  $i$  attributable to EOR injection pump blowdown, in metric tons;

$j$  = Injection pump;

$N$  = Annual number of blowdowns for injection pump  $j$ , determined in accordance with QC.33.4.18;

$V$  = Volume of gas per blowdown, determined in accordance with QC.33.4.18, in cubic metres at standard conditions;

$F_i$  = Mass fraction of greenhouse gas  $i$  in the gas injected with injection pump  $j$ ;

$\rho_i$  = Density of critical phase greenhouse gas  $i$ , determined in accordance with QC.33.4.18, in kilograms per cubic metre at standard conditions;

0.001 = Conversion factor, kilograms to metric tons;

$i$  =  $\text{CO}_2$  or  $\text{CH}_4$ .

QC.33.3.19. Calculation of  $\text{CO}_2$ ,  $\text{CH}_4$  and  $\text{N}_2\text{O}$  emissions attributable to the combustion of field gas and process vent gas

The annual  $\text{CO}_2$ ,  $\text{CH}_4$  and  $\text{N}_2\text{O}$  emissions attributable to the combustion of field gas and process vent gas must be calculated in accordance with QC.33.4.19.

QC.33.3.20. Calculation of fugitive emissions from other sources

Fugitive emissions from other sources that are not calculated using the methods in QC.33.3.1 to QC.33.3.19 must be calculated using the methods in the most recent version of

(1) "Compendium of Greenhouse Gas Emissions Methodologies for the Oil and Natural Gas Industry" published in August 2009 by the American Petroleum Institute;

(2) Table 6-22, "A National Inventory of Greenhouse Gas (GHG)", published by Clearstone Engineering Ltd.;



(3) “Criteria Air Contaminant (CAC) and Hydrogen Sulphide (H<sub>2</sub>S) Emissions by the Upstream Oil and Gas Industry, Volume 5”, published in September 2004 by the Canadian Association of Petroleum Producers.

QC.33.3.21. Calculation of annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O fugitive emissions at offshore oil and gas exploration and production facilities from equipment leaks, venting and flaring

The annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O fugitive emissions at offshore oil and gas exploration and production facilities from equipment leaks, venting and flaring must be calculated using the data estimation and collection method of the Bureau of Ocean Energy Management, Regulation and Enforcement (BOEMRE), and in accordance with the method in Parts 250.302 to 304 of Title 30 of the Code of Federal Regulations published by the U.S. Environmental Protection Agency (USEPA).

#### **QC.33.4. Sampling, analysis and measurement requirements**

An emitter operating an oil or natural gas exploration and production or natural gas processing establishment must

(1) ensure that all the instruments used for sampling, analysis and measurement are calibrated before the first emissions report and annually thereafter, and operate in accordance with the manufacturer's instructions or in accordance with the methods published by the following organizations:

- (a) Canadian Standards Association;
- (b) Canadian Gas Association;
- (c) Canadian Association of Petroleum Producers;
- (d) American National Standards Institute;
- (e) American Society of Testing and Materials;
- (f) American Petroleum Institute;
- (g) American Society of Mechanical Engineers;
- (h) North American Energy Standards Board;

- (i) Canadian Energy Pipeline Association;
- (j) Measurement Canada;
- (k) Centre d'expertise en analyse environnementale du Québec;

(2) conduct leak detection surveys and manage transmission and distribution system integrity in accordance with the most recent version of CSA Z662-11 "Oil and gas pipeline systems" published by the Canadian Standards Association in June 2011 and in accordance with the Construction Code (c. B-1.1, r. 2);

(3) determine the mole fraction of CO<sub>2</sub> and CH<sub>4</sub> in the natural gas by calculating the annual average of the following mole fractions in accordance with the second paragraph;

(4) from 1 January 2015, ensure that all high bleed pneumatic devices and all natural gas driven pneumatic pumps are equipped with meters.

The molar fraction of CO<sub>2</sub> and CH<sub>4</sub> must be determined as follows:

(1) for oil or natural gas exploration or production, by determining the molar fraction in the gas produced;

(a) if the facility is equipped with a continuous gas composition analyzer, using the average annual value;

(b) if the facility is not equipped with a continuous gas composition analyzer, using the annual average of the known gas composition for (in required order of preference):

(i) the establishment;

(ii) the company for the same oil or gas field operated during the same reporting period or, if not available, the previous reporting period;

(2) for natural gas processing, in the feed natural gas:

(a) for all equipment downstream of the de-methanizer or dew point control, by determining the molar fraction for all gas sources upstream of the de-methanizer or dew point control and in the gas going to transmission pipeline systems;

(b) for facilities that solely fractionate a liquid stream, by determining the molar fraction in the feed natural gas;

(c) for a facility that is equipped with a continuous gas composition analyzer in the feed gas stream, using the average annual value;

(d) for a facility that is not equipped with a continuous gas composition analyzer, using the annual average of the known gas composition for (in required order of preference):

(i) the establishment;

(ii) the company for the same oil or gas field operated during the same reporting period or, if not available, the previous reporting period.

#### QC.33.4.1. High bleed pneumatic device venting and natural gas driven pneumatic pump venting

For high bleed pneumatic device venting and natural gas driven pneumatic pump venting, the emitter must determine the number of high bleed pneumatic devices and natural gas driven pneumatic pumps as follows:

(1) for the first emissions report year, count all equipment by type or estimate the total equipment count and break down the result by the estimated percentage of each equipment type;

(2) for subsequent years, update the number of high bleed pneumatic devices and natural gas driven pneumatic pumps to reflect the annual changes.

In addition, the emitter must

(1) when using equation 33-2, determine the annual volume of natural gas consumed by the high bleed pneumatic devices or the quantity of natural gas consumed by the natural gas driven pneumatic pump using measuring equipment, such as a meter, installed on the equipment;

(2) when using equation 33-3, obtain from the equipment manufacturer the natural gas emission factor for each high bleed pneumatic device under normal operating conditions or, when those data are not available, use the flow for similar equipment. If there is no similar equipment, the emitter must use the data from Table 33-3 or 33-4 in QC.33.6;

(3) when using equation 33-4:

(a) obtain from the manufacturer the quantity of natural gas consumed per volume of liquid pumped in normal operating conditions for each model of pneumatic pump under normal operating conditions or, when those data are not available, use data for similar equipment;

(b) maintain a log of the quantity of liquid pumped annually by each natural gas driven pneumatic pump venting.

QC.33.4.2. Natural gas driven low or intermittent bleed pneumatic device venting

For natural gas driven low or intermittent bleed pneumatic device venting, the emitter must

(1) determine the number of natural gas driven low bleed pneumatic devices and the number of natural gas driver intermittent bleed pneumatic devices as follows:

(a) for the first emissions report year, by counting all devices by type or estimating the total device count and breaking down the result by the estimated percentage of each device type;

(b) for subsequent years, by updating the number of low bleed pneumatic devices and intermittent bleed devices to reflect annual changes;

(2) determine the emission factor for each type of pneumatic device as follows:

(a) for low bleed pneumatic devices, using the values specified in Table 33-3 in QC.33.6;

(b) for intermittent bleed pneumatic devices that maintain operating conditions such as liquid level, pressure, pressure differential or temperature, using the data available in the following order:

(i) the values specified in Table 33-4;

(ii) the emission factor for a similar device;

(iii) the emission factor for intermittent bleed pneumatic devices specified in Table 33-3;

(c) for intermittent bleed pneumatic devices used for compressor startup, using the emission factor provided by the manufacturer.

#### QC.33.4.3. Acid gas scrubbing equipment

For acid gas scrubbing equipment, the emitter must

(1) measure the annual volume of processed gas output from the acid gas scrubbing equipment using appropriate measuring equipment in accordance with a method published by one of the organizations listed in paragraph 1 of QC.33.4;

(2) measure the mole fraction of CO<sub>2</sub> in the input and output natural gas of the acid gas scrubbing equipment using a continuous gas composition analyzer or, when the equipment is not equipped with an analyzer, by taking a monthly sample;

(3) measure the mole fraction of H<sub>2</sub>S in the input and output natural gas of the acid gas scrubbing equipment using a continuous gas composition analyzer or, when the equipment is not equipped with an analyzer, using an analysis method published by an organization listed in QC.1.5.

#### QC.33.4.4. Dehydrator vents

To determine wet natural gas composition for dehydrator vents, the emitter must

(1) when the dehydrator is equipped with a continuous gas composition analyzer, use the average annual value;

(2) when the dehydrator is not equipped with a continuous gas composition analyzer, use the annual average of the measured gas composition for the establishment;

(3) use a method published by an organization listed in paragraph 1 of QC.33.4;

(4) when only the dry natural gas composition output from the dehydrator is available, assume that the wet input gas is saturated.

#### QC.33.4.5. Well venting for liquids unloading

For well venting for liquids unloading, the emitter must

(1) group the wells by well diameter and pressure in each gas producing field where wells are vented to the atmosphere;

(2) for each group of wells, install a meter on a representative well in the group;

(3) determine the average gas flow rate measured on the vent line used to vent gas from the well using the following method:

(a) by dividing the volume of gas measured on the vent line from the well by the total annual venting time for each liquid unloaded;

(b) by applying the average flow rate to all the wells in each group determined in accordance with paragraph 1;

(c) by recalculating the average flow rate for the group each year.

For a new producing field or a new horizon combination, the average flow rate must be calculated beginning in the first year of production.

#### QC.33.4.6. Natural gas well venting during completions or workovers

For natural gas well venting during completions or workovers, the emitter must

(1) measure the volume of natural gas vented from gas wells during completions or workovers using a flowmeter installed on the vent;

(2) when the method in paragraph 3 of QC.33.3.6 is used:

(a) make a series of measurements of upstream pressure and downstream pressure across a choke during the entire completion and workover period, at a sufficient frequency to determine the flow regime in accordance with subparagraph *b*;

(b) determine the flow regime by calculating the “downstream pressure over upstream pressure” ratio at the choke as follows:

Sonic flow regime if  $P_{av} / P_{am} \leq 0.542$

Subsonic flow regime if  $P_{av} / P_{am} > 0.542$

Where:

$P_{am}$  = Vent pressure upstream from choke point, in kilopascals;

$P_{av}$  = Vent pressure downstream from choke point, in kilopascals.

#### QC.33.4.7. Blowdown vent stacks

For blowdown vent stacks, the emitter must

(1) calculate the volume of natural gas in blowdown chambers between the isolation valves for each piece of equipment;

(2) when the volume is equal to or greater than 1.42 m<sup>3</sup> at standard conditions, log the annual number of blowdowns for each piece of equipment.

#### QC.33.4.8. Third party line hits

For fugitive emissions attributable to third party line hits, the emitter must

(1) for a pipeline puncture incident, determine whether or not the flow is choked, using the following method:

If  $P_{atm} / P_a \geq 0.546$  flow is not choked;

If  $P_{atm} / P_a < 0.546$  flow is choked;

Where:

$P_a$  = Pressure inside pipe, determined in accordance with paragraph 3 of QC.33.4.8, in kilopascals;

$P_{atm}$  = Atmospheric pressure at the damage point, in kilopascals;

(2) for a catastrophic pipeline rupture, determine the pressure inside the pipe at the place where the ruptured pipeline joins a larger pipeline;

(3) for a pipeline puncture incident, determine the pressure inside the pipe at the damage point.

33.4.9. Emissions attributable to venting from oil and natural gas storage tanks associated with onshore exploration, production and processing facilities

For emissions attributable to atmospheric pressure fixed roof storage tanks receiving hydrocarbon produced liquids from onshore oil and gas exploration and production facilities and onshore natural gas processing facilities, the emitter must, to calculate the gas oil ratio,

(1) collect a pressurized sample of produced liquids from the separator at a location upstream of the storage tank; the sample must be collected at the pressure of the final separation device before the transition to a storage tank at atmospheric pressure using one of the following methods:

(a) the most recent revision of “E&P TANK Version 2.0 User’s Manual Appendix C, Sampling Protocol Section”, published by the American Petroleum Institute;

(b) the guidance document “Oil and Gas Production Facilities, Chapter 6, Section 2 Permitting Guidance, Appendix D Sampling and Analysis of Hydrocarbon Liquids and Natural Gas”, published in August 2011 by the Wyoming Department of Environmental Quality Air Quality Division;

(c) “Standard 2174-93, Obtaining Liquid Hydrocarbon Samples for Analysis by Gas Chromatography” published by the Gas Processors Association (GPA);

(2) measure the sample pressure at the time of collection and again prior to analysis to insure that sample integrity has been maintained;

(3) measure the liquid temperature at the time of collection;

(4) conduct sampling and analysis at the frequency prescribed below at a time when operational parameters are representative of normal operating conditions:

<b>Oil production rate (m<sup>3</sup> per day)</b>	<b>Sampling frequency</b>
1.75 to 15.9	Annual
15.9 to 79.5	Semi-annual
> 79.5	Quarterly

(5) collect an additional sample if

(a) the production rate changes more than 20% compared to the normal rate for time periods in excess of one week;



(b) the separator operating pressure changes by more than 10% compared to the normal operating pressure;

(6) measure the volume of liquid produced during the sampling interval using equipment calibrated to be accurate to within 5%.

#### 33.4.10. Emissions attributable to transmission storage tanks

For transmission storage tanks, the emitter must

(1) to measure compressor scrubber dump valve leakage from condensate storage tanks connected to transmission storage tanks for water or hydrocarbon, determine the emission factor for leaks from each type of component using the following methods:

(a) using specific data related to the operation of the equipment by the emitter;

(b) using the method in the most recent version of "Methodology Manuel: Estimation of Air Emissions from the Canadian Natural Gas Transmission, Storage and Distribution System" published by Clearstone Engineering Ltd.;

(2) determine the duration of the equipment leakage using the following methods:

(a) when only one leak detection survey is conducted each year, the emitter must assume that the component was leaking from the start of the year until the leak was repaired. If the leak was not repaired, the emitter must assume that the component was leaking for the entire year;

(b) when more than one leak detection survey is conducted each year, the emitter must assume that the component has been leaking since the last survey. If a leak was detected at the last survey, the emitter must assume that the component, unless the leak has been repaired, was leaking for the entire year.

#### 33.4.11. Emissions attributable to well testing venting

To calculate emissions from well testing, the emitter must

(1) when using equation 33-21, determine the gas to liquid ratio (GLR) using a method published by one of the organizations listed in paragraph 1 of QC.33.4;

(2) when using equation 33-22, determine the average gas flow rate from well venting using measuring equipment installed on the vent.

#### 33.4.12. Associated gas emissions

To calculate associated gas emissions, the emitter must, when using equation 33-23, determine the gas to liquid ratio (GLR) using a method published by one of the organizations listed in paragraph 1 of QC.33.4.

#### QC.33.4.13. Emissions from flaring

To calculate emissions from flaring, the emitter must

(1) determine the volume of gas directed to flares using one of the following methods:

(a) when the flare is equipped with a continuous gas flow monitoring and recording system, using the gas volume flow or, when part of the gas is not measured by such a system, by estimating the unmeasured gas flow using a sector specific method;

(b) using a method published by an organization listed in paragraph 1 of QC.33.4;

(2) determine the gas composition using one of the following methods:

(a) using a continuous gas composition monitoring and recording system;

(b) when the flare is not equipped with a continuous gas composition analyzer and the exploration and production well is located onshore, using the annual average of the measured gas composition for the establishment;

(c) when the flare is not equipped with a continuous gas composition analyzer, using,

(i) for gas processing facilities where the flare is feeded with natural gas, the molar fraction of the feed gas for equipment upstream of the de-methanizer;

(ii) for sources downstream of the de-methanizer, the molar fraction of the output gas;

(iii) for facilities that solely fractionate a liquid stream, the molar fraction of the feed gas for the de-methanizer;

(iv) when the gas directed to the flare is composed of methane, ethane, propane, butane, pentane, hexane or hexanes-plus, the molar fraction determined by engineering calculation or based on available process data for the process concerned.

#### QC.33.4.14. Centrifugal compressor venting

For centrifugal compressors, the emitter must

(1) determine the gas flow from the wet seal oil degasing vent to the atmosphere and the gas flow directed to flares using a temporary or permanent flow meter in the operating mode in which it is found during the measurement period, namely:

(a) the centrifugal compressor is in operating, standby-pressurized mode and the gas emitted is from blowdown vent leakage;

(b) the centrifugal compressor is in operating mode;

(c) the centrifugal compressor is not operating and is in depressurized mode and the gas emitted is from isolation-valve leakage through the blowdown vent stack. In this case,

(i) each centrifugal compressor that is not equipped with blind flanges must be sampled at least once in every 3 consecutive years;

(ii) each centrifugal compressor that has been equipped with blind flanges for at least 3 consecutive years does not need to be sampled;

(2) when a centrifugal compressor is used for peaking purposes for no more than 200 hours per year and is not equipped with a meter, determine the volume of gas using data from meters installed on similar equipment;

(3) calibrate the meters in accordance with the methods in paragraph 1 of QC.33.4;

(4) determine the quantity of gas that is recovered using a vapour recovery system or destined for another use, expressed as a percentage, using the number of hours the recovery system is in operation and the quantity of gas directed to the combustible gas system;

(5) add the rated power of all centrifugal compressors at the establishment to determine if the aggregated power is greater than or below 186.4 kW.

#### QC.33.4.15. Reciprocating compressor venting

For reciprocating compressors, the emitter must

(1) determine the gas flow from reciprocating compressor venting using the following methods:

(a) when the reciprocating rod packing and blowdown vent for the compressor is connected to an open ended vent line, the emitter must determine the gas flow using one of the following methods:

(i) by measuring the gas flow from all vents, including gas manifolded to common vents, using calibrated bagging in accordance with paragraph 3 or a high-flow sampler in accordance with paragraph 4;

(ii) by measuring the gas flow from all vents, including gas manifolded to common vents, using a temporary or permanent flow meter in accordance with the methods in paragraph 1 of QC.33.4;

(iii) for leaks from valves connected to a vent line, such as the isolation valves of compressors that are not operating and pressurized and the blowdown valves of compressors that are pressurized, using an acoustic detection device in accordance with paragraph 2 of QC.33.4;

(b) when the compressor rod packing case is not equipped with a vent line:

(i) detect equipment leaks in accordance with paragraph 2 of QC.33.4;

(ii) measure the gas flow using a calibrated bag in accordance with paragraph 3, a high-flow sampler in accordance with paragraph 4 or a meter in accordance with a method published by an organization listed in paragraph 1 of QC.33.4;

(2) measure, annually, the gas flow from the reciprocating rod-packing vents, isolation valve vents and blowdown-valve vents of each reciprocating compressor, including gas manifolded to common vents, in the operating mode in which it is found during the measurement period, namely:

(a) reciprocating compressor is in operating, standby-pressurized mode and the gas emitted is from blowdown vent leakage;

(b) the reciprocating compressor is in operating mode and the gas emitted is from the reciprocating rod-packing;

(c) the compressor is not operating and is in depressurized mode and the gas emitted is from isolation valve leakage through the blowdown vent stack. In this case,

(i) each reciprocating compressor that is not equipped with blind flanges must be sampled at least once in every 3 consecutive years;

(ii) each reciprocating compressor that has been equipped with blind flanges for at least 3 consecutive years does not need to be sampled;

(3) when a reciprocating compressor is used for peaking purposes for no more than 200 hours per year and is not equipped with a flowmeter, determine the volume of gas using data from flowmeters installed on similar equipment;

(4) when using calibrated bags to measure the gas flow from reciprocating compressor venting, use bags only where the emissions are at near-atmospheric pressure and the concentration of hydrogen sulphide is such that it is safe to handle. The calibrated bag must be used according to the manufacturer's instructions and must be able to capture all the gas emitted during the measurement period. The emitter must also

(a) record the time required to completely fill the bag; if the bag inflates in less than once second, assume one second inflation time;

(b) perform 3 measurements of the time required to fill the bag, and use the average of the 3 measurements to determine the gas flow;

(5) when a high-flow sampler is used, measurements must be made in accordance with the manufacturer's instructions. The emitter must also calibrate the sampler following the manufacturer's instructions, at 2.5% CH<sub>4</sub> and 97.5% air and 100% CH<sub>4</sub> using gas samples representative of known concentrations;

(6) to determine the quantity of gas from reciprocating compressor venting recovered by vapour recovery system, maintain a log of operating times and quantities of gas directed to the recovery system.

#### QC.33.4.16. Leaks identified following a leak detection survey

An emitter must conduct leak detection surveys in accordance with paragraph 2 of QC.33.4, and must

(1) determine the emission leak factor from each type of component using the following methods:

(a) using specific data related to the operation of the equipment by the emitter and sector-specific methods;

(b) using data from Table W-2 in Part W of Title 40 of the Code of Federal Regulations published by the U.S. Environmental Protection Agency (USEPA), converting the factors into units appropriate for use in equation 33-31;

(c) using data from the Methodology Manuals of the Canadian Association of Petroleum Producers, converting the factors into units appropriate for use in equation 33-31;

(2) determine the duration of leakage from a component using the following methods:

(a) when only one leak detection survey is conducted each year, the emitter must assume that the component was leaking from the start of the year until the leak was repaired. If the leak was not repaired, the emitter must assume that the component was leaking for the entire year;

(b) when more than one leak detection survey is conducted each year, the emitter must assume that the component has been leaking since the last survey. If a leak was detected at the last survey, the emitter must assume that the component, unless the leak has been repaired, was leaking for the entire year.

#### QC.33.4.17. Fugitive emissions from all components

For fugitive emissions from all components, the emitter must

(1) determine the total number of components of each type, for each type of service, using one of the following methods:

(a) a sector specific method published by the Canadian Gas Association or the Canadian Association of Petroleum Producers;

(b) using enterprise-specific data;

(2) for the first emissions report year, use the emission factor for each type of component, by type of service, using the data in Tables 33-1 and 33-2 in QC.33.6. If no emission factor is specified in the Tables, the emitter must use a factor from Tables W-1A and W-2 in Part 98.230 of Title 40 of the Code of Federal Regulations published by the U.S. Environmental Protection Agency (USEPA), or the most recent version of "A National Inventory of Greenhouse Gas (GHG), Criteria Air Contaminant (CAC) and Hydrogen Sulphide (H<sub>2</sub>S) Emissions by the Upstream Oil and Gas Industry", published by Clearstone Engineering Ltd.;

(3) for subsequent emissions report years, determine the emission factor for leaks from each type of component, for each type of service, using the following methods:

(a) using equipment specific factors for the operation of the enterprise's equipment and a method published by an organization listed in paragraph 1 of QC.33.4;

(b) by updating the emission factors at least every 3 years;

(4) determine CO<sub>2</sub> and CH<sub>4</sub> concentration in natural gas in accordance with the methods in the most recent version of "Methodology Manuel: Estimation of Air Emissions from the Canadian Natural Gas Transmission, Storage and Distribution System" published by Clearstone Engineering Ltd.

#### QC.33.4.18. Enhanced oil recovery (EOR) injection pump blowdown

For EOR injection pump blowdown, the emitter must

(1) determine the volume of gas per blowdown for each pump by calculating the internal volume of the blowdown equipment between the isolation valves;

(2) maintain a log of the number of blowdown for each injecting pump during enhanced oil recovery;

(3) determine the density of critical phase greenhouse gas using a method published by an organization listed in paragraph 1 of QC.33.4 or, if those organizations have published no method, using an industry recognized method.

#### QC.33.4.19. Emissions attributable to the combustion of field gas and vent gas

An emitter who calculates the emissions attributable to the combustion of field gas and vent gas using equation 1-7 in paragraph 3 of QC.1.3.3 must determine the carbon content and molecular fraction of the gas in accordance with QC.1.5.5.

### **QC.33.5. Methods for estimating missing data**

When, in conducting sampling activities, an emitter is unable to obtain analytical data, the original sample, back-up sample or replacement sample must be analyzed again, using the methods prescribed in this protocol, for the same measurement and sampling periods.

When sampling or measurement data required by this protocol for the calculation of emissions is missing, the emitter must demonstrate that everything possible has been done to ensure that 100% of the data is sampled. The emitter must then use replacement data determined as follows:

(1) for an emitter who uses one of the calculation methods in this protocol:

(a) when the missing value concerns carbon content, high heat value, molecular weight, molar fraction, mass fraction, gas oil ratio, temperature, pressure or sampled data, the emitter must

(i) determine the sampling or measurement rate using the following equation:

#### **Equation 33-35**

$$S = \frac{Q_{E\text{Real}}}{Q_{E\text{Req}}}$$

Where:

S = Actual sampling rate or measurement rate, expressed as a percentage;

$Q_{E\text{Real}}$  = Actual number of samples or measurements carried out by the emitter;

$Q_{E\text{Req}}$  = Number of samples required or measurements carried out in accordance with QC.33.4;

(ii) for data requiring sampling or analysis:



- when  $T \geq 0.9$ : replace the missing value by the arithmetic average of the data sampled or measured immediately preceding and following the missing data period. If no data are available prior to the missing data period, the emitter must use the first data obtained after the missing data period;

- when  $0.75 \leq T < 0.9$ : replace the missing value by the highest value sample or analyzed during the report year for which the calculation is made;

- when  $T < 0.75$ : replace the missing value by the highest value sample or analyzed during the 3 preceding years;

(b) when the missing value concerns time, quantity of gas, quantity of liquid, liquid flow or gas flow, the replacement value must be estimated on the basis of all the data relating to the processes used;

(2) for an emitter who uses a continuous emission monitoring system, apply the procedure in the EPS 1/PG/7 protocol entitled "Protocols and performance specifications for continuous monitoring of gaseous emissions from thermal power generation" published in November 2005 by Environment Canada or apply the method in subparagraph a of paragraph 2 of QC.1.6 to the missing parameters.

#### QC.33.6. Tables

**Table 33-1. Average emission factors for an oil or natural gas exploration or production facility or a natural gas processing facility**

(QC.33.3.17)

Emission factor by component type	
Component – Type of service	Metric tons THC /component - hour
Valves - fuel gas	$2.81 \times 10^{-06}$
Valves - light liquid	$3.52 \times 10^{-06}$
Valves - gas/vapour - all	$2.46 \times 10^{-06}$
Valves - gas/vapour - sour	$1.16 \times 10^{-06}$
Valves - gas/vapour - sweet	$2.81 \times 10^{-06}$
Connectors - fuel gas	$8.18 \times 10^{-07}$
Connectors - light liquid	$5.51 \times 10^{-07}$
Connectors - gas/vapour - all	$7.06 \times 10^{-07}$
Connectors - gas/vapour - sour	$1.36 \times 10^{-07}$
Connectors - gas/vapour - sweet	$8.18 \times 10^{-07}$
Control valves - fuel gas	$1.62 \times 10^{-05}$

Control valves - light liquid	$1.77 \times 10^{-05}$
Control valves - gas/vapour - all	$1.46 \times 10^{-05}$
Control valves - gas/vapour - sour	$9.64 \times 10^{-06}$
Control valves - gas/vapour - sweet	$1.62 \times 10^{-05}$
Pressure relief valves - fuel gas and gas/vapour	$1.70 \times 10^{-05}$
Pressure relief valves - light liquid	$5.39 \times 10^{-06}$
Pressure regulators - fuel gas and gas/vapour	$8.11 \times 10^{-06}$
Pressure regulators - gas/vapour - sour	$4.72 \times 10^{-08}$
Pressure regulators - gas/vapour - sweet	$8.39 \times 10^{-06}$
Open ended lines - fuel gas	$4.67 \times 10^{-04}$
Open ended lines - light liquid	$1.83 \times 10^{-05}$
Open ended line- gas/vapour - all	$4.27 \times 10^{-04}$
Open ended lines - gas/vapour - sour	$1.89 \times 10^{-04}$
Open ended lines - gas/vapour - sweet	$4.67 \times 10^{-04}$
Pump seals - light liquid	$2.32 \times 10^{-05}$

**Table 33-2. Average emission factors for an oil and natural gas exploration and production facility**

(QC.33.2, QC.33.3.17, Q.33.4.17)

<b>Component – Type of service</b>	<b>Metric tons THC /component - hour</b>
Valves - fuel gas and gas/vapour	$1.51 \times 10^{-06}$
Valves - heavy liquid	$8.40 \times 10^{-09}$
Valves - light liquid	$1.21 \times 10^{-06}$
Connectors - fuel gas and gas/vapour	$2.46 \times 10^{-06}$
Connectors - heavy liquid	$7.50 \times 10^{-09}$
Connectors - gas/vapour - all	$1.90 \times 10^{-07}$
Control Valves - fuel gas and gas/vapour	$1.46 \times 10^{-05}$
Control Valves - light liquid	$1.75 \times 10^{-05}$
Pressure relief valves - fuel gas and gas/vapour	$1.63 \times 10^{-05}$
Pressure relief valves - heavy liquid	$3.20 \times 10^{-08}$
Pressure relief valves - light liquid	$7.50 \times 10^{-05}$
Pressure regulators - fuel gas and gas/vapour	$6.68 \times 10^{-06}$
Open ended lines - fuel gas and gas/vapour	$3.08 \times 10^{-04}$
Open ended lines - light liquid	$3.73 \times 10^{-06}$
Pump seals - heavy liquid	$3.20 \times 10^{-08}$
Pump seals - light liquid	$2.32 \times 10^{-05}$

**Table 33-3. Average emission factors for natural gas driven pneumatic devices**

(QC.33.4.1, QC.33.4.2)

<b>Component</b>	<b>m<sup>3</sup> at standard conditions per hour per component</b>
High bleed pneumatic device venting	1.3620
Intermittent bleed pneumatic device venting	0.4927
Low bleed pneumatic device venting	0.0510
Pneumatic pump	0.3766

**Table 33-4. Manufacturer-specified emission rates for leaks from liquid level controllers, positioners, pressure controllers, transducers and transmitters**

(QC.33.3.1, QC.33.3.2)

<b>Description</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Operating condition</b>	<b>Manufacturer rate (m<sup>3</sup>/hour)</b>
Liquid level controller	Bristol Babcock	Series 5453-Model 624-II	Continuous	0.0850
Liquid level controller	Fisher	2100	Continuous	0.0283
Liquid level controller	Fisher	2500	Continuous	1.1893
Liquid level controller	Fisher	2660	Continuous	0.0283
Liquid level controller	Fisher	2680	Continuous	0.0283
Liquid level controller	Fisher	2900	Continuous	0.6513
Liquid level controller	Fisher	L2	Continuous	0.0425
Liquid level controller	Invalco	AE-155	Continuous	1.5008
Liquid level controller	Invalco	CT Series	Continuous	1.1327
Liquid level controller	Norriseal	1001 (A) 'Envirosave'	Intermittent	0.0000
Liquid level controller	Norriseal	1001 (A) snap	Intermittent	0.0057

Liquid level controller	Norriseal	1001 (A) throttle	Intermittent	0.0002
Liquid level controller	Wellmark	2001 (snap)	Intermittent	0.0057
Liquid level controller	Wellmark	2001 (throttling)	Intermittent	0.0002
Positioner	Becker	EFP-2.0	Intermittent	0.0000
Positioner	Becker	HPP-5	Continuous	0.1416
Positioner	Fisher	3582	Continuous	0.4531
Positioner	Fisher	3590	Continuous	0.8495
Positioner	Fisher	3660	Continuous	0.1982
Positioner	Fisher	3661	Continuous	0.2959
Positioner	Fisher	3582i	Continuous	0.5833
Positioner	Fisher	3610J	Continuous	0.4531
Positioner	Fisher	3620J	Continuous	0.7532
Positioner	Fisher	DVC 5000	Continuous	0.2832
Positioner	Fisher	DVC 6000	Continuous	0.3964
Positioner	Fisher	Fieldview Digital	Continuous	0.8920
Positioner	Masoneilan	7400	Continuous	1.0477
Positioner	Masoneilan	4600B Series	Continuous	0.6796
Positioner	Masoneilan	4700B Series	Continuous	0.6796
Positioner	Masoneilan	4700E	Continuous	0.6796
Positioner	Masoneilan	SV	Continuous	0.1133
Positioner	Moore Products	73N-B	Continuous	1.0194
Positioner	Moore Products	750P	Continuous	1.1893
Positioner	PMV	D5 Digital	Continuous	0.0283
Positioner	Sampson	3780 Digital	Continuous	0.0283
Positioner	VCR	VP700 PtoP	Continuous	0.0283
Pressure controller	Ametek	Series 40	Continuous	0.1699
Pressure controller	Becker	HPP-SB	Continuous	0.0000
Pressure controller	Becker	VRP-B-CH	Continuous	0.1416
Pressure controller	Becker	VRP-SB	Continuous	0.0000
Pressure controller	Becker	VRP-SB Gap Controller	Continuous	0.0000
Pressure controller	Becker	VRP-SB-CH	Continuous	0.0000
Pressure controller	Becker	VRP-SB-PID Controller	Continuous	0.0000
Pressure controller	Bristol Babcock	Series 5453-Model 10F	Continuous	0.0850
Pressure controller	Bristol Babcock	Series 5455-Model 624-III	Continuous	0.0708
Pressure controller	CSV	4150	Continuous	0.6853

Pressure controller	CSV	4160	Continuous	0.6853
Pressure controller	Dyna-Flow	4000	Continuous	0.6853
Pressure controller	Fisher	2506	Continuous	0.6853
Pressure controller	Fisher	2516	Continuous	0.6853
Pressure controller	Fisher	4150	Continuous	0.7362
Pressure controller	Fisher	4160	Continuous	0.7362
Pressure controller	Fisher	4194	Continuous	0.1203
Pressure controller	Fisher	4195	Continuous	0.1203
Pressure controller	Fisher	4660	Continuous	0.1416
Pressure controller	Fisher	4100 (large orifice)	Continuous	1.4158
Pressure controller	Fisher	4100 (small orifice)	Continuous	0.4248
Pressure controller	Fisher	C1	Continuous	0.1472
Pressure controller	Fisher	DVC 6010	Continuous	0.0878
Pressure controller	Foxboro	43AP	Continuous	0.5097
Pressure controller	ITT Barton	338	Continuous	0.1699
Pressure controller	ITT Barton	358	Continuous	0.0510
Pressure controller	ITT Barton	359	Continuous	0.0510
Pressure controller	ITT Barton	335P	Continuous	0.1699
Pressure controller	ITT Barton	335P	Continuous	0.1699
Transducer	Bristol Babcock	9110-00A	Continuous	0.0119
Transducer	Bristol Babcock	Series 502 A/D	Continuous	0.1671
Transducer	Fairchild	TXI 7800	Continuous	0.2407
Transducer	Fisher	546	Continuous	0.8495
Transducer	Fisher	646	Continuous	0.2209
Transducer	Fisher	846	Continuous	0.3398
Transducer	Fisher	i2P-100	Continuous	0.2832
Transmitter	Bristol Babcock	Series 5457-70F	Continuous	0.0850
Transmitter	ITT Barton	273A	Continuous	0.0850
Transmitter	ITT Barton	274A	Continuous	0.0850
Transmitter	ITT Barton	284B	Continuous	0.0850
Transmitter	ITT Barton	285B	Continuous	0.0850

**QC.34. METAL POWDER PRODUCTION****QC.34.1. Covered sources**

The covered sources are all the processes used for the metal powder production.

**QC.34.2. Greenhouse gas reporting requirements**

In accordance with subparagraph 3 of the first paragraph of section 6.2, the greenhouse gas emissions report must, in particular, include the following information:

(1) the annual CO<sub>2</sub> emissions attributable to metal powder production, in metric tons;

(2) the annual CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub>O emissions attributable to the use of stationary combustion units, calculated and reported in accordance with QC.1, in metric tons;

(3) the annual quantity of each material or product that contributes 0.5% or more of the total carbon in the process, in metric tons;

(4) the average annual carbon content of each material or product that contributes 0.5% or more of the total carbon in the process, in metric tons of carbon per metric ton of material;

(5) the number of times that the methods for estimating missing data provided for in QC.34.5 were used;

(6) the total greenhouse gas emissions for each type of emission, namely:

(a) the annual fixed process emissions corresponding to the total of the emissions referred to in paragraph 1, in metric tons;

(b) the annual combustion emissions corresponding to the emissions referred to in paragraph 2, in metric tons CO<sub>2</sub> equivalent;

(7) the total annual quantity of metal powder produced, in metric tons.

Subparagraph 4 of the first paragraph does not apply to the CO<sub>2</sub> emissions of an emitter who calculates emissions using data from a continuous emission monitoring and recording system.

### QC.34.3. Calculation methods for CO<sub>2</sub> emissions attributable to primary and secondary zinc production processes

The annual CO<sub>2</sub> emissions attributable to metal powder production must be calculated in accordance with one of the methods in QC.34.3.1 and QC.34.3.2.

QC.34.3.1. Use of a continuous emission monitoring and recording system

The annual CO<sub>2</sub> emissions may be calculated using data from a continuous emission monitoring and recording system in accordance with QC.1.3.4.

QC.34.3.2. Calculation by mass balance

The annual CO<sub>2</sub> emissions may be calculated using equation 34-1:

#### Equation 34-1

$$CO_2 = \left[ \sum_{i=1}^n (M_i \times CC_{M,i}) - \sum_{j=1}^m (P_j \times CC_{p,j}) \right] \times 3.664$$

Where:

CO<sub>2</sub> = Annual CO<sub>2</sub> emissions attributable to metal powder production, in metric tons;

n = Number of types of material;

i = Type of material;

M<sub>i</sub> = Annual quantity of each material *i* that contributes 0.5% or more of the total carbon in the process, in metric tons;

CC<sub>M,i</sub> = Average annual carbon content of each material *i*, in kilograms of carbon per kilogram of material;

m = Number of types of product;

j = Type of product;

P<sub>j</sub> = Annual quantity of product *j* that contributes 0.5% or more of the total carbon in the process, in metric tons;

$CC_{p,j}$  = Carbon content of product  $j$ , in kilograms of carbon per kilogram of product;

3.664 = Ratio of molecular weights,  $CO_2$  to carbon.

#### **QC.34.4. Sampling, analysis and measurement requirements**

When the calculation method in QC.34.3.2 is used, the emitter who operates a facility or establishment that produces metal powder must:

(1) determine annually the carbon content of each material or product that contributes 0.5% or more of the total carbon in the process, either by using the data provided by the supplier, or by using the following methods:

(a) for iron or iron powder, using the most recent version of ASTM E1019 “Standard Test Methods for Determination of Carbon, Sulfur, Nitrogen, and Oxygen in Steel, Iron, Nickel, and Cobalt Alloys by Various Combustion and Fusion Techniques”, or using any other analysis method published by an organization listed in QC.1.5;

(b) for steel or steel powder, using one of the following methods:

(i) the most recent version of ASM CS-104 UNS G10460 “Carbon Steel of Medium Carbon Content” published by ASM International;

(ii) the most recent version of ISO/TR 15349-1 “Unalloyed steel - Determination of low carbon content – Part 1: Infrared absorption method after combustion in an electric resistance furnace (by peak separation)”;

(iii) the most recent version of ISO/TR 15349-3 “Unalloyed steel - Determination of low carbon content - Part 3: Infrared absorption method after combustion in an electric resistance furnace (with preheating)”;

(iv) the most recent version of ASTM E415 “Standard Test Method for Atomic Emission Vacuum Spectrometric Analysis of Carbon and Low-Alloy Steel”;

(v) any other analysis method published by an organization referred to in QC.1.5;



(c) for carbonaceous reducing agents and carbon electrodes, the most recent version of ASTM D5373 “Standard Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Laboratory Samples of Coal”, or any other analysis method published by an organization listed in QC.1.5;

(d) for flux materials, the most recent version of ASTM C25 “Standard Test Methods for Chemical Analysis of Limestone, Quicklime, and Hydrated Lime”, or any other analysis method published by an organization listed in QC.1.5;

(2) calculate the annual quantity of each material and product by direct weight measurement using the same plant instruments used for inventory purposes, such as weigh hoppers or belt weigh feeders.

#### **QC.34.5. Methods for estimating missing data**

When, in conducting sampling activities, an emitter is unable to obtain analytical data, the original sample, back-up sample or replacement sample must be analyzed again, using the methods prescribed in this protocol, for the same measurement and sampling periods.

When sampling or measurement data required by this protocol for the calculation of emissions is missing, the emitter must demonstrate that everything possible has been done to ensure that 100% of the data is sampled. The emitter must then use replacement data determined as follows:

(1) for an emitter who uses one of the calculation methods in this protocol:

(a) when the missing value concerns carbon content or another sampled value, the emitter must

(i) determine the sampling or measurement rate using the following equation:

#### **Equation 34-2**

$$S = \frac{Q_{E\text{Real}}}{Q_{E\text{Req}}}$$

Where:

S = Actual sampling rate or measurement rate, expressed as a percentage;

$Q_{EReal}$  = Actual number of samples or measurements carried out by the emitter;

$Q_{EReq}$  = Number of samples or measurements required under QC.34.4;

(ii) for data requiring sampling or analysis, the emitter must

- when  $T \geq 0.9$ : replace the missing value by the arithmetic average of the data sampled or measured immediately preceding and following the missing data period. If no data are available prior to the missing data period, the emitter must use the first data obtained after the missing data period;

- when  $0.75 \leq T < 0.9$ : replace the missing value by the highest value sample or analyzed during the report year for which the calculation is made;

- when  $T < 0.75$ : replace the missing value by the highest value sample or analyzed during the 3 preceding years ;

(b) when the missing value concerns the consumption of materials, the consumption of carbon electrodes or the production of products, the replacement value must be estimated on the basis of all the data relating to the processes used;

(2) for an emitter who uses a continuous emission monitoring system, apply the procedure in the EPS 1/PG/7 protocol entitled "Protocols and performance specifications for continuous monitoring of gaseous emissions from thermal power generation" published in November 2005 by Environment Canada or apply the method in subparagraph a of paragraph 2 of QC.1.6 to the missing parameters."

**20.** Schedule B of the Regulation is repealed.

**21.** For the 2012 emissions report, an emitter required by section 6.1 of the Regulation respecting mandatory reporting of certain emissions of contaminants into the atmosphere (R.R.Q., c. Q-2, r. 15), as it read prior to (*insert the date of coming into force of this Regulation*), to communicate monthly and quarterly data to the Minister that are no longer required as of that date must retain the data but is no longer required to communicate them.

**22.** This Regulation comes into force on 1 January 2013.